

Spazaafy

Create your account

I am a:

Consumer

Shop Owner

First name

Any

Last name

Lee

Email address

anylee@gmail.com

Phone (optional)

0624713078

Password

.....

Confirm password

.....

Shop name

Any's Spaza

Shop address

488 Ext

Province

Gauteng



HTTP 500 Internal Server Error: <!DOCTYPE html> <html lang="en"> <head> <meta http-equiv="content-type" content="text/html; charset=utf-8"> <meta name="robots" content="NONE,NOARCHIVE"> <title>TypeError at /api/auth/register</title> <style> html * { padding:0; margin:0; } body * { padding:10px 20px; } body * * { padding:0; } body { font-family: sans-serif; background-color:#fff; color:#000; } body > :where(header, main, footer) { border-bottom:1px solid #ddd; } h1 { font-weight:normal; } h2 { margin-bottom:.8em; } h3 { margin:1em 0 .5em 0; } h4 { margin:0

```

0 .5em 0; font-weight: normal; } code, pre { font-size:
100%; white-space: pre-wrap; word-break: break-word; }
summary { cursor: pointer; } table { border:1px solid #ccc;
border-collapse: collapse; width:100%; background:white;
} tbody td, tbody th { vertical-align:top; padding:2px 3px;
} thead th { padding:1px 6px 1px 3px; background:#fefefe;
text-align:left; font-weight:normal; font-size: 0.6875rem;
border:1px solid #ddd; } tbody th { width:12em; text-
align:right; color:#666; padding-right:.5em; } table.vars {
margin:5px 10px 2px 40px; width: auto; } table.vars td,
table.req td { font-family:monospace; } table td.code {
width:100%; } table td.code pre { overflow:hidden; }
table.source th { color:#666; } table.source td { font-
family:monospace; white-space:pre; border-bottom:1px
solid #eee; } ul.traceback { list-style-type:none; color:
#222; } ul.traceback li.cause { word-break: break-word; }
ul.traceback li.frame { padding-bottom:1em;
color:#4f4f4f; } ul.traceback li.user { background-
color:#e0e0e0; color:#000 } div.context { padding:10px 0;
overflow:hidden; } div.context ol { padding-left:30px;
margin:0 10px; list-style-position: inside; } div.context ol li
{ font-family:monospace; white-space:pre; color:#777;
cursor:pointer; padding-left: 2px; } div.context ol li pre {
display:inline; } div.context ol.context-line li {
color:#464646; background-color:#dfdfdf; padding: 3px
2px; } div.context ol.context-line li span {
position:absolute; right:32px; } .user div.context
ol.context-line li { background-color:#bbb; color:#000; }
.user div.context ol li { color:#666; } div.commands,
summary.commands { margin-left: 40px; } div.commands
a, summary.commands { color:#555; text-
decoration:none; } .user div.commands a { color: black; }
#summary { background: #ffc; } #summary h2 { font-
weight: normal; color: #666; } #info { padding: 0; } #info >
* { padding:10px 20px; } #explanation { background:#eee;
} #template, #template-not-exist { background:#f6f6f6; }
#template-not-exist ul { margin: 0 0 10px 20px; }
#template-not-exist .postmortem-section { margin-
bottom: 3px; } #unicode-hint { background:#eee; }
#traceback { background:#eee; } #requestinfo {
background:#f6f6f6; padding-left:120px; } #summary
table { border:none; background:transparent; }
#requestinfo h2, #requestinfo h3 { position:relative;
margin-left:-100px; } #requestinfo h3 { margin-
bottom:-1em; } .error { background: #ffc; } .specific {
color:#cc3300; font-weight:bold; } h2 span.commands {
font-size: 0.7rem; font-weight:normal; } span.commands
a:link {color:#5E5694;} pre.exception_value { font-family:
sans-serif; color: #575757; font-size: 1.5rem; margin: 10px
0 10px 0; } .append-bottom { margin-bottom: 10px; }
.fname { user-select: all; } </style> <script> function
hideAll(elems) { for (var e = 0; e < elems.length; e++) {

```

```

elems[e].style.display = 'none'; } } window.onload =
function() { hideAll(document.querySelectorAll('ol.pre-
context')); hideAll(document.querySelectorAll('ol.post-
context'));
hideAll(document.querySelectorAll('div.pastebin')); }
function toggle() { for (var i = 0; i < arguments.length; i++)
{ var e = document.getElementById(arguments[i]); if (e) {
e.style.display = e.style.display == 'none' ? 'block': 'none';
} } return false; } function switchPastebinFriendly(link) { s1
= "Switch to copy-and-paste view"; s2 = "Switch back to
interactive view"; link.textContent = link.textContent.trim()
== s1 ? s2: s1; toggle('browserTraceback',
'pastebinTraceback'); return false; } </script> </head>
<body> <header id="summary"> <h1>TypeError at
/api/auth/register</h1> <pre
class="exception_value">django.contrib.auth.models.UserMana
got multiple values for keyword argument
'&#x27;email&#x27;</pre> <table class="meta"> <tr> <th
scope="row">Request Method:</th> <td>POST</td>
</tr> <tr> <th scope="row">Request URL:</th>
<td>http://localhost:8000/api/auth/register</td> </tr>
<tr> <th scope="row">Django Version:</th>
<td>5.2.7</td> </tr> <tr> <th scope="row">Exception
Type:</th> <td>TypeError</td> </tr> <tr> <th
scope="row">Exception Value:</th> <td>
<pre>django.contrib.auth.models.UserManager.create_user()
got multiple values for keyword argument
'&#x27;email&#x27;</pre></td> </tr> <tr> <th
scope="row">Exception Location:</th> <td><span
class="fname">/app/apps/accounts/serializers.py</span>,
line 53, in create</td> </tr> <tr> <th scope="row">Raised
during:</th> <td>apps.accounts.views.RegisterView</td>
</tr> <tr> <th scope="row">Python Executable:</th>
<td>/usr/local/bin/python</td> </tr> <tr> <th
scope="row">Python Version:</th> <td>3.11.14</td>
</tr> <tr> <th scope="row">Python Path:</th> <td><pre>
<code>[&#x27;/app&#x27;,
&#x27;/usr/local/lib/python311.zip&#x27;,
&#x27;/usr/local/lib/python3.11&#x27;,
&#x27;/usr/local/lib/python3.11/lib-dynload&#x27;,
&#x27;/usr/local/lib/python3.11/site-packages&#x27;]
</code></pre></td> </tr> <tr> <th scope="row">Server
time:</th> <td>Fri, 24 Oct 2025 01:01:07 +0200</td>
</tr> </table> </header> <main id="info"> <div
id="traceback"> <h2>Traceback <span
class="commands"><a href="#" role="button"
onclick="return switchPastebinFriendly(this);"> Switch to
copy-and-paste view</a></span> </h2> <div
id="browserTraceback"> <ul class="traceback"> <li
class="frame django"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/django/core/handlers/exception.py</code>, line

```

```

55, in inner <div class="context"
id="c281473229915776"> <ol start="48" class="pre-
context" id="pre281473229915776"> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre></pre></li> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> return inner</pre></li>
<li onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> else:</pre></li> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre></pre></li> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> @wraps(get_response)
</pre></li> <li onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> def inner(request):
</pre></li> <li onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> try:</pre></li> </ol> <ol
start="55" class="context-line"> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> response =
get_response(request)
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^</pre> <span>...</span></li>
</ol> <ol start='56' class="post-context"
id="post281473229915776"> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> except Exception as
exc:</pre></li> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> response =
response_for_exception(request, exc)</pre></li> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> return response</pre>
</li> <li onclick="toggle('pre281473229915776',
'post281473229915776')"><pre></pre></li> <li
onclick="toggle('pre281473229915776',
'post281473229915776')"><pre> return inner</pre></li>
<li onclick="toggle('pre281473229915776',
'post281473229915776')"><pre></pre></li> </ol> </div>
<details> <summary class="commands">Local
vars</summary> <table class="vars"
id="v281473229915776"> <thead> <tr> <th
scope="col">Variable</th> <th scope="col">Value</th>
</tr> </thead> <tbody> <tr> <td>exc</td> <td
class="code">
<pre>TypeError(&quot;django.contrib.auth.models.UserManager
got multiple values for keyword argument
&#x27;email&#x27;&quot;)</pre></td> </tr> <tr>
<td>get_response</td> <td class="code">
<pre>&lt;bound method BaseHandler._get_response of
&lt;django.core.handlers.wsgi.WSGIHandler object at
0xfffffa890bed0&gt;&gt;</pre></td> </tr> <tr>
<td>request</td> <td class="code">

```

[illegible]

```

scope="col">Variable</th> <th scope="col">Value</th>
</tr> </thead> <tbody> <tr> <td>callback</td> <td
class="code"><pre>&lt;function
View.as_view.&lt;locals>.view at 0xffff9c23ac00&gt;
</pre></td> </tr> <tr> <td>callback_args</td> <td
class="code"><pre>()</pre></td> </tr> <tr>
<td>callback_kwargs</td> <td class="code"><pre>{}
</pre></td> </tr> <tr> <td>middleware_method</td> <td
class="code"><pre>&lt;bound method
CsrfViewMiddleware.process_view of
&lt;CsrfViewMiddleware
get_response=convert_exception_to_response.&lt;locals>.in
</pre></td> </tr> <tr> <td>request</td> <td
class="code"><pre>&lt;WSGIRequest: POST
&#x27;/api/auth/register&#x27;&gt;</pre></td> </tr> <tr>
<td>response</td> <td class="code"><pre>None</pre>
</td> </tr> <tr> <td>self</td> <td class="code">
<pre>&lt;django.core.handlers.wsgi.WSGIHandler object
at 0xffffa890bed0&gt;</pre></td> </tr> <tr>
<td>wrapped_callback</td> <td class="code">
<pre>&lt;function View.as_view.&lt;locals>.view at
0xffff9c23ac00&gt;</pre></td> </tr> </tbody> </table>
</details> </li> <li class="frame django"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/django/views/decorators/csrf.py</code>, line
65, in _view_wrapper <div class="context"
id="c281473229919488"> <ol start="58" class="pre-
context" id="pre281473229919488"> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre></pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre> async def
_view_wrapper(request, *args, **kwargs):</pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre> return await
view_func(request, *args, **kwargs)</pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre></pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre> else:</pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre></pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre> def
_view_wrapper(request, *args, **kwargs):</pre></li>
</ol> <ol start="65" class="context-line"> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre> return
view_func(request, *args, **kwargs)
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^</pre>
<span>...</span></li> </ol> <ol start="66" class="post-
context" id="post281473229919488"> <li

```



```

onclick="toggle('pre281473229919488',
'post281473229919488')"><pre></pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre>
_view_wrapper.csrf_exempt = True</pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre></pre></li> <li
onclick="toggle('pre281473229919488',
'post281473229919488')"><pre> return
wraps(view_func)(_view_wrapper)</pre></li> </ol> </div>
<details> <summary class="commands">Local
vars</summary> <table class="vars"
id="v281473229919488"> <thead> <tr> <th
scope="col">Variable</th> <th scope="col">Value</th>
</tr> </thead> <tbody> <tr> <td>args</td> <td
class="code"><pre>()</pre></td> </tr> <tr>
<td>kwargs</td> <td class="code"><pre>{}</pre></td>
</tr> <tr> <td>request</td> <td class="code">
<pre>&lt;WSGIRequest: POST
&#x27;/api/auth/register&#x27;&gt;</pre></td> </tr> <tr>
<td>view_func</td> <td class="code"><pre>&lt;function
View.as_view.&lt;locals&gt;.view at 0xffff9c293ce0&gt;
</pre></td> </tr> </tbody> </table> </details> </li> <li
class="frame django"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/django/views/generic/base.py</code>, line 105,
in view <div class="context" id="c281473229865664">
<ol start="98" class="pre-context"
id="pre281473229865664"> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> self = cls(**initkwargs)
</pre></li> <li onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> self.setup(request,
*args, **kwargs)</pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> if not hasattr(self,
'request'):</pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> raise
AttributeError(</pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> &quot;%s instance has
no &#x27;request&#x27; attribute. Did you override
&quot;</pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> &quot;setup() and
forget to call super()?&quot; % cls.__name__</pre></li>
<li onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> )</pre></li> </ol> <ol
start="105" class="context-line"> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> return

```

```
self.dispatch(request, *args, **kwargs)
<span>...</span></li> </ol> <ol start='106' class="post-
context" id="post281473229865664"> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre></pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> view.view_class =
cls</pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> view.view_initkwargs =
initkwargs</pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre></pre></li> <li
onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> # __name__ and
__qualname__ are intentionally left unchanged as</pre>
</li> <li onclick="toggle('pre281473229865664',
'post281473229865664')"><pre> # view_class should be
used to robustly determine the name of the view</pre>
</li> </ol> </div> <details> <summary
class="commands">Local vars</summary> <table
class="vars" id="v281473229865664"> <thead> <tr>
<th scope="col">Variable</th> <th
scope="col">Value</th> </tr> </thead> <tbody> <tr>
<td>args</td> <td class="code"><pre>()</pre></td>
</tr> <tr> <td>cls</td> <td class="code"><pre>&lt;class
&#x27;apps.accounts.views.RegisterView&#x27;&gt;;
</pre></td> </tr> <tr> <td>initkwargs</td> <td
class="code"><pre>{}</pre></td> </tr> <tr>
<td>kwarg<td class="code"><pre>{}</pre></td>
</tr> <tr> <td>request</td> <td class="code">
<pre>&lt;WSGIRequest: POST
&#x27;/api/auth/register&#x27;&gt;;</pre></td> </tr> <tr>
<td>self</td> <td class="code">
<pre>&lt;apps.accounts.views.RegisterView object at
0xffff97e17950&gt;;</pre></td> </tr> </tbody> </table>
</details> </li> <li class="frame user"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/rest_framework/views.py</code>, line 515, in
dispatch <div class="context" id="c281473229921216">
<ol start="508" class="pre-context"
id="pre281473229921216"> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre>
self.http_method_not_allowed</pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> else:</pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> handler =
self.http_method_not_allowed</pre></li> <li
onclick="toggle('pre281473229921216',
```



```
'post281473229921216')"><pre></pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> response =
handler(request, *args, **kwargs)</pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre></pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> except Exception as
exc:</pre></li> </ol> <ol start="515" class="context-
line"> <li onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> response =
self.handle_exception(exc)
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^</pre> <span>...
</span></li> </ol> <ol start='516' class="post-context"
id="post281473229921216"> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre></pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> self.response =
self.finalize_response(request, response, *args, **kwargs)
</pre></li> <li onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> return
self.response</pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre></pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> def options(self,
request, *args, **kwargs):</pre></li> <li
onclick="toggle('pre281473229921216',
'post281473229921216')"><pre> &quot;&quot;&quot;
</pre></li> </ol> </div> <details> <summary
class="commands">Local vars</summary> <table
class="vars" id="v281473229921216"> <thead> <tr> <th
scope="col">Variable</th> <th scope="col">Value</th>
</tr> </thead> <tbody> <tr> <td>args</td> <td
class="code"><pre>()</pre></td> </tr> <tr>
<td>handler</td> <td class="code"><pre>&lt;bound
method RegisterView.post of
&lt;apps.accounts.views.RegisterView object at
0xffff97e17950&gt;&gt;</pre></td> </tr> <tr>
<td>kwargs</td> <td class="code"><pre>{}</pre></td>
</tr> <tr> <td>request</td> <td class="code">
<pre>&lt;rest_framework.request.Request: POST
&#x27;/api/auth/register&#x27;&gt;</pre></td> </tr> <tr>
<td>self</td> <td class="code">
<pre>&lt;apps.accounts.views.RegisterView object at
0xffff97e17950&gt;</pre></td> </tr> </tbody> </table>
</details> </li> <li class="frame user"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/rest_framework/views.py</code>, line 475, in
handle_exception <div class="context"
id="c281473229926400"> <ol start="468" class="pre-
```

localhost:3000/#/register

```

got multiple values for keyword argument
'<email>';)
<td>exception_handler</td> <td class="code">
<pre>&lt;function exception_handler at
0xffff9c5e5120&gt;</pre></td> </tr> <tr>
<td>response</td> <td class="code"><pre>None</pre>
</td> </tr> <tr> <td>self</td> <td class="code">
<pre>&lt;apps.accounts.views.RegisterView object at
0xffff97e17950&gt;</pre></td> </tr> </tbody> </table>
</details> </li> <li class="frame user"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/rest_framework/views.py</code>, line 486, in
raise_uncaught_exception <div class="context"
id="c281473229926976"> <ol start="479" class="pre-
context" id="pre281473229926976"> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre></pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> def
raise_uncaught_exception(self, exc):</pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> if settings.DEBUG:
</pre></li> <li onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> request =
self.request</pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> renderer_format =
getattr(request.accepted_renderer, '<format>')
</pre></li> <li onclick="toggle('pre281473229926976',
'post281473229926976')"><pre>
use_plaintext_traceback = renderer_format not in
('<html>,<api>,<admin>')</pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre>
request.force_plaintext_errors(use_plaintext_traceback)
</pre></li> </ol> <ol start="486" class="context-line"> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> raise exc
^^^^^^^^^</pre> <span>...</span></li> </ol> <ol
start='487' class="post-context"
id="post281473229926976"> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre></pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> # Note: Views are
made CSRF exempt from within `as_view` as to
prevent</pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> # accidental removal of
this exemption in cases where `dispatch` needs to</pre>
</li> <li onclick="toggle('pre281473229926976',

```

```
'post281473229926976')"><pre> # be overridden.</pre>
</li> <li onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> def dispatch(self,
request, *args, **kwargs):</pre></li> <li
onclick="toggle('pre281473229926976',
'post281473229926976')"><pre> &quot;&quot;&quot;
</pre></li> </ol> </div> <details> <summary
class="commands">Local vars</summary> <table
class="vars" id="v281473229926976"> <thead> <tr> <th
scope="col">Variable</th> <th scope="col">Value</th>
</tr> </thead> <tbody> <tr> <td>exc</td> <td
class="code">
<pre>TypeError(&quot;django.contrib.auth.models.UserManager
got multiple values for keyword argument
&#x27;email&#x27;&quot;)</pre></td> </tr> <tr>
<td>renderer_format</td> <td class="code">
<pre>&#x27;json&#x27;</pre></td> </tr> <tr>
<td>request</td> <td class="code">
<pre>&lt;rest_framework.request.Request: POST
&#x27;/api/auth/register&#x27;&gt;</pre></td> </tr> <tr>
<td>self</td> <td class="code">
<pre>&lt;apps.accounts.views.RegisterView object at
0xffff97e17950&gt;</pre></td> </tr> <tr>
<td>use_plaintext_traceback</td> <td class="code">
<pre>True</pre></td> </tr> </tbody> </table> </details>
</li> <li class="frame user"> <code
class="fname">/usr/local/lib/python3.11/site-
packages/rest_framework/views.py</code>, line 512, in
dispatch <div class="context" id="c281473229918848">
<ol start="505" class="pre-context"
id="pre281473229918848"> <li
onclick="toggle('pre281473229918848',
'post281473229918848')"><pre> # Get the appropriate
handler method</pre></li> <li
onclick="toggle('pre281473229918848',
'post281473229918848')"><pre> if
request.method.lower() in self.http_method_names:
</pre></li> <li onclick="toggle('pre281473229918848',
'post281473229918848')"><pre> handler = getattr(self,
request.method.lower(),</pre></li> <li
onclick="toggle('pre281473229918848',
'post281473229918848')"><pre>
self.http_method_not_allowed</pre></li> <li
onclick="toggle('pre281473229918848',
'post281473229918848')"><pre> else:</pre></li> <li
onclick="toggle('pre281473229918848',
'post281473229918848')"><pre> handler =
self.http_method_not_allowed</pre></li> <li
onclick="toggle('pre281473229918848',
'post281473229918848')"><pre></pre></li> </ol> <ol
start="512" class="context-line"> <li
onclick="toggle('pre281473229918848',
```

```
"post281473229918848")"><pre> response =  
handler(request, *args, **kwargs)  
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^</pre>  
<span>...</span></li> </ol> <ol start='513' class="post-  
context" id="post281473229918848"> <li  
onclick="toggle('pre281473229918848',  
'post281473229918848')"><pre></pre></li> <li  
onclick="toggle('pre281473229918848',  
'post281473229918848')"><pre> except Exception as  
exc:</pre></li> <li  
onclick="toggle('pre281473229918848',  
'post281473229918848')"><pre> response =  
self.handle_exception(exc)</pre></li> <li  
onclick="toggle('pre281473229918848',  
'post281473229918848')"><pre></pre></li> <li  
onclick="toggle('pre281473229918848',  
'post281473229918848')"><pre> self.response =  
self.finalize_response(request, response, *args, **kwargs)  
</pre></li> <li onclick="toggle('pre281473229918848',  
'post281473229918848')"><pre> return  
self.response</pre></li> </ol> </div> <details> <summary  
class="commands">Local vars</summary> <table  
class="vars" id="v281473229918848"> <thead> <tr> <th  
scope="col">Variable</th> <th scope="col">Value</th>  
</tr> </thead> <tbody> <tr> <td>args</td> <td  
class="code"><pre>()</pre></td> </tr> <tr>  
<td>handler</td> <td class="code"><pre>&lt;bound  
method RegisterView.post of  
&lt;apps.accounts.views.RegisterView object at  
0xffff97e17950&gt;&gt;</pre></td> </tr> <tr>  
<td>kwarg<td class="code"><pre>{}</pre></td>  
</tr> <tr> <td>request</td> <td class="code">  
<pre>&lt;rest_framework.request.Request: POST  
&#x27;/api/auth/register&#x27;&gt;</pre></td> </tr> <tr>  
<td>self</td> <td class="code">  
<pre>&lt;apps.accounts.views.RegisterView object at  
0xffff97e17950&gt;</pre></td> </tr> </tbody> </table>  
</details> </li> <li class="frame user"> <code  
class="fname">/app/apps/accounts/views.py</code>, line  
14, in post <div class="context"  
id="c281473229925056"> <ol start="7" class="pre-  
context" id="pre281473229925056"> <li  
onclick="toggle('pre281473229925056',  
'post281473229925056')"><pre></pre></li> <li  
onclick="toggle('pre281473229925056',  
'post281473229925056')"><pre>class  
RegisterView(APIView):</pre></li> <li  
onclick="toggle('pre281473229925056',  
'post281473229925056')"><pre> permission_classes =  
[permissions.AllowAny]</pre></li> <li  
onclick="toggle('pre281473229925056',  
'post281473229925056')"><pre></pre></li> <li
```



```

onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> def post(self, request):
</pre></li> <li onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> ser =
RegisterSerializer(data=request.data)</pre></li> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> if ser.is_valid():</pre>
</li> </ol> <ol start="14" class="context-line"> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> user = ser.save()
^^^^^^^^^^</pre> <span>...</span></li> </ol> <ol
start='15' class="post-context"
id="post281473229925056"> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> # This is correct
because the RegisterSerializer's to_representation
is called</pre></li> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> return
Response(ser.to_representation(user),
status=status.HTTP_201_CREATED)</pre></li> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre> return
Response(ser.errors,
status=status.HTTP_400_BAD_REQUEST)</pre></li> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre></pre></li> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre></pre></li> <li
onclick="toggle('pre281473229925056',
'post281473229925056')"><pre>class
LoginView(APIView):</pre></li> </ol> </div> <details>
<summary class="commands">Local vars</summary>
<table class="vars" id="v281473229925056"> <thead>
<tr> <th scope="col">Variable</th> <th
scope="col">Value</th> </tr> </thead> <tbody> <tr>
<td>request</td> <td class="code">
<pre>&lt;rest_framework.request.Request: POST
&#x27;/api/auth/register&#x27;&gt;</pre></td> </tr> <tr>
<td>self</td> <td class="code">
<pre>&lt;apps.accounts.views.RegisterView object at
0xffff97e17950&gt;</pre></td> </tr> <tr> <td>ser</td>
<td class="code"><pre>RegisterSerializer(data=
{&#x27;email&#x27;: &#x27;anylee@gmail.com&#x27;,
&#x27;password&#x27;: &#x27;Eliana@123&#x27;,
&#x27;first_name&#x27;: &#x27;Any&#x27;,
&#x27;last_name&#x27;: &#x27;Lee&#x27;,
&#x27;phone&#x27;: &#x27;0624713078&#x27;,
&#x27;role&#x27;: &#x27;OWNER&#x27;,
&#x27;shop_name&#x27;: &quot;Any&#x27;s
Spaza&quot;, &#x27;address&#x27;: &#x27;488
Ext&#x27;, &#x27;province&#x27;: &#x27;1&#x27;});</pre>

```



```

email = EmailField() password = CharField(min_length=8,
write_only=True) first_name =
CharField(allow_blank=True, required=False) last_name =
CharField(allow_blank=True, required=False) phone =
CharField(allow_blank=True, required=False) role =
ChoiceField(choices=[('CONSUMER',
'CONSUMER'), ('OWNER',
'OWNER'), ('ADMIN',
'ADMIN')]) shop_name =
CharField(allow_blank=True, required=False) address =
CharField(allow_blank=True, required=False) province =
PrimaryKeyRelatedField(allow_null=True,
queryset=QuerySet [Province: Eastern Cape,
Province: Free State, Province: Gauteng,
Province: KwaZulu-Natal, Province:
Limpopo, Province: Mpumalanga,
Province: North West, Province: Northern
Cape, Province: Western Cape])
required=False)

```

in save <div class="context" id="c281473300258688">
 <ol start="203" class="pre-context"
 id="pre281473300258688"> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre>
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> if self.instance is not
 None:</pre> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> self.instance =
 self.update(self.instance, validated_data)</pre> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> assert self.instance is
 not None, (</pre> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> '`update()` did
 not return an object instance.'</pre> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre>)</pre> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> else:</pre>
 <ol start="210" class="context-line"> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> self.instance =
 self.create(validated_data)
 ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^</pre> ...
 <ol start="211" class="post-context"
 id="post281473300258688"> <li
 onclick="toggle('pre281473300258688',
 'post281473300258688')"><pre> assert self.instance is

```

not None, (</pre></li> <li
onclick="toggle('pre281473300258688',
'post281473300258688')"><pre> &#x27;`create()` did
not return an object instance.&#x27;</pre></li> <li
onclick="toggle('pre281473300258688',
'post281473300258688')"><pre> )</pre></li> <li
onclick="toggle('pre281473300258688',
'post281473300258688')"><pre></pre></li> <li
onclick="toggle('pre281473300258688',
'post281473300258688')"><pre> return
self.instance</pre></li> <li
onclick="toggle('pre281473300258688',
'post281473300258688')"><pre></pre></li> </ol> </div>
<details> <summary class="commands">Local
vars</summary> <table class="vars"
id="v281473300258688"> <thead> <tr> <th
scope="col">Variable</th> <th scope="col">Value</th>
</tr> </thead> <tbody> <tr> <td>kwargs</td> <td
class="code"><pre>{}</pre></td> </tr> <tr>
<td>self</td> <td class="code">
<pre>RegisterSerializer(data={&#x27;email&#x27;:
&#x27;anylee@gmail.com&#x27;,
&#x27;password&#x27;: &#x27;Eliana@123&#x27;,
&#x27;first_name&#x27;: &#x27;Any&#x27;,
&#x27;last_name&#x27;: &#x27;Lee&#x27;,
&#x27;phone&#x27;: &#x27;0624713078&#x27;,
&#x27;role&#x27;: &#x27;OWNER&#x27;,
&#x27;shop_name&#x27;: &quot;Any&#x27;s
Spaza&quot;, &#x27;address&#x27;: &#x27;488
Ext&#x27;, &#x27;province&#x27;: &#x27;1&#x27;});
email = EmailField() password = CharField(min_length=8,
write_only=True) first_name =
CharField(allow_blank=True, required=False) last_name =
CharField(allow_blank=True, required=False) phone =
CharField(allow_blank=True, required=False) role =
ChoiceField(choices=[(&#x27;CONSUMER&#x27;,
&#x27;CONSUMER&#x27;), (&#x27;OWNER&#x27;,
&#x27;OWNER&#x27;), (&#x27;ADMIN&#x27;,
&#x27;ADMIN&#x27;)]) shop_name =
CharField(allow_blank=True, required=False) address =
CharField(allow_blank=True, required=False) province =
PrimaryKeyRelatedField(allow_null=True,
queryset=&lt;QuerySet [&lt;Province: Eastern Cape&gt;,
&lt;Province: Free State&gt;, &lt;Province: Gauteng&gt;,
&lt;Province: KwaZulu-Natal&gt;, &lt;Province:
Limpopo&gt;, &lt;Province: Mpumalanga&gt;,
&lt;Province: North West&gt;, &lt;Province: Northern
Cape&gt;, &lt;Province: Western Cape&gt;]&gt;,
required=False)</pre></td> </tr> <tr>
<td>validated_data</td> <td class="code"><pre>
{&#x27;email&#x27;: &#x27;anylee@gmail.com&#x27;,
&#x27;first_name&#x27;: &#x27;Any&#x27;,

```

```

&#x27;last_name&#x27;; &#x27;Lee&#x27;;
&#x27;phone&#x27;; &#x27;0624713078&#x27;;
&#x27;role&#x27;; &#x27;OWNER&#x27;}</pre></td>
</tr> </tbody> </table> </details> </li> <li class="frame
user"> <code
class="fname">/app/apps/accounts/serializers.py</code>,
line 53, in create <div class="context"
id="c281473229922752"> <ol start="46" class="pre-
context" id="pre281473229922752"> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre></pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> # --- THIS IS THE
FINAL FIX ---</pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> # Explicitly pass
username and email to create_user.</pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> email =
validated_data.get(&#x27;email&#x27;)</pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> password =
validated_data.pop(&#x27;password&#x27;) # Password
must be handled separately</pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre></pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> # The remaining fields
are passed as extra fields.</pre></li> </ol> <ol start="53"
class="context-line"> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> user =
User.objects.create_user( </pre> <span>...</span></li>
</ol> <ol start="54" class="post-context"
id="post281473229922752"> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> username=email, # Use
email as the username</pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> email=email,</pre></li>
<li onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> password=password,
</pre></li> <li onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> **validated_data</pre>
</li> <li onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> )</pre></li> <li
onclick="toggle('pre281473229922752',
'post281473229922752')"><pre> # --- END OF FIX ---
</pre></li> </ol> </div> <details> <summary
class="commands">Local vars</summary> <table
class="vars" id="v281473229922752"> <thead> <tr> <th
scope="col">Variable</th> <th scope="col">Value</th>

```

```

</tr> </thead> <tbody> <tr> <td>address</td> <td
class="code"><pre>&#x27;488 Ext&#x27;</pre></td>
</tr> <tr> <td>email</td> <td class="code">
<pre>&#x27;anylee@gmail.com&#x27;</pre></td> </tr>
<tr> <td>password</td> <td class="code">
<pre>&#x27;Eliana@123&#x27;</pre></td> </tr> <tr>
<td>province</td> <td class="code"><pre>&#x27;&#x27;Province:
Eastern Cape&#x27;</pre></td> </tr> <tr> <td>self</td> <td
class="code"><pre>RegisterSerializer(data=
{&#x27;email&#x27;: &#x27;anylee@gmail.com&#x27;,
&#x27;password&#x27;: &#x27;Eliana@123&#x27;,
&#x27;first_name&#x27;: &#x27;Any&#x27;,
&#x27;last_name&#x27;: &#x27;Lee&#x27;,
&#x27;phone&#x27;: &#x27;0624713078&#x27;,
&#x27;role&#x27;: &#x27;OWNER&#x27;,
&#x27;shop_name&#x27;: &#x27;'Any&#x27;s
Spaza&#x27;address&#x27;: &#x27;488
Ext&#x27;, &#x27;province&#x27;: &#x27;1&#x27;}):
email = EmailField() password = CharField(min_length=8,
write_only=True) first_name =
CharField(allow_blank=True, required=False) last_name =
CharField(allow_blank=True, required=False) phone =
CharField(allow_blank=True, required=False) role =
ChoiceField(choices=[&#x27;CONSUMER&#x27;,
&#x27;CONSUMER&#x27;), (&#x27;OWNER&#x27;,
&#x27;OWNER&#x27;), (&#x27;ADMIN&#x27;,
&#x27;ADMIN&#x27;)]) shop_name =
CharField(allow_blank=True, required=False) address =
CharField(allow_blank=True, required=False) province =
PrimaryKeyRelatedField(allow_null=True,
queryset=&#x27;QuerySet [&#x27;Province: Eastern Cape&#x27;,
&#x27;Province: Free State&#x27;, &#x27;Province: Gauteng&#x27;,
&#x27;Province: KwaZulu-Natal&#x27;, &#x27;Province:
Limpopo&#x27;, &#x27;Province: Mpumalanga&#x27;,
&#x27;Province: North West&#x27;, &#x27;Province: Northern
Cape&#x27;, &#x27;Province: Western Cape&#x27;]&#x27;,
required=False)</pre></td> </tr> <tr>
<td>shop_name</td> <td class="code">
<pre>&#x27;'Any&#x27;s Spaza&#x27;</pre></td> </tr>
<tr> <td>validated_data</td> <td class="code"><pre>
{&#x27;email&#x27;: &#x27;anylee@gmail.com&#x27;,
&#x27;first_name&#x27;: &#x27;Any&#x27;,
&#x27;last_name&#x27;: &#x27;Lee&#x27;,
&#x27;phone&#x27;: &#x27;0624713078&#x27;,
&#x27;role&#x27;: &#x27;OWNER&#x27;}</pre></td>
</tr> </tbody> </table> </div> </li> </ul> </div> <form
action="https://dpaste.com/" name="pasteform"
id="pasteform" method="post"> <div
id="pastebinTraceback" class="pastebin"> <input
type="hidden" name="language"
value="PythonConsole"> <input type="hidden"
name="title" value="TypeError at /api/auth/register">

```

[illegible]


```
handle_exception self.raise_uncaught_exception(exc)
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^ File
"/usr/local/lib/python3.11/site-
packages/rest_framework/views.py", line 486, in
raise_uncaught_exception raise exc ^^^^^^^^^ File
"/usr/local/lib/python3.11/site-
packages/rest_framework/views.py", line 512, in dispatch
response = handler(request, *args, **kwargs)
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^ File
"/app/apps/accounts/views.py", line 14, in post user =
ser.save() ^^^^^^^^^^^^^ File "/usr/local/lib/python3.11/site-
packages/rest_framework/serializers.py", line 210, in save
self.instance = self.create(validated_data)
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^ File
"/app/apps/accounts/serializers.py", line 53, in create user
= User.objects.create_user( Exception Type: TypeError at
/api/auth/register Exception Value:
django.contrib.auth.models.UserManager.create_user()
got multiple values for keyword argument
'&#x27;email&#x27;' </textarea> <br><br> <input
type="submit" value="Share this traceback on a public
website"> </div> </form> </div> <div id="requestinfo">
<h2>Request information</h2> <h3 id="user-
info">USER</h3> <p>AnonymousUser</p> <h3 id="get-
info">GET</h3> <p>No GET data</p> <h3 id="post-
info">POST</h3> <p>No POST data</p> <h3 id="files-
info">FILES</h3> <p>No FILES data</p> <h3 id="cookie-
info">COOKIES</h3> <p>No cookie data</p> <h3
id="meta-info">META</h3> <table class="req"> <thead>
<tr> <th scope="col">Variable</th> <th
scope="col">Value</th> </tr> </thead> <tbody> <tr>
<td>ACCESS_TOKEN_LIFETIME_MIN</td> <td
class="code"><pre>&#x27;*~*****~&#x27;
</pre></td> </tr> <tr> <td>ALLOWED_HOSTS</td> <td
class="code"><pre>&#x27;*~&#x27;</pre></td> </tr> <tr>
<td>CONTENT_LENGTH</td> <td class="code">
<pre>&#x27;186~&#x27;</pre></td> </tr> <tr>
<td>CONTENT_TYPE</td> <td class="code">
<pre>&#x27;application/json~&#x27;</pre></td> </tr> <tr>
<td>CORS_ALLOWED_ORIGINS</td> <td class="code">
<pre>&#x27;http://localhost:5173,http://127.0.0.1:5173,http://loca
</pre></td> </tr> <tr>
<td>CSRF_TRUSTED_ORIGINS</td> <td class="code">
<pre>&#x27;http://localhost:5173,http://127.0.0.1:5173,http://loca
</pre></td> </tr> <tr> <td>DB_ENGINE</td> <td
class="code">
<pre>&#x27;django.contrib.gis.db.backends.postgis~&#x27;
</pre></td> </tr> <tr> <td>DB_HOST</td> <td
class="code"><pre>&#x27;db~&#x27;</pre></td> </tr>
<tr> <td>DB_NAME</td> <td class="code">
<pre>&#x27;spazaafy~&#x27;</pre></td> </tr> <tr>
<td>DB_PASSWORD</td> <td class="code">
```



```

<pre>#x27;*****&#x27;</pre></td> </tr>
<tr> <td>DB_PORT</td> <td class="code">
<pre>#x27;5432&#x27;</pre></td> </tr> <tr>
<td>DB_USER</td> <td class="code">
<pre>#x27;spazaafy&#x27;</pre></td> </tr> <tr>
<td>DJANGO_DEBUG</td> <td class="code">
<pre>#x27;true&#x27;</pre></td> </tr> <tr>
<td>DJANGO_SECRET_KEY</td> <td class="code">
<pre>#x27;*****&#x27;</pre></td> </tr>
<tr> <td>DJANGO_SETTINGS_MODULE</td> <td
class="code">
<pre>#x27;spazaafy_backend.settings&#x27;</pre>
</td> </tr> <tr> <td>GATEWAY_INTERFACE</td> <td
class="code"><pre>#x27;CGI/1.1&#x27;</pre></td>
</tr> <tr> <td>GPG_KEY</td> <td class="code">
<pre>#x27;*****&#x27;</pre></td> </tr>
<tr> <td>HOME</td> <td class="code">
<pre>#x27;/root&#x27;</pre></td> </tr> <tr>
<td>HOSTNAME</td> <td class="code">
<pre>#x27;11f17bb0715c&#x27;</pre></td> </tr> <tr>
<td>HTTP_ACCEPT</td> <td class="code">
<pre>#x27;*/*&#x27;</pre></td> </tr> <tr>
<td>HTTP_ACCEPT_ENCODING</td> <td class="code">
<pre>#x27;gzip, deflate, br, zstd&#x27;</pre></td>
</tr> <tr> <td>HTTP_ACCEPT_LANGUAGE</td> <td
class="code"><pre>#x27;en-ZA,en-GB;q=0.9,en-
US;q=0.8,en;q=0.7&#x27;</pre></td> </tr> <tr>
<td>HTTP_CONNECTION</td> <td class="code">
<pre>#x27;keep-alive&#x27;</pre></td> </tr> <tr>
<td>HTTP_HOST</td> <td class="code">
<pre>#x27;localhost:8000&#x27;</pre></td> </tr> <tr>
<td>HTTP_ORIGIN</td> <td class="code">
<pre>#x27;http://localhost:3000&#x27;</pre></td>
</tr> <tr> <td>HTTP_REFERER</td> <td class="code">
<pre>#x27;http://localhost:3000/&#x27;</pre></td>
</tr> <tr> <td>HTTP_SEC_CH_UA</td> <td
class="code"><pre>#x27;"Google
Chrome";v="141";, "Not?
A_Brand";v="8";,
"Chromium";v="141"&#x27;</pre>
</td> </tr> <tr> <td>HTTP_SEC_CH_UA_MOBILE</td>
<td class="code"><pre>#x27;?0&#x27;</pre></td>
</tr> <tr> <td>HTTP_SEC_CH_UA_PLATFORM</td> <td
class="code"><pre>#x27;"macOS"&#x27;
</pre></td> </tr> <tr>
<td>HTTP_SEC_FETCH_DEST</td> <td class="code">
<pre>#x27;empty&#x27;</pre></td> </tr> <tr>
<td>HTTP_SEC_FETCH_MODE</td> <td class="code">
<pre>#x27;cors&#x27;</pre></td> </tr> <tr>
<td>HTTP_SEC_FETCH_SITE</td> <td class="code">
<pre>#x27;same-site&#x27;</pre></td> </tr> <tr>
<td>HTTP_USER_AGENT</td> <td class="code"><pre>

```

```
(&#x27;Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7)
AppleWebKit/537.36 (KHTML, &#x27; &#x27;like Gecko)
Chrome/141.0.0.0 Safari/537.36&#x27;)</pre></td> </tr>
<tr> <td>LANG</td> <td class="code">
<pre>&#x27;C.UTF-8&#x27;</pre></td> </tr> <tr>
<td>MEDIA_ROOT</td> <td class="code">
<pre>&#x27;/app/media&#x27;</pre></td> </tr> <tr>
<td>PATH</td> <td class="code">
<pre>&#x27;/usr/local/bin:/usr/local/sbin:/usr/local/bin:/usr/sbin:/
</pre></td> </tr> <tr> <td>PATH_INFO</td> <td
class="code"><pre>&#x27;/api/auth/register&#x27;
</pre></td> </tr> <tr>
<td>PYTHONDONTWRITEBYTECODE</td> <td
class="code"><pre>&#x27;1&#x27;</pre></td> </tr> <tr>
<td>PYTHONUNBUFFERED</td> <td class="code">
<pre>&#x27;1&#x27;</pre></td> </tr> <tr>
<td>PYTHON_SHA256</td> <td class="code">
<pre>&#x27;8d3ed8ec5c88c1c95f5e558612a725450d2452813
</pre></td> </tr> <tr> <td>PYTHON_VERSION</td> <td
class="code"><pre>&#x27;3.11.14&#x27;</pre></td>
</tr> <tr> <td>QUERY_STRING</td> <td class="code">
<pre>&#x27;&#x27;</pre></td> </tr> <tr>
<td>REFRESH_TOKEN_LIFETIME_DAYS</td> <td
class="code"><pre>&#x27;*****&#x27;
</pre></td> </tr> <tr> <td>REMOTE_ADDR</td> <td
class="code"><pre>&#x27;192.168.65.1&#x27;</pre>
</td> </tr> <tr> <td>REMOTE_HOST</td> <td
class="code"><pre>&#x27;&#x27;</pre></td> </tr> <tr>
<td>REQUEST_METHOD</td> <td class="code">
<pre>&#x27;POST&#x27;</pre></td> </tr> <tr>
<td>RUN_MAIN</td> <td class="code">
<pre>&#x27;true&#x27;</pre></td> </tr> <tr>
<td>SCRIPT_NAME</td> <td class="code">
<pre>&#x27;&#x27;</pre></td> </tr> <tr>
<td>SERVER_NAME</td> <td class="code">
<pre>&#x27;11f17bb0715c&#x27;</pre></td> </tr> <tr>
<td>SERVER_PORT</td> <td class="code">
<pre>&#x27;8000&#x27;</pre></td> </tr> <tr>
<td>SERVER_PROTOCOL</td> <td class="code">
<pre>&#x27;HTTP/1.1&#x27;</pre></td> </tr> <tr>
<td>SERVER_SOFTWARE</td> <td class="code">
<pre>&#x27;WSGIServer/0.2&#x27;</pre></td> </tr> <tr>
<td>STATIC_ROOT</td> <td class="code">
<pre>&#x27;/app/staticfiles&#x27;</pre></td> </tr> <tr>
<td>TZ</td> <td class="code">
<pre>&#x27;Africa/Johannesburg&#x27;</pre></td> </tr>
<tr> <td>wsgi.errors</td> <td class="code">
<pre>&lt;_io.TextIOWrapper
name=&#x27;&lt;stderr&gt;&#x27; mode=&#x27;w&#x27;
encoding=&#x27;utf-8&#x27;&gt;</pre></td> </tr> <tr>
<td>wsgi.file_wrapper</td> <td class="code">
<pre>&lt;class &#x27;wsgiref.util.FileWrapper&#x27;&gt;</pre></td>
```

```

</pre></td> </tr> <tr> <td>wsgi.input</td> <td
class="code">
<pre>&lt;django.core.handlers.wsgi.LimitedStream object
at 0xffff97fb4190&gt;</pre></td> </tr> <tr>
<td>wsgi.multiprocess</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>wsgi.multithread</td> <td class="code">
<pre>True</pre></td> </tr> <tr> <td>wsgi.run_once</td>
<td class="code"><pre>False</pre></td> </tr> <tr>
<td>wsgi.url_scheme</td> <td class="code">
<pre>&#x27;http&#x27;</pre></td> </tr> <tr>
<td>wsgi.version</td> <td class="code"><pre>(1, 0)
</pre></td> </tr> </tbody> </table> <h3 id="settings-
info">Settings</h3> <h4>Using settings module
<code>spazaafy_backend.settings</code></h4> <table
class="req"> <thead> <tr> <th scope="col">Setting</th>
<th scope="col">Value</th> </tr> </thead> <tbody> <tr>
<td>ABSOLUTE_URL_OVERRIDES</td> <td
class="code"><pre>{}</pre></td> </tr> <tr>
<td>ADMINS</td> <td class="code"><pre>[]</pre></td>
</tr> <tr> <td>ALLOWED_HOSTS</td> <td
class="code"><pre>[&#x27;*&#x27;]</pre></td> </tr>
<tr> <td>APPEND_SLASH</td> <td class="code">
<pre>True</pre></td> </tr> <tr>
<td>AUTHENTICATION_BACKENDS</td> <td
class="code"><pre>&#x27;*****&#x27;
</pre></td> </tr> <tr>
<td>AUTH_PASSWORD_VALIDATORS</td> <td
class="code"><pre>&#x27;*****&#x27;
</pre></td> </tr> <tr> <td>AUTH_USER_MODEL</td>
<td class="code">
<pre>&#x27;*****&#x27;</pre></td> </tr>
<tr> <td>BASE_DIR</td> <td class="code">
<pre>PosixPath(&#x27;/app&#x27;)</pre></td> </tr> <tr>
<td>CACHES</td> <td class="code"><pre>
{&#x27;default&#x27;: {&#x27;BACKEND&#x27;:
&#x27;django.core.cache.backends.locmem.LocMemCache&#x
</pre></td> </tr> <tr>
<td>CACHE_MIDDLEWARE_ALIAS</td> <td
class="code"><pre>&#x27;default&#x27;</pre></td>
</tr> <tr> <td>CACHE_MIDDLEWARE_KEY_PREFIX</td>
<td class="code">
<pre>&#x27;*****&#x27;</pre></td> </tr>
<tr> <td>CACHE_MIDDLEWARE_SECONDS</td> <td
class="code"><pre>600</pre></td> </tr> <tr>
<td>CORS_ALLOWED_ORIGINS</td> <td class="code">
<pre>[&#x27;http://localhost:5173&#x27;,
&#x27;http://127.0.0.1:5173&#x27;,
&#x27;http://localhost:3000&#x27;,
&#x27;http://127.0.0.1:3000&#x27;]</pre></td> </tr> <tr>
<td>CSRF_COOKIE_AGE</td> <td class="code">
<pre>31449600</pre></td> </tr> <tr>

```

```

<td>CSRF_COOKIE_DOMAIN</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>CSRF_COOKIE_HTTPONLY</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>CSRF_COOKIE_NAME</td> <td class="code">
<pre>&#x27;csrftoken&#x27;</pre></td> </tr> <tr>
<td>CSRF_COOKIE_PATH</td> <td class="code">
<pre>&#x27;/&#x27;</pre></td> </tr> <tr>
<td>CSRF_COOKIE_SAMESITE</td> <td class="code">
<pre>&#x27;Lax&#x27;</pre></td> </tr> <tr>
<td>CSRF_COOKIE_SECURE</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>CSRF_FAILURE_VIEW</td> <td class="code">
<pre>&#x27;django.views.csrf.csrf_failure&#x27;</pre>
</td> </tr> <tr> <td>CSRF_HEADER_NAME</td> <td
class="code"><pre>&#x27;HTTP_X_CSRFTOKEN&#x27;
</pre></td> </tr> <tr>
<td>CSRF_TRUSTED_ORIGINS</td> <td class="code">
<pre>[&#x27;http://localhost:5173&#x27;,
&#x27;http://127.0.0.1:5173&#x27;,
&#x27;http://localhost:3000&#x27;,
&#x27;http://127.0.0.1:3000&#x27;]</pre></td> </tr> <tr>
<td>CSRF_USE_SESSIONS</td> <td class="code">
<pre>False</pre></td> </tr> <tr> <td>DATABASES</td>
<td class="code"><pre>{&#x27;default&#x27;:
{&#x27;ATOMIC_REQUESTS&#x27;: False,
&#x27;AUTOCOMMIT&#x27;: True,
&#x27;CONN_HEALTH_CHECKS&#x27;: False,
&#x27;CONN_MAX_AGE&#x27;: 0, &#x27;ENGINE&#x27;:
&#x27;django.contrib.gis.db.backends.postgis&#x27;,
&#x27;HOST&#x27;: &#x27;db&#x27;,
&#x27;NAME&#x27;: &#x27;spazaafy&#x27;,
&#x27;OPTIONS&#x27;: {}, &#x27;PASSWORD&#x27;:
&#x27;*****&#x27;, &#x27;PORT&#x27;:
&#x27;5432&#x27;, &#x27;TEST&#x27;:
{&#x27;CHARSET&#x27;: None,
&#x27;COLLATION&#x27;: None, &#x27;MIGRATE&#x27;:
True, &#x27;MIRROR&#x27;: None, &#x27;NAME&#x27;:
None}, &#x27;TIME_ZONE&#x27;: None,
&#x27;USER&#x27;: &#x27;spazaafy&#x27;}}</pre></td>
</tr> <tr> <td>DATABASE_ROUTERS</td> <td
class="code"><pre>[]</pre></td> </tr> <tr>
<td>DATA_UPLOAD_MAX_MEMORY_SIZE</td> <td
class="code"><pre>2621440</pre></td> </tr> <tr>
<td>DATA_UPLOAD_MAX_NUMBER_FIELDS</td> <td
class="code"><pre>1000</pre></td> </tr> <tr>
<td>DATA_UPLOAD_MAX_NUMBER_FILES</td> <td
class="code"><pre>100</pre></td> </tr> <tr>
<td>DATETIME_FORMAT</td> <td class="code">
<pre>&#x27;N j, Y, P&#x27;</pre></td> </tr> <tr>
<td>DATETIME_INPUT_FORMATS</td> <td
class="code"><pre>[&#x27;%Y-%m-%d

```

```
%H:%M:%S&#x27;, &#x27;%Y-%m-%d
%H:%M:%S.%f&#x27;, &#x27;%Y-%m-%d
%H:%M&#x27;, &#x27;%m/%d/%Y %H:%M:%S&#x27;,
&#x27;%m/%d/%Y %H:%M:%S.%f&#x27;,
&#x27;%m/%d/%Y %H:%M&#x27;, &#x27;%m/%d/%y
%H:%M:%S&#x27;, &#x27;%m/%d/%y
%H:%M:%S.%f&#x27;, &#x27;%m/%d/%y
%H:%M&#x27;]</pre></td> </tr> <tr>
<td>DATE_FORMAT</td> <td class="code">
<pre>&#x27;N j, Y&#x27;</pre></td> </tr> <tr>
<td>DATE_INPUT_FORMATS</td> <td class="code">
<pre>[&#x27;%Y-%m-%d&#x27;,
&#x27;%m/%d/%Y&#x27;, &#x27;%m/%d/%y&#x27;,
&#x27;%b %d %Y&#x27;, &#x27;%b %d, %Y&#x27;,
&#x27;%d %b %Y&#x27;, &#x27;%d %b, %Y&#x27;,
&#x27;%B %d %Y&#x27;, &#x27;%B %d, %Y&#x27;,
&#x27;%d %B %Y&#x27;, &#x27;%d %B, %Y&#x27;]
</pre></td> </tr> <tr> <td>DEBUG</td> <td
class="code"><pre>True</pre></td> </tr> <tr>
<td>DEBUG_PROPAGATE_EXCEPTIONS</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>DECIMAL_SEPARATOR</td> <td class="code">
<pre>&#x27;.&#x27;</pre></td> </tr> <tr>
<td>DEFAULT_AUTO_FIELD</td> <td class="code">
<pre>&#x27;django.db.models.BigAutoField&#x27;</pre>
</td> </tr> <tr> <td>DEFAULT_CHARSET</td> <td
class="code"><pre>&#x27;utf-8&#x27;</pre></td> </tr>
<tr> <td>DEFAULT_EXCEPTION_REPORTER</td> <td
class="code">
<pre>&#x27;django.views.debug.ExceptionReporter&#x27;
</pre></td> </tr> <tr>
<td>DEFAULT_EXCEPTION_REPORTER_FILTER</td> <td
class="code">
<pre>&#x27;django.views.debug.SafeExceptionReporterFilter&#
</pre></td> </tr> <tr> <td>DEFAULT_FROM_EMAIL</td>
<td class="code">
<pre>&#x27;webmaster@localhost&#x27;</pre></td>
</tr> <tr> <td>DEFAULT_INDEX_TABLESPACE</td> <td
class="code"><pre>&#x27;&#x27;</pre></td> </tr> <tr>
<td>DEFAULT_TABLESPACE</td> <td class="code">
<pre>&#x27;&#x27;</pre></td> </tr> <tr>
<td>DISALLOWED_USER_AGENTS</td> <td
class="code"><pre>[]</pre></td> </tr> <tr>
<td>EMAIL_BACKEND</td> <td class="code">
<pre>&#x27;django.core.mail.backends.smtp.EmailBackend&#x
</pre></td> </tr> <tr> <td>EMAIL_HOST</td> <td
class="code"><pre>&#x27;localhost&#x27;</pre></td>
</tr> <tr> <td>EMAIL_HOST_PASSWORD</td> <td
class="code"><pre>&#x27;*****&#x27;
</pre></td> </tr> <tr> <td>EMAIL_HOST_USER</td> <td
class="code"><pre>&#x27;&#x27;</pre></td> </tr> <tr>
<td>EMAIL_PORT</td> <td class="code"><pre>25</pre>
```



```

</td> </tr> <tr> <td>EMAIL_SSL_CERTFILE</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>EMAIL_SSL_KEYFILE</td> <td class="code">
<pre>&#x27;*****&#x27;</pre></td> </tr>
<tr> <td>EMAIL_SUBJECT_PREFIX</td> <td
class="code"><pre>&#x27;[Django] &#x27;</pre></td>
</tr> <tr> <td>EMAIL_TIMEOUT</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>EMAIL_USE_LOCALTIME</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>EMAIL_USE_SSL</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>EMAIL_USE_TLS</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>FILE_UPLOAD_DIRECTORY_PERMISSIONS</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>FILE_UPLOAD_HANDLERS</td> <td class="code">
<pre>
[&#x27;django.core.files.uploadhandler.MemoryFileUploadHand
&#x27;django.core.files.uploadhandler.TemporaryFileUploadHan
</pre></td> </tr> <tr>
<td>FILE_UPLOAD_MAX_MEMORY_SIZE</td> <td
class="code"><pre>2621440</pre></td> </tr> <tr>
<td>FILE_UPLOAD_PERMISSIONS</td> <td
class="code"><pre>420</pre></td> </tr> <tr>
<td>FILE_UPLOAD_TEMP_DIR</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>FIRST_DAY_OF_WEEK</td> <td class="code">
<pre>0</pre></td> </tr> <tr> <td>FIXTURE_DIRS</td>
<td class="code"><pre>[]</pre></td> </tr> <tr>
<td>FORCE_SCRIPT_NAME</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>FORMAT_MODULE_PATH</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>FORMS_URLFIELD_ASSUME_HTTPS</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>FORM_RENDERER</td> <td class="code">
<pre>&#x27;django.forms.renderers.DjangoTemplates&#x27;
</pre></td> </tr> <tr> <td>IGNORABLE_404_URLS</td>
<td class="code"><pre>[]</pre></td> </tr> <tr>
<td>INSTALLED_APPS</td> <td class="code"><pre>
[&#x27;django.contrib.admin&#x27;,
&#x27;django.contrib.auth&#x27;,
&#x27;django.contrib.contenttypes&#x27;,
&#x27;django.contrib.sessions&#x27;,
&#x27;django.contrib.messages&#x27;,
&#x27;django.contrib.staticfiles&#x27;,
&#x27;rest_framework&#x27;, &#x27;corsheaders&#x27;,
&#x27;drf_spectacular&#x27;,
&#x27;django.contrib.gis&#x27;, &#x27;apps.core&#x27;,
&#x27;apps.accounts&#x27;, &#x27;apps.shops&#x27;,
&#x27;apps.compliance&#x27;,

```



```

&#x27;apps.support&#x27;; &#x27;apps.visits&#x27;;
&#x27;apps.reports&#x27;]</pre></td> <tr>
<td>INTERNAL_IPS</td> <td class="code"><pre>[]
</pre></td> </tr> <tr> <td>LANGUAGES</td> <td
class="code"><pre>[(&#x27;af&#x27;;
&#x27;Afrikaans&#x27;), (&#x27;ar&#x27;;
&#x27;Arabic&#x27;), (&#x27;ar-dz&#x27;;
&#x27;Algerian Arabic&#x27;), (&#x27;ast&#x27;;
&#x27;Asturian&#x27;), (&#x27;az&#x27;;
&#x27;Azerbaijani&#x27;), (&#x27;bg&#x27;;
&#x27;Bulgarian&#x27;), (&#x27;be&#x27;;
&#x27;Belarusian&#x27;), (&#x27;bn&#x27;;
&#x27;Bengali&#x27;), (&#x27;br&#x27;;
&#x27;Breton&#x27;), (&#x27;bs&#x27;;
&#x27;Bosnian&#x27;), (&#x27;ca&#x27;;
&#x27;Catalan&#x27;), (&#x27;ckb&#x27;; &#x27;Central
Kurdish (Sorani)&#x27;), (&#x27;cs&#x27;;
&#x27;Czech&#x27;), (&#x27;cy&#x27;;
&#x27;Welsh&#x27;), (&#x27;da&#x27;;
&#x27;Danish&#x27;), (&#x27;de&#x27;;
&#x27;German&#x27;), (&#x27;dsb&#x27;; &#x27;Lower
Sorbian&#x27;), (&#x27;el&#x27;; &#x27;Greek&#x27;),
(&#x27;en&#x27;; &#x27;English&#x27;), (&#x27;en-
au&#x27;; &#x27;Australian English&#x27;), (&#x27;en-
gb&#x27;; &#x27;British English&#x27;),
(&#x27;eo&#x27;; &#x27;Esperanto&#x27;),
(&#x27;es&#x27;; &#x27;Spanish&#x27;), (&#x27;es-
ar&#x27;; &#x27;Argentinian Spanish&#x27;), (&#x27;es-
co&#x27;; &#x27;Colombian Spanish&#x27;), (&#x27;es-
mx&#x27;; &#x27;Mexican Spanish&#x27;), (&#x27;es-
ni&#x27;; &#x27;Nicaraguan Spanish&#x27;), (&#x27;es-
ve&#x27;; &#x27;Venezuelan Spanish&#x27;),
(&#x27;et&#x27;; &#x27;Estonian&#x27;),
(&#x27;eu&#x27;; &#x27;Basque&#x27;),
(&#x27;fa&#x27;; &#x27;Persian&#x27;), (&#x27;fi&#x27;;
&#x27;Finnish&#x27;), (&#x27;fr&#x27;;
&#x27;French&#x27;), (&#x27;fy&#x27;;
&#x27;Frisian&#x27;), (&#x27;ga&#x27;;
&#x27;Irish&#x27;), (&#x27;gd&#x27;; &#x27;Scottish
Gaelic&#x27;), (&#x27;gl&#x27;; &#x27;Galician&#x27;),
(&#x27;he&#x27;; &#x27;Hebrew&#x27;),
(&#x27;hi&#x27;; &#x27;Hindi&#x27;), (&#x27;hr&#x27;;
&#x27;Croatian&#x27;), (&#x27;hsb&#x27;; &#x27;Upper
Sorbian&#x27;), (&#x27;hu&#x27;;
&#x27;Hungarian&#x27;), (&#x27;hy&#x27;;
&#x27;Armenian&#x27;), (&#x27;ia&#x27;;
&#x27;Interlingua&#x27;), (&#x27;id&#x27;;
&#x27;Indonesian&#x27;), (&#x27;ig&#x27;;
&#x27;Igbo&#x27;), (&#x27;io&#x27;; &#x27;Ido&#x27;),
(&#x27;is&#x27;; &#x27;Icelandic&#x27;),
(&#x27;it&#x27;; &#x27;Italian&#x27;), (&#x27;ja&#x27;;
&#x27;Japanese&#x27;), (&#x27;ka&#x27;;

```

```

&#x27;Georgian&#x27;), (&#x27;kab&#x27;,
&#x27;Kabyle&#x27;), (&#x27;kk&#x27;,
&#x27;Kazakh&#x27;), (&#x27;km&#x27;,
&#x27;Khmer&#x27;), (&#x27;kn&#x27;,
&#x27;Kannada&#x27;), (&#x27;ko&#x27;,
&#x27;Korean&#x27;), (&#x27;ky&#x27;,
&#x27;Kyrgyz&#x27;), (&#x27;lb&#x27;,
&#x27;Luxembourgish&#x27;), (&#x27;lt&#x27;,
&#x27;Lithuanian&#x27;), (&#x27;lv&#x27;,
&#x27;Latvian&#x27;), (&#x27;mk&#x27;,
&#x27;Macedonian&#x27;), (&#x27;ml&#x27;,
&#x27;Malayalam&#x27;), (&#x27;mn&#x27;,
&#x27;Mongolian&#x27;), (&#x27;mr&#x27;,
&#x27;Marathi&#x27;), (&#x27;ms&#x27;,
&#x27;Malay&#x27;), (&#x27;my&#x27;,
&#x27;Burmese&#x27;), (&#x27;nb&#x27;,
&#x27;Norwegian Bokmål&#x27;), (&#x27;ne&#x27;,
&#x27;Nepali&#x27;), (&#x27;nl&#x27;,
&#x27;Dutch&#x27;), (&#x27;nn&#x27;,
&#x27;Norwegian Nynorsk&#x27;), (&#x27;os&#x27;,
&#x27;Ossetic&#x27;), (&#x27;pa&#x27;,
&#x27;Punjabi&#x27;), (&#x27;pl&#x27;,
&#x27;Polish&#x27;), (&#x27;pt&#x27;,
&#x27;Portuguese&#x27;), (&#x27;pt-br&#x27;,
&#x27;Brazilian Portuguese&#x27;), (&#x27;ro&#x27;,
&#x27;Romanian&#x27;), (&#x27;ru&#x27;,
&#x27;Russian&#x27;), (&#x27;sk&#x27;,
&#x27;Slovak&#x27;), (&#x27;sl&#x27;,
&#x27;Slovenian&#x27;), (&#x27;sq&#x27;,
&#x27;Albanian&#x27;), (&#x27;sr&#x27;,
&#x27;Serbian&#x27;), (&#x27;sr-latn&#x27;,
&#x27;Serbian Latin&#x27;), (&#x27;sv&#x27;,
&#x27;Swedish&#x27;), (&#x27;sw&#x27;,
&#x27;Swahili&#x27;), (&#x27;ta&#x27;,
&#x27;Tamil&#x27;), (&#x27;te&#x27;,
&#x27;Telugu&#x27;), (&#x27;tg&#x27;,
&#x27;Tajik&#x27;), (&#x27;th&#x27;, &#x27;Thai&#x27;),
(&#x27;tk&#x27;, &#x27;Turkmen&#x27;),
(&#x27;tr&#x27;, &#x27;Turkish&#x27;), (&#x27;tt&#x27;,
&#x27;Tatar&#x27;), (&#x27;udm&#x27;,
&#x27;Udmurt&#x27;), (&#x27;ug&#x27;,
&#x27;Uyghur&#x27;), (&#x27;uk&#x27;,
&#x27;Ukrainian&#x27;), (&#x27;ur&#x27;,
&#x27;Urdu&#x27;), (&#x27;uz&#x27;,
&#x27;Uzbek&#x27;), (&#x27;vi&#x27;,
&#x27;Vietnamese&#x27;), (&#x27;zh-hans&#x27;,
&#x27;Simplified Chinese&#x27;), (&#x27;zh-hant&#x27;,
&#x27;Traditional Chinese&#x27;)]</pre></td> </tr> <tr>
<td>LANGUAGES_BIDI</td> <td class="code"><pre>
[&#x27;he&#x27;, &#x27;ar&#x27;, &#x27;ar-dz&#x27;,
&#x27;ckb&#x27;, &#x27;fa&#x27;, &#x27;ug&#x27;,
&#x27;ur&#x27;]</pre></td> </tr> <tr>

```

```

<td>LANGUAGE_CODE</td> <td class="code">
<pre>en-us</pre></td> </tr> <tr>
<td>LANGUAGE_COOKIE_AGE</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>LANGUAGE_COOKIE_DOMAIN</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>LANGUAGE_COOKIE_HTTPONLY</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>LANGUAGE_COOKIE_NAME</td> <td class="code">
<pre>django_language</pre></td> </tr>
<tr> <td>LANGUAGE_COOKIE_PATH</td> <td
class="code"><pre>/</pre></td> </tr> <tr>
<td>LANGUAGE_COOKIE_SAMESITE</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>LANGUAGE_COOKIE_SECURE</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>LOCALE_PATHS</td> <td class="code"><pre>[]
</pre></td> </tr> <tr> <td>LOGGING</td> <td
class="code"><pre>{}</pre></td> </tr> <tr>
<td>LOGGING_CONFIG</td> <td class="code">
<pre>logging.config.dictConfig</pre></td>
</tr> <tr> <td>LOGIN_REDIRECT_URL</td> <td
class="code"><pre>/accounts/profile</pre>
</td> </tr> <tr> <td>LOGIN_URL</td> <td
class="code"><pre>/accounts/login</pre>
</td> </tr> <tr> <td>LOGOUT_REDIRECT_URL</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>MANAGERS</td> <td class="code"><pre>[]</pre>
</td> </tr> <tr> <td>MEDIA_ROOT</td> <td
class="code"><pre>/app/media</pre></td>
</tr> <tr> <td>MEDIA_URL</td> <td class="code">
<pre>/media</pre></td> </tr> <tr>
<td>MESSAGE_STORAGE</td> <td class="code">
<pre>django.contrib.messages.storage.fallback.FallbackStorage</pre>
</td> </tr> <tr> <td>MIDDLEWARE</td> <td
class="code"><pre>[
    corsheaders.middleware.CorsMiddleware,
    django.middleware.security.SecurityMiddleware,
    django.contrib.sessions.middleware.SessionMiddleware,
    django.middleware.common.CommonMiddleware,
    django.middleware.csrf.CsrfViewMiddleware,
    django.contrib.auth.middleware.AuthenticationMiddleware,
    django.contrib.messages.middleware.MessageMiddleware,
    django.middleware.clickjacking.XFrameOptionsMiddleware,
]
</pre></td> </tr> <tr> <td>MIGRATION_MODULES</td>
<td class="code"><pre>{}</pre></td> </tr> <tr>
<td>MONTH_DAY_FORMAT</td> <td class="code">
<pre>F j</pre></td> </tr> <tr>
<td>NUMBER_GROUPING</td> <td class="code">
<pre>0</pre></td> </tr> <tr>
<td>PASSWORD_HASHERS</td> <td class="code">
<pre>django.contrib.auth.hashers.PBKDFCPasswordHasher,
django.contrib.auth.hashers.PBKDFCSha1PasswordHasher,
django.contrib.auth.hashers.BCryptSHA256PasswordHasher,
django.contrib.auth.hashers.BCryptPasswordHasher,
django.contrib.auth.hashers.Argon2PasswordHasher,
django.contrib.auth.hashers.SHA256PasswordHasher,
django.contrib.auth.hashers.SHA512PasswordHasher,
django.contrib.auth.hashers.ScryptPasswordHasher,
</pre></td> </tr>

```

```

<tr> <td>PASSWORD_RESET_TIMEOUT</td> <td
class="code"><pre>&#x27;*****&#x27;
</pre></td> </tr> <tr> <td>PREPEND_WWW</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>REST_FRAMEWORK</td> <td class="code"><pre>
{&#x27;DEFAULT_AUTHENTICATION_CLASSES&#x27;;
&#x27;*****&#x27;;
&#x27;DEFAULT_PERMISSION_CLASSES&#x27;;
[&#x27;rest_framework.permissions.IsAuthenticated&#x27;],
&#x27;DEFAULT_SCHEMA_CLASS&#x27;;
&#x27;drf_spectacular.openapi.AutoSchema&#x27;}&#x27;
</pre></td> </tr> <tr> <td>ROOT_URLCONF</td> <td
class="code"><pre>&#x27;spazaafy_backend.urls&#x27;
</pre></td> </tr> <tr> <td>SECRET_KEY</td> <td
class="code"><pre>&#x27;*****&#x27;
</pre></td> </tr> <tr>
<td>SECRET_KEY_FALLBACKS</td> <td class="code">
<pre>&#x27;*****&#x27;</pre></td> </tr> <tr>
<td>SECURE_CONTENT_TYPE_NOSNIFF</td> <td
class="code"><pre>True</pre></td> </tr> <tr>
<td>SECURE_CROSS_ORIGIN_OPENER_POLICY</td> <td
class="code"><pre>&#x27;same-origin&#x27;</pre>
</td> </tr> <tr>
<td>SECURE_HSTS_INCLUDE_SUBDOMAINS</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>SECURE_HSTS_PRELOAD</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>SECURE_HSTS_SECONDS</td> <td class="code">
<pre>0</pre></td> </tr> <tr>
<td>SECURE_PROXY_SSL_HEADER</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>SECURE_REDIRECT_EXEMPT</td> <td
class="code"><pre>[]</pre></td> </tr> <tr>
<td>SECURE_REFERRER_POLICY</td> <td
class="code"><pre>&#x27;same-origin&#x27;</pre>
</td> </tr> <tr> <td>SECURE_SSL_HOST</td> <td
class="code"><pre>None</pre></td> </tr> <tr>
<td>SECURE_SSL_REDIRECT</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>SERVER_EMAIL</td> <td class="code">
<pre>&#x27;root@localhost&#x27;</pre></td> </tr> <tr>
<td>SESSION_CACHE_ALIAS</td> <td class="code">
<pre>&#x27;default&#x27;</pre></td> </tr> <tr>
<td>SESSION_COOKIE_AGE</td> <td class="code">
<pre>1209600</pre></td> </tr> <tr>
<td>SESSION_COOKIE_DOMAIN</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>SESSION_COOKIE_HTTPONLY</td> <td
class="code"><pre>True</pre></td> </tr> <tr>
<td>SESSION_COOKIE_NAME</td> <td class="code">
<pre>&#x27;sessionid&#x27;</pre></td> </tr> <tr>
<td>SESSION_COOKIE_PATH</td> <td class="code">

```

```

<pre>&#x27;/&#x27;</pre></td> </tr> <tr>
<td>SESSION_COOKIE_SAMESITE</td> <td
class="code"><pre>&#x27;Lax&#x27;</pre></td> </tr>
<tr> <td>SESSION_COOKIE_SECURE</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>SESSION_ENGINE</td> <td class="code">
<pre>&#x27;django.contrib.sessions.backends.db&#x27;
</pre></td> </tr> <tr>
<td>SESSION_EXPIRE_AT_BROWSER_CLOSE</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>SESSION_FILE_PATH</td> <td class="code">
<pre>None</pre></td> </tr> <tr>
<td>SESSION_SAVE_EVERY_REQUEST</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>SESSION_SERIALIZER</td> <td class="code">
<pre>&#x27;django.contrib.sessions.serializers.JSONSerializer&
</pre></td> </tr> <tr> <td>SETTINGS_MODULE</td> <td
class="code">
<pre>&#x27;spazaafy_backend.settings&#x27;</pre>
</td> </tr> <tr> <td>SHORT_DATETIME_FORMAT</td>
<td class="code"><pre>&#x27;m/d/Y P&#x27;</pre>
</td> </tr> <tr> <td>SHORT_DATE_FORMAT</td> <td
class="code"><pre>&#x27;m/d/Y&#x27;</pre></td> </tr>
<tr> <td>SIGNING_BACKEND</td> <td class="code">
<pre>&#x27;django.core.signing.TimestampSigner&#x27;
</pre></td> </tr> <tr>
<td>SILENCED_SYSTEM_CHECKS</td> <td
class="code"><pre>[]</pre></td> </tr> <tr>
<td>SIMPLE_JWT</td> <td class="code"><pre>
{&#x27;ACCESS_TOKEN_LIFETIME&#x27;:
&#x27;*****&#x27;,
&#x27;AUTH_HEADER_TYPES&#x27;:
&#x27;*****&#x27;,
&#x27;REFRESH_TOKEN_LIFETIME&#x27;:
&#x27;*****&#x27;}</pre></td> </tr> <tr>
<td>SPECTACULAR_SETTINGS</td> <td class="code">
<pre>{&#x27;TITLE&#x27;: &#x27;Spazaafy API&#x27;,
&#x27;VERSION&#x27;: &#x27;1.0.0&#x27;}</pre></td>
</tr> <tr> <td>STATICFILES_DIRS</td> <td
class="code"><pre>[]</pre></td> </tr> <tr>
<td>STATICFILES_FINDERS</td> <td class="code">
<pre>
[&#x27;django.contrib.staticfiles.finders.FileSystemFinder&#x27;
&#x27;django.contrib.staticfiles.finders.AppDirectoriesFinder&#
</pre></td> </tr> <tr> <td>STATIC_ROOT</td> <td
class="code"><pre>&#x27;/app/staticfiles&#x27;</pre>
</td> </tr> <tr> <td>STATIC_URL</td> <td class="code">
<pre>&#x27;/static/&#x27;</pre></td> </tr> <tr>
<td>STORAGES</td> <td class="code"><pre>
{&#x27;default&#x27;: {&#x27;BACKEND&#x27;:
&#x27;django.core.files.storage.FileSystemStorage&#x27;},
&#x27;staticfiles&#x27;: {&#x27;BACKEND&#x27;:

```



```

&#x27;django.contrib.staticfiles.storage.StaticFilesStorage&#x2
</pre></td> </tr> <tr> <td>TEMPLATES</td> <td
class="code"><pre>[&#x27;APP_DIRS&#x27;; True,
&#x27;BACKEND&#x27;;
&#x27;django.template.backends.django.DjangoTemplates&#x2
&#x27;DIRS&#x27;; [], &#x27;OPTIONS&#x27;;
{&#x27;context_processors&#x27;;
[&#x27;django.template.context_processors.debug&#x27;;,
&#x27;django.template.context_processors.request&#x27;;,
&#x27;django.contrib.auth.context_processors.auth&#x27;;,
&#x27;django.contrib.messages.context_processors.messages&
</pre></td> </tr> <tr>
<td>TEST_NON_SERIALIZED_APPS</td> <td
class="code"><pre>[]</pre></td> </tr> <tr>
<td>TEST_RUNNER</td> <td class="code">
<pre>&#x27;django.test.runner.DiscoverRunner&#x27;
</pre></td> </tr> <tr>
<td>THOUSAND_SEPARATOR</td> <td class="code">
<pre>&#x27;;&#x27;</pre></td> </tr> <tr>
<td>TIME_FORMAT</td> <td class="code">
<pre>&#x27;P&#x27;</pre></td> </tr> <tr>
<td>TIME_INPUT_FORMATS</td> <td class="code">
<pre>[&#x27;%H:%M:%S&#x27;;,
&#x27;%H:%M:%S.%f&#x27;;, &#x27;%H:%M&#x27;]
</pre></td> </tr> <tr> <td>TIME_ZONE</td> <td
class="code"><pre>&#x27;Africa/Johannesburg&#x27;
</pre></td> </tr> <tr> <td>USE_I18N</td> <td
class="code"><pre>True</pre></td> </tr> <tr>
<td>USE_THOUSAND_SEPARATOR</td> <td
class="code"><pre>False</pre></td> </tr> <tr>
<td>USE_TZ</td> <td class="code"><pre>True</pre>
</td> </tr> <tr> <td>USE_X_FORWARDED_HOST</td>
<td class="code"><pre>False</pre></td> </tr> <tr>
<td>USE_X_FORWARDED_PORT</td> <td class="code">
<pre>False</pre></td> </tr> <tr>
<td>WSGI_APPLICATION</td> <td class="code">
<pre>&#x27;spazaafy_backend.wsgi.application&#x27;
</pre></td> </tr> <tr> <td>X_FRAME_OPTIONS</td> <td
class="code"><pre>&#x27;DENY&#x27;</pre></td> </tr>
<tr> <td>YEAR_MONTH_FORMAT</td> <td
class="code"><pre>&#x27;F Y&#x27;</pre></td> </tr>
</tbody> </table> </div> </main> <footer
id="explanation"> <p> You're seeing this error because
you have <code>DEBUG = True</code> in your Django
settings file. Change that to <code>False</code>, and
Django will display a standard page generated by the
handler for this status code. </p> </footer> </body>
</html>

```

[Create account](#)

Already have an account? [Sign in](#)