Contract SPMYM327Q5008/SPMYM327P5008

Attachment 2

Section "B"

Stock Number: 5305-LL-D00-0249

Item Name: SOCKET HEAD CAPSCREW

CMMC: LEVEL 1

Section "C"

C.1: SOCKET HEAD CAP SCREW. FF-S-86J, TY VI. 0.3125-18UNC-3A X 1.500. NICUAL, QQ-N-286G, ANNEALED AND AGE HARDENED. HEAD TO BE DRILLED FOR LOCKWIRE IAW FF-S-86J, TABLE 1. NOTE: Earlier revisions of FF-S-86 are acceptable as long as the certifications or COC document that NICUAL material having been headed or roll threaded shall not be age hardened unless it has been solution annealed subsequent to the heading and threading operations. Threads formed after the final age hardening heat treatment shall be cut or ground only.

C.2 See Exhibit "A" Seq A001: CDRL DI-MISC-81356A (Certificate of Compliance).
C.3 See Exhibit "A" Seq. A002: CDRL DI-MISC-80678 (Certification / Data Report).
C.4 PNS Standard Clauses C500 (Mercury Exclusion), C524 (Marking & Certification Requirements) & C531 (Restrictions on K-Monel Material) Apply.

Section "D"

D2.2 STANDARD COMMERCIAL PRACTICE (**COMMERCIAL PACKAGING**) APPLIES.

Section "E"

PNS STANDARD FAR 52.246-1 CLAUSE (**CONTRACTOR INSPECTION REQUIREMENTS**), **E-2 (INSPECTION & ACCEPTANCE - DESTINATION) & E504 (NOTICE OF CONSTRUCTIVE ACCEPTANCE PERIOD**) APPLY.

Section "G"

NON LEVEL-1 MAT'L

Section "H"

STANDARD CLAUSE H500 (SPECIAL PROVISIONS FOR THREADED PRODUCTS) APPLIES.