EX FAN 5
EX FAN 5

DIVERTER VALVE
MAINTENANCE CONTROL PANEL
120V. PLC CONTROL VOLTAGE
SUPPLIED FROM MCC1/PLC LOCATED
N DUST COLLECTOR EQUIPMENT ROOM
SEPARATE 120V. CONTROL VOLTAGE
SUPPLIED FROM PANEL PPA CKT.-20 LOCATED
IN DUST COLLECTOR EQUIPMENT ROOM
DIVERTER VALVE #1
DIVERTER VALVE #2
DIVERTER VALVE #3
DIVERTER VALVE #4
SYSTEM I SYSTEM 2
DIVERTER VALVE #5
DIVERTER VALVE #6
DIVERTER VALVE #7
DIVERTER VALVE #8
ERTER #8
00 (FAN #8)
ERTER #2
00 (FAN #2)
IVERTER #6
PARE (FAN #6)

EXIT
EMERGENCY EXIT
ONLY

COOLING TOWER

CONDUCTIVITY LEVEL : 1100 - 1200

OPEN LOOP TREATMENT

TI – 310 T

RANGE: 50 - 100 PPM

BIOCIDE

BROM MAX 7.1

STAIRS LIGHT

CLOSED SYSTEM TREATMENT

CS 260 -- T

RANGE : 50 - 100 PPM

PUMP IS SET TO RUN 25 MINUTES A DAY

CONTROLLED BY TIMER

MAKE SURE TIME IS IN "AUTO"

Electro-therm
L O.
Electro-therm
40.7
PROCESS WATER
Supply
34-10
34-10