

Morelord Character Export

Module documentation reference

READMEs and user / GM documentation

September 7, 2026 | Local source snapshot

Local manifest version: **0.3.2**. This PDF collects the source documents listed below. Original manual version labels are preserved; older manuals may not cover newer README changes. This conversion does not establish current public release availability.

Included source	Document
morelord-character-export/README.md	Morelord Character Export

Prepared in the visual style of the Campaign Manager Product Summary v1.4 and Product and Development Plan v1.0. Use PDF bookmarks to navigate sections.

Morelord Character Export

Morelord Character Export adds a **Morelord Export** command to the title-bar controls of D&D 5e character sheets in Foundry Virtual Tabletop.

The command downloads a portable JSON file intended for the Morelord Character Manager. The export contains the Actor's complete source data, a snapshot of values already prepared by Foundry and D&D 5e, and an embedded image library for character-sheet artwork.

Compatibility

- **Foundry VTT:** v14 only.
- **Game system:** D&D 5e.
- Uses the Foundry v14 `getHeaderControlsApplicationV2` hook.
- Designed for the current D&D 5e ApplicationV2 character sheet and Tidy 5e character sheet.
- Foundry v13 and legacy ApplicationV1 sheets are not supported.

Current features

- Foundry VTT v14 support.
- D&D 5e character Actors only.
- ApplicationV2 title-bar integration.
- Complete serializable `Actor#toObject(true)` source data, including embedded Items, item activities, and Active Effects.
- Display-ready values copied from the live, prepared Actor under `derived`.
- Deduplicated embedded image library containing:
 - character portrait
 - prototype token image
 - class, subclass, species, background, feat, spell, equipment, container, tool, consumable, and other Item icons
- Item IDs mapped directly to their embedded image asset IDs.
- Images resized and converted to WebP when possible.
- Public API for macros and development testing.
- Exact Foundry and D&D 5e system versions recorded in every export.

Installation during development

Place the repository outside the Foundry data directory and create a Windows directory junction inside your Foundry modules folder.

Run Command Prompt as Administrator:

```
mklink /J "C:\Path\To\FoundryVTT\Data\modules\morelord-character-export"
"C:\Path\To\GitHub\morelord-character-export"
```

Enable **Morelord Character Export** under **Manage Modules** in the desired world.

Use

Open a D&D 5e player-character sheet and choose **Morelord Export** from the sheet's title-bar controls.

The downloaded filename uses this pattern:

```
character-name.morelord-character.json
```

Macro API

Export an Actor directly:

```
await game.modules.get("morelord-character-export").api.exportCharacter(actor);
```

Export the currently selected token's Actor:

```
const actor = canvas.tokens.controlled[0]?.actor;
if (!actor) return ui.notifications.warn("Select a token first.");
await game.modules.get("morelord-character-export").api.exportCharacter(actor);
```

Export by UUID:

```
await game.modules
  .get("morelord-character-export")
  .api.exportActorByUuid("Actor.ACTOR_ID");
```

Export format

Format version 3 stores all images once and references them by asset ID:

```
{
  "format": "morelord-character",
  "formatVersion": 3,
  "exportedAt": "2026-08-03T00:00:00.000Z",
  "source": {
    "moduleVersion": "0.3.0",
    "foundryVersion": "14.365",
    "systemVersion": "5.3.3"
  },
  "actor": {},
  "derived": {},
  "assets": {
    "images": {
      "image-1": {
        "path": "tokenizer/pc-images/example.webp",
        "mimeType": "image/webp",
        "data": "data:image/webp;base64,...",
        "embedded": true
      }
    },
    "references": {
      "actor": {
        "portrait": "image-1",
        "prototypeToken": "image-2"
      },
      "items": {
        "ITEM_ID": "image-3"
      }
    }
  }
}
```

```

    },
    "summary": {
      "requested": 3,
      "embedded": 3,
      "failed": 0
    }
  }
}

```

The raw Actor and embedded Item records retain their original Foundry image paths. The Character Manager should resolve portable images through `assets.references` and `assets.images`, then use the original path or a generic icon only as a fallback.

Installation from Foundry

In Foundry VTT Setup, open **Add-on Modules**, choose **Install Module**, and paste this manifest URL:

<https://github.com/morelordgaming/morelord-character-export/releases/latest/download/module.json>

After installation, enable **Morelord Character Export** under **Manage Modules** in a D&D 5e world.

Previous versions are available from the repository's GitHub Releases page.

Creating a release

The release workflow requires:

- Git
- GitHub CLI (gh)
- an authenticated GitHub CLI session (`gh auth login`)
- a clean Git working tree

From PowerShell in the repository root, publish a release with:

```
.\release.ps1 -Version 0.3.1
```

The script:

1. updates `module.json` with the requested version and version-specific download URL;
2. writes and validates `module.json` as UTF-8 without a byte-order mark;
3. builds `release/morelord-character-export.zip` with `module.json` at the ZIP root;
4. copies the standalone release manifest to `release/module.json`;
5. commits the version change, creates and pushes the Git tag;
6. publishes both assets to a GitHub Release.

To validate and build the package without changing Git or publishing a release:

```
.\release.ps1 -Version 0.3.1 -BuildOnly
```