TPMS API

- 1.1 Overview
- 1.2 Authentication
- 1.3 Endpoints
  - 1.3.1 [POST] /temptruckassign
  - 1.3.2 [GET] /techinfo
  - 1.3.3 [PUT] /techinfo
  - 1.3.4 [GET] /techsupdatedafter/{timestamp}
  - 1.3.5 [POST] /addtruck
- 1.4 Additional Information

1.1 Overview

- **API Name:** TPMS (Tech Profile Management) API
- **Description:** This API exposes operations that can be performed in TPMS GUI as API endpoints.
- **Base URL:**
  - https://hspsc-api-gateway-dev.stage.nextgen.shs.com/v1/api/techprofile/api [DEV]
  - https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api [QA]
  - https://hspsc-api-gateway.prod.nextgen.shs.com/v1/api/techprofile/api [PROD]
- **Version: v1**

1.2 Authentication

- **Type:** Bearer token
- **How to Obtain Credentials:** Get token from SOM Auth Service

1.3 Endpoints

1.3.1 [POST] /temptruckassign

- **Endpoint URL: https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/temptruckassign**
- **HTTP Method:** POST
- **Data Format:** JSON
- **Description:** Through this endpoint, a technician can ask for a temporary assignment (for today) of a truck in the same district.
- **Request Body:**

Column	Required (Y/N)	Format	Comments
`correlationId`	N		
`ldapId`	Y	Alphanumeric, Max length 8	Requesting Technician's LDAP id
`distNo`	Y	7 digits, prefixed	District that the Tech belongs to

		with 0 if needed	
`truckNo`	Y	6 digits, prefixed with 0 if needed	Truck # (this truck should belong to same district as the requesting tech)

- **Response:**

Column	Always present (Y/N)	Format	Comments
`correlationId`	Y	Alphanumeric	If correlation id was passed in request, same will be returned otherwise a new one will be created

`result`	Y		Possible values
			`ALLOCATED, // Assignment is allowed and temporary allocation done in DB`
			`DISALLOWED, // Assignment is not allowed because truck already allocated to another tech, or tech/truck not in same dist`
			`ERROR // Validation error or another error occurred during processing`

`messages`	N	List	Present when DISALLOWED or ERROR

- **Example Request:**

```
{
    "ldapId": "NSHAMS",
    "distNo": "0008169",
    "truckNo": "006527"
}
```

- **Example Response:**
- Allocated

```
{
    "correlationId": "1760516626050",
    "result": "ALLOCATED",
    "messages": null
}
```

- Disallowed

```
{
    "correlationId": "1760516002734",
    "result": "DISALLOWED",
    "messages": [
        "Truck 006527 is temporarily assigned to tech NSHAMS today, can't be assigned to NDESAI0"
```

```
    ]
}
```

- Error

```
{
    "correlationId": "1760517160828",
    "result": "ERROR",
    "messages": [
        "Tech Dist No  is required"
    ]
}
```

- **Rules:**

Technician cannot have more than one tech trucks assigned in a day. (when Tech tries to take another truck his assignment to the previous temp truck is automatically removed and new one is assigned.)

- Technician and Truck both need to belong to the same district.

1.3.2 [GET] /techinfo

- **Endpoint URL:** https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/techinfo/{key}
- **HTTP Method:** GET
- **Data Format:** -
- **Description:** Through this endpoint, one can get a Technician's profile information, addresses, shipping holds and FSSL/Overridden replenishment information.
- **Response:**

Column	Format	Comments
`correlationId`	String	If correlation id was passed in request header `x-correlation-id`, same will be returned otherwise a new one will be created
`messages`	List	"SUCCESS" when search is successful otherwise the relevant error message
`techInfoList`	List of `TechInfo`	

TechInfo	Format	Comments
`ldapId`	String	
`firstName`	String	
`lastName`	String	
`techId`	String	
`districtNo`	String	

`techManagerLdapId`	String	
`truckNo`	String	
`contactNo`	String	
`email`	String	
`addresses`	List of `TechAddress`	See below **TechAddress** table
`latestShippingHold`	`ShippingHold`	See below **ShippingHold** table
`techReplenishment`	`TechReplenishment`	See below **TechReplenishment** table
`lastUpdated`	`LocalDateTime`	Shows Year to Milliseconds. Format is yyyy-mm-ddThh:mi:ss.mil. Example "2026-01-22T08:05:01.332"

TechAddress	Format	Comments

`addressType`	String	One of
		`PRIMARY`
		`RE_ASSORTMENT,`
		`DROP_RETURN`
		`ALTERNATE`

`shipToName`	String	
`addrLine1`	String	
`addrLine2`	String	
`city`	String	
`stateCd`	String	
`zipCd`	String	

ShippingHold	Format	Comments
`beginDate`	Date (yyyy-MM-dd)	For example 2025-11-01
`endDate`	Date (yyyy-MM-dd)	For example 2025-11-10
`holdReason`	String	One of `Vacation`

		Weather Temporary Assignment Other

TechReplenishment	Format	Comments
`primarySrc`	String	
`providerName`	String	
`storeLocation`	String	
`alternateAddress`	`TechAddress`	This field is currently not saved in DB, so it will not be available in response for now
`overridePrimarySrc`	boolean	

- **Example Request**

https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/techinfo/WADEL

https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/techinfo/002545

- **Example Response**

Example with shipping hold


```json
{
    "correlationId": "1111-2222-333",
    "messages": [
        "SUCCESS"
    ],
    "ldapId": "WADEL   ",
    "firstName": "WAHIDULLAH",
    "lastName": "ADEL",
    "techId": "0543799",
    "districtNo": "0007084",
    "techManagerLdapId": "CONEI02 ",
    "truckNo": "022138 ",
    "latestShippingHold": {
        "beginDate": "2025-11-01",
        "endDate": "2025-11-10",
        "holdReason": "Vacation"
    },
    "lastUpdated": "2026-01-27T05:52:48.179"
}
```


Example with address and Tech replenishment override


```json
{
    "correlationId": "1111-2222-444",
    "messages": [
        "SUCCESS"
    ],
    "ldapId": "NSHAMS  ",
    "firstName": "NASER",
    "lastName": "SHAMS",
    "techId": "0646752",
    "districtNo": "0007084",
    "techManagerLdapId": "RNORRIS ",
    "truckNo": "002545 ",
    "addresses": [
        {
            "addressType": "PRIMARY",
```

```
            "addrLine1": "10 Southside Boulevard",
            "city": "Jacksonville",
            "stateCd": "FL",
            "zipCd": "32256"
        }
    ],
    "techReplenishment": {
        "primarySrc": "3PL",
        "overridePrimarySrc": false
    },
    "lastUpdated": "2026-01-27T05:52:48.179"
}
```


Example with all addresses present


```
{
    "correlationId": "1111-2222-111",
    "messages": [
        "SUCCESS"
    ],
    "ldapId": "JBOROWS ",
    "firstName": "JOSEPH",
    "lastName": "BOROWSKI",
    "techId": "0003459",
    "districtNo": "0004766",
    "techManagerLdapId": "AHARE1  ",
    "truckNo": "021960 ",
    "addresses": [
        {
            "addressType": "DROP_RETURN",
            "shipToName": "JBOROWS-Return",
            "addrLine1": "33 Southside Boulevard",
            "addrLine2": "#302",
            "city": "Jacksonville",
            "stateCd": "FL",
            "zipCd": "32256"
        },
        {
            "addressType": "PRIMARY",
            "shipToName": "JBOROWS",
            "addrLine1": "1111 Primary Addr",
            "city": "Chicago",
            "stateCd": "IL",
            "zipCd": "60708"
        },
        {
            "addressType": "ALTERNATE",
            "shipToName": "JBOROWS-Alt",
            "addrLine1": "420 PEARL ST",
            "city": "Danbury",
            "stateCd": "CT",
            "zipCd": "06067"
        },
        {
            "addressType": "RE_ASSORTMENT",
            "shipToName": "JBOROWS",
            "addrLine1": "2222 Secondary",
            "city": "Chicago",
            "stateCd": "IL",
            "zipCd": "60708"
        }
    ],
    "techReplenishment": {
        "primarySrc": "PDC",
        "providerName": "NA",
        "storeLocation": "NA",
        "overridePrimarySrc": false
    },
    "lastUpdated": "2026-01-27T05:52:48.179"
}
```


Example with no data found


```
{
    "correlationId": "1761664164533",
    "messages": [
        "No Data Found for ldap/truckNo NDESAI0"
    ]
}
```

And

```
{
    "correlationId": "1761664185636",
    "messages": [
        "No Data Found for ldap/truckNo 01010101"
    ]
}
```

1.3.3 [PUT] /techinfo

- **Endpoint URL:** https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/techinfo
- **HTTP Method:** PUT
- **Data Format:** JSON
- **Description:** Through this endpoint, following information for a tech can be changed
  - Profile - Contact No and Email
  - Assigned truck
  - Address
  - Tech Replenishment information [TBD]
- **Request Body:**

Column	Required (Y/N)	Format	Comments
`techLdapId`	Y	Alphanumeric, Max length 8	Requesting Technician's LDAP id
`upserts`	Y	`Upserts`	Section containing all inserts and updates to perform

Upserts	Required (Y/N)	Format	Comments
`techId`	N	String	Pass this if need to update techId for a technician. Pass "" if you want to remove techId of requesting tech
`truckNo`	N	String	Truck no to be assigned to this tech (represented by `techLdapId`). Cannot be assigned if already assigned to another tech. Pass "" if you want to remove current truck assignment for requesting tech

`contactNo`	N	String	Phone number. Pass “” if you want to remove phone no for requesting tech
`email`	N	String	Email Pass “” if you want to remove email for requesting tech
`addresses`	N	List of `TechAddress`	
`updatedBy`	Y	String	Required. Ldap Id of associate making this update

TechAddress	Required (Y/N)	Format	Comments
`addressType`	Y	String	One of P, D, R, A where P=PRIMARY R=RE_ASSORTMENT D=DROP_RETURN A=ALTERNATE
`shipToName`	N	String	
`addrLine1`	Y	String	Max length 30
`addrLine2`	N	String	Max length 30
`city`	Y	String	
`stateCd`	Y	String	2 character state code e.g. IL, AL etc.
`zipCd`	Y	String	Can be 5 or 9 characters
`distUnitNo`	N		7 Characters

- **Response:**

Column	Format	Comments
`correlationId`	String	

`updateSuccess`	List of String	Returns names of operations that succeeded for example
		`UPDATE_TECH_PROFILE,`
		`UPDATE_TECH_ID,`
		`UPDATE_TECH_REPLENISHMENT,`
		`UPDATE_TECH_ADDRESS,`
		`UPDATE_TRUCK_OWNER,`

`failedUpdates`	List of `FailedUpdate`	

FailedUpdate	Format	Comments

`fieldName`	String	Denotes which operation failed. One of
		`UPDATE_TECH_PROFILE,`
		`UPDATE_TECH_ID,`
		`UPDATE_TECH_REPLENISHMENT,`
		`UPDATE_TECH_ADDRESS,`
		`UPDATE_TRUCK_OWNER,`

`reason`	String	Reason for failure

- **Example Request:**

```
{
  "techLdapId": "JWALZE",
  "upserts": {
    "contactNo": "2223335555",
    "email" : "yzx@b.com",
    "truckNo": "011220",
    "addresses": [
      {
        "addressType": "A",
        "addrLine1": "123 Main St",
        "addrLine2": "#123",
        "city": "Chicago",
        "stateCd": "IL",
        "zipCd": "60601"
      },
      {
        "addressType": "P",
        "addrLine1": "45 Office St",
        "city": "Chicago",
        "stateCd": "IL",
        "zipCd": "60601"
      }
    ],
    "updatedBy": "NDESAI0"
  }
}
```

- **Example Response (all success):**

```
{
    "correlationId": "1769618784832",
    "responseCode": null,
    "responseMessage": null,
    "messages": [],
    "updateSuccess": [
        "UPDATE_TECH_PROFILE",
        "UPDATE_TECH_ADDRESS",
        "UPDATE_TRUCK_OWNER"
    ],
    "failedUpdates": []
```

```
}
```

- **Example Response (some failures):**

```
{
    "correlationId": "12345667890",
    "responseMessage": null,
    "messages": [],
    "updateSuccess": [
        "UPDATE_TECH_PROFILE"
    ],
    "failedUpdates": [
        {
            "fieldName": "UPDATE_TRUCK_OWNER",
            "reason": "Truck '002134' is already assigned to tech"
        },
        {
            "fieldName": "UPDATE_TECH_ADDRESS",
            "reason": "Unable to update address for tech due to java.lang.NullPointerException"
        }
    ]
}
```

1.3.4 [GET] /techsupdatedafter/{timestamp}

- **Endpoint URL:** https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/techsupdatedafter{timestamp}
- **HTTP Method:** GET
- **Data Format:** -
- **Description:** Through this endpoint, one can get profile information, addresses, shipping holds and FSSL/Overridden replenishment information of all those technicians whose info was updated after given timestamp. The timestamp needs to be of format “yyyy-mm-ddThh:mi:ss“ for example **2026-01-10T07:01:00**.
- **Response:**

Response structure is same as that of “/techInfo”.

1.3.5 [POST] /addtruck

- **Endpoint URL:** **https://hspsc-api-gateway-qa.stage.nextgen.shs.com/v1/api/techprofile/api/addtruck**
- **HTTP Method:** POST
- **Data Format:** JSON
- **Description:** Through this endpoint, a new truck can be created. It is meant to be called when a new Location is added in NetSuite.
- **Request Body:**

Column	Required (Y/N)	Format	Comments
`correlationId`	N		
`truckNo`	Y	Numeric, Max length 6	Truck to be added

`truckName`	Y	Alphanumeric, max length 40	
`regionNo`	Y	Numeric, 7 digits, prefixed with 0 if needed	
`distNo`	Y	Numeric, 7 digits, prefixed with 0 if needed	District that the Truck belongs to
`spareTruck`	N	Boolean	Whether this is a psare truck or not. Default N
`updatedBy`	Y	Max length 8	User who is creating new truck (LDAP Id)

- **Response:**

Column	Always present (Y/N)	Format	Comments
`correlationId`	Y	Alphanumeric	If correlation id was passed in request, same will be returned otherwise a new one will be created
`responseMessage`	Y		SUCCESS or FAILURE
`messages`	N	List	Shows error messages when there are errors

- **Example Request**

```
{
    "truckNo": "000001",
    "truckName": "Truck Number 000001",
    "regionNo": "0000890",
    "distNo": "0004766",
    "updatedBy": "NDESAI0"
}
```

- **Example Response**

Successful response (HTTP 201)

```
{
```

```
    "correlationId": "1773149776495",
    "responseCode": null,
    "responseMessage": "SUCCESS",
    "messages": []
}
```

When truck already exists (validation error HTTP 400)

```
{
    "correlationId": "1773149617283",
    "responseCode": null,
    "responseMessage": "FAILURE",
    "messages": [
        "Truck number already exists. "
    ]
}
```

When invalid data is sent (Validation error HTTP 400)

```
{
    "correlationId": "1773149684124",
    "responseCode": null,
    "responseMessage": "FAILURE",
    "messages": [
        "truckNo must be between 1 and 6 characters",
        "distNo is required",
        "distNo is not numeric",
        "distNo must be between 1 and 7 characters"
    ]
}
```

1.4 Additional Information

- **Related Jira(s):** PSC-2977: New TPMS API for STSD-1453 Prevent Technicians from Logging Into Invalid Van Numbers DONE
- PSC-2990: Develop endpoint "[GET] /techinfo" for Driveline integration with TPMS DONE
- PSC-3014: Develop endpoint "[PUT] /techinfo" for Driveline integration with TPMS DONE
- PSC-3055: Develop endpoint "[GET] /techsupdatedafter/{timestamp}" for Driveline integration with TPMS DONE
- PSC-3078