Try this prompt: I need to modify this SQL query to count how many teams had an average three-point shooting percentage of at least 37% (0.37) from 2018 onward: SELECT
team_home,
season,
AVG(home_team_win) AS avg_home_wins,
AVG(pct_3p_home) AS avg_3p_home
FROM nba.games
WHERE season >= '2018'
GROUP BY season,
team_home
ORDER BY season A;
How should I adjust my query to return only teams that meet this threshold, and should I use HAVING or WHERE to apply the filter?

OpenAI - GPT 5.6 Luna ($$)

Retrieved 9 sources

Use `WHERE` to restrict the input rows to seasons from 2018 onward, and use `HAVING` to filter groups based on the aggregate `AVG(pct_3p_home)`. `WHERE` is evaluated before grouping, while `HAVING` is evaluated after aggregates are calculated postgresql.org.

Return the qualifying team-season groups

sql CollapseCopy

```sql
SELECT
    team_home,
    season,
    AVG(home_team_win) AS avg_home_wins,
    AVG(pct_3p_home) AS avg_3p_home
FROM nba.games
WHERE season >= 2018
GROUP BY team_home, season
HAVING AVG(pct_3p_home) >= 0.37
ORDER BY season ASC, team_home;
```

`HAVING AVG(pct_3p_home) >= 0.37` keeps only team-season groups whose average three-point percentage is at least 37%. Aggregate conditions such as `AVG(...)` belong in `HAVING`, not `WHERE` navicat.com.

Count the qualifying team-season groups

sql CollapseCopy

```sql
SELECT COUNT(*) AS qualifying_team_seasons
FROM (
    SELECT
        team_home,
```

```
    season
FROM nba.games
WHERE season >= 2018
GROUP BY team_home, season
HAVING AVG(pct_3p_home) >= 0.37
) AS qualifying_groups;
```

This counts each qualifying **team-season combination**. If instead you want the number of **distinct teams** that met the threshold in at least one season, use:

sql CollapseCopy

```sql
SELECT COUNT(DISTINCT team_home) AS qualifying_teams
FROM nba.games
WHERE season >= 2018
GROUP BY team_home
HAVING AVG(pct_3p_home) >= 0.37;
```

However, the last query can return one count per qualifying team. To return one total count:

sql CollapseCopy

```sql
SELECT COUNT(*) AS qualifying_teams
FROM (
    SELECT team_home
    FROM nba.games
    WHERE season >= 2018
    GROUP BY team_home
    HAVING AVG(pct_3p_home) >= 0.37
) AS qualifying_teams;
```

Use `season >= 2018` rather than `season >= '2018'` if `season` is numeric.

+6 9 Sources