I'm trying to group my SQL query by both origin_purpose and destination_purpose, and I want to sum up daily_journeys for each pair. How should I write the GROUP BY clause when using multiple fi elds, and how can I sort the results so it's easy to see which combinations are most common?

OpenAI - GPT 5.6 Luna ($$)

Retrieved 3 sources

Use both fields in the `GROUP BY` clause, separated by commas, and sort by the aggregate sum in descending order:

sql ⇕ CollapseCopy

```sql
SELECT
    origin_purpose,
    destination_purpose,
    SUM(daily_journeys) AS total_daily_journeys
FROM your_table
GROUP BY
    origin_purpose,
    destination_purpose
ORDER BY
    total_daily_journeys DESC;
```

This produces one row for each unique `origin_purpose` / `destination_purpose` pair, with the most journeys listed first. `ORDER BY ... DESC` sorts aggregate results from highest to lowest learnsql.com.

If your SQL system does not allow the alias in `ORDER BY`, use the aggregate expression directly:

sql ⇕ CollapseCopy

```sql
ORDER BY SUM(daily_journeys) DESC;
```

You can add a secondary sort for readability:

sql ⇕ CollapseCopy

```sql
ORDER BY
    total_daily_journeys DESC,
    origin_purpose,
    destination_purpose;
```

3 Sources