



SAFETY DATA SHEET

Prepared to OSHA Hazard Communication Standard 29 CFR 1910.1200

WAGK LLC
30 N Gould St Ste R
Sheridan, WY 82801, USA
Tel: +1 (760) 271-8399
www.lvap-products.com

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

Product Type	SG-2
Product Name	LVAP Silicone Grease
Trademark	LVAP
Supplier / Responsible Party	WAGK LLC 30 N Gould St Ste R Sheridan, WY 82801, USA
Telephone	+1 (760) 271-8399
Website	www.lvap-products.com
Date	24th June 2026

SECTION 2 — HAZARD IDENTIFICATION

This Safety Data Sheet is compiled in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Primary Routes of Exposure	Main Hazards
EYE	May cause mild eye irritation. Direct exposure to vapors may cause stinging, tearing and redness. May aggravate existing conjunctivitis of the eye, based on data from components or similar materials.
SKIN	Repeated or prolonged contact with skin may cause irritation which may lead to various skin disorders such as dermatitis, oil acne, or folliculitis. Avoid prolonged skin contact.
INHALATION	Inhalation of vapors or mists may be harmful. Purposely breathing high concentrations of heated vapors may cause light-headedness and nausea, irritate mucosal membranes of mouth, nose, and throat; and aggravate existing respiratory diseases.
ORAL	Ingestion via minor contamination on fingers or food is not likely to cause significant discomfort or adverse effects. Gross amounts may cause irritation of the digestive tract (due to product consistency), nausea and vomiting. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury.

SECTION 3 — COMPOSITION / INFORMATION ON INGREDIENTS

Chemical / Common Name	CAS No.	%
Base Oil	63148-62-9	75~85
Thickener	7631-86-9	15~25
Additives		3~5
No hazardous components.		

SECTION 4 — FIRST AID MEASURES

Oral	DO NOT INDUCE VOMITING. If conscious, give 4 glasses of water. Get immediate medical attention.
------	---



SAFETY DATA SHEET

Prepared to OSHA Hazard Communication Standard 29 CFR 1910.1200

WAGK LLC

30 N Gould St Ste R

Sheridan, WY 82801, USA

Tel: +1 (760) 271-8399

www.lvap-products.com

Eye	Flush with water for at least 17 minutes. Get medical attention if eye irritation develops or persists.
Skin	Wash immediately with soap and water. Remove soiled clothing. Get medical attention if irritation develops. Launder contaminated clothing.
Inhalation	Remove exposed person to fresh air. If breathing is labored, administer oxygen and obtain immediate medical attention. If irritation persists or if toxic symptoms are observed, get medical attention.

SECTION 5 — FIRE FIGHTING MEASURES

Extinguishing Media	Use foam, dry chemical or carbon dioxide.
Unsuitable Extinguishing Media	Do not use water jet.
Special Hazards of Product	This product may give rise to hazardous fumes in a fire.
Protective Equipment for Fire-Fighting	Wear self-contained breathing apparatus.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal Precautions	Material can create slippery conditions underfoot.
Spillages	Transfer into suitable containers for recovery or disposal.

SECTION 7 — HANDLING AND STORAGE

Handling	Avoid prolonged skin contact, breathing vapors, and contaminated clothing. Use with adequate ventilation. Wear recommended protective equipment. Practice good personal hygiene after handling. Empty containers retain material residue. Do not cut, weld, braze, solder or expose containers to other ignition sources.
Storage	Storage temperature should be controlled to between 1 and 42 °C.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation	Use in areas of adequate ventilation.
Gloves	Nitrile or neoprene gloves are recommended.
Eye Protection	Safety glasses, goggles, or face shield are recommended.
Respiratory	Self-contained breathing apparatus is recommended for confined space entry.
Clothing	Long sleeve shirt and apron when potential for skin contact. Wear neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Semi-translucent
------------	------------------



SAFETY DATA SHEET

Prepared to OSHA Hazard Communication Standard 29 CFR 1910.1200

WAGK LLC

30 N Gould St Ste R
Sheridan, WY 82801, USA

Tel: +1 (760) 271-8399
www.lvap-products.com

Boiling Point	n/a
Evaporation Point	Negligible
Flammability	Combustible
Odor	Petroleum oil odor
Specific Gravity	n/a
Solubility in Water (kg/m ³)	Insoluble

SECTION 10 — STABILITY AND REACTIVITY

Stability	Material is normally stable at ambient temperature and pressure.
Conditions to Avoid	No specific measures necessary.
Materials to Avoid	Oxidizing agents. Do not heat above flash point.
Decomposition Products	Carbon dioxide, carbon monoxide.

SECTION 11 — TOXICOLOGICAL INFORMATION

Oral Toxicity	Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain.
Eye Irritation	Not expected to cause eye irritation.
Skin Irritation	Not expected to be a primary skin irritant. Prolonged or repetitive contact may cause irritation.

SECTION 12 — ECOLOGICAL INFORMATION

Mobility	The product is insoluble in water. If released to water the product will sink. The product is poorly absorbed onto soils or sediments.
Persistence / Degradability	The product is expected to be resistant to biodegradation.
Bio-accumulation	Product is not expected to bioaccumulate.

SECTION 13 — DISPOSAL CONSIDERATIONS

Disposal	Consult local regulations regarding disposal methods. Recycle used oil. Do not contaminate used oil with solvents or other chemicals.
----------	---

SECTION 14 — TRANSPORTATION INFORMATION

Transport tools generally used	Railway, boat, barrel. Container must contact the ground to prevent the danger of static electricity.
Temperature of storage	Same as air.
Temperature of pressure	Same as air.



SAFETY DATA SHEET

Prepared to OSHA Hazard Communication Standard 29 CFR 1910.1200

WAGK LLC

30 N Gould St Ste R

Sheridan, WY 82801, USA

Tel: +1 (760) 271-8399

www.lvap-products.com

SECTION 15 — REGULATORY INFORMATION

R Phrases	Keep away from sources of ignition — No smoking.
S Phrases	Use only in well ventilated areas. Keep out of reach of children.
Standard	OSHA Hazard Communication Standard (29 CFR 1910.1200).

SECTION 16 — OTHER INFORMATION

This information is, to the best of WAGK LLC's knowledge, correct and is intended to describe the product requirements. Since the conditions of use are outside WAGK LLC's control, any recommendations or suggestions are made without guarantee, and WAGK LLC disclaims any liability for loss or damage suffered from use of this information. Customers must satisfy themselves that the product is suitable for a particular purpose. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents.

LVAP is a trademark of WAGK LLC, 30 N Gould St Ste R, Sheridan, WY 82801, USA. Revision date: 24 June 2026.