

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical Name: LVAP Urine and Bowl Descaler **Application:** Removes urine and scale build-up **Product Number:** 5001
UN-Number: 1789

Manufacturer Information: WAGK LLC **Emergency Phone No.** Chemtrec: 1-800-424-9300

Remit: 30 N Gould St Ste R, Sheridan, WY 82801

Phone Number: 1 (760) 271-8399

Pages: 4 **Web:** <https://lvap-products.com/>

2. HAZARDS IDENTIFICATION

GHS Classification:


Acute Toxicity (Oral): Category 4

Acute Toxicity (Inhalation): Category 4

Skin Corrosion: Category 1

Serious Eye Damage: Category 1

GHS Pictograms: GHS05 (Corrosion), GHS07 (Exclamation Mark)



Signal Word: DANGER

Hazard Statements:

H302: Harmful if swallowed

H332: Harmful if inhaled

H314: Causes severe skin burns and eye damage

Precautionary Statements:

Prevention:

P260: Do not breathe mist/vapors

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using this product

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell

P330: Rinse mouth

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do

P310: Immediately call a POISON CENTER/doctor

Storage:

P405: Store locked up

Disposal:

P501: Dispose of contents/container in accordance with local regulations

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS #	Component WT%	PEL	TLV	IDLH
*Hydrochloric Acid	7647-01-0	20% – 25%	5 ppm	5 ppm	100 ppm

Comments: A proprietary formula. Strong acid, lung toxin, causes eye burn. Use protective equipment.

4. FIRST AID MEASURES

Inhalation: Move to an uncontaminated area. Call physician immediately. If not breathing give artificial respiration using back pressure-arm lift using Holger-Nelsen method. Watch for edema of the upper airway.

Skin Contact: Flush with water, immediately remove all contaminated clothing.

Ingestion: Do not induce vomiting, drink a large quantity of water and seek medical care.

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue for at least 15 minutes and seek physician help immediately.

Additional Information: None

5. FIRE FIGHTING MEASURES

Flash Point: Not flammable.

Upper Flammable Limit (UEL): N/A

Lower Flammable Limit (LEL): N/A

Auto Ignition: N/D

Rate of Burning: N/D

General Fire Hazards: Possibility of skin and eye burns from fumes, steam or from spray.

Hazardous Combustion Product: May produce irritating acid fumes.

Extinguishing Media: Foam, CO₂ and/or dry chemicals.

Fire Fighting Equipment/Instructions: Use SCBA equipment with full face piece operated in the positive pressure mode. **NFPA Rating:** (Flammability 0) (Health 3) (Reactivity 1)

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid skin contact. Use chemical resistant gloves, safety goggles or face shield and protective clothing. Do not apply the acid above the eye level. When using strong acid use extreme caution and read the label completely before use.

Environmental Precautions: Isolate and evacuate the spilled area. Prevent additional further leakage or spillage, if safe to do so.

Method for Cleanup & Containment: Wear appropriate protective equipment and clothing during the clean-up. By utilizing personal protective equipment (PPE) dilute with water fog, neutralize with baking soda or lime. Isolate spill and use non-combustible material like vermiculite, sand, clay or other absorbent material to absorb the spilled liquid.

Additional Information: Follow local and federal regulations with regard to chemical spills.

7. HANDLING AND STORAGE

Handling Procedure: Avoid breathing mist or vapors. Avoid prolonged contact with skin. Avoid contact with eye. Wear suitable PPE. Wash hands thoroughly after handling the product.

Storage Procedures: Keep in away from reactive chemicals in a cool, well ventilated area.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Occupational Exposure Limits:

ACGIH Components: Use ventilation adequate to maintain TLV.

OSHA Components: No

Engineering Measures: Use fan in confined area. Use local exhaust ventilation.

Personal Protective Equipment (PPE): Utilize suitable protective clothing, and other appropriate PPEs to protect eyes and hands. For exposure above the PEL or TLV, wear a full face piece or half-mask air-purifying (cartridge respirator equipped with an acid gas cartridge or supplied air).

Hygiene Recommendations: Use caution appropriate to strong acids utilizing goggles, face shield, chemical resistant gloves boots and apron. Consider the effect of exposure potentials, handling practices, chemical concentration and ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Orange brown liquid

Physical State: Liquid

Vapor Pressure: N/D

Boiling Point: 206°F

Solubility (H₂O): Soluble in water

Freezing Point: N/D

Odor: Pungent

pH: 2

Density: N/D

Vapor Density: N/A

Melting Point: N/D

Specific Gravity: 1.14

VOC: 0

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Contact with reactive metals.

Incompatibility: Oxidizing agents, Alkaline liquids, Metal powders strong chemicals and reactive metals.

Hazardous Decomposition: When heated to decomposition, emits toxic fumes of HCl and Cl⁻.

11. TOXICOLOGICAL INFORMATION

Route of Entry: Inhalation, skin, ingestion and eyes.

Acute Chronic Toxicity Data: Inhalation may cause lung edema. Eye exposure may cause irritation, burning, corneal damage with impairment of vision. Skin contact causes severe burns (Skin Corrosion Category 1). Ingestion can cause severe burns to entire gastrointestinal tract, including stomach and intestines.

NTP: No

IARC Monographs: No

Carcinogenicity: No component in this product is a carcinogenic.

Chronic Toxicity: Not established.

12. ECOLOGICAL INFORMATION

Ecotoxicity: N/D

Persistence and Degradability: N/D

Bioaccumulative potential: N/D

Mobility in Soil: N/D

Other Adverse effects: N/D

13. DISPOSAL CONSIDERATIONS

Disposal Instructions: Follow local and federal disposal regulations for corrosive material. It is recommended to pH neutralize with lime or baking soda and be solidified with stabilizing absorbent material before disposal.

14. TRANSPORTATION INFORMATION

US DOT Basic Description: UN1789, Hydrochloric acid, 8, PG III

UN Number: UN1789

Proper Shipping Name: Hydrochloric acid

Hazard Class: 8 (Corrosive)

Packing Group: III (hydrochloric acid concentration 20% – 25%, within the 10% – 25% band per 49 CFR 172.101)

Trade Name: LVAP Urine and Bowl Descaler

Marine Pollutant: No

Required Label: Class 8 Corrosive

Ground Limited Quantity: Eligible per 49 CFR 173.154(b) — maximum 5 L per inner packaging, 30 kg gross per package

15. REGULATORY INFORMATION

Classification: Toxic, Corrosive

Hazard Symbol: Exclamation Point, Corrosion

US Federal Regulations:

OSHA'S Hazard Communication Rule, 29 CFR 1910.1200 - Is a toxic and corrosive substance.

SARA Title III - This product does not contain chemicals component with known CAS number that exceed the threshold reporting levels established by SARA Title III, section 313.

State Regulations:

California Prop. 65 — WARNING: This product can expose you to chemicals including Strong Inorganic Acid Mists, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

SDS History

Date Prepared: 06/26/2025

Revision Date: 09/02/2026 (Rev. 2)

Revision Summary: Product name updated to LVAP Urine and Bowl Descaler. Section 3 — hydrochloric acid concentration stated as 20% – 25%; Section 14 — transport classification corrected to UN1789, Hydrochloric acid, 8, PG III; proper shipping name corrected; minor editorial corrections in Sections 9 and 11.

Contact Information:

WAGK LLC

Remit: 30 N Gould St Ste R, Sheridan, WY 82801

Phone Number: 1 (760) 271-8399

Web: <https://lvap-products.com/>

This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantability or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subjected to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein and neither the provider nor the manufacturer are liable to any party for any damages or nature. Including direct, special or consequential damages arising out of or in connection with accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions. The recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.