



ServiceClaims – Integration Guide

Create Request for Authorisation

17 May 2024

Offices:

1650 8180 Greensboro Drive, Suite 600, McLean, VA 22102
2961 W. MacArthur Blvd., Suite 212, Santa Ana, CA 92704
Suites 35-38 Regent House, Heaton Lane, Stockport, SK4 1BS

servicepower.com

© 2024 ServicePower All rights reserved

1. INFORMATION

1.1. DOCUMENT INFORMATION

Product	ServiceClaims
Subject	Integration Guide - Create Request for Authorisation
Version Number	1.10
Version Date	17-May-24
Next Review Date	13-Nov-24

1.2. VERSION HISTORY

Number	Date	Description
2.4	10-Sep-20	General update
2.5	17-May-24	Formatting and Clarity

2. CONTENTS

1.	INFORMATION	2
1.1.	DOCUMENT INFORMATION	2
1.2.	VERSION HISTORY	2
2.	CONTENTS	2
3.	OVERVIEW	2
4.	GENERAL INFORMATION	3
4.1.	AUTHENTICATION	3
4.2.	ELEMENT INFORMATION	3
4.3.	ERRORS	4
5.	GET REQUEST FOR AUTHORIZATION	4
5.1.	URLS	4
5.2.	REQUEST ELEMENTS	6
5.3.	SAMPLE REQUEST	10
5.4.	RESPONSE ELEMENTS	11
5.5.	SAMPLE RESPONSE	12

3. OVERVIEW

In many cases, jobs provided to you via ServiceDispatch will have pre-agreed terms and conditions and an agreed monetary compensation for completing the job. However, there are circumstances where the pre-agreed amount may not be sufficient to complete the job.

Examples may include;

- A job outside the usual area of coverage or in a difficult location.
- A job requires more than one technician for safeguarding reasons.
- The work or fault is not as described, and more time is required to complete the work.



- The work or fault is not as described, and additional parts are needed.

Alternatively, a maximum limit (either of time or money) may be agreed in advance and the ServicePower customer may require Servicers to submit a report once the agreed limit is reached.

When this occurs, Servicers are expected to request an additional authorisation detailing the expected work and/or parts and the impact this will have on the usual compensation. This document describes the API required to request the additional authorisation.

This document explains how to use the web service that exposes the ServicePower set request for authorization functionality.

4. GENERAL INFORMATION

All web services should be called over HTTPS, not HTTP.

4.1. AUTHENTICATION

The web service has an authentication section which contains two elements - user ID and password. A manufacturer client must obtain a user and password that is valid only for web service connections. The user id and password used to connect to the website will not work.

Servicers may use the same user and password that is used to log on to the web site.

Below is a sample of the authentication section.

```
"authentication":  
  {  
    "userId":"SOMEUSER",  
    "password":"userpwd"  
  },
```

4.2. ELEMENT INFORMATION

Certain elements have a restricted set of values specific to your manufacturer number. The valid values for the element will only be listed if all manufacturer numbers use identical values. If elements require specific data for each manufacturer number, the document will indicate that the list of valid values is set up specifically for your manufacturer number and this will be provided to you separately. It is assumed that manufacturer number specific values are values that are specific to the ServicePower system. If the value is something that is stored in your system the comments will indicate this.

Unless specifically indicated within the comments section of each table, elements are optional. However, this is only true from the perspective of the web service accepting the request. The web service may accept blank data but when the claim is edited within the interface, any errors will be highlighted.

The accepted data types for an element are:

- **A** – Alphanumeric
- **N** – Numeric



If the data type of the element is numeric, the maximum number of decimal places will be indicated. The length of a numeric data type indicates the maximum length, including decimals. E.g. A numeric data type of 7 length with 2 decimals means that up to 5 digits can exist prior to the decimal point and up to 2 digits after the decimal point.

4.3. ERRORS

When the web service executes normally, and data is returned, the messages collection will not be provided. All sample responses assume the return code from the web service is 'OK'.

If there are validation errors the messages array with messages for the specific claim will be returned and the response code will be 'ER'.

The messages array will be returned as follows.

```
"messages": [  
  {  
    "message": "Error Message 1"  
  },  
  {  
    "message": "Error Message 2"  
  }  
]
```

5. SET REQUEST FOR AUTHORIZATION

This web service is used to set a request for authorization for a specific manufacturer and call.

ServicePower provides two environments for customers, a staging environment used for testing and configuration purposes, and a production environment. These are accessible to servicers supporting ServicePower customers.

NOTE: The Staging environment is a copy of the Production environment. For that reason, the URLs contained in the welcome email always point to the Production environment. Please ensure that you use the correct URLs documented below.

5.1. URLS

The URLs used to POST to **Staging** are:

- **North America:** <https://upgdev.servicepower.com:8443/services/rfa/v2/setdetailssvc>
- **Europe:** <https://claimsga-eu.servicepower.com/services/rfa/v2/setdetailssvc>

The URLs used to POST to **Production** are:

- **North America:** <https://claimworks.servicepower.com:8443/services/rfa/v2/setdetailssvc>
- **Europe:** <https://claims-eu.servicepower.com/services/rfa/v2/setdetailssvc>



Please note that you may receive an email to the staging system whilst a ServicePower customer project is ongoing. In these circumstances, an invitation to the production environment will be sent once the system is launched.

When accessing the system for the first time, you will be required to change your password. It is important to retain a copy of your password as this will be provided, along with your unique login ID, when accessing the system user interface and when communicating with ServiceDispatch using any API listed in this document.



5.2. REQUEST ELEMENTS

ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
manufacturerName		A	30			
callNumber		A	20			
coreInfo (in collection requests)						
additionalManRequired		A	1		Y or N	
costEffectiveToRepair		A	1		Y or N	
estimatedHoursOnJob		N	3	0		
estimatedMinutesOnJob		N	3	0		
isProductRepaired		A	1		Y or N	
laborInWarranty		A	1		Y or N	
oemAuthorizedWithManufacturer		A	1		Y or N	
partsInWarranty		A	1		Y or N	
pickUpUnitRequired		A	1		Y or N	
whyHigherRate		A	250			
whyAdditionalManOnTheJobQuestions collection						
(These are specific to each manufacturer. Not all manufacturers use these and you will need to be provided with the possible question ids, question type and choice ids. If they are used, all questions need to be answered.						
choiceId		N	3	0	Manufacturer specific.	
responseText		A	50			Only needed if question type is text.
faultCode		A	10		Manufacturer specific.	
productInfo						
newBrand		A	20		Manufacturer specific.	Brand name.
newModel		A	20			



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
newSerialNumber		A	25			
productQuestions collection						
(These are specific to each manufacturer. Not all manufacturers uses these. You will need to be provided with the possible question ids, question type and choice ids. If they are used, all questions need to be answered.)						
questionId		N	3	0	Manufacturer specific.	
choiceId		N	3	0	Manufacturer specific.	Not needed if question type is text.
responseText		A	50			Only needed if question type is text.
Servicer Info						
servicerOnSite						
shippingInfo						
shipAlternateAddressSequence		N	3	0		
shipRecipient		A	1		C-Consumer S-Servicer	
shipShippingOption		A	3		Manufacturer specific.	
shipCompanyName		A	30			
shipFirstName		A	15			
shipLastName		A	20			
shipPhone		N	10	0		
shipEmail		A	50			
shipAddress1		A	30			
shipAddress2		A	30			
shipCity		A	20			
shipState		A	2			
shipZip		A	6			



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
amounts						
requestedLabor		N	7	2		
requestedLaborTax		N	7	2		
requestedMiles		N	5	0		
requestedRatePerMile		N	5	2		
requestedOther		N	7	2		
requestedOtherTax		N	7	2		
requestedPartsTax		N	7	2		
requestedShipping		N	7	2		
requestedFreight		N	7	2		
requestedTax		N	7	2		
requestedTravel		N	7	2		
parts collection						
Note: If you are updating the request and the part is not passed the part will be deleted from the request.						
partSequenceNumber	parts	N	3	0		If you are updating the part this value should be passed to ensure the correct part is updated. If the part number hasn't changed the part number is only on the request once, this value isn't required.
quantity	parts	N	3	0		
partNumber	parts	A	20			
partDescription	parts	A	30			
singlePartCost	parts	N	7	2		
nlaFlag	parts	A	1		Y or N	
partUnderWarranty	parts	A	1		Y or N	
selfSourced	parts	A	1		Y or N	



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
authentication						
userId		A	10			
Password		A	10			



5.3. SAMPLE REQUEST

Sample request data for **test** servers can be obtained from the following locations;

- **North America:**
<https://upgdev.servicepower.com/servicessample/rfa/v2/setrfarequestsvcv2.json>
- **Europe:** [https://claimsga-](https://claimsga-eu.servicepower.com/servicessample/rfa/v2/setrfarequestsvcv2.json)
[eu.servicepower.com/servicessample/rfa/v2/setrfarequestsvcv2.json](https://claimsga-eu.servicepower.com/servicessample/rfa/v2/setrfarequestsvcv2.json)

Sample request data for **production** servers can be obtained from the following locations;

- **North America:**
<https://claimworks.servicepower.com/servicessample/rfa/v2/setrfarequestsvcv2.json>
- **Europe:** <https://claims-eu.servicepower.com/servicessample/rfa/v2/setrfarequestsvcv2.json>



5.4. RESPONSE ELEMENTS

ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
responseCode		A	2		OK or ER	
messageText	Messages	A	132			



5.5. SAMPLE RESPONSE

Sample response data for **test** servers can be obtained from the following locations;

- **North America:**
<https://upgdev.servicepower.com/servicessample/rfa/v2/setrfaresponsesvcv2.json>
- **Europe:** <https://claimsga-eu.servicepower.com/servicessample/rfa/v2/setrfaresponsesvcv2.json>

Sample response data for **production** servers can be obtained from the following locations;

- **North America:**
<https://claimworks.servicepower.com/servicessample/rfa/v2/setrfaresponsesvcv2.json>
- **Europe:** <https://claims-eu.servicepower.com/servicessample/request/v2/setrfaresponsesvc2.json>

