



ServiceClaims – Integration Guide

Retrieve Request for Authorisation Web Service

13 May 2024

Offices:

1650 8180 Greensboro Drive, Suite 600, McLean, VA 22102
2961 W. MacArthur Blvd., Suite 212, Santa Ana, CA 92704
Suites 35-38 Regent House, Heaton Lane, Stockport, SK4 1BS

servicepower.com

© 2024 ServicePower All rights reserved

1. INFORMATION

1.1. DOCUMENT INFORMATION

Product	ServiceClaims
Subject	Integration Guide - Retrieve Request for Authorisation Web Service
Version Number	1.10
Version Date	13-May-24
Next Review Date	13-Nov-24

1.2. VERSION HISTORY

Number	Date	Description
2.9	10-Sep-20	General update
2.10	17-May-24	Formatting and Clarity

2. CONTENTS

1.	INFORMATION	2
1.1.	DOCUMENT INFORMATION	2
1.2.	VERSION HISTORY	2
2.	CONTENTS	2
3.	OVERVIEW	2
4.	GENERAL INFORMATION	3
4.1.	AUTHENTICATION	3
4.2.	ELEMENT INFORMATION	3
4.3.	ERRORS	4
5.	GET REQUEST FOR AUTHORIZATION	4
5.1.	URLS	4
5.2.	REQUEST ELEMENTS	5
5.3.	SAMPLE REQUEST	6
5.4.	RESPONSE ELEMENTS	7
5.5.	SAMPLE RESPONSE	13

3. OVERVIEW

In many cases, jobs provided to you via ServiceDispatch will have pre-agreed terms and conditions and an agreed monetary compensation for completing the job. However, there are circumstances where the pre-agreed amount may not be sufficient to complete the job.

Examples may include;

- A job outside the usual area of coverage or in a difficult location.
- A job requires more than one technician for safeguarding reasons.
- The work or fault is not as described, and more time is required to complete the work.



- The work or fault is not as described, and additional parts are needed.

Alternatively, a maximum limit (either of time or money) may be agreed in advance and the ServicePower customer may require Servicers to submit a report once the agreed limit is reached.

When this occurs, Servicers are expected to request an additional authorisation detailing the expected work and/or parts and the impact this will have on the usual compensation. Having submitted the original request for authorisation, as described in the Servicer Integration Guide – Create Request for Authorisation, it is necessary to retrieve the response before recommencing with work.

This document describes the API required to retrieve the current status of the authorisation request. As authorisations can be reviewed by the ServicePower customer throughout the course of the day, it is recommended that this API is scheduled to run frequently to return the required response.

4. GENERAL INFORMATION

All web services should be called over HTTPS, not HTTP.

4.1. AUTHENTICATION

The web service has an authentication section which contains two elements - user ID and password. A manufacturer client must obtain a user and password that is valid only for web service connections. The user id and password used to connect to the website will not work.

Servicers may use the same user and password that is used to log on to the web site.

Below is a sample of the authentication section.

```
"authentication":  
  {  
    "userId":"SOMEUSER",  
    "password":"userpwd"  
  },
```

4.2. ELEMENT INFORMATION

Certain elements have a restricted set of values specific to your manufacturer number. The valid values for the element will only be listed if all manufacturer numbers use identical values. If elements require specific data for each manufacturer number, the document will indicate that the list of valid values is set up specifically for your manufacturer number and this will be provided to you separately. It is assumed that manufacturer number specific values are values that are specific to the ServicePower system. If the value is something that is stored in your system the comments will indicate this.

Unless specifically indicated within the comments section of each table, elements are optional. However, this is only true from the perspective of the web service accepting the request. The web service may accept blank data but when the claim is edited within the interface, any errors will be highlighted.

The accepted data types for an element are:

- A – Alphanumeric



- **N** – Numeric

If the data type of the element is numeric, the maximum number of decimal places will be indicated. The length of a numeric data type indicates the maximum length, including decimals. E.g. A numeric data type of 7 length with 2 decimals means that up to 5 digits can exist prior to the decimal point and up to 2 digits after the decimal point.

4.3. ERRORS

When the web service executes normally, and data is returned, the messages collection will not be provided. All sample responses assume the return code from the web service is 'OK'.

If there are validation errors the messages array with messages for the specific claim will be returned and the response code will be 'ER'.

The messages array will be returned as follows.

```
"messages": [  
  {  
    "message": "Error Message 1"  
  },  
  {  
    "message": "Error Message 2"  
  }  
]
```

5. GET REQUEST FOR AUTHORIZATION

This web service is used retrieve a request for authorization using either the call number or a date range.

While there is no limit to the date range used the web service will only return a maximum number of calls. A message will indicate if more calls exist than were returned and an element in the web service will also be set to indicate this.

5.1. URLS

The URLs for POST to TEST are:

- **North America:** <https://upgdev.servicepower.com:8443/services/rfa/v2/getdetails>
- **Europe:** <https://claimsga-eu.servicepower.com/services/rfa/v2/getdetails>

The URLs to must POST to PRODUCTION are:

- **North America:** <https://claimworks.servicepower.com:8443/services/rfa/v2/getdetails>
- **Europe:** <https://claims-eu.servicepower.com/services/rfa/v2/getdetails>



5.2. REQUEST ELEMENTS

ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
callNumber		A	20			Mandatory if no date range passed.
manufacturerName		A	30			Not used for manufacturer user type. Mandatory for servicer user type if callNumber is passed. Optional if date range is used.
fromChangedOn		N	16			Optional if call number is passed. Format: CCYYMMDDHHMM
toChangedOn		N	16			Optional. Format: CCYYMMDDHHMM
authentication						
userId		A	10			Mandatory
password		A	10			Mandatory
manufacturerNumber		A	4			Mandatory for manufacturer user type. Not needed for servicer user type.



5.3. SAMPLE REQUEST

Sample request data for **test** servers can be obtained from the following locations;

- **North America:**
<https://upgdev.servicepower.com/servicessample/rfa/v2/getrfarequestv2.json>
- **Europe:** <https://claimsqa-eu.servicepower.com/servicessample/rfa/v2/getrfarequestv2.json>

Sample request data for **production** servers can be obtained from the following locations;

- **North America:**
<https://claimworks.servicepower.com/servicessample/rfa/v2/getrfarequestv2.json>
- **Europe:** <https://claims-eu.servicepower.com/servicessample/rfa/v2/getrfarequestv2.json>



5.4. RESPONSE ELEMENTS

ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
moreCallsExist		A	1		Y or N	
responseCode		A	2		OK or ER	
messageText	messages	A	132			
totalClaimsReceived		N	7			
requests						
NEW:		A	30			
manufacturerName						
callNumber		A	20			
parentRequestNumber		A	20			
amounts (in collection requests)						
authorizedFreight		N	7	2		
authorizedLabor		N	7	2		
authorizedLaborTax		N	7	2		
authorizedMileage		N	7	2		
authorizedMiles		N	5	0		
authorizedOther		N	7	2		
authorizedOtherTax		N	7	2		
authorizedParts		N	7	2		
authorizedPartsTax		N	7	2		
authorizedShipping		N	7	2		
authorizedTax		N	7	2		
authorizedTotal		N	7	2		
authorizedTravel		N	7	2		
preAuthorizedAmount		N	7	2		
requestedFreight		N	7	2		
requestedLabor		N	7	2		
requestedLaborTax		N	7	2		



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
NEW: requestedMiles		N	5	0		NEW: Updated max length and decimals.
NEW: requestedRatePerMile		N	5	2		
requestedMileage		N	5	0		
requestedOther		N	7	2		
requestedOtherTax		N	7	2		
requestedParts		N	5	2		
requestedPartsTax		N	7	2		
requestedShipping		N	7	2		
requestedTax		N	7	2		
requestedTravel		N	7	2		
requestedTotal		N	7	2		
approvalRejectInfo (in collection requests)						
approvedOrAdditionalInformationRequestNotes		A	256			
reasonCode		A	5		Manufacturer specific.	
reasonDescription		A	40			
auditInfo (in collection requests)						
approvedBy		A	10			
approvedOn		N	16		YYYYMMDDHHMMSS	
changedBy		A	10			
changedOn		N	16		YYYYMMDDHHMMSS	
createdBy		A	10			
createdOn		N	16		YYYYMMDDHHMMSS	
coreInfo (in collection requests)						
additionalDaysToFileClaim		N	3	0		
agreementNumber		A	10		Manufacturer specific.	



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
jobCode		A	4		Manufacturer specific.	
repeatCall		A	1		Y or N	
rfaStatus		A	30			Description is returned.
rfaStatusCode		A	3		OPN APV REJ WAI CLS	
customerInfo (in collection requests)						
address		A	30			
cellPhone		N	10	0		
city		A	20			
firstName		A	15			
lastName		A	20			
phone		N	10	0		
state		A	2			
workPhone		N	10	0		
zip		A	9			
otherInfo (in collection requests)						
additionalManRequired		A	1		Y or N	
costEffectiveToRepair		A	1		Y or N	
daysOwned		N	7	0		
estimatedHoursOnJob		N	3	0		
estimatedMinutesOnJob		N	3	0		
isProductRepaired		A	1		Y or N	
laborInWarranty		A	1		Y or N	
oemAuthorizedWithManufacturer		A	1		Y or N	
partsInWarranty		A	1		Y or N	
pickUpUnitRequired		A	1		Y or N	



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
whyHigherRate		A	250			
modificationsOccurred		A	1		Y or N	
whyAdditionalManOnTheJobQuestions collection						
choiceId		N	3	0	Manufacturer specific.	
choiceText		A	40		Manufacturer specific.	Only one of choiceText or responseText will have a value.
responseText		A	50			
questionText		A	150		Manufacturer specific.	
parts collection (in collection requests)						
partSequenceNumber	parts	N	3	0		If you plan to update the part information and you use integrated parts ordering this value will need to be stored. If you don't use integrated parts ordering you only need to store it if the part number might change.
quantity	parts	N	3	0		
partNumber	parts	A	20			
partDescription	parts	A	30			
selfSourced	parts	A	1		Y or N	
singlePartCost	parts	N	7	2		
extMarkUp	parts	N	7	2		
systemCost	parts	N	7	2		
total	parts	N	7	2		
nlaFlag	parts	A	1		Y or N	
distributorNumber	parts	A	12			



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
problemInfo (in collection requests)						
customerNotes		A	150			
repairDescription		A	250			
NEW: faultCode		A	10		Manufacturer specific.	
NEW: faultDescription		A	30			
productInfo (in collection requests)						
brand		A	20			Brand name.
newBrand		A	20		Manufacturer specific.	Brand name.
model		A	20			
newModel		A	20			
serialNumber		A	25			
newSerialSerialNumber		A	25			
product		A	30			Product Description
purchaseDate		N	8		YYYYMMDD	
dealerName		A	30			
productQuestions collection						
questionId		N	3	0	Manufacturer specific.	
questionText		A	150		Manufacturer specific.	
choiceId		N	3	0	Manufacturer specific.	
choiceText		A	40		Manufacturer specific.	
responseText		A	50			
servicerInfo (in collection requests)						



ELEMENT	COLLECTION	TYP	LEN	DEC	VALID VALUES	COMMENTS
assignedServiceId		A	10		Manufacturer specific.	
servicerOnSite		A	1		Y or N	
servicerOEMAuthorized		A	1		Y or N	
servicerProductInProfile		A	1		Y or N	
servicerZipInProfile		A	1		Y or N	
shippingInfo (in collection requests) Only returned if integrated parts ordering is used.						
shipAddress1		A	30			
shipAddress2		A	30			
shipAlternateAddressSequence		N	3	0		
shipCity		A	20			
shipCompanyName		A	30			
shipEmail		A	50			
shipFirstName		A	15			
shipLastName		A	20			
shipPhone		N	10	0		
shipRecipient		A	1		C-Consumer S-Servicer	
shipShippingOption		A	3		Manufacturer specific.	
shipState		A	2			
shipZip		A	6			
subRequests collection (in collection requests)						
subRequestNumber	subRequests	A	20			



5.5. SAMPLE RESPONSE

Sample response data for **test** servers can be obtained from the following locations;

- **North America:**
<https://upgdev.servicepower.com/servicessample/rfa/v2/getrfaresponsev2.json>
- **Europe:** <https://claimsqa-eu.servicepower.com/servicessample/rfa/v2/getrfaresponsev2.json>

Sample response data for **production** servers can be obtained from the following locations;

- **North America:**
<https://claimworks.servicepower.com/servicessample/rfa/v2/getrfaresponsev2.json>
- **Europe:** <https://claims-eu.servicepower.com/servicessample/request/v2/getrfaresponsev2.json>

