

FreeScan UE Nova Series

Wireless Metrology 3D Scanner for Greater Reach



FreeScan UE Nova Series, a wide-range wireless laser handheld 3D scanner, sets the new standard in 3D scanning with its unmatched field of view, enabling highly efficient capture of large objects and significantly enhancing portability, productivity and versatility.



Large-Scale Scanning Coverage

With an extra-large field of view (FOV) of 2.6×2.2 m and a maximum scanning distance of 2.6 m, it is ideal for large-scale projects.



Ultra-Fast Scan Speed

FreeScan UE Nova+ features 62 laser lines for rapid scanning, enabling fast data capture and significantly reducing scanning time.



Integrated Wireless Modules

Wireless modules enable real-time data transmission with high frame rates and stability.



Swappable Batteries

Featuring detachable, hot-swappable batteries, it guarantees continuous scanning during long-time projects or in remote locations.



Video Photogrammetry (VPG)

Utilizing SHINING 3D's patented video-based photogrammetry without coded markers, it integrates with a calibration rod for real-time marker verification, delivering volumetric accuracy of 0.072 mm + 0.012 mm/m for more efficient and reliable data acquisition.



Expand Possibilities with Trak Nova Series

Elevate your capabilities and tackle even the most complex work environments with FreeScan Trak Nova Series.

- Dynamic tracking
- Marker-free scanning



SHINING3D Inspect

SHINING3D Inspect (optional) delivers a streamlined, modular, and customizable approach to 3D inspection, simplifying workflows from data acquisition to reporting.



SPECIFICATIONS

FreeScan UE Nova Series	
Accuracy	0.072 mm (0.0028 in)
Volumetric accuracy with VPG	0.072 mm + 0.012 mm/m (0.0028 in + 0.00014 in/ft)
Scan speed	FreeScan UE Nova+: 5,714,000 points/s; FreeScan UE Nova: 4,600,000 points/s
Resolution	0.5 ~ 10 mm (0.0197 ~ 0.3937 in)
Flexible FOV	Up to 2600 x 2200 mm (102.36 x 86.61 in)
VPG	Included (no coded markers required)
FOV indicator of VPG	Included
High-speed scan	FreeScan UE Nova+: Included (62 laser lines); FreeScan UE Nova: Included (50 laser lines)
Detailed scan	Included (support near mode)
Depth of field	2300 mm (300 ~ 2600 mm) 90.55 in (11.81 ~ 102.36 in)
Connection	Wireless & Wired mode (fiber optic)
Output formats	stl, obj, ply, asc, 3MF, P3
Working temperature	-10 ~ 40 °C (14 ~ 104 °F)
Working humidity	10% ~ 90% RH
Net weight	1.6 kg (3.5 lb)
Certifications	CE, FCC, ROHS, WEEE, KC, FDA, UKCA, IP50, TELEC, TiSAX
Acceptance test	VDI/VDE 2634 Part 3 & ISO 10360 certified (Tested in the ISO/IEC 17025 accredited accuracy lab)
Recommended computer configuration	OS: Windows 10 Pro (64-bit) / Windows 11 Pro (64-bit) Processor: Intel Core i7 or i9 (13th/14th Gen HX) or above; Intel Core Ultra 9 285HX or above Graphics card: NVIDIA GeForce RTX 5080 Laptop GPU or above VRAM: 16G or above; RAM: 64G or above



PRECISE3DM

Contact US

Email Us:

sm@precise3dm.com

service@precise3dm.com

Mobile:

+91 98404 78347

+91 93638 75041

Website :

www.precise3dm.com