

# ISO Presentation

## Quantum Programming

Tristan NEMOZ

Supervisor: Mario BERTA

6 May 2020

# Quantum Computing applied to Machine Learning

- Goal: exponential speed-up

# Quantum Computing applied to Machine Learning

- Goal: exponential speed-up
- HHL<sup>1</sup> (2009):  $O(n) \rightarrow O(\log(n) \kappa^2)$

---

<sup>1</sup>Harrow, Hassidim, and Lloyd, “Quantum Algorithm for Linear Systems of Equations”.

# Quantum Computing applied to Machine Learning

- Goal: exponential speed-up
- HHL<sup>1</sup> (2009):  $O(n) \rightarrow O(\log(n) \kappa^2)$
- Quantum Recommendation Systems<sup>2</sup> (2016):  
 $O(n^2) \rightarrow O(\text{poly}(k) \text{polylog}(mn))$

---

<sup>1</sup>Harrow, Hassidim, and Lloyd, "Quantum Algorithm for Linear Systems of Equations".

<sup>2</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.

# Quantum Computing applied to Machine Learning

- Goal: exponential speed-up
- HHL<sup>1</sup> (2009):  $O(n) \rightarrow O(\log(n) \kappa^2)$
- Quantum Recommendation Systems<sup>2</sup> (2016):  
 $O(n^2) \rightarrow O(\text{poly}(k) \text{polylog}(mn))$

---

<sup>1</sup>Harrow, Hassidim, and Lloyd, "Quantum Algorithm for Linear Systems of Equations".

<sup>2</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.

## Real-world problem overview

- $m$  users can rate  $n$  products

## Real-world problem overview

- $m$  users can rate  $n$  products (binary voting)

## Real-world problem overview

- $m$  users can rate  $n$  products (binary voting)
- Not all ratings are known



## Real-world problem overview

- $m$  users can rate  $n$  products (binary voting)
- Not all ratings are known
- Can we predict whether user  $j$  will like product  $k$ ?

## Mathematical description

### Binary recommendation system

Let  $\mathbf{P} \in \{0; 1\}^{m \times n}$ , whose coefficients are known with a given probability. A quantum recommendation system, given  $\hat{\mathbf{P}}$  the incomplete representation of  $\mathbf{P}$  and an user  $j$ , predicts  $k$  such that  $\mathbf{P}_{j,k} = 1$  with high probability.

## Mathematical description

### Binary recommendation system

Let  $\mathbf{P} \in \{0; 1\}^{m \times n}$ , whose coefficients are known with a given probability. A quantum recommendation system, given  $\hat{\mathbf{P}}$  the incomplete representation of  $\mathbf{P}$  and an user  $j$ , predicts  $k$  such that  $\mathbf{P}_{j,k} = 1$  with high probability.

Impossible problem without assumptions

## Problem assumptions

### The low-rank assumption

Let  $\mathbf{P}$  be the unknown preference matrix. For a given precision parameter  $\varepsilon$ , there exists a rank- $k$  matrix  $\mathbf{T}$  such that:

$$\|\mathbf{P} - \mathbf{T}\|_F \leq \varepsilon \|\mathbf{P}\|_F .$$

## Problem assumptions

### The low-rank assumption

Let  $\mathbf{P}$  be the unknown preference matrix. For a given precision parameter  $\varepsilon$ , there exists a rank- $k$  matrix  $\mathbf{T}$  such that:

$$\|\mathbf{P} - \mathbf{T}\|_F \leq \varepsilon \|\mathbf{P}\|_F .$$

$\implies$  there are  $k$  types of typical users.

## Problem assumptions

### The low-rank assumption

Let  $\mathbf{P}$  be the unknown preference matrix. For a given precision parameter  $\varepsilon$ , there exists a rank- $k$  matrix  $\mathbf{T}$  such that:

$$\|\mathbf{P} - \mathbf{T}\|_F \leq \varepsilon \|\mathbf{P}\|_F .$$

$\implies$  there are  $k$  types of **typical** users.

## Problem assumptions

### The low-rank assumption

Let  $\mathbf{P}$  be the unknown preference matrix. For a given precision parameter  $\varepsilon$ , there exists a rank- $k$  matrix  $\mathbf{T}$  such that:

$$\|\mathbf{P} - \mathbf{T}\|_F \leq \varepsilon \|\mathbf{P}\|_F .$$

$\implies$  there are  $k$  types of typical users.

### Problem initialization

$\mathbf{P}$  can be sampled into  $\hat{\mathbf{P}}$  such that  $\hat{\mathbf{P}}$  holds the low-rank assumption. Hence,  $\varepsilon$  is assumed to be known.

# A Quantum Recommendation System

- Introduced in 2016<sup>3</sup>

---

<sup>3</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.



# A Quantum Recommendation System

- Introduced in 2016<sup>3</sup>
- Offers an exponential speed-up regarding to classical algorithms at that time

---

<sup>3</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.

## A Quantum Recommendation System

- Introduced in 2016<sup>3</sup>
- Offers an exponential speed-up regarding to classical algorithms at that time
- No practical implementation proposed

---

<sup>3</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.

# A Quantum Recommendation System

- Introduced in 2016<sup>3</sup>
- Offers an exponential speed-up regarding to classical algorithms at that time
- No practical implementation proposed

---

<sup>3</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.

# A Quantum Recommendation System

- Introduced in 2016<sup>3</sup>
- Offers an exponential speed-up regarding to classical algorithms at that time
- No practical implementation proposed

## Problem statement

How does the real-world implementation of the Quantum Recommendation System algorithm differs from its theoretic implementation?

---

<sup>3</sup>Kerenidis and Prakash, *Quantum Recommendation Systems*.

## Classical computing

- Operates on bit-strings 0110110001

## Classical computing

- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$

## Classical computing

- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, some are not

## Classical computing

- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, some are not
- Cloning or setting a bit to 0 can be done in  $O(1)$




## Classical computing

- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, some are not
- Cloning or setting a bit to 0 can be done in  $O(1)$
- Operates with a limited set of gates:

## Classical computing


- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, some are not
- Cloning or setting a bit to 0 can be done in  $O(1)$
- Operates with a limited set of gates:




(a) NOT gate

## Classical computing

- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, some are not
- Cloning or setting a bit to 0 can be done in  $O(1)$
- Operates with a limited set of gates:




(a) NOT gate




(b) OR gate

## Classical computing


- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, some are not
- Cloning or setting a bit to 0 can be done in  $O(1)$
- Operates with a limited set of gates:



(a) NOT gate



(b) OR gate




(c) AND gate


**Figure:** Classical gates

## Classical computing


- Operates on bit-strings 0110110001
- Bits are elements of  $\{0; 1\}$
- Some operations are reversible, **some are not**
- Cloning or setting a bit to 0 can be done in  $O(1)$
- Operates with a limited set of gates:



(a) NOT gate



(b) OR gate



(c) AND gate

**Figure:** Classical gates

## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$

## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**

## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**
- **All** operations are reversible



## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**
- **All** operations (aside from measuring) are reversible

## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbf{C}^2$**
- **All** operations (aside from measuring) are reversible
- Cloning or setting a qubit to  $|0\rangle$  is **impossible**

## Quantum computing


- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**
- **All** operations (aside from measuring) are reversible
- Cloning or setting a qubit to  $|0\rangle$  is **impossible** (in the general case)

## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**
- **All** operations (aside from measuring) are reversible
- Cloning or setting a qubit to  $|0\rangle$  is **impossible** (in the general case)
- Operates with a limited set of matrices/gates:

## Quantum computing


- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**
- **All** operations (aside from measuring) are reversible
- Cloning or setting a qubit to  $|0\rangle$  is **impossible** (in the general case)
- Operates with a limited set of matrices/gates:




(a) The  $R_z(\theta)$  gate

## Quantum computing

- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbb{C}^2$**
- **All** operations (aside from measuring) are reversible
- Cloning or setting a qubit to  $|0\rangle$  is **impossible** (in the general case)
- Operates with a limited set of matrices/gates:




(a) The  $R_z(\theta)$  gate




(b) The C – Z gate

## Quantum computing


- Operates on **qubits**-strings  $|q_1\rangle |q_2\rangle |q_3\rangle |q_4\rangle |q_5\rangle$
- Qubits are **normalized vectors of  $\mathbf{C}^2$**
- **All** operations (aside from measuring) are reversible
- Cloning or setting a qubit to  $|0\rangle$  is **impossible** (in the general case)
- Operates with a limited set of matrices/gates:



(a) The  $R_z(\theta)$  gate



(b) The C – Z gate



(c) The  $R_{xy}(\theta, \varphi)$  gate

**Figure:** Quantum gates

## Qubits

A qubit  $|q\rangle$  is a normalized vector of  $\mathbf{C}^2$ . We denote:

$$|q\rangle = \begin{pmatrix} \alpha \\ \beta \end{pmatrix}$$



## Qubits

A qubit  $|q\rangle$  is a normalized vector of  $\mathbf{C}^2$ . We denote:

$$|q\rangle = \begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

## Qubits

A qubit  $|q\rangle$  is a normalized vector of  $\mathbf{C}^2$ . We denote:

$$|q\rangle = \begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \alpha |0\rangle + \beta |1\rangle .$$

## Qubits

A qubit  $|q\rangle$  is a normalized vector of  $\mathbf{C}^2$ . We denote:

$$|q\rangle = \begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \alpha |0\rangle + \beta |1\rangle.$$

A qubits-string is called a **quantum register**.

## Qubits

A qubit  $|q\rangle$  is a normalized vector of  $\mathbf{C}^2$ . We denote:

$$|q\rangle = \begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \alpha |0\rangle + \beta |1\rangle .$$

A qubits-string is called a **quantum register**. It is mathematically described as the tensor product of these qubits, that is:


$$|q_1\rangle |q_2\rangle \cdots |q_n\rangle = \bigotimes_{j=1}^n |q_k\rangle .$$

## The Bloch sphere

A qubit  $|q\rangle$  can be represented on the so-called Bloch sphere:


## The Bloch sphere

A qubit  $|q\rangle$  can be represented on the so-called Bloch sphere:



# The Bloch sphere


A qubit  $|q\rangle$  can be represented on the so-called Bloch sphere:



**Figure:** The Bloch Sphere

# The Bloch sphere

A qubit  $|q\rangle$  can be represented on the so-called Bloch sphere:



**Figure:** The Bloch Sphere



# Quantum Computing principles

- Possibility to encode information with qubits-strings

# Quantum Computing principles

- Possibility to encode information with qubits-strings
- Linearity allows to apply operations on several qubits-string at a time

# Quantum Computing principles

- Possibility to encode information with qubits-strings
- Linearity allows to apply operations on several qubits-string at a time
- Possibility to get a probabilistic view of a qubit at the price of forcing it into a certain state.

# Quantum Computing principles

- Possibility to encode information with qubits-strings
- Linearity allows to apply operations on several qubits-string at a time
- Possibility to get a probabilistic view of a qubit at the price of forcing it into a certain state. **Measurement destroys information.**

# Implementing a Quantum Recommendation system

- The real-world implementation of the algorithm is quite straight-forward, except for:

# Implementing a Quantum Recommendation system

- The real-world implementation of the algorithm is quite straight-forward, except for:
  - Loading a vector stored in a classical structure as a quantum state

# Implementing a Quantum Recommendation system

- The real-world implementation of the algorithm is quite straight-forward, except for:
  - Loading a vector stored in a classical structure as a quantum state
  - Applying the Quantum Phase Estimation subroutine

# Implementing a Quantum Recommendation system

- The real-world implementation of the algorithm is quite straight-forward, except for:
  - Loading a vector stored in a classical structure as a quantum state
  - Applying the Quantum Phase Estimation subroutine
  - Comparing a qubits-string and a bits-string



# Implementing a Quantum Recommendation system

- The real-world implementation of the algorithm is quite straight-forward, except for:
  - Loading a vector stored in a classical structure as a quantum state
  - Applying the Quantum Phase Estimation subroutine
  - Comparing a qubits-string and a bits-string

## Loading a vector as a quantum state

### Loading a vector as a quantum state

Let  $\mathbf{x} \in \mathbf{R}^n$  be a normalized vector.

## Loading a vector as a quantum state

### Loading a vector as a quantum state

Let  $\mathbf{x} \in \mathbf{R}^n$  be a normalized vector. Then, its associated quantum state is:

$$|x\rangle = \sum_{j \in \{0; 1\}^{\lceil \log_2(n) \rceil}} \mathbf{x}_j |q\rangle .$$

## Loading a vector as a quantum state

### Loading a vector as a quantum state

Let  $\mathbf{x} \in \mathbf{R}^n$  be a normalized vector. Then, its associated quantum state is:

$$|x\rangle = \sum_{j \in \{0;1\}^{\lceil \log_2(n) \rceil}} \mathbf{x}_j |q\rangle .$$

Loading  $\mathbf{x}$  means creating  $|x\rangle$  from  $|0\rangle^{\otimes \lceil \log_2(n) \rceil}$  with a polylogarithmic number of gates<sup>4</sup>.

## QRAM<sup>5</sup>

A QRAM is a binary tree whose leaves stores the coefficients of a vector  $\mathbf{x}$  and whose nodes stores the sum of its leaves values.

## QRAM<sup>5</sup>


A QRAM is a binary tree whose leaves stores the coefficients of a vector  $\mathbf{x}$  and whose nodes stores the sum of its leaves values.

1

**Figure:** An example of a QRAM tree

## QRAM<sup>5</sup>


A QRAM is a binary tree whose leaves stores the coefficients of a vector  $\mathbf{x}$  and whose nodes stores the sum of its leaves values.



**Figure:** An example of a QRAM tree

## QRAM<sup>5</sup>

A QRAM is a binary tree whose leaves stores the coefficients of a vector  $\mathbf{x}$  and whose nodes stores the sum of its leaves values.



**Figure:** An example of a QRAM tree



## Loading from QRAM

- Method described in Dervovic et al., *Quantum linear systems algorithms: a primer*

## Loading from QRAM

- Method described in Dervovic et al., *Quantum linear systems algorithms: a primer*
- Uses  $2^k$  rotations gates around the  $y$ -axis at level  $k$  of the tree whose angle are determined using QRAM

## Loading from QRAM

- Method described in Dervovic et al., *Quantum linear systems algorithms: a primer*
- Uses  $2^k$  rotations gates around the  $y$ -axis at level  $k$  of the tree whose angle are determined using QRAM
- Goal: parallelize the execution of the rotations using superposition

## Parallel execution

### Parallel execution of controlled rotations

Let  $|x\rangle$  be a  $n$ -qubits quantum register and  $|0\rangle$  be a target qubit.

## Parallel execution

### Parallel execution of controlled rotations

Let  $|x\rangle$  be a  $n$ -qubits quantum register and  $|0\rangle$  be a target qubit. Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the  $y$ -axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$

## Parallel execution

### Parallel execution of controlled rotations

Let  $|x\rangle$  be a  $n$ -qubits quantum register and  $|0\rangle$  be a target qubit. Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the  $y$ -axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .

## Parallel execution

### Parallel execution of controlled rotations

Let  $|x\rangle$  be a  $n$ -qubits quantum register and  $|0\rangle$  be a target qubit. Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the  $y$ -axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .

### QRAM function assumption

It is possible, using QRAM, to design a gate  $\mathbf{L}_k$  such that:

$$\mathbf{L}_k |k\rangle |0\rangle^{\otimes t} = |k\rangle |\overline{\theta_k}\rangle$$

where  $\overline{\theta_k}$  is the best  $t$ -bits approximation of  $\theta_k$ .

## A simpler problem

### Parallel execution of rotations

It is possible to get the state  $|\theta\rangle e^{i\theta} |x\rangle$  from the state  $|\theta\rangle (\alpha |0\rangle + \beta |1\rangle)$



## A simpler problem

### Parallel execution of rotations

It is possible to get the state  $|\theta\rangle e^{i\theta} |x\rangle$  from the state  $|\theta\rangle (\alpha |0\rangle + \beta |1\rangle)$  in time  $O(1)$ .

## A simpler problem

### Parallel execution of rotations

It is possible to get the state  $|\theta\rangle e^{i\theta} |x\rangle$  from the state  $|\theta\rangle (\alpha |0\rangle + \beta |1\rangle)$  in time  $O(1)$ .

### The $z$ -rotation

Given an angle  $\theta$ , the rotation around the  $z$ -axis of the Bloch sphere is given by the gate:

$$\mathbf{R}_z(\theta) = \begin{pmatrix} 1 & 0 \\ 0 & e^{i\theta} \end{pmatrix}.$$

## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

$$|\theta_i\rangle \text{ --- } \boxed{\mathbf{R}_z\left(\frac{1}{2^k}\right)} \text{ --- } |\psi\rangle$$

**Figure:** Effect of the z-rotation on a qubit

## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

$$|\theta_i\rangle \text{ --- } \boxed{\mathbf{R}_z\left(\frac{1}{2^k}\right)} \text{ --- } |\psi\rangle$$

**Figure:** Effect of the z-rotation on a qubit

$$|\psi\rangle =$$

## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

$$|\theta_i\rangle \text{ --- } \boxed{\mathbf{R}_z\left(\frac{1}{2^k}\right)} \text{ --- } |\psi\rangle$$

**Figure:** Effect of the z-rotation on a qubit

$$|\psi\rangle = \begin{cases} |0\rangle & \text{if } \theta_i = 0 \end{cases}$$

## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

$$|\theta_i\rangle \longrightarrow \boxed{\mathbf{R}_z\left(\frac{1}{2^k}\right)} \longrightarrow |\psi\rangle$$

**Figure:** Effect of the z-rotation on a qubit

$$|\psi\rangle = \begin{cases} |0\rangle & \text{if } \theta_i = 0 \\ e^{i2^{-k}} |1\rangle & \text{if } \theta_i = 1 \end{cases}$$

## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

$$|\theta_i\rangle \longrightarrow \boxed{\mathbf{R}_z\left(\frac{1}{2^k}\right)} \longrightarrow |\psi\rangle$$

**Figure:** Effect of the z-rotation on a qubit

$$|\psi\rangle = \begin{cases} |0\rangle & \text{if } \theta_i = 0 \\ e^{i2^{-k}} |1\rangle & \text{if } \theta_i = 1 \end{cases} = e^{i\theta_i 2^{-k}} |\theta_i\rangle$$



## Parallel execution of rotations

Let  $\theta_i \in \{0; 1\}$ .

$$|\theta_i\rangle \longrightarrow \boxed{\mathbf{R}_z\left(\frac{1}{2^k}\right)} \longrightarrow |\psi\rangle$$

**Figure:** Effect of the z-rotation on a qubit


$$|\psi\rangle = \begin{cases} |0\rangle & \text{if } \theta_i = 0 \\ e^{i2^{-k}} |1\rangle & \text{if } \theta_i = 1 \end{cases} = e^{i\theta_i 2^{-k}} |\theta_i\rangle$$

## Parallel execution of rotations

$$\text{Let } \theta = \sum_{k=0}^{t-1} \theta_k 2^{-k}.$$

## Parallel execution of rotations


$$\text{Let } \theta = \sum_{k=0}^{t-1} \theta_k 2^{-k}.$$



**Figure:** Parallel execution of z-rotations

## Parallel execution of rotations

Let  $\theta = \sum_{k=0}^{t-1} \theta_k 2^{-k}$ .



**Figure:** Parallel execution of z-rotations

## Parallel execution of controlled $z$ -rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the  $y$ -axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the y-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Applying the z-rotation gates in the previous circuit applies a rotation on the target qubit around the z-axis of angle  $\theta_k$  in time  $O(1)$ .

## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the y-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Applying the z-rotation gates in the previous circuit applies a rotation on the target qubit around the z-axis of angle  $\theta_k$  in time  $O(1)$ .

## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the y-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Applying the z-rotation gates in the previous circuit applies a rotation on the target qubit around the z-axis of angle  $\theta_k$  in time  $O(1)$ .



## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the y-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Controlling the z-rotation gates on the target qubit in the previous circuit applies a rotation on the target qubit around the z-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time  $O(t)$ .

## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the y-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Controlling the z-rotation gates on the target qubit in the previous circuit applies a rotation on the target qubit around the z-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time  $O(t)$ .

## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation around the y-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Controlling the z-rotation gates on the target qubit in the previous circuit applies a rotation on the target qubit around the z-axis of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time  $O(t)$ .

## Parallel execution of controlled z-rotations

As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation **around the y-axis** of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Controlling the z-rotation gates on the target qubit in the previous circuit applies a rotation on the target qubit **around the z-axis** of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time  $O(t)$ .

## Parallel execution of controlled z-rotations


As a recall:

*Parallel execution of controlled rotations consists in applying on the target qubit a rotation **around the y-axis** of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time constant with respect to  $n$ .*

Controlling the z-rotation gates on the target qubit in the previous circuit applies a rotation on the target qubit **around the z-axis** of angle  $\theta_k$  only if the first quantum register is in state  $|k\rangle$  in time  $O(t)$ .

Is it possible to transform a y-rotation into a z-rotation of the same angle?


## Converting a $z$ -rotation to a $y$ -rotation



**Figure:** An example of a transformation of a  $y$ -rotation into a  $z$ -rotation

## Converting a $z$ -rotation to a $y$ -rotation


Rotate the sphere



**Figure:** An example of a transformation of a  $y$ -rotation into a  $z$ -rotation

## Converting a $z$ -rotation to a $y$ -rotation

Rotate the sphere



**Figure:** An example of a transformation of a  $y$ -rotation into a  $z$ -rotation







## Errata

- Patate

## Conclusion

- Patate

## References I

-  Dervovic, Danial et al. *Quantum linear systems algorithms: a primer*. 2018. arXiv: 1802.08227 [quant-ph].
-  Harrow, Aram W., Avinatan Hassidim, and Seth Lloyd. "Quantum Algorithm for Linear Systems of Equations". In: *Physical Review Letters* 103.15 (2009). ISSN: 1079-7114. DOI: 10.1103/physrevlett.103.150502. URL: <http://dx.doi.org/10.1103/PhysRevLett.103.150502>.
-  Kerenidis, Iordanis and Anupam Prakash. *Quantum Recommendation Systems*. 2016. arXiv: 1603.08675 [quant-ph].
-  Prakash, Anupam. "Quantum Algorithms for Linear Algebra and Machine Learning." PhD thesis. EECS Department, University of California, Berkeley, 2014. URL: <http://www2.eecs.berkeley.edu/Pubs/TechRpts/2014/EECS-2014-211.html>.