ALPHA MICROSYSTEMS
RIGHT. FROM THE START.

AlphaWRITE®
Reference Guide

DSM-00078-03

© 1996 Alpha Microsystems

REVISIONS INCORPORATED	
REVISION	DATE
00	15 March 1990
01	11 April 1991
02	21 May 1992
03	1 October 1992

AlphaWRITE Reference Guide
To re-order this document, request part number DSO-0078-00.

This document applies to AlphaWRITE version 2.1B

The information contained in this manual is believed to be accurate and reliable. However, no responsibility for the accuracy, completeness or use of this information is assumed by Alpha Microsystems.

This document was written by Sandra Tomlin, with editing assistance from Richard Spooner and David Pallmann.

This document may contain references to products covered under U.S. Patent Number 4,530,048.

The following are registered trademarks of Alpha Microsystems, Santa Ana, CA 92799:

AMIGOS	AMOS	Alpha Micro	AlphaACCOUNTING
AlphaBASIC	AlphaCALC	AlphaCOBOL	AlphaDDE
AlphaFORTRAN 77	AlphaLAN	AlphaLEDGER	AlphaMAIL
AlphaMATE	AlphaNET	AlphaPASCAL	AlphaRJE
AlphaWRITE	CASELODE	OmniBASIC	VER-A-TEL
VIDEOTRAX			

The following are trademarks of Alpha Microsystems, Santa Ana, CA 92799:

AlphaBASIC PLUS	AlphaVUE	AM-PC	AMTEC
AlphaDDE	AlphaConnect	DART	*in*Sight/am
*in*Front/am	ESP	MULTI	

All other copyrights and trademarks are the property of their respective holders.

ALPHA MICROSYSTEMS
2722 S. Fairview St.
P.O. Box 25059
Santa Ana, CA 92799

TABLE OF CONTENTS

LIST OF FIGURES..... xv

INTRODUCTION TO THE AlphaWRITE REFERENCE GUIDE.....xvii
WHAT IS A WORD PROCESSOR?..... xvii
AlphaWRITE WORD PROCESSING.....xvii
AlphaWRITE Is Easy to Learn..... xviii
Editing with AlphaWRITE.....xviii
AlphaWRITE's Complete Formatting..... xviii
THE AlphaWRITE ADVANTAGE.....xix
System Level Features.....xix
Publishing Features.....xx
Editing Features..... xx
YOUR AlphaWRITE DOCUMENTATION..... xxi
Conventions Used in This Reference Guide.....xxiii
The AlphaWRITE Documentation Library.....xxv
Special Note About Foreign Languages.....xxv
When You See Something You Don't Expect..... xxv

CHAPTER ONE - CALLING UP AND EXITING AlphaWRITE
CALLING UP AND EXITING AlphaWRITE.....1-1
Calling Up AlphaWRITE.....1-1
Exiting AlphaWRITE..... 1-2
HINTS FOR STARTING AlphaWRITE.....1-2
Using Command Type-Ahead.....1-2
HELP INFORMATION.....1-3
Displaying Help Information..... 1-3
Displaying Help from Command Screens 1-3
TYPE-AHEAD AND COMMAND ABBREVIATIONS.....1-3
Using Type-Ahead..... 1-3
Command Abbreviations.....1-4
MENUS AND SCREEN DISPLAYS: GETTING AROUND..... 1-5
Using Menu and Screen Displays.....1-5
Moving Around Command Screens..... 1-5
Getting Help Information..... 1-6
Using the Menu Key.....1-6
Using the Execute Key.....1-6
Using the Cancel Key..... 1-7
EMBEDDED TEXT SCREENS.....1-7
End-of-Document Characters..... 1-7
Embedded Displays: Message Text.....1-7
Exiting Embedded Text Screens..... 1-8
Interrupting Embedded Text Entry..... 1-8
Editing Features at Embedded Text Screens.....1-8
Editing an Embedded Text Entry.....1-8
Deleting An Embedded Text Entry..... 1-8
Copying and Moving Embedded Text Entries..... 1-8
Number of Lines Allowed..... 1-8
Size Restrictions..... 1-9

End of Paragraph Markers in Embedded Text..... 1-9
Block and Column Marks in Embedded Text..... 1-9
Some Editing Menu Commands Unavailable..... 1-10
Using Print Command from Embedded Screens.....1-10

CHAPTER TWO - CREATING, SAVING, AND EXITING DOCUMENTS
CREATING DOCUMENTS..... 2-1
Making a New Document.....2-1
If a "New" Document Name Already Exists.....2-2
HINTS FOR CREATING NEW DOCUMENTS.....2-2
Document Names..... 2-2
Prototype Documents..... 2-3
DEFDOC Prototype Document..... 2-3
Document Header.....2-4
DOCUMENT TEXT DISPLAY..... 2-4
Document Name and Description..... 2-4
The Text Area.....2-5
The Information Area..... 2-5
The Ruler Line.....2-6
The Margin Line..... 2-6
The Format Line..... 2-6
The Status Line..... 2-7
Information Block Messages.....2-7
Cursor Location..... 2-8
Messages..... 2-8
Insert and Overwrite Prompts..... 2-8
ENTERING TEXT..... 2-8
Moving the Cursor and Why It’s Important.....2-9
Wraparound..... 2-9
Editing Document Text..... 2-9
Overwrite..... 2-9
Erasing Characters.....2-10
Non-Printing Comments.....2-10
SAVING DOCUMENTS..... 2-11
EXITING DOCUMENTS..... 2-11
Exiting and Discarding Document Changes..... 2-11
Exiting and Keeping Your Document Changes.....2-11
SAMPLE DOCUMENTS.....2-12

CHAPTER THREE - MOVING AROUND AND EDITING TEXT
MOVING AROUND YOUR DOCUMENT.....3-1
Changing Screen Width..... 3-1
Moving the Screen Display..... 3-1
Moving the Cursor.....3-2
EDITING TEXT..... 3-3
Erasing Text..... 3-3
Deleting Text..... 3-3
Undo Previous Erase or Delete..... 3-3
Inserting Text.....3-4
Rearranging Text.....3-4
Using the Spacebar..... 3-5
MARKING TEXT.....3-5
Block Marks..... 3-5

Column Marks....3-6
Clearing Block or Column Marks.... 3-6
HINTS ON WORKING WITH MARKED TEXT.... 3-6
Clear Marks First....3-6
Marking Corners.... 3-6
Column Marks and the Spell Command.... 3-6

CHAPTER FOUR - SETTING MARGINS AND USING TABS
SETTING MARGINS AND TABS....4-1
Creating New Margins and Tabs....4-1
Changing an Existing Margin....4-3
Deleting an Existing Margin.... 4-4
HINTS FOR SETTING MARGINS AND TABS.... 4-4
Initial Format Settings Screen....4-4
Automatic Format on Margin Exit....4-4
Areas Affected by Margin....4-4
Clear Special Tabs....4-4
USING TABS AND INDENTING TEXT....4-4
Moving the Cursor to Next Tab Stop....4-4
Entering Indented Text....4-5
Indenting Existing Text....4-5
HINTS ON USING TABS AND INDENTING TEXT....4-5
Making A Column of Text....4-5
Collapsing Text....4-5
Collapsed Text Exercise....4-6
Double Indenting....4-7
Kinds of Tabs.... 4-7
Flush Left Tabs....4-7
Flush Right Tabs....4-7
Period Leader Tabs.... 4-8
Center Tabs....4-8
Decimal Tabs....4-8

CHAPTER FIVE - SETTING PAGE FORMAT AND FORMATTING TEXT
SETTING PAGE FORMAT....5-1
Format Settings....5-1
Getting to the Document Header Format Settings....5-1
Getting to the Margin Key's Format Settings.... 5-2
Default Format Settings.... 5-2
Units of Measurement....5-3
Laser Printer Page Format Considerations....5-4
Using the Preview Command.... 5-5
How Each Format Setting Affects the Printed Page.... 5-5
Document Header Fields and Format Settings....5-6
PAGE FORMAT FORMULA....5-12
UNIT OF MEASUREMENT CONVERSION TABLES....5-12
In Terms of One Inch....5-12
In Terms of One Point....5-12
In Terms of One Centimeter....5-12
In Terms of One Millimeter....5-12
In Terms of One Didot....5-12
In Terms of One Cicero....5-12
HINTS ON SETTING AND USING PAGE FORMAT....5-13

Formatting Your Document....5-13
Paginating and Format Settings....5-13
Kerning Methods....5-13
SAMPLE PAGE FORMATS....5-13
PAGE BREAKS....5-16
Paginating Your Document for Printing....5-17
Paginate's Soft Page Breaks....5-17
Forcing Hard Page Breaks....5-18
Using a Conditional Page Break....5-18
Deleting a Page Break....5-19
Moving Between Page Breaks....5-19
Page Counter....5-19
FORMATTING DOCUMENTS....5-19
Formatting A Paragraph....5-19
Formatting Text Between Margin Information Blocks....5-19
Formatting A Whole Document....5-20
Setting No Format for Whole Document....5-20
Setting No Format for Part of Your Document....5-20
Automatic Formatting....5-21
Discretionary Hyphens....5-21
HINTS FOR FORMATTING DOCUMENTS....5-21
Format Settings....5-21
Indent....5-21
Using the Paginate Command....5-22
Formatting and Discretionary Hyphens....5-22

CHAPTER SIX - PRINTING DOCUMENTS
PRINTING A DOCUMENT....6-1
Using the Print Command....6-1
HINTS FOR DOCUMENT PRINTING....6-3
Printers Available....6-3
Paginate Before Printing....6-3
The Printer Queue....6-3
Setting Page Breaks....6-3
Printed Page Numbers....6-3
PRINTING USING SHEET FEEDERS....6-4
Using Sheet Feeders....6-4
Selecting Specific Trays....6-4
Selecting the Tray Combination....6-4
HINTS FOR PRINTING WITH SHEET FEEDERS....6-5
Printing a Range Of Pages When Using Multiple Bins....6-5
WORKING WITH THE PRINTER QUEUE....6-5
Displaying the Printer's Queue....6-5
Removing a Document From the Printer's Queue....6-6
Choosing a Document to Print Next....6-6
Choosing a New Form Name for This Printer....6-6
Changing the Font Cartridge, Print Wheel or Thimble Setting....6-6
USING THE PREVIEW COMMAND....6-8
Using the PREVIEW Command....6-8

CHAPTER SEVEN - PRINTING FEATURES
SETTING TYPEFACE AND TYPESIZE....7-1
Setting or Changing Typeface on Laser Printers....7-1

Setting Typefaces on Impact Printers..... 7-2
Setting Typesize.....7-3
PRINTING PAGE OVERLAYS..... 7-3
Printing Page Overlays for only Part of A Document..... 7-4
Page Overlay Printed Appearance..... 7-5
USING SPECIAL PRINTING FEATURES..... 7-5
Using a Discretionary Hyphen..... 7-5
Underlining Text..... 7-5
Using Print Emphasis Features..... 7-6
Gray Shading..... 7-7
Using Keycap.....7-7
Printing One Character Over Another.....7-8
Selecting Ribbon Color..... 7-8
User Definable Features..... 7-9
Using a Required Space..... 7-9
Subscripting and Superscripting Text.....7-9
Using Special Print Characters.....7-10
Built-In Extended Characters.....7-11
Deleting Special Characters..... 7-12
Turning Off/On Information Block Display.....7-12
Composing Characters..... 7-12
Using AlphaWRITE's Compose Character Feature..... 7-13
Compose Character Chart..... 7-13
DRAWING BOXES AND LINES..... 7-18
What Are Element Numbers?..... 7-19
Drawing a Line.....7-19
Drawing a Box.....7-20
Setting Line Weight for Graphics..... 7-21
HINTS FOR USING GRAPHICS..... 7-22
Set Tabs.....7-22
Page Breaks and Graphics.....7-22
RESUME PRINT AT TOP OF PAGE..... 7-22

CHAPTER EIGHT - FOOTNOTES, TITLES, FOOTERS AND USING PAGE AND CHAPTER NUMBERS
MAKING FOOTNOTES..... 8-1
Creating a Footnote..... 8-1
Setting Footnote Options..... 8-2
HINTS FOR WORKING WITH FOOTNOTES..... 8-2
Footnotes and Paginate Command..... 8-2
Footnote Identifiers..... 8-2
Footnote Margin.....8-3
Footnotes are Embedded Text.....8-3
Previewing Footnote Text.....8-3
MAKING TITLES.....8-3
Creating a Title.....8-3
Setting Page Format for a Title..... 8-4
HINTS FOR WORKING WITH TITLES.....8-4
Page and Chapter Numbers..... 8-4
Even and Odd Titles.....8-5
Titles are Embedded Text..... 8-5
Title Word Wrap and Formatting..... 8-5
Title Margin..... 8-5

Typeface and Typesize..... 8-5
Previewing Title Text..... 8-5
Importing Images..... 8-5
MAKING FOOTERS..... 8-6
Creating a Footer..... 8-6
Footers are Embedded Text..... 8-6
Footer Word Wrap and Formatting..... 8-7
Setting Page Format for Footer..... 8-7
HINTS FOR WORKING WITH FOOTERS..... 8-7
Placement..... 8-7
Typeface and Typesize..... 8-7
Even and Odd Footers..... 8-7
Page and Chapter Numbers..... 8-8
Previewing Footer Text..... 8-8
Importing Images..... 8-8
WORKING WITH PAGE AND CHAPTER NUMBERS..... 8-8
Printing a Page Number..... 8-8
Pound Sign or Pound Sterling as Characters..... 8-8
Printing a Chapter Number..... 8-8
Making a New Chapter Page Break..... 8-9
Printing a Page and Chapter Number Together..... 8-9
Percent Sign as Character..... 8-9
Selecting Page and Chapter Number Style..... 8-9
Changing the Page Number to Specific Number..... 8-10
Changing the Chapter Number..... 8-11
Setting Non-Numeric Page References..... 8-12
HINTS FOR WORKING WITH PAGE AND CHAPTER NUMBERS..... 8-13
Command Placement..... 8-13
Default Page Number Format..... 8-13

CHAPTER NINE - CUT, PASTE, SEARCH, REPLACE, GLOBAL AND SPELL COMMANDS

COPYING TEXT BETWEEN DOCUMENTS..... 9-1
Cutting Text to Its Own Document..... 9-1
Pasting A Document Into This Document..... 9-2
HINTS FOR USING CUT AND PASTE..... 9-2
Cut and Its Temp Document..... 9-2
Cutting Text from a Password Protected Document..... 9-3
Paste and Its Input Document Named Temp..... 9-3
Paste and Eligible Input Document Names..... 9-3
Paste Command and Format Settings..... 9-4
FINDING AND REPLACING DOCUMENT TEXT..... 9-4
Using the Search Command..... 9-4
Using the Replace Command..... 9-5
Using the Global Command..... 9-5
HINTS FOR USING SEARCH, REPLACE AND GLOBAL COMMANDS..... 9-6
Formatting..... 9-6
Interrupt..... 9-6
Not Found..... 9-6
Capitalization..... 9-6
SPELL CHECKING YOUR DOCUMENT..... 9-7
Using Spell on Your Whole Document..... 9-7

Using Spell On Part of Document..... 9-7
HINTS FOR USING THE SPELL COMMAND.....9-8
Spell's Dictionaries.....9-8
Marking Procedure.....9-8
About Spell's Options.....9-8
Accept Word As Is Option..... 9-8
Edit The Line Option.....9-9
Accept Word And Remember It Option.....9-9
Insert The Word Into Personal Dictionary.....9-9
Displaying and Using A Dictionary List..... 9-9
Using the Dictionary Word List.....9-10
Moving Through the Display of Words:..... 9-10
Inserting a Dictionary Word:.....9-10
After Using the Spell Command.....9-10

CHAPTER TEN - USING DIRECTORY, ERASE, COPY AND RENAME COMMANDS
LIST OF DOCUMENTS.....10-1
Displaying Document List From Any Command Screen 10-1
The Directory Command.....10-2
Document Selection Criteria..... 10-3
Using WRTDIR From AMOS Command Level..... 10-4
HINTS FOR USING DIRECTORY.....10-5
Document Header and Directory Information..... 10-5
Alphabetic Order.....10-5
Directory List Sent to Printer as Disk Output Only.....10-5
ERASING DOCUMENTS.....10-5
Erasing a Document..... 10-5
What AlphaWRITE Erases From This Account..... 10-6
COPYING DOCUMENTS.....10-6
Copying a Document..... 10-6
HINTS FOR USING COPY COMMAND.....10-6
Copying a Document From Another Account..... 10-6
Copying a Document From Another Computer.....10-6
AlphaWRITE Understands Ersatz Names..... 10-7
RENAMING A DOCUMENT..... 10-7
Renaming a Document..... 10-7
HINTS FOR USING RENAME COMMAND.....10-7
Files AlphaWRITE Renames..... 10-7

CHAPTER ELEVEN - CHOOSING OPERATION SETTINGS AND SCREEN DISPLAY MODES
OPERATION SETTINGS.....11-1
Using the Mode Command..... 11-1
Fold Case During Search and Replace?..... 11-2
Menu Bypass?..... 11-2
Character Insert On?..... 11-3
Line Insert On?..... 11-3
Use Quick Dictionary?..... 11-3
Use Standard Dictionary?.....11-4
Use Professional Dictionary?.....11-4
Use Personal Dictionary?..... 11-4
Use Verb Dictionary?..... 11-4
Reformat For Best Output?.....11-5

Use Font Substitution?.....11-5
On-screen Attributes?.....11-5
Use Color?.....11-6
Use High and Low Intensity?.....11-6
Use Proportional Fonts?.....11-6
Perform Keystroke Journaling?.....11-6
Keystrokes Between Updates.....11-7
Maximum Journal Keystrokes.....11-7
HINTS FOR USING THE MODE COMMAND.....11-7
Default Settings.....11-7
SELECTING SCREEN DISPLAY OPTIONS.....11-8
Changing Column Text Display Width.....11-8
Displaying Underline & Bold As Screen Highlight.....11-8
Displaying AlphaWRITE in Color.....11-8
Using Proportional Display Fonts.....11-9

CHAPTER TWELVE - USING ADVANCED AlphaWRITE FEATURES
RECORD AND PLAYBACK.....12-1
Recording Keystrokes.....12-1
Erasing a Recording.....12-2
Playing Back a Recording.....12-2
HINTS FOR USING RECORD AND PLAYBACK.....12-2
Maximum Recording Length.....12-2
Record vs. Glossary.....12-3
CALENDAR.....12-3
HINTS FOR USING CALENDAR.....12-4
System Date.....12-4
MATH MODE.....12-4
Using Math Mode.....12-4
Totalling a Column or Row of Numbers.....12-5
HINTS FOR USING MATH MODE.....12-5
Remember to Clear the Accumulator.....12-5
Non-numeric Characters.....12-6
Numeric Characters.....12-6
OUTLINING.....12-6
Setting Outline Format.....12-6
Beginning an Outline In Your Document.....12-8
Moving In or Out An Outline Level.....12-8
Exiting Outline Mode.....12-8
Inserting One Outline in an Existing Outline.....12-8
Inserting Multiple Outline Items in An Existing Outline.....12-8
Moving an Existing Outline Item In or Out.....12-9
HINTS FOR USING OUTLINE MODE.....12-9
How Outlining Behaves.....12-9
Tabs and Outlining.....12-9
Automatic Outlining.....12-9
Exiting Automatic Outlining.....12-10
GLOSSARY.....12-10
Inserting a Glossary Entry Into Your Document.....12-10
Displaying Glossary Contents.....12-11
The Default Glossary: GLOSS.WRT.....12-11
Using A Glossary Document Other Than Gloss.....12-11

Creating A Glossary Document..... 12-11
Brackets as Text Characters.....12-12
Adding A Glossary Entry.....12-12
HINTS FOR USING GLOSSARY..... 12-13
Where You Can Use The Glossary Feature.....12-13
Using Universal Key Sequences for AlphaWRITE Features..... 12-13
Insert vs. Overwrite Mode When Using Glossary..... 12-13

CHAPTER THIRTEEN - USING SORT, INDEX, TOC AND MERGE COMMANDS
SORTING TEXT..... 13-1
HINTS FOR SORTING TEXT.....13-2
Sort Order..... 13-2
Text Used By Sort..... 13-2
Abandoning Sorted Text.....13-2
MAKING AN INDEX.....13-3
About A Book's Index.....13-3
Creating an Index Entry..... 13-3
Requesting an Index.....13-4
Using the Index Command..... 13-5
Using the Layout Key's Print Index Option.....13-5
HINTS FOR INDEXING YOUR DOCUMENT.....13-6
Index Entries are Embedded Text.....13-6
Index Entries and Their Corresponding Page Numbers..... 13-6
The Index Prototype Document..... 13-6
Index Entry Appearance in Your Index Output Document..... 13-6
MAKING A TABLE OF CONTENTS..... 13-7
About a Book's Table of Contents.....13-7
Creating a TOC Entry.....13-8
Requesting A Table of Contents..... 13-8
Using the TOC Command.....13-9
Using the Layout Key's Print TOC Option.....13-9
HINTS FOR MAKING A DOCUMENT TABLE OF CONTENTS..... 13-10
Table of Contents Entries Are Embedded Text..... 13-10
Table of Contents Entries and Their Page Numbers..... 13-10
The TOC Prototype Document.....13-10
Table of Contents Entry Appearance in Your Output Document.....13-10
MERGING DOCUMENTS.....13-10
Creating Your Template Document..... 13-11
Brackets as Text Characters.....13-12
Creating Your Data Document..... 13-12
Sample Data Document.....13-13
Using the Merge Command.....13-13
Using Merge Command Interactively.....13-14
HINTS FOR MERGING DOCUMENTS..... 13-15
Before Using the Merge Command..... 13-15
About Your Output Document..... 13-15
Sample Output Document.....13-15

CHAPTER FOURTEEN - USING JOURNAL FILES; USING POSTSCRIPT PROGRAMS AND IMPORTING FILES
JOURNAL FILES AND RECOVERY PROCEDURES.....14-1

Recovering an AlphaWRITE Document....14-2
When the Journal File is Full....14-3
DOCUMENTS AND FILES AlphaWRITE CREATES....14-4
IMPORTING FILES TO YOUR DOCUMENT....14-5
Importing an AlphaCALC Worksheet....14-5
Importing an Image File....14-6
Import Image File Handling....14-7
Using the Import Image Feature....14-7
To Import Image File Now:....14-7
To Import Image File at Print Time:....14-7
Image Files and Document Size....14-8
Image File Name Display....14-8
USING POSTSCRIPT WITH AlphaWRITE....14-8
Encapsulated PostScript File Format....14-9
Creating a PostScript Embedded Program....14-9
Getting a Print Out of Your PostScript Program....14-10
Sample PostScript Program....14-10
How AlphaWRITE Processes PostScript Blocks....14-10
Absolute and Relative Positioning....14-11
Important Note About Direct ASCII Codes....14-12
Recommended Reading....14-12
Writing Postscript Programs To Use As .IMG Files....14-12

CHAPTER FIFTEEN - AlphaWRITE'S DICTIONARIES
THE DICTIONARIES AlphaWRITE USES DURING SPELL....15-1
Spell Command's Dictionary Search Path....15-1
Short Dictionary....15-1
Quick Dictionary....15-2
Standard Dictionary....15-2
Verb Dictionary....15-2
Professional Dictionary....15-2
Local Dictionary....15-2
Dictionaries and the Mode Command....15-2
The Short Dictionary - SHORT.DCT....15-3
The Random House Dictionary - SMALL.DCT....15-3
The Main Random House Dictionary - SPELL.DCT....15-4
The Verb Dictionary - VERB.DCT....15-4
The Professional Dictionary....15-4
The Dictionary Created By Spell - LOCAL.DCT....15-5
CREATING A PROFESSIONAL DICTIONARY....15-5
The Source File....15-6
LOCAL.DCT As Source for Professional Dictionary....15-6
Sorting the Source File....15-7
Building the Professional Dictionary....15-7
Including the Professional Dictionary in the Initialization File....15-8

CHAPTER SIXTEEN - AlphaWRITE'S DOCUMENT SECURITY
AlphaWRITE PROTECTION SCHEMES....16-1
WHAT IS ENCRYPTION?....16-1
STANDARD PASSWORD PROTECTION....16-2
ENCRYPTED PASSWORD PROTECTION....16-2

APPENDIX A - UNIVERSAL KEY SEQUENCES.....A-1
WHAT IS AN ALTERNATE KEY SEQUENCE?.....A-1
UPPER OR LOWER CASE?.....A-1
USING THE CONTROL KEY.....A-1
USING THE ESCAPE KEY.....A-1
If You Don't Have An Escape Key.....A-1
HOW TO USE THE TABLE.....A-2

APPENDIX B - FONT SUBSTITUTION CHARTS-
FONT SUBSTITUTION: TURNING OFF AND ON.....B-1
HOW TO USE THE FONT SUBSTITUTION CHARTS.....B-1
FONT SUBSTITUTION FOR POSTSCRIPT PRINTERS.....B-2
FONT SUBSTITUTION FOR HEWLETT-PACKARD LASERJET SERIES PRINTERS.....B-3
FONT AVAILABILITY ON HEWLETT-PACKARD PRINTERS.....B-3
THIRD-PARTY FONT NAMES.....B-4

APPENDIX C - AlphaWRITE'S DEFAULT SETTINGS

APPENDIX D - ERROR MESSAGES

APPENDIX E - SUPPORTED PRINTER FEATURES

APPENDIX F - POSTSCRIPT SAMPLE FONT FAMILIES
POSTSCRIPT FONT FAMILIES.....F-1
Dingbats and Symbol Typefaces.....F-2
Dingbats Typeface.....F-3
Symbol Typeface.....F-5

APPENDIX G - CONVERTING FILES TO AlphaWRITE WITH AWCONV
AWCONV: DIFFERENCES BETWEEN VERSIONS.....G-1
When To Use AWCONV.....G-1
Help Information for AWCONV.....G-1
CONVERTING DOCUMENTS INTO AlphaWRITE 2.x FORMAT.....G-2
CONVERTING AlphaWRITE 2.x DOCUMENTS TO OTHER FORMATS.....G-3
WORDPERFECT TO AlphaWRITE CONVERSION.....G-4
AlphaWRITE to WORDPERFECT CONVERSIONS.....G-7
SUPERVUE TO AlphaWRITE CONVERSION.....G-8

APPENDIX H - AlphaWRITE'S INITIALIZATION FILE
WHAT DOES AlphaWRITE'S INITIALIZATION FILE DO?.....H-1
CREATING AN AlphaWRITE INITIALIZATION FILE.....H-1
The Name of the Initialization File.....H-2
Location of the Initialization File.....H-2
AlphaWRITE's Search Path for Its Initialization File.....H-2
Comment Characters.....H-3
INITIALIZATION FILE COMMANDS.....H-3
CHARINSERT COMMAND.....H-4
COLOR.....H-4
DICTIONARY.....H-5
DICTIONARYTWO.....H-6
DIRECTORYSIZE.....H-6

DISPLAYATTRIBUTE....H-6
FONT....H-7
FONTCARTRIDGE....H-7
INTENSITY....H-8
JOURNAL....H-9
JOURNALSIZE....H-9
KEYSTROKES....H-9
LINEINSERT....H-9
MENUBYPASS....H-10
The Mode Command and Menu Bypass....H-11
MODEM....H-11
PALETTE....H-11
PRINTER....H-12
PROPORTIONAL....H-12
REFORMAT....H-12
SEARCHFOLD....H-13
SUBSTITUTE....H-13
WIDOW....H-14
WIDTH....H-14
DEFAULT SETTINGS....H-14
AlphaWRITE INITIALIZATION FILE ACCOMPANYING YOUR SOFTWARE....H-15
AlphaWRITE WRITE.NEW Initialization File....H-16
THE INITIALIZATION FILE PRINTER COMMAND....H-17
Printer Name....H-18
Driver Name....H-18
Symbolic Name....H-19
Print Wheel....H-19
Printer Settings....H-21
Sheet Feeder....H-21
CPU Identification....H-22
A Note About Commas....H-22
Default Printers....H-23
Printing To A Terminal's Printer Port....H-23
AlphaWRITE PRINTER DRIVERS....H-23
Entering Direct ASCII Codes for Your Printer....H-23

APPENDIX I - USER DEFINED FUNCTIONS
ADDING NEW PRINT FEATURES....I-1
CHANGING THE LIST OF SUPPORTED FONTS....I-2
About the Font Table....I-3
(1): Font Logical Name Field....I-3
(2): Cartridge Field....I-3
(3): Font Physical Name....I-3
(4): Font Flags....I-3
(5): Font Table Field....I-4
(6): Font Size Field....I-4
(7): Leading Field....I-4
(8): Characters Per Inch Field....I-4
Printer Driver Font Table Sample....I-4
Font Table Sample from LASJET.M68....I-5

APPENDIX J - HP LASER PRINTING

TYPES OF HEWLETT-PACKARD LASER PRINTERS.....J-1
Look-Alike Printers.....J-1
HP LASER PRINTERS USING A POSTSCRIPT FONT CARTRIDGE..... J-1
DEFINING THE LASERJET PRINTER TO AlphaWRITE.....J-2
LASERJET FONTS.....J-2
Resident Fonts..... J-3
Font Cartridges..... J-3
Matching AlphaWRITE's Expected Character Spacing.....J-4
Purchase HP Font cartridges That AlphaWRITE Supports.....J-4
Soft Fonts.....J-5
Font Selection.....J-5
Font Size Selection.....J-5
Bold & Italic Fonts.....J-6
Orientation.....J-6
Font Width Tables..... J-7
TEACHING AlphaWRITE ABOUT NEW FONTS.....J-7

APPENDIX K - EMBEDDED TEXT HANDLING
HOW AlphaWRITE HANDLES LARGE DOCUMENTS.....K-1
HOW AlphaWRITE HANDLES EMBEDDED TEXT AREAS.....K-1
MAXIMUM SIZE OF AN EMBEDDED TEXT AREA.....K-1
DIFFERENCES IN AlphaWRITE'S EMBEDDED TEXT DLING.....K-2
GUIDELINES FOR AVOIDING MEMORY PROBLEMS.....K-3
Use Import At Print Time..... K-3
Avoid Large Embedded Text Areas.....K-3

APPENDIX L - SPECIFICATIONS

APPENDIX M - SPECIAL CHARACTER KEY: OPTION E - EXTENDED CHARACTER
USING AN EXTENDED CHARACTER.....M-1
EXTENDED CHARACTER SYMBOLS AND CODES..... M-2
ABOUT THE CHARTS.....M-2
Dingbats Typeface Extended Characters..... M-3
Symbol Typeface Extended Characters.....M-6
EXTENDED CHARACTER CODES AVAILABLE..... M-9
ACCESSING ISO LATIN 1 CHARACTERS VIA EXTENDED
CHARACTER.....M-9

APPENDIX N - FONT WIDTH TABLES
HEWLETT-PACKARD LASERJET SERIES.....N-1
LASERJET III AND IIID SCALABLE TYPEFACES..... N-4
POSTSCRIPT PRINTERS..... N-5

APPENDIX O - AlphaWRITE SEARCH PATHS
TYPES OF SEARCH PATHS.....O-1
Your Log Account Search Path..... O-1
Standard Search Path.....O-1
Image File Search Path.....O-2
Worksheet Search Path..... O-2
SEARCH PATHS FOR COMMANDS AND FEATURES..... O-2
Search Path For Copy Command.....O-2
Search Path For Create Command.....O-3
Search Path For Cut Command.....O-3

Search Path For Edit Command.....O-3
Search Path For Erase Command.....O-3
Search Path For Glossary Command.....O-3
Search Path For Import AlphaCALC Worksheet (At Print Time).....O-3
Search Path For Import AlphaCALC Worksheet (Now).....O-3
Search Path For Import Image File (At Print Time).....O-4
Search Path For Import Image File (Now).....O-4
Search Path For Index Command.....O-4
Search Path For Merge Command.....O-4
Search Path For Paste Command.....O-4
Search Path For Print Command.....O-4
Search Path For Rename Command.....O-5
Search Path For Toc Command.....O-5

APPENDIX P - ISO LATIN-1 CHARACTERS AND LASER PRINTING
POSTSCRIPT LASER PRINTING AND 8-BIT CHARACTERS.....P-1
ABOUT THE CHART.....P-1

DOCUMENT HISTORY

INDEX

READERS' COMMENTS

INTRODUCTION TO THE AlphaWRITE REFERENCE GUIDE

Any word processor does what a typewriter does—lets you put your words to paper. The difference is the way your words get there—via computer. Computerized word processing has many advantages; for instance, you can revise text you type without ever having to re-type entire pages, quickly rearrange paragraphs and large sections of text, duplicate entire pages without re-typing, and much more.

AlphaWRITE is Alpha Microsystems' word processing software and in this introduction you find out why AlphaWRITE is an especially convenient and powerful software tool.

WHAT IS A WORD PROCESSOR?

A word processor helps you organize and manage what you write. Word processors, including AlphaWRITE, don't do anything you can't already do with a typewriter—that is, if you want to spend all of your time typing, cutting and pasting, proofing, retyping, duplicating and filing what you write. These jobs, and many others which may be laborious and time consuming for you, are performed in seconds by your computer and word processor.

AlphaWRITE, Alpha Microsystems' word processor, offers all the basics of word processing and many more sophisticated time saving features—leaving you free to concentrate on the content and presentation of what you write rather than the mechanics of getting it to paper.

AlphaWRITE WORD PROCESSING

Whether you're writing a one page business letter, a multi-column financial report, or a 1000 page manual, AlphaWRITE makes your job fast, easy, and efficient. In fact, this *AlphaWRITE Reference Guide* was written using AlphaWRITE software exclusively.

Don't have time to check for typos? AlphaWRITE can do it for you. Wish you could avoid tedious text formatting? Let AlphaWRITE handle it. AlphaWRITE does it all... and does it better.

AlphaWRITE Is Easy to Learn

AlphaWRITE is easy to learn and very quickly you can learn to create, edit and print your first document.

With AlphaWRITE there's no need to spend weeks memorizing cryptic and complicated word processing commands. AlphaWRITE menus display a list of main operations; you choose the one you want by entering the option's name from the list. Single keystrokes perform most editing operations and on-line help screens explain features at your request.

What's more, you never have to exit AlphaWRITE to perform operations on your documents. Everything you need to work on your documents is available from within AlphaWRITE, so you don't have to switch back and forth between command level and the software.

Editing with AlphaWRITE

When it comes to editing, AlphaWRITE has the features you need to prepare documents quickly and accurately.

AlphaWRITE speeds editing with rapid cursor movement. You can move the cursor anywhere on a line, anywhere on a page, anywhere in your document. You can then insert, delete, or move characters, words, lines, or entire sections of your text.

AlphaWRITE speeds proofreading. Using its multiple dictionaries, it automatically checks for misspellings, typographic and capitalization errors. You can even add your own technical terms, proper names and other words to a dictionary. When AlphaWRITE finds an error, the word is highlighted on your screen—in context, so you can make changes efficiently.

Other AlphaWRITE features help you save the time you might spend scanning through pages of text to find a specific character, word or phrase. Just tell AlphaWRITE what you want to look for, and each occurrence appears on your screen. AlphaWRITE can also automatically replace groups of words or numbers with other text—you tell AlphaWRITE what to look for and what to replace it with and it does the rest!

AlphaWRITE can do your retyping too. You can copy or move any section of text, any size, to anywhere in the same document or any other document. If your documents have common text, AlphaWRITE can store and insert it for you. You only have to type the text once.

Last minute corrections and revisions are never a problem. You can make any change from inserting a character to adding blocks of text, without retyping your entire document.

AlphaWRITE's Complete Formatting

Some word processors tell you how to format your documents and only show what your document looks like after you print it. With AlphaWRITE, you're in control.

For each document, you decide how long a single line should be, how many lines on a page, if and where page numbers should appear.

You decide between proportional and fixed printing styles and whether your text has an evenly aligned or ragged right margin. You can change margins and tab settings whenever you want, and your document text adjusts on the screen automatically.

You can choose any type of line spacing—single, single and half, double, double and half, triple or whatever you need.

AlphaWRITE's formatting capabilities include "smart paging" to break pages so single lines of text aren't stranded at the top or bottom of a document page.

You can tell AlphaWRITE to underline text, print bold face text, and include titles and footer text on your document pages. AlphaWRITE can even put text in outline form, generating numbers and letters and indenting your text automatically.

In short, you decide exactly how you want your document to look and let AlphaWRITE do the work.

THE AlphaWRITE ADVANTAGE

While you can start using AlphaWRITE in a matter of minutes, it has so many powerful features, and so many ways to combine them, that you can create sophisticated type-set quality output.

The next sections summarizes AlphaWRITE's features, divided between these major groups:

- System Level Features
- Publishing Features
- Editing Features

System Level Features

Some AlphaWRITE system level features are:

- Ersatz location for AlphaWRITE program files to free up space on DSK0:.
- AWCONV utility allowing for batch conversions, and conversion for WordPerfect documents and Sony Series 35 word processing files. More thorough conversions now take place for TXTFMT and SuperVUE format files.
- Foreign language support.
- Mode terminal support.
- On-screen color support.
- Keystroke journaling to ensure preservation of your work between saves.
- Built-in laser printing features for HP LaserJet II and IID, Apple LaserWriter printers, or any PostScript compatible printer.
- Increase in maximum number of printers from 8 to 32.

Publishing Features

AlphaWRITE features which let you create near-typeset quality documents include:

- Index capabilities.
- Chapter numbering features.
- Titles and footers allow multiple lines of text.
- Use titles and footers on all pages, only on even or odd numbered pages, or any combination.
- Center lines of text between margins in one keystroke.
- Determine hyphenation for words at the end of a line.
- **PAGINATE** processes for the printer you select.
- Graphics to draw boxes and lines on laser printers.
- Multiple fonts and sizes on laser printers.
- Reverse, screened and gray text on laser printers.
- Multiple units of measurement supported: lines, characters, metric, inches, points, didots, and ciceros.
- Special characters: keycap: KEYCAP, star: ★, bullet: ●, em dash: —, en dash: –, degree: °, paragraph: ¶, dagger: †, section: §, cent: ¢, quarter: ¼, half: ½, trademark: ™, copyright: ©, registered: ®.
- Support for laser printer fonts' extended character set.
- Document header format settings such as leading, format text, kerning, page orientation.
- **MERGE** lets you choose between including or excluding automatically generated page breaks in your output document. Other mail-merge features: Data field maximum length of 8,192, variable name length of 64 characters, and up to 128 variable names.
- Type footnote text and have AlphaWRITE keep track of the right place to print it.
- Print or display a complete list of your documents, or just some documents.
- Display a list of document names any time you are asked to enter a document name.
- Print all or only a few pages of your document.
- Monitor the progress of documents being printed.
- Cancel print requests.
- Move any print request forward, to print sooner.

Editing Features

To make AlphaWRITE more flexible and easier to use for entering and editing text, these editing features will come in handy:

- See your text automatically wrap around from the end of one line to the next line, saving you the trouble of pressing return.
- Reformat paragraphs of text with one keystroke, or one command.
- Insert the current date or time using a few keystrokes.
- Perform arithmetic calculations with numbers in your document.
- Display a calendar for any month between 1900 and 2155.
- Alphabetize text.
- Perform editing operations on columns.
- Quickly reverse the case of an entire word.
- Easily reverse a transposition error.
- Choose from 5 numbering schemes for printed page numbers.
- Choose from two password protection schemes to secure your document for

privileged use.
- Use mail merge operations to customize letters and forms.
- Undelete previous character, word or line with [CANCEL].
- Record and playback your keystrokes.
- Enhancements to glossary: on-line addition of glossary entries supported from all command screens, and default entries for current file, user name, current disk and account.
- Next and Previous match for **SEARCH** command.
- Restart print at top of page (laser printers only).
- Margin ruler in inches.
- Import feature lets you include image files and AlphaCALC worksheets in your document.
- **PREVIEW** displays your formatted document.
- Direct PostScript programming from your document.

YOUR AlphaWRITE DOCUMENTATION

The *AlphaWRITE Reference Guide* has two major divisions: Chapters and Appendices. A summary is shown below.

Chapter 1 - Calling Up and Exiting AlphaWRITE: describes how to use the **WRITE** command, return to AMOS command level, and some aspects of working with AlphaWRITE's screens.

Chapter 2 - Creating, Saving and Exiting Documents: gives you the ins and outs of using **CREATE** to make a new document, using **SAVE** to keep your changes and how to exit a document when you are through.

Chapter 3 - Moving Around and Editing Text: lists the keys you can use to move around in AlphaWRITE documents and keys you use to make changes to your text.

Chapter 4 - Setting Margins and Using Tabs: steps you through using [MARGIN] to set margins and tabs and then how to use them.

Chapter 5 - Setting Page Format and Formatting Text: the Document Header fields and [MARGIN] Format Screen fields are described completely in this chapter. You will also find information on using the **FORMAT** command and [FORMAT] key here.

Chapter 6 - Printing Documents: **PRINT** and its many options are discussed in this chapter.

Chapter 7 - Printing Features: AlphaWRITE has many print features affecting how characters appear on the printed page and each is discussed in this chapter.

Chapter 8 - Using Page Numbers, Footnotes, Titles and Footers: describes page number styles available, how to make footnotes and create titles and footers in your document.

Chapter 9 - Using Copy, Search, Replace, Global and Spell Commands: gives you instructions for using these commands on your documents.

Chapter 10 - Using Directory, Erase, Copy and Rename Commands: describes commands that use existing documents. It introduces you to **DIRECTORY** which gives you a list of your documents, and shows you how to erase, duplicate and rename documents.

Chapter 11 - Choosing Operation Settings and Screen Display Modes: discusses features and commands that let you change how AlphaWRITE behaves.

Chapter 12 - Using Advanced AlphaWRITE Features: covers recording and playing back keystrokes, the calendar feature, math mode, outlining and the glossary feature.

Chapter 13 - Using Sort, Index, Toc, and Merge Commands: describes how to alphabetize document text, make an index and table of contents for your document, and how to create data and template documents to use with AlphaWRITE's mail-merge feature.

Chapter 14 - Using Journaling, Importing Files and Using PostScript: gives you information on how AlphaWRITE's journaling feature works, files you can import into your document text and how to use the PostScript programming feature.

Chapter 15 - AlphaWRITE's Dictionaries: lists the dictionaries AlphaWRITE uses and how you can work with them.

Chapter 16 - AlphaWRITE's Document Security: discusses the protection methods available to secure documents from unwanted use.

Appendix A - Universal Key Sequences: contains a table listing all of the keys you use to work with AlphaWRITE and the key sequences available for use on many terminals.

Appendix B - Font Substitution Charts: shows the typefaces AlphaWRITE will substitute for an unavailable typeface during laser printing.

Appendix C - Default Command Settings: lists the default settings for AlphaWRITE's commands and features.

Appendix D - Error Messages: gives you a complete list of AlphaWRITE's error messages, why they occur and what you can do to correct the situation.

Appendix E - Printer Features: provides a chart listing each of AlphaWRITE's printing features and their availability on a range of printers.

Appendix F - Sample Font Families: illustrates typeface styles available on PostScript laser printers.

Appendix G - Converting Files to AlphaWRITE With AWCONV: gives you complete instructions on using the AWCONV utility to convert non-AlphaWRITE and older AlphaWRITE documents to the current AlphaWRITE version.
Appendix H - AlphaWRITE's Initialization File: describes all the commands supported in the initialization file. An important section in this appendix describes how to define a printer to AlphaWRITE.

Appendix I - User Defined Functions: gives you instructions for making use of AlphaWRITE's user defined functions available through the [LAYOUT] key.

Appendix J - HP Laser Printing: describes using AlphaWRITE and printing on HP laser printers.

Appendix K - Embedded Text Handling: contains information on AlphaWRITE's memory handling of embedded text.

Appendix L - Specifications: is a complete list of AlphaWRITE's features and their characteristics.

Appendix M - Special Character Key Option E: Extended Character: gives you instructions and illustrates the special printing symbols available to you through the [SPEC CHAR] key's option E for extended characters.

Appendix N - Font Width Tables: provides a listing of the font width table names and the printers to which they apply.

Appendix O - AlphaWRITE's Search Paths: discusses the path AlphaWRITE follows to find documents and files it needs during its operation.

Appendix P - ISO Latin I Characters and Laser Printing: gives character availability for PostScript and HP laser printers.

Chapter and Appendix text is divided into sections so you can find information easily. There are, at most, three levels of division: Major section titles and secondary headings begin at the left margin. Major titles are in bold type all capitals; secondary headings are in bold type initial capitals; subordinate headings are underlined.

Conventions Used in This Reference Guide

In order to make this document as easy as possible to understand, we use several conventions in layout and type style, so you can recognize whether we are talking about a command or key, when you're to type an entry, and so on.

CONVENTION	EXPLANATION
COMMAND	AlphaWRITE command names are shown in all capitals, bold type in a smaller point size than main text.
COMMAND	AMOS command names and some AlphaWRITE file names, such as DEFDOC.WRT, are shown in all capitals, non-bold type and in the same point size as main text.

CONVENTION	EXPLANATION
AlphaWRITE Main Menu	AlphaWRITE screen names are printed like the example: no bold, initial capitals.
`What You Type`	Text you are expected to type is shown in a bold Courier typeface.
`What AlphaWRITE Displays`	Text AlphaWRITE displays as prompts, messages or responses to what you type is shown in a non-bold Courier typeface.
KEY	Keys you need to press to use AlphaWRITE are shown in a keycap box. Characters inside the box are either function key names, such as BLOCK COPY; symbols, such as ↑; or key names such as TAB or RETURN.
CTRL KEY	Indicates a control-key sequence to use a particular AlphaWRITE feature, such as CTRL Y to delete text to end of line. (See Appendix A for complete operating instructions.)
ESC KEY	Indicates an escape-key sequence to use a particular AlphaWRITE feature, such as ESC @ to mark a column. (See Appendix A for complete operating instructions.)
	The halt symbol denotes an important piece of information you should read carefully before continuing. Usually, text next to this symbol contains instructions for something you MUST or MUST NOT do, so read carefully.
	The hint symbol denotes a helpful bit of information. It is often used to point out a short cut which may save you time or trouble.
	The remember symbol denotes information you need to keep in mind while you are following a set of instructions.

The AlphaWRITE Documentation Library

The *AlphaWRITE Reference Guide* is just one part of the AlphaWRITE Documentation Library, the other documents are:

- The *AlphaWRITE Release Notes* - this document describes enhancements or changes in the current version of AlphaWRITE from the last version.

- The *AlphaWRITE Installation Instructions*, DSO-00151-00 - provides complete instructions for installing the AlphaWRITE software on your computer.
- *AlphaWRITE Programmer's Information* - DSO-00076-00 provides technical information for accessing AlphaWRITE's command line processing from application programs and other topics of interest to programmers.

- *AlphaWRITE Keyboard Commands Reference Card* - DSS-10316-00

If you want to order another AlphaWRITE Documentation Library and receive the slip case and binder along with the documentation, please use part number PDB-00004-03.

Special Note About Foreign Languages

AlphaWRITE's messages, prompts and screen displays can be altered and translated to other languages. However, throughout this *AlphaWRITE Reference Guide*, we assume AlphaWRITE is being used in its released form with United States English messages and responses.

Therefore, your version of AlphaWRITE may be only slightly modified to reflect changes in these areas:

- Date format: This book shows all dates using the format MM/DD/YY—month, day, year. Use whatever date format is correct for your language.

- Yes and No Responses: The correct responses to yes/no prompts may be set to something other than the English Y and N.

In either case, talk with your System Operator who can let you know what changes, if any, have been made.

When You See Something You Don't Expect

You and AlphaWRITE are in constant communication with one another. As you enter commands or instructions it responds by doing what you ask. And, you know all is well when AlphaWRITE responds to your requests just as you expect, as it is documented in this book.

From time to time though, AlphaWRITE may not respond by proceeding with your request. When this happens AlphaWRITE lets you know by sending you a message. Some messages just tell you what AlphaWRITE is doing at the moment so you know everything is working well. Other messages inform you about an improper response to a question AlphaWRITE asks you. Still other messages tell you about potential problems with AlphaWRITE or your computer.

If you ever see a message and aren’t quite sure what to do next, you can quickly look it up in Appendix D - "Error Messages." This appendix lists the messages AlphaWRITE displays, tells you when and why you might see the message, and also gives you instructions on how to proceed.

CHAPTER ONE
CALLING UP AND EXITING AlphaWRITE

Chapter One contains information on:

- Starting and Leaving AlphaWRITE
- Help Information
- Menus and Screen Displays: Getting Around
- Embedded Text Screens

CALLING UP AND EXITING AlphaWRITE

You use the **WRITE** command from AMOS command level to call up AlphaWRITE. The **WRITE** command uses instructions in AlphaWRITE's initialization file to determine the operation settings to use.

Some Alpha Micro computers are customized and display a menu rather than the AMOS command prompt. When this is the case, you can usually choose AlphaWRITE from a list of software shown on the menu.

When you use **QUIT** to exit AlphaWRITE, your screen returns to where you were when you first called up AlphaWRITE.

Calling Up AlphaWRITE

To call up AlphaWRITE, from AMOS command level:

WRITE [RETURN]

The Main Menu, shown in the following illustration, appears on your screen and from here you can make new documents or access existing ones.

```
alphaWrite

AlphaWRITE WORD PROCESSING SYSTEM VERSION 2.0(103)

Monday, February 12, 1990 05:41:02 PM

HELP   - display help information     COPY      - make a copy of a document
                                      ERASE     - erase a document
CREATE - create a new document        RENAME    - rename a document
EDIT   - edit an existing document    DIRECTORY - display list of documents

MERGE  - combine two documents        MODE      - change operating parameters
PRINT  - send document to printer
QUEUE  - printer queue maintenance    QUIT      - return to AMOS command level

Enter command name and press RETURN: ▮
```

AlphaWRITE Main Menu

If this is the first time AlphaWRITE has ever been called up on your computer, the first screen you see is an installation screen. Let your System Operator know if this happens; the AlphaWRITE software requires a product installation code before you can proceed.

Exiting AlphaWRITE

To exit AlphaWRITE, and return to where you were when you first started, from the Main Menu type:

QUIT RETURN

HINTS FOR STARTING AlphaWRITE

Using Command Type-Ahead

You can use an existing document's name along with **WRITE** and immediately begin an edit session with it:

WRITE docnam RETURN

Other command options are available with **WRITE**; please see the *AlphaWRITE Programming Information Manual* for more information.

HELP INFORMATION

Displaying Help Information

Help topics for all of AlphaWRITE's features are available from Text Display and from the Main and Editing Menu. The help topics you can choose from depend on where you are when you request help.

To request the help topic list for the area of AlphaWRITE you are currently working in:

1. From either the Main or Editing Menu type **HELP** [RETURN], or press [HELP].

   From Text Display, press [HELP].

2. From the Help Topics screen display, type the number associated with the topic you want to see information about and press [RETURN].

3. Use [NEXT SCREEN] and [PREV SCREEN] to move forward and backward through help screens.

4. To exit, press [MENU] and return to where you were when you requested the help topic list.

Displaying Help from Command Screens

You can display help information about the particular command you are working with by pressing [HELP] at that command screen.

On some command screens, such as the one you see during **MODE** or **HEADER**, you can display mini-help about a particular field. To do so:

1. Position the cursor in the field you want help information about.

2. Press [HELP]. Mini-help text appears at the bottom of your screen.

3. If you want to see the more general help information for this particular command, press [HELP] again.

4. Press [MENU] to return to your command screen display.

TYPE-AHEAD AND COMMAND ABBREVIATIONS

Using Type-Ahead

From the Main and Editing Menu you can type command information in shorthand AlphaWRITE will understand as command type-ahead.

For example, you can type a document name to **EDIT** directly at the command line of the Main Menu—without first displaying the Edit Command Screen.

For example, you can type:

`EDIT docnam` RETURN

where **`docnam`** represents your document name. Command type-ahead is available for all the menu commands: you type the command name first, press the spacebar, type your response to that command's first prompt and then press RETURN.

Type-ahead saves time when you are using Menubypass mode and have the full display of the Editing Menu turned off. It does require, however, that you be familiar with AlphaWRITE's commands and the responses it expects from you.

Command Abbreviations

All of AlphaWRITE's commands can be abbreviated at the Main Menu and Editing Menu command lines.

For most commands, the fewest characters making it unique are the acceptable abbreviations.

MENU	COMMAND	ABBREV.
Main	Directory	D
Main	Copy	Co
Main	Create	C
Main	Edit	E
Main	Erase	Er
Main	Help	H
Main	Merge	M
Main	Mode	Mo
Main	Print	P
Main	Queue	Que
Main	Quit	Q
Main	Rename	R
Editing	Cut	C
Editing	Directory	D
Editing	Finish	F
Editing	Format	Fo
Editing	Global	G
Editing	Glossary	Glos
Editing	Header	H
Editing	Help	Hel
Editing	Index	I
Editing	Mode	M
Editing	Outline	O
Editing	Paginate	Pa
Editing	Paste	Pas

MENU	COMMAND	ABBREV.
Editing	Preview	Pre
Editing	Print	P
Editing	Queue	Que
Editing	Quit	Q
Editing	Replace	R
Editing	Save	Sa
Editing	Search	S
Editing	Sort	So
Editing	Spell	Sp
Editing	Toc	T
Editing	Width	W

MENUS AND SCREEN DISPLAYS: GETTING AROUND

Using Menu and Screen Displays

All of AlphaWRITE's menu and command screens display instructions on how to proceed near the bottom of the screen. This part of the display is reserved on all command screens to show various actions you can take. For example:

- What options may be available. For example:

```
[ Press UP ARROW or DOWN ARROW to scroll directory ]
```

- When you need to press [EXECUTE] and/or [RETURN] after responding to a prompt or field.

```
Enter command name and press RETURN:

[ Press EXECUTE to begin printing ]
```

- It tells how to exit the command screen, which is frequently by pressing [MENU] or [CANCEL].

```
[ Press MENU or CANCEL to leave this screen ]
```

On menus, the display shows the commands available along with a synopsis of each one's purpose.

Moving Around Command Screens

AlphaWRITE lets you move between fields on a screen such as the Document Header or the AlphaWRITE Print command screen with these keys:

[↑] [↓] [←] [→] [RETURN]

Generally, you can change your response to a particular prompt at a command screen after you've made an entry there. To do so:

1. Return the cursor to that field with the arrow keys, or by repeatedly pressing [RETURN]—depending on what you are prompted for. At prompts for document names, use [RETURN] because the up and down arrows display a directory list.

2. Retype your entry and press [RETURN].

Once you press [EXECUTE] to process a command you won't be able to change a prompt response but will be able to halt the command with [CANCEL].

Getting Help Information

You can display help information from all of AlphaWRITE's screens by pressing [HELP]. (See *Help Information* for complete details on how the help feature operates.)

One nice help feature is available from the **MODE** and **HEADER** command screens. From any field on these screens:

1. Press [HELP] once to display abbreviated operating tips for that field

2. Press [HELP] again to display help information applicable to the whole command.

Using the Menu Key

[MENU] is an important key and you use it to:

- Return to the Main Menu from any Main Menu command screen.
- Interrupt any command not yet finished and return to where you were before starting the command.
- From document text display, causes the Editing Menu to appear.
- From the Editing Menu, returns you to document text display.
- Interrupts any feature begun by using a key sequence at document text display.

Using the Execute Key

You use [EXECUTE] on all command screens to signal AlphaWRITE to go ahead with that command.

When you enter a response to a command screen field or prompt, you type your response and press [RETURN]. Once all answers are satisfactory, press [EXECUTE].

[EXECUTE] is used throughout AlphaWRITE to signal that you are through with a command and want AlphaWRITE to proceed and process it.

Using the Cancel Key

[CANCEL] is used throughout AlphaWRITE, except at Text Display, to abandon the current AlphaWRITE operation. From text display, [CANCEL] is used as an undo key to retrieve the most previous delete. See Chapter 3 from complete operation details on the undo feature.

EMBEDDED TEXT SCREENS

Embedded text screens are displayed whenever you use any of the options from [EMBED].

Other than the specific differences described below, embedded text screens behave and are used in the same ways as document text display. You use the same special or function keys to move the cursor, work with text, or type as you do from Text Display.

The screens you see when you select any [EMBED] option function with few differences from standard Text Display. The differences to keep in mind are described below.

End-of-Document Characters

The embedded screen end-of-document characters are not `*****` but rather:

```
&&&&&
```

These ampersands are a quick visual signal so you know you are working at an embedded screen and not your main document Text Display.

Embedded Displays: Message Text

On the bottom left side of embedded displays you see a message indicating the kind of embedded text you are working with now. The messages are:

```
Title                  TOC
Odd Title              Index entry
Even Title             PostScript
Footer                 Footnote
Even Footer            Page Overlay
Odd Footer             Collapsed Text
```

These messages also appear at Text Display when the cursor is positioned on the embedded text's information block.

Exiting Embedded Text Screens

You exit embedded text screens by pressing [EMBED] or [EXECUTE].

Interrupting Embedded Text Entry

If you begin embedded text entry inadvertently, or want to return to your document's Text Display from the embedded text screen, press [EMBED] or [EXECUTE].

Editing Features at Embedded Text Screens

You can use AlphaWRITE's editing features at the embedded text screen—such as moving, copying or deleting text, special print features, outlining, math mode, glossary entries, and so on. However, certain Editing Menu commands are not available (see below) and you cannot nest an embedded text entry within an embedded text entry.

Editing an Embedded Text Entry

You can edit any embedded text screen by positioning the cursor on the information block associated with that embedded text entry and press [EMBED].

Deleting An Embedded Text Entry

Embedded text information blocks are not protected like the [MARGIN] key's information block. Consequently, you can very easily delete any embedded text entry, regardless of the amount of text it holds.

To delete an embedded text entry, from Text Display:

1. Position the cursor on the embedded text information block.
2. Press [CHAR DEL].

Embedded text entry information blocks will also be deleted if they are held within a marked section of text and you use [BLOCK DEL].

Copying and Moving Embedded Text Entries

You copy embedded text entries by including its information block within a marked area of text and using [BLOCK COPY] or [ESC] [M] to move the marked text.

Number of Lines Allowed

Each kind of embedded screen allows a certain number of lines. They are shown in the following table.

EMBEDDED SCREEN	NUMBER OF LINES	RESTRICTIONS/ HINTS
Title, Odd Title, Even Title, Footer, Even Footer, & Odd Footer	Multiple	No word-wrap or text formatting available. All print features available.
Index entry	Two	Printable text characters only; SPEC CHAR symbols (bullet, star, etc.) are unavailable; print features (bold, italic, etc.) are ignored.
Toc	One	All print features available.
PostScript	Multiple	Two uses: as PostScript program when first two characters are %!; direct printer commands when numbers separated by spaces or commas. All document text display features available.
Footnote	Multiple	All document text display features available.
Page Overlay	One	Text characters only; no special print, formatting, or text alignment features.
Collapsed Text	One	Special print, text alignment features allowed, SPEC CHAR symbols honored.

Size Restrictions

Embedded text blocks allowing multiple lines also allow you to **PASTE** files into them. However, the maximum size of these embedded text blocks is restricted to 16K (32 blocks). File(s) you attempt to **PASTE** that cause an embedded text block to exceed this limit will provoke an error message.

End of Paragraph Markers in Embedded Text

As with your document text, pressing RETURN to signal the end of a paragraph affects the printed appearance of the text. Use RETURN at the end of single lines, or at the end of a paragraph, so AlphaWRITE will properly control this text's format.

Block and Column Marks in Embedded Text

When you arrive at any embedded text screen, block or column marks present in your document text are cleared—just as if you pressed BLOCK CLEAR. The same is true when you return to document text display: any block or column marks you make at embedded text are automatically cleared.

Some Editing Menu Commands Unavailable

Although you can display the Editing Menu by pressing MENU from an embedded command screen, not all Editing Menu commands are available. These commands are specifically not available:

FINISH	**PAGINATE**	**QUIT**	**SORT**
INDEX	**PREVIEW**	**SAVE**	**TOC**

When executed from Document Text Display's version of the Editing Menu, these commands do take into account the embedded text.

Using Print Command from Embedded Screens

Using **PRINT** from any embedded command screen sends the text of the embedded screen to the printer. This is especially helpful for getting a printed version of lengthy footnotes, or PostScript program code held as embedded text.

CHAPTER TWO
CREATING, SAVING, AND EXITING DOCUMENTS

Chapter Two contains information about:

- Creating Documents
- Saving Documents
- Exiting Documents
- Sample documents

CREATING DOCUMENTS

Making A New Document

CREATE lets you make a new document with a unique name in the account where you called up AlphaWRITE .

To make a new AlphaWRITE document, from the Main Menu:

1. Type **CREATE** [RETURN].

2. At the Enter Document Name prompt, type a document name of 6 or less alphanumeric characters and press [RETURN]. For example:

   DOCNAM [RETURN]

   Use the [↑] or [↓] to display a list of document names currently in use.

3. At the Prototype Document Name prompt, you can either use the prototype document DEFDOC, or type a different prototype document name and press [RETURN].

   If it is protected, you'll be asked to enter its password. Type the password and press [RETURN].

You can use an AlphaWRITE document from this account as a prototype document name, or from any account on your computer that you normally have access to, or from a computer available to you over a network.

You can enter a maximum number of 36 characters to this prompt.

4. To continue press [EXECUTE].

5. At the Document Header screen, type information as you choose in the fields on the description area of this screen. Press [RETURN] to move through fields.

   See Chapter 5 -"Setting Page Format" for more information about using the fields shown on the Document Header.

   Press [EXECUTE] to continue from the Document Header.

6. At Text Display, type the text of your document.

   Chapters 3 and 4 will be helpful if you are new to working at Text Display; they discuss how to move around in your document and how to set margins and tabs.

7. From Text Display, use [MENU] to display the Editing Menu. From here you can **SAVE** the contents of your document and continue working on it; **FINISH** from this document which saves its text and returns you to the Main Menu where you started.

8. From the Main Menu you can call up the document you just created with **EDIT**.

If A "New" Document Name Already Exists

If the document name you type at **CREATE**'s Enter a Document Name prompt already exists, you can choose from the following actions:

- Type a different new document name. Check the directory list to see what names are in use.

- **EDIT** the existing document. To do this, press [NEXT SCREEN] and you get the Edit Existing Document Screen. Then, press [EXECUTE] to call up the existing document name you specified.

HINTS FOR CREATING NEW DOCUMENTS

Document Names

AlphaWRITE document names are six or less alphanumeric characters belonging to the ASCII character set.

Prototype Documents

The prototype document name prompt gives you a quick way to copy an existing document into the one you **CREATE** now. Supplying a prototype document name is mandatory and the default prototype document name is DEFDOC.

Using a prototype document copies that document's format settings and text into the new document; making them the same except for their document names.

You can supply a document name from the account where you are currently logged, or use a full file specification to use a document from another account or device. For example:

DSK1:LETTER[153,4]

Only AlphaWRITE documents can be used as a prototype document.

DEFDOC Prototype Document

The default prototype document is DEFDOC. This document comes with AlphaWRITE and holds all the default settings for the Document Header. DEFDOC can be edited and hold format settings you use most frequently. The Document Header format settings for DEFDOC are shown in the next illustration.

```
                         AlphaWRITE DOCUMENT HEADER

Description
Author                        Operator                        Department
Protection - (N, P or PE) N
                                     FORMAT
Leading ...................... 6        Left Paper Offset ............ 1"
Page Length .................. 11"      Right Justify - (Y or N) ..... N
Top Margin ................... 0.5"     Characters Per Inch (pitch) .. 10
Title Length ................. 0.5"     Word Spacing - (F, V or P) ... P
Text Length .................. 9"       Line Spacing (half lines) .... 2
Space Before Footnotes ....... 0.5"     Footnote Print Type - (B or E) B
Footer Length ................ 0.5"     Footnote Line Separator ...... _
Printer Form Name ............ NORMAL   Kerning (N, Light, Med, Tight) N
Allow Format of Text (Y or N)  Y        Orientation - (P or L) ....... P

Created: 15-Jun-88 08:57           STATISTICS       Keystrokes/Minute:     0
Revised: 13-Feb-90 09:31     Times Revised:  12     Total Time Open:   00:00
Printed:                     Times Printed:   0     Total Keystrokes:    445

    UNITS     [ Press UP ARROW or DOWN ARROW to select fields ]     UNITS
 "  = inches   [ Press HELP for information about this field ]  pts = points
 cm = metric      [ Press EXECUTE or MENU to update header ]    ci  = ciceros
 mm = metric      [ Press CANCEL to forget header changes ]     di  = didots
```

Document Header for DEFDOC.WRT

To be used, DEFDOC must be present in either the account where you are using AlphaWRITE or in WRT:. AlphaWRITE automatically looks for DEFDOC first in the account where you are logged then in the project account ([,0]), and finally in WRT:.

Document Header

The Document Header screen you see when you first **CREATE** a document can be accessed whenever you are at Text Display by using the Editing Menu's **HEADER** command.

DOCUMENT TEXT DISPLAY

When you exit the Document Header after using the **CREATE** command, or after you complete the procedures for the **EDIT** command, your screen displays the beginning of your document text, as shown below.

Name and Description

Text Area

Information Area

```
_ LETTER  Business Letter                                                  _
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
*****
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-
<   L    L    L    L    L    L    L    L    L    L    L    L    >
Font C 10  Frmt Y  Orient P  Text 9"  Lpo 1"  Cpi 10  Just N  Wspc P Lspc 2
          Pag 1   Lin 1    Col 1                 Line Ovr  Char Ins
```

Document Text Display

The display itself is divided into either two or three sections, depending on the type of terminal you are using:

- Name and description of your document, appearing on the top line of only certain terminals.
- Text area occupying the middle of your screen.
- Information area at the bottom of the screen.

Each area of your screen is described in the next sections.

Document Name and Description

Your document's name and description appears on the top line of the display if your terminal is capable of displaying it. Terminals with this capability include Alpha Micro's AM-6x and AM-7x family and many others.

On terminals not capable of displaying this top line, the text area starts at the very top of the screen.

The Text Area

The text of your document occupies most of the screen and appears between the name and description line if present and the information area at the bottom.

The exact number of lines and columns visible at one time varies from terminal to terminal. Remember, this may be only a small portion of your document.

Each line can be up to 255 columns long, and the number of lines is virtually unlimited, depending only on the storage capacity of your computer.

When you first **CREATE** a document without using a prototype containing text, each line in the text area begins with five asterisks:

```
*****
```

The asterisks indicate the current end of your document. As you enter text, the document expands and the asterisks move down the screen. These asterisks always follow the last line of your document.

The Information Area

The information area occupies the bottom four lines of your screen and looks like this:

```
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-....
<   L    L    L    L    L    L    L    L    L    L    L    L    >
Font C 10  Frmt Y  Orient P  Text 9"   Lpo 1"   Cpi 10  Just N  Wspc P  Lspc 2
                    Pag 1   Lin 1    Col 1                Line Ovr  Char Ins
```

The information area shows you:

- The number of columns and positions on the Ruler Line.
- Margins and tabs currently set on the Margin Line.
- Your document's page format settings on the Format Line.
- The cursor's current page, line and column position along with other information on the Status Line.

Each of these lines is described in more detail in the next sections.

The Ruler Line

The first line in the information area is a column ruler:

```
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-....
```

Each column represents one tenth of an inch and is marked with a period, a dash, or a number:

- A period represents one tenth of an inch.
- A dash indicates the fifth column of a ten column interval and is an increment of a half inch.
- Numbers indicate ten column intervals in inches. Only one digit is used to represent the column number. For example, a 2 indicates column 20 or 120, a 3 means 30 or 130, etc.

The Margin Line

The Margin Ruler is directly beneath the Ruler Line and shows you where margins and tabs are currently set:

```
<   L   L   L   L   L   L   L   L   L   L   L   L   >
```

The table below shows the symbols that may appear on this line:

SYMBOL	MEANING	DEFDOC DEFAULT
<	Left Margin Setting	Column 1
>	Right Margin Setting	Column 65
L	Flush Left Tab	Every 5 columns - ½"
R	Flush Right Tab	None
P	Period Leader Tab	None
C	Centered Tab	None
D	Decimal Tab	None

When you **CREATE** a new document, the margins are preset set at columns 1 and 65 with flush left tab stops set every five columns. You can change any of these settings with [MARGIN], see Chapter 4 for more information.

The Format Line

The third line of the information area is the Format Line and displays the page format settings for this portion of your document, as set either in the Document Header or using the [MARGIN] key:

```
Font C 10  Frmt Y  Orient P  Text 9"   Lpo 1"   Cpi 10  Just N  Wspc P  Lspc 2
```

The following table shows the abbreviation, meaning and default setting for the format line. See Chapter 5 form more information on format settings.

ABBRV.	MEANING	DEFAULT†
Font	Typeface	C 10
Frmt	Format	Y
Orient	Page Orientation	P(ortrait)
Text	Text Length	9.5"
Lpo	Left paper offset	1"
Cpi	Characters per inch	10
Just	Justify	N
Wspc	Word spacing	P
Lspc	Line spacing	2

† These are DEFDOC.WRT's defaults.

The Status Line

The bottom line of the screen is the Status Line and can be further divided into four areas:

- Information block messages
- Cursor location information
- Messages
- Insert and overwrite prompts

The illustration below shows you where each of the four areas appear on the status line.

```
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-....
<   L    L    L    L    L    L    L    L    L    L    L    L    >
Font C 10  Frmt Y  Orient P  Text 9"   Lpo 1"   Cpi 10  Just N  Wspc P  Lspc 2
Bold                Pag 1   Lin 1    Col 1   Not Found     Line Ovr  Char Ins

INFORMATION BLOCK       CURSOR LOCATION        MESSAGES      INSERT/OVERWRITE
     MESSAGES                                                    PROMPTS
```

Text Display Status Line

Information Block Messages

Information blocks appear in your text when you use some of AlphaWRITE's special features, such as different printer fonts or the MARGIN key. In the text, information blocks appear as checkerboard-type blocks:

When you position the cursor on any information block, the block's meaning displays on the far left side of the Status Line. A message also appears here if the cursor is positioned on an underscore character, indicating the beginning or end of underlined text.

Cursor Location

The cursor's position in your document appears in terms of page, line and column at the right of the information block message area.

Messages

The area immediately to the right of the cursor location information is reserved for the information and error messages AlphaWRITE displays. The messages appearing in this area are discussed under their corresponding features.

Insert and Overwrite Prompts

The insert and overwrite prompts appear at the far right side of the status line. Two messages appear here indicating whether or not you are in line or character insert mode.

The first message may say either "Line Ovr", when you have line overwrite mode engaged, or "Line Ins" if you have line insert mode engaged.

The second message may say one of three things: "Char Ins" when character insert is engaged, "Char Ovr" when character overwrite is engaged, or "Word Ins" when word insert is engaged.

AlphaWRITE's line, character, and word insert modes are discussed in Chapter 3

ENTERING TEXT

When you first use CREATE to make a new document and reach document text display, the cursor is located in column 1, line 1 of page 1—at the upper left of the text area, ready for you to type in your text. From this point, you can use AlphaWRITE just like a typewriter, with a few important exceptions.

The next sections describe what makes AlphaWRITE different from using a typewriter:

- Moving the cursor and why it's important
- Wraparound
- Editing document text
- Non-printing comments

Moving the Cursor and Why It's Important

The cursor is a visible reference point, to always let you know exactly where you are working on your screen. As you begin to type your text, the cursor keeps one step ahead of what you are typing and shows you where you've left off. The cursor also lets you communicate with AlphaWRITE; telling it exactly where you want something done. Putting the cursor in position is the first step in using many of AlphaWRITE's features.

You need to be able to move the cursor by other means than typing text. And the simplest way to move the cursor around your document is to use the [ARROW] keys. The [ARROW] keys move the cursor in the direction of the arrow.

The [ARROW] keys all repeat—if you hold one of them down the cursor continues to move in that direction. Notice when the cursor moves over existing text, it doesn't change the text at all.

There are many other ways to move the cursor around in your document, some of them much faster than the [ARROW] keys. They are discussed in Chapter 3.

Wraparound

Another advantage over a typewriter is how your text wraps around to the next line of text as you finish the first—you don't have to press [RETURN] to get to the next line.

When you reach the right margin column of your page, shown on the margin and tabs ruler, the cursor automatically moves to the beginning of the next line. If you are in the middle of a word at the time, the whole word shifts to the next line too.

This "wrapping around" of text lets you type without worrying about how close you are to the end of a line, because AlphaWRITE makes sure no words get split at the right margin. The only time you use [RETURN] while entering text are at the ends of paragraphs and on blank lines.

Editing Document Text

These next paragraphs describe a few ways for you to make simple changes as you go along in your document. You can find information for all the ways you can correct or change existing text in Chapter 3.

Overwrite

The easiest way to change text in AlphaWRITE is to just type over it.

When you notice an error, or anything you want to change, move the cursor to the proper place using the **ARROW** keys, and type in the correct characters. As you type, the new characters replace the old ones.

This method works when you are in overwrite mode, not insert mode. You can tell quickly what mode you are currently in by looking at the status line of your text display. When both the prompts at the far right of the line say Ovr you are in overwrite mode.

Erasing Characters

To erase characters you don't want, position the cursor on the first character and press the spacebar. The cursor moves one space to the right each time you press it, erasing as it goes. If you hold the spacebar down, it repeats.

If both prompts on the status line indicate you are working in character insert mode, the characters you type, or spaces if you press the spacebar, are inserted within your text.

You can also erase characters with the RUBOUT key, erasing from the current cursor position to the left along the line. Pressing the RUBOUT key moves the cursor back one space, and erases the character at the space the cursor moves to.

Non-Printing Comments

At times, you may want to include text in your document for display only and *not* have it show when you **PRINT** the document. You may want to leave a note to yourself to check or add some information, add comments on how you've edited the document or other information.

You can include non-printing text in your document using AlphaWRITE's comment embedded command. To add a non-printing comment to your text:

- Move the cursor to the first column of the line where you want to add the comment.
- Type two slashes: `//`
- Type the text you want as comment text.

The two slashes are the key to entering comment text. AlphaWRITE does **not** print any line, or use instructions on any line, which begin with two slashes.

When you have more than one comment line, be sure to begin each comment line with two slashes in the first two columns. For example, the following lines are comment text and would be ignored at time of printing if the slashes were in the first two columns:

```
//  These lines only appear when you display your
//  AlphaWRITE document-- as long as they begin with
//  two slashes, they will never print.
```

AlphaWRITE treats comment text differently than regular text. These differences are:

- Comment text does not "wrap around" when you reach the right margin. You must press RETURN to go to the next line.

- Comment text is not affected by formatting in your document, whether with the [FORMAT] key or any other feature.

SAVING DOCUMENTS

SAVE stores, in permanent memory, the changes you made to the document you are currently editing without leaving it. To use this command, from Text Display:

1. Press [MENU].
2. At the Editing Menu type **SAVE** [RETURN].

Whenever you use **SAVE**, AlphaWRITE writes the contents of your document to disk and also clears the journal file. See Chapter 14 for more information on journal files.

It's a good idea to use **SAVE** periodically whenever you are working with a document.

EXITING DOCUMENTS

Exiting and Discarding Document Changes

You can leave your document and discard any changes you have made. To do so, from Text Display:

1. Press [MENU].
2. At the Editing Menu type **QUIT** [RETURN].
3. At the prompt asking you to confirm that you want to quit, type **YES** [RETURN] to proceed. If you choose not to quit now, press [CANCEL].

   If you made no changes in this document, the confirmation prompt does not appear and you return to the Main Menu.

This command instructs AlphaWRITE to leave the document you are currently editing with no update and returns the display to the Main Menu.

QUIT is useful for leaving a document when you have made no updates to it in this editing session, or have made changes you do not want to keep.

Exiting and Keeping Your Document Changes

You can leave your document and retain any changes you have made. To do so, from your Text Display:

1. Press [MENU].

2. At the Editing Menu type **FINISH** RETURN.

FINISH stores your document, with all changes you made in this editing session, in permanent memory and then returns your display to the Main Menu.

SAMPLE DOCUMENTS

AlphaWRITE comes with sample documents that you can use as prototypes; they can be found in WRT: The table below give you their names and a description of their contents.

DOCUMENT NAME	DESCRIPTION
DEFDOC.WRT	AlphaWRITE's default prototype document.
FAX.WRT	Sample fax form.
MEMO.WRT	Sample memo form.
ENV.WRT	Sample envelope document containing format settings to print business envelopes.
TOC.WRT	AlphaWRITE's default table of contents template document.
INDEX.WRT	AlphaWRITE's default index template document.
LAND.WRT	Like DEFDOC, except header format settings are defined for landscape orientation for laser printing.
LEGAL.WRT	Like DEFDOC, except header format settings are defined for printing legal size paper.

CHAPTER THREE
MOVING AROUND AND EDITING TEXT

Chapter Three contains information about:

- Moving Around Your Document
- Editing Text
- Marking Text

MOVING AROUND YOUR DOCUMENT

Changing Screen Width

The Editing Menu **WIDTH** command lets you switch between 80- and 132-column display on your terminal. It only affects Text Display; not menu displays. Not all terminals have dual column-width support.

To switch column display width, from the Editing Menu:

1. Type **WIDTH** [RETURN].

Use **WIDTH** again to return to the column display you were previously using.

Moving the Screen Display

There are many ways to move the cursor to other screens of your AlphaWRITE document. The next sections describe the ones you use to move the cursor and shift from one screen to another.

TO:	PRESS:
Position current line mid-screen	[CENTER SCREEN]
Move screen left	[SCREEN LEFT]

TO:	PRESS:
Move screen right	[SCREEN RIGHT]
Move up	[PREV SCREEN]
Move down	[NEXT SCREEN]
Move to next page break	[SHIFT] [NEXT SCREEN]
Move to previous page break	[SHIFT] [PREV SCREEN]
Move to specific page	[PAGE] At Enter Code prompt, type **2** to select Go To Page. At Enter Page Number prompt, type page number and press [RETURN].
Scan through document	[SCAN] Use [SPACEBAR] to halt, type **S** to go slower, **F** to go faster.

Moving the Cursor

TO MOVE CURSOR:	PRESS:
Left	[←]
Right	[→]
Up	[↑]
Down	[↓]
To beginning of line	[SHIFT] [←]
To end of line	[SHIFT] [→]
To beginning of document	[HOME]
To end of document	[SHIFT] [HOME]
To next word	[NEXT WORD]
To previous word	[PREV WORD]

Moving the Cursor (continued)

TO MOVE CURSOR:	PRESS:
To next sentence	SHIFT NEXT WORD
To previous sentence	SHIFT PREV WORD

EDITING TEXT

Erasing Text

TO ERASE	POSITION CURSOR AND PRESS:
Characters and move cursor to left	RUBOUT
From cursor to end of line	CTRL Y

Deleting Text

TO DELETE	POSITION CURSOR AND PRESS:
A character	CHAR DEL
A line	LINE DEL
A word	WORD DEL
A block of text	Mark text block, press BLOCK DEL
A column of text	Mark text column, press BLOCK DEL

Undo Previous Erase or Delete

You can undo the last character, word or line you erased or deleted by pressing CANCEL. All characters removed will be returned to your document except for information blocks created with the EMBED key, or by the import feature (ESC /).

Undo cannot restore any block or column delete operations to your document's text.

To use undo:

1. Position the cursor where you want the deleted text to be returned.
2. Press [CANCEL].

The undo feature remembers the most recently removed text until you erase or delete other text, or exit AlphaWRITE. Consequently, you can "undo" the last text you erased or deleted more than once.

Inserting Text

TO INSERT	POSITION CURSOR AT INSERT POINT AND PRESS:
A character	[CHAR INS]
Multiple characters (character insert mode)	[AUTO INS CHAR] and type text, or press [SPACEBAR] to insert blanks, then type text. Press [AUTO INS CHAR] again and return to overwrite mode.
A word (word insert mode)	[WORD INS] and type word. When done, press [SPACEBAR] or [RETURN].
A line	[LINE INS]
Multiple lines (line insert mode)	[AUTO INS LINE] and type text, or press [RETURN] to insert blank lines, then type text. Press [AUTO INS LINE] again to return to overwrite mode.

Rearranging Text

TO	DO THIS:
Reverse two characters	Position cursor on first character and press [REVERSE CHAR].
Change capitalization	Position cursor on first character and press [REVERSE CASE].
Center a line	Position cursor on line and press [CENTER LINE]. Do not use tabs within the text line being centered; AlphaWRITE cannot intermix these two features on one line.

Rearranging Text (continued)

TO	DO THIS:
Break a Line	Position cursor where you want to split line and press [LINE INS].
Join Two lines	With cursor on top line, press [SHIFT] [↑].
Copy text block or column	Mark text. Move cursor to insert point and press [BLOCK COPY].
Move text block or column	Mark text. Move cursor to new location and press [ESC] [M].

Using the Spacebar

You press the spacebar "key" after typing a word, or a sentence to create blank space in your text. The printed width of this blank space depends on the typeface and type size you have currently set with the [STYLE] key.

Your terminal cannot *display* a blank space that is the same width as the *printed* result which is determined by the current typeface and type size. Therefore, using blank spaces, i.e. the spacebar, to position text at a particular column is an unreliable method and will probably not result in printed alignment.

For consistent and accurate results, use tab settings and [TAB] to position text in particular columns.

MARKING TEXT

Block Marks

Block mark operations let you select whole or partial lines of document text for use with [BLOCK COPY], [BLOCK DELETE] and block move ([ESC] [M]) operations.

Additionally, some AlphaWRITE commands can perform procedures using marked areas of your document. The commands with this feature are **SPELL**, **SEARCH**, **GLOBAL** and **REPLACE**. The **CUT** command also relies on marked text.

To mark sections of text, from Text Display:

1. Position cursor where you want mark to begin and press [BLOCK MARK].
2. Move cursor to end of text to mark and press [BLOCK MARK] again.

3. The text between the marks is highlighted on your screen and is ready to be used by the feature you've chosen.

4. Be sure to use [BLOCK CLEAR] to remove the marks when you are through.

Column Marks

Column marks let you select vertical sections of your document text to use with [BLOCK COPY], [BLOCK DELETE] and block move operations. Column marked portions of text are required by **SORT** and understood by the **CUT** command.

To mark a column of text:

1. At Text Display, position cursor at the top left corner of text and press [ESC] [@].

2. Move the cursor to bottom right corner of text and press [ESC] [@] again.

3. The text between the marks is highlighted on your screen and is ready to be used by the feature you've chosen.

4. Be sure to use [BLOCK CLEAR] to remove the marks when you are through.

Clearing Block or Column Marks

At Text Display, press [BLOCK CLEAR] to clear marked text.

HINTS ON WORKING WITH MARKED TEXT

Clear Marks First

Use clear operations to remove any existing marks from your document before marking any new section.

Marking Corners

Columns are identified when you use [ESC] [@] on the **upper left** and **lower right** section of text. AlphaWRITE does not understand a column of text marked by using the upper right and lower left corners.

Column Marks and the Spell Command

The **SPELL** command neither objects nor honors column marks in your text. It will behave as if no marks exist whatsoever and perform its operation on your whole document.

CHAPTER FOUR
SETTING MARGINS AND USING TABS

Chapter Four contains information about:

- Setting Margins and Tabs
- Using Tabs and Indenting Text

SETTING MARGINS AND TABS

You set margins and tabs in an AlphaWRITE document using [MARGIN]. Settings made with [MARGIN] can be in effect for all, or only part of your document. You can also change the page format settings for portions of your document, overriding those set in the Document Header.

Creating New Margins and Tabs

To set new margins and/or tabs, from Text Display:

1. Position the cursor where you want the settings to take effect and press [MARGIN].
2. To use the Document Margin Screen:

TO:	DO THIS:
Move the cursor	Use [←], [→], [↑], [↓], [NEXT WORD], [PREV WORD].
Move to end of line	Press [SHIFT] [→].
Move to beginning of line	Press [SHIFT] [←].
Shift ruler right	Position cursor on any column and press [CHAR INS].

TO:	DO THIS:
Delete a tab	Position the cursor on that tab and press [SPACEBAR].
Insert spaces	Press [CHAR INS], this moves the following settings further out.
Delete spaces	Use [DEL CHAR] to delete spaces only, not settings.

3. How to set each type of tab and margins:

TO SET:	DO THIS:
Left Margin	Move cursor to column and press [<].
Right Margin	Move cursor to column and press [>].
Evenly spaced flush left tab	Type the number representing how many spaces between each tab. Use numbers in the range 1 to 9.
Flush left tab	Type **L**
Flush right tab	Type **R**
Centered tab	Type **C**
Period leader tab	Type **P**
Decimal tab	Type **D**

4. You also have these options at the Document Margin Screen:

TO:	DO THIS:
Clear all tabs	Type **0** (zero).
Use previous margin settings	Type **S**

TO:	DO THIS:
Delete existing margin	Press [DEL LINE].
Keep all changes	Press [EXECUTE].
Abandon changes	Press [CANCEL].

5. Displaying the Format Settings Screen:

   At the Document Margin Screen you can display the Format Settings Screen. Changes you make to Margin's Format Settings override those made in the Document Header.

   To see Margin's Format Settings, press [NEXT SCREEN] while the Document Margin Screen is displayed. Chapter 5 - "Setting Page Format and Formatting Text" describes using the format settings.

   To exit the Format Settings Screen and keep changes you make to it, press [EXECUTE]. To leave it and discard your format settings changes, press [CANCEL].

6. To keep your changes to the Document Margin Screen press [EXECUTE]; to exit and abandon your margin changes, press [CANCEL].

7. Any margin information blocks you make in your document appear in the first column, or where the left margin is set if other than column 1, on the line where you used [MARGIN].

   When the cursor is placed on this information block, the message on your status display reads "Margin."

Changing An Existing Margin

You can change any existing margin information block. To do so, from Text Display:

1. Position cursor on the margin information block you want to change.

2. Press [MARGIN].

3. Make changes to the Document Margin Screen or the Format Settings as described in the previous section.

4. Exit the Document Margin Screen with [EXECUTE] to keep your changes, [CANCEL] to forget them and return the ruler to its initial state.

Deleting An Existing Margin

There are two ways to delete a particular margin.

1. Include that margin information block in a marked area of text and use [BLOCK DELETE].
2. Position the cursor on the margin information block and press [MARGIN]. From the Document Margin Screen, press [LINE DEL]

HINTS FOR SETTING MARGINS AND TABS

Initial Format Settings Screen

The initial format settings for the Document Margin Format screen are determined by the initial settings in the Document Header, or by the previous margin setting, whichever is currently in effect.

See Chapter 5 - "Setting Page Format and Formatting Text" for information about the Document Header.

Automatic Format on Margin Exit

When you exit from the Document Margin Screen with [EXECUTE], all text until either the next margin block, or the end of your document is automatically reformatted.

Areas Affected by Margin

Settings made with [MARGIN] remain in effect from the information block where they are set until either the end of the document, or until the next margin information block.

To affect an entire document, use [MARGIN] at the very beginning.

Clear Special Tabs

Clear special tabs or margins you have set for a portion of your document as soon as you no longer need them. This ensures they won’t interfere with indenting, outlining or tabular work later in the document.

USING TABS AND INDENTING TEXT

Moving the Cursor to Next Tab Stop

At text display, to move cursor to the next tab stop, press [TAB].

Entering Indented Text

At text display, to automatically indent text as you type it:

1. Position the cursor at the beginning of the line, press [INDENT] until cursor is at the tab column you want text indented on.

2. Type the text.

3. Text automatically wraps to the tab setting you've indented to until you press [RETURN].

Indenting Existing Text

At text display, to indent existing text;

1. Position cursor at beginning of first line you want indented and press [INDENT] until text is at the tab column you want it indented to.

2. Repeat step one for the second line.

3. Move the cursor to the first line of text and press [FORMAT]. Or, use the **FORMAT** command to reformat the text.

HINTS ON USING TABS AND INDENTING TEXT

Making A Column of Text

To make a column of text and ensure it aligns properly when printed, use [TAB] instead of [SPACEBAR].

It is better to use [TAB] because tab settings correspond to specific positions on your printed page: a left tab at column 10 prints 1" plus the left paper offset setting from the left edge of the paper; a tab at column 20 prints 2" plus the left paper offset setting from the edge, etc. Thus, using [TAB] lets you precisely position text on your printed page.

Do not use the [SPACEBAR] to align columnar text; it provides unreliable printed results. See Chapter 3 - "Moving Around and Editing Text" for more information about [SPACEBAR].

If the columns are numbers, you might prefer to set decimal or flush right tabs to align the numbers and make entering them easier.

Collapsing Text

Your screen display cannot illustrate the exact printed size of text you enter at a tab setting. Therefore, text you type may appear to exceed the available space between tab stops even though the text will have adequate space for printing.

To adjust for this screen display limitation, AlphaWRITE has the Collapsed text feature. Collapsed text is an embedded feature and is accessed through the [EMBED] key.

To use collapsed text:

1. At Text Display, position the cursor on the column where you want the collapsed text held.

2. At this tab setting, press [EMBED].

3. At the Enter Code prompt, type **B** to select Collapsed text.

4. At the Collapsed embedded text screen, type the text you want aligned at this tab stop. You are limited to one line of text at this screen.

5. Press [EMBED] or [EXECUTE] to return to Text Display. A Collapsed text information block appears at the column where you press [EMBED].

You can enter some text at the tab setting before pressing [EMBED] and selecting Collapsed text.

You can edit your collapsed text by positioning the cursor on the information block and pressing [EMBED]. To delete a collapsed text entry, use [CHAR DEL].

Collapsed Text Exercise

If you follow the next steps, you'll see how the collapsed text feature works.

1. Create a new document and go to its document text display. Use the default tab arrangement of flush left tabs every 5 spaces which prints tabbed text at half inch intervals.

   Follow the next steps to make two columns of text lining up up at 1" (column 10) and 1.5" (column 15) from the left paper offset on your printed page.

2. You know there will be enough space between each tab setting to **print** half inch columns. But is there enough space to type it? Type the following, *with no intervening spaces*:

   [TAB] [TAB] **12345** [TAB] **12345**

   As you see, the tab indicator appears not on column 15, but on column 20. This is because the display can only show four characters between tab indicators.

3. To remedy this display idiosyncrasy, try this: Press [RETURN] a few times to move down and arrive on a new line. Type the following, *with no intervening spaces*:

   [TAB] [TAB] **123** [EMBED] **B45** [EXECUTE] [TAB] **123** [EMBED] **B45** [EXECUTE]

Collapsed text is a handy way to be sure tabbed text appears in the column where you want it, on your printed page *and* your screen.

Collapsed text use is not limited to tabular text, though. As the need arises, you can use collapsed text to solve differences between printed output and screen display limitations.

Double Indenting

If you want to achieve an indented appearance for text at both the left and right margins, use [MARGIN] and change the right margin by the equivalent of the indent tab you use.

> For example, the margin setting used for this paragraph allows *indent* of text one inch from the left margin (two inches from the left side of the page) and has a right margin setting one inch shorter than the paragraph above. This type of paragraph formatting is sometimes called "double indent."

Kinds of Tabs

Flush Left Tabs

Flush left tabs are the most commonly used tabs. They function just like the tabs on a typewriter—text you type after pressing [TAB] key begins at the column where the tab is set and continues to the right as you type.

You can set flush left tabs in two ways:

- Evenly from the left to the right margin.
- Individually in any column.

To set flush left tabs evenly from one margin to the other of your document, from the Margin Menu:

– Type the number of columns you want between each tab stop.

For example, type 6 to set flush left tabs every six columns— in columns 6, 12, 18, and so on to the right margin setting. Valid entries are number from 1 to 9.

When you enter the number, all existing tab stops are cleared from the ruler, and L's appear in each column where there is now a left tab set.

Flush Right Tabs

Flush right tabs align the ends of words in a particular column, creating a right justified column of text. For example:

```
This text was aligned
          using a flush
       right tab stop.
```

The cursor does not move as you type text entered at a flush right tab stop. Rather, as you type each character the previous characters move one space to the left to make room, so the last character you type is always in the column where the flush right tab is set.

When you use a flush right tab, you can enter only as many characters as fit between the flush right tab and the previous tab stop or the left margin. If there are more characters, you can use the EMBED key's collapsed text feature.

Period Leader Tabs

Period leader tabs work like right flush but also a row of periods from the previous tab setting, or the left margin, to the text you enter at the tab. As with flush right tabs, they move previous characters to the left as you type, keeping the cursor in the same column. The result is a row of periods leading to the beginning of a right justified column of text.

Period leader tabs are excellent for tables of contents, as shown in the example below. Left tabs are set for the text and a period leader tab to align the page numbers:

THE MARGIN KEY.....3
Margin Blocks..... 3
Using the Margin Key.....3

The table of contents and list of figures in the *AlphaWRITE Reference Manual* use period leader tabs.

Center Tabs

Center tabs align text evenly on either side of the column where the tab is set. When you type text at a center tab, every second character moves the cursor to the left one column. This keeps the text centered on the tab position as you enter it. For example:

This is
a centered
column
of text.

Decimal Tabs

Decimal tabs are used for entering columns of numeric data; they align a number's decimal point in the column where the tab is set. For example:

113.783
6.9
.74
15,478.00

As you type the number, each numeral moves to the left until you type the decimal (period), then each numeral you type moves to the right. You can use the SPACE BAR to insert a decimal when entering decimal tabs, pressing it instead of the period key.

CHAPTER FIVE
SETTING PAGE FORMAT AND FORMATTING TEXT

Chapter Five contains information on these topics:

- Setting Page Format
- Page Breaks
- Formatting Documents

SETTING PAGE FORMAT

Format Settings

All of AlphaWRITE's format settings are located on the Document Header. A subset of these settings are available on the Margin key's Format Screen as described in Chapter 4 - "Setting Margins and Using Tabs."

Changes you make to format settings in the Document Header affect your entire document. The format settings you change via [MARGIN] override those set in the Document Header. Margin format settings are in effect from the point where they occur until the end of your document, or until they are changed again with [MARGIN].

Getting to the Document Header Format Settings

You see the Document Header when you first **CREATE** a document. Once a document is created, you can display the Document Header and make changes to it. To do so:

1. From Text Display, press [MENU].
2. At the Editing Menu, type **HEADER** [RETURN].
3. You can move the cursor to the field(s) you want to change with the arrow keys.

   To display information about a particular field, press [HELP] which tells you that field's purpose and the valid responses to use.

4. To return to your Text Display and keep your changes press [EXECUTE] or [MENU].

   To return to Text Display and discard your changes, press [CANCEL].

Getting to the Margin Key's Format Settings

You can make changes to format settings via the Margin key. To do so, from Text Display:

1. Position the cursor on the line where you want to make new format settings.

2. Press [MARGIN].

3. At Document Margin Screen, press [NEXT SCREEN].

4. These format settings are available for change at the Document Margin Screen:

Leading	Left Paper Offset
Page Length	Right Justify
Top Margin	Characters Per Inch
Title Length	Word Spacing
Text Length	Line Spacing
Footer Length	Kerning
Allow Format	Page Orientation

5. To keep your format changes, press [EXECUTE] twice: once from Margin Format Screen, once from the Document Margin Screen.

   To discard format changes, press [CANCEL] to return to Margin Menu. From the Margin Menu, press [EXECUTE] if you made changes to the ruler you want to keep; press [CANCEL] to discard margin changes too and return to Text Display.

Changes made to format settings with [MARGIN] are in effect from the line where they are made until the next change made via [MARGIN], or to the end of your document if no other format changes are made with [MARGIN].

You can return to the format settings made in a previous margin information block with the Margin's key S option. See Chapter 4 - "Setting Margins and Using Tabs" for more details.

Default Format Settings

AlphaWRITE comes with a default document named DEFDOC.WRT which is the default prototype document whenever you **CREATE** a new document. DEFDOC's Document Header settings are shown in the following illustration:

```
                          AlphaWRITE DOCUMENT HEADER

Description
Author                        Operator                        Department
Protection - (N, P or PE) N
                                   FORMAT
Leading ...................... 6        Left Paper Offset ............ 1"
Page Length .................. 11"      Right Justify - (Y or N) ..... N
Top Margin ................... 0.5"     Characters Per Inch (pitch) .. 10
Title Length ................. 0.5"     Word Spacing - (F, V or P) ... P
Text Length .................. 9"       Line Spacing (half lines) .... 2
Space Before Footnotes ....... 0.5"     Footnote Print Type - (B or E) B
Footer Length ................ 0.5"     Footnote Line Separator ...... _
Printer Form Name ............ NORMAL   Kerning (N, Light, Med, Tight) N
Allow Format of Text (Y or N)  Y        Orientation - (P or L) ....... P

Created: 15-Jun-88 08:57           STATISTICS       Keystrokes/Minute:     0
Revised: 13-Feb-90 09:31     Times Revised:  12     Total Time Open:   00:00
Printed:                     Times Printed:   0     Total Keystrokes:    445

    UNITS     [ Press UP ARROW or DOWN ARROW to select fields ]     UNITS
 "  = inches   [ Press HELP for information about this field ]  pts = points
 cm = metric      [ Press EXECUTE or MENU to update header ]    ci  = ciceros
 mm = metric      [ Press CANCEL to forget header changes ]     di  = didots
```

Document Header for DEFDOC.WRT

All the Document Header fields are discussed in the following sections.

A modified copy of DEFDOC.WRT can be located in a local account and has the result of letting you determine the format settings AlphaWRITE uses. If this is the case on your computer, the default settings may be different than those listed above. See the section describing prototype documents in Chapter 2 - "Creating Documents" for more information.

Units of Measurement

AlphaWRITE's format settings shown on the Document Header or Margin Format Screen allow you to work with various units of measurements. You signal which unit of measurement you intend to use with a symbol or an abbreviation.

The symbol or abbreviation can appear adjacent to the value you are setting, or be separated by a space. Also, if it is an abbreviation, it can be in either upper or lower case.

UNITS OF MEASUREMENT	SYMBOL OR ABBREVIATION
Characters & lines	No symbol necessary, whole numbers only, i.e.: 6, 66, or 2.
Points	Use the abbreviation pts, i.e.: 72 pts, 10.5 pts, and so on.

UNITS OF MEASUREMENT	SYMBOL OR ABBREVIATION
Inches	Use the quote symbol ("), i.e.: 11", 0.5", or 1.25".
Centimeters	Use the abbreviation cm, i.e.: 10 cm, 12.5cm.
Millimeters	Use the abbreviation mm, i.e.: 20mm, 20.75 mm.
Ciceros	Use the abbreviation ci, i.e.: 10ci, 52 ci.
Didots	Use the abbreviation di, i.e.: 54di, 102di.

If you do not include a symbol or abbreviation, AlphaWRITE defaults to a unit of measurement in characters or lines. The default unit of measurement for fields requiring a measurement is shown in the section below discussing each format field.

Although AlphaWRITE can interpret a mixture of units of measurements—millimeters intermixed with points and inches—it will probably be easier for you to set up page format using compatible units, i.e., centimeters and millimeters; ciceros; didots; inches, characters and lines; or points.

Laser Printer Page Format Considerations

All laser printers have boundaries within which they print. Typically, a perimeter of 0.25" on the paper is regarded as unprintable. Keep this non-printable area in mind as you define your page format: if you set an improper format, AlphaWRITE can create printed output which might encroach this non-printable area and result in text fading off the edges of the page.

Settings which particularly affect the non-printable boundaries are shown below.

FIELD	SETTING
Left paper offset	Ideally should be 0.25", or greater.
Left margin setting	When added to left paper offset setting, should not total less than 0.25".
Right margin setting	When added to left paper offset setting should be at least 0.25" less than the paper width. For example, for 8.5" wide paper: when left paper offset equals 0.25", the right margin cannot exceed column 80 (8.0"). Otherwise, text will fade off the right side of the page.

FIELD	SETTING
Top margin setting	Ideally should be 0.25", or greater.
Page format formula	Top margin setting + Title length setting + Text length setting + Footer length setting Should not exceed Page length setting. For example, for 11" paper length: if top margin is 0.5", title length is 0.5", and footer length is 0.5", text length should not exceed 9.5". Otherwise, text will fade off the bottom of printed page.

Using the Preview Command

AlphaWRITE's Editing Menu **PREVIEW** command is a handy way to see your format settings in effect. See Chapter Six - "Printing Documents" for more information.

How Each Format Setting Affects the Printed Page

The following illustration shows you how particular page format settings affect your printed page. The positions occupied by the format setting names are relative; that is, they are positioned to show the general area of the page.

The ruler at the bottom of the illustration represents your text display's Margin ruler. It shows how column one begins at the left paper offset position.

Sorry, but this image could not be converted to Adobe Acrobat Format.
Please refer to your printed manual for this diagram.

Page Format Settings On the Printed Page

Document Header Fields and Format Settings

Document Header fields and each of AlphaWRITE's format settings is described below. They are listed in alphabetic order. Default settings are those belonging to DEFDOC.WRT. The default unit of measurement shown applies when no other unit of measurement is specified in that field's setting.

SETTING	DESCRIPTION
Allow Format	Determines whether or not text is automatically aligned according to current page format settings when text could be formatted.

SETTING	DESCRIPTION
Allow Format (continued)	Y Allows automatic format. N Prevents format. Useful when text should print using the same spacing as the screen. Use for tables, diagrams, charts, etc. Default: Y. Also available on Margin Format Screen.
Author	Holds up to 20 characters to identify this document's originator. Default: blank. Not available on Margin Format Screen.
Characters Per Inch	Used by printers having a daisy-wheel or thimble print-element, and by some dot-matrix printers. Typical settings are 10, 12 or 15 and should match the currently installed print-element on your printer for best results. Laser printers ignore this format field; character spacing is determined by the laser printer's font width tables. Leave this field at 10 for laser printing; changing it from 10 will affect text display. 10, 12 and 15 are the most common settings. Default: 10. Also available on Margin Format Screen.
Description	Holds up to 60 characters to describe document contents and purpose. Some DIRECTORY displays show only the first 42 characters of description. Default: blank. Not available on Margin Format Screen.
Department	Holds up to 6 characters to identify a department number or other code. Default: blank.
Footer Length	Reserves vertical space at the bottom of each page for printing footer text. Footers, set through EMBED, can have multiple lines of text. Default: 0.5". Default Unit of Measurement: lines. Also available on Margin Format Screen.
Footnote Line Separator	Selects the character used to print a short line—ten characters long—to separate your document text from your footnote text. The default is underscore but any character may be used.

SETTING	DESCRIPTION
Footnote Line Separator (continued)	Default: _ (Underscore character). Not available on Margin Format Screen.
Footnote Print Type	Determines where footnotes print. Valid settings are: B Prints footnote at the bottom of the page where it occurs. E Groups footnotes and prints them in order of their occurrence at the end of your document. Default: B. Not available on Margin Format Screen.
Kerning	Adjusts the amount of space between characters only on laser printers. Valid settings are: N None: spaces characters as they are naturally defined in the corresponding font width table. L Light: decreases space between characters by 5% from N setting M Medium: decreases space between characters by 10% from N setting. T Tight: decreases space between characters by 15% from N setting. Default: N. Available on Margin Format Screen.
Leading	Determines how many text lines print in a given vertical space. Technically, leading is the space between lines of type. Default Setting: 6 Default Unit of Measurement: lines. Also available on Margin Format Screen. Valid responses are: **Whole numbers (6, 8, etc.):** On impact printers, this setting is lines per inch. On laser printers, any whole number automatically forces leading to be calculated at 20% based on the current font size. This is always a good choice, especially when you will be using multiple type sizes in your document.

SETTING	DESCRIPTION
Leading (continued)	**Point sizes (10pt, 12pt, etc.)** Defines explicit spacing between lines for laser printers. Setting leading to 12pt when laser printing yields 6 lines per inch. **Percentages (15%, 20%, etc.)** Defines spacing based on current font size height on laser printers.
Left Paper Offset	Determines how much horizontal white space is reserved as the left margin of the paper. Determines where column 1 prints on your page; this corresponds to column 1 on your screen. Many laser printers require a minimum of 0.25" (a quarter inch). Default: 1.0" Default Unit of Measurement: characters. Also available on Margin Format Screen.
Line Spacing	This value determines how many blank half lines are used between text lines. Valid responses are whole numbers 1 to 255. Common settings are: 2 Single spacing 3 Single and a half spacing 4 Double spacing 6 Triple spacing Default: 2 (single spacing). Also available on Margin Format Screen.
Operator	Holds up to 20 characters to name the person typing this document. Default: current user name. Not available on Margin Format Screen.
Orientation	On laser printers only, lets you choose whether printed text prints vertically on page (portrait mode) or horizontally (landscape mode). Valid settings are: P Portrait orientation L Landscape orientation Default: P. Also available on Margin Format Screen.

SETTING	DESCRIPTION
Page Length	Vertical measurement of paper you will print this document on. Page length setting must equal or exceed the sum of Top Margin plus Title Length plus Text Length plus Footer Length. Default Setting: 11". Default Unit of Measurement: lines. Also available on Margin Format Screen.
Printer Form Name	Used to identify different types of paper used in your printer. Form names are 6 or less characters and are assigned by your System Operator, who can tell you what names are currently assigned. Default: NORMAL. Not available on Margin Format Screen.
Protection	Lets you select document protection and assign a password. There are three responses to the Protection prompt: N Selects no protection. P Standard protection, assigns password. PE Encrypted protection, assigns password. For P or PE selections you are asked to enter a password. The password you assign should make sense to you so it won't be easily forgotten. Passwords can be up to ten characters long. Once entered, as an added security measure, when you press RETURN, the password itself disappears from the screen although the prompt remains. To display the password again, move the cursor back to the Password prompt. Remember the password for your document! It must be entered every time this protected document is used. If you forget the password after exiting your protected document, you are not able to use this document at all! Default: N (no password).
Right Justify	Lets you choose an evenly aligned right margin (Y), or a ragged right margin (N). Default: N. Also available on Margin Format Screen.
Space Before Footnotes	Sets the minimum amount of blank vertical space to be reserved between the end point of the text length setting and printing of the footnote line separator.

SETTING	DESCRIPTION
Space Before Footnotes (cont'd)	Common settings are the equivalent of 1 or 2 blank lines. Default: 0.5". Default Unit of Measurement: lines. Not available on Margin Format Screen.
Text Length	Sets amount of vertical space reserved for printing the text body on each document page. Default: 9". Default Unit of Measurement: lines. Also available on Margin Format Screen.
Title Length	Reserves this amount of vertical space at the top of each page for printing title text. Titles, set through EMBED, can occupy multiple lines. Default: 0.5". Default Unit of Measurement: lines. Also available on Margin Format Screen.
Top Margin	Sets how much blank vertical space is reserved between the top edge of the paper and the beginning of title area. Many laser printers require this setting to be at least 0.25". Default: 0.5". Default Unit of Measurement: lines. Also available on Margin Format Screen.
Word Spacing	Determines how characters and words are spaced when using impact printers—word spacing is ignored by laser printers. The correct word spacing is important when you set the format setting Right Justify to Y. Valid responses to Word Spacing are: F (**F**ixed) to set all characters and spaces to the same width, a common setting for use on dot-matrix printers. V (**V**ariable) allows micro-spacing between words during right justify for a more evenly filled lines of text. P (**P**roportional) tells AlphaWRITE you are using a proportional print-element where each character's printed width varies. Default: P. Also available on Margin Format Screen.

PAGE FORMAT FORMULA

AlphaWRITE uses a uniform system to calculate text positioning on the printed page. For designing page layouts, you may find this formula to be helpful:

```
  Top Margin
+ Title Length
+ Text Length
+ Footer Length
_________________
  Must be less than or equal to Page length
```

UNIT OF MEASUREMENT CONVERSION TABLES

You may not be familiar with all the units of measurements AlphaWRITE supports and it will probably help to put them in terms you can understand.

The tables below translate each of the measurements in terms of the others. For example if you can visualize an inch measurement on a ruler, knowing 72 points fit in that space gives you a good approximation of just how big (small!) one point is, it is 1/72nd of an inch.

In Terms of One Inch			In Terms of One Point		
5.6306 ciceros	=	1 inch	0.035 centimeter	=	1 point
2.54 centimeters	=	1 inch	0.0782 ciceros	=	1 point
20.7039 didots	=	1 inch	0.2876 didots	=	1 point
25.4 millimeters	=	1 inch	0.0139 inch	=	1 point
72† points	=	1 inch	0.3528 millimeters	=	1 point

†Typography usage generally defines 72 points as 0.9986 inches; however, laser printer technology uses 72 points as 1.0 inches as standard.

In Terms of One Centimeter			In Terms of One Millimeter		
2.2168 ciceros	=	1 centimeter	0.1 centimeters	=	1 millimeter
8.1511 didots	=	1 centimeter	0.2217 ciceros	=	1 millimeter
0.39 inch	=	1 centimeter	0.8151 didots	=	1 millimeter
10 millimeters	=	1 centimeter	0.039 inch	=	1 millimeter
28.346 points	=	1 centimeter	2.8346 points	=	1 millimeter

In Terms of One Didot			In Terms of One Cicero		
0.1227 centimeter	=	1 didot	0.4508 centimeter	=	1 cicero
0.2720 ciceros	=	1 didot	3.6770 didots	=	1 cicero
0.0483 inch	=	1 didot	0.1776 inch	=	1 cicero
1.2268 millimeter	=	1 didot	4.5076 millimeter	=	1 cicero
3.4776 points	=	1 didot	12.7873 points	=	1 cicero

HINTS ON SETTING AND USING PAGE FORMAT

Formatting Your Document

Use **FORMAT** to automatically have your whole document arranged according to the format settings you choose. Use [FORMAT] to arrange paragraphs of text.

Paginating and Format Settings

Use **PAGINATE** before printing a document to ensure page breaks fall in accordance to the format settings you choose.

Kerning Methods

AlphaWRITE uses two types of kerning methods: pair and track. Pair kerning is automatically handled by AlphaWRITE and it determines the horizontal distance between characters. This distance is based on the font width tables and is always in effect. Track kerning is controlled by the kerning format setting which allows you to uniformly reduce the distance between all characters. Four degrees of kerning are available as defined in the format setting chart.

SAMPLE PAGE FORMATS

Although you may normally use 8½" by 11" paper, you may need to use other paper sizes from time to time. The tables below illustrate format settings for various sizes used in impact and laser printers. Two units of measurement are used: one in characters and lines, the other in inches.

LEGAL PAPER, ENVELOPES AND LABELS
UNIT OF MEASUREMENT: CHARACTERS & LINES

Format Setting	8½"x14" Legal	3¼"x21½" Envelope	Label	Label
Leading	6	6	6	6
Page length	84	24	6	15
Top Margin	6	12	1	1
Title Length	2	0	0	0
Text length	72	12	5	13
Space before Footnotes	0	0	0	0
Footer Length	2	0	0	0
Left paper offset†	10	50††	2	2
Line spacing	2	2	2	2

† Assumes character per inch setting of ten for impact printers. Adjust if needed for other character spacing.

†† Begins printing near center of envelope; no margin adjustment is necessary. Adjust setting if necessary to suit your envelope style.

PAPER - PORTRAIT MODE UNIT OF MEASUREMENT: INCHES				
Format Setting	**8½"x11" Letter**	**8½"x14" Legal**	**14½"x11" 132 Col.**	**A4†**
Leading	6	6	6	6
Page length	11"	14"	11"	11.75"
Top Margin	0.5"	0.5"	0.5"	0.5"
Title Length	0.5"	0.5"	0.5"	0.5"
Text length	9"	12"	9"	9.75"
Space before Footnotes	0.5"	0.5"	0.5"	0.5"
Footer Length	0.5"	0.5"	0.5"	0.5"
Left paper offset	1"	1"	1"	1"
Line spacing	2	2	2	2
Orientation	P	P	P	P

† A4 is a standard paper size used in the United Kingdom and Europe. It is the most common size for correspondence printing and its dimensions are 8.25"x11.75"

PAPER - LANDSCAPE MODE - LASER PRINTERS ONLY UNIT OF MEASUREMENT: INCHES			
Format Setting	**8½"x11" Letter**	**8½"x14" Legal**	**A4**
Leading	6	6	6
Page length	8.5"	8.5"	11.75"
Top Margin	0.5"	0.5"	0.5"
Title Length	0.5"	0.5"	0.5"
Text length	6.5"	6.5"	9.75"
Space before Footnotes	0.5"	0.5"	0.5"
Footer Length	0.5"	0.5"	0.5"
Left paper offset	1"	1"	1"
Line spacing	2	2	2
Orientation†	L	L	L

† Be sure to adjust the right margin to accommodate the wider paper orientation.

ENVELOPES - PORTRAIT MODE - IMPACT PRINTERS ONLY UNIT OF MEASUREMENT: INCHES		
Format Setting	**9½"x4" Letter Size**	**A4† Size**
Leading	6	6
Page length	4"	4.25"
Top Margin	2"	2"
Title Length	0"	0"
Text length	2"	2.25"
Space before Footnotes	0"	0"
Footer Length	0"	0"
Left paper offset*	5"††	5"††
Line spacing	2	2
Orientation	P	P

† A4 is a standard paper size used in the United Kingdom and Europe. The A4 envelope dimensions are 8.75" x 4.25".

†† Begins printing near center of envelope; no margin adjustment is necessary.

ENVELOPES - LANDSCAPE MODE - LASER PRINTERS ONLY UNIT OF MEASUREMENT: INCHES		
Format Setting	**9½"x4" Letter Size**	**A4† Size**
Leading	6	6
Page length	9.5"††	8.75"††
Top Margin	2"	2"
Title Length	0"	0"
Text length	2"	2.25"
Space before Footnotes	0"	0"
Footer Length	0"	0"
Left paper offset	5"†††	5"†††
Line spacing	2	2
Orientation††	L	L

† The A4 envelope dimensions are 8.75"x4.25".

†† Envelopes are inserted sideways into the laser printer, unlike impact printers where they are rolled in top to bottom.

††† Begins printing near center of envelope; no margin adjustment is necessary.

LABELS ON IMPACT PRINTERS UNIT OF MEASUREMENT: INCHES		
Format Setting	**3½"x1" Label†**	**4¼"x3½" Label†**
Leading	6	6
Page length	3.5"	4.5"
Top Margin	0.5"	1.25"
Title Length	0	0
Text length	3.5"	3.75"
Space before Footnotes	0	0
Footer Length	0	0
Left paper offset	0.25"	1"
Line spacing	P	2
Orientation	P	P

†Single bank of labels, 1 label per form.

PAGE BREAKS

There are four kinds of page breaks: Soft Page Breaks, Conditional Soft Page Breaks, Hard Page Breaks and Chapter Page Breaks. They look something like this on your screen display:

```
////////// SOFT PAGE BREAK //////////

////////// SOFT PAGE BREAK //////////
//CONDITIONAL PAGE BREAK n

////////// HARD PAGE BREAK //////////

//////// CHAPTER PAGE BREAK ////////
```

The **PAGINATE** command and the conditional page break feature both create soft page breaks; only PAGE's Page Break option 1, creates a hard page break; only LAYOUT's New Chapter option 4 creates a chapter page break.

You create a conditional page break by using PAGE's option 3. After you create it and before it is put in effect by **PAGINATE**, it looks like this:

```
//CONDITIONAL PAGE BREAK n
```

where n represents the whole number of lines you do not want separated between two pages. A soft page break symbol appears above this text only after using **PAGINATE** when the number of lines left is less than what you requested.

To determine where page breaks belong, the **PAGINATE** command uses Format Settings made in the Document Header, or Margin Format Setting Screen. The settings it uses are the Page Length and Text Length format settings in effect, conditional or hard page breaks you included; and the printer you intend to use.

Paginating Your Document for Printing

You can see where page breaks fall in your document before using the **PRINT** command by using the **PAGINATE** command first. Use **PAGINATE** and select the printer you intend to print on. When your text display returns, soft page breaks appear where a new pages begin.

To use **PAGINATE**, from the Editing Menu:

1. Type **`PAGINATE`** [RETURN].

2. At the AlphaWRITE Document Pagination screen's Enter Printer Number prompt, select the printer you want this document paginated for.

   To do so, type the number associated with the printer and press [RETURN].

   If you are not given a selection, only one printer is available to you and **PAGINATE** will automatically perform its operation for that printer.

Paginate's Soft Page Breaks

When **PAGINATE** places a soft page break in your document based solely on your format settings and not as a result of a conditional page break, it uses a split-line display technique to show you where the page break falls.

PAGINATE literally splits a displayed text line between pages to show you the last word on one page and first word on the next. This is especially helpful when your document contains multi-lined paragraphs and you are using any proportional (non-Courier) typeface and typesize.

The split-line paginate scheme lets you see where the breaks fall before you print. Although the display might appear to be unformatted, it is not.

Before **PAGINATE**:

```
Here is an example of display text before PAGINATE and
afterward.  Notice the lines immediately preceding and
following the soft page break.  If you use the FORMAT
command, or FORMAT key, and disrupt the soft page break, your
text line will be joined back together.  Printed
text lines will fill the page from left to right margins.
```

After **PAGINATE**:

```
Here is an example of display text before PAGINATE and
afterward. Notice the lines immediately preceding and
following the soft
//////////////// SOFT PAGE BREAK ////////////////////
page break.  If you use the FORMAT
command, or FORMAT key, and disrupt the soft page break,
your text line will be joined back together.  Printed
text lines will fill the page from left to right margins.
```

The printed results will have filled lines with no gaps according to the format settings you are using.

You can rejoin the paragraph display lines by using any method which normally removes or relocates soft page breaks: **PAGINATE** for another printer, [FORMAT] or **FORMAT**, or [SHIFT]-[↑] to join the next line to this one. The split line is then rejoined and the soft page break removed. Running **PAGINATE** again, will insert new soft page breaks, displaying split lines where applicable.

Forcing Hard Page Breaks

To force a hard page break at a specific line in your document, from Text Display:

1. Position the cursor anywhere on the line before the one where you want the page break.
2. Press [PAGE].
3. Type **1** to select hard page break.

Using a Conditional Page Break

AlphaWRITE's conditional page break feature lets you make sure text you want to appear together is not separated between pages. To do so, at Text Display:

1. Position the cursor anywhere on the first line of text belonging to the text you do not want split between pages.
2. Press [PAGE].
3. At the Enter Code prompt, type **3** to select the Conditional Page option.
4. At the Enter Size prompt, type the number [RETURN], where the number represents the number of lines you do not want split between pages. The measurement is in lines.
5. Use the **PAGINATE** command to see displayed results of conditional paging. If there are not enough lines for this text left on the page, a soft page break will appear; otherwise, no page break is included at this line.

Deleting a Page Break

You can delete any page break with [LINE DEL], or by including the page break in any marked text you intend to delete.

All page breaks, except hard page breaks, can automatically be rearranged by the **PAGINATE** command. So, from time to time, page breaks may be removed from one line and reset on another based on the document changes you've made and the current format settings.

Moving Between Page Breaks

The [PAGE] key's Go To Page option, and the [NEXT PAGE] and [PREV PAGE] features let you move to specific page breaks.

Page Counter

The value shown on the Text Display status line for Page is determined by the number of page breaks present in your document.

FORMATTING DOCUMENTS

Formatting realigns text to conform to the margins of your document, filling in lines with text from subsequent lines and/or shortening lines by moving text as needed.

Formatting is especially important when you have changed text in a document area where right-justify is in use, or when you have used the Document Header to switch from no justify to right justify.

You can format a paragraph, text between margin information blocks or your entire document. You can also set no format for all or just part of your document.

Formatting A Paragraph

To format a paragraph, or to format to the next paragraph marker:

1. Position cursor on first line of paragraph, or line where format is to begin to take effect.
2. Press [FORMAT].

Formatting Text Between Margin Information Blocks

To format text between two margin information blocks:

1. Position the cursor on the first margin information block.

2. Press [MARGIN].

3. Press [EXECUTE].

Formatting A Whole Document

To format your whole document, from the Editing Menu, type:

FORMAT [RETURN]

Setting No Format for Whole Document

You can identify whole or only part of a document so it will not be realigned to the current settings. This is useful when you want your printed text to appear exactly as it is arranged at your screen display.

To set no format for your whole document when no margin information blocks are set, from Text Display:

1. Press [MENU] to display the Editing Menu.

2. Type **HEADER** [RETURN].

3. Type **N** at the Document Header's `Allow format of text` field.

4. Press [EXECUTE] to put the change into effect.

Setting No Format for Part of Your Document

To set no format for a part of your document, from Text Display:

1. Position the cursor on a line preceding the area you want to set to allow no formatting.

2. Press [MARGIN].

3. Press [NEXT SCREEN] to display the Margin Format Screen.

4. Type **N** in the field named Allow Format of Text.

5. Press [EXECUTE] to return to the first margin screen.

6. Press [EXECUTE] to put your change into effect and return to Text Display.

7. To resume format, move the cursor to where you want to set formatting, and repeat steps 1 to 3.

8. Type **Y** in the field named Allow Format of Text and repeat steps 5 and 6.

Automatic Formatting

Several AlphaWRITE features format sections of your document as part of their normal operation. These features are:

- EXECUTE from using MARGIN
- **REPLACE** and **GLOBAL** commands
- **SPELL** command when a correction is made
- **MERGE** command as it substitutes text

Discretionary Hyphens

A discretionary hyphen inserts optional hyphens into words. When a word containing a discretionary hyphen does not entirely fit on a line when a paragraph is formatted, the word is divided between two lines at the discretionary hyphen and a visible hyphen appears.

If the word does not need to be divided to fit on a line, the discretionary hyphen is ignored and no visible hyphen appears.

Discretionary hyphens help right justify text fill lines more evenly and reduce the "rivers of white space" effect.

To use a discretionary hyphen, from Text Display:

1. Position the cursor on character to be preceded by a discretionary hyphen.

2. Press ESC –.

3. Press FORMAT. This area of text is formatted, words split at discretionary hyphens as needed.

HINTS FOR FORMATTING DOCUMENTS

Format Settings

All format operations rely on and use the format settings currently in effect at the Document Header, or the current Margin Format Settings.

Indent

INDENT lets you set a temporary left margin to which any format operation will align the following lines of text.

Using the Paginate Command

Since formatting a section of text could make it require either more or fewer lines, it is always a good idea to use **PAGINATE** after any of the format operations discussed above. Unless you have set a hard or chapter page break, formatting a part or all of your document will remove soft page breaks because they are no longer accurate.

Formatting and Discretionary Hyphens

Formatting text before inserting discretionary hyphens shows you where they are needed. You must format text after inserting discretionary hyphens in order for them to take effect. When a discretionary hyphen is in effect, a visible hyphen follows the information block at the end of the line.

CHAPTER SIX
PRINTING DOCUMENTS

Chapter Six contains information about these topics:

- Printing a Document
- Printing Using Sheet Feeders
- Working with the Printer Queue
- Previewing Your Document

PRINTING A DOCUMENT

Using the Print Command

AlphaWRITE's Main Menu **PRINT** command allows printing of any AlphaWRITE document located in this account. The Editing Menu **PRINT** command sends the document you are currently working on to the printer.

To use **PRINT**, from either menu:

1. Type **`PRINT`** [RETURN].

   If from Main Menu, type **`docnam`** [RETURN]. Type its password if the document is protected.

   Editing Menu **PRINT** assumes you want to print the document you are currently editing.

2. From either menu, when there is more than one printer, type the number shown on the list for the printer you want to use and press [RETURN].

3. A list of options appears after you select a printer. Once you answer them to your satisfaction, press [EXECUTE] to process your print request.

   Use the table below to select the result you want. The corresponding responses you need to make to the **PRINT** prompts are shown in the second column.

TO	PRINT PROMPT / RESPONSE	
Print document as disk file	Disk output only?	**Y**
	After **PRINT**, a file with the same name as your document but with an extension of .LST will reside in the account where you used **PRINT**. Select the same printer from AMOS command level to print your resulting .LST file as you used with AlphaWRITE's **PRINT** command.	
Print file now	Disk output only?	**N**
Print all pages	Start at page number End at page number Print odd-numbered pages? Print even-numbered pages?	**1** **x*** **Y** **Y**
	*where **x** is the last page of your document as determined with the **PAGINATE** command, or the default setting 9999.	
Print only one page	Start at page number End at page number Print odd-numbered pages? Print even-numbered pages?	**x*** **x*** **Y** **Y**
	*where **x** is the one page number you want to print.	
Print only odd-numbered pages	Print odd-numbered pages? Print even-numbered pages?	**Y** **N**
Print only even-numbered pages	Print odd-numbered pages? Print even-numbered pages?	**N** **Y**
Use continuous paper	One page at a time?	**N**
Use single sheets	One page at a time?	**Y**
Use sheet feeders	Use cut-sheet feeder? One page at a time?	**Y** **N**
Ignore sheet feeder	Use cut-sheet feeder?	**N**
Select number of copies	Number of copies	**x***
	*where **x** is in the range 1 to 999.	

HINTS FOR DOCUMENT PRINTING

Printers Available

Printers available for AlphaWRITE's use are defined specifically in the AlphaWRITE initialization file, or are defined globally by your computer's printer definition file.

Paginate Before Printing

If you want to see where the pages break in your document, you must use **PAGINATE**. However, if you do not use **PAGINATE** AlphaWRITE will page your document when you use the **PRINT** command but **PRINT** will not place soft page breaks in your document.

Although **PAGINATE** and **PRINT** appear to be performing the same activity on your document, they are processing your document in different ways. **PAGINATE**'s job is to make page breaks appear in the appropriate places in your document display based on your format settings. It takes into consideration right-justification, widow and orphan control, filling lines based on the measurements you've made in your Margin Ruler, and so on.

The **PRINT** command's job, on the other hand, is much more extensive. **PRINT** performs all of **PAGINATE**'s activities—except inserting soft page breaks in your document—and more. **PRINT** performs many operations on your document to make it printer-ready: It ensures all the print features you've used are taken into account and prepares your document with the appropriate printer instructions for features such as typeface, typesize, bold, italic, graphics lines, hyphenation, graphics, special characters. **PRINT** processes line-by-line from the beginning of your document to take into account every print element used.

The Printer Queue

Use **QUEUE** to halt a print in progress, change the priority of documents waiting to be printed, select new form names for printing and change the font or printwheel currently set.

Setting Page Breaks

Set conditional or hard page breaks to control page breaking with the [PAGE] key. Chapter page breaks are set by using the [LAYOUT] New Chapter option.

Printed Page Numbers

Printed page numbers might differ from the page counter you see at document display because you have used the set page number command to change the printed ones. Use document text display's status line page counter as your guide for responses to **PRINT**.

Also use the page counter as your guide to moving between page breaks with the [PAGE] go to page option.

PRINTING USING SHEET FEEDERS

Using Sheet Feeders

Sheet feeders are trays installed on certain printers which allow automatic feed of single sheet pages into the printer. Sheet-feeders let you use your own letterhead or other paper without having to hand-feed the printer with single sheets.

Documents can include special embedded bin instructions about which sheet feeder to use on a particular printer. (See below.)

To use a printer's sheet feeder(s), from the Main Menu or Editing Menu:

1. Type **PRINT** [RETURN].

   If necessary, select the printer on which the sheet-feeders are installed and press [RETURN].

2. At the Document Printing menu, respond to the Use Cut-Sheet Feeder prompt by typing **Y** and to the Disk Output Only prompt by typing **N**.

   When all other prompts are answered satisfactorily, press [EXECUTE].

Selecting Specific Trays

The default feeder selection is tray 1 for document pages. You can override this scheme by using [LAYOUT]'s bin option to request your own bin selection arrangement.

Selecting the Tray Combination

To select a particular tray combination, from Text Display:

1. Position the cursor on line 1 of the document page you want to affect.

2. Press [LAYOUT].

3. At the Enter Code prompt type **7** to select the bin option.

4. At the Enter Code prompt type the character shown on the menu representing the combination you want to use.

   AlphaWRITE supports up to four different trays on your printer and you can select from six combinations.

BIN	RESULT
1	Uses paper from tray 1 (default combination.)
2	Uses paper from tray 2.
3	Uses paper from tray 3.
4	Uses paper from tray 4.
C	Uses paper from tray 1 for this page, paper from tray 2 for pages thereafter.
E	Ejects page from the current tray; do not load another sheet.

5. An information block appears on the line where you made a bin selection. When the cursor is on this information block, it shows the bin currently selected.

As long as the bin selection is on the first line of the page, bin selection goes into effect on that page.

HINTS FOR PRINTING WITH SHEET FEEDERS

Printing A Range Of Pages When Using Multiple Bins

When you choose to print only some of your document pages on a printer using sheet feeders, they may not print on the paper you want. When a bin selection is not present on one of the pages you have chosen to print, **PRINT** assumes the default tray combination unless it encounters a bin selection.

WORKING WITH THE PRINTER QUEUE

QUEUE displays the list of documents and files currently in a printer's waiting list. Using it you can:

- Select a document to print next.
- Cancel a print request.
- Change the form name currently used on the printer.
- Temporarily change the font specification for a printer. This change affects only documents **you** print and lasts until you exit AlphaWRITE.
- See a continuously updated list of documents waiting to print.

Displaying the Printer's Queue

From either the Editing Menu or Main Menu:

1. Type **QUEUE** [RETURN].

2. In response to Enter Printer Number, type the number corresponding to the printer you want to work with and press [RETURN]. (If no printer list appears, either no printers are defined for AlphaWRITE's use, or only one printer is defined.)

   If there are more documents waiting to print than fits on your screen, scroll through the list by pressing [↑] or [↓].

3. To exit from the AlphaWRITE Printer Queue Maintenance screen press [MENU], or [CANCEL].

Removing a Document From the Printer's Queue

From **QUEUE**'s Enter Printer Option prompt:

1. Type **R** [RETURN] to select the Remove option.

2. At the Enter Number of Selected File prompt, type the document number corresponding to the document (or file) you want to remove and press [RETURN].

Choosing a Document to Print Next

From **QUEUE**'s Enter Printer Option prompt:

1. Type **S** [RETURN] to select the Select option.

2. At the Enter Number of Selected File prompt, type the document number corresponding to the document (or file) you want to print next and press [RETURN].

Choosing a New Form Name for This Printer

From **QUEUE**'s Enter Printer Option prompt:

1. Type **M** [RETURN] to select the Mount option.

2. At the Enter Name of New Form prompt, type the form name and press [RETURN].

You can set a new form name only on your computer's local printers. You cannot set a new form name on a printer networked to your computer.

Changing the Font Cartridge, Print Wheel or Thimble Setting

From **QUEUE**'s Enter Printer Option prompt:

1. Type **F** [RETURN] to select the Font option.

2. At the prompt requesting the font cartridge, print wheel or thimble type, type the number(s) corresponding to the element(s) you want and press [RETURN]. The numbers are shown below, in the column at the left of the description.

Changes you make via the font option are in effect only for documents **you** print and last until you exit AlphaWRITE.

TYPE	AM-302 & DIABLO PRINTERS
1	Diablo 88 WP (metal 88)
2	Diablo 88 LEGAL (metal 88)
3	96 COMM (metal 96)
4	Diablo 96 WP (metal 96)
5	Diablo USASCII A (plastic 96)
6	Diablo US LEGAL (plastic 96)

TYPE	AM-306 & NEC PRINTERS
1	ASCII 2
2	Multilingual A
3	Legal A
4	Proportional spacing
5	Word processing
6	Not assigned

TYPE	HP CARTRIDGE
A	Courier 1
B	TMS Prop 1
C	Int'l 1
D	Prestige Elite
E	Letter Gothic
F	TMS Prop 2
G	Legal Elite
H	Legal Courier
I	Pacific Data†
J	Math Elite
K	Math TMS
L	Courier P & L
M	Prestige Elite
N	Letter Gothic
O	Unassigned
P	TMS RMN P & L
Q	Memo 1
R	Presentations
S	Report 1

†25 in 1 cartridge.

TYPE	HP CARTRIDGE
T	Tax 1
U	Forms Port
V	Forms Land
W	OCR A
X	OCR B
Y	PC Courier
Z	Microsoft
0	Pro Collection
1	P. Worksheets
2	WordPerfect
3-9	Unassigned

Font (typeface) changes for HP printers should have matching settings here on the **QUEUE** font selection and in your document made with the [STYLE] typeface option.

Typeface settings for PostScript or PostScript-compatible printers require only a [STYLE] typeface setting, no change with the **QUEUE** font option is necessary.

PREVIEWING A DOCUMENT

AlphaWRITE's **PREVIEW** command gives you the opportunity to see how **PRINT** will arrange your document's text before sending it to a printer. As of AlphaWRITE 2.1A, **PREVIEW** is operational on computers where AMIGOS (**A**lpha **Mi**cro **G**raphics **O**perating **S**ystem) is up and running, when you are using an AMIGOS-compatible terminal such as the AM-72.

If you use **PREVIEW** on an unsupported terminal, AlphaWRITE displays an error message.

Using the PREVIEW Command

The **PREVIEW** command's operation is similar to the **PRINT** command's.

From the Editing Menu,

1. Type **PREVIEW** and press [RETURN].

2. Select the printer number whose output you want **PREVIEW** to image for you and press [EXECUTE].

3. The **PREVIEW** command screen behaves in the same way **PRINT**'s does; however, some fields are not used. **PREVIEW** disregards the "Disk output only," "One page at a time," "Use cut sheet feeders," and "Number of copies" fields and lets you skip over them.

4. Press [EXECUTE] to signal you are through making selections and want the command to process.

5. **PREVIEW** displays your document's graphic footprint on a background the relative shape of the page size you have defined in your format settings.

   Bold, italic, underlining, and graphics features are depicted. Text set in 18 points or larger is shown legibly.

6. Press [SPACEBAR] to see the next page of your document. When you reach the end, press any key to return to document display.

   Use [CANCEL] to halt the command and return to your document display.

CHAPTER SEVEN
PRINTING FEATURES

Chapter Seven contains information about these topics:

- Setting Typeface and Typesize
- Printing Page Overlays
- Using Special Printing Features
- Drawing Boxes and Lines

SETTING TYPEFACE AND TYPESIZE

Setting or Changing Typeface on Laser Printers

A typeface you select remains in effect until you change it. You can switch between the typefaces available throughout a document, even switch typefaces on a single line.

From Text Display:

1. Position the cursor at the beginning of your document to affect your whole document. Or, position the cursor at the column and line where you want the change in typeface to take effect.
2. Press STYLE.
3. At the Enter Code prompt, type **2** to select Typeface.
4. Type the letter corresponding to the typeface you want to use:

TYPE	TYPEFACE	TYPE	TYPEFACE
A	Avant Garde	L	Ltr Gothic
B	Bookman	M	Coronet
C	Courier*	N	New Century
D	Dingbats	O	Optima
E	Prestige	P	Palatino
F	Broadway	R	Bodoni

TYPE	TYPEFACE	TYPE	TYPEFACE
G	Garamond	S	Symbol
H	Helvetica	T	Times Roman
I	Helv-Narrow	U	University
J	Cooper	V	Line Printer
K	Presentation	Z	Zapf-Chancery

***** The PostScript Courier typeface is implemented differently than other typefaces accompanying a PostScript printer. In older versions of PostScript Courier, certain characters are unavailable: Upper and lower case AE ligature, one-half symbol, one-quarter symbol, copyright mark, registered mark, and trademark.

Appendix F - "Sample Font Families" illustrates the PostScript typefaces listed above.

Selections Q, W, X and Y are user-defineable. See your System Operator for information about what these selections will do. System Operator: refer to Appendix I - "User Defined Functions" for more information.

Not all typefaces may appear on your menu, nor may all typefaces be available to you on your printer. If there is a FONT command in your AlphaWRITE initialization file, it defines the typefaces (fonts) available to you and the typefaces displayed here on this menu.

If you are using an HP laser printer, a font cartridge (typeface) selection with the STYLE key may also require a change to the font cartridge currently installed on the printer. See Chapter 6 which contains instructions for using the **QUEUE** command's Font option to change your printer's font cartridge (typeface) setting.

Setting Typefaces on Impact Printers

The method of setting typefaces for impact printers, as described below, works only with printers supporting multiple fonts **without** requiring any physical change to the printer—such as mounting a new printwheel. The typeface options 0-9 lets you mix fonts within your document, even on the same line. From Text Display:

1. Position the cursor at the beginning of your document to affect your whole document. Or, position the cursor at the column and line where you want the change in font to take effect.

2. Press STYLE.

3. At the Enter Code prompt, type **2** to select Typeface.

4. Type the number corresponding to the font you want to use. Valid responses are 0 to 9. Your System Operator can tell you what fonts are available on your impact printer and which value (0 to 9) corresponds to a particular font.

If you select a laser printer typeface or a font number which is not available on your printer, your document prints using the default font for your printer. If you send this document to a laser printer, setting a font number will not be understood and your document will print using the default typeface used by the the laser printer.

Setting Typesize

Laser printers allow you to select typefaces and typesize. AlphaWRITE uses a default size of 10 points. You can change the typesize any time for your entire document, or for sections, or even within a single line.

From Text Display:

1. Position the cursor where you want the change in point size to take effect. Position the cursor at the beginning of your document to affect the whole document.

2. Press [STYLE].

3. At the Enter Code prompt, type **3** to select Typesize option.

4. At the Enter Typesize prompt, type the point size you want to use and press [RETURN]. 10 and 12 are the most common sizes but you can specify any whole number from 1 to 999. AlphaWRITE knows the number you enter is in points so you do not have to specify a unit of measurement.

Some sample typesizes:

This is Helvetica typeface using a typesize of 16.
This is Helvetica typeface using a typesize of 14.
This is Helvetica typeface using a typesize of 12.
This is Helvetica typeface using a typesize of 10.
This is Helvetica typeface using a typesize of 8.
This is Helvetica typeface using a typesize of 6.

On PostScript printers, any available typeface can be printed in any typesize. On non-PostScript printers, only certain typesizes are available for a given typeface. To determine typesizes available on a non-PostScript printer, look at the font cartridge installed in the printer; or, refer to documentation accompanying your printer.

PRINTING PAGE OVERLAYS

The overlay feature is available only on PostScript compatible laser printers.

AlphaWRITE’s overlay feature lets you supply a few words of text to be printed and centered diagonally across the page in a gray print style. This feature is useful for printing documents with a printed notation such as "CONFIDENTIAL" or "DRAFT", and so on.

From Text Display:

1. Position cursor at the beginning of your document to cause the overlay to print on all pages from beginning to end. Or, position the cursor **before** the page break of the page where you want page overlay printing to begin.

2. Press [EMBED].

3. Type **A** to select pg overlay.

4. Type the text you want printed as an overlay. The maximum number of characters is approximately 20. The exact number you can use depends on the width of the characters you've chosen, since the overlay prints using a proportional Helvetica typeface.

5. Press [EXECUTE] or [EMBED] to return to Text Display.

An instruction to print a page overlay remains in effect for your entire document unless you explicitly tell AlphaWRITE otherwise.

Printing Page Overlays for only Part of A Document

When you want a page overlay for only a few pages of your document, from Text Display:

1. Position the cursor **before** the page break of the page where you want page overlay printing to begin.

2. Press [EMBED].

3. Type **A** to select pg overlay.

4. Type the text you want printed as an overlay. The maximum number of characters is approximately 20. The exact number you can use depends on the width of the characters you've chosen, since the overlay prints using a proportional Helvetica font.

5. Press [EXECUTE] or [EMBED] to return to Text Display.

6. Move the cursor to a line **before** the page break of the page you want to print without an overlay.

7. Press [EMBED].

8. Type **A** to select pg overlay.

9. Make no entry to the overlay embedded screen; leave it blank.

10. Press [EXECUTE] or [EMBED] to return to Text Display.

Page Overlay Printed Appearance

Overlay text prints diagonally on your page from the bottom left to the upper right, and it automatically uses the Helvetica typeface. You cannot change the typeface overlay text uses or change its typesize.

USING SPECIAL PRINTING FEATURES

AlphaWRITE has many special printing features letting you take advantage of your printer's capabilities.

Using a Discretionary Hyphen

The discretionary hyphen feature inserts optional hyphens into words. When a word containing a discretionary hyphen does not entirely fit on a line when a paragraph is formatted, the word is divided between two lines at the discretionary hyphen and a visible hyphen appears.

If the word does not need to be divided to fit on a line, the discretionary hyphen is ignored and no visible hyphen appears.

To use it, from Text Display:

1. Position cursor on character which is to follow the hyphen.
2. Press [ESC] [–].
3. Reformat paragraph using [FORMAT] or **FORMAT** command.

You can delete a discretionary hyphen with [CHAR DEL].

Underlining Text

AlphaWRITE's underlining feature lets you instruct your printer to underline parts of your document when printing. You can use [UNDER] as you are entering text or go back after text entry and use it afterward.

To use it, from Text Display:

1. Position cursor where you want underline to begin.
2. Press [UNDER].
3. Move cursor where you want underline to end.
4. Press [UNDER].

You can delete an underline character with [CHAR DEL].

Underline is always done in pairs—one to begin, one to end.

Using Print Emphasis Features

AlphaWRITE has many special print emphasis features, most of which are used in pairs.

To use print emphasis, from Text Display:

1. Position cursor where you want print emphasis to begin.
2. Press STYLE.
3. At the Enter Code prompt, type the number corresponding to the print feature you want to use:

STYLE FEATURE	TYPE CODE	SAMPLE
Bold	1	**Bold text**
Italic[1]	4	*Italic text*
Reverse[1]	5	Reverse text
Screened[1]	6	Screeened text
Strikeout	7 then strikeout character	~~Strikeout with slash~~
Overbar	8	$\overline{\text{Overbar text}}$
Double underscore[2]	9	Double Underscore
Gray	0	Gray text-40%
Outline Fonts[1]	F	16 pt Helvetica

[1]Only available on some laser printers.
[2]Available on impact printers if printing element is capable of printing this character.

4. Move cursor to where print emphasis ends.
5. Press STYLE.
6. Type the same number as you selected to begin the print feature. If you select strikeout, type the same character you used to begin strikeout.

You can delete any print emphasis feature with CHAR DEL.

Gray Shading

Gray shading affects the darkness of the STYLE key's gray print feature (option 0); gray shading does not affect any other feature. Gray print must be in effect in your document, or you will not see any result from choosing a different degree of darkness with LAYOUT's Set Gray option.

To use the set gray shading option, from Text Display:

1. Position cursor where you want the change in shading to be in effect.
2. Press LAYOUT.
3. At the Enter Code prompt, type **8** to select Set Gray.
4. At Shading prompt, enter a percentage value, in whole numbers to determine the intensity of gray shading and press RETURN:

TYPE	GRAY PRINT RESULT
100	One hundred percent gray (black)
75	Seventy-five percent gray
50	Fifty percent gray
25	Twenty-five percent gray
10	Ten percent gray

The closer to 100, the blacker the text. The closer to 0, the lighter the text.

If you change the gray setting from 100 percent, be sure to return it to 100 when you are through.

Using Keycap

AlphaWRITE lets you insert text within a keycap box, just like the keycaps you see in this documentation. The keycap feature is available on PostScript compatible printers and only some of the other laser printers.

To use the keycap feature, from Text Display:

1. Position cursor where you want the keycap to begin.
2. Press STYLE.
3. At the Enter Code prompt, type **E** to select Key.
4. Move cursor to where you want the keycap to end.
5. Press STYLE.

6. At the Enter Code prompt, type **E** to end the keycap.

You can delete the information blocks invoking the keycap with [CHAR DEL].

You can adjust the amount of white space between the keycap box and the text it contains. Insert a required space ([FUNCT] [SPACEBAR]) before and after the keycap text. You can prevent multi-word keycap text from being split between two lines by using required spaces to separate the words.

Printing One Character Over Another

You can print one character over another, to do so from Text Display:

1. Position cursor on character (or space) immediately following the one you want printed over with another character.
2. Press [STYLE].
3. At the Enter Code prompt, type **B** to select Overprint.
4. Next to the information block that appears, type character to be used to overprint the previous character.

Selecting Ribbon Color

You can select a particular ribbon color to use for your text, if your printer supports multi-colored ribbons.

To do so, from Text Display:

1. Position the cursor where you want to set ribbon color. To select a color for your whole document, position cursor at beginning of document.
2. Press [STYLE].
3. At Enter Code prompt, press [A] to select Type Color.
4. At Enter Code prompt, type the number corresponding to the ribbon color you want to use:

RIBBON COLOR	TYPE	RIBBON COLOR	TYPE
Black	1	Orange	5
Blue	2	Violet	6
Red	3	Green	7
Yellow	4	Brown	8

5. Move cursor where you want color to end and repeat steps 2 and 3 for a new color.

User Definable Features

The user definable features are available to customize the way AlphaWRITE is used on your computer; they may or may not be currently defined. However, if they are, see your System Operator who can tell you what features are associated with each option, and give you instructions for their use.

To access the features that may be defined specifically on your system, from Text Display:

1. Position cursor.
2. Press [LAYOUT].
3. Type the letter corresponding to the option you want to use:

OPTION	TYPE
User 1	A
User 2	B
User 3	C
User 4	D

Appendix I - "User Defined Functions" provides information about creating user defined features.

Using a Required Space

A required space—sometimes called a non-breaking space or a non-expandable blank—inserts a necessary blank space to separate characters. It is considered a part of the text and can prevent text from being split between two lines.

To use it, from Text Display:

1. Position cursor where you want to insert a required space.
2. Hold down [FUNCT] then press [SPACEBAR]

You can delete a required space with [CHAR DEL].

Subscripting and Superscripting Text

The superscript feature lets you print sections of text a ½ line above the rest of the text line. It is also used to end subscripted portions of text.

The subscript feature causes text to print a ½ line below the rest of the text line and is used to end superscripted portions of text.

You can cause printing to occur in multiples of half lines by inserting more than one instruction. However, you must use the opposite instruction the same number of times to return printing back to the base line.

To use superscripting or subscripting, from Text Display:

1. Position cursor where you want to begin.
2. Press STYLE.
3. Type the letter corresponding to the feature you want to use:

FEATURE	TYPE	EXAMPLE
Superscript	C	$\text{Super}_{\text{script}}$
Subscript	D	$\text{Sub}^{\text{script}}$

4. Move cursor to end of text to be affected.
5. Press STYLE.
6. To end superscript type **D** to select subscript.
   to end subscript, type **C** to select superscript.

Superscript is shown on your screen as an up arrow; a subscript is shown as a down arrow. You can delete either instruction by positioning the cursor on the arrow and pressing CHAR DEL.

Using Special Print Characters

Special print characters are not available on all printers. In fact, some are available only on laser printers—they are marked with a dagger (†) in the list below.

To use a special character, from Text Display:

1. Position cursor where you want symbol to print.
2. Press SPEC CHAR.
3. At Enter Code prompt, type the number or letter corresponding to the character you want to print:

DESCRIPTION	EX.	TYPE CODE
Degree	°	1
Paragraph	¶	2
Dagger	†	3
Section	§	4
Cent	¢	5
Quarter Fraction[1]	¼	6
Half Fraction[1]	½	7
Trademark[1]	™	8
Copyright[1]	©	9
Registered[1]	®	0
Star[2]	★	A
Bullet[2]	●	B
Em Dash[2]	—	C
En Dash[2]	–	D
Extended Character [2]	none	E[3]

[1] These characters are not directly present in the PostScript Courier typeface.
[2] Available only on laser printers.
[3] At prompt for Extended Character Code, type the number associated with the extended character in the typeface you are using and press RETURN. AlphaWRITE has built-in extended characters for use on PostScript Laser printers; this is described in the next section. See Appendix M - "Special Character Key: Option E - Extended Character" for a list of other codes available and their printed result.

Built-In Extended Characters

The SPEC CHAR key's Extended Character option E introduces 15 new built-in symbols for use on PostScript printers. Designed for software documentation needs, the symbols depict terminal screen display attributes. The chart below shows the code you type at the Extended Character Code prompt to request the symbol described. An example of each symbol is printed in the last column:

CODE	DESCRIPTION	EXAMPLE
1	Control symbol	▲
2	Split bar	¦
3	Cursor	▉
4	Small box	▫
5	Big box	□
8	Left arrow	←
9	Tab symbol	⇥
10	Down arrow (subscript)	↓
11	Up arrow (superscript)	↑

CODE	DESCRIPTION	EXAMPLE
12	Right arrow	→
13	End of paragraph marker	◄
17	Long shaded box	▒
19	Information block	▒
22	Underscore	_
24	Cross-hatched block	▓

Deleting Special Characters

To delete any special character, at Text Display:

1. Position the cursor on the special character symbol.
2. Press [CHAR DEL].

Turning Off/On Information Block Display

Most special print instructions insert an information block into your document's text. Other features also insert information blocks into your text. You can turn off or turn on the display of these special symbols.

To do so, from Text Display press [SHIFT] [↓]. Repeat this procedure to reverse the effect.

Composing Characters

AlphaWRITE's Compose Character feature makes international symbols, and characters—such as yen, umlaut, ligatures— available for display and printing. These characters belong to the ISO Latin I character set of which ASCII characters are a subset.

If you are using an AM-65 terminal, the Compose Character feature causes the international character to be visible on your screen as well as being printed in your document.

If you don't have an AM-65 terminal, not to worry. Although the international character you enter may not display as the symbol you request, a message on the status line tells you an international character is located at this cursor position and you see a character as much like your request as your terminal is capable of displaying.

Not all printers or printer drivers support the international characters you can compose. If this happens, AlphaWRITE displays a message telling you so when you **PRINT** your document. See Appendix P - "ISO Latin I Characters and Laster Printing" for information on character printing availability.

Using AlphaWRITE's Compose Character Feature

To use the Compose Character feature:

1. Press [ESC] and release it, press [`] (accent grave) and release it.

2. Then type the characters you want to use, as shown in the chart below. For example, press [A] ["] to print an A umlaut, or [o] [~] to print o tilde, and so on; the two keys you press signal composition of the new character.

   Typically, capitalization is important when you are entering the two-characters following [ESC] [`]. However, AlphaWRITE is not sensitive to the order in which you type the two characters, it interprets ["] [A] and [A] ["] to mean A umlaut.

Compose Character Chart

Use the following chart to find the character you want to use and the keys to press to get that character. In some cases, AlphaWRITE cannot display the complete character description as shown and when this occurs AlphaWRITE abbreviates the message it displays. Text shown in parentheses in column one in following chart gives you the abbreviation AlphaWRITE displays.

For legibility, only [ESC] and [SPACEBAR] are shown within keycaps; the other keys you press are shown in Courier bold type separated by spaces. Do not press [SPACEBAR] unless the chart specifically tells you to do so; the spaces in the key list are for format only. In most cases, the names of the two keys to press follow in parentheses after the [ESC] ‘ (accent grave) keys.

CHARACTER/ MESSAGE TEXT	PRESS THESE KEYS (key name/key name)
Required Space	ESC ' SPACEBAR SPACEBAR
Inverted Exclamation (Inv. Exclam.)	ESC ' ! ! (exclamation/exclamation)
Cents	ESC ' c / (c/slash)
Cents	ESC ' C / (C/slash)
Sterling	ESC ' l - (l/hyphen)
Sterling	ESC ' L - (L/hyphen)
Currency	ESC ' x o (x/o)
Currency	ESC ' X O (X/O)
Yen	ESC ' y = (y/equal)
Yen	ESC ' Y = (Y/equal)
Split Bar	ESC ' | | (split bar/split bar)
Section	ESC ' s o (s/o)
Section	ESC ' S O (S/O)
Umlaut[1]	ESC ' " " (double quote/double quote)
Copyright	ESC ' c o (c/o)
Copyright	ESC ' C O (C/O)
Ord Feminine	ESC ' a _ (a/underline)[6]
Ord Feminine	ESC ' A O (A/O)
Left Guillemot	ESC ' < < (left angle/left angle)
Not	ESC ' - , (hyphen/comma)
Discretionary Hyphen (Disc Hyphen)	ESC ' - - (hyphen/hyphen)
Registered	ESC ' r o (r/o)
Registered	ESC ' R O (R/O)

CHARACTER/ MESSAGE TEXT	PRESS THESE KEYS (key name/key name)
Macron (Hyphen)	ESC ' _ + (underline[6]/plus)
Ring[2]	ESC ' SPACEBAR * (asterisk)
Plus or Minus	ESC ' + - (plus/hyphen)
Raised 2	ESC ' 2 ^ (2/caret)
Raised 3	ESC ' 3 ^ (3/caret)
Acute Accent	ESC ' ' ' (single quote/single quote)
Micro	ESC ' / u (slash/u)
Micro	ESC ' / U (slash/U)
Paragraph[3]	ESC ' p ! (p/exclamation)
Paragraph[3]	ESC ' P ! (P/exclamation)
Raised Dot	ESC ' . ^ (period/caret)
Cedilla	ESC ' , , (comma,comma)
Raised 1	ESC ' 1 ^ (1/caret)
Ord Masculine	ESC ' o _ (o/underline[6])
Ord Masculine	ESC ' O _ (O/underline[6])
Right Guillemot	ESC ' > > (right angle/right angle)
One-quarter	ESC ' 1 4 (1/4)
One-half	ESC ' 1 2 (1/2)
Three-quarters	ESC ' 3 4 (3/4)
Inverted Question (Inv. Quest.)	ESC ' ? ? (question/question)
A grave	ESC ' A ' (A/accent grave)
A acute	ESC ' A ' (A/single quote)

CHARACTER/ MESSAGE TEXT	PRESS THESE KEYS (key name/key name)
A caret	ESC ‘ A ^ (A/caret)
A tilde	ESC ‘ A ~ (A/tilde)
A umlaut[1]	ESC ‘ A " (A/double quote)
A ring	ESC ‘ A * (A/asterisk)
AE ligature	ESC ‘ A E (A/E)
C cedilla	ESC ‘ C , (C/comma
E grave	ESC ‘ E ‘ (E/accent grave)
E acute	ESC ‘ E ’ (E/single quote)
E caret	ESC ‘ E ^ (E/caret)
E umlaut[1]	ESC ‘ E " (E/double quote)
I grave	ESC ‘ I ‘ (I/accent grave)
I acute	ESC ‘ I ’ (I/single quote)
I caret	ESC ‘ I ^ (I/caret)
I umlaut[1]	ESC ‘ I " (I/double quote)
Eth	ESC ‘ - D (hyphen/D)
N tilde	ESC ‘ N ~ (N/tiled)
O grave	ESC ‘ O ‘ (O/accent grave)
O acute	ESC ‘ O ’ (O/single quote)
O caret	ESC ‘ O ^ (O/caret)
O tilde	ESC ‘ O ~ (O/tiled)
O umlaut[1]	ESC ‘ O " (O/double quote)
Multiplication[4]	ESC ‘ X X (X/X)
O slash	ESC ‘ O / (O/slash)

CHARACTER/ MESSAGE TEXT	PRESS THESE KEYS (key name/key name)
U grave	ESC ‘ U ‘ (U/accent grave)
U acute	ESC ‘ U ’ (U/single quote)
U caret	ESC ‘ U ^ (U/caret)
U umlaut[1]	ESC ‘ U " (U/double quote)
Y acute	ESC ‘ Y ’ (Y/ single quote)
Thorn	ESC ‘ T H (T/H)
Ess Tset[5]	ESC ‘ S S (S/S)
a grave	ESC ‘ a ‘ (a/accent grave)
a acute	ESC ‘ a ’ (a/single quote)
a caret	ESC ‘ a ^ (a/caret)
a tilde	ESC ‘ a ~ (a/tilde)
a umlaut[1]	ESC ‘ a " (a/double quote)
a ring	ESC ‘ a * (a/asterisk)
ae ligature	ESC ‘ a e (a/e)
c cedilla	ESC ‘ a , (a/comma)
e grave	ESC ‘ e ‘ (a/accent grave)
e acute	ESC ‘ e ’ (e/single quote)
e caret	ESC ‘ e ^ (e/caret)
e umlaut[1]	ESC ‘ e " (e/double quote)
i grave	ESC ‘ i ‘ (i/accent grave)
i acute	ESC ‘ i ’ (i/single quote)
i caret	ESC ‘ i ^ (i/caret)
i umlaut[1]	ESC ‘ i " (i/double quote)

CHARACTER/ MESSAGE TEXT	PRESS THESE KEYS (key name/key name)
eth	ESC ‘ - d (hyphen/d)
n tilde	ESC ‘ n ~ (n/tilde)
o grave	ESC ‘ o ‘ (o/accent grave)
o acute	ESC ‘ o ’ (o/single quote)
o caret	ESC ‘ o ^ (o/caret)
o tilde	ESC ‘ o ~ (o/tilde)
o umlaut[1]	ESC ‘ o " (o/double quote)
Division	ESC ‘ - : (hyphen/semi-colon)
o slash	ESC ‘ o / (o/slash)
u grave	ESC ‘ u ‘ (u/accent grave)
u acute	ESC ‘ u ’ (u/single quote)
u caret	ESC ‘ u ^ (u/caret)
u umlaut[1]	ESC ‘ u " (u/double quote)
y acute	ESC ‘ y ’ (y/single quote)
thorn	ESC ‘ t h (t/h)
y umlaut[1]	ESC ‘ y " (y/double quote)

1 Also known as *dieresis*.
2 Also known as *degree*.
3 Also known as *pilcrow*.
4 Also known as *times*.
5 Also known as *German double s*.
6 The underline character is usually located on the same key as hyphen, in the shifted position; underline is not the same as the UNDER function key.

DRAWING BOXES AND LINES

AlphaWRITE’s graphic features lets you take advantage of special printing capabilities on your laser printer.

Graphic printing features are invoked by using the LAYOUT key’s graphic option and each is assigned an element number. Element numbers are described first and are followed by instructions for each graphic feature.

What Are Element Numbers?

Lines and boxes are drawn using a pair of instructions; one to begin, one to end. For each pair of instructions you use, you are asked to assign that pair one element number, in the range 1 to 9. This system of element numbers serves two purposes:

- Using element numbers lets you overlap more than one line or box in the same area of the page.
- Element numbers let AlphaWRITE keep track of which pair of instructions are beginning and/or ending.

Element numbers are reuseable. AlphaWRITE "reads" the graphic instructions line by line: from left to right, top to bottom. Once AlphaWRITE has read the begin **and** end instruction associated with an element number, the element number becomes eligible for re-use.

Remember, an element number cannot be re-used until AlphaWRITE has encountered both its begin and end graphic instruction. Otherwise, AlphaWRITE warns you of the conflict with an error message at print time and your graphic will not print correctly.

For example, suppose you wanted to draw four horizontal lines, from column 10 to column 20, on lines 1, 2, 3 and 4 of your document. Although you could assign four different element numbers to each pair of lines, you could also legally assign the element number 1 to all four lines. This re-use of element number 1 is legal because AlphaWRITE "read" left to right and found the begin and end instruction for the first line associated with element number 1 **before** encountering the second line associated with element number 1.

On the other hand, suppose you wanted to draw four vertical lines, from line 3 to line 13, at columns 15, 30, 45 and 60. Because of the way AlphaWRITE reads the instructions, from left to right, top to bottom, it finds all four begin instructions at columns 15, 30, 45 and 60 on line 3 before any end instructions are encountered on line 13. Consequently, four **different** element numbers must be used to draw these lines.

Drawing A Line

To draw a line in your document, from Text Display:

1. Press [TAB] to position cursor at the column where you want the line to begin. Set tabs with [MARGIN] according to where you want your printed output to appear.
2. Press [LAYOUT].
3. At the Enter Code prompt, type **0** to select Graphics.
4. At the Enter Code prompt, type **1** for begin line.
5. In response to the Number prompt, type a number in the range 1 to 9. The element number cannot already be in use.

6. Use [TAB] to position cursor where you want the line to end.

7. Press [LAYOUT].

8. At the Enter Code prompt, type **0** to select Graphics.

9. At the Enter Code prompt, type **2** to end line.

10. In response to the Number prompt, type the same element number you assigned in step 5.

Drawing A Box

To draw a box in your document, from Text Display:

1. To ensure the drawn box prints where you expect it and in the dimensions you want, set tabs accordingly with [MARGIN].

2. Use [TAB] to position cursor at the upper left corner of where you want box to be drawn.

3. Press [LAYOUT].

4. At the Enter Code prompt, type **0** to select Graphics.

5. At the second Enter Code prompt, type the number associated with the type of box you want to begin:

BEGIN BOX	TYPE
Square corner	3
Round corner	5
Gray square corner	7

6. At the Number prompt, type the element number you want to assign to this pair of begin and end instructions for drawing the box.

7. Move the cursor to the line where you want the box to end by pressing [RETURN] or [↓]. Then, press [TAB] to position the cursor on the column where you want the lower right corner of the box to end.

8. Press [LAYOUT].

9. At the Enter Code prompt, type **0** to select Graphics.

10. At the Enter Code prompt, type the number to end the box that corresponds to the kind of box you selected in step 4. Do not mix and match the begin and end codes; mismatched pairs of instructions will give undefined results.

END BOX	TYPE
Square corner	4
Round corner	6
Gray square corner	8

11. In response to Number, type the same element number you assigned in step 5.

Setting Line Weight for Graphics

Setting line weight affects the line thickness used in lines and boxes drawn with the LAYOUT key's graphic option. Changing line weight does not affect the underscore feature.

To set line weight, from Text Display:

1. Position cursor where you want the change in line weight to take effect.

   The line weight in effect at the **end** graphics instruction determines the line weight used to draw the line or box.

2. Press LAYOUT.

3. At the Enter Code prompt, type **9** to select Line Weight.

4. At Enter Weight prompt, enter a number and press RETURN. The number value is understood in points unit of measurement, the default value is one point. The legal point values can range from .001 to 9999.999. The default line weight is 1 point.

SETTING	RESULT
Line weight 1 pt.	
Line weight 2 pts.	
Line weight 4 pts.	
Line weight 8 pts.	

5. It's a good idea to return to the line weight to 1 point when you are through, that way you always know what the current line weight is.

HINTS FOR USING GRAPHICS

Set Tabs

To ensure you get the printed results you want with drawing boxes and lines, be sure you set tabs and use [TAB] to align text. Do not use blank spaces made by using the space bar.

Although using tabs is not imperative when you use non-proportional typefaces, such as Courier, it is imperative when you use proportional typefaces like Helvetica, New Century Schoolbook, and so on. For consistent results, always begin and end graphics instructions on left tab settings.

Page Breaks and Graphics

Most laser printers cannot understand draw box and line instructions that span page breaks. If this occurs in your document, your printed result will not be what you expect. Be sure a box or line you draw is begun and ended all within the same page before printing. Use **PAGINATE** before you print to troubleshoot any potential difficulties.

RESUME PRINT AT TOP OF PAGE

The [PAGE] key's option 4 "resume at top of page" allows you to give AlphaWRITE a print instruction for making columns of text. The resume at top of page option tells AlphaWRITE's **PRINT** command to return to the previous page break and print the text on the lines following the resume instruction, at the top of the previous page. This feature is operative only on laser printers.

Intervening soft page breaks interfere with the resume print at top of page feature; be sure there are no intervening page breaks between the resume information block and the previous page break where you want printing to begin from.

Generally, the resume at top of page feature is used once your text is finalized and you will not be doing any more editing. Adding or deleting lines causes a change in where second column printing occurs, so work with text you do not intend to change overmuch, if at all.

To use resume at top of page, from text display:

1. Position the cursor before the line you want printed at the top of the page; the line which will be the first line of the second column.

2. Use [MARGIN] to set a left margin suitable for the second column of text. You could also use the left paper offset format setting to obtain a suitable column position.

2. Press the [PAGE] key.

3. In response to the Enter code: prompt, type **4** [RETURN].

4. Text following the resume instruction will print beginning from the previous page break remain in effect until it encounters the next page break.

CHAPTER EIGHT
FOOTNOTES, TITLES, FOOTERS AND USING PAGE AND CHAPTER NUMBERS

Chapter Eight describes:

- Making Footnotes
- Making Titles
- Making Footers
- Working with Page and Chapter Numbers

MAKING FOOTNOTES

AlphaWRITE's footnote feature lets you enter text which is automatically included as reference text at either the bottom of a document page or the end of your document. Footnotes can be pages long or only a few lines, and can be edited like regular document text.

Creating a Footnote

To create a footnote, from Text Display, position cursor on line and column for the footnote location:

1. Type a character to identify this footnote, for example, an asterisk.
2. Press [EMBED].
3. At Enter Code prompt, **0** to select footnote option.
4. At footnote embedded text screen, type text of your footnote. Be sure to use [RETURN] to signal end of paragraphs or a single line.
5. When complete, press [EMBED] or [EXECUTE] to return to Text Display.

Setting Footnote Options

Footnote format options are available on the Document Header only. To make changes to these options, from Text Display:

1. Press [MENU] to display the Editing Menu.
2. At the Editing Menu, type **`header`** [RETURN].
3. Move cursor to footnote fields to change options:

FOOTNOTE SETTING	CONTROLS
Space before Footnotes	Amount of blank space preceding footnote line separator. Default is in inches.
Footnote Print Type	Where footnotes print. **B** sets printing for bottom of page of occurrence. **E** sets printing for end of document.
Footnote Line Separator	Sets character used to print as footnote line separator. Default is underline character.

4. Press [EXECUTE] to keep your changes and return to Text Display.

HINTS FOR WORKING WITH FOOTNOTES

Footnotes and Paginate Command

Except on laser printers, you must use **PAGINATE** prior to printing a document with footnotes appearing at the bottom of the page to ensure correct placement of footnotes on your printout.

Footnote Identifiers

Footnotes are often used more than once in a document. To identify each footnote in your document, include a unique character prior to the footnote location in your document text **and** as the first character of your footnote text.

Superscripted numbers or letters are often used when there is more than one footnote; an asterisk is sometimes used when there is just one footnote.

Footnote Margin

As the first character of your footnote text display, you see a margin information block. Your footnote uses the margins, tabs and any format settings in effect where you pressed EMBED to select footnote from your document text display.

Footnotes are Embedded Text

Footnotes are embedded text and follow all the rules described in the Embedded Text Screens section of Chapter 1 "Calling Up and Exiting AlphaWRITE."

Previewing Footnote Text

The **PREVIEW** command lets you assess the cumulative printed effect and output of the footnotes in your document.

MAKING TITLES

AlphaWRITE's page title feature lets you print single or multiple lines of text as a title to print at the top of each page of your document. There are three types of titles:

- Title: prints title text on every page.
- Even title: prints title text on even numbered pages only.
- Odd title: prints title text on odd numbered pages only.

You can use these commands in any combination within your document; the most recently encountered one for a particular page is the one in effect.

Creating a Title

To create a title, from Text Display:

1. For a title to print on first page, position cursor on the first line of your document before any text.

   For a title to print on all subsequent pages except the first, position the cursor after the first text occurrence.

2. Press EMBED.

3. At the Enter Code prompt:

TYPE	TO
1	Select title option to print title text on all pages.
2	Select odd title option; print title text on odd number pages.
3	Select even title option; print title text on even number pages.

4. At embedded text display, type text you want used as the title. Press [RETURN] to signal end of lines when you are creating titles having multiple lines.

   You can enter multiple lines of text at the embedded screen; however, be sure the printed result of the text you enter does not exceed the amount of space you allocated for titles in the Document Header Title Length setting.

5. Press [EMBED] or [EXECUTE] to return to Text Display.

Setting Page Format for a Title

Page format for printed titles is available on the Document Header and Margin Format Screen.

Display the Document Header by using the Editing Menu **HEADER** command.

Move the cursor to the field whose option you want to change:

FORMAT OPTION	CONTROLS
Top Margin	Amount of blank space preceding the first line of title text.
Title Length	Amount of space reserved to print your title text.

These settings are also available from the Margin Format Settings screen. But, if changes are made via the Margin Format screen, they will be in effect for only as long as that margin remains in effect.

HINTS FOR WORKING WITH TITLES

Page and Chapter Numbers

To include the page number in a page title, type sign (#), or in the UK, type pound sterling (£), at the line position where you want the page number to appear within the title text.

If you are using chapters, type the percent sign (%) where you want the chapter number to appear within the title text.

Even and Odd Titles

To print different titles on odd and even numbered pages use a combination of an odd title command and an even title command.

Titles are Embedded Text

Titles are embedded text and follow all the rules described in the Embedded Text Screens section of Chapter 1 "Calling Up and Exiting AlphaWRITE"

Title Word Wrap and Formatting

Unlike other embedded text screens, text entered at title and footer embedded text screens will not automatically wrap around to the next line when you reach the right margin. For this reason, [FORMAT] and **FORMAT** will have no affect on title and footer embedded text.

To make a new title or footer line, press [RETURN] where you want one line to end and then continue typing on the next line.

Title Margin

When the title display first appears, it uses the default margin settings. To use the margin settings in effect for your document, use [MARGIN] and select the **S** option to invoke your currently set margins.

Typeface and Typesize

If a title information block appears as the first character of your document, before a typeface or typesize information block, the title text prints using the default Courier typeface and default 10 pt. typesize.

Previewing Title Text

The **PREVIEW** command lets you assess the cumulative printed effect and output of the title in your document.

Importing Images

Titles do not allow you to import image or other files with the import feature [ESC] [/].

MAKING FOOTERS

AlphaWRITE's page footer feature lets you print single or multiple lines of text to print at the bottom of each page of your document. There are three types of footer commands:

- Footer: prints footer text on every page.
- Even footer: prints footer text on even numbered pages only.
- Odd footer: prints footer text on odd numbered pages only.

You can use these commands in any combination within your document; the most recently encountered one for a particular page is the one in effect.

Creating a Footer

To create a footer, from Text Display:

1. Position the cursor on the page where you want footer text to first print.
2. Press EMBED.
3. At the Enter Code prompt:

TYPE	TO
4	Select footer option; print footer text all pages.
5	Select odd footer option; print footer text odd number pages.
6	Select even footer option; print footer text even number pages.

4. At embedded display, type text you want used as the footer. Press RETURN to signal end of lines when you are creating titles having multiple lines.

   You can enter multiple lines of text at the embedded screen; however, be sure the printed result of the text you enter does not exceed the amount of space you allocated for footers in the Document Header Footer Length setting.

5. To return to Text Display, press EMBED or EXECUTE.

Footers are Embedded Text

Footers are embedded text and follow all the rules described in the Embedded Text Screens section of Chapter 1 "Calling Up and Exiting AlphaWRITE"

Footer Word Wrap and Formatting

Unlike other embedded text screens, text entered at title and footer embedded text screens will not automatically wrap around to the next line when you reach the right margin. For this reason, FORMAT and **FORMAT** will have no affect on title and footer embedded text.

To make a new title or footer line, press RETURN where you want one line to end and then continue typing on the next line.

Setting Page Format for Footer

Page format settings for printed footers are available from the Document Header and Margin Format Settings Screen.

Display the Document Header by using the Editing Menu **HEADER** command. Use MARGIN to get to the Margin Format Settings screen.

Move cursor to the format field whose setting you want to change:

FORMAT OPTION	CONTROLS
Footer Length	Amount of space reserved to print your footer text.

This setting is also available from the Margin Format Settings screen. But, if it is changed there, it is only in effect for as long as that margin remains in effect.

HINTS FOR WORKING WITH FOOTERS

Placement

A footer need only appear once in your document to affect all document pages thereafter.

Typeface and Typesize

If a footer information block appears as the first character of your document, before a typeface or typesize information block, the footer text prints using the default Courier typeface and default 10 pt. typesize.

Even and Odd Footers

To print different footers on odd and even numbered pages use a combination of odd and even footers.

Page and Chapter Numbers

To include the page number in a page footer, type the number sign (#) or, in the UK, type the pound sterling (£) where you want the page number to appear within the footer text.

If you are using chapters, type the percent sign (%) where you want the chapter number to appear within the footer text.

Previewing Footer Text

The **PREVIEW** command lets you assess the cumulative printed effect and output of the footers in your document.

Importing Images

Footers do not allow you to import image or other files with the import feature [ESC] [/].

WORKING WITH PAGE AND CHAPTER NUMBERS

You request AlphaWRITE to print page or chapter numbers by including a simple code in the text of any title or footer. Numbering for chapters and pages can be set to specific numbers and you can choose from five numbering formats.

Printing a Page Number

To print page numbers, type **#**, or in the UK, type **£** in any kind of title and/or footer.

You can also include text along with the signal to print page numbers:

`Page #` or `Page £`

AlphaWRITE keeps track of the page numbers automatically. AlphaWRITE advances the page number each time it encounters a soft or hard page break in your document. You can affect this outcome by setting the page number to a specific number, discussed a little further on in this chapter.

Pound Sign or Pound Sterling as Characters

To include a pound sign (#) or, in the UK pound sterling (£) as a character and not signal a page number, type two characters with no intervening spaces, like this:

or ££

Printing a Chapter Number

To have a chapter number print, type **%** in a title or footer.

For example, the [EMBED] key's option 1 for Title might include this text so chapter numbers print:

```
Chapter %
```

AlphaWRITE keeps track of the chapter numbers automatically. AlphaWRITE advances the chapter number each time it encounters a chapter page break in your document. You can affect this outcome by setting the chapter to a specific number; this is discussed a little further on in this section.

Where page breaks determine the current page number, only chapter page breaks increment a chapter number by one.

Making a New Chapter Page Break

To begin a new chapter, which will advance the chapter number by one and reset the page number to one, from Text Display:

1. Position the cursor where you want the chapter page break.
2. Press LAYOUT.
3. At the Enter Code prompt, type **4** to select New Chapter.
4. A new chapter page break appears in your document. It behaves like a hard page break.

Printing A Page and Chapter Number Together

If you want the currently set chapter and page number to print in a title or footer, type **%** along with **#**, or in the UK, **£**. For example, you might choose a numbering scheme to print the chapter number, a dash then the page number:

`Page %-#` or `Page %-£`

Percent Sign as Character

To include a percent sign (%) as a character and not signal a chapter number, type two percent signs with no intervening spaces, like this:

%%

Selecting Page and Chapter Number Style

AlphaWRITE automatically uses arabic numerals for page and chapter numbering unless you specifically tell it to do otherwise.

To select a particular page and chapter numbering style, from Text Display:

1. Position cursor at beginning of document to affect the whole document, or preceding the first occurrence of the page or chapter number you want to effect.

2. Press LAYOUT.

3. At the Enter Code prompt, type **1** to select Set Page # Style.

4. At the Set Numbering Style prompt, the cursor is initially positioned in the Page field.

   You can change either the page number or the chapter number, or both at this prompt.

   Use RETURN to move the cursor between the Page and Chapter fields.

5. To set the number, put the cursor in the field you want to change and type the number corresponding to the style you want to use:

STYLE	SAMPLE	TYPE
Arabic numerals	1, 2, 3...	1
Upper case alphabet	A, B, C...	2
Lower case alphabet	a, b, c...	3
Upper case roman numerals	I, II,III...	4
Lower case roman numerals	i, ii, iii...	5

Changing the style of the printed numbers does not affect how you respond to the set page number or set chapter number Layout key option, discussed in the next sections.

Even if the the page or chapter number is in a style other than Arabic numerals, you still respond with an arabic numeral to set a specific page reference.

Changing the Page Number to Specific Number

You can set a page number to a specific number or change the number that prints as the page number:

1. To make the change take effect from the beginning of your document, position cursor on document page 1. Or, position the cursor preceding the first occurrence of the page number you want to effect.

2. Press LAYOUT.

3. Type **2** to select Set Page #.

4. At the Page Number prompt, type your response and press RETURN.

TO	TYPE
Set page number to a specific number	**n** where n is the page number.
To add n to the current page number	**+n** where n is the number you want added to the current page number.
To subtract n from the current page number	**-n** where n is the number you want subtracted from the current page number.

Changing the Chapter Number

You can set a chapter number to a specific number or change the number that prints as the chapter number:

1. To make the change effect your whole document, position cursor on document page one. Or, position the cursor preceding the first occurrence of the page number you want changed.

2. Press LAYOUT.

3. Type **3** to select Set Chapter #.

4. At the Chapter No. prompt, type your response and press RETURN.

TO	TYPE
Set chapter number to a specific number	**n** where n is the chapter number.
To add n to the current chapter	**+n** where n is the number you want added to the current page number.

TO	TYPE
To subtract n from the current chapter number	**-n** where n is the number you want subtracted from the current chapter number.

Setting Non-Numeric Page References

When you are using a numbering scheme other than arabic numerals and want to set the page reference to a specific character, use the numbers below to set the specific character you want (shown as **n** in the previous discussions).

For space saving reasons, the chart reflects the numbers associated with the alphabet. If you want to use a roman numeral larger than what is shown, type the arabic equivalent of the roman numeral i.e., 50 for L or l, 100 for C or c, and so on.

1. Position the cursor where you want the change in page reference to take place. For your whole document, position the cursor at the beginning.

2. Press LAYOUT.

3. Type **2** in response to the Enter code: prompt.

4. To set a page reference to a specific character in a character style other than Arabic numerals, find the character you want to use in the chart below. Then, at the Number: prompt, type the number shown in the Type column.

TYPE	CHARACTER STYLE			
1	A	a	I	i
2	B	b	II	ii
3	C	c	III	iii
4	D	d	IV	iv
5	E	e	V	v
6	F	f	VI	vi
7	G	g	VII	vii
8	H	h	VIII	viii
9	I	i	IX	ix
10	J	j	X	x
11	K	k	XI	xi
12	L	l	XII	xii
13	M	m	XIII	xiii
14	N	n	XIV	xiv
15	O	o	XV	xv
16	P	p	XVI	xvi
17	Q	q	XVII	xvii

TYPE	CHARACTER STYLE			
18	R	r	XVIII	xviii
19	S	s	XIX	xix
20	T	t	XX	xx
21	U	u	XXI	xxi
22	V	v	XXII	xxii
23	W	w	XXIII	xxiii
24	X	x	XXIV	xxiv
25	Y	y	XXV	xxv
26	Z	z	XXVI	xxvi

When you use the LAYOUT set number option for page or chapter and want to increase or decrease the printed page or chapter reference by a certain number of pages, type the arabic numeral representing the number of pages.

HINTS FOR WORKING WITH PAGE AND CHAPTER NUMBERS

Command Placement

The page format and page number instructions take effect the next time AlphaWRITE includes a page number in your printed document. This is the footer on the page where you enter the command if a page number is specified there, or the title of the **next** page if the page number is specified in a title.

Default Page Number Format

The default page number format is arabic and the default for the first page number is 1.

CHAPTER NINE
CUT, PASTE, SEARCH, REPLACE, GLOBAL AND SPELL COMMANDS

Chapter Nine contains information about:

- Copying Text Between Documents
- Finding and Replacing Document Text
- Spell Checking Documents

COPYING TEXT BETWEEN DOCUMENTS

The two Editing Menu commands, **CUT** and **PASTE**, let you move text between documents.

CUT lets you copy a marked portion of the document you are currently editing and store it in another document. The document holding the cut text is like any other document.

PASTE copies another document or file into the one you are currently editing.

Cutting Text to Its Own Document

To copy text from the document where you are currently working to another document, from Text Display:

1. Use [BLOCK MARK] or [ESC] [@] (column mark) to select the text you want from this document.
2. Press [MENU] to display the Editing Menu.
3. At the Editing Menu type **CUT** [RETURN].
4. To use the document name TEMP, press [RETURN].

   Or, type a document name of your choice and press [RETURN].

If a document name you select already exists, you are asked if you want to overwrite its contents. Either choose to do so by typing **YES** [RETURN], or not by typing **NO** [RETURN].

However, if TEMP already exists, AlphaWRITE automatically overwrites its contents without prompting you.

5. On return to Text Display, press [BLOCK CLEAR] to remove marks.

Pasting A Document Into This Document

To copy another document or file into the one you are currently working with, from Text Display:

1. Position the cursor on the line where you want the document you are bringing in.

2. Press [MENU] to display the Editing Menu.

3. At the Editing Menu, type **PASTE** [RETURN].

4. At the Enter Document Name prompt, press [RETURN] to **PASTE** the document named TEMP into this one.

   To check a document name, press [↑] or [↓] to display a directory list.

   Or, type the document name you want and press [RETURN].

   If the document you select is password protected, enter the password and press [RETURN].

   You are allowed a maximum of 36 characters at the Enter Input Document Name prompt. This is so you can identify a file from a different account on this device, from a different device and account, or from a different computer altogether. See the section below describing the files eligible for pasting.

5. When you return to Text Display, the text is inserted beginning with the line you had positioned the cursor on.

HINTS FOR USING CUT AND PASTE

Cut and Its Temp Document

CUT uses the default document name TEMP when no other name is selected, allowing you to use it as "temporary" document containing only the most recently **CUT** text.

Because TEMP is automatically overwritten each time it is used for **CUT**, TEMP can be used over and over again, like a scratch pad, without cluttering your account with unnecessary little documents.

When you want to keep text selected by CUT more permanently, use a document name other then TEMP.

Cutting Text from A Password Protected Document

When you mark text to CUT in a password protected document, the password assigned to that document is also assigned to the document CUT creates for you.

Whenever you use any AlphaWRITE feature asking you for the document name holding the CUT text—such as, PASTE, EDIT, etc.—you are asked to enter its password, which is the same password used for the source document where the CUT text originated.

You are asked to enter the password when the password for the document you are overwriting and the password for the document you are editing are different. When the password is the same for the document you are overwriting and the one you are editing, you are not asked to enter it.

Paste and Its Input Document Named Temp

The input document name defaults to TEMP, which is the same default document name that CUT uses.

Paste and Eligible Input Document Names

You can enter an Input document name other than TEMP by typing an existing AlphaWRITE document's name, located in the account where you called up AlphaWRITE. For example:

```
MEMO
```

Or, you can specify any ASCII file stored in your account, for example:

```
SAMPLE.TXT
```

You can enter a full file specification for any ASCII file stored on your computer's disk, for example:

```
DSK3:PUBLSH.LST[150,2]
```

You can specify an AlphaWRITE document stored on your computer's disk by entering the location, the document name without extension and the account number:

```
DSK1:LETTER[153,4]
```

But wait, there's more! You can also PASTE a document or file residing on another computer if that computer is available to you over a network. To do this, specify the network number (CPU identification number) and the file specification of the document to copy:

1694629889-DSK2:[251,0]CHAP01

The network number 1694629889 has ten characters but other network numbers may have more or fewer characters.

Paste Command and Format Settings

Documents you **PASTE** into your current document use the margin settings accompanying the document being pasted. Format settings from the Document Header of the document you are currently editing override any settings contained in the document you copied with **PASTE**.

FINDING AND REPLACING DOCUMENT TEXT

The **SEARCH, REPLACE** and **GLOBAL** commands let you locate, or locate and replace document text. Each one is discussed below.

Using the Search Command

AlphaWRITE's **SEARCH** command locates every occurrence of text in either a marked block or an entire document.

1. To search only part of your document, use [BLOCK MARK] on the area you want to search.

   To use **SEARCH** on your whole document, be sure there are no marks currently set.

2. Press [MENU] to display the Editing Menu.

3. Type **SEARCH** [RETURN].

4. Type text you want to find and press [EXECUTE]. **SEARCH** allows you to enter a maximum of 60 characters. The "searching" message appears while **SEARCH** is looking and remains until the first occurrence is found or no matches are found.

5. When **SEARCH** finds the first occurrence of the text, you can make any changes at that location, or move elsewhere in your document.

   Press [NEXT MATCH] to find the next occurrence, [PREV MATCH] to return to a previous occurrence, [CANCEL] to halt **SEARCH** altogether.

SEARCH remembers the text you entered at its command screen from the time you enter it until the next search string is specified with **SEARCH**, **REPLACE**, or **GLOBAL**, or until you end this editing session with this document.

You can **SEARCH** your document again for the text entered the last time you specified a search string. To do so, press [HOME], then [NEXT MATCH].

Using the Replace Command

The **REPLACE** command substitutes text you enter at its command screen for existing text in your document. **REPLACE** finds the existing text for you and then offers choices at each occurrence.

1. To use **REPLACE** on only part of your document, use [BLOCK MARK] on the area you want.

   To use **REPLACE** on your whole document, be sure there are no marks currently set.

2. Press [MENU] to display the Editing Menu.

3. Type **REPLACE** [RETURN].

4. Type the text you want to replace and press [RETURN]. **REPLACE** allows you to enter a maximum of 60 characters.

5. Type **replacement text** [RETURN]. **REPLACE** allows you to enter a maximum of 60 characters.

6. When both responses are satisfactory, press [EXECUTE] to begin **REPLACE**. The "searching" message appears while **REPLACE** is looking and remains until the first occurrence is found or no matches are found.

7. When **REPLACE** finds the first occurrence of the text you specified for it to locate, you are given the choices below. Type the letter associated with the action you want **REPLACE** to take:

TYPE	FOR THIS ACTION
Y	**Y**es: replace this occurrence
N	**N**o: ignore this occurrence and continue to next one.
C	**C**enter: to position this occurrence at mid-screen.
Q	**Q**uit: to halt **REPLACE**.

8. For every additional occurrence, until the last occurrence, you are given the choices above.

Using the Global Command

The **GLOBAL** command performs a search and automatic replacement of every occurrence of text in this document.

Use **GLOBAL** carefully; it automatically replaces all occurrences it finds.

You can stop **GLOBAL** while it is processing by pressing either [MENU] or [CANCEL].

1. To use **GLOBAL** on only part of your document, use [BLOCK MARK] on the area you want.

   To use **GLOBAL** on your whole document, be sure there are no marks currently set.

2. Press [MENU] to display the Editing Menu.

3. Type **`GLOBAL`** [RETURN].

4. Type text you want replaced and press [RETURN]. **GLOBAL** allows you to enter a maximum of 60 characters.

5. Type **`replacement text`** [RETURN]. **GLOBAL** allows you to enter a maximum of 60 characters.

6. When both responses are satisfactory, press [EXECUTE] to begin **GLOBAL**. The "searching" message appears while **GLOBAL** is looking and remains until **GLOBAL** is through or no matches are found.

   You can halt **GLOBAL** by pressing [CANCEL].

7. When all occurrences have been found and replaced, **GLOBAL** lets you know with a message.

HINTS FOR USING SEARCH, REPLACE AND GLOBAL COMMANDS

Formatting

REPLACE and **GLOBAL** will automatically reformat affected text after performing the substitution of the new text. However, if you have turned off the Allow Format of Text setting in the Document Header or Margin Format screen, text will not automatically reformat.

Interrupting

You can halt **SEARCH**, **REPLACE**, or **GLOBAL** in mid-stream by pressing [CANCEL].

Not Found

When **SEARCH**, **REPLACE** or **GLOBAL** does not find the text you specified, the message "?Specified string not found" or "Not Found" appears on your screen.

Capitalization

The MODE command's Fold Case during Search and Replace option determines how **SEARCH**, **REPLACE** and **GLOBAL** commands handle capitalization of text. When this option is set to N, capitalization is honored; when set to Y capitalization is ignored.

SPELL CHECKING YOUR DOCUMENT

AlphaWRITE's **SPELL** command automatically checks the correct spelling of words in all or part of your document.

Using Spell on Your Whole Document

From Text Display of the document you want to spell check:

1. Press [MENU] to display the Editing Menu.
2. Type **SPELL** [RETURN]. Once you start spell, you can halt it at any time by pressing [MENU] or [CANCEL].
3. Choose from these spell options if an unrecognized word is found:

OPTION	YOUR ACTION
Accept this word this occurrence	Type **A**
Accept this word for rest of document	Type **R**
Insert word in local dictionary	Type **I**
Edit this word	Type **E**, edit the word. Press [EXECUTE] when through.
Display dictionary word	Press [HELP] once for standard dictionary, press [HELP] twice for professional dictionary; press [HELP] a third time for verb dictionary. Use [NEXT SCREEN] and [PREV SCREEN] to scroll through list of words.
Use dictionary word	Position cursor on word with the arrow keys, press [RETURN] to insert it in document.

4. When **SPELL** is through, it shows a recap of the words it processed. From this display, press any key to exit back to your document.

Using Spell On Part of Document

From document you want to spell check:

1. Use [BLOCK MARK] to select the portion of document you want to check.

2. Follow the steps shown for spell checking a whole document.

3. When you return to your document display, remember to use [BLOCK CLEAR] to remove block marks.

HINTS FOR USING THE SPELL COMMAND

Spell's Dictionaries

The **MODE** command, described in Chapter 11, has four dictionary options, letting you choose which, if not all, available dictionaries **SPELL** references.

AlphaWRITE's initialization file contains information pertinent to **SPELL**'s performance.

You can find more information in Chapter 15 "AlphaWRITE's Dictionaries" and Appendix H "AlphaWRITE's Initialization File."

Marking Procedure

Do **not** use column mark ([ESC] [@]) operations to select a portion of your document, **SPELL** only honors [BLOCK MARK].

About Spell's Options

SPELL displays a list of 4 options when a document word does not compare to a dictionary word. Plus, you can display dictionary words by pressing [HELP].

```
                    AlphaWRITE SPELL CHECKING

   ➡Do not use column mark ( ESC  @ ) operations to select a portion
   ➡of your document,  SPELL  only honors  BLOCK MARK .◀
◀
◀
  About Spell's Options ◀
◀
   ➡  SPELL  displays a list of 4 options when a document word
   ➡does not compare to a dictionary word.◀
◀
◀
_____________________________________________________________________

       I do not recognize this word:    Spell's
       Please enter option: ▉
       A - Accept word as is           R - Accept the word and remember it
       E - Edit the line               I - Insert word in personal dictionary



                   [ Press HELP to display dictionary ]
              [ Press MENU or CANCEL to stop spell check ]
```

AlphaWRITE Spell Checking Screen

Accept Word As Is Option

The Accept Word As Is option (**A**) tells **SPELL** this occurrence of the questioned word is acceptable, but to question it again the next time it is found in this document.

Edit The Line Option

The Edit The Line option (**E**) lets you make changes on the line containing the questioned word. The line is displayed and you can delete, add or change any word on that line.

These editing keys are available to make changes on the line:

[REVERSE CHAR] [CHAR INS] [CHAR DEL] [RUBOUT] [CTRL] [Y] [WORD DEL]

You can position the cursor anywhere on the line you are editing. Use these keys to move the cursor:

[NEXT WORD] [PREV WORD] [←] [→] [SHIFT] [←] [SHIFT] [→]

Accept Word And Remember It Option

The Accept Word and Remember It option (**R**) lets **SPELL** know this and all other occurrences of the questioned word are acceptable in this document. The word is remembered for the rest of this spell session, but it will be questioned again the next time you use **SPELL**.

Insert The Word Into Personal Dictionary

The Insert The Word Into Personal Dictionary option (**I**) lets you record the questioned word in your personal dictionary. The word is saved in your personal dictionary, a file named LOCAL.DCT and **SPELL** won't question it in any document using this dictionary.

Displaying and Using A Dictionary List

You can display a list of standard dictionary words, professional dictionary words, or verb dictionary words (if you are using a language other than English) when **SPELL** finds a word it does not recognize.

You can choose dictionary word list display as your first option or after you use the Edit option. And, once the list is displayed you can replace the unrecognized word **SPELL** found with a word shown in the list by selecting it and pressing [RETURN].

To display the standard dictionary list of words:

–Press [HELP] once.

When you have a professional dictionary on your computer, display its words when you;

–Press [HELP] twice.

When you are using a language other than English, you may also have a verb dictionary. To see the infinitive (base) form of the words:

–Press [HELP] three times.

If you use **MODE** to turn off a dictionary, you cannot display or insert its words. When you attempt to do so, you see a message say the dictionary is disabled. To have **SPELL** refer to the dictionary, halt **SPELL**, and use **MODE** to turn the dictionary on, then run **SPELL** again.

Using the Dictionary Word List

You can move forward and backward through the display of dictionary words. Also, you can substitute any word you see in the list for the unrecognized word. You work with both of these dictionary lists in the same way, as described in the next sections.

Moving Through the Display of Words:

When a dictionary list appears you can see words before and after this spelling:

–Press [NEXT SCREEN] to move forward alphabetically

–Press [PREV SCREEN] to move backward alphabetically

Inserting A Dictionary Word:

When a list of dictionary words is on your screen, you can choose a word from the list to use in place of the word **SPELL** questioned. There are three steps involved:

1. Display the dictionary you want to use.

2. Select the dictionary word using the dictionary word cursor. Press any of the arrow keys to cause the dictionary word cursor to appear.

   [→]: cursor first appears on last word in the first column, then moves the cursor right to the next word.

   [←]: cursor first appears on last word in the last column, then moves the cursor left to the previous word.

   [↑]: cursor first appears on last word in last column, then moves the cursor up a row, in the same column.

   [↓]: cursor first appears on first word in first column, then moves the cursor down a row, in the same column.

3. Insert the word by pressing [RETURN]. The questioned word clears along with the option list, and is replaced with the dictionary word you've chosen. **SPELL** automatically formats the paragraph where the change took place and continues.

After Using the Spell Command

Use the **SAVE** or **FINISH** command after using **SPELL** to keep any changes or corrections you've made to your document.

CHAPTER TEN
USING DIRECTORY, ERASE, COPY AND RENAME COMMANDS

Chapter Ten contains information about:

- List of Documents
- Erasing Documents
- Copying Documents
- Renaming Documents

LIST OF DOCUMENTS

You can request a list of documents from most AlphaWRITE command screens and from the Main or Editing Menu with the **DIRECTORY** command. You can also display a directory list of AlphaWRITE documents from AMOS command level without calling up AlphaWRITE first.

From AMOS command level you can use the WRTDIR command to get a listing of AlphaWRITE documents

Displaying Document List From Any Command Screen

You can see a list of documents from most Main or Editing Menu command screens. To do so, press:

[↑] or [↓]

The list you see is the Standard format directory display.

You can move forward through the directory list when there are more entries than fit on your screen by pressing [↓]. To move backward, press [↑].

The Directory Command

The **DIRECTORY** command offers more options for a document listing than a list displayed from any command screen. **DIRECTORY** is available from both the Main and Editing Menu. To use it, from either menu:

1. Type **`DIRECTORY`** [RETURN]

   DIRECTORY asks you questions and the list you get depends on how you answer them.

2. The first prompt in the list asks you to Enter Directory Option. This is where you choose how much information the directory list shows about each document.

   Type the letter representing the format you want and press [RETURN].

TYPE	TO GET THIS INFORMATION
S	Standard directory shows document name, created date, revised date, document description and protection status.
N	Name directory shows document name and description.
H	History directory shows document name, description, author, operator, department, created date, protection status, date last revised, date last printed, number of times revised, number of times printed.

3. The second prompt asks you if you want to Display All Documents. Type the letter representing your choice and press [RETURN].

TYPE	TO GET THIS INFORMATION
Y	To get a list of all documents in this account.
N	To get a list of documents based on selection criteria you choose. When you press [EXECUTE], **DIRECTORY** will show you another screen where you enter selection criteria. See the section below describing how to choose the document criteria.

4. The Output to Printer prompt lets you print your directory list and behaves just like the **PRINT** command.

   Type the letter representing your choice and press [RETURN].

TYPE	TO GET THIS INFORMATION
N	Display your document list now.
Y	To use the directory print option. See the chapter describing how to print documents for information on how to respond to the prompts directory printing will give you.

5. Once your responses are typed at the command screen, press EXECUTE.

   If you have requested to see a selection of documents, you are shown a Directory criteria screen, described below. After using this screen, your list is either displayed or sent to the printer depending on how you responded to the Output to Printer prompt.

   If you have requested Output to Printer, you are asked to answer directory printing questions.

Document Selection Criteria

When you respond with **N** to **DIRECTORY**'s Display All Documents prompt and press EXECUTE, AlphaWRITE displays the Directory Criteria screen.

```
                 AlphaWRITE DOCUMENT DIRECTORY DISPLAY


Document name ■

Description

Author

Operator

Department

Creation date range start               Range end



              [ Enter directory criteria and press RETURN ]

                     [ Press EXECUTE for directory ]

              [ Press MENU or CANCEL to leave this screen ]
```

Directory Command's Selection Criteria Screen

At the Selection Criteria Screen you:

- Move between these fields with ↑, ↓, or RETURN.
- Enter as little as one character in the name, description, author and operator fields. **DIRECTORY** matches your criteria when it finds characters appearing consecutively anywhere within the field.

  It acts something like **SEARCH**—looking for a match within a group of words—finding the first occurrence of the sequence of characters you specify no matter where they appear in the field; beginning, middle or end.
- Enter date information in any of these formats:

  MM/DD/YY MM-DD-YY MM.DD.YY

  In Europe, if your System Operator has defined it in the system Language Definition File, **DIRECTORY** supports this format:

  DD/MM/YY DD-MM-YY DD.MM.YY

  where MM is the month, DD is the date, and YY is the year. Some computers use a different date format; check with your System Operator if you are unsure what format to use.
- More criteria to get a more specific directory list.

When you are through entering selection criteria, press EXECUTE to instruct **DIRECTORY** to process your request.

Using WRTDIR From AMOS Command Level

You can display a list of AlphaWRITE documents from AMOS command level by using the **WRTDIR** command. To see a list of AlphaWRITE documents in the account where you are logged, from AMOS command level, type:

WRTDIR RETURN

Your screen shows the equivalent information of **DIRECTORY**'s standard directory option. WRTDIR shows you only those files having the extension .WRT. You can use wildcards in a filename to see a specific grouping of AlphaWRITE documents. To supply a wildcard for one character, use the **?**, to supply a wildcard for more than one character use *****. For example:

WRTDIR ST* RETURN

Responds with a list of all AlphaWRITE documents (extension .WRT), whose first two characters are ST. Whereas:

WRTDIR ST?? RETURN

This example indicates you want only those AlphaWRITE documents whose names are four characters long and whose first two characters are ST.

WRTDIR follows the conventions used for other AMOS information commands—like DIR—except it does not support any command switches. Use the same wildcard conventions for device and account locations as you do for other AMOS commands.

For example, to get a list of all AlphaWRITE documents on your computer:

`WRTDIR ALL:[]` [RETURN]

HINTS FOR USING DIRECTORY

Document Header and Directory Information

The AlphaWRITE Document Header determines the information shown by **DIRECTORY**. You can use the **HEADER** command to change information for any particular document, such as: document description, author, operator, department and protection status.

Alphabetic Order

AlphaWRITE's directory listings are always shown in alphabetic order by document name, even when you use selection criteria.

Directory List Sent to Printer as Disk Output Only

AlphaWRITE stores the directory with the name DIRECT.LST in the account where you called up AlphaWRITE. This file is accessible from AMOS command level and not directly by AlphaWRITE's **EDIT** command. However, you can use **PASTE** to insert the contents of DIRECT.LST into a document you **CREATE** or **EDIT**.

ERASING DOCUMENTS

Erasing A Document

The Main Menu **ERASE** command deletes an existing document from the account where you called up AlphaWRITE. To use it, from the Main Menu:

1. Type **ERASE** [RETURN].

2. At the Document Name to Erase prompt, type the document name you want to erase and press [EXECUTE].

   To erase a password protected document, you must also enter the document's password.

3. You can enter another document name to erase, or press [MENU] to return to the Main Menu.

What AlphaWRITE Erases From This Account

ERASE removes AlphaWRITE created files with the document name you specified with the extensions .WRT, .JRN and .BAK, from the account where you are currently logged.

COPYING DOCUMENTS

Copying A Document

COPY duplicates the contents of an existing document in a new document using a unique name you choose. You can **COPY** documents located in the account where you are currently logged or from another account you normally have access to.

To use the command, from the Main Menu:

1. Type **COPY** [RETURN].

2. At the Enter Document Name to Copy prompt, type the original document's name and press [RETURN]. The maximum number of characters allowed is 36.

   If this document is protected, type its password and press [RETURN].

3. At the Enter Document Name to Copy To prompt, type a new document name and press [RETURN].

   If the original document was password protected, the copy will be too and will use the same password as the original.

4. Use **EDIT** to work with the new document.

HINTS FOR USING COPY COMMAND

Copying A Document From Another Account

You can **COPY** an AlphaWRITE document from another account into the account where you are currently logged by specifying the copy's file specification, without the extension:

```
DSK3:GLOSS[150,4]
```

Copying A Document From Another Computer

You can also **COPY** a document residing on another computer if that computer is available to you over a network. To do this, specify the network and the file specification of the document to copy:

```
1694629889-DSK2:[251,0]CHAP01
```

The network number 1694629889 has ten characters but other network numbers may have more or less.

AlphaWRITE Understands Ersatz Names

Some accounts and networks have abbreviated names called ersatz names.

An ersatz name may be defined to identify a CPU identification for a computer available to you over a network. An ersatz name may also be defined as "shorthand" to identify a particular device and account specification on your computer.

Check with your System Operator for the names in use on your computer.

RENAMING A DOCUMENT

Renaming A Document

RENAME lets you change the name of an existing document in the account where you are working with AlphaWRITE. To use it, from the Main Menu:

1. Type **RENAME** [RETURN].

2. At the prompt for Document Name to Rename, type the original document's name and press [RETURN]. You can only **RENAME** AlphaWRITE documents, and only ones located in the account where you are currently logged.

   If this document is protected, type its password and press [RETURN].

3. At the prompt for New Document Name type the document name you now want this document known by and press [EXECUTE].

If the original document was protected, the renamed document will be too and protected with the same password.

HINTS FOR USING RENAME COMMAND

Files AlphaWRITE Renames

The only file AlphaWRITE renames for you is the one you identified which has a .WRT extension; any files with the same name but different extensions are not changed with **RENAME**.

CHAPTER ELEVEN
CHOOSING OPERATION SETTINGS AND SCREEN DISPLAY MODES

Chapter Eleven contains information about:

- Operation Settings
- Selecting Screen Display Options

OPERATION SETTINGS

The **MODE** command affects AlphaWRITE's operation and appearance. Using **MODE** overrides operation settings put into effect by the initialization file when you first called up AlphaWRITE. Changes you make with **MODE** are in effect until you change them by using **MODE** again, or exit AlphaWRITE.

Using the Mode Command

To change AlphaWRITE's operation settings, from either the Main Menu or Editing Menu, type:

1. **MODE** [RETURN]

2. The Mode Command Screen is shown in the following illustration.

   Settings available from the AlphaWRITE Mode Screen and their effect are described after these instructions.

   To make changes, move the cursor to the field you want to change, type the change and press [RETURN].

```
                    AlphaWRITE MODE SCREEN

              GENERAL                              DISPLAY

Fold Case during Search and Replace? Y   On-screen attributes? ....... N
Menu bypass? ....................... Y   Use color? .................. Y
Character insert on? ............... Y   Use high and low intensity? . Y
Line insert on? .................... N   Use proportional fonts? ..... N

            SPELL CHECKING                         JOURNALING

Use QUICK dictionary? .............. Y   Perform keystroke journaling? Y
Use STANDARD dictionary? ........... Y   Keystrokes between updates .. 16
Use PROFESSIONAL dictionary? ....... N   Maximum journal keystrokes .. 20480
Use PERSONAL dictionary? ........... Y
Use VERB dictionary? ............... Y

               PRINTING

Reformat for best output? .......... Y
Use font substitution? ............. Y

               [ Use UP ARROW and DOWN ARROW to select fields ]
               [ Press EXECUTE or MENU to update mode settings ]
               [ Press CANCEL to leave mode settings unchanged ]
```

Mode Command Screen

3. For help information on any field, position the cursor in that field and press HELP. Press HELP again to see information for the **MODE** command.

4. Once you make all the changes you want, press EXECUTE to put your changes into effect.

Changes you make with **MODE** are in effect for this session with AlphaWRITE. **MODE** settings return to the default values or to settings made via the AlphaWRITE initialization file the next time you use AlphaWRITE.

Fold Case During Search and Replace?

Fold Case During Search and Replace? determines how capitalization is regarded during **SEARCH**, **REPLACE** and **GLOBAL** commands.

TYPE	TO
Y	Ignore capitalization.
N	Honor capitalization.

Menu Bypass?

Menu Bypass lets you turn off, or on, the full Editing Menu display. When Menu Bypass is on and you press MENU from Text Display, you see this prompt:

```
Enter command name and press RETURN:
```

Prompts for some AlphaWRITE Editing Menu commands appear in abbreviated form near the bottom of Text Display.

TYPE	TO
Y	Bypass Editing Menu display and see command line only.
N	Allow full Editing Menu display.

Character Insert On?

Character Insert On? lets you choose to arrive at Text Display, or work at Text Display with automatic character insert mode turned on or off. You use [AUTO INS CHAR] to switch between overwrite and insert modes at text display.

TYPE	TO
Y	Engage automatic insert character mode.
N	Engage character overwrite mode.

Line Insert On?

Line Insert On? lets you choose to arrive at Text Display, or work at Text Display with automatic line insert mode turned on or turned off. Use [AUTO INS LINE] to switch between overwrite and insert modes at text display.

TYPE	TO
Y	Engage automatic insert line mode.
N	Engage line overwrite mode.

Use Quick Dictionary?

Use Quick Dictionary? lets you choose whether or not to have **SPELL** refer to the dictionary named SMALL.DCT during spell verification. SMALL.DCT is the 12,000 word Random House® Dictionary.

TYPE	TO
Y	Have **SPELL** refer to SMALL.DCT.
N	Have **SPELL** ignore SMALL.DCT.

Use Standard Dictionary?

Use Standard Dictionary? lets you choose whether or not to have SPELL refer to the dictionary SPELL.DCT during spell verification. SPELL.DCT is the 80,000 word Random House® Dictionary.

TYPE	TO
Y	Have SPELL refer to SPELL.DCT.
N	Have SPELL ignore SPELL.DCT.

Use Professional Dictionary?

Use Professional Dictionary? lets you choose whether or not to have SPELL refer to the professional dictionary you have defined by your AlphaWRITE initialization file's DICTIONARYTWO command.

TYPE	TO
Y	Have SPELL refer to the professional dictionary.
N	Have SPELL ignore the professional dictionary.

Use Personal Dictionary?

Use Personal Dictionary? lets you choose whether or not to have SPELL refer to the dictionary named LOCAL.DCT during spell verification.

TYPE	TO
Y	Have SPELL refer to your personal dictionary.
N	Have SPELL ignore your personal dictionary.

Use Verb Dictionary?

Use Verb Dictionary? lets you choose whether or not to have SPELL refer to the dictionary VERB.DCT during spell verification. VERB.DCT is especially for international language support and holds the infinitive form of verbs; it is unused in English.

TYPE	TO
Y	Have **SPELL** refer to VERB.DCT.
N	Have **SPELL** ignore VERB.DCT.

Reformat For Best Output?

Reformat for Best Output? determines if your document reformats based on the printer selected with **PRINT**, or if the printed results reflect your screen display.

When turned off (N) it will disable the effect of [FORMAT] and **FORMAT**. This setting causes text to print just as it appears on your screen.

TYPE	TO
Y	Allow format for best output.
N	Set no format for this text.

Use Font Substitution?

Use Font Substitution? causes the best font match available on your laser printer if the font you selected is not available. If you turn off font substitution and a font is not available, your laser printer output will use whatever is defined as the default type font.

See Appendix B for more information about how AlphaWRITE substitutes fonts when the one you request is not available.

TYPE	TO
Y	Allow font substitution.
N	Prevent substitution.

On-screen Attributes?

On-screen Attributes? selects whether or not underlined text is displayed with underscores, and if bold text appears in reverse (bright) display on terminals which can display these attributes.

TYPE	TO
Y	Allow display of attributes.
N	Prevent attributes from displaying.

Use Color?

Use Color? turns on or off color display of AlphaWRITE screens and menus. (Display colors used are set by the PALETTE command in your AlphaWRITE initialization file.) If you are not using a color terminal, this setting has no effect.

TYPE	TO
Y	Allow color display.
N	Prevent color display.

Use High and Low Intensity?

Use High And Low Intensity? turns on or off use of bright and dim display. Turning off high and low intensity causes all screens to appear in bright display. If you are using a color terminal, setting this field to N helps to unclutter your screen.

If you are using a monochrome terminal, it is better to set this field to Y so marked text may be distinguished from non-marked text.

TYPE	TO
Y	Allow high and low intensity.
N	Prevent high and low intensity display.

Use Proportional Fonts?

Use Proportional Fonts? displays menu and command screen text using a proportional type face, if your terminal supports it. This setting affects your terminal's display only, not printed documents.

TYPE	TO
Y	Allow proportional text display.
N	Prevent proportional text display.

Perform Keystroke Journaling?

Perform Keystroke Journaling? lets you capture, or prevent capture of keystrokes you make in a document so you can recover your work in the event of system malfunction.

TYPE	TO
Y	Allow keystroke journaling. (Keystrokes between updates and Maximum journal keystrokes in effect; see below.)

TYPE	TO
N	Prevent keystroke journaling. Settings for Keystrokes Between Updates and Maximum Journal Keystrokes are ignored.

Keystrokes Between Updates

Keystrokes Between Updates determines how frequently your journal file is updated with a record of your keystrokes. The Perform Keystroke Journaling setting must be set to Y before any value for the Keystrokes Between Updates will be honored.

Valid responses are whole numbers in the range 4 to 512.

Maximum Journal Keystrokes

Maximum Journal Keystrokes determines the size of the journal file (.JRN) that holds your keystrokes when journaling is turned on. This setting is disregarded if Keystroke Journaling is turned off.

Valid responses are in the range 512 to 999,936 (approximate size: 1 to 1950 blocks).

HINTS FOR USING THE MODE COMMAND

Default Settings

Default settings for some of MODE's options are determined by your AlphaWRITE initialization file. These specific commands affect the values initially used by AlphaWRITE's MODE command.

INITIALIZATION COMMAND	MODE SETTING AFFECTED
CHARINSERT	Character Insert On?
COLOR	Use Color?
DICTIONARYTWO	Use Professional Dictionary?
DICTIONARY	Use Quick and Standard Dictionary?
DISPLAYATTRIBUTE	On-Screen Attributes?
INTENSITY	Use High & Low Intensity?
JOURNAL	Perform Keystroke Journaling?
JOURNALSIZE	Maximum Journal Keystrokes
KEYSTROKES	Keystrokes Between Updates
LINEINSERT	Line Insert On?
MENUBYPASS	Menu Bypass?
PROPORTIONAL	Use Proportional Fonts?
REFORMAT	Reformat for Best Output?
SEARCHFOLD	Fold Case During Search & Replace?

SELECTING SCREEN DISPLAY OPTIONS

AlphaWRITE makes use of many display features present on Alpha Micro's terminals.

Changing Column Text Display Width

The **WIDTH** command is used to switch between 80 and 132 column display on your terminal and only affects document text display; not menu displays.

WIDTH only works on terminals capable of switching between 80 and 132 column width.

To use this command:

1. From Text Display, press [MENU] to display the Editing Menu.
2. Type **WIDTH** [RETURN].

Your display now switches column width. Repeat these steps to reverse the effect.

Displaying Underline & Bold As Screen Highlight

AlphaWRITE's on-screen attribute feature underscores text you underline in a document, and shows bolded text in a bright highlight (reverse video).

You can enable or suppress this feature by changing the Display On-screen Attributes setting available with the **MODE** command.

Changes made to On-screen Attribute with **MODE** are in effect for this session with AlphaWRITE. If you want the change to be more permanent, you can use the **DISPLAYATTRIBUTE** command in your AlphaWRITE initialization file. Please refer to Appendix H - "AlphaWRITE's Initialization File."

Displaying AlphaWRITE in Color

You can enable or suppress the use of color by changing the Use Color setting available with the **MODE** command. Of course, this is only available on terminals supporting color display (specifically on mode type terminals).

Changes made to Color with **MODE** are in effect for this session with AlphaWRITE. If you want the change to be more permanent, you can use the **COLOR** command in your AlphaWRITE initialization file. Please refer to Appendix H - "AlphaWRITE's Initialization File" for complete information on using this command.

The colors AlphaWRITE uses when you elect to use color display are governed by its AlphaWRITE initialization file's **PALETTE** command. If no **PALETTE** command is present, AlphaWRITE uses this color scheme:

AlphaWRITE	COLOR
Field Prompts	Cyan
Text Display	Green
Information Text	White
Input Fields	Yellow
Error Messages	Red

The color scheme AlphaWRITE uses ignores foreground and background colors that may have been set at AMOS command level with the SET T command.

When you exit AlphaWRITE, whatever colors you may have set for use from AMOS command level will be in effect again.

Using Proportional Display Fonts

You can enable or suppress the use of proportional display fonts by changing the Use Proportional Fonts setting available with the **MODE** command. This is only available on terminals supporting this capability.

When set to Y, this setting displays menu and command screen text using a proportional type face. N sets a mono-spaced type face for screen display. This setting affects menu and command display only, not your typed entries at Text Display or your printed documents.

CHAPTER TWELVE
USING ADVANCED AlphaWRITE FEATURES

Chapter Twelve contains information about:

- Record and Playback
- Calendar
- Math Mode
- Outlining
- Glossary

RECORD AND PLAYBACK

AlphaWRITE's record feature stores your keystrokes at Text Display from the time you turn it on until you turn it off. The playback feature replays what you last recorded in this session with AlphaWRITE.

Valid recordings include editing operations, Editing Menu commands, function key menu selection as well as text characters. If you exit your document prior to ending a recording, AlphaWRITE automatically ends recording for you.

Recording Keystrokes

You can record a sequence of keystrokes at Text Display to playback at a later time. To do so:

1. When you want to begin recording, press [RECORD]. A message appears at the bottom of your screen to remind you recording is engaged.

2. Type the characters you want to record; this can include any function key selections, special keys or editing keys, and so on. However, recording will halt if you exit this document before ending the recording.

3. When you have finished typing, press [RECORD] again to end the recording. The record message will clear from your screen to signal recording is complete.

4. AlphaWRITE remembers this recording for this session with AlphaWRITE, or until you make a new recording.

For example, you could record a particular phrase:

[RECORD] **`A rose is a rose is a rose.`** [RECORD]

Or, you could record an editing sequence to move the cursor to the next word, delete it and type another word:

[RECORD] [NEXT WORD] [WORD DEL] **`Gertrude`** [RECORD]

The record feature has many applications and is very useful when you must use the same series of keystrokes repeatedly.

Erasing A Recording

The following procedure serves to clear a recording entirely:

1. At Text Display, press [RECORD].

2. Press [RECORD] again.

The most recent recording is also erased when you make a new recording and when you exit AlphaWRITE.

Playing Back A Recording

To play back what is currently recorded:

1. If you are inserting text, you may want to have [AUTO INS CHAR] engaged so existing text is not overwritten by your recording.

2. Position the cursor where you want the playback to begin.

3. Press [PLAYBACK].

HINTS FOR USING RECORD AND PLAYBACK

Maximum Recording Length

The maximum length allowed for a recording is 256 keystrokes.

Record vs. Glossary

If what you want to record involves many keystrokes and is complicated, you may opt to use a glossary entry instead of recording.

Recording is best suited for relatively brief sequences, whereas glossary can handle fairly long and complicated sequences. Once you make a recording, you cannot go back and edit it, as you can with a glossary entry.

CALENDAR

AlphaWRITE's calendar feature displays a monthly calendar in the upper right portion of your Text Display. You can view any month from January 1900 through December 2155.

To display the calendar, from Text Display press: [ESC] [J].

```
◀
    ➡If what you want to record involves many keys
    ➡complicated, you may opt to use a glossary en
    ➡recording.◀
◀
    ➡Recording is best suited for relatively brief
    ➡whereas glossary can handle fairly long and c
    ➡sequences.  Once you make a recording, you ca
    ➡edit it, as you can with a glossary entry.◀
◀
◀
◀
CALENDAR◀
◀
    ➡AlphaWRITE's calendar feature displays a monthly calendar in
    ➡the upper right portion of your Text Display.  You can view
    ➡any month from January 1900 through December 2155.◀
◀
    ➡To display the calendar, from Text Display press: ESC J.
◀
◀
◀
        [ Press UP ARROW or DOWN ARROW to scroll (monthly) calendar ]
       [ Press PREV SCREEN or NEXT SCREEN to scroll (yearly) calendar ]
           [ Press HOME to return to current date, MENU to exit ]
                    Pag 3   Lin 24   Col 10              Line Ovr  Char Ins

April           1990
Su Mo Tu We Th Fr Sa
 1  2  3  4  5  6  7
 8  9 10 11 12 13 14
15 16 17 18 19 20 21
22 23 24 25 26 27 28
29 30
```

Calendar Display Example

Once the calendar is on your screen, use these keys to move around:

[↓]	Next month	[PREV SCREEN]	Previous year
[↑]	Previous month	[NEXT SCREEN]	Next year
[MENU]	Exit	[CANCEL]	Exit
[HOME]	Return to current month/year		

HINTS FOR USING CALENDAR

System Date

AlphaWRITE's calendar uses the current date set at AMOS command level. If the month or date on the calendar display is incorrect, inform your System Operator who can use the appropriate commands to correct this information.

MATH MODE

AlphaWRITE's [MATH] key lets you switch into and out of math mode. While in math mode, you can perform arithmetic operations on numbers in your text.

However, while you are in math mode, you cannot perform normal text entry and editing.

Using Math Mode

After you enter numbers in your document text:

1. Press [MATH]. When you do, you'll see the accumulator display at the bottom of your screen.

2. Position the cursor on the number you want to work with.

   Use any of the standard cursor movement keys to position the cursor on the numbers you want to work with. For example, [↑], [↓], [←], [→], [NEXT WORD], [PREV WORD], [HOME], etc.

3. Load the number in the accumulator. To do so, press [RETURN].

4. Choose the operation you want to perform on the number loaded in step 3.

   The table below shows the operations you can perform once a number is loaded.

OPERATION	WHAT YOU DO
Addition	Position cursor on next number. Press [+].
Clear Accumulator	At any time, press [C].
Divide	Position cursor on number to divide by. Press [/].
Insert Accumulator Value	Position cursor at insert point. Press [=].

OPERATION	WHAT YOU DO
Load Number	Position cursor on number. Press [RETURN].
Multiply	Position cursor on number to multiply by. Press [*].
Percentage	Position cursor on percentage number. Press [%].
Subtract	Position cursor on number to subtract from accumulator. Press [−].

5. When you are through, press [MATH] to exit math mode. The accumulator display clears from the bottom of your screen.

Totalling a Column or Row of Numbers

After you enter a column or row of numbers in your document text:

1. Press [MATH]. When you do, you'll see the accumulator display at the bottom of your screen.

2. Position the cursor in the column, or row, of numbers, on the first number you want included in the total.

3. To total a column, press [T]. All numbers are added from the initial cursor position until a non-numeric character is encountered.

   To total a row, press [R]. All numbers are added from the initial cursor position until a non-numeric character is encountered.

4. Use the result with any other math operation discussed above, or press [MATH] to exit.

HINTS FOR USING MATH MODE

Remember to Clear the Accumulator

Like a hand-held calculator, remember to clear Math Mode's accumulator of unwanted values before totalling.

Non-numeric Characters

When totalling a row or column, the operation stops when it encounters a non-numeric character. In a column, spaces are considered non-numeric; in a row, they are not, since they are needed to separate numbers.

Numeric Characters

AlphaWRITE's math mode considers these characters to be numeric:

DESCRIPTION	ILLUSTRATION
Numbers	0 1 2 3 4 5 6 7 8 9
Decimal Point	.
Plus Sign	+
Minus Sign	–
Dollar Sign	$
Comma	,
Parentheses	( )
Debit†	DB
Credit†	CR
Scientific Notation	E

†Only when appearing after a numeric character.

OUTLINING

AlphaWRITE's outlining feature lets you create automatically numbered lists with up to seven levels of subordination. You can use this feature to make numbered lists, develop outlines for reports, or organize material using a decimal numbered format.

Setting Outline Format

The **OUTLINE** command lets you choose the numbering scheme for each of the seven outline levels available. To use it:

1. Press [MENU] to display Editing Menu.

2. At the Editing Menu, type **OUTLINE** [RETURN].

```
                    AlphaWRITE OUTLINE FORMAT

            Level 1 -    I.    Upper-Case Roman Numerals
            Level 2 -    A.    Upper-Case Alphabetics
            Level 3 -    1.    Arabic Numerals
            Level 4 -    a)    Lower-Case Alphabetics
            Level 5 -    (1)   Parenthesized Arabic Numerals
            Level 6 -    (a)   Parenthesized Lower-Case Alphabetics
            Level 7 -    i)    Lower-Case Roman Numerals

        Enter level number followed by format selection: ▌

A. Arabic Numerals                  E. Lower-Case Roman Numerals
B. Upper-Case Alphabetics           F. Decimal Numbering
C. Lower-Case Alphabetics           G. Parenthesized Arabic Numerals
D. Upper-Case Roman Numerals        H. Parenthesized Lower-Case Alphabetics

                  [ Press EXECUTE to update outline ]
            [ Press MENU or CANCEL to leave outline unchanged ]
```

Outline Command Format Screen

3. At the Format screen, you type two characters to make a change to the format. The first character is the number representing the outline level you want to change, 1 through 7. The second character is a letter from the list on the lower part of the screen to select the format.

   Type each character and press RETURN.

   The formats available are shown in the following table.

TYPE	TO SELECT FORMAT
A	Arabic Numerals 1., 2., 3., etc.
B	Upper-Case Alphabet A., B., C., etc.
C	Lower-Case Alphabet a), b), c), etc.
D	Upper-Case Roman Numerals I., II., III., etc.
E	Lower-Case Roman Numerals i), ii), iii), etc.
F	Decimal Numbering 1.0, 1.1, 1.2, etc.
G	Parenthesized Arabic Numerals (1), (2), (3), etc.
H	Parenthesized Lower-Case Alphabet (a), (b), (c), etc.

4. The Format screen shows your updated selection and your response to the prompt clears. You can make more changes to the format used for outline levels

   To put your changes into effect, press [EXECUTE].

   To abandon your changes, press [CANCEL].

Beginning An Outline In Your Document

To begin an outline in your document, from Text Display:

1. Position cursor on line where you want to begin the outline.
2. Press [OUTLINE IN].
3. Type text [RETURN].

Moving In or Out An Outline Level

To indent further into an outline press [OUTLINE IN]

To return to an earlier outline level, press [OUTLINE OUT].

Exiting Outline Mode

To exit outline mode press [OUTLINE OUT] until the cursor is back on column one.

Inserting One Outline in an Existing Outline

You can insert an outline item into an existing outline:

1. Position cursor where you want to insert the outline item.
2. Press [LINE INSERT] twice if line overwrite mode is engaged.
3. Press [OUTLINE IN] until you see the outline level you want.
4. Type text for outline item and press [RETURN].

Inserting Multiple Outline Items in An Existing Outline

You can insert multiple items into an existing outline. To do so:

1. Position cursor where you want to insert the outline items.
2. Engage automatic outline mode: press [AUTO INS LINE] to turn on automatic line insert, if it is not already on.

3. Press [OUTLINE IN] until you see the outline level you want.

4. Type text for your outline item and press [RETURN].

5. Use [OUTLINE IN] and [OUTLINE OUT] as necessary to reach the outline level you want.

6. Exit automatic outlining by pressing [OUTLINE OUT] until you reach column 1. You can also exit by turning off automatic line insert, just press [AUTO INS LINE].

Moving an Existing Outline Item In or Out

You can edit outline items and move them in and out within your outline. To do so:

1. Position the cursor on the item you want to change.

2. To move the item out: press [OUTLINE OUT] once for every level you want to move,

   To move the item in: press [OUTLINE IN] once for every level you want to move,

HINTS FOR USING OUTLINE MODE

How Outlining Behaves

[OUTLINE IN] lets you do three things:

- Begin outline mode at level 1.
- Move in an outline level while entering text.
- Move an existing outline item in one level.

[OUTLINE OUT] lets you do three things:

- Leave outline mode altogether.
- Move out an outline level while entering text.
- Move an existing outline item out one level.

Tabs and Outlining

Tabs set with [MARGIN] determine the position of the characters denoting outline levels and the beginning of outline text. Outlining works best with left justified tabs.

Automatic Outlining

You are in automatic outline mode when you are entering outline items at the end of your document or when [AUTO INS LINE] is on. When you press [RETURN] at the end of an outline under either of these conditions, you receive the character for the next step of that particular outline level.

Exiting Automatic Outlining

There are two ways to leave outline mode:

- Move the cursor off the current outline item.
- After pressing [RETURN] at the end of your last outline item, press [OUTLINE OUT] until the cursor is positioned at the left margin.

GLOSSARY

The glossary feature lets you insert words or phrases and/or the current date, time, user name, account or file name into your document.

You use [GLOSSARY] with a two-character code to insert an entry in your document and **GLOSSARY** to select the glossary document you want referred to when you press [GLOSSARY].

Inserting a Glossary Entry Into Your Document

To insert a glossary entry into your document:

1. Position cursor where you want the entry to appear. This can be at the Main Menu, Editing Menu, any command screen, Embedded display or Text Display.

2. Press [GLOSSARY] then type the two character code associated with the glossary entry you want.

   You can use the built-in two-character codes which are always available, as shown in the illustration below.

```
                    AlphaWRITE GLOSSARY HELP

Default glossary entries

D1  System date formatted as "April 23, 1990"
D2  System date formatted as "23 April 1990"
D3  System date formatted as "23-Apr-90"
D4  System date formatted as "4/23/90"
D5  System date formatted as "23/4/90"

T1  System time formatted as "05:17 PM"
T2  System time formatted as "17:17"

U1  User name as in "Your Name"

F1  Document name as in "CHAP12.WRT"

A1  Account name as in "DSK5:[150,43]"



                  [ Press any key to continue ]
          [ Press MENU or CANCEL to return to Text Display ]
```

Glossary Help Screen for Built-In Entries

Displaying Glossary Contents

To see the glossary codes available now, from Text Display:

1. Press [GLOSSARY] then press [HELP].

2. Press any key to move forward through the list of currently defined glossary entries.

The Default Glossary: GLOSS.WRT

Unless you specify otherwise with the **GLOSSARY** command, AlphaWRITE assumes you want to use its default glossary document named GLOSS.WRT. Under this assumption, AlphaWRITE uses the first GLOSS.WRT it finds in its search path. It first looks for GLOSS.WRT in the account where you are currently logged. If still not not found, it looks in the project account ([,0]), then in WRT:.

If GLOSS.WRT is in the project account ([,0]), it can be shared by all users in that account series. Or, if GLOSS.WRT is in WRT:, it can be shared by all users on the computer.

Using A Glossary Document Other Than Gloss

To have the [GLOSSARY] key refer to a document holding glossary codes and entries other than the default one named GLOSS, from the Editing Menu:

1. Type **GLOSSARY** [RETURN].

2. At the Enter Glossary Document Name prompt, type the document name and press [RETURN].

   You can type up to 36 characters at the request for document name so you can select a glossary document located in another account, another account on another device or even another computer.

   AlphaWRITE follows the same search path for the glossary document you specify as it does for GLOSS.WRT. If it cannot find the glossary document, it tells you so with a message.

3. The glossary document you named will be used for this session with AlphaWRITE. Once you exit AlphaWRITE and return, AlphaWRITE defaults to using the glossary document named GLOSS.

Creating A Glossary Document

Glossary documents differ from other documents because their contents are in a special format; they contain a list of two-character codes and corresponding entries.

To make a glossary document, from the Main Menu:

1. **CREATE** a new document. Name it `GLOSS` if one does not already exist with that name, or choose another name.

2. At Text Display, beginning in the first column, type:

   `xx,<glossary entry>` [RETURN]

   where `xx` represents a two character letter or number code. Glossary definitions must follow these guidelines:

   - The two-character code must begin in column one.
   - The two-character code must be followed by a comma.
   - The glossary entry must be surrounded by angle brackets: < >
   - The ending right angle bracket (>) must be followed by an end of paragraph marker ([RETURN]).

Brackets as Text Characters

You can use a left angle bracket as a text character in your glossary entry; AlphaWRITE views any left angle bracket following the first left bracket in the glossary entry as a text character.

Adding A Glossary Entry

You can add a glossary entry to a particular glossary document by calling it up with **EDIT** and adding the entry. This method also gives you the benefit of making changes to existing entries or deleting them.

However, when you just want to make an addition and carry on with the task at hand, you can add a glossary entry to the currently selected glossary document from anywhere in AlphaWRITE—without having to stop what you are doing and **EDIT** the glossary document. To do so:

1. Press [GLOSSARY] [=]

2. At the AlphaWRITE On-Line Glossary Definition screen, type:

   xx [RETURN]

   where xx represents the unique two-character glossary code.

   If you enter a two-character glossary code that already exists, AlphaWRITE objects and tells you so with a message.

3. At the < symbol, begin typing your glossary entry.

   Use any function keys, characters or AlphaWRITE operations you choose. To correct your mistakes, use [RUBOUT] to back up over and erase previous characters.

4. When you are through with the glossary entry, press [GLOSSARY].

5. You can use your newly defined glossary code right away. AlphaWRITE automatically appends and saves the on-line glossary entry you just entered to the currently selected glossary document.

If the currently selected glossary document is GLOSS, and it not does not exist, AlphaWRITE creates it when you make your on-line entry.

HINTS FOR USING GLOSSARY

Where You Can Use The Glossary Feature

Glossary codes can be used from any AlphaWRITE menu or screen. However, you cannot use [GLOSSARY] [HELP] while making an on-line glossary entry. Also, you may receive unexpected results should you define a glossary entry within a glossary entry.

Using Universal Key Sequences for AlphaWRITE Features

Glossary entries can include universal key sequence instructions to invoke an AlphaWRITE feature.

For example, if you type ^P in a glossary entry in a glossary document you **EDIT**, when used it will activate the block mark feature.

An on-line entry automatically interprets function key instructions into this universal key sequence for you. If you press [BLOCK MARK] at an on-line entry, your screen displays the symbols ^P.

See Appendix A - "Universal Key Sequences" for more information about the key sequences associated with all of AlphaWRITE's features. The key sequence information is also available as a help screen; use [HELP] from Text Display and select help topic 1 "Function Key List."

Insert vs. Overwrite Mode When Using Glossary

Unless character insert mode is engaged, inserting a glossary entry in your document is done in overwrite mode. This means if your glossary entry contains text, it could overwrite existing document text.

If you are inserting glossary text on a line having text, you may want to engage [AUTO INS CHAR] beforehand. This action preserves any existing text from being overwritten.

CHAPTER THIRTEEN
USING SORT, INDEX, TOC AND MERGE COMMANDS

Chapter Thirteen contains information about these topics:

- Sorting Text
- Making an Index
- Making a Table of Contents
- Merging Documents

SORTING TEXT

SORT arranges text you column mark in alphabetic and numeric order according to the contents of the marked column. The marked column is called the sort key.

You can mark as narrow or as wide a column as you want for the sort key, but **SORT** will rearrange entire lines.

To sort text, from Text Display:

1. First, column mark the text you want to **SORT**. To do this, position the cursor on the first line in the sort range, on the first character to sort by.

2. Press [ESC] [@].

3. Move cursor to last line of sort range, last character to sort by and press [ESC] [@].

4. After you mark the text it is ready to be used by **SORT**. Press [MENU] to display the Editing Menu and type **SORT** [RETURN].

5. At the prompt Ascending Order? type **Y** [RETURN] to obtain text rearranged alphabetically A-Z, 1, 2, etc.

   Type **N** [RETURN] to use obtain a descending sort, Z-A, 2 before 1, etc.

6. When **SORT** is complete, you return to Text Display with lines of text rearranged in the order you selected. Press [BLOCK CLEAR] to remove the column marks.

HINTS FOR SORTING TEXT

Sort Order

SORT takes characters other than letters and numbers into consideration as it arranges the lines of text.

Text Used By Sort

Text outside the column you mark is ignored for purposes of alphabetizing. Always include the entire word or phrase you want **SORT** to use. For example:

Joseph, Sandi
Joseph, Lee
Joseph, Bob
Joseph, Dave

If you mark only the first five characters of the line—shown by the gray area—then **SORT** these four names, they stay in the same order since the different first names are out of the marked area.

If you include both the first and last names in the column you mark and **SORT**:

Joseph, Sandi
Joseph, Lee
Joseph, Bob
Joseph, Dave

The result is correctly alphabetized by first and last names: Bob, Dave, Lee, Sandi as follows:

Joseph, Bob
Joseph, Dave
Joseph, Lee
Joseph, Sandi

Abandoning Sorted Text

Before performing a **SORT**, use **SAVE** so you are sure to keep the current changes to your document. After **SORT**, should you find you do **not** want to keep your rearranged text, you can use **QUIT** to abandon the change introduced by **SORT** and return to the previous version before the changes.

MAKING AN INDEX

AlphaWRITE's index feature consolidates and alphabetizes index entries you create. When you request AlphaWRITE to index your document, all the index entries you have entered in your document are alphabetized and then consolidated if appropriate. Duplicate entries on separate pages appear as one entry with the separate page numbers listed.

There are two steps in generating an index:

1. Enter the index entry text in your document. This entry is made from the Index Embedded Text Screen which you arrive at via the [EMBED] key.

2. Request AlphaWRITE to find every index entry and compile the index for you. This is done via the **INDEX** command, or with [LAYOUT]'s Print Index option.

Creating the index entry itself is a relatively straightforward process. Requesting an index is a bit more detailed because of the variety of options you have.

About A Book's Index

If you look at a reference book, you'll see there are some general standards the format of a index takes. Generally, there are two varieties of index entries: a main entry alone and a main entry with a subordinate entry.

A main entry usually consists of a key word(s) for a topic and a page reference. For example:

AlphaWRITE.....1-1

The second type of index entry, a main entry with a subordinate entry, consists of a key word(s) for a topic followed by a more detailed key word(s) reference about that topic, then a page reference. For example:

AlphaWRITE
  features.....2-4

AlphaWRITE's indexing feature lets you identify the key word(s) to be referenced in a document and automatically keeps track of the page(s) they occur on.

Creating an Index Entry

How you enter the text at AlphaWRITE's index embedded text screen determines if the index entry is a single main entry, or a main entry with a subentry. See step 4 for details.

To create an index entry, from Text Display:

1. To instruct indexing to use a particular word, position the cursor immediately **after** the word. (You'll leave the index screen blank in step 4, if you choose this method.)

Or, position the cursor on the line where the reference you want to index occurs.

Establish a convention for entering index entries to make editing a document containing them easier. For example, in this documentation, index entries are placed beginning in column 1, on an otherwise blank line between text, with a blank space between each entry, with an end-of-paragraph marker (RETURN) at the end of the line.

2. Press EMBED.

3. At the Enter Code prompt, type **7** to select the Index Entry option.

4. At the Index embedded text screen, type the text you want AlphaWRITE to use as the index text and press RETURN.

   If you leave this screen blank, AlphaWRITE uses the single word preceding the column where you pressed EMBED. At text display, this is the word immediately preceding the index information block.

   AlphaWRITE uses only the first two lines of the index screen.

   The first line holds the main entry, the second line holds the subentry.

   If the first line has text and the second line is blank, AlphaWRITE assumes this is a main, one line entry. For example:

   ```
   AlphaWRITE
   ```

   If there is text on both lines, AlphaWRITE knows this is a main and subentry, for example:

   ```
   AlphaWRITE
   features
   ```

   Another example of a main and subentry:

   ```
   AlphaWRITE features
   indexing your document
   ```

5. Press EXECUTE or EMBED to finish the entry and return to Text Display.

Requesting an Index

Once your document contains index entries, you have two two ways to request an index:

1. With the Editing Menu **INDEX** command.

2. With LAYOUT's Print Index option.

The **INDEX** command asks you to supply the template index document name and a new document name to hold the indexed result made from this document. The result of this command is a separate document which you can use **PASTE** to put it into this one or use

EDIT to handle otherwise. To keep your resulting index current and accurate, each time you change your document's index entries, use **INDEX**.

Where **INDEX** gives you flexibility in handling your output document, the [LAYOUT] Print Index option, keeps your index list up to date with the most recent changes. This is because this option inserts an information block at the point where you want the index to be printed. It is re-created every time you use **PRINT** on your document; this is an ideal choice for documents undergoing a lot of change either in content or in the index entries themselves.

Using the Index Command

From the Editing Menu:

1. Type **INDEX** [RETURN].

2. At Enter Name of Prototype Index prompt: press [RETURN] to accept the name INDEX. Or, type the name of the index prototype document you want to use and press [RETURN].

   The maximum number of characters at this prompt is 36 so you can enter a full file specification for an index prototype.

3. At Enter Name of Output Index Document, enter a new document name of 6 characters or less and press [RETURN].

4. When you have answered both prompts satisfactorily, press [EXECUTE].

When indexing is complete, the index output document you named can be called up with **EDIT**, used with **PRINT**, brought into the document you are working with now with **PASTE**, or used just like any other document you have made.

Using the Layout Key's Print Index Option

From Text Display:

1. Position the cursor at the beginning of the line where you want this document's index to be printed. Typically, this is somewhere near the end of your document.

   The closer you position the cursor to the beginning of the line, the easier the print index information block will be for you to find.

   If you want the index to begin printing on a new page, be sure to use [PAGE] to insert a hard page break before where you want the index to be printed.

2. Press [LAYOUT].

3. At the Enter Code prompt, type **6** to select the Print Index option.

Every time you use **PRINT**, AlphaWRITE will automatically recreate your index and print its contents at the point you've requested.

HINTS FOR INDEXING YOUR DOCUMENT

Index Entries are Embedded Text

Index entries are embedded text and follow all the rules described in the Embedded Text Screens section of Chapter 1 "Calling Up and Exiting AlphaWRITE."

Index Entries and Their Corresponding Page Numbers

To be certain AlphaWRITE determines the correct page number for your index entries, always use **PAGINATE** before requesting an index.

Page numbering for the index entries defaults to arabic numerals unless a page number style has been selected with [LAYOUT]. Any change you have made to page numbering, such as using [LAYOUT] to set a page number, is taken into consideration.

If chapter numbering is used in page numbers, AlphaWRITE uses the chapter number as part of the page number where the index entry occurs. If no chapter number style has been set, AlphaWRITE assumes arabic numerals for the chapter numbers.

The Index Prototype Document

AlphaWRITE comes with a template index document named INDEX which it uses unless you have created your own.

Typically, a template index document holds the format settings, margin and tab arrangements, title, footer, and any other directions for the printed document's appearance.

AlphaWRITE looks for the template index document named INDEX first in the account where you are currently logged. If it is not found there, then AlphaWRITE looks in your project account, if it isn't there, it looks in WRT:.

Index Entry Appearance in Your Index Output Document

When you request an index, AlphaWRITE takes your index entries, alphabetizes them and arranges them in your index output document. Here is what AlphaWRITE does with each kind index entry:

- Main entries: begin at the left margin setting and are followed by a tab at which the page number reference is inserted. A paragraph marker is placed after the page number.

- A main entry having one sub-entry: the main entry begins at the left margin and ends with a paragraph marker. The sub-entry appears on the line immediately following the main entry, preceded by two blank spaces, followed by a tab at which the page number reference is inserted. A paragraph marker is placed after the page number.

- A main entry having multiple sub-entries: the main entry begins at the left margin and ends with a paragraph marker. The sub-entries appear in alphabetic order on the lines immediately following the main entry. Each one is preceded by two blank spaces, followed by a tab at which the page number reference is inserted. A paragraph marker is placed after the page number.

- Page numbers used: AlphaWRITE uses the printed page number scheme you have set for this document.

- Page numbers: multiple occurrences of an entry on non-consecutive page numbers are shown separated by commas. For example:

  AlphaWRITE 1, 5, 8, 23

- Page numbers: multiple occurrences of an entry on consecutive page numbers are shown as a range of pages, inclusive. For example, occurrences of the main entry "AlphaWRITE" on pages 1, 2, 3, 4, 5, 6, 7, and 8 would be shown as:

  AlphaWRITE 1 to 8

MAKING A TABLE OF CONTENTS

AlphaWRITE's table of contents feature consolidates table of contents entries you create. When you request AlphaWRITE to make a table of contents for your document, all table of contents entries in your document are then arranged in the order in which they appear.

There are two steps in generating a table of contents:

1. Write the table of contents text entry in your document. This is done from the TOC Embedded Text Screen which you arrive at via the EMBED key.

2. Request AlphaWRITE to find every table of contents entry and compile the table of contents for you. This is done via the **TOC** command, or with LAYOUT's Print TOC option.

Creating the table of contents entry itself is a relatively straightforward process. Requesting a table of contents is a bit more detailed because of the variety of options you have.

About a Book's Table of Contents

Generally, a table of contents includes the chapter names and section headings with a corresponding page number.

The list of chapters and headings appears in the same order as the headings do in the book.

For example, the table of contents entry for this discussion is located under Chapter 13, under the main heading "Making A Table of Contents," at the sub-heading "About a Book's Table of Contents."

Creating a TOC Entry

You create a table of contents entry from the table of contents embedded text screen.

To create a table of contents entry, from Text Display:

1. Position the cursor on the line containing the heading reference you want used in the table of contents.

   To instruct table of contents to use a heading already entered in your document text, position the cursor in the first column of the line where the heading resides, **before** the heading text. (You'll leave the table of contents screen blank in step 4, if you choose this method.)

2. Press [EMBED].

3. Type **8** to select the TOC Entry option.

4. At the TOC embedded text screen, type the text you want AlphaWRITE to use as the table of contents entry and press [RETURN].

   You are limited to one line of text.

   If you make no entry at all, AlphaWRITE assumes all of the text appearing on the line where the TOC information block resides is the text you want to appear as the table of contents entry.

5. Press [EXECUTE] or [EMBED] to finish the entry and return to Text Display.

Requesting A Table of Contents

There are two ways to request a table of contents:

- With the Editing Menu **TOC** command.
- With [LAYOUT]'s Print Toc option.

The **TOC** command asks you to supply the prototype TOC document name and a new document name to hold the resulting table of contents made from this document. The result of the command is a separate document which you can **PASTE** into this one or leave separate to handle otherwise. To keep your resulting TOC current and accurate, each time you change your document's TOC entries, use **TOC**.

Where **TOC** gives you flexibility in handling your output document, the [LAYOUT] Print TOC option, keeps your TOC list up to date with the most recent changes. This is because it inserts an information block at the point where you request your TOC to be printed. The table of contents is re-created every time you use **PRINT** on your document; this is an ideal choice for documents undergoing a lot of change either in content or in the TOC entries themselves.

Using the TOC Command

From the Editing Menu:

1. Type **TOC** [RETURN].

2. At Enter Name of Prototype TOC prompt: press [RETURN] to accept the name TOC. Or, type the name of the TOC prototype document you want to use and press [RETURN].

   The maximum number of characters at this prompt is 36 so you can enter a full file specification for a TOC prototype.

3. At Enter Name of Output TOC Document, enter a new document name of 6 characters or less and press [RETURN].

4. When your answer to both prompts is satisfactory, press [EXECUTE].

The new output document is available to you for editing, printing, even pasting entirely into the document you are working with now.

Using the Layout Key's Print TOC Option

From Text Display

1. Position the cursor at the beginning of the line where you want the TOC to be printed. Typically, this is somewhere near the beginning of your document.

   The closer you position the cursor to column one, the easier the print TOC information block will be for you to spot in your document.

   If you want the TOC to begin printing on a new page, be sure to use [PAGE] to insert a hard page break before where you want the TOC to be printed.

2. Press [LAYOUT].

3. Type **5** to select the Print TOC option.

4. After the print TOC information block, use [PAGE] again to force another page break.

Every time you use **PRINT**, AlphaWRITE will automatically recreate your TOC and print its contents at the point you've requested.

HINTS FOR MAKING A DOCUMENT TABLE OF CONTENTS

Table of Contents Entries Are Embedded Text

Table of contents entries you make are embedded text and follow all the rules described in the Embedded text screen section of Chapter 1 "Calling Up and Exiting AlphaWRITE."

Table of Contents Entries and Their Page Numbers

To be certain AlphaWRITE determines the correct page numbers for your table of contents, always use **PAGINATE** before using **TOC**.

Page numbering for the table of contents entries defaults to arabic numerals unless a page number style has been selected with [LAYOUT]. Any change you have made to page numbering, such as using [LAYOUT] to set a page number, is taken into consideration.

If chaptering is used in the document, AlphaWRITE uses the chapter number as part of the page number where the table of contents entry occurs. If no chapter number style has been set, AlphaWRITE assumes arabic numerals for the chapter numbers.

The TOC Prototype Document

AlphaWRITE comes with a prototype table of contents document named TOC which it will use unless you have created your own.

The prototype table of contents document holds the format settings, margin and tab arrangements, title, footer, and any other directions for the printed document's appearance.

AlphaWRITE looks for TOC first in the account where you are currently logged. If not found there, AlphaWRITE looks for TOC in your project account; if not found there, then it looks in WRT:.

Table of Contents Entry Appearance in Your Output Document

When you request a table of contents, AlphaWRITE takes your table of contents entries, using the exact text and arrangement you used in your entry and lists them in the same order as they occur. AlphaWRITE inserts a tab at the end of the entry, inserts the page number where this entry occurs and ends the line with a paragraph marker.

MERGING DOCUMENTS

AlphaWRITE's **MERGE** command lets you produce multiple customized forms—such as form letters—by combining a template document containing the form with a data document containing customizing information.

The template document contains the text of the form you want to **MERGE**. You can include variable names anywhere within the text. When you use **MERGE**, the replacement text

you provide for each variable name—either in the data document or interactively during **MERGE**—is inserted in place of the variable name.

The data document contains two lists: A variable name definition list used by the template document and an optional replacement data list. If the data list is present, **MERGE** processes automatically. If absent, **MERGE** is used interactively.

There are three steps to a merge operation:

1. Creating the template document.
2. Creating the data document.
3. Using the **MERGE** command.

Creating Your Template Document

The following rules apply to variable names in the template document. Variable names:

- Can be up to 64 characters long.
- Must be identical to the variable names defined in the data document. The same capitalization and spacing is important.
- Must be enclosed within angle brackets: < >
- Can be used more than once in a template document.

While all variable names in the template document must appear in the data document, you do not have to use all of the variable names found in the data document in the template document. A sample template document screen display is shown below.

```
◖
◖
23 April 1990◖
◖
<Name>◖
<Street>◖
<State>◖
◖
Dear <Name>,◖
◖
Thank you for your recent submission.  While it shows
considerable promise it does not meet our needs at this time.
Please keep us in mind for future submissions.◖
◖
J. N. Saypah◖
Ragtime, Inc.◖
◖
◖
◖
◖
◖
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-....
<   L L  L  L L    L L  L    L    L    L    L    L    L    L    >
Font C 10  Frmt Y  Orient P  Text 9.7" Lpo 1"   Cpi 10  Just N  Wspc P  Lspc 2
                    Pag 1   Lin 1    Col 1                Line Ovr  Char Ins
```

Merge Sample Template Document

Brackets as Text Characters

You can include a left or right angle bracket as a text character in your template document. As long as a left angle bracket is not followed by a valid variable name, or a right angle bracket is not preceded by a valid variable name, AlphaWRITE will view the bracket as a text character and not a signal for a variable name.

Creating Your Data Document

The following rules apply to the data document:

Variable Names

1. Must be defined at the beginning of the data document. Variable names can exceed one line but a comma must follow the last variable name on a line, except the last line, when more than one line is required.
2. The variable definition line length can be a maximum line length of 253 characters; set with [MARGIN].
3. Must be enclosed within angle brackets: < >
4. Must be separated by commas: < >,< >,< >
5. Maximum number of variable names is 128.
6. Can be up to 64 or less alphanumeric characters, upper or lower case.

Data Lines

1. No more than one complete data set per line.
2. Must be enclosed within angle brackets: < >
3. Must end with an end of paragraph marker ([RETURN]).
4. Must be supplied in the same order they are to be substituted for variable names in the definition list.
5. Blank data can be supplied by typing < >[RETURN].
6. Can be up to 8,192 characters.

Data Documents

1. Data documents can be either AlphaWRITE generated documents (.WRT) or ASCII format text files.
2. ASCII files used as data documents must follow all the rules applicable to variable names and data lines described above.
3. ASCII files can be created by using the AMOS text editor AlphaVUE or by some other software program.
4. ASCII files used as data documents can be used in conjunction with AlphaWRITE's command line processing feature to automate word processing output. Use AlphaWRITE's system command level help file WRTCLP.HLP or see the *AlphaWRITE Programmer's Information Manual* for more information about command line processing.

Sample Data Document

The following sample shows three variable names and has a data list which supplies two complete sets of data for the variable names.

```
<Name>,<Street>,<State>◀
◀
<L. Joseph>◀
<42354 Tuxedo Way>◀
<New York, New York>◀
<J. Lee>◀
<32457 Inglewood Drive>◀
<San Francisco, California>◀
◀
◀
◀
◀
*****
*****
*****
*****
*****
*****
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-....
<   L L  L    L    L    L    L    L    L    L    L    L    L    >
Font C 10  Frmt Y  Orient P  Text 9.7" Lpo 1"   Cpi 10  Just N  Wspc P  Lspc 2
                   Pag 1   Lin 1   Col 1                Line Ovr  Char Ins
```

Merge Sample Data Document

Using the Merge Command

To use **MERGE**, from the Main Menu:

1. Type **MERGE** [RETURN].

2. Type the name of your Template document and press [RETURN]. Use [↑] or [↓] to check the directory list for document names. You are allowed a maximum of 36 characters at this prompt. The template document must be an AlphaWRITE document (.WRT).

3. Type the name of your Data Document and press [RETURN]. You are allowed a maximum of 36 characters at this prompt. Unless you specify otherwise, AlphaWRITE assumes the document name's extension is .WRT.

4. Type your Output Document Name and press [RETURN]. AlphaWRITE allows a maximum of six characters at this prompt. If the name you type already exists, AlphaWRITE asks you if you want to overwrite the existing document. Type **YES** [RETURN] to overwrite. Type **NO** [RETURN] to keep the document and have the opportunity to enter another output document name.

5. In response to Insert Page Breaks field:

   Type **Y** if you want AlphaWRITE to put a hard page break at the end of each completed template document.

   Type **N** if you do not want page breaks.

6. You can change any document name you supplied so far by pressing [RETURN] to move to the field you want.

7. When you are ready to process the merging documents press [EXECUTE].

Treat the output document as you would any other: use **EDIT** to see and work with its contents, **PRINT** to send it to the printer and so on.

Using Merge Command Interactively

You can use **MERGE** and supply the customizing data to the template document while **MERGE** runs. This is called interactive merge and does not require the contents of the data document to hold anything other than the variable definition line.

In fact, to use **MERGE** interactively, the data document cannot contain anything other than the variable definition line.

1. Be sure your data document contains no customizing data, only the data definitions.

2. To use **MERGE** interactively, follow the steps shown above for using the **MERGE** command.

3. The command screen then displays your list of variable names and waits for your response to the first variable.

4. Type your response to the variable name, but do not exceed 132 characters. Press [RETURN] to proceed to the next variable.

5. You can make changes to this data before you press [EXECUTE]; these keys will help you to make editing changes:

   - Use [↑] to move the cursor to the previous field, [↓] to move to next field.
   - Use [NEXT SCREEN] to move the cursor forward through your variable names, [PREV SCREEN] to move backward.
   - Position the cursor within a line with [←], [→], [NEXT WORD], [PREV WORD].
   - Use [SHIFT] [←] to move to beginning of line.
   - Use [SHIFT] [→] to move to end of line.
   - Use [RUBOUT], [CHAR DEL], [CHAR INS], [WORD DEL], [REVERSE CASE] and [REVERSE CHAR] to remove and rearrange characters.
   - Use [CTRL] [Y] to delete to end of line.

6. When your responses are satisfactory, press [EXECUTE] to process this set of data you supplied.

7. Treat the output document as you would any other: use **EDIT** to see and work with its contents, **PRINT** to send it to the printer and so on.

HINTS FOR MERGING DOCUMENTS

Before Using the Merge Command

The template and data documents for MERGE must exist before you use MERGE. One or both may be located in the account where you are currently logged, or another account on your computer to which you normally have access. One or both of these documents can also reside on another computer.

The document name you supply for either the template or data documents allows you to enter up to 36 characters, so you have room to specify a full file specification, including a CPU ID of another computer.

About Your Output Document

After you use MERGE, the output document contains one copy of each form created. The number of forms is determined by the number of sets of variable data supplied. MERGE automatically inserts a page break at the end of each form in the output document if you have requested so. The output document uses the same format settings, margin settings and password protection scheme as used in the template document.

Sample Output Document

The sample output document illustrated below shows how the template and data samples described earlier are blended by MERGE. The screen-length is exaggerated to show as much of the output document as possible.

```
23 April 1990◂
◂
L. Joseph◂
42354 Tuxedo Way◂
New York, New York◂
◂
Dear L. Joseph,◂
◂
Thank you for your recent submission.  While it shows
considerable promise it does not meet our needs at this
time.◂

Please keep us in mind for future submissions.◂
◂
J. N. Saypah◂
Ragtime, Inc.◂
//////////////////////////// HARD PAGE BREAK ////////////////////////////////
23 April 1990◂
◂
J. Lee◂
32457 Inglewood Drive◂
San Francisco, California◂
◂
Dear J. Lee◂
◂
Thank you for your recent submission.  While it shows
considerable promise it does not meet our needs at this
time.◂
◂
Please keep us in mind for future submissions.◂
◂
J. N. Saypah◂
Ragtime, Inc.◂
*****
*****
*****
....-....1....-....2....-....3....-....4....-....5....-....6....-....7....-....
<   L    L    L    L    L    L    L    L    L    L    L    L    >
Font C 10  Frmt Y  Orient P  Text 9"   Lpo 1"   Cpi 10  Just N  Wspc P  Lspc 2
                   Pag 1   Lin 1    Col 1                 Line Ovr  Char Ins
```

Merge Sample Output Document

CHAPTER FOURTEEN: USING JOURNAL FILES, IMPORTING FILES, USING POSTSCRIPT PROGRAMS

Chapter Fourteen contains information about the following topics:

- Journal Files and Recovery Procedures
- Documents and Files AlphaWRITE Creates
- Importing Files Into Your Document
- Using PostScript with AlphaWRITE

JOURNAL FILES AND RECOVERY PROCEDURES

AlphaWRITE's capability of recording keystrokes to a disk file as you type is called journaling. This feature is a preventive one; should your job or computer malfunction for some reason, your editing session can be re-created by AlphaWRITE.

Keystroke journaling is in effect by default, and you will be generally unaware it is working—until you need it! Options that affect the performance of journaling may be set in AlphaWRITE's initialization file or with **MODE**. The AlphaWRITE initialization commands affecting keystroke journaling are shown below.

COMMAND	PURPOSE
JOURNAL	Enables or disables keystroke journaling. The default condition is to enable journaling.
JOURNALSIZE	Defines how much disk space to reserve for the journal file. The journal file is a random file with the same name as the document being edited, but has extension .JRN.

COMMAND	PURPOSE
JOURNALSIZE	*(continued)* The numeric argument defines the file size in keystrokes (bytes). The number of bytes is divided by 512 and rounded up to form the number of blocks allocated. The JOURNALSIZE argument may range from 512 (1 block) through 2,048,000 (4,000 blocks). The default JOURNALSIZE value is 20,480 keystrokes (40 blocks).
KEYSTROKES	The KEYSTROKES command defines the journal update interval. The numeric argument defines the number of keystrokes between disk writes to the journal file. The KEYSTROKES argument may range from 4 through 512. The default value is 16.

Recovering An AlphaWRITE Document

If your computer crashes while using AlphaWRITE, or if your job on the computer hangs for some reason, while you are working in an AlphaWRITE 2.0 document when journaling is engaged, you will be able to recover information you have typed in your document.

To recover a document which was exited because of some sort of computer problem:

1. Log into the account where you were using AlphaWRITE at the time of the system malfunction.

2. Call up AlphaWRITE with the **WRITE** command, or whatever command you typically use to call up AlphaWRITE 2.0.

3. At the Main Menu, use **EDIT** to call up the document you had been working in when the malfunction occurred.

4. You will see the following information displayed on your screen as AlphaWRITE gives you the option to recover a journal file:

```
                    AlphaWRITE JOURNAL RECOVERY

There is a journal file for this document.  This usually means that you
weren't able to SAVE, FINISH, or QUIT the last time you were editing the
document.

If you wish to recover the keystrokes from the journal, enter YES and you
will see the keystrokes reenter themselves on the screen.  You can stop the
journal recovery prematurely by pressing the CANCEL key while this is
happening.

If you don't wish to recover the keystrokes from the journal file, enter NO.
The journal file will be erased and you will have no further opportunity to
recover from it.

If you aren't sure what to do, then just press CANCEL or MENU.  The journal
file will remain on the disk, and the next time the document is edited this
same message will reappear.

Do you wish to recover from the journal file? ▮

                     [ Enter YES to recover from journal ]
                 [ Enter NO to forget journal and erase it ]
            [ Press MENU or CANCEL to leave journal file intact ]
```

AlphaWRITE Journal Recovery Screen

5. At the Journal Recovery Screen screen, type **YES** [RETURN] to recover the information you entered in your document.

   If you do not want to recover the information you entered, type **NO** and press [RETURN].

6. If you have elected to recover the journal file for your document, you will see the keystrokes enter themselves on the screen. When it is through, you will be at the same point in your document as when the system malfunction occurred.

   If you elect to not recover the journal file, your document appears on your screen just as it does when you use **EDIT** on it. This choice behaves just as if you had used **QUIT** to exit your document the last time you used it.

When the Journal File is Full

From time to time, the journal file holding the "recording" of your keystrokes may become full; if this happens while editing a document, you see this message on your screen:

```
KEYSTROKE JOURNAL FILE FULL

The keystroke journal file is full.  AlphaWRITE will not be able to
store any more of your keystrokes until the next time you SAVE, QUIT, or
FINISH.  Any of these actions will clear the journal file.

The usual action to take when the journal file fills up is to simply enter
the SAVE command from the Editing Menu.

Keystroke journaling is now temporarily suspended.

[ Press MENU to return to the Editing Menu ]
```

Keystroke Journal File Full Screen

To retain the current changes to your document, use **SAVE** to update the disk file with your document's present contents and empty your journal file to hold more keystrokes.

Every time you **SAVE** your document, AlphaWRITE empties the journal file. When you **FINISH** from your document, AlphaWRITE empties then erases the journal file. When you **QUIT** from your document, AlphaWRITE erases the journal file.

DOCUMENTS AND FILES AlphaWRITE CREATES

While using AlphaWRITE, it creates files other than your document (.WRT). Some files remain after exiting AlphaWRITE and some are deleted automatically. The file extensions and when AlphaWRITE creates them are shown below.

FILE	DESCRIPTION
.BAK	Backup file of the current document.
.###	(numeric extension) Files for printing, often erased after printing has taken place.
.JRN†	Journal file created when Journaling is engaged to store keystrokes.
.LST†	Print command's disk output only files.

FILE	DESCRIPTION
.TMB†	Temporary mark operations (block and column).
.TMF†	Temporary footnote file.
.TMI†	Temporary index file.
.TMT†	Temporary table of contents file.
.TML†	Temporary listing file.
.TMP†	Temporary file used to hold your editing changes between SAVES and FINISH.
.TMR†	Temporary file used as a secondary holding file for the footnote feature.
.TMS†	Temporary file used by SORT.
.TMX†	Temporary file used during conversion of an earlier AlphaWRITE document when it is being used by a more recent version of AlphaWRITE.
LOCAL.DCT	Created when you use SPELL's personal dictionary for the first time.
GLOSS.WRT	Glossary document created the first time you make an on-line addition to the glossary, if it doesn't already exist.
TEMP.WRT	A "scratch" document created by CUT used during PASTE.

†These documents are usually not present in your account unless you are currently working with AlphaWRITE.

IMPORTING FILES TO YOUR DOCUMENT

Importing an AlphaCALC Worksheet

AlphaWRITE lets you bring all or only part of an AlphaCALC worksheet into the document you are currently working with. You have the choice of bringing in the contents now, or leaving an instruction for AlphaWRITE to get and print the worksheet contents, at the location you specify, when you print the document.

The difference between these choices is where the import contents are stored: if you choose to bring it into this document now, the contents of the worksheet increase the size of your document. From Text Display:

1. Position cursor on the line where you want the AlphaCALC worksheet contents to appear.

   Be sure the current margin and tab settings can accommodate the width of the information being brought in from the AlphaCALC worksheet.

   Use the AlphaCALC cell width for the cell range you are importing as your initial tab settings for each column in the data range. AlphaWRITE interprets the divisions between each cell column as a tab character and each column. Once imported to your AlphaWRITE document, each column will be separated by one AlphaWRITE tab stop.

2. Press [ESCAPE] [/].

3. At the Enter Code prompt, type **1** to select AlphaCALC Worksheet Now and have AlphaWRITE bring the contents of the worksheet into your document now.

   Type **2** to select AlphaCALC Worksheet At Print Time and to print the contents of the worksheet at this location when you **PRINT** this document.

4. At the prompt to supply the filename, type the worksheet name and press [RETURN]. AlphaWRITE assumes the extension is .ALC so you do not have to include it in your response.

   You are allowed a maximum of 36 characters. If you do not specify otherwise, AlphaWRITE assumes the worksheet is located in the account in which you are currently logged.

5. At the prompt for Cell Range, type the cell range you want included from the worksheet and press [RETURN]. If it is the whole worksheet, type A1:IU255 [RETURN].

6. If you have requested the cell range to be included now, the contents appear in your document at the location you requested.

   If you have requested the worksheet cell range to be included when you **PRINT** the document, you will not see the results until you do so.

Be sure the format settings for the area where you are bringing in the AlphaCALC worksheet text accommodates this new information.

Importing an Image File

An image file contains special print instructions for laser printers and are printer dependent. The AlphaWRITE import image feature allows you to access the image files you may have which print pictures or symbols.

Remember, if you choose to use an image file in a particular document, you must print that document on the printer that the image file you have used is intended for. Otherwise, you will not get the printed results you anticipate.

Import Image File Handling

Typically, imported image files are understood by specific printers. AlphaWRITE's printer drivers detect the presence of an import image file at print time, and determine if this image is valid for this printer.

Files with extensions .IMG, .PS, or .EPS, are valid only on PostScript printers. Files with .PCL, .HP, or .LJ extensions are valid only on the HP LaserJet models.

Imported images in documents will be suppressed if the printer driver determines they are invalid for this printer.

Using the Import Image Feature

To import an image file, from Text Display:

1. Position cursor on the line where you want the laser printer image to print. The column and line where you position the cursor is used as the upper left corner of the printed image.

2. Press ESC /.

3. At the Enter Code prompt, you can choose to import the image file now, or at print time.

   To Import Image File Now:

   At the Enter Code prompt, type **3** to select Image File Now and have AlphaWRITE bring the contents of the image and have it reside under an information block.

   When you use option 3 to select Import Image Now, the image file size cannot exceed 16K (approximately 31 blocks). Also, only one Import Image File Now information block is allowed per line.

   To Import Image File at Print Time:

   Type **4** to select Image File At Print Time and instruct AlphaWRITE to use this image file from the location you specified when you **PRINT** this document.

   When you use option 4 and elect to have your image imported at print time, there is no size restriction on the image file. Also, you can have more than one Import Image File At Print Time per line. If you use more than one on a line be careful during positioning and choosing image size, so images don't overlap or disturb your page layout.

4. At the prompt to supply the filename, type the image file's specification and press RETURN. AlphaWRITE assumes the default extension .IMG and you do not have to include that in your response.

   You are allowed a maximum of 36 characters. If you do not specify otherwise, AlphaWRITE assumes the image file is located in the account in which you are currently logged.

5. At the prompt for Printed Height (Inches), type the printed size you want for this image and press RETURN. Valid responses include fractions to a maximum of nine characters. For example, 0.25 prints the image 1/4" big, where 2.5 prints an image 2.5" high.

Image Files and Document Size

When you request an image file to be included now, instructions to the printer for this image file reside in your document at the location of its information block. Thus, the size of your document is increased by the size of the image file you used. Refer to step 3 for more information.

If you have requested the image file to be included when you **PRINT** the document, only the reference to that particular file resides at the information block and there is a negligible increase in your document's size.

Image File Name Display

When your cursor is on the information block created by the Import Image feature, the image file name and size appears on your display. The message also shows if it the image is imported now or at print time.

USING POSTSCRIPT WITH AlphaWRITE

PostScript is a page definition language used by certain printers and typesetting machines. PostScript is capable of defining almost any output to a laser-printed page.

Some of the more popular PostScript printers are:

- Apple LaserWriter®, LaserWriter Plus, LaserWriter II
- Dataproducts LZR™ 2665
- DEC PrintServer 40™, ScriptPrinter™
- IBM® 4216 Personal PagePrinter
- Linotype Company Linotronic 300, Linotronic 500
- NEC SilentWriter™ LC-890
- QMS JetScript™, QMS-PS 800 series, QMS-PS 2400, PSjet™+
- Qume ScripTEN™
- Texas Instruments® Omnilaser™ 2100 series
- Wang LCS15

AlphaWRITE has a direct PostScript programming feature. Through an embedded text screen you include your own PostScript program in your AlphaWRITE document. When you use the **PRINT** command to send this document to a PostScript (or compatible) laser printer, AlphaWRITE sends the PostScript code to the printer which in turn interprets your PostScript instructions.

Encapsulated PostScript File Format

AlphaWRITE adheres to the EPSF (**E**ncapsulated **P**ost**S**cript File **F**ormat) guidelines published by Adobe Corporation. By adhering to EPSF you:

- Insure your PostScript program will function as intended, even when embedded in the midst of a larger PostScript program. In particular, it will function properly in concert with AlphaWRITE.
- Make it easier for other people to understand your program.

The rules for EPSF in their entirety are contained in supplemental material available from Adobe. Since most PostScript users have the PostScript Language Reference Manual ("the red book"), you may want to refer to its Appendix C for some basic information on structuring conventions.

Creating a PostScript Embedded Program

From Text Display:

1. Position cursor where you want the PostScript information block to appear.
2. Press [EMBED].
3. At the Enter Code prompt, type **9** to select the PostScript option.
4. At the PostScript embedded text display, type in your PostScript program, or **PASTE** in an existing one. The first two characters of your PostScript program must be percent sign, exclamation point:

   %!

   Otherwise, AlphaWRITE will interpret the contents of your embedded text as "raw" data. For more information, please refer to the note about direct ASCII Codes at the end of this section.

   All the editing word processing features available to embedded text screens are available to you while you write your program at this screen. See Chapter 1 for details on working at Embedded Text Screens.
5. Press [EXECUTE] or [EMBED] to return to Text Display.

Getting A Print Out of Your PostScript Program

After you've written a PostScript program, you can get a print out of the program's text. To do so,

1. Position cursor on the PostScript information block whose contents you want to print.
2. Press EMBED.
3. From PostScript embedded text display, press MENU.
4. Use this Editing Menu's **PRINT** command, just as you normally use it.
5. To exit PostScript embedded text display, press EXECUTE or EMBED.

Sample PostScript Program

This sample program shows the PostScript code used to draw the circle illustrated.

```
%!

%Draw a circle.

currentpoint
newpath
50 0 360 arc
stroke
```



How AlphaWRITE Processes PostScript Blocks

In terms of PostScript programming operators (shown in Courier type), AlphaWRITE performs a `mark save` before processing your PostScript information block, and a `restore unmark` afterward. It also temporarily redefines the `showpage` operator. This redefinition has the following results:

- Any changes your PostScript program makes to the environment are undone immediately after the PostScript information block in the document. For example, the following operators will not affect where AlphaWRITE positions on the page, or what typefaces it uses in document text:

  ```
  translate        setfont
  moveto           setlinewidth
  ```

- After the PostScript information block is processed, the stack is restored to its original state. Restoring the stack resolves problems that might be encountered if your program fails to clean up after itself.

- The PostScript `showpage` operator, frequently the last statement of PostScript programs, performs no function. AlphaWRITE's disabling of this operator means that you can import PostScript programs and use them without editing them to remove such keywords.

Absolute and Relative Positioning

Most PostScript operators to `move`, `stroke`, and `fill` come in both absolute and relative varieties. For example, the `moveto` operator is absolute and `rmoveto` is relative.

If your PostScript program makes use of *absolute operators*, its information block position in AlphaWRITE's document text has little or no affect on printed output.

The PostScript absolute operators determine the page position of the program's printed output, regardless of where the PostScript information block is positioned on your document page.

On the other hand, if your PostScript program uses *relative operators*, it is position-independent and its information block position in the AlphaWRITE document text directly determines where the PostScript program affects the printed page.

Many PostScript programs combine absolute and relative operators. These programs are generally not position-independent.

This sample program to draw a box uses absolute positioning:

```
%! Draw a box using absolute positioning (moveto)

270 360 moveto
0 72 rlineto
72 0 rlineto
0 -72 rlineto
4 setlinewidth
stroke
```

This sample program to draw a box uses relative positioning:

```
%! Draw a box using relative positioning (rmoveto)

270 360 rmoveto
0 72 rlineto
72 0 rlineto
0 -72 rlineto
4 setlinewidth
stroke
```

Important Note About Direct ASCII Codes

If you have converted an older version of an AlphaWRITE document that contains /OUT commands, it is converted into a PostScript information block. This conversion is understood because a PostScript information block containing numbers separated by commas (i.e., 233,251,240) are interpreted as direct ASCII codes for AlphaWRITE to output. Thus, the PostScript information block can be used to interface to impact printers.

Recommended Reading

Adobe Corporation. *PostScript® Language Reference Manual*.
Addison-Wesley Publishing Company, Inc., 1986.

Adobe Corporation. *PostScript® Tutorial and Cookbook*.
Addison-Wesley Publishing Company, Inc., 1986.

Writing Postscript Programs To Use As .IMG Files

You can write PostScript programs to be used as image (.IMG) files and import them into your AlphaWRITE document.

If you have the Laser Printer Support Software Product on your computer, you have sample .IMG files which you can inspect for format. Typically, they are located in IMG: (DSK0:[7,30]).

You can use AlphaVUE, Alpha Micro's Text Editor, to inspect any of these .IMG files. The .IMG files are written in PostScript; you can use them as a guideline and reference when creating your own image files.

CHAPTER FIFTEEN
AlphaWRITE'S DICTIONARIES

AlphaWRITE compares words in your document to words in dictionaries whenever you use the SPELL command. This chapter describes the dictionaries AlphaWRITE refers to: the order in which they are referred, the words contained in each, the location of each dictionary and how you can work with them.

THE DICTIONARIES AlphaWRITE USES DURING SPELL

AlphaWRITE verifies the spelling accuracy of a document by comparing each word of the document, one word at a time, to words contained in the AlphaWRITE dictionaries. During SPELL, AlphaWRITE can reference as many as six dictionaries.

Dictionaries are referred to in a particular order during SPELL. When a word is not matched in one dictionary, AlphaWRITE looks to the next dictionary to find a match for the document word. AlphaWRITE continues this process of checking until the document word is found in a dictionary, if the document word can't be matched then you are given options by SPELL for working with the document word in question.

Spell Command's Dictionary Search Path

The following list shows you the order AlphaWRITE uses to search the dictionaries, along with the dictionary's name and the kind of words it contains.

1. Short Dictionary (SHORT.DCT) - message file.
2. Quick Dictionary (SMALL.DCT) - version of Random House Concise® Dictionary.
3. Standard Dictionary (SPELL.DCT) - Random House Concise® Dictionary.
4. Verb Dictionary (VERB.DCT) for languages other than English.
5. Professional Dictionary (named by you)
6. Personal dictionary (LOCAL.DCT) - created by SPELL and updated when you use its insert option.

The next sections describe each dictionary in more detail.

Short Dictionary

The Short Dictionary (SHORT.DCT) is the first dictionary checked during SPELL. This dictionary is in the form of a message file and contains common words having only a few characters. When you begin SPELL, SHORT.DCT is loaded into your memory partition.

Quick Dictionary

The Quick Dictionary (SMALL.DCT) is the second dictionary checked during SPELL. This dictionary is a version of the Random House Concise Dictionary and contains approximately 12,000 of the most commonly used words in English. SMALL.DCT is always in memory unless there is not enough memory available.

Standard Dictionary

The Standard Dictionary (SPELL.DCT) is the third dictionary checked during SPELL. This dictionary is the main Random House Concise Dictionary and contains approximately 80,000 English words.

Verb Dictionary

The Verb dictionary (VERB.DCT) is the fourth dictionary spell checks during SPELL. If the unrecognized word ends in a conjugation ending, then the infinitive form of the word is looked for in VERB.DCT.

Professional Dictionary

If present, the professional dictionary is the fifth dictionary checked during SPELL. This dictionary is prepared by you as described near the end of this appendix.

Local Dictionary

Your local dictionary (LOCAL.DCT) is the last dictionary SPELL checks. This dictionary is originally created by SPELL the first time you use SPELL option I to insert a word in your personal dictionary and it grows with the addition of each word.

If AlphaWRITE does not locate the document's word in any of these dictionaries, you receive a list of SPELL options to work with the questioned word.

These dictionaries are described in more detail in the following pages, in the same order as AlphaWRITE refers to them during SPELL.

Dictionaries and the Mode Command

AlphaWRITE's Editing Menu MODE command has four dictionary options allowing you to choose whether or not AlphaWRITE references a particular dictionary. These four options allow you to choose if AlphaWRITE refers to all or only some of the dictionaries during SPELL.

The default setting for each of the four dictionary options is on, meaning AlphaWRITE refers to them. These are the four dictionaries MODE can control:

- Quick Dictionary, named SMALL.DCT.
- Standard Dictionary, named SPELL.DCT.
- Professional Dictionary, named by you.
- Personal dictionary, named LOCAL.DCT.

The only dictionary you cannot control with **MODE** dictionary options is SHORT.DCT. SHORT.DCT is always referred to whenever you use **SPELL**.

The Short Dictionary - SHORT.DCT

The dictionary named SHORT.DCT is located in DSK0:[7,12] and is the first dictionary **SPELL** uses. SHORT.DCT holds words containing few characters and all of AlphaWRITE's embedded command names. The source file SHORT.M68 for SHORT.DCT can be modified using AlphaVUE, following the procedures for changing message files as described in the *AlphaWRITE Programmer's Information Manual* DSO-00076-00.

Whenever you use the **SPELL** command AlphaWRITE loads SHORT.DCT into user memory, increasing the speed at which **SPELL** works.

The Random House Dictionary - SMALL.DCT

The second dictionary AlphaWRITE refers to during spelling verification is a smaller version of the main Random House Concise® Dictionary. This smaller version of the main dictionary consists of approximately 12,000 of the most commonly used English words.

The file name for this dictionary is SMALL.DCT and it is initially located on DSK0:[7,12]. However, the location of SMALL.DCT may be changed in the AlphaWRITE initialization file with the DICTIONARY command. Refer to Appendix D - "AlphaWRITE's Initialization File" for instructions on relocating the dictionaries.

SMALL.DCT may be loaded into system memory via the AMOS initialization file to increase the speed at which AlphaWRITE performs spelling verification. SMALL.DCT requires approximately 71K bytes of system memory. If you do not have adequate memory available to load SMALL.DCT in system memory, spelling verification is performed at a somewhat reduced rate of speed. For complete information on installing files in system memory, refer to the system initialization command file section in the *AMOS System Operator's Guide*, DSO-00001-00.

When you use **SPELL** AlphaWRITE looks for SMALL.DCT before beginning verification and first looks for it in system memory. If SMALL.DCT is not loaded into system memory, AlphaWRITE attempts to load it into the AlphaWRITE Operator's memory partition before continuing. Once AlphaWRITE locates SMALL.DCT in either system memory or the AlphaWRITE Operator's memory partition, spelling verification begins.

If SMALL.DCT is not found in system memory and there is not enough memory available in the Operator's partition to load SMALL.DCT, AlphaWRITE does not refer to SMALL.DCT at all, but begins the spelling verification process by referring to SPELL.DCT, the main dictionary.

AlphaWRITE verifies the spelling accuracy by comparing each document word to the small dictionary SMALL.DCT. If a word is not found in SMALL.DCT, or SMALL.DCT is not in system memory, or the AlphaWRITE Operator's memory partition, AlphaWRITE then refers to the main dictionary SPELL.DCT.

The Main Random House Dictionary - SPELL.DCT

The main dictionary AlphaWRITE refers to during **SPELL** is the Random House Concise Dictionary, containing approximately 80,000 words. The file name for this dictionary is SPELL.DCT and it is initially located on DSK0:[7,12].

As with SMALL.DCT, the location of the dictionary may be changed by using the DICTIONARY command available in the AlphaWRITE initialization file. See Appendix H "AlphaWRITE's Initialization File" for more information.

The SPELL.DCT dictionary words are ones available for display during dictionary help in the **SPELL** process.

If a word is not found in this main dictionary, AlphaWRITE then checks for a professional dictionary. If you have a professional dictionary on your system, AlphaWRITE then refers to it. If the word in question is not found there, AlphaWRITE checks the last dictionary, LOCAL.DCT.

If you do **not** have a professional dictionary, AlphaWRITE refers to the last dictionary, LOCAL.DCT, for any word not found in SPELL.DCT.

The Verb Dictionary - VERB.DCT

AlphaWRITE automatically searches for and uses a dictionary named VERB. Like the other dictionaries, AlphaWRITE first looks for VERB.lan. If VERB.lan is not found, VERB.DCT is used. If no verb dictionary exists (the normal case for English), no error results and the conjugation feature shuts down.

The location of the VERB dictionary is the same as the main dictionary, SPELL. This is normally WRT:. If the WRITE.INI file contains a DICTIONARY=account command to redirect the location of the dictionaries, this applies to the VERB dictionary as well.

The VERB dictionary's internal structure is identical to that of a professional dictionary. The instructions for creating, sorting, and building a verb dictionary are the same as for a professional dictionary. The usual DICSRT and BLDPRF commands are used. It is up to the creator of the dictionary to insure that only the infinitive forms of regular verbs are included in the verb dictionary.

The Professional Dictionary

AlphaWRITE allows the use of a special dictionary called a professional dictionary. You can create this dictionary using the instructions at the end of this appendix.

The professional dictionary, if present, is the third dictionary AlphaWRITE looks at during SPELL. If a professional dictionary is present and the AlphaWRITE initialization file contains the DICTIONARYTWO command specifying the professional dictionary's name and location, AlphaWRITE uses it for reference.

Professional dictionary words are available for display with dictionary help during SPELL. Words from the professional dictionary appear when you press the HELP key twice when **spell** encounters an unfamiliar word. The first time you press HELP, you see a list of standard dictionary words from SPELL.DCT, the second time you press HELP will display professional dictionary words.

If the document's word is not represented in this professional dictionary, AlphaWRITE then moves on to check the personal dictionary, LOCAL.DCT.

The Dictionary Created By Spell - LOCAL.DCT

The last dictionary AlphaWRITE refers to during SPELL is named LOCAL.DCT. This dictionary is a file, initially located in the AlphaWRITE Operator's account. LOCAL.DCT is created automatically the first time you use the "Insert Word into Personal Dictionary" option available when SPELL doesn't recognize a word. The Insert Word option copies the questioned word into the LOCAL.DCT file. Each subsequent use of the insert option appends the questioned word to LOCAL.DCT.

You can edit LOCAL.DCT to correct errors in capitalization or inadvertent entries made during SPELL. To edit LOCAL.DCT, you must use AlphaVUE. If you are unfamiliar with AlphaVUE, please refer to the *AlphaVUE User's Manual* (DSO-00023-00) for more information.

AlphaWRITE first looks for LOCAL.DCT in the account where the AlphaWRITE Operator is currently logged. If not found there, AlphaWRITE then checks for LOCAL.DCT in the project library account, also called the comma zero account. If not found in either place, AlphaWRITE assumes LOCAL.DCT does not exist.

If no LOCAL.DCT exists in the account where AlphaWRITE is called from, but LOCAL.DCT does exist in a library account, when the insert option is used from the spell verification screen, a copy of the questioned word is placed in the LOCAL.DCT file stored in the library account.

As your personal dictionary grows to contain special words and jargon particular to your business, you may find it useful to make this dictionary available to everyone using AlphaWRITE within the same project series. You can do this by moving LOCAL.DCT to a project library account.

CREATING A PROFESSIONAL DICTIONARY

AlphaWRITE lets you use your own dictionary during SPELL. You can create a new dictionary or prepare an existing dictionary for AlphaWRITE's use.

The next pages describe each of the following steps more thoroughly.

1. Create or have the source of your professional dictionary.

2. Use the DICSRT utility to arrange the words in your dictionary words in alphabetical order.

3. Use the BLDPRF utility to prepare the dictionary file so AlphaWRITE can read it.

4. Include the DICTIONARYTWO command with the prepared professional dictionary's file name, extension and location on your computer.

The Source File

The source for the professional dictionary is a text file containing the list of words to be used. You can make your own list of words by creating a text file with AlphaVUE, Alpha Micro's text editor. Or, you can modify a text file of dictionary words which you have purchased to meet the professional dictionary requirements described in here. Guide lines for this text file are:

- One word per line.
- No one or two letter words.
- Capitalize words requiring capitalization.
- Use lower case for words not requiring capitalization.

Words can contain:

- Letters A through Z, a through z
- Commercial at sign @
- Left and Right Square Bracket [ ]
- Backslash \
- Circumflex ^
- Accent '
- Left and Right Parentheses ( )
- Vertical Bar |
- Tilde ~
- Hyphen -
- Numbers only after the third character

LOCAL.DCT As Source for Professional Dictionary

A typical source file for a professional dictionary is often LOCAL.DCT; the personal dictionary AlphaWRITE creates for you when you use SPELL.

When your personal dictionary becomes large or isn't modified frequently, you may want to consider converting LOCAL.DCT to a professional dictionary using the steps we describe here. If you do, SPELL can refer to the words contained there faster—the professional dictionary is earlier in the search path and the file format makes it more efficient. Once you convert LOCAL.DCT though, give it a name other than LOCAL.DCT—so AlphaWRITE won't check the same words twice.

No matter what source you use for the professional dictionary words, keep it on hand. If it's a source file you can make changes to, you may want to update it from time to time. After an update, it's easy to convert it again and have a current version of your professional dictionary.

Sorting the Source File

Once you create the source text file containing the words to be used in the professional dictionary, or use the text file of an existing dictionary the words must be sorted alphabetically using the DICSRT utility accompanying AlphaWRITE's release.

To sort your file, use the DICSRT command from AMOS command level. At the AMOS prompt, type DICSRT and press RETURN:

DICSRT RETURN

A new prompt appears, asking for the name of the file you want to sort. Type the name of the file, its extension and press RETURN. If you don't specify an extension DICSRT uses the default .SPL.

File to sort: **filenm.ext** RETURN

The following messages appear on your screen as the entries in your text file are sorted:

```
Sorting in process....
Checking for duplicate words....

AlphaWRITE sort is complete!
```

If DICSRT encounters an exact duplicate of a word in the file you named, it removes this word from the file. This action removes any unnecessary duplicates to keep the size of the dictionary file as small as possible.

When DICSRT is through, all words in the file you named are arranged in alphabetical order. The file is now ready to be prepared for AlphaWRITE's use with the BLDPRF utility.

Building the Professional Dictionary

When the source text file for your professional dictionary is in sorted order, you can prepare the file for use by AlphaWRITE.

The BLDPRF utility accompanies AlphaWRITE and is used to build the professional dictionary, that is, prepare it so AlphaWRITE can refer to it during **SPELL**.

To run BLDPRF, at the AMOS command prompt, type BLDPRF and press RETURN:

BLDPRF RETURN

A new field appears asking for the input file name. Type the file name and extension of the sorted dictionary file and press RETURN. If you do not specify an extension, BLDPRF assumes the default extension .SPL.

```
Enter input file name:  filenm.ext RETURN
```

You are then asked to enter the output file name. Enter the file name and extension you want to use for your professional dictionary. If you do not specify an extension, BLDPRF assumes the default extension .DCT. If you want to use another extension, enter it as part of the filename:

```
Enter output file name:  filenm.ext RETURN
```

As BLDPRF builds the dictionary, each word is shown on your screen. Any words encountered which are unacceptable as dictionary words are displayed in square brackets [ ]. Make note of these words. To correct them, you must go back and edit the **source** file and use BLDPRF again.

When BLDPRF is through, it tells you the size of the random file it created which is the size of your built and sorted professional dictionary. The final message BLDPRF displays tells you it is outputting the index table. Then, you are returned to AMOS command level.

You now have a professional dictionary AlphaWRITE can use when you specify the dictionary's name and location in the initialization file with the DICTIONARYTWO command.

Including the Professional Dictionary in the Initialization File

In order for AlphaWRITE to use the dictionary you've made, you must include the dictionary name and location in the initialization file with the DICTIONARYTWO command, as described in Appendix H "AlphaWRITE's Initialization File." If the professional dictionary is not named in this command, AlphaWRITE does not look for or refer to this dictionary during the SPELL command.

CHAPTER SIXTEEN
AlphaWRITE'S DOCUMENT SECURITY

AlphaWRITE offers two protection schemes to secure documents from unauthorized use. Both the standard password and password encrypted protection schemes are described in this chapter.

AlphaWRITE PROTECTION SCHEMES

AlphaWRITE offers a way to protect your documents in the AlphaWRITE Document Header. The Protection field of the Document Header allows three options:

- N for no protection.
- P for standard password protection.
- PE for password encrypted protection.

When either standard password or password encryption protection is selected, access to the document is restricted by the password assigned to this document. Although both options require a password, the password encrypted option takes security a step further.

The following sections describe encryption in more detail then go on to provide you with information regarding both types of protection.

WHAT IS ENCRYPTION?

AlphaWRITE uses an encryption procedure, transparent to you, which actually changes the characters entered in your document at the time it is stored on the disk. This encryption is much like a secret code which only AlphaWRITE can decipher.

Encryption occurs only on the password itself when the standard password protection scheme is chosen. But when the protected encryption scheme is chosen, this kind of scrambling occurs for both the password and the document.

When AlphaWRITE encrypts characters in either protection scheme, those character are scrambled using non-displayable and unreadable characters.

The scrambling of characters takes place whenever you instruct AlphaWRITE to store your document to disk, such as when using the SAVE or FINISH commands.

The encrypted characters are decoded whenever you use the correct password to retrieve your document—for standard protection only the password is decoded, for password encrypted protection both password and document are decoded.

STANDARD PASSWORD PROTECTION

Choosing standard password protection instructs AlphaWRITE to ask for the password you assign whenever someone wants to work with this protected document. Once the password is correctly entered, AlphaWRITE proceeds with the requested operation.

The password associated with the protected document is actually encrypted. However, the rest of the protected document is not changed in any way when it is written out or restored from the disk.

ENCRYPTED PASSWORD PROTECTION

Like standard password protection, password encryption instructs AlphaWRITE to ask for the password you assign whenever someone wants to work with this document. When the password is correctly entered, AlphaWRITE proceeds with the requested operation.

Both the password and the contents of the document are scrambled, that is, encrypted. If someone attempts to use AMOS commands such as TYPE to see the protected document, non-displayable characters are sent to the terminal. The resulting screen display is illegible and the terminal will probably lock up. If this accidentally happens, turn the terminal off and on again to return to AMOS Command level.

When AlphaWRITE encrypts a document, the entire file is modified when being written to or restored from disk. Only AlphaWRITE can interpret the encryption scheme properly— ensuring the security of your document.

APPENDIX A
UNIVERSAL KEY SEQUENCES

The Universal Key Sequence appendix contains a listing of alternate key sequences for AlphaWRITE features. These key sequences work on **all** terminals and are especially useful when your terminal does not have the function or special key normally used by AlphaWRITE.

WHAT IS AN ALTERNATE KEY SEQUENCE?

Alternate key sequences use a combination of two keys—either the [CONTROL] or [ESCAPE] and a character key. The character key is always pressed last in the key sequence.

UPPER OR LOWER CASE?

[CONTROL] and [ESCAPE] by themselves are not affected by pressing [SHIFT] and therefore are not sensitive to upper or lower case.

Letters in the key sequence may be entered as either upper or lower case. On the next pages they are shown in upper case so you can read them easily. Use whichever case is more convenient for you at the time.

Of course, some characters require you to press [SHIFT] to use them, such as an exclamation point, question mark, etc. When this kind of character is called for in a sequence be sure to press [SHIFT] to engage it.

USING THE CONTROL KEY

The [CONTROL] key is sometimes labelled CTRL on your keyboard. To use [CTRL], this is what to do:

Hold down [CTRL] and at the same time press the character shown.

USING THE ESCAPE KEY

The [ESCAPE] key is sometimes labeled ESC on your keyboard. When an alternate key sequence signals you to use [ESC], this is what to do:

Press [ESC] once and release it, then press the character shown.

If You Don’t Have An Escape Key

If you do not have [ESC], use the following method when the key sequence calls for use of [ESC]:

Hold down [CONTROL] and at the same time press [[] (left square bracket key). Release both keys, then press the character shown.

HOW TO USE THE TABLE

If a key sequence in the table contains a hyphen, press the first key and simultaneously press the next key. For example, to use CTRL-C press the key labelled CTRL while you press the C key.

If a key sequence contains ESC, press the key labelled ESC, release it and *then* press the rest of the keys shown. For example, to use ESC P, press and release the ESC key then press the P key.

Where multiple keys are used for an operation, a comma appears between the key sequences. For example, to use the Go To Page feature you see:

ESC K, 2

In two instances a range of numbers appear; any one number in this range is a valid response.

OPERATION	UNIVERSAL KEY SEQUENCE
Auto Insert Character	CTRL-Q
Auto Insert Line	CTRL-\
Beginning of line	CTRL-U
Bin, selection	ESC H, 7
Block Clear	ESC Q
Block Copy	ESC C
Block Delete	ESC D
Block Mark	CTRL-P
Block Move	ESC M
Bold, print feature	ESC N, 1
Break Line	CTRL-B
Bullet, printing	ESC Y, B
Calendar	ESC J
Cancel	CTRL-C
Cent Sign, printing	ESC Y, 5
Center Line	ESC L
Center Screen	CTRL-S
Chapter, set #	ESC H, 3
Chapter, set style	ESC H, 1
Chapter, make new	ESC H, 4
Collapsed Text	ESC &
Collapsed Text	ESC E, B
Color, select printing ink	ESC N, A
Column Mark	ESC @
Compose Character	ESC ’
Copyright Symbol, printing	ESC Y, 9
Cursor Down	CTRL-J
Cursor End of document	CTRL-E
Cursor Home	CTRL-^
Cursor Left	CTRL-H
Cursor Right	CTRL-L
Cursor Up	CTRL-K
Dagger Symbol, printing	ESC Y, 3
Degree Symbol, printing	ESC Y, 1
Delete Character	CTRL-D
Delete Line	CTRL-Z
Delete Word	CTRL-V
Discretionary Hyphen	ESC -
Double Underscore, print feature	ESC N, 9
Em Dash, printing	ESC Y, C
Embedded text menu	ESC E
En Dash, printing	ESC Y, D
End of Line	CTRL-N
Erase to Line End	CTRL-Y
Escape Key	CTRL-[
Execute Command	ESC X
Extended Character	ESC Y, E

OPERATION	UNIVERSAL KEY SEQUENCE
Footer	ESC E, 4
Footer, Even	ESC E, 6
Footer, Odd	ESC E, 5
Footnote, text entry	ESC *
Footnote, text entry	ESC E, 0
Format Text	ESC F
Glossary†	ESC G, xx
Glossary, add entry	ESC G, =
Glossary, date	ESC G, D, 1-5
Glossary, disk and account	ESC G, A, 1
Glossary, display entries	ESC G, ESC ?
Glossary, file name	ESC G, F, 1
Glossary, time	ESC G, T, 1-2
Glossary, user name	ESC G, U, 1
Go to Page	ESC K, 2
Graphics	ESC H, 0
Graphics, begin draw line	ESC H, 0, 1
Graphics, end draw line	ESC H, 0, 2
Graphics, begin draw box	ESC H, 0, 3
Graphics, end draw box	ESC H, 0, 4
Graphics, begin draw gray box	ESC H, 0, 7
Graphics, end draw gray box	ESC H, 0, 8
Graphics, begin draw rounded box	ESC H, 0, 5
Graphics, end draw rounded box	ESC H, 0, 6
Graphics, set gray	ESC H, 8
Graphics, set line weight	ESC H, 9
Gray, print feature	ESC N, 0
Half Symbol, printing	ESC Y, 7
Help Display	ESC ?
Import File, AlphaCALC now	ESC /, 1
Import File, AlphaCALC at print	ESC /, 2
Import File, image now	ESC /, 3
Import File, image at print	ESC /, 4
Indent Text	ESC A
Index, make entry	ESC E, 7
Index, print here	ESC H, 6
Insert Character	CTRL-F
Insert Line	CTRL-B
Insert Word	ESC >
Italic, print feature	ESC N, 4
Join Line	CTRL-O
Keycap	ESC | (vertical bar)
Keycap	ESC N, E
Layout Menu	ESC H
Margin	ESC SPACEBAR

† Where xx represents a two-character glossary code.

OPERATION	UNIVERSAL KEY SEQUENCE
Math Mode On/Off	ESC =
add	+
add column	T
add row	R
clear accumulator	C
divide	/
insert result	=
load accumulator	RETURN
multiply	*
percent	%
subtract	-
Menu	ESC ESC
New Line	ESC RETURN
Next Match	CTRL-X
Next Page	ESC P
Next Screen	CTRL-T
Next Sentence	ESC)
Next Word	CTRL-W
Outline Fonts, print feature	ESC N, F
Outline In	ESC I
Outline Out	ESC O
Overbar, print feature	ESC N, 8
Overprint, print feature	ESC N, B
Page Menu	ESC K
Page #, set number	ESC H, 2
Page #, set style	ESC H, 1
Page Break, hard	ESC K, 1
Page Break, conditional	ESC K, 3
Page Overlay, text entry	ESC E, A
Paragraph Symbol, printing	ESC Y, 2
Playback Keystrokes	ESC ;
PostScript, program entry	ESC E, 9
Previous Match	ESC <
Previous Page	ESC ^
Previous Screen	CTRL-R
Previous Sentence	ESC (
Previous Word	CTRL-A
Quarter Symbol, printing	ESC Y, 6
Record Keystrokes	ESC :
Register Mark, printing	ESC Y, 0
Required Space	ESC W
Return	CTRL-M
Resume Print at Top of Page	ESC K, 4
Reverse, print feature	ESC N, 5
Reverse Case	ESC R
Reverse Character	CTRL-G

OPERATION	UNIVERSAL KEY SEQUENCE
Rubout, erase previous character††	DEL
Scan	ESC V
Screen Left	ESC [
Screen Right	ESC]
Screened, print feature	ESC N, 6
Section Symbol, printing	ESC Y, 4
Special Character	ESC Y
Star, printing	ESC Y, A
Strikeout, print feature	ESC N, 7
Style Menu	ESC N
Subscript	ESC B
Subscript	ESC N, D
Superscript	ESC S
Superscript	ESC N, C
Symbol Display, on/off	ESC _
Tab	CTRL-I
Table of Contents, make entry	ESC E, 8
Table of Contents, print here	ESC H, 5
Trademark Symbol, printing	ESC Y, 8
Title	ESC E, 1
Title, Even	ESC E, 3
Title, Odd	ESC E, 2
Typeface, select	ESC N, 2
Type Size, select	ESC N, 3
Undelete	CTRL-C
Underline	ESC U
User Defined Print Feature	ESC H, A-D

†† The symbol on this keycap differs between terminals.

APPENDIX B
FONT SUBSTITUTION CHARTS

Font substitution gives AlphaWRITE permission to use the closest available typeface when a requested typeface does not exist on the laser printer you selected for printing.

When a document is printed and the selected printer does not support a typeface requested in the document, AlphaWRITE makes a "best match." The tables in this appendix tell you the typeface AlphaWRITE will substitute if the one you request is not present on your printer.

FONT SUBSTITUTION: TURNING OFF AND ON

Font substitution is a feature which can be turned off or on in AlphaWRITE's initialization file or with the **MODE** command. If font substitution is turned off and AlphaWRITE encounters a typeface not supported on this printer, it gives you a message telling you which typeface is not supported and prints your text using the default typeface. The message uses this format:

```
?Font x is not supported by this printer
```

Where x represents the typeface selection character set in the document.

HOW TO USE THE FONT SUBSTITUTION CHARTS

Two font substitution tables are included in this appendix. They apply to:

- PostScript and PostScript-compatible Printers
- Hewlett Packard LaserJet Series Printers

The left column in the tables shows all the typeface choices AlphaWRITE gives you when you use STYLE option 2 to select Typeface. The right column shows the font that particular printer will use when you select the typeface shown. The character in parentheses shows the typeface selection being used.

Bold lines in the table indicate the typeface is **not** available and shows the replacement typeface. Non-bold lines indicate this font selection is available.

FONT SUBSTITUTION FOR POSTSCRIPT PRINTERS

REQUESTED FONT		PRINTED RESULT	
A	Avant Garde	(A)	Avant Garde
B	Bookman	(B)	Bookman
C	Courier	(C)	Courier
D	Dingbats	(D)	Dingbats
E	**Prestige**	**(C)**	**Courier**
F	**Broadway**	**(H)**	**Helvetica**
G	**Garamond**	**(N)**	**New Century Schoolbook**
H	Helvetica	(H)	Helvetica
I	HelvNarrow	(I)	HelvNarrow
J	**Cooper**	**(H)**	**Helvetica**
K	**Presentations**	**(I)**	**HelvNarrow**
L	**Letter Gothic**	**(C)**	**Courier**
M	**Coronet**	**(Z)**	**Zapf Chancery**
N	New Century Schoolbook	(N)	New Century Schoolbook
O	**Optima**	**(P)**	**Palatino**
P	Palatino	(P)	Palatino
Q	**Font Q†**	**(C)**	**Courier**
R	**Bodoni**	**(N)**	**New Century Schoolbook**
S	Symbol	(S)	Symbol
T	Times	(T)	Times
U	**University**	**(A)**	**Avant Garde**
V	**Line printer**	**(C)**	**Courier**
W	**Font W†**	**(C)**	**Courier**
X	**Font X†**	**(C)**	**Courier**
Y	**Font Y†**	**(C)**	**Courier**
Z	Zapf Chancery	(Z)	Zapf Chancery

† These are user-defined font selections. Refer to Appendix I - "User Defined Functions" for more information.

FONT SUBSTITUTION FOR HEWLETT-PACKARD LASERJET SERIES PRINTERS

REQUESTED FONT		PRINTED RESULT	
A	**Avant Garde**	**(H)**	**Helvetica**
B	**Bookman**	**(T)**	**Tms Rmn**
C	Courier	(C)	Courier
D	**Dingbats**	**(C)**	**Courier**
E	Prestige	(E)	Prestige
F	Broadway	(F)	Broadway
G	Garamond	(G)	Garamond
H	Helvetica	(H)	Helvetica
I	**HelvNarrow**	**(H)**	**Helvetica**
J	Cooper	(J)	Cooper
K	Presentations	(K)	Presentations
L	Letter Gothic	(L)	Letter Gothic
M	Coronet	(M)	Coronet
N	New Century Schoolbook	(N)	New Century Schoolbook
O	Optima	(O)	Optima
P	**Palatino**	**(T)**	**Tms Rmn**
Q	**Font Q†**	**(C)**	**Courier**
R	Bodoni	(R)	Bodoni
S	Symbol	(S)	TMS Math
T	Times	(T)	Tms Rmn
U	University	(U)	University
V	Line printer	(V)	Line Printer
W	**Font W†**	**(C)**	**Courier**
X	**Font X†**	**(C)**	**Courier**
Y	**Font Y†**	**(C)**	**Courier**
Z	**Zapf Chancery**	**(M)**	**Coronet Bold**

† These are user-defined font selections. Refer to Appendix I - "User Defined Functions" for more information.

FONT AVAILABILITY ON HEWLETT-PACKARD PRINTERS

Font availability on Hewlett-Packard printers depends on that font existing in the printer, either as a resident font, a cartridge installed in the printer, or a font downloaded to the printer from a computer. Your AlphaWRITE initialization file must have a FONTCARTRIDGE command listing the fonts available for printing. See Appendix H - "AlphaWRITE's Initialization File" for more information.

Font substitution relies on both the font being available from the printer **and** the presence of the FONTCARTRIDGE command. If both of these conditions are not met, font substitution will not take place and the default typeface will be used.

THIRD-PARTY FONT NAMES

Some people use third-party "clone" printers and/or third party fonts. To avoid trademark infringement, alternate names must be used for the third-part fonts. For example, HP calls their font that resembles Times Roman, "Tms Rmn."

Here are some of the more common third-part font names, and what typeface they are supposed to resemble:

Times Roman Look-Alike	**Helvetica Look-Alike**
Tms Rmn (HP	Helv (HP)
Tms Rm (Kyocera)	Helv2 (HP)
CG Times (HP LaserJet III)	Univers (HP LaserJet III)
Dutch (Bitstream)	Swiss (Bitstream)

APPENDIX C
AlphaWRITE'S DEFAULT SETTINGS

COMMAND	FIELD OR FEATURE	DEFAULT
Create	Enter name of prototype document	DEFDOC
Cut	Enter output document name	TEMP
Directory	Default directory file name	DIRECT.LST
	Display all documents?	Y
	Enter directory option	S (Standard)
	Enter printer number	1
	Output to printer	N
Glossary	Enter glossary document name	GLOSS
Header (DEFDOC.WRT defaults)	Allow Format of Text?	Y
	Author	none
	Characters Per Inch (pitch)	10
	Department	none
	Description	none
	Footer Length	0.5"
	Footnote Line Separator	_ (underscore)
	Footnote Print Type	B
	Kerning (N, Light, Med, Tight)	N
	Leading	6
	Left Paper Offset	1"
	Line Spacing (half lines)	2
	Operator	Current User Name
	Orientation (P or L)	P
	Page Length	11"
	Password	none
	Printer Form Name	NORMAL
	Protection	N
	Right Justify (Y or N)	N
	Space before Footnotes	0.5"

COMMAND	FIELD OR FEATURE	DEFAULT
Header (continued)	Text Length	9"
	Title Length	0.5"
	Top Margin	0.5"
	Word Spacing (F, V, or P)	P
Index	Enter prototype INDEX document	INDEX
Mode	**General:**	
	Character insert on?	N
	Fold case during SEARCH and REPLACE?	Y
	Line insert on?	N
	Menu Bypass?	N
	Spell:	
	Use PERSONAL dictionary?	Y
	Use PROFESSIONAL dictionary?	N
	Use QUICK dictionary?	Y
	Use STANDARD dictionary?	Y
	Use VERB dictionary?	Y
	Printing:	
	Reformat for best output?	Y
	Use font substitution?	Y
	Display:	
	On-screen attributes?	Y
	Use color?	N
	Use high and low intensity?	Y
	Use proportional fonts?	N
	Journaling:	
	Perform Keystroke Journaling?	Y
	Keystrokes between updates	16
	Maximum journal keystrokes	20480
Outline	Level 1	Upper Case Roman Numerals
	Level 2	Upper Case Alphabetics
	Level 3	Arabic Numerals
	Level 4	Lower Case Alphabetics
	Level 5	Parenthesized Arabic Numerals
	Level 6	Parenthesized Lower Case Alpha
	Level 7	Lower Case Roman Numerals
Paginate	Enter printer number	1
Paste	Enter input document name	TEMP

COMMAND	FIELD OR FEATURE	DEFAULT
Print	Default typeface	C (Courier)
	Default leading	12 pt
	Default point size	10 pt
	Disk output only	N
	End at page number	9999
	Enter printer number	1
	Number of copies	1
	One page at a time?	N
	Print even-numbered pages	Y
	Print odd-numbered pages	Y
	Start at page number	1
	Use cut-sheet feeder	N
Queue	Enter printer number	1
	Enter printer option	R (Remove)
Sort	Ascending Order?	Y
Toc	Enter prototype TOC document	TOC
Width	Column default	Current terminal setting

APPENDIX D
ERROR MESSAGES

Error and other messages which can appear while you're working with AlphaWRITE are located in this appendix.

The messages are organized alphabetically. Each message is followed by specific information regarding the message, including its probable cause and hints or instructions about how you can correct the problem.

The messages in this appendix are AlphaWRITE's means of communicating with you. Some messages just tell you what AlphaWRITE is doing at the moment so you know everything is in good working order. Other messages let you know you haven't responded properly to a question AlphaWRITE asked you. Still other messages inform you of potential problems with AlphaWRITE or your computer system.

Messages making you aware of possible system problems don't always originate from AlphaWRITE, but come directly through from AMOS, the operating system. Since some kinds of messages do come from the operating system, and AlphaWRITE acts only as a messenger, you may not find them in this appendix. If you see a message on your terminal and cannot find it here, let your System Operator know right away. The message could indicate a problem with your computer, outside of AlphaWRITE, which only your System Operator is qualified to diagnose and resolve.

Abandoning unchanged document

You see this message after using the Editing Menu **QUIT** command on a document where you have not made any changes. AlphaWRITE is letting you know it is leaving your document in the same condition as when you called it up.

You need not worry, no action is necessary.

?AlphaCALC worksheet not found

The AlphaCALC worksheet you requested to be imported at print time cannot be found. Check the worksheet name to be sure there are no typos. Be sure the worksheet is in the account you have specified.

?AlphaCALC worksheet open error

The AlphaCALC worksheet you are attempting to import to your document is currently in use by someone else on your computer. You will not be able to access it until the other person is through. This message may also be caused by a disk error condition.

%Bypassing (filespec)
%No files exported or **%No files imported**

The AWCONV command format you used contained incorrect syntax. Check the command line to be sure there are no extraneous spaces and/or invalid characters. Try again.

?Cannot alter display width on this terminal

If you attempt to use the Editing Menu **WIDTH** command and your terminal does not support 132 column display, you will receive this message. Since your terminal isn't capable of switching between 80 and 132 column display, you won't be able to use **WIDTH**. Sorry.

?Cannot copy document - file not found

AlphaWRITE cannot find the document name you entered to **COPY**. Check the document name you entered to be sure you typed it correctly. Be sure the document exists in the place you specified. Correct any mistakes and try again.

?Cannot erase document - file not found

AlphaWRITE cannot find the document name you entered to **ERASE**. Check the document name you entered to be sure it is typed correctly. Be sure the document exists in this account. Correct any mistakes and try again.

?Cannot generate index - out of memory

While using the **INDEX** command, AlphaWRITE requires memory to sort the index entries for this document—more memory than is currently available in your memory partition. Let your System Operator know you received this message so a corrective action can be taken. System Operator: increase the memory partition size adequately to accommodate the volume of index entries required for the document in question.

?Cannot rename document - file not found

AlphaWRITE cannot find the document name you asked it to **RENAME**. Check the document name you entered; be sure it is typed correctly. Be sure the document exists in this account. Correct any mistakes and try again.

?Can't determine kerning method

AlphaWRITE can't understand the font width table for the font you have selected. The file could be corrupted. Proportional spacing will not work if you receive this error message. Contact your System Operator.

?Can't SAVE or FINISH in demo mode

You are currently working with a demonstration version of AlphaWRITE which will not allow you to use either the **SAVE** or **FINISH** commands. The purpose of the demonstration version is to introduce you to AlphaWRITE and its features.

To make use of all of AlphaWRITE's capabilities you must purchase it; consult your Alpha Microsystems dealer who can make arrangements for its installation on your computer.

%Command ignored

AlphaWRITE has encountered an invalid command, or one it does not recognize, as it processes its initialization file when you first call it up. The command AlphaWRITE ignores is listed in the message.

The command associated with the message will not be carried out. Verify the command is supported. System Operator: check the spelling and format of the initialization file's commands.

Data document is old and must be converted

The data document you specified with the **MERGE** command is from an earlier version of AlphaWRITE. Documents must be in AlphaWRITE 2.1 or later format to be compatible with the current AlphaWRITE software.

Halt your **MERGE** command. To convert your data document, use the **EDIT** command, then **FINISH** from the file. You can also convert your document using the AWCONV utility. Try **MERGE** again.

If your document predates AlphaWRITE version 1.2A, you must first convert it to AlphaWRITE 1.2A before it can be converted to the current AlphaWRITE. If this is the case, please call your dealer for assistance.

?Data document not found

AlphaWRITE cannot locate the data document you entered during **MERGE**. Check the spelling of the data document name. If incorrect, make changes and try again.

If this isn't the problem, check the document directory to be sure the data document you want is there. If it is not in this account, perhaps it is located in another account. You need to supply the full file specification for the data document if it is located in an account other than the one where you are currently logged. You may have to **QUIT**

AlphaWRITE and locate the data document you want to use and try again.

?Device Full

Let your System Operator know immediately if you receive this message.

System Operator: this message means there is not adequate disk space for this user to **FINISH** or **SAVE** from their current document. The user can abort from this session with their document or retry the command. For the retry to be effective, you must free up some disk space for them. You can erase or move files from their device to increase disk space.

Divide by zero

In math mode, during the current calculation, you made an attempt to divide a number by zero. This is an invalid mathematical operation, although one AlphaWRITE lets you attempt. In response, AlphaWRITE displays the largest number it is capable of displaying—approximately 1×10^{38}. Press [C] to clear the accumulator of this value and don't attempt to divide by zero.

?Document already exists

The document name you entered in **CREATE, COPY** or **RENAME** already exists. Check the directory list to determine a unique document name and try again.

Document already exists - overwrite? (YES or NO):

The document name you entered already exists but you can overwrite it. To do so, type **YES** [RETURN].

To keep this document, type **NO** [RETURN] and you will leave the existing document unchanged. You are then given another chance to enter a new document name at the command screen.

?Document does not exist

The document name you specified to **PASTE** into this one does not exist. Be sure you entered the document name correctly. If you have given a full file specification, be sure it is correct and try again.

Document in use

The document you are attempting to use is currently in use by someone else. You will be able to work with it once the other person is finished.

?Document invalid

The contents of the document you are trying to access are invalid. The file could have been corrupted in some way. Let your System Operator know you received this message.

Document has been corrupted and cannot be edited

AlphaWRITE encountered an unexpected byte when it attempted to load the document for editing. This could indicate disk problems. Let your System Operator know you received this message. System Operator: You can restore the .BAK file and EDIT it.

Document names must be from one to six alphabetic or numeric characters

The document name you are attempting to CREATE or use is not a valid document name. Document names cannot exceed six characters. Valid characters are numbers and letters. Try again.

Error in variable list

The data document you specified with the MERGE command contains an error in the variable line. Halt MERGE and EDIT the data document you specified. Be sure the variable definition line uses the correct format: surround the text in angle brackets and separate each one with a comma.

File in use

The file you are attempting to use is currently in use by someone else. You will be able to work with it once the other person is finished with it.

File is too large to paste into embedded text

AlphaWRITE allows a maximum file size of 32 blocks (16K) to be PASTEd into an embedded text information block. The file you specified exceeds the maximum allowed. Sorry.

File not found

AlphaWRITE cannot find the filename you specified. Be sure you have typed the name correctly; be sure the file is actually in the location you have specified. Try again.

?Font not found: font name

Where **font name** is the font you selected using the [STYLE] key. Font substitution is not turned on, and the font you requested in this document is not available on this printer. Your document will **PRINT** using the default font in use on your printer.

?Footer calculation error

The text in the footer exceeds the size allowed for it by the format settings currently in effect.

Use the **HEADER** command, or the [MARGIN] format screen, to adjust the space allowed for printing your footer text. Your other option is to reduce the length of your footer text.

Glossary definition already exists

The on-line glossary addition you just attempted to make currently exists in your glossary document. Choose a unique two-character code identify this entry.

To see a list of the defined glossary definitions for the currently selected glossary document, exit on-line glossary addition. From text display use [GLOSSARY] [HELP].

(HELP not available)

You have requested **SPELL** to display a list of dictionary words from a dictionary which is not currently selected to be used by **SPELL**. Check the **MODE** command settings for the dictionaries; if they are turned off—set to N—turn them on by typing **Y**.

If these dictionaries are not present on your computer, you will not be able to display a list of words. Sorry.

?Illegal value in initialization file: message

Your AlphaWRITE initialization file contains a command whose argument value is invalid, as shown by the word **message**. Let your AlphaWRITE Administrator or System Operator know you have received this message.

The initialization file must contain correct and valid arguments for each of its commands in order for this particular instruction to be understood by AlphaWRITE. This command's format may be entered incorrectly. Information about AlphaWRITE's initialization file and its commands is in Appendix H - "AlphaWRITE's Initialization File."

?Image file not found

During printing, AlphaWRITE cannot find the image file you identified with the Import feature and therefore cannot print it. Check to be sure you supplied the correct file name, disk and account location. Be sure the image file is present in the location you named.

?Image file open error

The image file you requested for printing with the Import feature is currently in use by someone else on your computer. Until it is available, your document will not be printed with this image included. Wait a minute or so and try printing this document again. If the image file is still in use, let your System Operator know you have received this message. Perhaps a duplicate image file can be made so access conflicts can be prevented.

?Improper overlay version:

AlphaWRITE matches the major, minor, sub-letter and edit elements of the version number associated with each of its overlays with that belonging to WRITE.LIT. For example, using this version number:

1.0A(100)

the major element is 1, the minor element is 0, the sub-letter element is A, and edit element is 100.

Let your System Operator know you received this message.

System Operator: this message means one of the elements associated with an AlphaWRITE overlay does **not** match that of WRITE.LIT. Possible causes are: one version's overlay files are being used with a newer or an older version of WRITE.LIT, or one of the overlay files has been corrupted. Verify the overlays are correct and if necessary restore them from a backup of your software or from the AlphaWRITE installation tape.

Incorrect entry

You've made an invalid entry in a field on the Document Header or [MARGIN] format setting screen. Press [HELP] while the cursor is in the offending field to display the acceptable responses in this field and try again.

Or, in response to [ESC] [#] to enter an extended character, you made an invalid response. See the *Programmer's Information Manual* for information.

Index prototype is old format and must be converted

The **INDEX** document you specified with the **INDEX** command is from an earlier version of AlphaWRITE. Documents must be in AlphaWRITE 2.1 or later format to be compatible with the current AlphaWRITE software.

Halt your **INDEX** command to convert your index document, and exit the document you are trying to index. Use the **EDIT** command to call up the offending index prototype document, then **FINISH** from the file. You can also convert your document using the AWCONV utility. Try **INDEX** again.

If your document predates AlphaWRITE version 1.2A, you must first convert it to AlphaWRITE 1.2A before it can be converted to the current version of AlphaWRITE. If this is the case, please call your dealer for assistance.

?Input document not found

The document name you supplied to AlphaWRITE cannot be found. Double check the document name's spelling. Correct any mistakes and try again.

If the spelling is correct, display the document directory list to be sure the document you want is in the account where you are currently logged. If the document isn't there, you may need to **QUIT** AlphaWRITE and log into the account where the document is located.

?Insufficient memory to SPELL check

The amount of memory currently available to you from your memory partition is not adequate to run **SPELL**.

If you are using a professional dictionary and its use is not absolutely necessary for spell checking this document, you may choose to disable its use temporarily by using the **MODE** command's dictionary option. The professional dictionary requires excess memory and disabling it may free up enough memory to run **SPELL**.

Otherwise, your only course is to ask your System Operator to increase the size of your memory partition. System Operator: the **SPELL** command alone requires approximately 175K of memory to run.

?Invalid document name

The document you specified is not an AlphaWRITE document. Check to make sure you entered the name correctly and try again.

Invalid message file

Someone has incorrectly modified one of AlphaWRITE's message files, and AlphaWRITE cannot understand it. Or, the message file was corrupted on the disk. Let your System Operator know you received this message.

ITC error

ITC is an acronym for **I**nter-**T**ask **C**ommunications. This kind of error is related to printers and printing. The message can occur when you use **PRINT**, the **DIRECTORY** print option, or **QUEUE**.

The printer associated with this message is available for you to use but for some reason is experiencing a problem. The problem could be:

1. The printer spooler controlling the printer's activity is experiencing a problem.

2. A network printer didn't respond to AlphaWRITE in the amount of time AlphaWRITE allotted.

3. A network printer is off-line.

4. You are not currently on the network and therefore do not have access to a network printer.

5. The system with the network printer is not currently on the network.

Wait a few moments and try your request again. If you still receive this message when trying to print a document on a printer available via your computer's network, try a printer on your own system.

If you have no other printer and must use the network printer make sure you are currently linked on the network.

If your second request to use a printer on your system still results in this message, let your System Operator know you received this message. Your System Operator who determine what steps you should take next.

Line or box number already in use: number

Where **number** represents the element number associated with this graphic instruction. The message appears during printing and will also show the page and line number where the offending graphic resides.

Before you can re-use a graphic element number, it must already be used as a begin **and** end instruction. Check your document to be sure you have ended the graphics instruction with the same element number you began it with and try again.

Line overflow

AlphaWRITE's internal line counter has lost track of the correct line position the cursor should be on. To remedy the situation, press HOME to go to the beginning of your document. This action resets the internal and displayed line counters to zero; AlphaWRITE can now calculate the line positions accurately.

?Line stack overflow

This is an internal AlphaWRITE error. During **PRINT, PAGINATE,** or **PREVIEW,** AlphaWRITE has run out of memory. You can still print, but your document may not be formatted correctly. Let your System Operator know you received this message.

Line underflow

AlphaWRITE's internal line counter has lost track of the correct line position the cursor should be on. To remedy the situation, press HOME to go to the beginning of your document. This action resets the internal and displayed line counters to zero; AlphaWRITE can now recalculate the line positions accurately.

Math error

You pressed a key or made an entry to Math mode's accumulator that it did not understand. Only certain keys are operational when using Math mode.

Refer to the chapter describing Math mode for more information. Generally, valid keys are plus sign, minus sign, asterisk, slash, percent sign, equal sign, RETURN, decimal (period) and cursor moving keys.

Memory module not found

A file AlphaWRITE is trying to access, which had been loaded into memory, is no longer there. A system error may have occurred. Let your System Operator know you received this message.

No block is marked

The feature you intend to use requires a column or block of document text to be marked. No text is currently marked. Mark the area you want to work with and try again.

No dictionaries available

After you request **SPELL**, AlphaWRITE looks for the dictionaries currently selected for use by **MODE**. If the **MODE** dictionary spell checking options are all turned off, AlphaWRITE is not able to access any of its dictionaries. If this is the case, use **MODE** and enable the dictionary settings.

If the **MODE** spell checking options are on, then for some other reason AlphaWRITE cannot locate the dictionaries. Perhaps there is a DICTIONARY command in the initialization file pointing to a location where the only available dictionary is supposed to reside and does not. Let your System Operator know you received this message.

System Operator: To remedy, make sure the dictionaries are in the account where AlphaWRITE expects to find them.

?No font width table for font

The font width table file for the typeface you selected with the STYLE Typeface option cannot be found where AlphaWRITE expects it to be. Your document can still be printed, though proportional spacing will not be correct. Let your System Operator know you received this message.

System Operator: be sure all font width tables are located in AlphaWRITE's account. Refer to Appendix N - "Font Width Tables" for more information. Also refer to the *AlphaWRITE 2.0 Release Notes* for their installed location.

No more levels

In outline mode, only seven outline levels are available. You have attempted to exceed this number.

?No response from task manager

You have used **QUEUE** to display information and the task manager is not responding. This is caused by an AMOS problem, not AlphaWRITE. Let your System Operator know you received this message.

No tabs

You pressed [TAB] when there were no tab stops set and available on the line. Use [MARGIN] to set tab stops.

Not a number

While in Math mode, you requested an operation on non-numeric characters. Check the location where you positioned the cursor to work with a number. If it is on a character Math mode considers to be non-numeric, move the cursor to a numeric character. A list of numeric characters is given in the chapter describing Math mode.

?Not an AlphaWRITE document

The document name you specified is not an AlphaWRITE document (.WRT file) and you can't perform the operation you requested on it. You must identify a valid AlphaWRITE document. Try again.

Not found

The information AlphaWRITE is looking for cannot be located.

If you see this message during [GLOSSARY], it means the two-character code you specified is not defined in the glossary document currently being used. Check the available entries by using [GLOSSARY] [HELP]. Be sure you are using the correct capitalization for the two-character code.

If you see this message when using [NEXT MATCH] or [PREV MATCH], it means AlphaWRITE cannot find any further occurrences of the text you asked it to look for.

Out of memory

AlphaWRITE doesn't have enough memory to perform the operation you requested. Follow the directions on your screen for how to proceed. Let your System Operator know you received this message.
System Operator: you can display information regarding AlphaWRITE's version number, operating system version number, user memory partition size and details about the memory map by using the DEBUG command from the AlphaWRITE Main Menu.

Output document already exists - overwrite it?

During **MERGE** you specified an output document name that already exists in this account. You have these choices:

1. Type **YES** [RETURN] to overwrite this document.

2. Type **NO** [RETURN] to keep the existing document and re-enter a new document name.

You can use [↑] and [↓] to see a list of the document names used in this account.

Overflow

During math operations, the number the math feature is currently working with exceeds approximately 1×10^{38}, which is the largest number math mode can handle. AlphaWRITE displays the largest number it is capable of in the accumulator. Press [C] to clear the accumulator.

If you are working with financial numbers, express the numbers in terms of hundreds or thousands—whatever units or division is appropriate for your calculations—and try again.

?Overlay not found: filename

AlphaWRITE uses a series of program overlay files to perform various feature operations. The overlay file named by **filename** cannot be found. Let your System Operator know you have received this message.

System Operator: Refer to the *AlphaWRITE 2.0 Release Notes* for information regarding the files AlphaWRITE requires for its operation.

Page format error

AlphaWRITE lets you know the Document Header contains entries exceeding the page format size specified. displaying this error message.

Use these formulas to check that page format settings are in the range AlphaWRITE expects:

```
Top Margin + Title Length + Text Length + Footer Length <= Page length
```

If your unit of measurement is lines, you can use the following formula:

```
Page length (in inches) x Leading (in lines) = Page length in lines
```

Printer Driver not found

After you select a printer to use with the **PRINT** command, AlphaWRITE looks for and loads the printer driver used by this printer. For some reason the printer driver associated with the printer you selected cannot be found. Let your System Operator know you received this message.

System Operator: Check the PRINTER command line in the AlphaWRITE Initialization command file to be sure the printer driver specified actually exists in DVR: (DSK0:[1,6]).

Printer Spooler Not Found
[Press any key to continue]

This error message means you are printing to a nonexistent printer; that is, a printer not defined as one available on your computer. AlphaWRITE will "print" your document as a disk file with the same document name but with a numeric extension such as, .000, .001, etc. AlphaWRITE waits until you press a key to continue to be sure you are aware of this printing event. Let your System Operator know you received this message.

?Printing of file has started

You are trying to select the document currently printing as the document to print next with **QUEUE**'s Select option. This is not allowed. Only documents or files **waiting** to be printed can be selected to print next.

Protected block

AlphaWRITE secures instructions in your text—such as the margin information block or page breaks—so they cannot accidentally be deleted. Move the cursor off of the information block before you press any more keys.

?Prototype document not found

During **CREATE**, you have specified a prototype document name AlphaWRITE cannot locate. Check the spelling of the document name by displaying a directory list. Correct any spelling errors and try again.

If the prototype document is still not found, the document may not be in the same account as you are currently logged. Be sure you are logged into the account where the prototype document is located, or that a copy of this document exists in the account where you are are currently logged.

?Queue entry not found

The document number you specified does not appear on the list of documents shown when you used QUEUE. Check the document number you entered and be sure it is shown in the list of documents displayed. Please try again.

?Sorry - I can't help you on that subject

You have requested help on a topic for which AlphaWRITE has no information. This message appears if you mistype a help screen topic number. Check the number to be sure you've entered it correctly and try again.

This message can also mean the text file associated with the help topic cannot be found. If you continue to receive this message when choosing the same help topic, let your System Operator know.

Sort error - line too long

The column of document text marked for the SORT command exceeds the maximum line length allowed. The SORT command can rearrange lines up to 255 characters long. Shorten your marked column width or adjust your line length. Re-mark the column and try again.

?Specified string was not found

AlphaWRITE finds no occurrences of the characters you've asked it to find. The characters you entered cannot be matched to any in your document's text.

If you think there should be a match try again and re-enter the string—taking care not to make any typing mistakes. If this message still occurs, the capitalization you use for the characters you are looking for may be important. If so, MODE's Fold Case option may be set to N and you need to use the exact capitalization you want to find. You can also change the MODE Fold Case option setting.

Also, if you have a marked block in your document, AlphaWRITE searches only the marked text. If necessary, clear the block marks and try SEARCH again.

TOC prototype is old format and must be converted

The TOC prototype document you specified with the TOC command is from an earlier version of AlphaWRITE. Documents must be in AlphaWRITE 2.1 or later format to be compatible with the current AlphaWRITE software.

Halt your TOC command. To convert your TOC prototype document, exit from the document you are using now. Use the EDIT command to call up the offending TOC document, then FINISH from the file. You can also convert your document using the AWCONV utility. Try TOC again.

If your document predates AlphaWRITE version 1.2A, you must first convert it to AlphaWRITE 1.2A before it can be converted to the current version of AlphaWRITE. If this is the case, please call your dealer for assistance.

Template document is not an AlphaWRITE document

The template document name you specified to the MERGE command is not an AlphaWRITE document. Check the document name and try again.

Template document is old and must be converted

The template document you specified with the MERGE command is from an earlier version of AlphaWRITE. Documents must be in AlphaWRITE 2.1 or later format to be compatible with the current AlphaWRITE software.

Halt your MERGE command. To convert your template document, use the EDIT command, then FINISH from the file. You can also convert your document using the AWCONV utility. Try MERGE again.

If your document predates AlphaWRITE version 1.2A, you must first convert it to AlphaWRITE 1.2A before it can be converted to the current version of AlphaWRITE. If this is the case, please call your dealer for assistance.

?Template document not found

AlphaWRITE cannot locate the template document you specified with MERGE.

Check the spelling of the document name. Display the directory list to check document names. Correct any spelling errors and try again.

If the template document is still not found, the document may not be in the account where you are currently logged. Be sure you are logged into the account where the template document is located or you have provided a full file specification for its location on your computer.

?That command may only be used while editing main document text

While working at any embedded text screen, only certain Editing Menu commands are available. You have attempted to use a command which is unavailable from embedded text display. Invalid embedded text Editing Menu commands are shown in dim display at the Editing Menu.
The command you requested will be available once you return to your main document text by pressing either [EMBED] or [EXECUTE].

?That document is in use at the moment

The document you have requested is in use by someone else right now. Wait a few moments and try again.

That is not the correct password for this document

The password you entered does not match the one associated with this protected document. Re-enter the password for this document, being sure its spelling is right. Let your System Operator know if you still receive this message.

?That printer does not exist

You are trying to use a printer attached to another computer available to you through a network, and AlphaWRITE cannot find the printer. It's possible the printer's name was changed on the other computer. Let your System Operator know you received this message.

The document you are requesting is in use right now.

AMOS' file locking feature (LOKSER) has reported to AlphaWRITE that the document you want to EDIT or CUT is currently being used by someone else. A single document or file cannot be used by two people at the same time. When they are through working with it you will be able to use it.

The keystroke journal file is full. AlphaWRITE will not be able to store any more of your keystrokes until the next time you SAVE, QUIT, or FINISH. Any of these actions will clear the journal file. The usual action to take when the journal file fills up is to simply enter the SAVE command from the Editing Menu. Keystroke journaling is now temporarily suspended.

To resume keystroke journaling, press [MENU] from Text Display to display the Editing Menu and use SAVE. Once you do this, keystroke journaling will resume.

The personal dictionary has been disabled

The MODE command spell checking option for your local dictionary is turned off. You must be able to access your local dictionary when you use SPELL and attempt to use the insert option (option `I`) to put a word in your local dictionary. Use MODE and turn on the local dictionary option.

The preview command cannot run because AMIGOS has not been installed

The PREVIEW command is supported on AMIGOS-compatible terminals on computers where AMIGOS is installed and up and running. AMIGOS has not been installed on your computer. Install AMIGOS and try again. See the *AMIGOS Reference Manual* for more information.

The preview command cannot run because there is no graphics driver

The PREVIEW command is supported on AMIGOS-compatible terminals on computers where AMIGOS is installed and up and running. The terminal you are using to PREVIEW is not an AMIGOS-compatible terminal. PREVIEW on your terminal is currently unsupported. Sorry.

?The printer does not support printwheels or font cartridges.

You have selected a printer to use with QUEUE's Font option that does not support printwheels or font cartridges. Be sure you have selected the correct printer from the list of printers and try again. Check the printer to be sure it supports printwheels or font cartridges.

The spelling dictionary file has been corrupted: filespec

Where **filespec** is the name of the dictionary file. This dictionary file has been corrupted on the disk and cannot be used. Let your System Operator know you received this message.

System Operator: restore this dictionary file from a backup tape.

There are no fields in the data document

When using MERGE you selected a data document which does not contain any data definition fields. Valid data documents must have at least one data field defined. Check your data document to be sure it is in the correct format. Be sure you have specified the correct document as your data document.

%There are no documents in this directory

This message may appear during DIRECTORY or any request to display a directory list at a command screen. There are no existing documents in this account, where you called up AlphaWRITE.

If there should be existing documents, check to be sure you have logged into the proper account. If you are logged into the right account and receive this message,let your System Operator know.

?There is no marked block of text to cut

There is no marked text in your document for CUT to copy to another document. Press [MENU] to return to your document text display and use [BLOCK MARK] to select the portion of this document you want to CUT. Try the command again.

?There is no marked column to sort

You used the **SORT** command before you marked the text you wanted **SORT** to rearrange. Press any key to return to your document text display. Use [COLUMN MARK] operations to designate the text you want **SORT** to rearrange and try again.

%There are no such documents in this directory

There are no documents in this directory matching the criteria you've entered during the **DIRECTORY** command. Make sure you are in the correct account and have entered the criteria you want.

?There isn't enough memory for this command: command

You might see this message during any AlphaWRITE command but you have received it in response to using the **command** shown. The command requires more memory than is available in your job partition. Let your System Operator know you received this message.

System Operator: you may want to increase the amount of memory assigned to this user.

?This command is not available while in embedded text

While at an embedded text screen, reached through the [EMBED] key, you have requested an Editing Menu command that cannot be used on embedded text. The Editing Menu display you have access to from embedded text shows the unavailable commands in dim display.

This font does not exist on your printer

The document you are currently trying to **PRINT** contains a typeface command that is not available on the printer you selected. Send your document to a printer that you know supports the typeface selected. Or, use a FONTSUBSTITUTION command in your AlphaWRITE intialization file. Or, modify your document's typeface information blocks to a font you know is present on the printer available to you. Try printing again.

Too long

You can see this message if you try to go past column 255 of your document, or at various points in AlphaWRITE's operation when you respond to prompts.

The answer you gave in response to AlphaWRITE's question is longer than what is allowed. This message appears when more than 6 characters are entered for a document's name, more than 10 characters are used for a password or anywhere AlphaWRITE sets a limit on the number of characters you use in response.

Check your entry to be sure it has the appropriate number of characters for this response, and try again.

Unable to allocate file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to allocate memory module

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to close file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to deallocate memory module

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to delete file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

?Unable to justify text

The format setting for justify is set to Y and word spacing is set to proportional, but the printer you've chosen doesn't support proportional text. Either choose a printer that supports proportional spacing or change the word spacing setting.

Unable to load file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

?Unable to load font width table

AlphaWRITE can't find the font width table for the font you selected. You can still print the document, but you may not get the results you expect. Let your System Operator know you received this message.

Unable to load message file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to load overlay

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to open file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to read from file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to rename file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Unable to write to file

This message indicates a possible operating system error. Follow the instructions on your screen. Let your System Operator know you received this message.

Underflow

During math operations, the number the math feature is currently working with is smaller than what it can handle. In response, AlphaWRITE displays the number it considers to be equivalent to zero.

If you are working with fractional numbers, express the numbers in terms of hundredths or thousandths, whichever division is appropriate for your calculations. Try again.

?Unrecognized command - type HELP for more information

AlphaWRITE does not understand the command you typed at the menu. Check your entry to be sure your spelling of the command matches the spelling displayed on the menu.

Be sure an abbreviation you used is correct. Try again, type **HELP**, or press HELP for more information.

?Unrecognized command in initialization file: command

The **command** shown in the message is not recognized as a valid AlphaWRITE initialization file command. Let your System Operator know you have received this message.

System Operator: Be sure the initialization file's commands are spelled correctly, contain valid arguments and/or parameters. Refer to Appendix H - "AlphaWRITE's Initialization File" for more information.

Unsupported document version

The document you are attempting to use with the current version of AlphaWRITE is in an old format and cannot be supported. The document must be converted to a minimum AlphaWRITE version of 1.2A before the current version of AlphaWRITE can work with it. If you have AlphaWRITE 1.2A on your computer, use it now to convert the document in question. If you do not have AlphaWRITE 1.2A available to you, please call your dealer.

Warning: an error condition has occurred. The error is: message

Where message tells you what the specific error was. Look under the specific message in this appendix. Possible messages include but are not limited to:

File in use
ITC error
Invalid message file
Memory module not found
Out of memory
Unable to allocate file
Unable to allocate memory module
Unable to close file
Unable to deallocate memory module
Unable to delete file
Unable to load file
Unable to load message file
Unable to load overlay
Unable to open file
Unable to read from file
Unable to rename file
Unable to write to file

Warning: printer does not support full character set

The document you are printing now contains extended character instructions, such as international characters or the built-in PostScript extended characters. The printer you sent the document to does not support the characters you have requested. Be sure you have sent the document to the correct printer. AlphaWRITE will make best-choice character substitutions for the 8-bit characters it does not understand.

System Operators Note: If the printer does support extended characters, be sure the printer is defined using a printer driver which supports the character set. See the *AlphaWRITE Installation Instructions* for more information.

?You must confirm with "YES" in order to quit

The response you gave to the **QUIT** "Do you wish to abandon your changes?" prompt was something other than **YES** [RETURN].

Type **YES** [RETURN] if you want to leave your document without keeping your latest changes, press [MENU] if you do not want to **QUIT** now.

APPENDIX E
SUPPORTED PRINTER FEATURES

Not all of AlphaWRITE's printing features are available on every printer. The following chart shows the features available on the printers supported by AlphaWRITE 2.1 and later. The notes associated with the superscripted numbers appear at the end of the chart.

Print Feature	Apple Laser-Writer+	HP LaserJet II/IID/IIP III/IIID	AM-301/ AM-302	AM-306	Misc.
Bin Commands	yes	yes	yes	no	no
Bold	yes	yes	yes[1]	yes	yes[1]
Bullet	yes	yes	no	no	no
Compose Character	yes	yes	no	no	no
Change Color	no[2]	no	no	yes	no
Double Underscore	yes	yes	no	no	no
Draw line	yes	yes	no	no	no
Draw box	yes	yes	no	no	no
Draw rounded	yes	yes[3]	no	no	no
Draw gray box	yes	yes	no	no	no
Em dash	yes	yes[4]	yes[4]	yes[4]	yes[4]
En dash	yes	yes[4]	yes[4]	yes[4]	yes[4]
Ext. Chars. Built-in[9]	yes	no	no	no	no
Fonts 0-9	yes	yes	yes	no	no
Fonts A-Z	yes	yes	no	no	no
Gray	yes	yes[5]	no	no	no
Italic	yes	yes	no	no	no
Keycap	yes	no	no	no	no
Outline Fonts	yes	no	no	no	no

Print Feature	Apple Laser-Writer+	HP LaserJet II/IID/IIP III/IIID	AM-301/ AM-302	AM-306	Misc.
Overbar	yes	yes	no	no	no
Orientation (P)	yes	yes	yes	yes	yes
Orientation (L)	yes	yes	no	no	no
Overprint	yes	yes	yes	yes	yes
Page Overlays	yes	no	no	no	no
PostScript	yes	no[6]	no[6]	no[6]	no[6]
Print Image	yes	yes	no	no	no
Reverse	yes	no	no	no	no
Screened	yes	no	no	no	no
Sheet Feeder	yes	yes	yes	no	no
Special Chars	yes	yes[7]	yes[7]	no	no
Star	yes	yes[8]	yes[8]	yes[8]	yes[8]
Strikeout	yes	yes	yes	yes	yes
Subscript	yes	yes	yes	yes	no
Superscript	yes	yes	yes	yes	no
Type sizes	yes	yes	no	no	no
Underscore	yes	yes	yes	yes	yes

NOTES:

1. Bold is simulated by overprinting.
2. Color settings are translated to changes in gray shading.
3. Rounded box is simulated with a cornered box.
4. Em and en dash are simulated with a standard dash.
5. HP LaserJet IID, IIP, III, IIID, and IIIP only.
6. The PostScript feature can be used as a replacement for the /OUT command.
7. Availability of all characters is dependent upon the font cartridge or printwheel in use.
8. Star is simulated with an asterisk.
9. Extended characters built-in for PostScript compatible printers.

APPENDIX F
POSTSCRIPT SAMPLE FONT FAMILIES

POSTSCRIPT FONT FAMILIES

The chart below illustrates the typestyle of the PostScript fonts available with the STYLE typeface option (option 2). The typefaces shown are:

Avant Garde	New Century SB
Bookman	Palatino
Courier	Times-Roman
Helvetica	Zapf Chancery
Helv-Narrow	

The samples are in 11 point, no bold, no italic.

TYPE-FACE:	FONT NAME	POSTSCRIPT NAME	SAMPLE
A	Avant Garde	Avant Garde	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-='_+~|
B	Bookman	Bookman	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-='_+~|
C	Courier	Courier	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-='_+~|

TYPE-FACE:	FONT NAME	POSTSCRIPT NAME	SAMPLE
H	Helvetica	Helvetica	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-='_+~|
I	Helv-Narrow	Helv-Narrow	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-='_+~|
N	New Century	New Century SB	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-=' _+~ |
P	Palatino	Palatino	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,. / <>?;':"{}[] !@#$%^&*()-=' _+~ |
T	Times	Times-Roman	The quick brown fox jumped over the lazy dogs. ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 1234567890,./<>?;':"{}[] !@#$%^&*()-='_+~|
Z	Zapf Chancery	Zapf Chancery	*The quick brown fox jumped over the lazy dogs.* *ABCDEFGHIJKLMNOPQRSTUVWXYZ* *abcdefghijklmnopqrstuvwxyz* *1234567890,./<>?;':"{}[]* *!@#$%^&*()-='_+~*

Dingbats and Symbol Typefaces

The charts on the below illustrates the Dingbats and Symbol typefaces, available with the STYLE typeface option (option 2). The first column labeled "Char" is the key you press while in the Dingbats or Symbol typeface to get the character shown in the column labeled "Ex" and "Description." For example, to print the Dingbats character described as Nova 2:

1. Press STYLE.
2. Type **2** to select typeface, type **D** to select Dingbats.
3. Type **G** to select Nova 2.
4. Return typeface from Dingbats to previous setting.

Dingbats Typeface

CHAR	EX.	DESCRIPTION
A	✡	Jewish star
B	✣	Quadrifid 1
C	⌘	Quadrifid 2
D	⌘	Quadrifid 3
E	✣	Quadrifid 4
F	✦	Nova 1
G	✧	Nova 2
H	★	Star 1
I	☆	Star 2
J	✪	Star 3
K	☆	Star 4
L	☆	Star 5
M	☆	Star 6
N	☆	Star 7
O	☆	Star 8
P	☆	Star 9
Q	✶	Six pointed star 1
R	✶	Six pointed star 2
S	✶	Eight pointed star 1
T	✶	Eight pointed star 2
U	✶	Eight pointed star 3
V	✶	Six pointed star 3
W	✶	Eight pointed star 4

CHAR	EX.	DESCRIPTION
X	✷	Eight pointed star 5
Y	✹	Twelve pointed star
Z	✺	Eighteen pointed star
a	❁	Flower 1
b	☼	Sun
c	❀	Flower 2
d	❄	Snow flake 1
e	❄	Snow flake 2
f	❄	Snow flake 3
g	✳	Design 1
h	✺	Design 2
i	❇	Design 3
j	❇	Design 4
k	✳	Design 5
l	●	Circle
m	❍	Eclipse
n	■	Box 1
o	❑	Box 2
p	❒	Box 3
q	❑	Box 4
r	❒	Box 5
s	▲	Triangle 1
t	▼	Triangle 2

Dingbats Typeface (continued)

CHAR	EX.	DESCRIPTION
u	◆	Diamond 1
v	❖	Diamond 2
w	◗	Half circle
x	▏	1/8 box
y	▌	1/4 box
z	▮	1/2 box
@	✠	Iron cross
%	✆	Telephone 1
^	❀	Flower 3
&	✆	Telephone 2
*	☛	Index 1
+	☞	Index 2
(	✈	Plane
)	✉	Envelope
~	❞	Close double quote
-	✍	Writing hand
|	❜	Close single quote
{	❛	Open single quote
}	❝	Close single quote
_	✿	Flower 4
‘	❀	Flower 5
\	✻	Flower 6
[	✼	Flower 7

CHAR	EX.	DESCRIPTION
]	❽	Flower 8
:	✚	Cross 1
;	✛	Cross 2
<	✜	Cross 3
=	†	Christian cross 1
>	✞	Christian cross 2
!	✁	Scissors 1
#	✂	Scissors 2
$	✃	Scissors 3
"	✄	Scissors 4
’	✇	Magtape
,	✌	Peace; victory
.	✎	Pencil 1
0	✐	Pencil 2
1	✓	Nib 1
2	✒	Nib 2
3	✓	Check mark 1
4	✔	Check mark 2
5	✕	X 1
6	✖	X 2
7	✗	X 3
8	✘	X 4
9	✙	Cross 4

Symbol Typeface

CHAR	EX.	DESCRIPTION
A	Α	Alpha
B	Β	Beta
C	Χ	Chi
D	Δ	Delta
E	Ε	Epsilon
F	Φ	Phi
G	Γ	Gamma
H	Η	Eta
I	Ι	Iota
J	ϑ	Theta (alt. style)
K	Κ	Kappa
L	Λ	Lambda
M	Μ	Mu
N	Ν	Nu
O	Ο	Omicron
P	Π	Pi
Q	Θ	Theta
R	Ρ	Rho
S	Σ	Sigma
T	Τ	Tau
U	Υ	Upsilon
V	ς	Sigma (alt. style)
W	Ω	Omega

CHAR	EX.	DESCRIPTION
X	Ξ	Xi
Y	Ψ	Psi
Z	Ζ	Zeta
a	α	alpha
b	β	beta
c	χ	chi
d	δ	delta
e	ε	epsilon
f	ϕ	phi
g	γ	gamma
h	η	eta
i	ι	iota
j	φ	phi (alt. style)
k	κ	kappa
l	λ	lambda
m	μ	mu
n	ν	nu
o	ο	omicron
p	π	pi
q	θ	theta
r	ρ	rho
s	σ	sigma
t	τ	tau

Symbol Typeface

CHAR	EX.	DESCRIPTION
u	υ	upsilon
v	ϖ	omega (alt. style)
w	ω	omega
x	ξ	xi
y	ψ	psi
z	ζ	zeta
0	0	Arabic numeral 0
1	1	Arabic numeral 1
2	2	Arabic numeral 2
3	3	Arabic numeral 3
4	4	Arabic numeral 4
5	5	Arabic numeral 5

CHAR	EX.	DESCRIPTION
6	6	Arabic numeral 6
7	7	Arabic numeral 7
8	8	Arabic numeral 8
9	9	Arabic numeral
"	∀	Universal
$	∃	Existential
’	∋	Such that
@	≅	Congruence
\	∴	Therefore
^	⊥	Perpendicular
‘	¯	Radical ex
~	~	Similar

APPENDIX G
CONVERTING FILES TO AlphaWRITE WITH AWCONV

AWCONV: DIFFERENCES BETWEEN VERSIONS

AlphaWRITE 1.2A included AWCONV.CMD, AWCONV.RUN, and AWCONV.SBR. This combination of files converted a single ASCII, TXTFMT, or SuperVUE file to AlphaWRITE 1.2A format.

AlphaWRITE 2.x includes AWCONV.LIT, a self-contained command which converts more kinds of document types than AlphaWRITE 1.2A and supports full wildcarding.

When To Use AWCONV

You use the AWCONV command for these purposes:

- To get a summary of the command's syntactical rules.
- To convert documents into AlphaWRITE 2.x format.
- To convert AlphaWRITE 2.x documents to another format.

Help Information for AWCONV

Help information for using the conversion utility AWCONV is available from AMOS command level. Typing **AWCONV** RETURN, with no command line arguments, displays a summary of the command formats and options available.

The screen illustration on the next page shows you the summary you see.

```
AWCONV utility version 2.x - converts to or from AlphaWRITE format

  To convert file(s) to AlphaWRITE 2.x format:

      .AWCONV InFiles {/switches}

  To convert files(s) from AlphaWRITE 2.x format to something else:

      .AWCONV OutFiles=InFiles {/switches}

  Available switches are:
      /D     delete destination file if it exists
      /E     erase source file after conversion
      /Q     query: ask Y)es or N)o for each file
      /P     place paragraph marker after each line
      /K     keep unsupported commands in destination file
      /A     converting to or from ASCII text file
      /T     converting from TXTFMT file (assumed for *.TXT)
      /S     converting from SuperVUE file (assumed for *.T)
      /SONY  converting from Sony Shared Files file (assumed for *.SNY)
      /W     converting to or from WordPerfect 5.x file (assumed for *.WP)
```

AWCONV Help Screen

CONVERTING DOCUMENTS INTO AlphaWRITE 2.x FORMAT

To convert one or more documents from another format to AlphaWRITE 2.x format, type **`AWCONV`** followed by a wildcard file specification and press RETURN.

For example, to convert all files with the extension .TXT in the account where you are currently logged, type:

`.AWCONV *.TXT` RETURN

AWCONV converts the files it finds and displays information as it performs its operation: For example

```
LETTER.TXT (TXTFMT) to LETTER.WRT (AlphaWRITE 2.x)
SAMPLE.TXT (TXTFMT) to SAMPLE.WRT (AlphaWRITE 2.x)
Total of 2 files imported
```

AWCONV makes assumptions about the format of the files to convert based on their file extensions, according to the table below:

EXT.	FILE FORMAT ASSUMED TO BE:
.SNY	Sony series 35 document
.T	SuperVUE 3.0 document
.TXT	TXTFMT document
.WP	WordPerfect 5.0, 5.1 document
.WRT	AlphaWRITE 1.2A document
other	ASCII text

If your files do not conform to the extensions shown above, you can override AWCONV's defaults using the switches shown below:

USE	RESULT
/A	assumes files are plain ASCII text
/S	assumes files are SuperVUE 3.0 documents
/SONY	assumes files are Sony series 35 documents
/T	assumes files are TXTFMT documents
/W	assumes files are WordPerfect documents

For each file AWCONV processes, a .WRT file is created.

The conversion of AlphaWRITE 1.2A documents is a special case. In this instance the AlphaWRITE 1.2A document is renamed to a .BAK extension, and the newly created AlphaWRITE 2.x document is given a .WRT extension.

Options AWCONV supports are shown in the following chart.

USE	RESULT
/D	Deletes destination file if it exists
/NOD	Does not delete destination file if it exists (default)
/Q	Queries: ask Y)es or N)o for each file
/P	Places paragraph marker after each line
/K	Keeps unsupported slash or dot commands in file

CONVERTING AlphaWRITE 2.x DOCUMENTS TO OTHER FORMATS

To convert AlphaWRITE 2.x documents to plain ASCII text or to WordPerfect format, specify AWCONV, an output filespec, an equal sign, and an input filespec. From AMOS command level, type:

```
AWCONV *.WP=*.WRT RETURN
DOC.WRT (AlphaWRITE 2.x) to DOC.WP (WordPerfect)
DOC2.WRT (AlphaWRITE 2.x) to DOC2.WP (WordPerfect)
Total of 2 files imported
```

The above example creates a WordPerfect document for each AlphaWRITE document in the user's current account.

AlphaWRITE will not export AlphaWRITE documents created by AlphaWRITE versions earlier than 2.1. If you attempt to convert a pre-2.1 document, AlphaWRITE reports "skipping - old version" for this document.

The same rules for extensions and override switches apply as described in the

preceding section. However, AWCONV can only convert to these formats:

- AlphaWRITE 2.x to plain text
- AlphaWRITE 2.x to WordPerfect

AWCONV assumes it is converting to WordPerfect format if the output files have an extension of .WP; otherwise, AWCONV will output ASCII text.

WORDPERFECT TO AlphaWRITE CONVERSION

When you use AWCONV to convert a WordPerfect document to AlphaWRITE, it creates an AlphaWRITE 2.1x document. AWCONV processes the WordPerfect file linearly: as it reads a document element from the WordPerfect document, it writes a corresponding document element to the AlphaWRITE document it is creating.

The converted document is based AlphaWRITE's on default document, DEFDOC.WRT and is updated according to settings read in from the WordPerfect file. The chart below lists the WordPerfect settings and what they are converted to in AlphaWRITE. If a WordPerfect feature is not specifically listed below, the feature is ignored upon conversion to AlphaWRITE

The list is organized into these groups:

- Text characters
- Spaces
- Hyphens
- Soft/Hard Return
- Page breaks
- Justification
- Extended characters
- Centering
- Tabs/Indent
- Superscript/Subscript
- Fonts
- Set size
- Outline
- Print emphasis: italic, bold, etc.
- Line height
- Margins, line spacing, tabs
- Font change

WordPerfect Feature	Converts to AlphaWRITE Features
Text characters	Copied without change.

WordPerfect Feature	Converts to AlphaWRITE Features
Hard Hyphen	A dash.
Soft Return	An End Of Line; paragraph marker is not created.
Hard Return	An End Of Line; Paragraph marker is created.
Soft Page Break	Soft Page Break.
Hard Page Break	Hard page break. If the current WordPerfect text line has not yet been terminated, an End Of Line will be output first.
Justification On	Triggers a new margin block when the next WordPerfect text character is encountered. The margin block will set right justification to "Y".
Justification Off	Triggers a new margin block when the next WordPerfect text character is encountered. The margin block will set right justification to "N".
Set Justification	Triggers generation of a new margin with corresponding right justification format setting when the next text character is encountered.
Extended Character	An extended character. Supported character sets are: ASCII, Multinational 1, Typographic Symbols (and those available in ISO Latin 1). If the WordPerfect extended character is not a member of any of the supported character sets, AlphaWRITE ignores the character.
Align Center	A centered line information block for this line.
Align Tab	Left tab.
Indent	An indent becomes a left tab. AlphaWRITE will continue the indent on successive lines until it reaches the end of paragraph. AWCONV keeps an "indent count" to know when to end the indent.
End Indent	End indent clears AWCONV’s "indent count" and indenting is halted.
Superscript	Superscript.

WordPerfect Feature	Converts to AlphaWRITE Features
Subscript	Subscript.
Extra Large Font	A 24 point typesize information block.
Very Large Font	An 18 point typesize information block.
Large Font	A 14 point typesize information block.
Small Font	A 10 point typesize information block.
Fine Font	An 8 point typesize information block.
Set Size On	A typesize information block set to the previously set point size. AWCONV keeps track of the prior typesize.
Set Size Off	A restore of the prior point size as a typesize information block.
Outline	An outline level.
Italics	Italic information block.
Double Underscore	Double underscore information block.
Bold	Bold information block.
Strike-out	Strike-out with slash (/) information block.
Underscore	Underline instruction.
Reverse	Reverse information block.
Set Line Height	A typesize information block.
Set Left and Right Margins	Triggers generation of a new margin with corresponding angle brackets to set the left and right margins when the next text character is encountered.
Line Spacing	Triggers generation of a new margin with corresponding line spacing format setting when the next text character is encountered.
Set Tabs	Triggers generation of a new margin with corresponding left tab settings when the next text character is encountered.

WordPerfect Feature	Converts to AlphaWRITE Features
Font Change	Generates a typeface information block and typesize information block.

AlphaWRITE to WORDPERFECT CONVERSIONS

When you use AWCONV to convert an AlphaWRITE document to WordPerfect, a limited number of AlphaWRITE features are converted. AWCONV creates a WordPerfect document compatible with WordPerfect 5.0 and 5.1. AWCONV processes the AlphaWRITE document linearly: as it reads a document element from the AlphaWRITE document, it writes a corresponding document element to the WordPerfect document it is creating.

The chart below lists the AlphaWRITE settings and what they are converted to in WordPerfect. If an AlphaWRITE feature is not specifically listed below, the feature is ignored upon conversion to WordPerfect.

The list is organized into these groups:

- Text characters
- Page breaks
- Margin/tabs
- End of line, required space, end of paragraph
- Print emphasis features
- Embedded text.

AlphaWRITE Feature	Converts to WordPerfect Feature
Text characters	Copied without change.
Hard Page Break	Hard Page Break
Soft Page Break	Soft Page Break
Margin	Set Left and Right Margin command with corresponding number of left tab stops.
Tabs	Tab codes or "Align Center" commands, as most nearly match AlphaWRITE's document ruler where the tab is encountered.
Center Line	Align Center
End of Line	Soft Return
Required Space	Hard Space

AlphaWRITE Feature	Converts to WordPerfect Feature
End of Paragraph Marker	Hard Return
Reverse	Reverse On/Reverse Off
Bold	Bold On/Bold Off
Strike-out	Strike-out On/Strike-out Off
Underline	Underscore On/Underscore Off
Italic	Italic On/Italic Off
Outline Font	Outline Font On/Outline Font Off
Double Underscore	Double Underscore On/Double Underscore Off
Embedded Text	Ignored

SUPERVUE TO AlphaWRITE CONVERSION

When you use AWCONV to convert a SuperVUE file to AlphaWRITE, it creates an AlphaWRITE 2.1x document. AWCONV processes the SuperVUE file linearly: as it reads a document element from the SuperVUE file, it writes a corresponding document element to the AlphaWRITE document it is creating.

The converted document is based on AlphaWRITE's default document, DEFDOC.WRT and is updated according to settings read in from the SuperVUE file. The chart below lists the SuperVUE settings and what they are converted to in AlphaWRITE. If a SuperVUE feature is not specifically listed below, that feature is ignored upon conversion to AlphaWRITE.

SuperVUE Feature	Converts to AlphaWRITE Feature
Text	Unchanged except for underscore (see below.)
Rulers	The standard ruler with no right justify instruction becomes a margin information block with a Right Justify Setting of "N". The right justify ruler becomes a margin information block with a Right Justify Setting of "Y".
Comments	Discarded and not retained in AlphaWRITE document unless the /K switch is used on AWCONV's command line to retain unsupported commands in destination document.

SuperVUE Feature	Converts to AlphaWRITE Feature
.bm n{"}	Ignored.
.bottommargin n{"}	These SuperVUE commands set bottom margin. No bottom margin setting exists in AlphaWRITE per se, it is implied from other settings.
.bottomtitle text .bt text .btitle text	Footer embedded text blocks.
.center text .centre text	Center information block followed by text.
.c text .chapter text	Chapter Page Break.
.ds on|off .doublespace on|off	"On" Generates a margin information block with Line Spacing set to 4. "Off" generates a margin information block with Line Spacing set to 2.
.font typefacename	Typeface information block.
.highlight style {style {... style} } .hlt style {style {... style} }	These commands select what special print effect the underscore character triggers in SuperVUE. For example, `.hlt bold underline` causes the text "This is _quite_ an interesting _day_" to print as "This is <bold-on>quite <bold-off> an interesting <underscore-on>day<underscore-off>." AWCONV remembers the highlighting style list, and as underscore characters are encountered in the document text, the appropriate AlphaWRITE equivalent styles (when they exist) are toggled.
.illus n .illustration n	Ignored.
.include docname	Ignored.
.keep	Ignored.
.laser	Ignored.
.length n	Margin information block with matching Page Length setting.

SuperVUE Feature	Converts to AlphaWRITE Feature
.m n{"}	
.margin n{"}	Margin information block with matching Left Paper Offset setting.
.microspace printertype	Ignored.
.mirror	Ignored.
.n n	
.number n	Set page number information block.
.page n	Conditional page break n.
.points n	Typesize information block.
.printer type	Ignored.
.stretch n	Ignored.
.table	Ignored.
.t text	
.title text	Title embedded information block.
.tm n{"}	
.topmargin n{"}	Margin information block with matching Top Margin setting.
page break	Hard page break.
tabs	SuperVUE files do not have tabs, they are stored as spaces. AWCONV cannot discern SuperVUE's spaces from tabs and will will convert all spaces to spaces.
all other commands	Ignored.

APPENDIX H
AlphaWRITE'S INITIALIZATION FILE

The AlphaWRITE initialization file allows you to define the printers available in AlphaWRITE and choose how certain AlphaWRITE features operate. This appendix describes how you can set the options available in the initialization file.

You can call up the AlphaWRITE initialization file only from AMOS command level. To modify or create an initialization file, you must use AlphaVUE, the Alpha Micro text editor. This appendix assumes you are familiar with changing text files using AlphaVUE.

WHAT DOES AlphaWRITE'S INITIALIZATION FILE DO?

AlphaWRITE's initialization file customizes AlphaWRITE's operation to match your needs. Your initialization file can include many commands customizing AlphaWRITE for your particular computer installation. Each command is discussed later on in this appendix.

CREATING AN AlphaWRITE INITIALIZATION FILE

AlphaWRITE comes with a sample initialization file, named WRITE.NEW; a printed version of this file is shown at the end of this appendix. However, you may want to create your own initialization file, either to affect only some user accounts, or to change the options selected for your entire system.

When you create an initialization file, you must follow these guidelines:

- The initialization file must be created with AlphaVUE, the system text editor.
- The initialization file name may be either WRITE.INI or WRITE.lan, where lan is the message file extension from your system Language Definition file.
- Each command within the file occupies one line.

You can create an initialization file in any account on your system. Which users are affected by an initialization file depends on the location of the file.

The Name of the Initialization File

You may name an AlphaWRITE initialization file either WRITE.INI or WRITE.lan, where *lan* is the message file extension for your language, taken from your system Language Definition file.

In most cases, you would call the initialization file WRITE.INI. However, if your system is set up to use AlphaWRITE in more than one language, you should delete all WRITE.INI files, and create separate initialization files for each language, using the appropriate extensions.

The initialization file named WRITE.INI has priority; if both WRITE.INI and WRITE.lan exist, AlphaWRITE uses the WRITE.INI file.

For information on how to determine the correct language extension for your system, and how to use AlphaWRITE in more than one language, refer to *AlphaWRITE Programmer's Information* - DSO-00076-00.

Location of the Initialization File

You can locate an initialization file in any account on any device. The file's location determines whether it affects all user accounts, user accounts in one project, or a single user account.

TO AFFECT:	PLACE FILE IN:
One Account	This User's account
One Project	Project library account. [project,0]
All accounts	WRT:

You may have several initialization files on your system. When there is more than one initialization file, AlphaWRITE searches your system in a specific way, shown below.

AlphaWRITE's Search Path for Its Initialization File

First, AlphaWRITE looks for WRITE.INI in the account where you are currently logged. If found there, AlphaWRITE uses this file.

If there is no WRITE.INI in the current account, AlphaWRITE looks for WRITE.INI in the project library account ([project,0]). If found there, AlphaWRITE uses this file.

Finally, when no initialization files are found in either the current or project library account, AlphaWRITE looks for WRITE.INI in WRT:.

If there is no WRITE.INI in any of these accounts, AlphaWRITE repeats this search pattern, looking for WRITE.lan.

If no initialization file—either WRITE.INI or WRITE.lan— is found anywhere on your system, you can still use AlphaWRITE. With the exception of the PRINTER command, AlphaWRITE will then use the default settings for all the valid initialization file commands. Default settings for all initialization file commands are listed in their own section, near the end of this appendix.

If there are no AlphaWRITE initialization file PRINTER commands, but you have a centralized printer definition file, AlphaWRITE uses the PRINTER commands in this file as the printer settings. If you do not have a centralized printer definition file or an AlphaWRITE initialization file, you cannot print from AlphaWRITE.

Comment Characters

Semicolons as the first character of any line in the initialization file are comment characters—meaning information following the semicolon is ignored. A semicolon can be used to disengage any command appearing in the initialization file when inserted as the first character.

INITIALIZATION FILE COMMANDS

Although we show the recommended conventions for entering the command lines to AlphaWRITE's initialization file, these are the general rules for the initialization file's format:

- Each command occupies one line.
- Commands may be entered using either upper or lower case, or a combination of both.
- Most command lines consists of the command name, an equal sign (=), and the value for the command.
- Each command name is one word, with no spaces. You can have a space before the command name, or on either side of the equal sign.
- Blank lines are ignored.
- Any line starting with a semicolon (;) is a comment line and is ignored.
- If you omit any command, AlphaWRITE uses the default value for the command.
- Where a boolean response is appropriate in a command's syntax, for clarity we use the term TRUE as an instruction after the equal sign. However, the terms ON, YES, or 1 are also valid.

- Where a boolean response is appropriate in a command's syntax, for clarity we use the term FALSE as an instruction after the equal sign. However, the terms OFF, NO or 0 are also valid.

You can use as many blank lines and comment lines as you want to make your initialization file easy to read. However, **every** comment line must start with a semicolon or AlphaWRITE attempts to interpret it as a command. You receive an error message when you call up AlphaWRITE for any line in the initialization file that is **not** in proper format.

The initialization file commands discussed in the next sections are:

CHARINSERT	INTENSITY	PALETTE
COLOR	JOURNAL	PRINTER
DICTIONARY	JOURNALSIZE	PROPORTIONAL
DICTIONARYTWO	KEYSTROKES	REFORMAT
DIRECTORYSIZE	LINEINSERT	SEARCHFOLD
DISPLAYATTRIBUTE	LOCAL	WIDOW
FONT	MENUBYPASS	WIDTH
FONTCARTRIDGE	MODEM	

CHARINSERT COMMAND

The syntax for the CHARINSERT command is:

```
CHARINSERT = boolean
```

The CHARINSERT command lets you choose to have AlphaWRITE in character insert mode when you call it up. If you prefer to use character insert mode, this command saves pressing the [AUTO INS CHAR] key to engage it.

To use automatic character insert mode in this fashion, enter this command:

```
CHARINSERT=TRUE
```

You still use the [AUTO INS CHAR] from AlphaWRITE to switch between insert and overwrite mode no matter what is set in the initialization file.

Although the command CHARINSERT=FALSE is valid and causes AlphaWRITE to be in overwrite mode when initially called, it is unnecessary. The CHARINSERT command is optional and if not specified in the initialization file, AlphaWRITE automatically assumes overwrite mode.

COLOR

The syntax for the COLOR command is:

```
COLOR = boolean
```

The COLOR command is used to enable or disable the use of color display, not printing. If COLOR is enabled, and your terminal supports color, AlphaWRITE will use color. If the COLOR command is present and enabled, but your terminal does not support color, COLOR is ignored.

The colors AlphaWRITE uses are governed by a five-color palette. See the PALETTE command for details.

Only the mode form of color, as used in PCs and the AM-72 terminal, is supported. The older attribute form of color, as used in the AM-70 terminal, is **not** supported.

Default: FALSE.

DICTIONARY

There are situations where you may wish to place the dictionaries somewhere other than the main system disk. Both the 80,000 word Random House® Concise Dictionary named SPELL.DCT and the smaller dictionary named SMALL.DCT can be relocated to another account and/or a different device. If you choose to use this option, you must relocate **both** dictionaries.

To do this, use the AMOS COPY command to relocate both of the dictionary files from their original location in WRT: to the same device and account.

After these two files have been copied to the same device and account, you must add a DICTIONARY command to AlphaWRITE's initialization file. The DICTIONARY command tells AlphaWRITE where to look for these dictionaries when performing a spell check.

The syntax for the DICTIONARY command is:

```
DICTIONARY devn:[p,pn]
```

where `devn:` is the device where the dictionaries are now located and `[p,pn]` is the account number where they can be found. For example, DSK4:[100,13].

It is not necessary to specify either of the dictionaries' file names, just their location. Only one DICTIONARY command is recognized in the initialization file.

You may use ersatz names to define the location of the dictionary, in which case the syntax is:

```
DICTIONARY ersatz:
```

If no location or ersatz for location is given in the DICTIONARY command line, then AlphaWRITE assumes the location is where the user is currently logged.

When no DICTIONARY command appears in the initialization file, AlphaWRITE assumes SMALL.DCT and SPELL.DCT are located in WRT:. If no WRT: ersatz location exists, AlphaWRITE looks in DSK0:[7,12].

DICTIONARYTWO

AlphaWRITE supports the use of a professional dictionary.

When you prepare a professional dictionary to use with AlphaWRITE, you must use the DICTIONARYTWO command in the initialization file to let AlphaWRITE know you want this dictionary to be used and where it is located.

The syntax for the DICTIONARYTWO command is:

```
DICTIONARYTWO devn:filenm.ext[p,pn]
```

where `devn:` is the device specification where your professional dictionary is located, `filenm.ext` is the filename and extension for your professional dictionary and `[p,pn]` is the account number where it is located. You may use ersatz names to define the location of the dictionary. In which case the syntax is:

```
DICTIONARYTWO ersatz:filenm.ext
```

If no location or ersatz for location is given in the DICTIONARYTWO command line, then AlphaWRITE assumes the location is where the user is currently logged.

The DICTIONARYTWO command is optional and if not specified in the initialization file, AlphaWRITE assumes there is no professional dictionary when you use **SPELL**.

DIRECTORYSIZE

You can set the total number of documents AlphaWRITE shows you whenever you use the **DIRECTORY** or any of the quick directories available from most command screens. You do this with the initialization file's DIRECTORYSIZE command which is particularly useful when system memory is at a premium.

The syntax for the DIRECTORYSIZE command is:

```
DIRECTORYSIZE xxx
```

where **xxx** represents a number from 1 to a maximum number limited only by the amount of memory available. When no DIRECTORYSIZE command is included in the initialization file AlphaWRITE displays a maximum of 400 documents.

Memory tip: System operators may need to know each file (document) specified in DIRECTORYSIZE requires 8 bytes of memory. For example, increasing the default from 400 to 500 documents increases memory consumption by 800 bytes, from 3.2K to 4K.

DISPLAYATTRIBUTE

The syntax for the DISPLAYATTRIBUTE command is:

```
DISPLAYATTRIBUTE = boolean
```

DISPLAYATTRIBUTE controls the appearance of bold and underscored text in Text Display. When DISPLAYATTRIBUTE is enabled, underscored text is underlined on the screen, where feasible, and bold text is shown in reverse video, where feasible. When DISPLAYATTRIBUTE is disabled, begin/end underscores are shown as underline characters and begin/end bold blocks are shown as shaded blocks on the screen.

DISPLAYATTRIBUTE causes underscored and bolded text to appear as underline and reverse video attributes only when the starting and ending underscore/bold blocks are on the same line. When multiple lines are involved (such as in an underlined paragraph), the standard underscore character or shaded block is used.

Default: TRUE.

FONT

The syntax for the FONT command is:

```
FONT = range, {range,}...
```

Where `range` represents the font-list of one or more font letters or font ranges, separated by commas. A font range is a starting font letter, followed by a dash, followed by an ending font letter. For example:

```
FONT = A-D, Q, T-V, X, Z
```

The FONT command allows specific fonts to be enabled or disabled, so you see only the available fonts during font selection.

The FONT command allows the sub-menu for the STYLE typeface selection to be customized to show only the fonts that are actually available to you. This is particularly important when using HP LaserJet printers because you may not have all the cartridges available.

Default: A-P, R-V, Z

FONTCARTRIDGE

The syntax for the FONTCARTRIDGE command is:

```
FONTCARTRIDGE PrinterName = Font1 {,Font2}{,Font3}
```

where `Font1 {,Font2}{,Font3}` refers to an HP font cartridge expressed as a single letter or digit. Capitalization is not important.

FONTCARTRIDGE is expressly for HP printers and allows you to preset a font cartridge setting. `PrinterName` is the name of the printer whose font cartridge you are defining. Up to three cartridges may be defined per printer.

The following example for FONTCARTRIDGE selects Math Elite (J) and Math TMS (K): FONTCARTRIDGE HP=J,K.

Default: use resident fonts only.

These are the cartridge character assignments for HP printers:

CHR.	ASSIGNMENT
A	Courier
B	TMS Proportional 1
C	International
D	Prestige Elite
E	Letter Gothic
F	TMS Proportional 2
G	Legal Elite
H	Legal Courier
I	Pacific Data (25 in 1)
J	Math Elite
K	Math TMS
L	Courier P&L
M	Prestige Elite P&L
N	Letter Gothic P&L
O	Unassigned
P	TMS Rmn P & L
Q	Memo 1
R	Presentations 1
S	Report 1
T	Tax 1
U	Forms Portrait
V	Forms Landscape
W	OCR A
X	EAN/UPC/OCR-B
Y	PC Courier 1
Z	Microsoft®
0	ProCollection
1	P. Worksheets
2	WordPerfect
3-9	Unassigned

INTENSITY

The syntax for the INTENSITY command is:

```
INTENSITY = boolean
```

The INTENSITY command allows the use of bright and dim intensity to be enabled or disabled. This command was added with people who use color terminals in mind. Some people prefer to disable mixed intensity when using color so the display is less cluttered.

INTENSITY Default: TRUE

JOURNAL

The syntax for the JOURNAL command is:

```
JOURNAL = boolean
```

The JOURNAL command enables or disables keystroke journaling.

Default: JOURNAL = TRUE

JOURNALSIZE

The syntax for the JOURNALSIZE command is:

```
JOURNALSIZE = n
```

where n defines the size of keystroke journal files. The argument n is in characters, and the size of the journal file created is the minimum number of blocks required to hold the specified number of characters in a contiguous file. There are 512 bytes in a block, one character equivalent to one byte.

For example, a JOURNALSIZE setting of 750 characters results in a journal file size of 2 blocks—at least two blocks are needed to hold 750 characters.

Default: 20000 (40 blocks)

KEYSTROKES

The syntax for the KEYSTROKES command is:

```
KEYSTROKES = n
```

where n defines the keystroke update interval; that is, the number of keystrokes between disk updates of the journal file. Valid ranges for n are 4 through 512.

Default: 16.

LINEINSERT

The syntax for the LINEINSERT command is:

```
LINEINSERT = boolean
```

The LINEINSERT command lets you choose to have AlphaWRITE in line insert mode when you call it up. If you prefer line insert mode, this command saves pressing [AUTO INS LINE] to engage it. To use automatic line insert mode in this fashion, enter this command:

```
LINEINSERT=TRUE
```

You still use [AUTO INS LINE] to switch between insert and overwrite mode no matter what is set in the initialization file.

Default: FALSE.

MENUBYPASS

The syntax for the MENUBYPASS command is:

```
MENUBYPASS = boolean
```

As you become more familiar with using AlphaWRITE, you may not need to see the list of AlphaWRITE Editing Menu commands in order to know which one you want. You can disengage, or bypass, the full AlphaWRITE Editing Menu display by using the MENUBYPASS command in the initialization file.

Menu bypass is a speed and convenience feature intended for experienced AlphaWRITE operators When you turn on menu bypass, AlphaWRITE does not display the full AlphaWRITE Editing Menu when you press [MENU] from document text display. Instead of taking the time to refresh your entire screen, AlphaWRITE clears the information lines from the bottom of document text display, and replaces it with the Editing Menu command line.

The MENUBYPASS command affects only the display of the Editing Menu and not the AlphaWRITE Main Menu, the command is operative only on terminals supporting split screen. If the MENUBYPASS command is used on a terminal without split screen, an error message appears and the command is ignored.

To enable menu bypass mode, enter this command:

```
MENUBYPASS = TRUE
```

Whenever you press [MENU] from document text display to work with the Editing Menu you see its command line at the bottom of the display:

```
Enter command name and press RETURN:
```

You enter Editing Menu commands on this prompt line, as they would normally be entered on the same prompt line of the full menu display.

The command MENUBYPASS=FALSE is valid, although it is unnecessary. The MENUBYPASS command is optional and if not specified in the initialization file, AlphaWRITE automatically displays the entire menu.

Default: FALSE.

The Mode Command and Menu Bypass

Menu bypass can also be turned on or off from within AlphaWRITE using the **MODE** menu bypass option. However, whatever is included in the initialization file is the default setting for **MODE**.

MODEM

The syntax for the MODEM command is:

```
MODEM = boolean
```

The MODEM command allows some of AlphaWRITE's terminal display to be defeated. For example, the screen will not turn off when MODEM display mode is enabled. This makes AlphaWRITE tolerable for use over modems at slow speeds.

Default: FALSE.

PALETTE

The syntax for the PALETTE command is:

```
PALETTE =  a, b, c, d, e{, f}
```

where `a, b, c, d, e{, f}` represent colors for AlphaWRITE's displays. The PALETTE command allows the color palette to be defined. The color palette is a set of these colors:

WHERE	REPRESENTS
a	color for informational text
b	color for field prompts
c	color for text display
d	color for input fields
e	color for error messages
{f}	color for background {optional}

To identify a color, substitute a number in this chart for the letter in the syntax example. Each color is represented by a number from 0-7:

NUMBER	COLOR
0	black
1	white
2	blue

NUMBER	COLOR
3	magenta
4	red
5	yellow
6	green
7	cyan

The PALETTE command has no effect unless color is in use. This requires that the COLOR = TRUE command has been specified **and** your terminal supports mode color.

Defaults: color a - 1 (white)
color b - 7 (cyan)
color c - 6 (green)
color d - 2 (yellow)
color e - 4 (red)
color f - 0 (black) {optional}

PRINTER

Please refer to the last section of this appendix for information about setting up PRINTER commands in your AlphaWRITE Initialization command file.

PROPORTIONAL

The syntax for the PROPORTIONAL command is:

```
PROPORTIONAL = boolean
```

The PROPORTIONAL command enables or disables the use of proportional display fonts for the AM-72 terminal. If enabled, proportional fonts are used in menu displays.

This command has no effect when used on a non-AM-72 terminal.

Default: FALSE.

REFORMAT

The syntax for the REFORMAT command is:

```
REFORMAT = boolean
```

The REFORMAT command enables or disables automatic reformatting at print time.

When REFORMAT is enabled, AlphaWRITE reformats paragraphs at print time for best output on the printer selected. Automatic reformat makes decisions when a requested font family or font size is not available so that the final output is as close to the requested page layout as possible. It is not necessary to **PAGINATE** documents when automatic reformat is in effect, as page breaks are calculated dynamically during printing. However, you may choose to **PAGINATE** in order to see the proper location of page breaks on the editing screen, prior to printing.

The times you are required to **PAGINATE** are:

- When you are using an impact printer and have fixed or variable spacing set.
- Before you use **INDEX** or **TOC** to produce accurate page number references.

When REFORMAT is disabled, AlphaWRITE outputs exactly what is on the edit screen. It is therefore crucial for you to **PAGINATE** the document before printing when reformatting has been disabled.

Default: TRUE.

SEARCHFOLD

The syntax for the SEARCHFOLD command is:

```
SEARCHFOLD = boolean
```

The SEARCHFOLD command enables or disables case folding during **SEARCH**, **REPLACE**, and **GLOBAL** operations.

Default: TRUE.

SUBSTITUTE

The syntax for the SUBSTITUTE command is:

```
SUBSTITUTE = boolean
```

The SUBSTITUTE command enables or disables font substitution.

Printer drivers that support font families (laser printers) may contain font substitution tables. The presence of these tables allows AlphaWRITE to make intelligent decisions about how to print a document when you have requested a font that does not exist.

For example, an attempt to print in Garamond on an Apple LaserWriter will actually print in New Century Schoolbook which is the font most closely matching Garamond available.

Default: TRUE.

WIDOW

The syntax for the WIDOW command is:

```
WIDOW = boolean
```

The WIDOW command controls whether widow and orphan handling is performed.

Default: TRUE.

WIDTH

The syntax for the WIDTH command is:

```
WIDTH = n
```

where n can be either 80 or 132. The WIDTH command sets the terminal width for Text Display. The only accepted values for this command are 80 or 132.

Default: currently set terminal width.

DEFAULT SETTINGS

All of AlphaWRITE's initialization file's commands are optional and if omitted, cause default to a preset value. Omitting the command has the same effect as using the default value for the command in the initialization file.

The default command settings are also in effect when no AlphaWRITE initialization file is found when you first call up AlphaWRITE. The following table shows each command's default setting.

COMMAND	DEFAULT
CHARINSERT	FALSE
COLOR	FALSE
DICTIONARY	WRT:
DICTIONARYTWO	none
DIRECTORYSIZE	400
DISPLAYATTRIBUTE	TRUE
FONT	A-P, R-V, Z
FONTCARTRIDGE	resident fonts only
INTENSITY	TRUE
JOURNAL	TRUE
JOURNALSIZE	20000 (40 blocks)
KEYSTROKES	16
LINEINSERT	FALSE

COMMAND	DEFAULT
MENUBYPASS	FALSE
MODEM	FALSE
PALETTE	1,7,6,5,4,0 (white, cyan, green, yellow, red, black)
PRINTER	PRTDEF Initialization File DSK0:[1,4]†
PROPORTIONAL	FALSE
REFORMAT	TRUE
SEARCHFOLD	TRUE
SUBSTITUTE	TRUE
WIDOW	TRUE
WIDTH	current terminal width

† If PRTDEF.INI is not present, see the section below about default printers.

AlphaWRITE INITIALIZATION FILE ACCOMPANYING YOUR SOFTWARE

The AlphaWRITE software you install on your computer system comes equipped with an initialization file to get you started. This file's name is WRITE.NEW and it is located in WRT:.

The following shows the contents of the initialization file WRITE.NEW accompanying your AlphaWRITE software.

AlphaWRITE WRITE.NEW Initialization File

```
;*************************
;*  Printer Definitions  *
;*************************

;PRINTER LASER,LASWRT,"Apple LaserWriter+",,,0
;PRINTER LPT0,LASJET,"HP LaserJet II",,,0
;PRINTER LPT1,MISC,"Draft Printer",,,0
;PRINTER LPT2,AM301,"AM301 Letter Quality Printer",,,0
;PRINTER LPT2,AM302,"AM302 Letter Quality Printer",,,0
;PRINTER LPT3,AM306D,"AM306 Draft Quality  ",,,0
;PRINTER LPT3,AM306C,"AM306 Corres. Quality",,,0
;PRINTER LPT3,AM306L,"AM306 Letter Quality ",,,0

;FONT=A-D,H,I,N,P,S,T,Z
;FONTCARTRIDGE LPT0=I,K

;******************
;*  Memory Usage  *
;******************

;DIRECTORYSIZE 400

;****************************
;*  Text Display Defaults  *
;****************************

;CHARINSERT=TRUE
;LINEINSERT=TRUE
;MENUBYPASS=TRUE

;**********************
;*  Display Defaults  *
;**********************

;DISPLAYATTRIBUTE=FALSE
;PROPORTIONAL=TRUE
;INTENSITY=FALSE
;COLOR=TRUE
;PALETTE=1,7,6,5,4
;MODEM=TRUE
;WIDTH=132

;***************************
;*  Keystroke Journaling  *
;***************************

JOURNAL=TRUE
JOURNALSIZE=20000

;**************
;*  Printing  *
;**************

REFORMAT=TRUE
SUBSTITUTE=TRUE

;*******************
;*  Miscellaneous  *
;*******************

;DICTIONARY DSK0:[7,12]
;DICTIONARYTWO DSK0:PROF.DCT[7,12]
SEARCHFOLD=TRUE
```

AlphaWRITE's WRITE.NEW Initialization File

To use this particular initialization file, you will need to modify it, at least to customize the PRINTER commands, and rename it to WRITE.INI. If you define your printers in the centralized printer definition file, you will need to either remove the PRINTER command lines or mark them as comments. See the section on the PRINTER command for a discussion of the printer definition file.

THE INITIALIZATION FILE PRINTER COMMAND

The PRINTER command defines the printers available from AlphaWRITE. You can define up to thirty-two printers.

You can define printers either in an AlphaWRITE initialization file or in the system printer definition file. Defining printers in a central printer definition file instead of in the AlphaWRITE initialization file allows you to change printer definitions for multiple software packages, such as AlphaCALC and AlphaMAIL, by changing one command line in one file.

The name of the central printer definition file is PRTDEF. Like the AlphaWRITE initialization file, its extension can be either .INI or .lan—the message file extension for your language. If both PRTDEF.INI and PRTDEF.lan exist, AlphaWRITE uses PRTDEF.INI, located in DSK0:[1,4].

AlphaWRITE uses printer definitions in the printer definition file only when there are <u>no</u> printer definitions in the AlphaWRITE initialization file. You cannot define some printers in one file and some in the other. If you want to use PRTDEF to define your printers, you must delete or mark as comments all PRINTER command lines in your AlphaWRITE initialization file.

The same rules apply to printer definitions in either the AlphaWRITE initialization file or the printer definition file.

The PRINTER command must appear on one line and in this format:

```
PRINTER prtrnm,drvrnm,"symbolnm",prtwheel,sheetfdr,cpuid
```

The first word on the line—PRINTER—lets AlphaWRITE know information on this line defines a printer. The words afterward represent information appearing on the command line and are called parameters. The sample command line shown above uses these abbreviations for parameters:

ABBREV.	MEANING
`prtrnm`	printer name
`drvrnm`	printer driver name
`symbolnm`	symbolic name
`prtwheel`	print wheel
`sheetfdr`	sheet feeder
`cpuid`	central processing unit identification

You enter the values for these parameters in the same fashion as shown in the format:

- A comma separates each value.
- No blank spaces except the one following PRINTER.
- The symbolic printer name enclosed within quotation marks.

Printer Name

The printer name parameter is the name used to identify this printer to the printer spooler. You can determine the printer initialization files being used by checking the AMOS initialization file.

By looking at this printer initialization file's NAME commands you see what names are used to identify printers on your system, if you do not already know.

Driver Name

The driver name is the name of the printer driver to be used for the particular type of printer. Because each type of printer has special characteristics, you need to tell AlphaWRITE the type of printer you have.

Printer drivers have the extension .PDV and are stored on DSK0:[1,6]. Alpha Micro supports these AlphaWRITE printer drivers:

DRIVER NAME	FOR PRINTER
AM301.PDV	Support for the Alpha Micro AM-301 letter quality printer. This driver supports fixed, variable and proportional spacing.
AM302.PDV	Support for the Alpha Micro AM-302 letter quality printer, Diablo 630 Models RO and API and other compatible printers. This driver supports fixed, variable and proportional spacing.
AM306?.PDV	Support for the Alpha Micro AM-306 letter quality printer. This driver supports multi-colored ribbons, expanded characters, etc. Using variable or proportional word spacing with this driver is not supported.
MISC.PDV	Support for standard serial and line printers. Examples of these printers are the Alpha Micro AM-304, Texas Instruments 810, Data Products B-300 and B-600, ETC. This driver supports only fixed word spacing; variable or proportional word spacing is not supported.

DRIVER NAME	PRINTER
LASJET.PDV	Support for Hewlett-Packard LaserJet II laser printers.
LASII.PDV	Support for Hewlett-Packard LaserJet II laser printers.
LASWRT.PDV	Support for Apple LaserWriter Plus and any other PostScript compatible laser printers.
LASIID.PDV	Support for Hewlett-Packard LaserJet IID and IIP laser printers.
LASIII.PDV	Support for Hewlett-Packard LaserJet III and IIID laser printers.
PSCART.PDV	Support for Hewlett-Packard LaserJet printers with a PostScript cartridge installed. (See Appendix J - " HP Laser Printing for more information.)

Other printer drivers for AlphaWRITE may be available on your system. System Operator: please refer to the last section of this appendix for more information about AlphaWRITE and printer drivers.

Symbolic Name

The symbolic name appears on any of the AlphaWRITE Document Printing Menus, AlphaWRITE Printer Queue Maintenance screens and appears when you print a document directory via the DIRECTORY command. The symbolic name is the name by which the AlphaWRITE operator identifies the printer. The printer names appear in the list displayed by AlphaWRITE in the same order as they appear in AlphaWRITE's initialization file.

The symbolic name:

- Must be enclosed within double quotation marks " "
- Can be up to 30 characters long.
- May contain spaces.

Print Wheel

Print wheel is an optional parameter applying to printers using the AM301.PDV or AM302.PDV printer driver and specifies the type of print-wheel used on the printer. Because different print wheels have different character sets, AlphaWRITE must know which print wheel is mounted in order to properly print the special characters.

The print wheel parameter is a number and corresponds to the print wheel description listed in the following table. Under each description you'll see a list of print wheels; these are some of the most common print wheels of that type.

To use this list, find the type of print wheel you'll be using in the description column. Then use the value with its comma, shown in the parameter value column, as the entry on the PRINTER command line.

For AM-301 printers, refer to the table on the next page showing the thimble layout to find the value with its comma.

VALUE	AM-302 PRINT WHEEL DESCRIPTION
1,	Standard Diablo 88-character metal print-wheel Diablo type 88 WP, such as: PICA 10 — CUBIC PS SPOKESMAN 10 — MASTER 12 ROMAN PS — ELITE 12 BOLD PS — GOTHIC PS TITAN 10 — TREND PS VINTAGE 12 — TROJAN 10 TITAN 12
2,	Legal font Diablo 88-character metal print-wheel Diablo type 88 LEGAL, such as: BOLD LEGAL PS — TITAN LEGAL 10
3,	Titan 10 style Diablo 96-character metal print-wheel. Diablo type 96 COMM, such as: TITAN 10 — ELITE 12 OCR-B 10 — CUBIC PS
4,	Pica 10 style Diablo 96-character metal print-wheel. Diablo type 96 WP, such as: PICA 10 — BOLD.PS
5,	Standard Diablo 96-character plastic print wheel. Diablo type USASCII A, such as: PICA 10 — OCR-B 10 COURIER 10 — COURIER 72 ELITE 12
6,	Legal font Diablo 96-character plastic printwheel. Diablo types US LEGAL 1 and US LEGAL 3, such as: PICA LEGAL 10A — COURIER LEGAL 10A

VALUE	AM-301 THIMBLE LAYOUT DESCRIPTION
1,	ASCII 2, such as: COURIER 72
2,	Multilingual A, such as: DUAL GOTHIC 12 PICA 10
3,	Legal A, such as: NEW PRESTIGE ELITE 12 COURIER 72
4,	Proportional Spacing, such as: ITC SOUVENIR PS 7 BOLD PS 8
5,	Word Processing, such as: ITC AVANT GARDE 10 NEW COURIER 10
6,	Currently unassigned

Printer Settings

Very often you must make corresponding settings on your printer when you change print wheels. Be sure the settings for your printer correspond to those required by the print wheel you specify with the print wheel parameter. And, using different pitch print wheels or some type faces, such as proportional, also requires corresponding settings in the AlphaWRITE Document Header.

Sheet Feeder

The sheet feeder parameter allows you to choose the default setting of the **PRINT** command menu prompt "Use sheet feeder?". The sheet feeder parameter is only allowed within PRINTER commands containing printers and printer drivers supporting sheet feeders. These values are valid:

- Y, for yes. Prompt display is "Use sheet feeder? Y"
- N, for no. Prompt display is "Use sheet feeder? N"

CPU Identification

The last parameter in the PRINTER command accommodates computer systems configured with AlphaNET, Alpha Micro's Network. The CPU Identification (CPU ID) parameter lets you define a printer, physically connected to another computer system, which you can use for printing from within AlphaWRITE.

To determine the CPU ID of the computer system whose printer you want to define in the PRINTER command, use the NTSTAT command from AMOS command level. NTSTAT is an information command and lists specific information about your particular network configuration, including the CPU ID. The CPU ID can be expressed as the number assigned it, or an ersatz name if it is so defined. For example:

```
PRINTER LETTER,AM302,"Letter Quality",1,N,ACCTNG:
```

where `ACCTNG:` is the ersatz definition for the CPU ID.

If you do not have AlphaNET, no value is necessary for this parameter.

When you identify a printer available to you via the network, you are able to select this printer from the list shown on AlphaWRITE's Printing Menus. However, there are two conditions when a network printer won't be available for use; when your computer system is not linked to the network and when the system whose printer is defined is not linked. "Not linked" means you temporarily cannot communicate with the other computer system. Therefore, you temporarily cannot communicate with the networked printer.

If either of these conditions exist when you attempt to use **PRINT** on this printer, you see a message letting you know your system cannot communicate with the network system, followed by the PRINTER in question. For example:

```
ITC Failure!
PRINTER LETTER,AM302,"Letter Quality",1,N,12345678
```

A Note About Commas

The commas in the PRINTER command are delimiters, letting AlphaWRITE differentiate one parameter from the next. You may choose to omit a parameter value but include one immediately following. When this is the case, the commas <u>must</u> appear within the command line. For example:

```
PRINTER AM302,AM302,"The Letter Quality Printer",,N,
```

Although no value for the print wheel parameter or CPU ID appears, a value does appear for the sheet feeder prompt and therefore the commas are included before and after the N.

Likewise, if no values are set for any parameters except the CPU ID, the command line still must have the commas. For example:

```
PRINTER AM302,MISC,"The Poor Draft Printer",,,12345678
```

Default Printers If PRTDEF.INI does not exist on your system and there are no PRINTER commands in the AlphaWRITE initialization file, you will not be able to use **PRINT** or the **DIRECTORY** print option.

One printer must be defined for AlphaWRITE's use; either in its initialization file or in PRTDEF.INI.

Printing To A Terminal's Printer Port

You can send printed output directly to your terminal's printer port. When you use this kind of printing arrangement with **PRINT**, AlphaWRITE sends the printed output to the printer port rather than a spooler.

To define a terminal's printer port as an AlphaWRITE printer, identify the printer name as SELF and use the printer driver appropriate for the printer connected to your terminal's printer port. For example, if an AM-302 printer is connected to your terminal's printer port you would use this PRINTER command:

```
PRINTER SELF,AM302,"Printer on AM-62A",,,0
```

AlphaWRITE PRINTER DRIVERS

If you are writing your own printer driver for AlphaWRITE you may want to refer to the *AlphaWRITE Programmer's Information* document DSO-00076-00.

In addition to the information contained in the Printer Driver document, you will also be interested in knowing about a particular AlphaWRITE embedded feature.

The [EMBED] key's PostScript option lets you send PostScript code directly to PostScript printers and ASCII sequences to a printer having features which our current printer drivers do not support. The next section describes how to do this.

Entering Direct ASCII Codes for Your Printer

AlphaWRITE's [EMBED] key's PostScript option lets you enter a sequence of decimal numbers, which are sent to the printer as ASCII values when you print your document. This allows you to send control codes to a printer AlphaWRITE normally does not support. By including the correct series of values, you can control your printer using this command.

To use direct ASCII codes, beginning at the left margin of the PostScript embedded screen type the series of decimal values, each representing an ASCII character:

xx,xxx,xx,x,xxx,xx,xx

where x represents a digit of the decimal number.

The format of the line follows these rules:

- The numbers must be separated by commas.
- Each number can have from one to three digits.
- You may include as many decimal values as fit on a line of your document. To send additional codes, use another PostScript information block.

For example, this is a valid direct ASCII code to include in the EMBED PostScript option:

83,97,109,112,108,101,32,49,46

This example line sends the ASCII characters represented by these decimal values to your printer, just as if you had typed the characters they represent on the line. In this case, the line reads:

Sample 1.

Obviously, the normal use of this command is not to enter the ASCII values of standard printing characters, since you can enter the text much more easily. Rather, you can enter the decimal equivalents of the ASCII control codes, allowing you to send control sequences to your printer to envoke special printing features.

A complete listing of ASCII codes and their decimal equivalents is included as an Appendix in the *AlphaWRITE Programmer's Information Manual*.

APPENDIX I
USER DEFINED FUNCTIONS

Some of AlphaWRITE's features can be customized. The following instructions are intended for knowledgeable users, specifically System Operators, or AlphaWRITE System Administrators.

Please refer to the *AlphaWRITE Programmer's Information* manual, DSO-00076-00, for information regarding the extended printer drivers.

The features that are easily changed include the following:

- Adding new print features
- Changing the list of supported fonts

Both of the above require a modest understanding of assembly language. In both cases, a mandatory edit of the printer driver and an optional change to a message file are involved.

ADDING NEW PRINT FEATURES

AlphaWRITE's LAYOUT submenu includes options A through D which call user functions 1 through 4 in the printer driver. In the printer drivers released with AlphaWRITE 2.0, these calls perform no function and exist solely as an avenue for enhancements.

To add a user function, follow this procedure:

1. Make a copy of an existing printer driver under a new name. You should never modify the original copy of a printer driver for two important reasons:
    - If you make an error, you can always refer to the original driver.
    - If you update to a later release of AlphaWRITE someday, you won't be in danger of accidentally overwriting changes you have made.

The LASJET.M68 printer driver source file contains instructions for an output name after assembly (LASJET, LASII, or LASIID). If you copy this driver source to modify it, make appropriate changes to the OBJNAM directives to avoid conflict in printer driver naming conventions.

2. Edit your copied driver with AlphaVUE and locate the appropriate section of code. If you want to output a pre-defined series of control codes to your printer, locate one of these four labels and insert a string (in the format used throughout the rest of the driver):

   USR1: USR2: USR3: USR4:

   When defining an output string in the printer driver, take a good look at the conventions used elsewhere in the code. Some PDVs use a length byte followed by an ASCII string; others just use an ASCIZ string.

   If the print feature you want to add is more complex and requires the execution of code, modify the PDCTL: routine and insert special code there.

   A well-behaved printer driver leaves all registers unchanged. If you need to use scratchpad registers in your code, use the SAVE and REST instructions to protect AlphaWRITE and other applications which call that printer driver. In addition, remember that register A3 is used to index the printer driver communication area, and should **not** be used for any other purpose.

3. Assemble your driver with the M68 command and copy the resulting .PDV file into the DVR: account, DSK0:[1,6].

4. Modify your PRTDEF.INI or WRITE.INI file to reflect the change in printer driver name.

5. In an AlphaWRITE document, select LAYOUT user option A for User 1, option B for User 2, option C for User 3, and/or option D for User 4. Print your test document to the printer whose driver you changed.

   You will need to reboot prior to this step, if the printer driver already exists and is in system memory.

CHANGING THE LIST OF SUPPORTED FONTS

AlphaWRITE supports 26 font families, designated A through Z, each of which are available in multiple sizes. Four font families are unassigned:

Font Q Font W Font X Font Y

To add a new font to AlphaWRITE requires a modification to the *Font Table* of a printer driver. The font table is a list of entries. Each entry describes a font. On PostScript printers, one entry per font family is sufficient because the fonts can be scaled; on HP printers, there is one distinct entry for each size of each supported typeface family.

An entry in the font table consists of the fields described next.

```
;*************************************
;*  Printer Driver Font Table Entry  *
;*************************************

     .OFINI
     .OFDEF      FO.LOG,3q0.          ; (1) logical name of font (ASCIZ)
     .OFDEF      FO.CAR,10.           ; (2) cartridge name (ASCIZ)
     .OFDEF      FO.PHY,40.           ; (3) physical name of font
     .OFDEF      FO.FLG,4             ; (4) font flags
                 FO$PRO      =1       ;  proportionally spaced font
                 FO$KRN      =2       ;  kerned font
                 FO$BLD      =4       ;  bold font
                 FO$OBL      =10      ;  oblique font
                 FO$SCL      =20      ;  scalable font (no fixed point size)
                 FO$POR      =40      ;  orientation portrait
                 FO$LAN      =100     ;  orientation landscape
                 FO$RES      =200     ;  resident font
     .OFDEF      FO.TBL,4             ; (5) width table name (RAD50)
     .OFDEF      FO.SIZ,2             ; (6) type size (points) (zero if scalable)
     .OFDEF      FO.LED,2             ; (7) leading (points) (zero if scalable)
     .OFDEF      FO.CPI,2             ; (8) CPI/pitch (for fixed fonts)
     .OFSIZ      FO.ESZ               ;  table entry size
```

Printer Driver Font Table Entry Example

About the Font Table

The font table consists of any number of entries and is terminated by a zero word. Each of its fields and aspects are described in the next sections. The numbers shown refer to the numbers in the comment area of the illustration.

(1): Font Logical Name Field

The font logical name field is 30 characters in length, but currently only single letter font family names are being used. The extra space is for future expansion.

(2): Cartridge Field

The cartridge field contains cartridge settings. Currently, this applies the HP LaserJet II printer only and contains one or more cartridge letters. AlphaWRITE will only trust that this font exists if it has been given reason to believe that one of the indicated cartridges is present at print time.

(3): Font Physical Name

The font physical name is a control sequence sent to the printer to select the font in question. On some printers this is an escape sequence, on others it is a text field.

(4): Font Flags

Font flags describe characteristics of the font. This allows AlphaWRITE to make the best decision about selecting a font based on current settings such as bold and italic.

(5): Font Table Field

The font table field, if non-zero, contains the RAD50 name of the font width table (.FWT) file associated with this font. Font width tables are necessary in order to get proper line fill and justification.

(6): Font Size Field

The font size field contains the character height of the font. This field contains zero if the font is scalable, as is the case on PostScript printers.

(7): Leading Field

The leading field contains the default leading for the font. This is typically 0-20% above and beyond the printed height of the font. On printers with controllable leading, such as most laser printers, this field is ignored.

(8): Characters Per Inch Field

The characters per inch (or pitch) field contains the characters per inch setting for a monospaced font. If this field is zero then AlphaWRITE's CPI setting from the Document Header's or Margin Format Screen's format setting field takes precedence.

Printer Driver Font Table Sample

The illustration on the following pages shows a portion of a font table reproduced from the HP LaserJet II printer driver, LASJET.

Font Table Sample from LASJET.M68

```
;***********
;*  TIMES  *
;***********
'

;Times Roman 8 (portrait)

T8:   FONT          T,FIKZ                                  ; FO.LOG
      ESC           <(0U>,<(s1p8vsb5T>                      ; FO.PHY
      LWORD         FO$POR!FO$KRN!FO$PRO                    ; FO.ALG
      RAD50         /HPT08 /                                ; FO.TBL
      WORD          8.                                      ; FO.SIZ
      WORD          0.                                      ; FO.LED
      WORD          0.                                      ; FO.CPI
      ENDF

;Times Roman 10 (portrait)

T10:  FONT          T,BFIKPZ                                ; FO.LOG
      ESC           <(0U>,<(s1p10vsb5T>                     ; FO.PHY
      LWORD         FO$POR!FO$PRO!FO$KRN                    ; FO.FLG
      RAD50         /HPT10 /                                ; FO.TBL
      WORD          10.                                     ; FO.SIZ
      WORD          0.                                      ; FO.LED
      WORD          0.                                      ; FO.CPI
      ENDF

;Times Roman 10 BOLD (portrait)

T10B: FONT          T,BFIKPZ                                ; FO.LOG
      ESC           <(0U>,<(s1p10vs1b5T>                    ; FO.PHY
      LWORD         FO$POR!FO$KRN!FO$BLD!FO$PRO             ; FO.FLG
      RAD50         /HPT10B/                                ; FO.TBL
      WORD          10.                                     ; FO.SIZ
      WORD          0.                                      ; FO.LED
      WORD          0.                                      ; FO.CPI
ENDF

;Times Roman 10 ITALIC (portrait)

T10I: FONT          T,IZ                                    ; FO.LOG
      ESC           <(0U>,<(s1p10v1sb5T>                    ; FO.PHY
      LWORD         FO$POR!FO$KRN!FO$OBL!FO$PRO             ; FO.FLG
      RAD50         /HPT10I/                                ; FO.TBL
      WORD          10.                                     ; FO.SIZ
      WORD          0.                                      ; FO.LED
      WORD          0.                                      ; FO.CPI
      ENDF

;Times Roman 12 (portrait)

T12:  FONT          T,IZ                            ; FO.LOG
      ESC           <(0U>,<(s1p12vsb5T>                     ; FO.PHY
      LWORD         FO$POR!FO$PRO!FO$KRN                    ; FO.FLG
      RAD50         /HPT12 /                                ; FO.TBL
      WORD          12.                                     ; FO.SIZ
      WORD          0.                                      ; FO.LED
      WORD          0.                                      ; FO.CPI
      ENDF

;Times Roman 12 BOLD (portrait)

T12B: FONT          T,IZ                                    ; FO.LOG
      ESC           <(0U>,<(s1p12vs1b5T>                    ; FO.PHY
      LWORD         FO$POR!FO$KRN!FO$BLD!FO$PRO             ; FO.FLG
      RAD50         /HPT12B/                                ; FO.TBL
      WORD          12.                                     ; FO.SIZ
      WORD          0.                                      ; FO.LED
      WORD          0.                                      ; FO.CPI
      ENDF
```

Font Table Sample from LASJET.M68

APPENDIX J
HP LASER PRINTING

TYPES OF HEWLETT-PACKARD LASER PRINTERS

Hewlett-Packard (HP) manufactures a wide variety of laser printers. AlphaWRITE is designed to be usable with a subset of these printers known as the *LaserJet* series. The printers that comprise the LaserJet series are:

HP LaserJet I	HP LaserJet Plus
HP LaserJet 500	HP LaserJet 500+
HP LaserJet II	HP LaserJet IID
HP LaserJet IIP	HP LaserJet III
HP LaserJet IIID	

AlphaWRITE is designed specifically to support the HP LaserJet II and III printers. The other printers in the LaserJet series do not contain all of the features of the LaserJet II and III, and this can cause different results than you expect when using AlphaWRITE.

Look-Alike Printers

In addition to the printers manufactured by Hewlett-Packard, there are many "look-alike" printers available from a variety of sources. These third-party printers tend to be less than 100% compatible with the HP, despite advertising claims to the contrary.

If you are using a look-alike printer with AlphaWRITE's printer driver for the HP, be aware AlphaWRITE advanced printing features and typesetting capabilities depend on strict HP LaserJet II or III compatibility.

HP LASER PRINTERS USING A POSTSCRIPT FONT CARTRIDGE

The information in this appendix does not apply to your HP laser printer if it has a PostScript font cartridge installed and it is defined as a PostScript printer on your Alpha Micro computer.

PostScript font cartridges are available for HP laser printers which effectively turn the HP printer into a PostScript printer: the HP printer will be defined on your computer as a PostScript printer using the LSW.DVR device driver and the PSCART.PDV printer driver.(See the *Laser Printer Support Software Installation Instructions* for complete information on defining PostScript laser printers.)

Once your HP laser printer has been defined as a PostScript printer, you have all the PostScript features available to you and can disregard information in this appendix regarding HP laser printers.

DEFINING THE LASERJET PRINTER TO AlphaWRITE

The printer driver used for the LaserJet printer depends on the HP printer you are using. AlphaWRITE comes with four printer driver flavors to support HP printers:

- LASJET.PDV - LaserJet I, LaserJet Plus, LaserJet 500, LaserJet 500+
- LASII.PDV - LaserJet II
- LASIID.PDV - LaserJet IID and LaserJet IIP
- LASIII.PDV - LaserJet III and LaserJet IIID

The printer driver must reside in account DVR: (DSK0:[1,6]) on your computer in order for AlphaWRITE to be able to print to your LaserJet printer. Loading the printer driver into system memory during system initialization is a good idea, but is not absolutely necessary.

The AlphaWRITE initialization file or system printer definition file contains one or more PRINTER command lines defining the printer(s) available on your system. Some sample printer definitions are shown below:

```
PRINTER HP,LASII,"HP LaserJet II",,,0
PRINTER LASER,LASWRT,"Apple LaserWriter+",,,0
PRINTER LPT0,MISC,"The Draft Line Printer",,,0
PRINTER LPT0,AM302,"AM302 Letter Quality",,,0
```

The first printer definition shown above defines an HP LaserJet II printer. After the keyword PRINTER are:

- Printer name = HP
- Printer driver name = LASII
- Symbolic name = HP LaserJetII

The printer name may be different on your system; the printer driver name should be one associated with the HP LaserJet printers (see previous page); and the printer description is up to you. See Appendix H - "AlphaWRITE's Initialization File" for complete details on the PRINTER command.

LASERJET FONTS

The available fonts (typefaces) for LaserJet printers vary greatly. A basic understanding of the HP LaserJet's rules of font selection is fundamental to achieving good results from AlphaWRITE.

Resident Fonts

"Resident fonts" are the fonts that are built-in to the LaserJet. The only fonts you can be sure of are 12-point Courier (plain, bold, and italic) and 8.5-point Line Printer. More recent models also have 10-point Courier (plain, bold, and italic). The LaserJet III/IIID printers have resident CG Times (Plain, bold, italic, bold-italic) and CG Univers (plain, bold, and italic) fonts that re scalable to any size. The following charts show the resident fonts for each model printer. Note: CG Univers is selected via font H (Helvetica) on the LaserJet III/IIID.

	HP LASERjET MODEL					
FONT	**I**	**II**	**IID**	**IIP**	**III**	**IIID**
Courier 10	no	no	yes	yes	yes	yes
Courier 10-Bold	no	no	yes	yes	yes	yes
Courier 10-Italic	no	no	yes	yes	yes	yes
Courier 12	yes	yes	yes	yes	yes	yes
Courier 12-Bold	yes	yes	yes	yes	yes	yes
Courier 12-Italic	yes	yes	yes	yes	yes	yes
Line Printer 8.5	yes	yes	yes	yes	yes	yes
Times[1]	no	no	no	no	yes	yes
Times-Bold[1]	no	no	no	no	yes	yes
Times-Italic[1]	no	no	no	no	yes	yes
Times-Bold Italic[1]	no	no	no	no	yes	yes
Helvetica[1]	no	no	no	no	yes	yes
Helvetica-Bold[1]	no	no	no	no	yes	yes
Helvetica-Italic[1]	no	no	no	no	yes	yes
Helvetica-Bold-Italic [1]	no	no	no	no	yes	yes

[1]Fonts scalable to any typesize.

Font Cartridges

The available fonts in a LaserJet II tend to vary because different users own different subsets of the available cartridges.

If you request a font that is internal to the HP, such as Courier 12, you will always get it. If you request a font such as Helvetica 12, you will get it only if you have instructed AlphaWRITE that a cartridge containing Helvetica 12 point type is currently present in the printer.

By using the FONTCARTRIDGE command in your AlphaWRITE initialization file, or the **QUEUE** command's font option, you can tell AlphaWRITE what cartridge(s) are installed in your HP, or look-alike, printer. This allows AlphaWRITE to make intelligent decisions about font selection and substitution.

Cartridges contain multiple fonts in a variety of sizes, and enable LaserJet users to print in more than one font. While the LaserJet front panel gives you the ability to manually select the default font and font size, *AlphaWRITE users are never required to manually adjust the printer.* All font selection is handled automatically by the output AlphaWRITE sends to the printer. Attempting to supersede AlphaWRITE by changing the front panel settings of the printer will have no effect on your printed output.

HP manufactures more than twenty-five cartridges for the HP LaserJet series of printers. These cartridges are given single-letter names. For example, the "K" cartridge is a Math/Times cartridge, containing a number of Times Roman-type fonts and special symbols suited to mathematics applications.

In addition to font cartridges manufactured by HP, many third party companies manufacture font cartridges. These third party cartridges are very popular because they offer more fonts than HP's cartridges; however, HP has introduced a 64-in-one font cartridge.

Third-party cartridges can be grouped into two categories:

- Those with fonts whose character spacings exactly match the equivalent HP fonts
- Those whose fonts have different character spacings.

If the third-party font cartridge uses different character spacings than HP does, then AlphaWRITE's typeset output will be wrong, sometimes grossly wrong. This is because AlphaWRITE consults font width tables for typesetting. These tables are based on character spacing information provided by Hewlett-Packard.

Matching AlphaWRITE's Expected Character Spacing

As an AlphaWRITE user, you will want to insure the font cartridges in use in your printer match the character spacings AlphaWRITE expects.

Use only those third-party cartridges **known** to use correct character spacings.

Purchase HP Font Cartridges That AlphaWRITE Supports

All of the HP LaserJet printers have cartridge slots that are exactly the same size. That is, any HP font cartridge will fit in any HP LaserJet model. In some cases, such as the "K" cartridge, this presents no problem. However, other cartridges are **not** model independent; such as the following:

1. Third-party font cartridges (such as Pacific Data 25-in-1).
2. Pacific page PostScript emulator.
3. HP'S own PostScript Cartridges.

The cartridges listed above are manufactured for a particular model of printer. Putting a cartridge in the wrong model will damage the cartridge, possibly damage the printer, or both. Be sure the cartridge you are using is intended for your HP LaserJet model.

Soft Fonts

Fonts are also sold in the form of files, which a host computer can send to an HP printer. The original LaserJet I cannot accept soft fonts, but all subsequent models can. The number of soft fonts your printer can hold is dependent on how much memory your printer has. Small fonts take up very little memory; large fonts take up a great deal of memory. Memory expansions are available.

Although AlphaWRITE does not know about any particular soft fonts, the extensible printer driver mechanism makes it easy for software companies, dealers, or users to define new fonts to AlphaWRITE. Some companies sell fonts along with the necessary printer driver changes, new font width tables, and font loading utilities.

Font Selection

Because the available fonts in an HP vary from site to site, it is up to you to select fonts that actually exist on your printer.

If you select a font that is not normally available for the LaserJet, AlphaWRITE performs font substitution and will use a typeface that is known to exist for the HP. Again, the results will only be good if the substituted typeface actually exists. Refer to Appendix B - "Font Substitution Charts" for tables showing the font substitution AlphaWRITE uses for LaserJet printers.

For example, imagine you have selected typeface P, Palatino—a typeface not available on an HP. If you print to a LaserJet, AlphaWRITE will request Font T (Tms Rmn) because it knows Palatino is not available. If your printer has a Tms Rmn font available, the document will use this expected substitution.

The font substitution feature may be disabled in the WRITE.INI file with the SUBSTITUTION command, or while in AlphaWRITE using the **MODE** command. The rules for font substitution are controlled by a table in the printer driver. Customizing this table is simple and straightforward, doing so is described in the *AlphaWRITE Programming Information Manual*.

Font Size Selection

The LaserJet III and IIID contain internal scalable typefaces. Earlier models only support typefaces in pre-defined sizes. For example, a cartridge may supply Helvetica 10-point and 12-point, but not 11-point.

Because AlphaWRITE documents are printer-independent, it is possible for you to select a point-size that is invalid for an HP font. When this occurs, AlphaWRITE scans the font table in the LaserJet's printer driver to see what's theoretically available in a LaserJet, and selects the closest typesize it believes is legal.

Consider a document set up for 11-point Helvetica. At print time, AlphaWRITE scans the printer driver, and finds 11-point Helvetica is **not** defined. It scans the font table a second time and decides that 10-point Helvetica is as close as it can come.

When AlphaWRITE is forced to make a change in the type size, it recalculates the pagination of the document on the spot so that the format settings for page length, text size, title area size, and so forth continue to be correct. In other words, if you set an unavailable point size for a typeface, you will not be penalized for it.

Bold & Italic Fonts

To further complicate the matter of typeface selection, only some fonts are available in bold and/or italic forms. With a particular cartridge, you may find that Times in 12 point is available in normal, bold, and italicized forms, but that 10 point Times is available only in normal form.

Most fonts for the HP are available in plain, bold, and/or italic forms; bold-italic is usually not available. Two exceptions are the scalable fonts in the LaserJet III, and soft fonts, both of which support the bold-italic style.

As with point size, AlphaWRITE will select the closest font it can to the one you request. If you select a bold or italic font and don't get it on the printed page, the reason is usually the absence of a bold or italicized font in the LaserJet.

Orientation

The LaserJet fonts that are available in a portrait orientation are separate and distinct from the fonts that are available in a landscape orientation. In general, less than 10% of the fonts on a cartridge will be for landscape printing; the bulk of the available typefaces will be portrait.

As with point size, and bold/italicized selections, AlphaWRITE automatically locates the closest font available when you ask for a font that does not exist while you are in landscape mode.

On the LaserJet IID, IIP, III, and IIID enhancements to the printing technology allow all portrait fonts to be used in landscape mode. The LASIID and LASIII printer drivers are aware of this, and should be used for these printers.

The LaserJet IID, IIP, III, and IIID can mix portrait and landscape fonts on the same page; earlier models cannot.

Font Width Tables

If AlphaWRITE cannot find a font width table for the typeface you request, it will still print your document, but the spacing between characters will be guesswork. This is most obvious in a right-justified document; the text will suddenly become ragged right after a font change.

However, during printing, AlphaWRITE will display one or more error messages should this situation occur. For example:

```
?Unable to load font width table HPT12I.FWT
```

The name of the font width table shown will be HP followed by the typeface letter and size. The letter "I" will follow for an italic font, "B" for a bold font, and "X" for a bold italic font. The sample message above indicates that the font width table for Times 12-point italic cannot be found.

Refer to Appendix N - "Font Width Tables" for a complete list of AlphaWRITE's font width tables for HP printers.

TEACHING AlphaWRITE ABOUT NEW FONTS

AlphaWRITE is only aware of resident fonts and the cartridges listed earlier. The software does not recognize any soft fonts. This does not mean, however, that new fonts cannot be used. Printer drivers use a very flexible font definition mechanism that makes it simple to define new fonts to AlphaWRITE.

Defining a new font to AlphaWRITE is a two-step process:

1. Modify the printer driver's font table to recognize the new font(s).

2. Construct a new font width table for each new font.

Step 1 is the easy part. At the end of LASJET.M68 is a table of font entries. Even if you're not an experienced assembly language programmer, understanding the entries in this table is very straightforward. *AlphaWRITE Programmers Information* documents the format of the font table entries. Adding new entries is simple.

Step 2 is a little tougher. While font width tables are not difficult in concept or structure, you must somehow obtain the width information for the font(s) you want to add. Typically, you will need to write a conversion program that reads the font widths as supplied by the manufacturer and generates an AlphaWRITE-format font width table file. A sample font width source file is provided with AlphaWRITE: HPT10.M68[10,12].

In your AlphaWRITE documents, you use the new fonts through the STYLE key's typeface option.

APPENDIX K
EMBEDDED TEXT HANDLING

HOW AlphaWRITE HANDLES LARGE DOCUMENTS

When you are editing a document, AlphaWRITE shuffles parts of your document to and from disk as necessary. This allows you to **EDIT** documents even when they are much larger than the amount of memory available to you.

The part of your document that you are working on at any given time is kept in memory and is called the *text window*.

HOW AlphaWRITE HANDLES EMBEDDED TEXT AREAS

Embedded text areas are contained within lines of your main document text and include the information blocks you make with [EMBED] or files you import now with [ESC] [/] (import feature).

Whenever you create or modify an embedded text block, it is part of the *text window*. This means that it must fit completely in memory. AlphaWRITE cannot page embedded text areas to disk.

Similarly, when you use the Import Image Now option of the import feature ([ESC] [/], option 3), AlphaWRITE brings an image file into your document. This image file, like embedded text areas, must fit completely in memory.

There are no such problems when you import an image *at print time*—[ESC] [/], option 4—because only the image file's filename is stored in the document, not the image itself. This takes an extremely small amount of memory to represent. Only when you import the image itself directly into your document will a lot of memory overhead be required.

MAXIMUM SIZE OF AN EMBEDDED TEXT AREA

Calculating the maximum size of an embedded text area is difficult because there may be more than one of them, even on the same line.

Whenever you return to the Editing Menu, AlphaWRITE displays the number of bytes (characters) of available memory remaining. As you insert and delete characters and information blocks this assessment of memory is constantly being updated.

If you are creating or editing an embedded text area, and AlphaWRITE sees less than 8K (8,192 bytes)[1] remaining in the *text window*, you receive this message:

```
Low on Memory
```

The message will be displayed on the status line and no additional lines can be inserted into the embedded text area with [INS LINE] or [RETURN].

AlphaWRITE can run out of memory even sooner if you extensively use the Import Image Now feature—option 3 of the Import Image feature ([ESC] [/]). Many image files are quite large; importing several of them directly into your document can use up most of your available memory. This is particularly prevalent when you import multiple images in the same area of a document or on the same line.

You can avoid this potential problem by using the Import Image At Print Time instead—option 4 of the Import Image feature ([ESC] [/]). Importing at print time requires just a few bytes to store the image file's name.

It is also possible AlphaWRITE will refuse to load a document if the embedded text areas or image file blocks within it are so large that AlphaWRITE cannot load a single line into memory. This is extremely rare and happens when **both** of these conditions simultaneously exist:

- An AlphaWRITE user with a very large memory partition creates embedded text areas which are extremely large, and
- An AlphaWRITE user with a very small memory partition later attempts to **EDIT** that document.

DIFFERENCES IN AlphaWRITE'S EMBEDDED TEXT HANDLING

AlphaWRITE 1.2A gave users as much memory as possible for editing, and only performed virtual paging when absolutely necessary. This resulted in fast operation and a minimum of overhead, *but* caused difficulties in the handling of large footnotes.

AlphaWRITE 2.0 attempts to keep available memory never quite filled, so that there is always plenty of space for embedded text areas and block operations. the following illustration compares the differences between AlphaWRITE 1.2A and AlphaWRITE 2.0's memory handling. While this does mean that virtual paging comes into effect sooner than it would under AlphaWRITE 1.2A, it also means that embedded text handling becomes easier. There are far fewer situations under AlphaWRITE 2.0 where large footnotes cannot be handled.

---

[1]AlphaWRITE reserves 8K of memory for block operations and virtual paging of the main document text.



AlphaWRITE 1.2A
Text Area



AlphaWRITE 2.0
Text Area

GUIDELINES FOR AVOIDING MEMORY PROBLEMS

Following a few simple rules will avoid most or all of the problem situations discussed in this appendix.

Use Import At Print Time

One way to conserve memory is to use the Import feature's Import At Print Time option 4 instead of the Import Image Now option—unless there is a good reason not to.

Typically, you only need to import a particular image file now if you want to create a self-contained, portable document to give to another Alpha Micro user.

Also, if you import an AlphaCALC worksheet, it conserves memory to do this at print time which is option 2 on the Import Feature menu.

Avoid Large Embedded Text Areas

Another way to conserve available memory is to avoid creating large embedded text areas with [EMBED]. For example, embedded text for PostScript programs or Footnotes might become very large, very quickly.

If your application or document requires a large embedded text area, increase your memory so you will not receive an Out Of Memory error message from AlphaWRITE.

APPENDIX L
SPECIFICATIONS

FEATURE	SPECIFICATION
Character Pitch	10, 12, or 15 characters per inch
Character Set	All ISO Latin I characters plus special characters for legal use, including copyright, trademark, paragraph, section, 1/4, 1/2 etc.
Disk Storage Requirements	Approximately 5950 blocks of disk storage are required. Approximately 800 blocks need to be on DSK0: to hold .LIT, .PDV, .BAS, .M68, and .HLP files. AlphaWRITE's ersatz name feature allows the remainder of the software to be relocated to any account on any disk.
Document Description	Up to 60 characters.
Document Duplicating	Copy Command: Accepts up to 36 characters to specify a full file specification or document from another account. Create Command: Prototype document field accepts up to 36 characters to specify a full file specification or document from another account.
Document Name	Up to 6 characters belonging to the ASCII character set.
Document Size	The only limit to document size is available disk space.
Embedded Text	The maximum size of embedded text (footnotes, titles, footers, TOC entries, index entries, PostScript) depends on the amount of memory available. In all but the most severe cases, the user can expect 8,192 characters to be minimally available for each embedded text entry. As the user nears the limit on available memory, a Low On Memory message is displayed on the bottom status line.

FEATURE	SPECIFICATION
Fonts	For laser printers, 36 font families are supported (A-Z, 0-9). For daisy-wheel and thimble printers, 10 fonts are supported (0-9).
Formatting	Titles (any number of lines) Footers (any number of lines)
Glossary	Glossary Document Name: Accepts up to 26 characters to specify a glossary document from another account. Number of Items in Glossary: Limited only by available disk space. Length of Glossary Entry; Limited only by available disk space.
Graphics	Start-End Line Start-End Box Start-End Rounded Box Start-End Gray Box Embedded PostScript Up to nine reusable graphics entities may overlap.
HP LaserJet Font Sizing	Typefaces come in specific sizes in the HP printing environment. For example, with the proper cartridge one can print in Helvetica 12-point or Helvetica 14-point, but not Helvetica 13-point. This is a sharp contrast to the PostScript printer support, which scales fonts to any size automatically. The LaserJet III and IIID contain resident scalable typefaces.
HP LaserJet Support	AlphaWRITE supports the HP LaserJet-series printers in general, and the HP LaserJet II and III in particular. The PDVs provided were specifically written with the LaserJet II, IID, IIP, III, IIID in mind, but should be compatible with other members of the LaserJet family, and with look-alike printers from other manufacturers.
HP Type Families	The following type families are supported for the HP LaserJet series of printers:

FEATURE	SPECIFICATION
HP Type Families (cont'd)	The letter shown to the left is the character used in response to the STYLE typeface option. **TYPE — TYPEFACE NAME** C — Courier E — Prestige F — Broadway G — Garamond H — Helvetica (HELV) or Univers I — HelveticaNarrow (HELV2) J — Cooper K — Presentations L — Letter Gothic M — Coronet N — Century Schoolbook O — Optima R — Bodoni S — Symbol (TMS MATH) T — Times (TMS RMN) or CG Times U — University V — Line Printer Support is present for all of the HP font cartridges, and for the Pacific Data 25-in-1 font cartridge. However, some of the fonts are available only as soft fonts, down-loadable to the HP printer from a computer.
Hyphenation	Manual with Discretionary Hyphen.
Justification	Fixed - monospace Variable - microspace Proportional
Keystroke Macros	Glossary Record and Playback keys
Line length	Maximum line length on the screen is 255 characters.
Mail Merge	Maximum number of fields: 128 Maximum field length: 8,192 characters (batch merge)

FEATURE	SPECIFICATION
Mail Merge (cont'd)	Maximum field length: 132 characters (interactive merge) Maximum variable name length: 64 characters
Math Mode	Available Functions: Add, Subtract, Multiply, Divide, Percent, Total Row, Total Column, Clear, Enter Accumulator contents to document.
Measurement	Lines (vertical only) Characters (horizontal only) Inches Millimeters Centimeters Ciceros Didots Points
Memory Requirements	With nothing in system memory: 360K of user memory is required when one printer using the LASWRT.PDV is defined. With **all** pertinent AlphaWRITE files loaded into system memory: 170K of user memory is required. See the *Installation Instructions* to determine the amount of memory required in your computer's configuration.
Orientation	Portrait Landscape (laser printers only)
Outlining	Number of Outline Levels: 7 Number of Outline Items: limited only by available disk space.
Password	Up to 10 characters in length.
Paste	Input Document Name Length: As many as 36 characters to specify a full file specification or document in another account. Input Document Type: AlphaWRITE documents; any ASCII character file.
PostScript Font Sizing	Each type family may be scaled in size from 1 point to 999 points inclusive. Only integer sizes are permitted (e.g. you cannot specify Helvetica 11.5 point type).

FEATURE	SPECIFICATION
PostScript Printer Support	AlphaWRITE supports PostScript printers in general, and the Apple LaserWriter Plus in particular. The PDV provided was specifically written with the LaserWriter Plus in mind, but should be compatible with other PostScript printers. Other printers that have been tested, and found to be fully compatible with AlphaWRITE 2.0, include the following: • Apple LaserWriter II NX • NEC LC890 Page Printer • Texas Instruments OmniLaser
PostScript Type Families	The following type families are supported for PostScript printers. The letter shown to the left is the character used in response to the STYLE typeface option. **TYPE TYPEFACE NAME** A Avant Garde B Bookman C Courier D Zapf Dingbats H Helvetica I Helvetica-Narrow N New Century Schoolbook P Palatino S Symbol T Times-Roman Z Zapf Chancery
Preview	Requires AMIGOS (**A**lpha **Mi**cro **G**raphics **O**perating **S**ystem) be installed on computer. Fully functional on AMIGOS-compatible graphics terminals such as the AM-72.
Print Features	Bold Built-in extended characters (PostScript printers only) Double-underscore Graphics (laser printers only) Gray (PostScript printers only) Italic Keycap Multiple typeface sizes Multiple typefaces Outline fonts (PostScript printers only) Overbar Overprint

FEATURE	SPECIFICATION
Print features *cont.*	Reverse (PostScript printers only) Screened (PostScript printers only) Special Characters Strike-out with character Subscript/Superscript Underscore
Printers	Up to 32 printers may be defined.
Printing	There are two methods of document printing available: • Print document as it appears on the screen • Reformat document while printing for best output Maximum Number of Copies at one printing: 99 Maximum Number of Pages: 9999 Symbolic Printer Name Length, specified in the initialization file: up to 30 alphanumeric characters.
Protection	Standard and Encryption.
Search and Replace	Size of search string: up to 60 characters. Size of replacement string: up to 60 characters.
Spelling Verification	Number of Words in Dictionary: Approximately 80,000 Source of Dictionary: Random House© Concise Dictionary. Number of Words in Local Dictionary: limited only by available disk space. Professional Dictionary: limited only by available disk space. Verb dictionary: limited only by available disk space.

FEATURE	SPECIFICATION
Spelling *cont.*	Source of Professional and Verb Dictionary: Operator defined. Dictionary Words Available for Display: Standard, Professional, and Verb Dictionaries.

APPENDIX M
SPECIAL CHARACTER KEY: OPTION E - EXTENDED CHARACTER

The [SPEC CHAR] key's option E, to select "Ext Char," allows you to access characters available in PostScript's Dingbats and Symbol fonts. This option is also an alternate way to access ISO Latin I characters in the PostScript typeface you are currently using. This appendix describes:

- Using the Extended Character option.
- Symbols available in PostScript's Symbols and Dingbats typefaces.
- Accessing ISO Latin I characters

If you use extended characters in your document, you forfeit printer-independence. Your correct printed result relies on using a printer that understands the extended character codes you use.

USING AN EXTENDED CHARACTER

The steps below show you how to use the extended character option specifically. From your document text display:

1. Position the cursor on the line and column where you want to print an extended character; just as you would any special character.

2. To use a symbol from the Dingbats or Symbol chart, use the [STYLE] key's option 2 to set the typeface now.

3. Unless you specify otherwise **before** requesting the extended character, it prints in the typesize currently set. If you want a smaller or larger typesize than what is currently set, use the [STYLE] typesize option to change typesize now.

4. Press [SPEC CHAR].

5. At the Enter code: prompt, type **E**.

6. At the Extended character code: prompt, type the three digit code representing the symbol you want and press [RETURN].

Do not use codes that are shown as unassigned in the chart. No printable instruction is associated with them.

7. An information block is inserted at the point where you pressed SPEC CHAR.

   When the cursor is on the information block you see a message on your display telling you it is an extended character and its code number.

   You can delete, mark, copy, and move this information block just as you do others.

For more information on using SPEC CHAR, see Chapter 7 - "Printing Features."

EXTENDED CHARACTER SYMBOLS AND CODES

The charts on the following page shows the extended character code, an illustration of that character and a descriptive name of the extended character.

The information in the Dingbats typeface symbol chart applies to the PostScript Dingbats typeface. This typeface must be in effect in order to request the symbol shown. This is the STYLE typeface selection D for Dingbats.

The information in the Symbol typeface symbol chart applies to the PostScript Symbol typeface. This typeface must be in effect in order to request the symbol shown. This is the STYLE typeface selection S for Symbol.

ABOUT THE CHARTS

The charts on the following pages show you the extended code number you supply to the SPEC.CHAR extended character option E to print the symbol illustrated.

Not all extended character codes have a printable symbol associated with them. When this is the case, the example column is empty and the descriptive name is given as Unassigned. Do not request an unassigned extended character code.

Set the typeface whose extended character or symbol you want to use **before** using the SPEC CHAR extended character option. Otherwise, you won't get the results you expect.

The typeface used for the headings and text is Helvetica; the typesize is 11 point. The typesize for the symbols themselves is 15 points.

Dingbats Typeface Extended Characters

CODE	EX.	DESCRIPTION
160		Unassigned
161	❡	Fancy pilcrow
162	❢	Fancy exclamation 1
163	❣	Fancy exclamation 2
164	❤	Heart 1
165	❥	Heart 2
166	❦	Ivy 1
167	❧	Ivy 2
168	♣	Club
169	♦	Diamond
170	♥	Heart
171	♠	Spade
172	①	Circled 1 (serif)
173	②	Circled 2 (serif)
174	③	Circled 3 (serif)
175	④	Circled 4 (serif)
176	⑤	Circled 5 (serif)
177	⑥	Circled 6 (serif)
178	⑦	Circled 7 (serif)
179	⑧	Circled 8 (serif)
180	⑨	Circled 9 (serif)
181	⑩	Circled 10 (serif)
182	❶	Reverse circled 1 (serif)

CODE	EX.	DESCRIPTION
183	❷	Reverse circled 2 (serif)
184	❸	Reverse circled 3 (serif)
185	❹	Reverse circled 4 (serif)
186	❺	Reverse circled 5 (serif)
187	❻	Reverse circled 6 (serif)
188	❼	Reverse circled 7 (serif)
189	❽	Reverse circled 8 (serif)
190	❾	Reverse circled 9 (serif)
191	❿	Reverse circled 10 (serif)
192	①	Circled 1 (no serif)
193	②	Circled 2 (no serif)
194	③	Circled 3 (no serif)
195	④	Circled 4 (no serif)
196	⑤	Circled 5 (no serif)
197	⑥	Circled 6 (no serif)
198	⑦	Circled 7 (no serif)
199	⑧	Circled 8 (no serif)
200	⑨	Circled 9 (no serif)
201	⑩	Circled 10 (no serif)
202	❶	Reverse circled 1 (no serif)
203	❷	Reverse circled 2 (no serif)
204	❸	Reverse circled 3 (no serif)
205	❹	Reverse circled 4 (no serif)

Dingbats Typeface Extended Characters (continued)

CODE	EX.	DESCRIPTION
206	❺	Reverse circled 5 (no serif)
207	❻	Reverse circled 6 (no serif)
208	❼	Reverse circled 7 (no serif)
209	❽	Reverse circled 8 (no serif)
210	❾	Reverse circled 9 (no serif)
211	❿	Reverse circled 10 (no serif)
212	➔	Arrow 1
213	→	Arrow 2
214	↔	Arrow 3
215	↕	Arrow 4
216	↘	Arrow 5
217	➔	Arrow 6
218	➘	Arrow 7
219	→	Arrow 8
220	➔	Arrow 9
221	→	Arrow 10
222	→	Arrow 11
223	➡	Arrow 12
224	➡	Arrow 13
225	➡	Arrow 14
226	➢	Arrow 15
227	➢	Arrow 16
228	➢	Arrow 17

CODE	EX.	DESCRIPTION
229	➥	Arrow 18
230	➦	Arrow 19
231	➧	Arrow 20
232	➡	Arrow 21
233	⇨	Arrow 22
234	⇨	Arrow 23
235	⇨	Arrow 24
236	⇨	Arrow 25
237	⇨	Arrow 26
238	⇨	Arrow 27
239	⇨	Arrow 28
240		Unassigned
241	⇨	Arrow 29
242	➧	Arrow 30
243	⇨	Arrow 31
244	➘	Arrow 32
245	➡	Arrow 33
246	➚	Arrow 34
247	➘	Arrow 35
248	➡	Arrow 36
249	➚	Arrow 37
250	→	Arrow 38
251	➔	Arrow 39

Dingbats Typeface Extended Characters (continued)

CODE	EX.	DESCRIPTION
252	➨	Arrow 40
253	➽	Arrow 41
254	➢	Arrow 42

Symbol Typeface Extended Characters

CODE	EX.	DESCRIPTION
160		Unassigned
161	ϒ	Upsilon (alternate style)
162	′	Minutes; feet
163	≤	Less than or equal to
164	⁄	Fraction
165	∞	Infinity
166	ƒ	Florin
167	♣	Club
168	♦	Diamond
169	♥	Heart
170	♠	Spade
171	↔	Left and right arrow
172	←	Left arrow
173	↑	Up arrow
174	→	Right arrow
175	↓	Down arrow
176	°	Degree
177	±	Plus or minus
178	″	Seconds; inches
179	≥	Greater than or equal to
180	×	Multiplied by
181	∝	Proportional; varies as
182	∂	Differential; variation

CODE	EX.	DESCRIPTION
183	•	Bullet
184	÷	Divided by
185	≠	Not equal to
186	≡	Identical with
187	≈	Approximately equal to
188	…	Ellipsis
189	|	Vertical bar; arrow extender
190	—	Horiz. bar; arrow extender
191	↵	Carriage return
192	ℵ	Aleph
193	ℑ	I fraktur
194	ℜ	R fraktur
195	℘	Weierstrass
196	⊗	Circled multiplication sign
197	⊕	Circled plus sign
198	∅	Null (empty set)
199	∩	Log. product or intersection
200	∪	Log. sum or union
201	⊃	Is a superset of
202	⊇	Is a reflex superset of
203	⊄	Is not a subset of
204	⊂	Is a subset of
205	⊆	Is a reflex subset of

Symbol Typeface Extended Characters (continued)

CODE	EX.	DESCRIPTION
206	∈	Is an element of
207	∉	Is not an element of
208	∠	Angle
209	∇	Gradient
210	®	Registered (serif)
211	©	Copyright (serif)
212	™	Trademark (serif)
213	∏	Product
214	√	Radical; root; square root
215	·	Times
216	¬	Logical not
217	∧	Logical and
218	∨	Logical or
219	⇔	Double left and right arrow
220	⇐	Double left arrow
221	⇑	Double up arrow
222	⇒	Double right arrow
223	⇓	Double down arrow
224	◊	Lozenge
225	〈	Angle left
226	®	Registered (no serif)
227	©	Copyright (no serif)
228	™	Trademark (no serif)

CODE	EX.	DESCRIPTION
229	∑	Sum
230	⎛	Left paranthesis (top)
231	⎜	Left parenthesis (middle)
232	⎝	Left parenthesis (bottom)
233	⎡	Left bracket (top)
234	⎢	Left bracket (middle)
235	⎣	Left bracket (bottom)
236	⎧	Left brace (top)
237	⎨	Left brace (middle)
238	⎩	Left brace (bottom)
239	⎪	Left brace (extender)
240		Apple logo - Apple printers
241	〉	Angle right
242	∫	Integral
243	⎮	Integral (top)
244	⎮	Integral (middle)
245	⎮	Integral (bottom)
246	⎞	Right parenthesis (top)
247	⎟	Right parenthesis (middle)
248	⎠	Right parenthesis (bottom)
249	⎤	Right bracket (top)
250	⎥	Right bracket (middle)
251	⎦	Right bracket (bottom)

Symbol Typeface Extended Characters (continued)

CODE	EX.	DESCRIPTION
252	⎫	Right brace (top)
253	⎬	Right brace (middle)
254	⎭	Right brace (bottom)

EXTENDED CHARACTER CODES AVAILABLE

If you are not using a PostScript, or PostScript-compatible printer, you can find the extended character by referring to the owner's manual accompanying your laser printer.

Your printer manual provides the list of available symbols and their associated extended character codes. These codes are also referred to as encoding vectors, character set, alternate character set, character, or conversion.

The extended character code you supply to AlphaWRITE must be in decimal radix (base ten). Some printer manual charts give you the extended character code in octal or hexadecimal radix (base eight, base sixteen respectively). The number given to AlphaWRITE must be in base ten. Therefore, if the number in your chart is in some other radix, you must first convert it to decimal before supplying it to AlphaWRITE's SPEC CHAR extended character code prompt.

ACCESSING ISO LATIN 1 CHARACTERS VIA EXTENDED CHARACTER

AlphaWRITE supports a group of characters named the ISO Latin 1 Character Set, of which the ASCII Character Set is a subset. Thus, ISO Latin 1 includes the capital and small letters A to Z, numbers, punctuation, and so on that belong to the ASCII character set, and includes other characters and symbols that are used internationally.

Typically, you'll use AlphaWRITE's Compose Character feature, discussed in Chapter 7 - "Printing Features," to access the international characters and symbols. Although Compose Character is the recommended way to access these characters, you can use the Extended Character option to access them, too.

To use Extended Character in this fashion, supply the ISO Latin I Decimal Code for the character you want to print at SPEC CHAR Extended Character's Enter Code prompt. Appendix P - "ISO Latin I Characters and Laser Printing" contains a list of the decimal codes, the character each represents, and their availability on PostScript or HP Laser printers.

The Advantages of Compose Character: Compose Character displays the ISO Latin 1 Character on your screen if you have an AM-65 terminal; or gives you a message showing the name of the character you used: Yen, Pound Sterling, and so on. Extended Character, on the other hand, will only show you an information block and what decimal code you entered; you'll have to print your document to have more than this clue about the character you selected.

APPENDIX N
FONT WIDTH TABLES

All font width tables have the extension .FWT and reside in the WRT: account. As new fonts and font cartridges are made available from manufacturers, new font width tables will be made available for AlphaWRITE. The font tables shown below are the ones accompanying the AlphaWRITE software.

HEWLETT-PACKARD LASERJET SERIES

The availability of typefaces, specific type sizes, and portrait and landscape orientations is dependent upon the font cartridges in use at the time of printing. The following fonts are the ones for which HP has provided font width table information. Other fonts, if available, may be used, but AlphaWRITE will be unable to right-justify proportionally spaced fonts properly.

HP .FWT Name	Typeface	Font	Size	Bold	Italic
HPF14	Broadway 14 pt	F	14	off	off
HPF18	Broadway 18 pt	F	18	off	off
HPF24	Broadway 24 pt	F	24	off	off
HPF30	Broadway 30 pt	F	30	off	off
HPC10	Courier 10 pt	C	10	off	off
HPC10B	Courier Bold 10 pt	C	10	on	off
HPC10I	Courier Italic 10 pt	C	10	off	on
HPC12	Courier 12 pt	C	12	off	off
HPC12B	Courier Bold 12 pt	C	12	on	off
HPC12I	Courier Italic 12 pt	C	12	off	on
HPC12X	Courier Bold-Italic 12pt	C	12	on	on
HPG06	Garamond 6 pt	G	6	off	off
HPG06B	Garamond Bold 6 pt	G	6	on	off
HPG06I	Garamond Italic 6 pt	G	6	off	on
HPG07	Garamond 7 pt	G	7	off	off
HPG07B	Garamond Bold 7 pt	G	7	on	off
HPG07I	Garamond Italic 7 pt	G	7	off	on
HPG08	Garamond 8 pt	G	8	off	off
HPG08B	Garamond Bold 8 pt	G	8	on	off
HPG08I	Garamond Italic 8 pt	G	8	off	on
HPG09	Garamond 9 pt	G	9	off	off

HP .FWT Name	Typeface	Font	Size	Bold	Italic
HPG09B	Garamond Bold 9 pt	G	9	on	off
HPG09I	Garamond Italic 9 pt	G	9	off	on
HPG10	Garamond 10 pt	G	10	off	off
HPG10B	Garamond Bold 10 pt	G	10	on	off
HPG10I	Garamond Italic 10 pt	G	10	off	on
HPG11	Garamond 11 pt	G	11	off	off
HPG11B	Garamond Bold 11 pt	G	11	on	off
HPG11I	Garamond Italic 11 pt	G	11	off	on
HPG12	Garamond 12 pt	G	12	off	off
HPG12B	Garamond Bold 12 pt	G	12	on	off
HPG12I	Garamond Italic 12 pt	G	12	off	on
HPG14	Garamond 14 pt	G	14	off	off
HPG14B	Garamond Bold 14 pt	G	14	on	off
HPG14I	Garamond Italic 14 pt	G	14	off	on
HPG18	Garamond 18 pt	G	18	off	off
HPG18B	Garamond Bold 18 pt	G	18	on	off
HPG18I	Garamond Italic 18 pt	G	18	off	on
HPG24	Garamond 24 pt	G	24	off	off
HPG24B	Garamond Bold 24 pt	G	24	on	off
HPG24I	Garamond Italic 24 pt	G	24	off	on
HPG30	Garamond 30 pt	G	30	off	off
HPG30B	Garamond Bold 30 pt	G	30	on	off
HPG30I	Garamond Italic 30 pt	G	30	off	on
HPH06	Helvetica 6 pt	H	6	off	off
HPH08	Helvetica 8 pt	H	8	off	off
HPH08B	Helvetica Bold 8 pt	H	8	on	off
HPH10	Helvetica 10 pt	H	10	off	off
HPH10B	Helvetica Bold 10 pt	H	10	on	off
HPH10I	Helvetica Italic 10 pt	H	10	off	on
HPH12	Helvetica 12 pt	H	12	off	off
HPH12B	Helvetica Bold 12 pt	H	12	on	off
HPH14	Helvetica 14 pt	H	14	off	off
HPH14B	Helvetica Bold 14 pt	H	14	on	off
HPJ14	Cooper 14 pt	J	14	off	off
HPJ18	Cooper 18 pt	J	18	off	off
HPJ24	Cooper 24 pt	J	24	off	off
HPJ30	Cooper 30 pt	J	30	off	off
HPM14	Coronet 14 pt	M	14	off	off
HPM18	Coronet 18 pt	M	18	off	off
HPM24	Coronet 24 pt	M	24	off	off
HPM30	Coronet 30 pt	M	30	off	off
HPN06	Century Schoolbook 6 pt	N	6	off	off
HPN06B	Century Schoolbook Bold 6 pt	N	6	on	off
HPN06I	Century Schoolbook Italic6 pt	N	6	off	on
HPN07	Century Schoolbook 7 pt	N	7	off	off
HPN07B	Century Schoolbook Bold 7 pt	N	7	off	off

HP .FWT Name	Typeface	Font	Size	Bold	Italic
HPN07I	Century Schoolbook Italic7 pt	N	7	off	off
HPN08	Century Schoolbook 8 pt	N	8	off	off
HPN08B	Century Schoolbook Bold 8 pt	N	8	on	off
HPN08I	Century Schoolbook Italic8 pt	N	8	off	on
HPN09	Century Schoolbook 9 pt	N	9	off	off
HPN09B	Century Schoolbook Bold 9 pt	N	9	on	off
HPN09I	Century Schoolbook Italic9 pt	N	9	off	on
HPN10	Century Schoolbook 10 pt	N	10	off	off
HPN10B	Century Schoolbook Bold 10 pt	N	10	on	off
HPN10I	Century Schoolbook Italic10 pt	N	10	off	on
HPN11	Century Schoolbook 11 pt	N	11	off	off
HPN11B	Century Schoolbook Bold 11 pt	N	11	on	off
HPN11I	Century Schoolbook Italic11 pt	N	11	off	on
HPN12	Century Schoolbook 12 pt	N	12	off	off
HPN12B	Century Schoolbook Bold 12 pt	N	12	on	off
HPN12I	Century Schoolbook Italic12 pt	N	12	off	on
HPN14	Century Schoolbook 14 pt	N	14	off	off
HPN14B	Century Schoolbook Bold 14 pt	N	14	on	off
HPN14I	Century Schoolbook Italic14 pt	N	14	off	on
HPN18	Century Schoolbook 18 pt	N	18	off	off
HPN18B	Century Schoolbook Bold 18 pt	N	18	on	off
HPN18I	Century Schoolbook Italic18 pt	N	18	off	on
HPN24	Century Schoolbook 24 pt	N	24	off	off
HPN24B	Century Schoolbook Bold 24pt	N	24	on	off
HPN24I	Century Schoolbook Italic24pt	N	24	off	on
HPN30	Century Schoolbook 30pt	N	30	off	off
HPN30B	Century Schoolbook Bold 30pt	N	30	on	off
HPN30I	Century Schoolbook Italic30pt	N	30	off	on
HPO06	Optima 6 pt	O	6	off	off
HPO06B	Optima Bold 6 pt	O	6	on	off
HPO06I	Optima Italic 6 pt	O	6	off	on
HPO07	Optima 7 pt	O	7	off	off
HPO07B	Optima Bold 7 pt	O	7	on	off
HPO08	Optima 8 pt	O	8	off	off
HPO08B	Optima Bold 8 pt	O	8	on	off
HPO08I	Optima Italic 8 pt	O	8	off	on
HPO09	Optima 9 pt	O	9	off	off
HPO09B	Optima Bold 9 pt	O	9	on	off
HPO10	Optima 10 pt	O	10	off	off
HPO10B	Optima Bold 10 pt	O	10	on	off
HPO10I	Optima Italic 10 pt	O	10	off	on
HPO11	Optima 11 pt	O	11	off	off
HPO11B	Optima Bold 11 pt	O	11	on	off
HPO11I	Optima Italic 11 pt	O	11	off	on
HPO12	Optima 12 pt	O	12	off	off
HPO12B	Optima Bold 12 pt	O	12	on	off

HP .FWT Name	Typeface	Font	Size	Bold	Italic
HPO12I	Optima Italic 12 pt	O	12	off	on
HPO14	Optima 14 pt	O	14	off	off
HPO14B	Optima Bold 14 pt	O	14	on	off
HPO14I	Optima Italic 14 pt	O	14	off	on
HPO17I	Optima Italic 17 pt	O	17	off	on
HPO18	Optima 18 pt	O	18	off	off
HPO18B	Optima Bold 18 pt	O	18	on	off
HPO18I	Optima Italic 18 pt	O	18	off	on
HPO19I	Optima Italic 19 pt	O	19	off	on
HPO24	Optima 24 pt	O	24	off	off
HPO24B	Optima Bold 24 pt	O	24	on	off
HPO24I	Optima Italic 24 pt	O	24	off	on
HPO30	Optima 30 pt	O	30	off	off
HPO30B	Optima Bold 30 pt	O	30	on	off
HPO30I	Optima Italic 30 pt	O	30	off	on
HPR14	Bodoni 14 pt	R	14	off	off
HPR18	Bodoni 18 pt	R	18	off	off
HPR24	Bodoni 24 pt	R	24	off	off
HPR30	Bodoni 30 pt	R	30	off	off
HPS10	Symbol 10 pt	S	10	off	off
HPT08	Tms Rmn 8 pt	T	8	off	off
HPT10	Tms Rmn 10 pt	T	10	off	off
HPT10B	Tms Rmn Bold 10 pt	T	10	on	off
HPT10I	Tms Rmn Italic 10 pt	T	10	off	on
HPT12	Tms Rmn 12 pt	T	12	off	off
HPT12B	Tms Rmn Bold 12 pt	T	12	on	off
HPU14	University 14 pt	U	14	off	off
HPU18	University 18 pt	U	18	off	off
HPU24	University 24 pt	U	24	off	off
HPU30	University 30 pt	U	30	off	off
HPV06	Line Printer 6 pt	V	6	off	off
HPV08	Line Printer 8 pt	V	8	off	off
HPV12	Line Printer 12 pt	V	12	off	off

LASERJET III AND IIID SCALABLE TYPEFACES

These LaserJet fonts can be scaled to any point size (noted as x in the size column). All fonts are available in Portrait and Landscape orientations.

LaserJet .FWT Name	Typeface	Font	Size	Bold	Italic
HPH00	CG Univers scalable	H	x	off	off

HP .FWT Name	Typeface	Font	Size	Bold	Italic
HPH00B	CG Univers bold scalable	H	x	on	off
HPH00I	CG Univers italic scalable	H	x	off	on
HPH00X	CG Univers bold italic scalable	H	x	on	on
HPT00	CG Times scalable	T	x	off	off
HPT00B	CG Times bold scalable	T	x	on	off
HPT00I	CG Times italic scalable	T	x	off	on
HPT00X	CG Times bold italic scalable	T	x	on	on

POSTSCRIPT PRINTERS

PostScript fonts can be scaled to any point size. All fonts are available in Portrait and Landscape orientations.

PostScript .FWT Name	Typeface	Font	Size	Bold	Italic
PSA00	Avant Garde	A	any	off	off
PSA00B	Avant Garde Bold	A	any	on	off
PSA00I	Avant Garde Italic	A	any	off	on
PSA00X	Avant Garde Bold-Italic	A	any	on	on
PSB00	Bookman	B	any	off	off
PSB00B	Bookman Bold	B	any	on	off
PSB00I	Bookman Italic	B	any	off	on
PSB00X	Bookman Bold-Italic	B	any	on	on
PSC00	Courier	C	any	off	off
PSC00B	Courier Bold	C	any	on	off
PSC00I	Courier Italic	C	any	off	on
PSC00X	Courier Bold-Italic	C	any	on	on
PSD00	Zapf Dingbats	D	any	off	off
PSH00	Helvetica	H	any	off	off
PSH00B	Helvetica Bold	H	any	on	off
PSH00I	Helvetica Italic	H	any	off	on
PSH00X	Helvetica Bold-Italic	H	any	on	on
PSI00	HelveticaNarrow	I	any	off	off
PSI00B	HelveticaNarrow Bold	I	any	on	off
PSI00I	HelveticaNarrow Italic	I	any	off	on
PSI00X	HelvitcaNarrow Bold-Italic	I	any	on	on
PSN00	New Century Schoolbook	N	any	off	off
PSN00B	New Century Schoolbook Bold	N	any	on	off
PSN00I	New Century Schoolbook Italic	N	any	off	on
PSN00X	New Century Schoolbook Bold-Italic	N	any	on	on
PSP00	Palatino	P	any	off	off
PSP00B	Palatino Bold	P	any	on	off

PostScript .FWT Name	Typeface	Font	Size	Bold	Italic
PSP00I	Palatino Italic	P	any	off	on
PSP00X	Palatino Bold-Italic	P	any	on	on
PSS00	Symbol	S	any	off	off
PST00	Times Roman	T	any	off	off
PST00B	Times Bold	T	any	on	off
PST00I	Times Italic	T	any	off	on
PST00X	Times Bold-Italic	T	any	on	on
PSZ00	Zapf Chancery	Z	any	off	off

APPENDIX O
AlphaWRITE'S SEARCH PATHS

TYPES OF SEARCH PATHS

Essentially, AlphaWRITE uses four types of search paths when it looks for a document or file you have requested:

- Your Log Account
- Standard Search Path
- Image Search Path
- Worksheet Search Path

Each search path is defined below. The specific search path a particular AlphaWRITE command or feature uses is given afterward.

Your Log Account Search Path

When you supply a 1-6 alphanumeric characters to specify a document name, AlphaWRITE assumes an extension of .WRT. AlphaWRITE looks for the document name you specified only in the account you are currently logged into.

Standard Search Path

When AlphaWRITE accepts up to 36 characters for a document name and the name you enter consists of 1-6 alphanumeric characters, AlphaWRITE looks for the document in the following places until it finds it. AlphaWRITE assumes an extension of .WRT.

1. Your log account.
2. Your project library account ([xxx,0]).
3. The WRT: account.

If you specify more than 1-6 alphanumeric characters, then AlphaWRITE will look for the file only in the account you have specified. These are examples that would cause AlphaWRITE to look only in one specific account:

```
JOHN:LETTER RETURN
DSK1:TEMPLA.WRT[100,34] RETURN
CHAP2[45,0] RETURN
```

Image File Search Path

For image files, if the file specified cannot be found using the standard search path, AlphaWRITE will also look in the IMG: account.

AlphaWRITE assumes an extension of .IMG, if you have not specified otherwise. The search path followed is:

1. Your log account.
2. Your project library account ([xxx,0]).
3. The WRT: account.
4. The IMG: account.

Worksheet Search Path

For worksheet files, if the file specified cannot be found using the standard search path, AlphaWRITE will also look in the ALC: account.

AlphaWRITE assumes an extension of .ALC, if you have not specified otherwise. The search path followed is:

1. Your log account.
2. Your project library account ([xxx,0]).
3. The WRT: account
4. The ALC: account.

SEARCH PATHS FOR COMMANDS AND FEATURES

The sections below describe the search paths used for AlphaWRITE's features and commands in terms of the types of paths defined in the previous section. In each case, the command's field name and search path is supplied.

Search Path For Copy Command

FILE	SEARCH PATH
Document to copy from	Standard search path
Document to copy to	Your log account

Search Path For Create Command

FILE	SEARCH PATH
Document name to create:	Your log account
Prototype document name:	Standard search path

Search Path For Cut Command

FILE	SEARCH PATH
Document name to cut	Your log account

Search Path For Edit Command

FILE	SEARCH PATH
Document name to edit:	Your log account

Search Path For Erase Command

FILE	SEARCH PATH
Document name to erase	Your log account

Search Path For Glossary Command

FILE	SEARCH PATH
Glossary document name	Standard search path

Search Path For Import AlphaCALC Worksheet (At Print Time)

FILE	SEARCH PATH
Worksheet name to import	Worksheet search path

Search Path For Import AlphaCALC Worksheet (Now)

FILE	SEARCH PATH
Worksheet name to import	Worksheet search path

Search Path For Import Image File (At Print Time)

File	SEARCH PATH
Image file name to import	Image search path

Search Path For Import Image File (Now)

FILE	SEARCH PATH
Image file name to import	Image search path

Search Path For Index Command

FILE	SEARCH PATH
Index prototype document name	Standard search path
Index output document name	Your log account

Search Path For Merge Command

FILE	SEARCH PATH
Template document name	Standard search path
Data document name	Standard search path
Output document name	Your log account

Search Path For Paste Command

FILE	SEARCH PATH
Document name to paste	Standard search path

Search Path For Print Command

FILE	SEARCH PATH
Document name to print	Your log account

Search Path For Rename Command

FILE	SEARCH PATH
Document old name	Your log account
Document new name	Your log account

Search Path For Toc Command

FILE	SEARCH PATH
TOC prototype document name	Standard search path
TOC output document name	Your log account

APPENDIX P
ISO LATIN I CHARACTERS AND LASER PRINTING

This appendix lists the ISO Latin I character set and provides information regarding character printing availability on PostScript and HP LaserJet printers.

POSTSCRIPT LASER PRINTING AND 8-BIT CHARACTERS

Documents containing 8-bit characters—Latin ISO Character I characters 200 to 255 decimal—and typeface changes, require your PostScript printer's memory. Typically, you will not experience any difficulty in printing these kind of documents. However, if there are excessive typeface changes on a single page where you these 8-bit characters, print difficulties may occur.

The PostScript printer requires approximately 3K of virtual memory the **first** time a typeface is used on a page where 8-bit characters are present; subsequent typeface changes on this page require 3K each. At the end of each page, the memory is reclaimed and the memory requirement process starts over again for subsequent pages.

ABOUT THE CHART

Note	Description
N/P	Means not a printable character in ISO Latin I.
N/AP	Means character is valid but is not available in a PostScript printer. If this character appears in your document, it will print as a question mark on a PostScript printer.
N/AH	Means character is valid but is not available in an HP printer.
1	Not available in earlier PostScript printers.
2	Not available in the Courier typeface in earlier PostScript printers.
3	The LASWRT driver will substitute a bullet (•) for a raised dot.
4	The printer driver will substitute a vertical bar (|) for a split bar.
5	This character is not native to the PostScript character set. The driver will substitute a constructed graphic.
6	This character will not right-justify because it is a constructed graphic; AlphaWRITE has no width information on constructed graphics.

HP	PS	DEC	OCT	CHARACTER NAME
N/P	N/P	0	0	Control-@; Null
N/P	N/P	1	1	Control-A
N/P	N/P	2	2	Control-B
N/P	N/P	3	3	Control-C
N/P	N/P	4	4	Control-D
N/P	N/P	5	5	Control-E
N/P	N/P	6	6	Control-F
N/P	N/P	7	7	Control-G
N/P	N/P	8	10	Control-H
N/P	N/P	9	11	Control-I
N/P	N/P	10	12	Control-J
N/P	N/P	11	13	Control-K
N/P	N/P	12	14	Control-L
N/P	N/P	13	15	Control-M
N/P	N/P	14	16	Control-N
N/P	N/P	15	17	Control-O
N/P	N/P	16	20	Control-P
N/P	N/P	17	21	Control-Q
N/P	N/P	18	22	Control-R
N/P	N/P	19	23	Control-S
N/P	N/P	20	24	Control-T
N/P	N/P	21	25	Control-U
N/P	N/P	22	26	Control-V
N/P	N/P	23	27	Control-W
N/P	N/P	24	30	Control-X
N/P	N/P	25	31	Control-Y
N/P	N/P	26	32	Control-Z
N/P	N/P	27	33	Control-[
N/P	N/P	28	34	Control-\
N/P	N/P	29	35	Control-]
N/P	N/P	30	36	Control-^
N/P	N/P	31	37	Control-_
		32	40	Space
!	!	33	41	Exclamation
"	"	34	42	Double Quote
#	#	35	43	Pound
$	$	36	44	Dollar
%	%	37	45	Percent
&	&	38	46	Ampersand
’	’	39	47	Single Quote
(	(	40	50	Left Parenthesis
)	)	41	51	Right Parenthesis
*	*	42	52	Asterisk
+	+	43	53	Plus
,	,	44	54	Comma
-	-	45	55	Minus; Dash
.	.	46	56	Period; Decimal Point

HP	PS	DEC	OCT	CHARACTER NAME
/	/	47	57	Slash
0	0	48	60	Zero
1	1	49	61	One
2	2	50	62	Two
3	3	51	63	Three
4	4	52	64	Four
5	5	53	65	Five
6	6	54	66	Six
7	7	55	67	Seven
8	8	56	70	Eight
9	9	57	71	Nine
:	:	58	72	Colon
;	;	59	73	Semicolon
<	<	60	74	Less Than; Left Angle Bracket
=	=	61	75	Equal
>	>	62	76	Greater Than; Right Angle Bracket
?	?	63	77	Question
@	@	64	100	At
A	A	65	101	Upper Case A
B	B	66	102	Upper Case B
C	C	67	103	Upper Case C
D	D	68	104	Upper Case D
E	E	69	105	Upper Case E
F	F	70	106	Upper Case F
G	G	71	107	Upper Case G
H	H	72	110	Upper Case H
I	I	73	111	Upper Case I
J	J	74	112	Upper Case J
K	K	75	113	Upper Case K
L	L	76	114	Upper Case L
M	M	77	115	Upper Case M
N	N	78	116	Upper Case N
O	O	79	117	Upper Case O
P	P	80	120	Upper Case P
Q	Q	81	121	Upper Case Q
R	R	82	122	Upper Case R
S	S	83	123	Upper Case S
T	T	84	124	Upper Case T
U	U	85	125	Upper Case U
V	V	86	126	Upper Case V
W	W	87	127	Upper Case W
X	X	88	130	Upper Case X
Y	Y	89	131	Upper Case Y
Z	Z	90	132	Upper Case Z
[	[	91	133	Left Square Bracket
\	\	92	134	Backslash
]	]	93	135	Right Square Bracket

HP	PS	DEC	OCT	CHARACTER NAME
^	^	94	136	Caret; Circumflex
_	_	95	137	Underscore
‘	‘	96	140	Grave Accent
a	a	97	141	Lower Case A
b	b	98	142	Lower Case B
c	c	99	143	Lower Case C
d	d	100	144	Lower Case D
e	e	101	145	Lower Case E
f	f	102	146	Lower Case F
g	g	103	147	Lower Case G
h	h	104	150	Lower Case H
i	i	105	151	Lower Case I
j	j	106	152	Lower Case J
k	k	107	153	Lower Case K
l	l	108	154	Lower Case L
m	m	109	155	Lower Case M
n	n	110	156	Lower Case N
o	o	111	157	Lower Case O
p	p	112	160	Lower Case P
q	q	113	161	Lower Case Q
r	r	114	162	Lower Case R
s	s	115	163	Lower Case S
t	t	116	164	Lower Case T
u	u	117	165	Lower Case U
v	v	118	166	Lower Case V
w	w	119	167	Lower Case W
x	x	120	170	Lower Case X
y	y	121	171	Lower Case Y
z	z	122	172	Lower Case Z
{	{	123	173	Left Curly Brace
|	|	124	174	Vertical Bar
}	}	125	175	Right Curly Brace
~	~	126	176	Tilde
N/P	N/P	127	177	DEL or RUBOUT
N/P	N/P	128	200	Upper Control-@; Upper Null
N/P	N/P	129	201	Upper Control-A
N/P	N/P	130	202	Upper Control-B
N/P	N/P	131	203	Upper Control-C
N/P	N/P	132	204	Upper Control-D
N/P	N/P	133	205	Upper Control-E
N/P	N/P	134	206	Upper Control-F
N/P	N/P	135	207	Upper Control-G
N/P	N/P	136	210	Upper Control-H
N/P	N/P	137	211	Upper Control-I
N/P	N/P	138	212	Upper Control-J
N/P	N/P	139	213	Upper Control-K
N/P	N/P	140	214	Upper Control-L

HP	PS	DEC	OCT	CHARACTER NAME
N/P	N/P	141	215	Upper Control-M
N/P	N/P	142	216	Upper Control-N
N/P	N/P	143	217	Upper Control-O
N/P	N/P	144	220	Upper Control-P
N/P	N/P	145	221	Upper Control-Q
N/P	N/P	146	222	Upper Control-R
N/P	N/P	147	223	Upper Control-S
N/P	N/P	148	224	Upper Control-T
N/P	N/P	149	225	Upper Control-U
N/P	N/P	150	226	Upper Control-V
N/P	N/P	151	227	Upper Control-W
N/P	N/P	152	230	Upper Control-X
N/P	N/P	153	231	Upper Control-Y
N/P	N/P	154	232	Upper Control-Z
N/P	N/P	155	233	Upper Control-[
N/P	N/P	156	234	Upper Control-\
N/P	N/P	157	235	Upper Control-]
N/P	N/P	158	236	Upper Control-^
N/P	N/P	159	237	Upper Control-_
N/P	N/P	160	240	Required Space
¡	¡	161	241	Inverted Exclamation
¢	¢	162	242	Cent
£	£	163	243	Sterling
¤	¤	164	244	Currency
¥	¥	165	245	Yen
|	N/AP	166	246	Split Bar[4]
§	§	167	247	Section
¨	¨	168	250	Dieresis; Umlaut
N/AH	©	169	251	Copyright [2]
a	a	170	252	Ord Feminine
«	«	171	253	Left Guillemot
N/AH	N/AP	172	254	Not
N/P	N/P	173	255	Discretionary Hyphen
N/AH	®	174	256	Registered[2]
¯	¯	175	257	Macron
°	°	176	260	Degree; Ring
?	N/AP	177	261	Plus/Minus
?	N/AP	178	262	Raised 2
?	N/AP	179	263	Raised 3
‘	‘	180	264	Acute Accent
?	N/AP	181	265	Micro
¶	¶	182	266	Pilcrow; Paragraph
•	N/AP	183	267	Raised Dot[3, 6]
¸	¸	184	270	Cedilla
?	N/AP	185	271	Raised 1
º	º	186	272	Ord Masculine
»	»	187	273	Right Guillemot
¼	¼	188	274	One-quarter[5, 6]

HP	PS	DEC	OCT	CHARACTER NAME
½	½	189	275	One-half[5, 6]
¾	¾	190	276	Three-quarters[5, 6]
¿	¿	191	277	Inverted Question
À	À	192	300	A-grave
Á	Á	193	301	A-acute
Â	Â	194	302	A-caret
Ã	Ã	195	303	A-tilde
Ä	Ä	196	304	A-dieresis; A-umlaut
Å	Å	197	305	A-ring
Æ	Æ	198	306	AE[2]
Ç	Ç	199	307	C-cedilla
È	È	200	310	E-grave
É	É	201	311	E-acute
Ê	Ê	202	312	E-caret
Ë	Ë	203	313	E-dieresis; E-umlaut
Ì	Ì	204	314	I-grave
Í	Í	205	315	I-acute
Î	Î	206	316	I-caret
Ï	Ï	207	317	I-dieresis or I-umlaut
ð	ð	208	320	Eth[1]
Ñ	Ñ	209	321	N-tilde
Ò	Ò	210	322	O-grave
Ó	Ó	211	323	O-acute
Ô	Ô	212	324	O-caret
Õ	Õ	213	325	O-tilde
Ö	Ö	214	326	O-dieresis; O-umlaut
?	N/AP	215	327	Multiplication; Times
Ø	Ø	216	330	O-slash
Ù	Ù	217	331	U-grave
Ú	Ú	218	332	U-acute
Û	Û	219	333	U-caret
Ü	Ü	220	334	U-dieresis; U-umlaut
?	N/AP	221	335	Y-acute
Þ	Þ	222	336	Thorn[1]
ß	ß	223	337	Ess-tset; German Double S
à	à	224	340	a-grave
á	á	225	341	a-acute
â	â	226	342	a-caret
ã	ã	227	343	a-tilde
ä	ä	228	344	a-dieresis; a-umlaut
å	å	229	345	a-ring
æ	æ	230	346	ae[2]
ç	ç	231	347	c-cedilla
è	è	232	350	e-grave
é	é	233	351	e-acute
ê	ê	234	352	e-caret
ë	ë	235	353	e-dieresis; e-umlaut

HP	PS	DEC	OCT	CHARACTER NAME
ì	ì	236	354	i-grave
í	í	237	355	i-acute
î	î	238	356	i-caret
ï	ï	239	357	i-dieresis; i-umlaut
ð	ð	240	360	eth[1]
ñ	ñ	241	361	n-tilde
ò	ò	242	362	o-grave
ó	ó	243	363	o-acute
ô	ô	244	364	o-caret
õ	õ	245	365	o-tilde
ö	ö	246	366	o-dieresis; o-umlaut
?	N/AP	247	367	Division; Divide
ø	ø	248	370	o-slash
ù	ù	249	371	u-grave
ú	ú	250	372	u-acute
û	û	251	373	u-caret
ü	ü	252	374	u-dieresis; u-umlaut
?	N/AP	253	375	y-acute
þ	þ	254	376	thorn[1]
ÿ	ÿ	255	377	y-dieresis; y-umlaut

INDEX

//

// symbol
  comment 2-10

£

£ symbol
  as character 8-8
  as page number 8-8

#

symbol
  as character 8-8
  as page number 8-8
  footers 8-8
  titles 8-4, 8-5

%

% symbol
  as chapter number 8-8, 8-9
  as character 8-9
  footers 8-8
  titles 8-4, 8-5
%! symbols
  PostScript programming 14-9

*

* symbol 2-5
  wildcard 10-4

.

.### files 14-4
.BAK files 14-4
.JRN files 14-4
  mode command 11-6
.LST files 14-4
  .WRT document as 6-2
.TMB files 14-5
.TMF files 14-5
.TMI files 14-5
.TML files 14-5
.TMP files 14-5
.TMR files 14-5
.TMS files 14-5
.TMT files 14-5
.TMX files 14-5
.WRT files 10-4, 14-4

/

/OUT command
  direct ASCII codes 14-12

<

< symbol 2-6
  as character 12-12
  as text character 13-12
  glossary entries 12-12
  merge command 13-11, 13-12

>

> symbol 2-6
  as text character 13-12
  glossary entries 12-12
  merge command 13-11, 13-12

?

? symbol
  wildcard 10-4

132-column display 3-1
  width command 11-7, 11-8

80-column display 3-1
  width command 11-7, 11-8

A

Abbreviations
  commands 1-4, 1-5
Account name
  inserting with Glossary key 12-10
Accumulator
  Math key 12-4, 12-5
Addition
  Math key 12-4
Allow format
  format setting 5-6, 5-7
Alphabet
  numbering style 8-10
Alphabetic order
  directory listings 10-5
Alphabetizing text 13-1, 13-2
AlphaCALC worksheets
  importing 14-5, 14-6
AlphaWRITE
  calling up 1-1, 1-2
  default settings C-1 to C-3
  exiting 1-1, 1-2
  overview xviii to xxi
AlphaWRITE 1.2A document
  converting G-2, G-3
AlphaWRITE Installation Instructions xxv
AM-301 printers
  print features available E-1, E-2
AM-302 printers
  print features available E-1, E-2
AM-306 printers
  print features available E-1, E-2
AM-65 terminal
  ISO Latin-1 characters 7-12

AM-70 terminal
kind of color used H-5
AM-72 terminal
palette command for color H-11
AMIGOS 6-8, 6-9
AMIGOS-compatible terminals 6-8, 6-9
AMOS
command level 1-1
error messages D-1
printing documents 6-2
WRTDIR command 10-4, 10-5
Ampersands
end of embedded text screens 1-7
Apple laser printers
font substitution B-2
print features available E-1, E-2
Arabic numerals 8-10
numbering style 8-9, 8-10, 8-13
Arithmetic operations
Math key 12-4 to 12-6
Arrow keys
command screens 1-6
ASCII
character set, document names 2-2
converting text files G-2
file, paste input document 9-3
sequences 14-12
Asterisks 2-5
end-of-document characters 1-7
Attribute color H-5
Author field
Document Header 5-7
Auto Insert Character key 3-4
charinsert command H-4
mode command 11-3
Auto Insert Line key
lineinsert command H-9
mode command 11-3
outlining 12-8, 12-9
AWCONV
conversion utility xix, G-1 to G-4
SuperVUE conversions G-8
WordPerfect conversions G-4

B

Bins
selecting with Layout key 6-4, 6-5
Blank spaces 3-5
BLDPRF utility 15-6, 15-7
Block Clear key 3-6
cut command 9-2
sort command 13-2
spell command 9-8
Block Copy key 3-5, 3-6
Block Delete key 3-3, 3-5, 3-6
Block Mark key 3-5, 3-6
cut command 9-1
document text display 1-9
embedded text screens 1-9
global command 9-5
replace command 9-5
search command 9-4
spell command 9-7
Block Move feature 3-5, 3-6
Blocks
copying 3-5
deleting 3-3
moving 3-5
undo feature 3-3
Bold
display 11-5, 11-8
displayattribute command H-7
print feature 7-6
Boolean response
initialization file H-3, H-4
Boxes
drawing 7-18 to 7-22
Brackets
as characters 12-12
as text characters 13-12
Bullet
printing 7-11

C

Calculator
Math key 12-4 to 12-6
Calendar feature 12-3, 12-4
Cancel key 1-6, 1-7, 3-3
Document Margin Screen 4-3
when to use 1-5
Capitalization
changing 3-4
mode option 11-2
search, replace, global commands 9-6
Cell range
importing worksheets 14-6
Cent symbol
printing 7-11
Center Line key 3-4
Center Screen key 3-1
Center tabs 4-8
Centered tab 4-2
Centimeters
unit of measurement 5-4
Chapter and page number
printing together 8-9
Chapter numbers 8-8 to 8-13
chapter page break 8-9
footers 8-8
setting to specific number 8-10 to 8-13
style 8-9 to 8-13
titles 8-4, 8-5
Chapter page breaks 6-3, 8-9
Character Delete key 3-3
Character Insert key 3-4
Document Margin Screen 4-1, 4-2
Character insert mode 3-4
mode option 11-3
Character width
blank spaces 3-5
Characters
change capitalization 3-4
deleting 3-3
erasing 3-3
inserting 3-4
reversing 3-4
unit of measurment 5-3
Characters per inch
format setting 5-7
Charinsert command
default for mode command 11-7
initialization file H-4
Cicero
unit of measurement 5-4
Clearing marks 3-6
Clones
third-party fonts B-4
Collapsed text 4-5
deleting 4-6
editing 4-6
exercise 4-6
number of lines allowed 1-9
Color
color command H-4, H-5
intensity command H-8
mode option 11-6 to 11-9

Color *(continued)*
ribbon selection 7-8
set with palette command H-11
Column mark operations 3-6
corners 3-6
cut command 9-1
document text display 1-9
embedded text screens 1-9
sort command 13-1
spell command 9-8
Column position
cursor 2-5
Columns
adding numbers in 12-5
copying 3-5
deleting 3-3
making 4-5, 4-7
moving 3-5
numbers at decimal tab 4-8
resume print at top of page 7-22, 7-23
text display 2-5
undo feature 3-3
Command screens
displaying directory list 10-1
exiting 1-5
Command type-ahead
edit command 1-2
write command 1-2
Commands
abbreviations 1-4, 1-5
default settings C-1 to C-3
executing 1-6, 1-7
help information 1-3
interrupting 1-6
type-ahead 1-3, 1-4
Comment characters
initialization file H-3
Comments
non-printing text 2-10
Compose character feature 7-12 to 7-18
Conditional page breaks 5-18, 6-3
Conjugating verb dictionary 15-2
Control key A-1
Conventions
used in this book xxiii
Conversion tables
units of measurement 5-12
Copies
during printing 6-2
Copy command 10-6, 10-7
Copyright symbol
printing 7-11
Courier typeface
character availability 7-2, 7-11
CPU ID
copy command 10-7
paste command 9-3, 9-4
Create command 2-1 to 2-4
default setting C-1
document name conflict 2-2
going to edit command 2-2
new documents 2-1 to 2-4
prototype document name 2-1, 2-2
CTRL-Y feature 3-3
Cursor
current position 2-5
moving 3-1 to 3-6
moving at Document Margin Screen 4-1
moving in document 2-9
moving to tab setting 4-4
position 2-8
Cut command 9-1 to 9-3
column marks 3-6
default setting C-1
marked text 3-5

D

Dagger symbol printing 7-11
Dashes
printing 7-11
Data document
ASCII files as 13-12
data lines 13-12
merge command 13-12
Date
American format 10-4
Calendar feature 12-3, 12-4
European format 10-4
formats directory criteria 10-4
inserting with Glossary key 12-10
Decimal tabs 4-2, 4-8
Space Bar 4-8
Default settings C-1 to C-3
AWCONV command G-3
mode command 11-7
DEFDOC prototype document
default 2-1 to 2-3
default settings C-1
format settings 2-3, 5-3
sample document 2-12
search path 2-3, 5-3
Degree symbol
printing 7-11
Delete Character key
Document Margin Screen 4-2
Delete Line key
Document Margin Screen 4-3
Deleting text 3-3
undo previous 3-3
Department field
Document Header 5-7
Description field
Document Header 5-7
DICSRT utility 15-6, 15-7
Dictionaries 15-1 to 15-8
mode command 11-3, 11-4
spell command 9-7 to 9-10
Dictionary command
default for mode command 11-7
initialization file H-5
Dictionary words
displaying 9-9, 9-10
using 9-10
Dictionarytwo command 15-5, 15-6
default for mode command 11-7
initialization file H-6
mode command 11-4
Didots
unit of measurement 5-4
Dingbats typeface F-2 to F-4
DIRECT.LST 10-5
Directory command 10-2 to 10-4
default settings C-1
Directory criteria
date formats 10-4
Directory display
from command screens 1-5
Directorysize command
initialization file H-6
Discretionary hyphen 5-21, 7-5
formatting 5-22
Disk output only
directory list 10-5
print prompt 6-2
Display
information block - turning off/on 7-12
Display settings
color command H-4, H-5, H-12
displayattribute command H-6, H-7

Display settings *(continued)*
intensity command H-8
menubypass command H-10
mode command H-11
modem command H-11
palette command H-11, H-12
Displayattribute command
default for mode command 11-7
initialization file H-6, H-7
Division
Math key 12-4
Document conversions
temporary files 14-5
Document Header
create document 2-4
directory command 10-5
displayed during create command 2-2
format settings 5-1
mini-help 1-3, 1-6
Document Margin Screen 4-1 to 4-4
exiting without change 4-3
formatting upon exit 4-4
keeping changes 4-3
Document names 1-4, 2-2
conflict with create command 2-2
displaying from command screens 1-5
maximum characters for prototype 2-2
maximum characters paste command 9-2, 9-3
new documents 2-1
overwriting existing 9-2
specifying with write command 1-2
TEMP 9-1 to 9-3
Document text display
create command 2-2
information block messages 1-7
Documentation xxi to xxv
Documents
asterisks as end characters 2-5
available for copy command 10-6, 10-7
converting with AWCONV G-1 to G-4
copying 10-6, 10-7
copying text between 9-1 to 9-4
creating 2-1 to 2-4
default GLOSS.WRT 12-11
editing text 3-1 to 3-6
entering text 2-8
erasing 10-5, 10-6
exiting with finish 2-11, 2-12
exiting with quit 2-11
exiting with save 2-11
glossary 12-11
importing AlphaCALC worksheets 14-5, 14-6
importing image files 14-6 to 14-8
indexing 13-3 to 13-7
list of 10-1 to 10-4
merging 13-10 to 13-15
moving to beginning 3-2
moving to end 3-2
printing 6-1 to 6-8
protected and cut command 9-3
protection schemes 16-1, 16-2
recovering with journaling 14-2
sample 2-12
saving 2-11
setting margins and tabs 4-1 to 4-7
size and import images 14-8
spell checking 9-7 to 9-10
table of contents generation 13-7 to 13-10
that AlphaWRITE creates 14-4, 14-5
Double underscore
print feature 7-6
Down Arrow key 3-2
command screens 1-5, 1-6
screen displays 1-5
Downloadable font B-3

E

Edit command 2-2
from create command 2-2
type-ahead 1-3, 1-4
type-ahead with write command 1-2
Editing features xx, xxi
document text 3-1 to 3-6
Editing Menu
command abbreviations 1-4, 1-5
commands available from embedded text 1-10
help information 1-3
menubypass command 11-3, H-10
moving to text display 1-6
type-ahead 1-3, 1-4
Element numbers 7-19
graphics feature 7-19
Em dash
printing 7-11
Embed key 1-7, 1-8, 8-1 to 8-13
collapsed text feature 4-5, 4-6
exit embedded text screens 1-8
index entry option 13-3, 13-4
page overlay 7-4, 7-5
PostScript option 14-8 to 14-12
toc entry 13-7, 13-8
undo feature 3-3
Embedded text
behavior of screens 1-7, 1-8
Editing Menu commands 1-10
exiting 1-8
footers 8-6
footers word wrap 8-7
footnotes 8-3
index entries 13-6
interrupting text entry 1-8
kinds of 1-8
number of lines allowed 1-8
printing contents 1-10
restrictions 1-9
size restrictions 1-9
table of contents 13-10
titles 8-5
titles word wrap 8-5
En dash
printing 7-11
Encryption 16-2
protection scheme 16-1
End-of-document characters
document text display 1-7
embedded text screens 1-7
Enhancement list xix
ENV.WRT
sample document 2-12
Envelope
format settings 5-15
EPSF standard
PostScript programming 14-9
Erase command 10-5, 10-6
Erasing characters 2-10
Erasing text 3-3
undo previous 3-3
Error messages xxv, xxvi, D-1 to D-22
color used for display 11-9
Ersatz account xix
Ersatz names
AlphaWRITE account H-2
dictionary location H-5, H-6
input documents 10-7
Escape key A-1
substitute A-1

Even footers 8-6, 8-7
number of lines allowed 1-9
Even titles 8-3 to 8-5
number of lines allowed 1-9
Execute key 1-6
behavior 1-6, 1-7
Document Margin Screen 4-3
embedded text screens 1-8
when to use 1-5
Extended characters
built-in 7-11, 7-12
printing 7-11
Extensions
used by AlphaWRITE 14-4, 14-5

F

FAX.WRT
sample document 2-12
Feature list xix
Features
default settings C-1 to C-3
interrupting 1-6
Field prompts
color used 11-9
Filename
inserting with Glossary key 12-10
Files (see also documents)
converting to AlphaWRITE G-1 to G-4
importing 14-5 to 14-8
that AlphaWRITE creates 14-4, 14-5
Finish command 2-2
availability embedded text screen 1-9
exiting documents 2-11, 2-12
Flush left tabs 4-2, 4-7
evenly spaced 4-2
Flush right tabs 4-2, 4-7
Fold case
mode option 11-2
search, replace, global commands 9-6
Font cartridges B-3
Font command
fontcartridge command B-1, B-3
initialization file H-7
Font families
PostScript samples F-1 to F-6
print samples F-1, F-2
Font names B-4
Font option
Style key's typeface menu 7-2
Font specification
changing with Queue command 6-5 to 6-8
Font substitution B-1 to B-3
mode option 11-5
Fontcartridge command B-1, B-3
initialization file H-7, H-8
Fonts
on impact printers 7-2, 7-3
Footer length
format setting 5-7
Footers 8-6, 8-7
footer length format setting 8-7
importing images 8-8
number of lines allowed 1-9
typeface and typesize 8-7
Footnote line separator
format setting 5-7, 5-8
Footnote print type
format setting 5-8
Footnotes 8-1 to 8-3
identifiers 8-2
line separator format setting 8-2
number of lines allowed 1-9
print type format setting 8-2
Footnotes *(continued)*
temporary file 14-5
Foreign language support xix, xxv
Form name
changing 6-5, 6-6
Format
automatic 4-4, 9-6
command 7-5
Format key 7-5
Format key and indented text 4-5
Format key and mode command 11-5
glossary documents 12-12
mode command 7-5, 11-5
outline command 12-6 to 12-9
Format command 5-20
footers 8-7
mode command 11-5
titles 8-5
Format key 5-19
footers 8-7
titles 8-5
Format line
text display 2-5, 2-6
Format settings 5-1 to 5-20, 5-22
default 5-2
displayed by Margin key 4-3, 4-4
Document Header 2-2, 5-1
footers 8-7
footnotes 8-2
formula 5-12
importing worksheets 14-6
laser printing 5-4
Margin key 5-2
mini-help 1-3, 1-6
page relationship 5-5
paste command 9-4
titles 8-4
Formatting 5-19
allow format 5-20
automatic 5-21
Full file specification
paste input document name 9-3
Funct key 7-9

G

Global command 9-4 to 9-6
automatic formatting 5-21
capitalization 11-2
interrupting 9-6
marked text 3-5
GLOSS.WRT file 14-5
default glossary document 12-11
search path for 12-11
Glossary 12-10 to 12-13
brackets as characters 12-12
command 12-11
compared to record 12-3
default GLOSS.WRT 12-11
Glossary command
default settings C-1
Glossary key 12-10
Go to page feature
Page key 3-2
Graphics
line weight 7-21
printing 7-18 to 7-22
Graphics terminals
preview command 6-8, 6-9

Gray print feature 7-6, 7-7
  page overlays 7-3

H

Half fraction symbol
  printing 7-11
Hard page breaks 5-18, 6-3
Header command 10-5
  default settings C-1
  format settings 2-4
  mini-help 1-3, 1-6
Help information
  displaying 1-3, 1-6
  glossary entries 12-10
  Help command 1-3
  Help key 1-3, 1-6
  Help screens 1-3
  spell's dictionaries and Help key 15-5
Hewlett-Packard printers
  font availability B-3
  font names B-4
  font substitution B-3
High and low intensity
  mode option 11-6
History directory list 10-2
Home key 3-2
Home key (shifted) 3-2
HP laser printers
  font cartridge designations H-8
  font command H-7
  font selection 6-8
  font substitution B-3
  image file validity 14-7
  print features available E-1, E-2
  typeface selection 7-2
  typeface option 6-8
Hyphen
  discretionary 7-5

I

Image files
  importing 14-6 to 14-8
  writing your own 14-12
Impact printers
  fonts 7-2, 7-3
Import feature 14-5 to 14-8
Importing images
  footers 8-8
  titles 8-5
Inches
  unit of measurement 5-4
Indent key 4-5
  double indent 4-7
  format settings 5-21
INDEX.WRT
  sample document 2-12
Indexing 13-3 to 13-7
  availability of index command 1-9
  index command 13-3 to 13-5
  index command default settings C-2
  index entries 1-9, 13-3, 13-4, 13-7
  INDEX.WRT 13-5, 13-6
  temporary file 14-5
Information area
  text display 2-5
Information blocks
  messages 2-7
  turning on/off display 7-12
Information message
  color used 11-9
Initialization file H-1 to H-12
  command list H-4
  comment characters H-3
  creating H-1
  default settings for mode command 11-7
  Dictionarytwo command 11-4
  journal features 14-1, 14-2
  location H-2
  mode command 11-1
  name H-2
  Palette command 11-6
  printers defined by 6-3
  rules for H-3, H-4
  search path for H-2, H-3
  used by write command 1-1
Input fields
  color used 11-9
Insert mode 2-8
  and glossary feature 12-13
Inserting text 3-4
Installation screen
  for PIC entry 1-2
Intensity command
  default for mode command 11-7
  initialization file H-8
International characters
  printing 7-13 to 7-18
Interrupt
  Cancel key 9-6
ISO Latin-1 characters
  printing 7-12 to 7-18
Italics
  print feature 7-6

J

Journaling
  journal command 14-1, H-9
  journal command default 11-7
  journal file and save command 2-11
  journal file extension 14-4
  journal file full 14-3, 14-4
  journal files 14-1 to 14-4
  journalsize command 14-1, H-9
  journalsize command and mode command 11-7
  keystrokes command H-9
  mode command 11-6
  mode option 11-6

K

Kerning
  format setting 5-8
  methods of 5-13
Key sequences A-1 to A-6
  used in glossary entries 12-13
Keycap
  printing 7-7
Keystroke journaling xix, 14-2 to 14-4
  mode command 11-6
Keystrokes
  playing back recorded 12-2
  recording 12-1 to 12-3
Keystrokes between updates
  mode option 11-7
Keystrokes command
  default for mode command 11-7
  initialization file 14-2, H-9

L

Labels
  format settings 5-16

LAND.WRT
sample document 2-12
Landscape orientation 5-14
Language Definition File
date format 10-4
.lan extension H-1
Laser printers
font samples F-1, F-2
format settings 5-4, 5-5
graphics printing 7-18 to 7-22
Layout key 7-9, 8-8 to 8-13
bin option 6-4, 6-5
chapter page breaks 6-3
graphics features 7-18 to 7-22
print index option 13-3 to 13-5
print toc option 13-7 to 13-9
set gray option 7-7
Leading
format setting 5-8, 5-9
six lines per inch 5-9
Leave AlphaWRITE
quit command (Main Menu) 1-2
Left Arrow key 3-2
command screen 1-6
shifted 3-2
Left margin 5-4
Left paper offset
format setting 5-4, 5-9
Left tabs 4-7
Legal paper
format settings 5-13
LEGAL.WRT
sample document 2-12
Line Delete key 3-3
Line Insert key 3-4, 3-5
outlining 12-8
Line insert mode 3-4
mode command setting 11-3
Line position
cursor 2-5
Line spacing
format setting 5-9
Line weight
setting 7-21
Lineinsert command
default for mode command 11-7
initialization file H-9, H-10
Lines
breaking 3-5
centering 3-4
delete to end of 3-3
deleting 3-3
drawing 7-18 to 7-22
inserting 3-4
joining 3-5
moving to beginning 3-2
moving to end 3-2
unit of measurement 5-3
Lines per inch
printing 6 lpi 5-9
Listing files
temporary 14-5
Local dictionary
mode command 11-4
LOCAL.DCT 14-5, 15-1 to 15-5
dictionary 9-9
mode command 11-4
source for professional dictionary 15-6
Look-alike font names B-4

M

Main Menu
command abbreviations 1-4, 1-5
help information 1-3
illustrated 1-2
returning to from command screen 1-6
type-ahead 1-3, 1-4
when displayed 1-1
Margin key 4-1 to 4-7
areas affected by 4-4
format settings 5-2, 5-21
Format Settings screen 4-3, 4-4
outlining 12-9
setting previous margin 4-2
titles 8-5
Margin screen
formatting from 5-21
Margins
deleting existing 4-3
double indenting 4-7
setting left 4-2
setting right 4-2
Marking and clearing text 3-5, 3-6
Math key 12-4 to 12-6
Maximum journal keystrokes
mode option 11-6
Measurement
conversion tables 5-12
MEMO.WRT
sample document 2-12
Memory
loading dictionaries 15-3
Memory tip
directorysize command H-6
Menu Bypass feature
menubypass command 11-7, H-10, H-11
mode command 11-3
Menu key
behavior 1-6
document text display 2-2
help screens 1-3
menu bypass option 11-3, H-10
when to use 1-5
Menus
using 1-5 to 1-7
Merge command 13-10 to 13-15
automatic formatting 5-21
using interactively 13-14
Message text
embedded text screens 1-7
Messages
error condition D-1 to D-22
information block 2-7
Millimeters
unit of measurement 5-4
Mode color H-5
Mode command 11-1 to 11-9
default settings 11-7, C-2
dictionary options 15-2
fold case option 9-6
font substitution B-1
journaling 14-1, 14-2
mini-help 1-3, 1-6
spell command 9-8
Modem command
initialization file H-11
Moving
through document 3-1 to 3-6
Multiplication
Math key 12-5

N

Name directory list 10-2
Network number
  paste command 9-3, 9-4
Networks
  copy command 10-6
  using files over 2-2
Next Match key
  search command 9-4
Next Page feature 3-2
Next Screen key 3-2
  help screens 1-3
  (shifted) 3-2
Next Sentence feature 3-3
Next Word key 3-2
  (shifted) 3-3
Non-breaking space 7-9
Non-expandable blank 7-9
Non-numeric characters
  Math key 12-6
Numbers
  adding column or row 12-5
  entering at decimal tab 4-8
  page and chapter 8-8 to 8-13
Numeric characters
  Math key 12-6

O

Odd footers 8-6, 8-7
  number of lines allowed 1-9
Odd titles 8-3 to 8-5
  number of lines allowed 1-9
On-screen attributes
  mode option 11-5
Operation settings 11-1 to 11-9
Operator field
  Document Header 5-9
Orientation
  format setting 5-9
Outline command 12-6 to 12-8
  default settings C-2
Outline fonts
  print feature 7-6
Outline In key 12-8, 12-9
Outline Out key 12-8 to 12-10
Output document
  merge command 13-13, 13-15
Overbar
  print feature 7-6
Overlays
  printing 7-3 to 7-5
Overprinting 7-8
Overwrite mode 2-8, 2-9
  and glossary feature 12-13

P

Page
  resuming print at top 7-22, 7-23
Page and chapter number
  printing together 8-9
Page breaks 5-16, 8-8
  chapter 8-9
  conditional 5-18
  deleting 5-19
  hard 5-18
  merge command 13-13
  moving between 5-19, 6-3
  setting 6-3
Page counter 5-19
  versus page number 6-3
Page format 5-1 to 5-20, 5-22
  formula 5-12
  samples 5-13
Page key 3-2, 6-3
  conditional page option 5-18
  go to page option 5-19
  hard page break option 5-18
Page length
  format setting 5-10
Page numbers 8-8 to 8-13
  footers 8-8
  index entries 13-6, 13-7
  moving to in document 3-2
  printed versus displayed 6-3
  printing even only 6-2
  printing odd only 6-2
  printing range of 6-2
  setting to specific number 8-10 to 8-13
  sheet feeder printing range of 6-5
  style 8-9 to 8-13
  table of contents 13-10
  titles 8-4, 8-5
  to use with print command 6-3
Page orientation
  landscape 2-12
Page overlays
  number of lines allowed 1-9
  printing 7-3 to 7-5
Page position
  cursor 2-5
Paginate command 5-16, 5-19, 5-22
  availability embedded text screen 1-9
  default settings C-2
  footnotes and 8-2
  print command 6-3
  printing 5-17
  responsibilities of 6-3
  soft page breaks 5-17, 6-3
Pair kerning 5-13
Palette command 11-6
  initialization file H-11, H-12
Paper
  continuous 6-2
  single sheets 6-2
Paper trays
  selecting specific 6-4, 6-5
  sheet feeders 6-4
Paragraph markers
  embedded text screens 1-9
Paragraph symbol
  printing 7-11
Passwords
  cut and paste commands 9-3
  protection 16-2
Paste command 9-1 to 9-4
  default settings C-2
  embedded text entries 1-9
  input document name 9-2, 9-3
  temporary file 14-5
PC terminals
  kind of color used H-5
Percentage
  Math key 12-5
Period leader tabs 4-2, 4-8
Personal dictionary 9-7, 9-9, 15-1, 15-5
  mode option 11-4
Playback key 12-2
Points
  unit of measurement 5-3
Portrait orientation 5-14
PostScript
  Courier typeface 7-2, 7-11
  font family print samples F-1 to F-6
  font substitution laser printers B-2

image file importing 14-6 to 14-8
image file validity 14-7
number of lines allowed 1-9
postioning: absolute and relative 14-11
printer built-in extended characters 7-11, 7-12
printing programs from AlphaWRITE 14-10
programming with the Embed key 14-8 to 14-12
programs as .IMG files 14-12
Preview command 5-5, 6-8, 6-9
embedded text 1-9
footers 8-8
footnotes 8-3
titles 8-5
Previous Match key
search command 9-4
Previous Page feature 3-2
Previous Screen key 3-2
help screens 1-3
Previous Screen key (shifted) 3-2
Previous Sentence feature 3-3
Previous Word key 3-2
(shifted) 3-3
Print command 6-1 to 6-8
default settings C-3
embedded text screens 1-10
index generation 13-6
paginate command 6-3
paginating 5-16, 5-17
reformat option 11-5
responsibilities of 6-3
soft page breaks 5-17
table of contents generation 13-9
Print features
availability on printers E-1, E-2
Print files
extensions 14-4
Printer definition file
printers defined by 6-3
Printer name
format setting 5-10
Printers
availability during print 6-3
font substitution B-1 to B-3
maximum number xix
PostScript compatible 14-8
sheet feeders 6-2, 6-4, 6-5
Printing
chapter numbers 8-8 to 8-13
choosing next file 6-5, 6-6
directory listings 10-2, 10-3, 10-5
features 7-1 to 7-23
one page at a time 6-2
page numbers 8-8 to 8-13
page numbers # or £ characters 8-8
resume top of page 7-22, 7-23
Printwheel 7-2, 7-3
Professional dictionary 15-1, 15-2, 15-4, H-6
creating 15-5 to 15-8
displaying words 9-7
mode option 11-4
Programming
PostScript 14-8 to 14-12
Proportional command
default for mode command 11-7
Proportional display fonts
mode command 11-6, 11-9
Protected documents
copy command 10-6
erasing 10-5
Protection
schemes 16-1, 16-2
Protection field
Document Header 5-10
Prototype documents 2-12
DEFDOC default 2-1 to 2-3
INDEX.WRT 13-4, 13-6
TOC.WRT 13-9, 13-10
PRTDEF.INI
central printer definition file H-3
Publishing features xx

Q

Quarter fraction symbol
printing 7-11
Queue command 6-3, 6-5 to 6-8
default settings C-3
font option 7-2
Quick dictionary 15-1, 15-2
mode option 11-3, 11-4
Quit command (Editing Menu)
availability embedded text display 1-9
exiting documents 2-11
Quit command (Main Menu)
exit AlphaWRITE 1-1, 1-2
return to AMOS 1-1

R

Random House Concise Dictionary 15-1, H-5
Rearranging text 3-4, 3-5
Record key 12-1 to 12-3
Recovery procedures
journal files 14-1 to 14-4
Reformat command
default for mode command 11-7
Reformat for best output
mode option 11-5
Registered symbol
printing 7-11
Rename command 10-7
Replace command 9-4, 9-5
automatic formattings 5-21
capitalization 11-2
interrupting 9-6
marked text 3-5
Replacement data list
merge command 13-11
Required space 7-9
Resident font B-3
Resident fonts H-8
Resume print
top of page 7-22, 7-23
Return key
command screens 1-6
embedded text screens 1-9
when to use 1-5
wraparound 2-9
Reverse
print feature 7-6
Reverse Case key 3-4
Reverse Character key 3-4
Ribbon color
selecting 7-8
Right Arrow key 3-2
command screens 1-6
Right Arrow key (shifted) 3-2
Right justify
discretionary hyphens 7-5
format setting 5-10
Right justify tabs 4-7
Right margin 5-4
Roman numerals
numbering style 8-10
Rows
adding numbers 12-5
Rubout key 2-10, 3-3

Ruler line
  text display 2-5

S

Sample documents 2-12
Sample page formats 5-13
Save command 2-2, 2-11
  and journal file 2-11
  availability embedded text display 1-9
Scan key 3-2
Screen display modes 11-1 to 11-9
  changing width of 3-1
  moving 3-1, 3-2
Screen displays
  using 1-5 to 1-7
Screen Left key 3-1
Screen Right key 3-2
Screen symbols
  turning off/on display 7-12
Screened
  print feature 7-6
Search command 9-4
  capitalization 11-2
  interrupting 9-6
  marked text 3-5
  restarting 9-4
Search path
  GLOSS.WRT 12-11
Search paths
  DEFDOC prototype document 2-3, 5-3
  dictionaries 15-1
  initialization file H-2, H-3
Searchfold command
  default for mode command 11-7
Section symbol
  printing 7-11
Security
  documents 16-1, 16-2
Selection criteria
  directory command 10-2 to 10-4
Sheet feeders 6-2, 6-4, 6-5
Shift Down Arrow key
  turn off symbol display 7-12
SHORT.DCT dictionary 15-1, 15-3
SMALL.DCT dictionary 15-1 to 15-3, H-5
  mode command 11-3, 11-4
Sony Series 35 files
  converting G-2
Sort command 13-1, 13-2
  availability embedded text screens 1-9
  column marks 3-6
  default settings C-3
  selecting text 13-2
  temporary file 14-5
Source file
  professional dictionary 15-6
Space before footnotes
  format setting 5-10, 5-11, 8-2
Spacebar 3-5
  columns of text 4-5
  decimal tabs 4-8
Special Character key
  availability in Courier 7-2
  built-in extended characters 7-11, 7-12
  Courier typeface 7-11
Spell command 9-7 to 9-10
  automatic formatting 5-21
  column marks 3-6
  dictionaries 15-1 to 15-5
  marked text 3-5
  quick dictionary 11-3, 11-4
  verb dictionary 11-4
SPELL.DCT dictionary 15-1, 15-2, 15-4, H-5
  mode command 11-4
Split-line pagination 5-17
Standard dictionary 15-1, 15-2
  displaying words 9-7
  list 10-2
  mode option 11-4
Standard protection 16-2
Star symbol
  printing 7-11
Status line
  text display 2-7
Strikeout
  print feature 7-6
Style
  numbering 8-9 to 8-13
Style key 7-6 to 7-8
  blank spaces 3-5
  font command H-7
  gray shading and set gray 7-7
  typeface option 6-8, 7-1, 7-2, F-1 to F-6
Subscripting 7-9
Subtraction
  Math key 12-5
Superscripting 7-9
  for footnotes 8-2
SuperVUE conversions G-8
  converting files G-2
Symbol typeface F-2, F-5, F-6
Symbols
  printing 7-10, 7-11
System date 12-4
System level features xix

T

Table of contents 13-7 to 13-10
  temporary file 14-5
Tabs
  center 4-8
  clearing all 4-2
  clearing special 4-4
  collapsed text and 4-5
  columns of text 4-5, 4-7
  correspondence to printed page 4-5
  decimal 4-8
  deleting at Document Margin Screen 4-2
  flush left 4-7
  flush right 4-7
  how to set 4-2
  kinds available 4-2
  outlining 12-9
  period leader 4-8
  setting and using 4-1 to 4-7
  text alignment with 3-5
  using 4-4
TEMP document name
  cut command 9-1 to 9-3
  paste command 9-2
  TEMP.WRT file 14-5
Template document
  merge command 13-10, 13-11
Temporary files
  created by AlphaWRITE 14-5
Terminal support xix
  AMIGOS-compatible 6-8, 6-9
  display limitations 3-5, 4-5, 4-6
  display settings 11-5, 11-6, 11-8, 11-9
  display setttings 11-7
  display width 3-1
  keys for features A-1 to A-6
Text
  aligning on tab 3-5, 4-4
  alphabetizing 13-1, 13-2
  collapsing for tabs 4-5

Text *(continued)*
columns 4-5, 4-7
copying between documents 9-1 to 9-4
creating non-printing 2-10
deleting 3-3
entering to document 2-8
erasing 2-10, 3-3
finding, replacing document 9-4
indenting 4-5
inserting 3-4
marking 3-5, 3-6
rearranging 3-4, 3-5
substituting with replace command 9-5
wraparound feature 2-9
Text display 2-4
color used 11-9
moving to Editing Menu 1-6
Text length
format setting 5-11
Time
inserting with Glossary key 12-10
Titles 8-3 to 8-5
importing images 8-5
length format setting 5-11
number of lines 1-9
title length format setting 8-4
typeface and typesize 8-5
Toc command 13-7 to 13-9
availability embedded text screens 1-9
default settings C-3
Toc entries
number of lines allowed 1-9
TOC.WRT 13-9, 13-10
sample document 2-12
Top margin
format setting 5-5, 5-11, 8-4
Track kerning 5-13
Trademark symbol
printing 7-11
Two-character code
Glossary key 12-10
TXTFMT files
converting G-2
Type-ahead 1-3, 1-4
write command and document name 1-2
Typeface
default for Footers 8-7
default for Titles 8-5
samples F-1 to F-6
setting 7-1 to 7-3
substitution B-1 to B-3
user-defined 7-2
Typesize
default for footers 8-7
default for titles 8-5
setting 7-1 to 7-3

U

Under key 7-5
Underline 7-5
Underscore
display 11-5, 11-8
displayattribute command H-7
Undo feature 3-3, 3-4
restrictions 3-3
Units of measurement 5-3, 5-4
conversion tables 5-12
Universal key sequences A-1 to A-6
used in glossary entries 12-13
Up Arrow key 3-2
command screens 1-5, 1-6
screen displays 1-5
(shifted) 3-5
User name
inserting with Glossary key 12-10
User-defined features 7-2
Layout key 7-9

V

Variable names
merge data document 13-11, 13-12
merge template document 13-11
Verb dictionary 15-2, 15-4
displaying words 9-7
VERB.DCT dictionary 15-1
mode command 11-4

W

Width command 3-1, 11-7, 11-8
default settings C-3
Wildcards
WRTDIR 10-4
Word Delete key 3-3
Word Insert key 3-4
Word insert mode 3-4
Word processor xvii
Word spacing
format setting 5-11
Word wrap
footers 8-7
titles 8-5
WordPerfect files
converting G-2, G-4
Words
deleting 3-3
moving to next 3-2
moving to previous 3-2
Worksheets, AlphaCALC
importing to document 14-5, 14-6
Wraparound feature 2-9
Write command 1-1
journaling feature 14-2
options available 1-2
WRITE.INI
initialization file H-1, H-2
WRITE.NEW
initialization file H-1
WRTDIR command 10-4, 10-5