

DECLARATION OF PERFORMANCE

No. 008CPR06-06-2014

NEOLITH 10+

1. Product type for identification:

Dry-pressed ceramic tiles, with water absorption $E_b \le 0.5\%$

Intended use:

For internal and external wall/ceiling finishes and floorings.

3. Manufacturer:

THESIZE Surfaces, S.L. P.I. Camí Fondo, Supoi 8.

C/ Dels Ibers 31, 12550, Almassora (Castellón), Spain.

4. Systems of assessment and verification of constancy of performance (AVPC)

System 3 & 4.

5. Name and identification number of notified laboratory:

Instituto de Tecnología Cerámica, notified laboratory number 1605 has performed the testing for the determination of the emission of hazardous substances (lead and cadmium), subject to the system 3 and issued the test reports no. C121942, C121943 and C121944 dated 5th of July 2012.

6. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A2-s1, d0	
Release of dangerous substance, for:		
- Cadmium	< 0,0007 mg·dm ⁻²	
- Lead	< 0,007 mg·dm ⁻²	
Breaking strength	> 3000 N	
Slipperiness:		EN 14411:2012
Static coefficient of friction - wet	0,43 - 0,67	
- dry	0,76 - 0,94	
Thermal shock resistance	Pass	
Durability for:		
- internal use	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in

Signed for and on behalf of the manufacturer by:

Jacco Jurrisen, Quality Manager.

Factory and main office P.J. Cami Fondo, Supoi 8 C/ dels lbers, 31 12550 Almassora Castellón (Spain)

T. +34 964 652 233 F.+34 964 652 209

info@thesize.es

