

## **DECLARATION OF PERFORMANCE**

No. 012CPR06-06-2014

## **NEOLITH 5+3**

Product type for identification:

Dry-pressed ceramic tiles, with water absorption  $E_b \le 0.5\%$ 

Intended use:

For internal and external wall/ceiling finishes and floorings.

3. Manufacturer:

THESIZE Surfaces, S.L. P.I. Camí Fondo, Supoi 8.

C/ Dels Ibers 31, 12550, Almassora (Castellón), Spain.

 Systems of assessment and verification of constancy of performance (AVPC)

System 3 & 4.

5. Name and identification number of notified laboratory:

Instituto de Tecnología Cerámica, notified laboratory number 1605 has performed the testing for the determination of the emission of hazardous substances (lead and cadmium), subject to system 3 and issued the tests reports no. C140268 through C140285 dated 26<sup>th</sup> of February 2014.

## 6. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A2-s1, d0	
Release of dangerous substance, for:		
- Cadmium	< 0,001 mg·dm <sup>-2</sup>	
- Lead	< 0,01 mg·dm <sup>-2</sup>	
Breaking strength	> 2500 N	
Slipperiness:		
Static coefficient of friction - wet	0,43 - 0,67	EN 14411:2012
- dry	0,76 – 0,94	8
Bond strength/adhesion	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Jacco Jurrisen, Quality Manager.

Almassora, June 2014.

Factory and main office P.I. Cami Fondo, Supoi 8 C/ dels Ibers, 31 12550 Almassora Castellón (Spain) T. +34 964 652 233 F. +34 964 652 209

info@thesize.es www.thesize.es



PI. CAMI FONDO, SUPOI 8, C/ DEL IBERS Nº 31 C.P. 12550 ALMAZORA (CASTELLÓN)