CleanNotes

Visual styles and quick reference

First name Last name

Choose a box by its appearance. Titles, colours and content are yours to choose. Every box uses the same three optional arguments:

```
\begin {accentbox}[Title][docblue][extra options]
Content ...  \end {accentbox}
```

Omit the options for the defaults. Use `[]` for an empty title.

The six visual styles

Lorem ipsum. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

`accentbox` — Soft background, coloured left border, inline title.

Lorem ipsum

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

$$a^2 + b^2 = c^2$$

`framedbox` — Thin outline, separate tinted title bar.

Box 1 · *Lorem ipsum*

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

`numberedbox` — Automatic number; supports `\label` and `\ref`.

Lorem ipsum

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut enim ad minim veniam.

`cardbox` — Smaller type and padding, title on its own line.

Lorem ipsum

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

`solidbox` — Solid colour with white text.

Lorem ipsum Dolor sit amet

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

`splitbox` — Two heading fields; start the body with `\rightheading {Right text}`.

Colours and custom variants

Lorem ipsum. Lorem ipsum dolor sit amet.

```
\begin {accentbox}[Title.][alertred]
```

Lorem ipsum. Lorem ipsum dolor sit amet.

```
\begin {accentbox}[Title.][leafgreen]
```

Available colours: `docblue`, `tiporange`, `alertred`, `leafgreen`, `slategray` and `softgray`. Any named xcolor colour also works.

Define a reusable variant once in the preamble:

```
\newaccentbox {custombox}{leafgreen}{Lorem ipsum.}
```

Lorem ipsum. Lorem ipsum dolor sit amet, consectetur adipiscing elit.

Then use `\begin {custombox} ... \end {custombox}`. It accepts the same three optional arguments as the built-in boxes. For a one-off adjustment, use the third argument:

```
\begin {accentbox}[Title.][docblue][colback=white]
```

Other built-in commands

Command	Purpose or output
`\documentsetup {title={...},author={...}}`	Title-block and PDF metadata.
`\makedocumenthead`	Compact title block, as on page 1.
`\newaccentbox {name}{colour}{Title.}`	Define an accent-box variant.
`\rightheading {Right text}`	Right heading inside `splitbox`.
`\begin {steps} ... \end {steps}`	Labelled steps: `\item [Label] Content.`
`\step {Lorem}`	**Lorem** ipsum dolor sit amet.
`\reason {lorem ipsum}`	In maths: $x = 2$ lorem ipsum.
`\begin {proof} ... \end {proof}`	Standard proof with an ending square.

Lorem ipsum Dolor sit amet, consectetur adipiscing elit.

Dolor sit amet Ut enim ad minim veniam.

Proof. Lorem ipsum dolor sit amet, consectetur adipiscing elit. □

Language, layout and standard LaTeX

English is the default. In your project, change the package line in `preamble.tex` to `\usepackage [dutch]{cleannotes}` for Dutch labels and hyphenation. Command names stay the same. Your own titles and text remain yours to translate.

Other options: `[unnumbered]` for headings without numbers; `[onepager]` for landscape A4 with narrow margins and no running header/footer. Options combine: `[dutch,onepager]`. Content determines the page count.

Ready to use: `\section` , `\subsection` , `\tableofcontents` , `itemize`, `enumerate`, `equation`, `align`, `tabularx`, `figure`, `\includegraphics` , TikZ, `multicols`, `\href` and `\url` . Cross-reference: Box 1 via `\ref {box:lorem}`. See the preamble for optional plotting and bibliography packages.