

Technical drawing of the rear view of a wall box. The drawing shows a square outer frame with rounded corners (R10.1) and a central rectangular cutout. Two oval-shaped slots are positioned horizontally on either side of the center. A dashed circle indicates a recess for a box rim. Dimensions include a total width of 89.2 and a distance of 60 between screw holes. Callouts specify features like the insertion window, M4 slots, and a 45-degree seat for countersunk heads.

Annotations and dimensions:

- R10.1 (concentric to R4)
- Insertion window, travel 15 (hidden behind the device)
- 2x slot 5 x 11 for M4 recess Ø9, 3 deep, 45° seat for countersunk heads
- Recess for box rim Ø78 x 1.5 deep (back)
- 89.2
- 60 (screws)
- Section line A-A

Device: insert from the front, slide 15 mm down

Diagram illustrating a wedge-shaped device (shaded gray) placed on a rail. The device is tilted at an angle of 12° relative to the vertical. The base of the device is labeled 48. A dashed line indicates the device's position when it is slid 15 mm down the rail. A note states: "Device (dash-dot) is placed on the rail and slid 15 mm down." Another note points to the gap between the device and the rail: "5 mm air gap: vents stay free".

Project CO2 Wall Sensor	Title Wall plate and desk stand	Material PETG (or PLA)	Scale 1:1
Author Tobias Schneider	General tolerance ISO 2768-m	Date 2026-10-10	Format A3
Units mm	Projection ISO-E (first angle)	Source generate_enclosure.py	Sheet 2 / 2
Generated from the parametric Fusion model. Verify placeholder dimensions (SCD41 board) before printing.			