

(/).

Curriculum

SE Foundations

Average: 108.76%

# 0x05. AirBnB clone - RESTful API

- Python
- Back-end
- API
- Webserver
- Flask

By: Guillaume, CTO at Holberton School
Weight: 2
Project to be done in teams of 2 people (your team: Baraka Ngaira, Trevor Jey)
Project over - took place from <u>Sep 28, 2023 6:00 AM</u> to <u>Oct 3, 2023 6:00 AM</u>
<input checked="" type="checkbox"/> An auto review will be launched at the deadline

## In a nutshell...

- **Auto QA review:** 127.1/267 mandatory & 4.25/52 optional
- **Altogether: 51.49%**
  - Mandatory: 47.6%
  - Optional: 8.17%
  - Calculation: 47.6% + (47.6% \* 8.17%) == **51.49%**

## Concepts

For this project, we expect you to look at these concepts:

- [REST API \(/concepts/45\)](#)
- [AirBnB clone \(/concepts/74\)](#)

## Resources

Read or watch:

- **REST API** concept page
- [Learn REST: A RESTful Tutorial \(/rltoken/rycjU2GvZAlahHa61WWDBg\)](#)
- [Designing a RESTful API with Python and Flask \(/rltoken/WfKwKtaROCybta0\\_E849AQ\)](#)
- [HTTP access control \(CORS\) \(/rltoken/D55IFF8lgZDLPyIX6b6C5A\)](#)
- [Flask cheatsheet \(/rltoken/L01qANfgx0al8\\_an4mtPuw\)](#)
- [What are Flask Blueprints, exactly? \(/rltoken/QxbV8TCzNI3oP9br8CV5Lw\)](#)
- [Flask \(/rltoken/OLWDI7iDVpWKykekaznWpQ\)](#)
- [Modular Applications with Blueprints \(/rltoken/y3Lhj6w1g59MA\\_HPtc578w\)](#)
- [Flask tests \(/rltoken/UGo4ArPFHhx-ow2QtZWILA\)](#)
- [Flask-CORS \(/rltoken/vq8ER3xb99-N2anC-zke3A\)](#)

## Learning Objectives

At the end of this project, you are expected to be able to [explain to anyone \(/rltoken/5ySNbjsNA0dTL8YhhgtFog\)](#), **without the help of Google**:

### General

- What REST means
- What API means
- What CORS means
- What is an API
- What is a REST API
- What are other type of APIs
- Which is the HTTP method to retrieve resource(s)
- Which is the HTTP method to create a resource
- Which is the HTTP method to update resource
- Which is the HTTP method to delete resource
- How to request REST API



# Copyright - Plagiarism

- You are tasked to come up with solutions for the tasks below yourself to meet with the above learning objectives.
- You will not be able to meet the objectives of this or any following project by copying and pasting someone else’s work.
- You are not allowed to publish any content of this project.
- Any form of plagiarism is strictly forbidden and will result in removal from the program.

## Requirements

### Python Scripts

- Allowed editors: `vi` , `vim` , `emacs`
- All your files will be interpreted/compiled on Ubuntu 20.04 LTS using `python3` (version 3.4.3)
- All your files should end with a new line
- The first line of all your files should be exactly `#!/usr/bin/python3`
- A `README.md` file, at the root of the folder of the project, is mandatory
- Your code should use the `PEP 8` style (version 1.7)
- All your files must be executable
- The length of your files will be tested using `wc`
- All your modules should have documentation ( `python3 -c 'print(__import__("my_module").__doc__)'` )
- All your classes should have documentation ( `python3 -c 'print(__import__("my_module").MyClass.__doc__)'` )
- All your functions (inside and outside a class) should have documentation ( `python3 -c 'print(__import__("my_module").my_function.__doc__)'` and `python3 -c 'print(__import__("my_module").MyClass.my_function.__doc__)'` )
- A documentation is not a simple word, it’s a real sentence explaining what’s the purpose of the module, class or method (the length of it will be verified)


### Python Unit Tests

- Allowed editors: `vi` , `vim` , `emacs`
- All your files should end with a new line
- All your test files should be inside a folder `tests`
- You have to use the [unittest module \(/rltoken/5BK144LjyD8OKE1QdRdSBw\)](#).
- All your test files should be python files (extension: `.py` )
- All your test files and folders should start by `test_`
- Your file organization in the tests folder should be the same as your project: ex: for `models/base_model.py` , unit tests must be in: `tests/test_models/test_base_model.py`
- All your tests should be executed by using this command: `python3 -m unittest discover tests`
- You can also test file by file by using this command: `python3 -m unittest tests/test_models/test_base_model.py`
- We strongly encourage you to work together on test cases, so that you don’t miss any edge cases

## GitHub

There should be one project repository per group. If you clone/fork/whatever a project repository with the same name before the second deadline, you risk a 0% score.

## More Info



# Install Flask

```
$ pip3 install Flask
```

## Video library (2 total)

Search by title

Python: Flask RestAPI

AirBnB API

# Tasks

## 0. Restart from scratch!

mandatory

Score: 100.0% (Checks completed: 100.0%)

No no no! We are already too far in the project to restart everything.

But once again, let's work on a new codebase.

For this project you will fork this [codebase \(https://github.com/alexaorrico/AirBnB\\_clone\\_v2.git\)](https://github.com/alexaorrico/AirBnB_clone_v2.git):

- Update the repository name to `AirBnB_clone_v3`
- Update the `README.md` :
  - Add yourself as an author of the project
  - Add new information about your new contribution
  - Make it better!
- If you're the owner of this codebase, create a new repository called `AirBnB_clone_v3` and copy over all files from `AirBnB_clone_v2`

Repo:

- GitHub repository: `AirBnB_clone_v3`

☒ Done!

Help

Check your code

QA Review

## 1. Never fail!

mandatory

Score: 43.08% (Checks completed: 53.85%)





Since the beginning we’ve been using the `unittest` module, but do you know why `unittests` are so important? Because when you add a new feature, you refactor a piece of code, etc... you want to be sure you didn't break anything.

At Holberton, we have a lot of tests, and they all pass! Just for the Intranet itself, there are:

- 5,213 assertions *(as of 08/20/2018)*
- 13,061 assertions *(as of 01/25/2021)*

The following requirements **must** be met for your project:

- all current tests must pass (don't delete them...)
- add new tests as much as you can (tests are mandatory for some tasks)

```
guillaume@ubuntu:~/AirBnB_v3$ python3 -m unittest discover tests 2>&1 | tail -1
OK
guillaume@ubuntu:~/AirBnB_v3$ HBNB_ENV=test HBNB_MYSQL_USER=hbnb_test HBNB_MYSQL_PWD=hbnb_test_pwd
HBNB_MYSQL_HOST=localhost HBNB_MYSQL_DB=hbnb_test_db HBNB_TYPE_STORAGE=db python3 -m unittest discover tests 2>&1 /dev/null
| tail -n 1
OK
guillaume@ubuntu:~/AirBnB_v3$
```

Repo:

- GitHub repository: AirBnB\_clone\_v3

☐ Done?

Help

Check your code

Ask for a new correction

Get a sandbox

QA Review

2. Improve storage

mandatory

Score: 100.0% *(Checks completed: 100.0%)*

Update `DBStorage` and `FileStorage` ,adding two new methods. **All changes should be done in the branch `storage_get_count`** :

A method to retrieve one object:

- Prototype: `def get(self, cls, id):`
  - `cls`: class
  - `id` : string representing the object ID
- Returns the object based on the class and its ID, or `None` if not found

A method to count the number of objects in storage:

- Prototype: `def count(self, cls=None):`
  - `cls` : class (optional)
- Returns the number of objects in storage matching the given class. If no class is passed, returns the count of all objects in storage.

Don't forget to add new tests for these 2 methods on each storage engine.



```
guillaume@ubuntu:~/AirBnB_v3$ cat test_get_count.py
#!/usr/bin/python3
""" Test .get() and .count() methods """

from models import storage
from models.state import State

print("All objects: {}".format(storage.count()))
print("State objects: {}".format(storage.count(State)))

first_state_id = list(storage.all(State).values())[0].id
print("First state: {}".format(storage.get(State, first_state_id)))

guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ HBNB_MYSQL_USER=hbnb_dev HBNB_MYSQL_PWD=hbnb_dev_pwd HBNB_MYSQL_HOST=localhost
HBNB_MYSQL_DB=hbnb_dev_db HBNB_TYPE_STORAGE=db ./test_get_count.py
All objects: 1013
State objects: 27
First state: [State] (f8d21261-3e79-4f5c-829a-99d7452cd73c) {'name': 'Colorado', 'updated_at': datetime.datetime(2017, 3, 25, 2, 17, 6), 'created_at': datetime.datetime(2017, 3, 25, 2, 17, 6), '_sa_instance_state': <sqlalchemy.orm.state.InstanceState object at 0x7fc0103a8e80>, 'id': 'f8d21261-3e79-4f5c-829a-99d7452cd73c'}
```

```
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ ./test_get_count.py
All objects: 19
State objects: 5
First state: [State] (af14c85b-172f-4474-8a30-d4ec21f9795e) {'updated_at': datetime.datetime(2017, 4, 13, 17, 10, 22, 378824), 'name': 'Arizona', 'id': 'af14c85b-172f-4474-8a30-d4ec21f9795e', 'created_at': datetime.datetime(2017, 4, 13, 17, 10, 22, 378763)}
```

```
guillaume@ubuntu:~/AirBnB_v3$
```

For this task, you **must** make a pull request on GitHub.com, and ask at least one of your peer to review and merge it.

- Repo:
- GitHub repository: AirBnB\_clone\_v3
  - File: models/engine/db\_storage.py, models/engine/file\_storage.py, tests/test\_models/test\_engine/test\_db\_storage.py, tests/test\_models/test\_engine/test\_file\_storage.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

3. Status of your API

mandatory

Score: 65.0% *(Checks completed: 100.0%)*

It's time to start your API!

Your first endpoint (route) will be to return the status of your API:

```
guillaume@ubuntu:~/AirBnB_v3$ HBNB_MYSQL_USER=hbnb_dev HBNB_MYSQL_PWD=hbnb_dev_pwd HBNB_MYSQL_HOST=localhost
HBNB_MYSQL_DB=hbnb_dev_db HBNB_TYPE_STORAGE=db HBNB_API_HOST=0.0.0.0 HBNB_API_PORT=5000 python3 -m api.v1.app
 * Running on http://0.0.0.0:5000/ (Press CTRL+C to quit)
...
```

In another terminal:

```
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/status
{
  "status": "OK"
}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET -s http://0.0.0.0:5000/api/v1/status -vvv 2>&1 | grep Content-Type
< Content-Type: application/json
guillaume@ubuntu:~/AirBnB_v3$
```

Magic right? (No need to have a pretty rendered output, it's a JSON, only the structure is important)

Ok, let starts:

- Create a folder `api` at the root of the project with an empty file `__init__.py`
- Create a folder `v1` inside `api` :
  - create an empty file `__init__.py`
  - create a file `app.py` :
    - create a variable `app` , instance of `Flask`
    - import `storage` from `models`
    - import `app_views` from `api.v1.views`
    - register the blueprint `app_views` to your Flask instance `app`
    - declare a method to handle `@app.teardown_appcontext` that calls `storage.close()`



- (/)

■ inside if \_\_name\_\_ == "\_\_main\_\_": ,run your Flask server (variable app ) with:

■ host = environment variable HBNB\_API\_HOST or 0.0.0.0 if not defined

■ port = environment variable HBNB\_API\_PORT or 5000 if not defined
- threaded=True
- Create a folder views inside v1 :

◦ create a file \_\_init\_\_.py :

■ import Blueprint from flask [doc \(/rltoken/y3Lhj6w1g59MA\\_HPtc578w\)](#)

■ create a variable app\_views which is an instance of Blueprint (url prefix must be /api/v1 )

■ wildcard import of everything in the package api.v1.views.index => PEP8 will complain about it, don't worry, it's normal and this file ( v1/views/\_\_init\_\_.py ) won't be check.

◦ create a file index.py

■ import app\_views from api.v1.views

■ create a route /status on the object app\_views that returns a JSON: "status": "OK" (see example)

- Repo:
- GitHub repository: AirBnB\_clone\_v3

• File: api/\_\_init\_\_.py, api/v1/\_\_init\_\_.py, api/v1/views/\_\_init\_\_.py, api/v1/views/index.py, api/v1/app.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

4. Some stats?

mandatory

Score: 65.0% (Checks completed: 100.0%)

- Create an endpoint that retrieves the number of each objects by type:
- In api/v1/views/index.py

• Route: /api/v1/stats

• You must use the newly added count() method from storage

```
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/stats
{
  "amenities": 47,
  "cities": 36,
  "places": 154,
  "reviews": 718,
  "states": 27,
  "users": 31
}
guillaume@ubuntu:~/AirBnB_v3$
```

(No need to have a pretty rendered output, it's a JSON, only the structure is important)


- Repo:
- GitHub repository: AirBnB\_clone\_v3

• File: api/v1/views/index.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

5. Not found

mandatory

Score: 65.0% (Checks completed: 100.0%)

Designers are really creative when they have to design a "404 page", a "Not found"... [34 brilliantly designed 404 error pages \(/rltoken/8NwELW0j77kZ1jTM6hJFhA\)](#)

Today it's different, because you won't use HTML and CSS, but JSON!

In api/v1/app.py , create a handler for 404 errors that returns a JSON-formatted 404 status code response. The content should be: "error": "Not found"





```
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/nop
{
  "error": "Not found"
}
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/nop -vvv
*   Trying 0.0.0.0...
* TCP_NODELAY set
* Connected to 0.0.0.0 (127.0.0.1) port 5000 (#0)
> GET /api/v1/nop HTTP/1.1
> Host: 0.0.0.0:5000
> User-Agent: curl/7.51.0
> Accept: */*
>
* HTTP 1.0, assume close after body
< HTTP/1.0 404 NOT FOUND
< Content-Type: application/json
< Content-Length: 27
< Server: Werkzeug/0.12.1 Python/3.4.3
< Date: Fri, 14 Apr 2017 23:43:24 GMT
<
{
  "error": "Not found"
}
guillaume@ubuntu:~/AirBnB_v3$
```

- Repo:
- GitHub repository: AirBnB\_clone\_v3
  - File: api/v1/app.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

6. State

mandatory

Score: 65.0% (*Checks completed: 100.0%*)

Create a new view for `State` objects that handles all default RESTful API actions:

- In the file `api/v1/views/states.py`
- You must use `to_dict()` to retrieve an object into a valid JSON
- Update `api/v1/views/__init__.py` to import this new file

Retrieves the list of all `State` objects: `GET /api/v1/states`

Retrieves a `State` object: `GET /api/v1/states/<state_id>`

- If the `state_id` is not linked to any `State` object, raise a `404` error

Deletes a `State` object:: `DELETE /api/v1/states/<state_id>`

- If the `state_id` is not linked to any `State` object, raise a `404` error
- Returns an empty dictionary with the status code `200`

Creates a `State` : `POST /api/v1/states`

- You must use `request.get_json` from Flask to transform the HTTP body request to a dictionary
- If the HTTP body request is not valid JSON, raise a `400` error with the message `Not a JSON`
- If the dictionary doesn't contain the key `name`, raise a `400` error with the message `Missing name`
- Returns the new `State` with the status code `201`

Updates a `State` object: `PUT /api/v1/states/<state_id>`

- If the `state_id` is not linked to any `State` object, raise a `404` error
- You must use `request.get_json` from Flask to transform the HTTP body request to a dictionary
- If the HTTP body request is not valid JSON, raise a `400` error with the message `Not a JSON`
- Update the `State` object with all key-value pairs of the dictionary.
- Ignore keys: `id`, `created_at` and `updated_at`
- Returns the `State` object with the status code `200`



```
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/states/
[{"id": "8f165686-c98d-46d9-87d9-d6059ade2d99", "name": "Louisiana", "created_at": "2017-04-14T00:00:02", "updated_at": "2017-04-14T00:00:02"}, {"id": "1a9c29c7-e39c-4840-b5f9-74310b34f269", "name": "Arizona", "created_at": "2017-04-14T16:21:42", "updated_at": "2017-04-14T16:21:42"}]
...
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/states/8f165686-c98d-46d9-87d9-d6059ade2d99
{"id": "8f165686-c98d-46d9-87d9-d6059ade2d99", "name": "Louisiana", "created_at": "2017-04-14T00:00:02", "updated_at": "2017-04-14T00:00:02"}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X POST http://0.0.0.0:5000/api/v1/states/ -H "Content-Type: application/json" -d '{"name": "California"}' -vvv
* Trying 0.0.0.0...
* TCP_NODELAY set
* Connected to 0.0.0.0 (127.0.0.1) port 5000 (#0)
> POST /api/v1/states/ HTTP/1.1
> Host: 0.0.0.0:5000
> User-Agent: curl/7.51.0
> Accept: */*
> Content-Type: application/json
> Content-Length: 22
>
* upload completely sent off: 22 out of 22 bytes
* HTTP 1.0, assume close after body
< HTTP/1.0 201 CREATED
< Content-Type: application/json
< Content-Length: 195
< Server: Werkzeug/0.12.1 Python/3.4.3
< Date: Sat, 15 Apr 2017 01:30:27 GMT
<
{"id": "feadaa73-9e4b-4514-905b-8253f36b46f6", "name": "California", "created_at": "2017-04-15T01:30:27.557877", "updated_at": "2017-04-15T01:30:27.558081"}
* Curl_http_done: called premature == 0
* Closing connection 0
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X PUT http://0.0.0.0:5000/api/v1/states/feadaa73-9e4b-4514-905b-8253f36b46f6 -H "Content-Type: application/json" -d '{"name": "California is so cool"}'
{"id": "feadaa73-9e4b-4514-905b-8253f36b46f6", "name": "California is so cool", "created_at": "2017-04-15T01:30:28", "updated_at": "2017-04-15T01:51:08.044996"}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/states/feadaa73-9e4b-4514-905b-8253f36b46f6
{"id": "feadaa73-9e4b-4514-905b-8253f36b46f6", "name": "California is so cool", "created_at": "2017-04-15T01:30:28", "updated_at": "2017-04-15T01:51:08"}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X DELETE http://0.0.0.0:5000/api/v1/states/feadaa73-9e4b-4514-905b-8253f36b46f6
{}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/states/feadaa73-9e4b-4514-905b-8253f36b46f6
```





```
{
  (/)error": "Not found"
}
guillaume@ubuntu:~/AirBnB_v3$
```

- Repo:
- GitHub repository: AirBnB\_clone\_v3
  - File: api/v1/views/states.py, api/v1/views/\_\_init\_\_.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

7. City

mandatory

Score: 4.81% (Checks completed: 7.41%)

Same as `State` , create a new view for `City` objects that handles all default RESTful API actions:

- In the file `api/v1/views/cities.py`
- You must use `to_dict()` to serialize an object into valid JSON
- Update `api/v1/views/__init__.py` to import this new file

Retrieves the list of all `City` objects of a `State` : `GET /api/v1/states/<state_id>/cities`

- If the `state_id` is not linked to any `State` object, raise a `404` error

Retrieves a `City` object.: `GET /api/v1/cities/<city_id>`

- If the `city_id` is not linked to any `City` object, raise a `404` error

Deletes a `City` object: `DELETE /api/v1/cities/<city_id>`

- If the `city_id` is not linked to any `City` object, raise a `404` error
- Returns an empty dictionary with the status code `200`

Creates a `City` : `POST /api/v1/states/<state_id>/cities`

- You must use `request.get_json` from Flask to transform the HTTP body request to a dictionary
- If the `state_id` is not linked to any `State` object, raise a `404` error
- If the HTTP body request is not a valid JSON, raise a `400` error with the message `Not a JSON`
- If the dictionary doesn't contain the key `name` , raise a `400` error with the message `Missing name`
- Returns the new `City` with the status code `201`

Updates a `City` object: `PUT /api/v1/cities/<city_id>`

- If the `city_id` is not linked to any `City` object, raise a `404` error
- You must use `request.get_json` from Flask to transform the HTTP body request to a dictionary
- If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
- Update the `City` object with all key-value pairs of the dictionary
- Ignore keys: `id` , `state_id` , `created_at` and `updated_at`
- Returns the `City` object with the status code `200`



```
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/states/not_an_id/cities/
{
  "error": "Not found"
}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/states/2b9a4627-8a9e-4f32-a752-9a84fa7f4efd/cities
[
  {
    "__class__": "City",
    "created_at": "2017-03-25T02:17:06",
    "id": "1da255c0-f023-4779-8134-2b1b40f87683",
    "name": "New Orleans",
    "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
    "updated_at": "2017-03-25T02:17:06"
  },
  {
    "__class__": "City",
    "created_at": "2017-03-25T02:17:06",
    "id": "45903748-fa39-4cd0-8a0b-c62bfe471702",
    "name": "Lafayette",
    "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
    "updated_at": "2017-03-25T02:17:06"
  },
  {
    "__class__": "City",
    "created_at": "2017-03-25T02:17:06",
    "id": "e4e40a6e-59ff-4b4f-ab72-d6d100201588",
    "name": "Baton rouge",
    "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
    "updated_at": "2017-03-25T02:17:06"
  }
]
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/cities/1da255c0-f023-4779-8134-2b1b40f87683
{
  "__class__": "City",
  "created_at": "2017-03-25T02:17:06",
  "id": "1da255c0-f023-4779-8134-2b1b40f87683",
  "name": "New Orleans",
  "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
  "updated_at": "2017-03-25T02:17:06"
}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X POST http://0.0.0.0:5000/api/v1/states/2b9a4627-8a9e-4f32-a752-9a84fa7f4efd/cities -H
"Content-Type: application/json" -d '{"name": "Alexandria"}' -vvv
* Trying 0.0.0.0...
* TCP_NODELAY set
* Connected to 0.0.0.0 (127.0.0.1) port 5000 (#0)
> POST /api/v1/states/2b9a4627-8a9e-4f32-a752-9a84fa7f4efd/cities/ HTTP/1.1
> Host: 0.0.0.0:5000
> User-Agent: curl/7.51.0
> Accept: */*
> Content-Type: application/json
> Content-Length: 22
>
* upload completely sent off: 22 out of 22 bytes
* HTTP 1.0, assume close after body
< HTTP/1.0 201 CREATED
< Content-Type: application/json
< Content-Length: 249
< Server: Werkzeug/0.12.1 Python/3.4.3
< Date: Sun, 16 Apr 2017 03:14:05 GMT
<
{
  "__class__": "City",
  "created_at": "2017-04-16T03:14:05.655490",
  "id": "b75ae104-a8a3-475e-bf74-ab0a066ca2af",
  "name": "Alexandria",
  "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
  "updated_at": "2017-04-16T03:14:05.655748"
}
* Curl_http_done: called premature == 0
* Closing connection 0
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X PUT http://0.0.0.0:5000/api/v1/cities/b75ae104-a8a3-475e-bf74-ab0a066ca2af -H
"Content-Type: application/json" -d '{"name": "Bossier City"}'
{
  "__class__": "City",
  "created_at": "2017-04-16T03:14:06",
  "id": "b75ae104-a8a3-475e-bf74-ab0a066ca2af",
```



```
"name": "Bossier City",
("state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
"updated_at": "2017-04-16T03:15:12.895894"
}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/cities/b75ae104-a8a3-475e-bf74-ab0a066ca2af
{
  "__class__": "City",
  "created_at": "2017-04-16T03:14:06",
  "id": "b75ae104-a8a3-475e-bf74-ab0a066ca2af",
  "name": "Bossier City",
  "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
  "updated_at": "2017-04-16T03:15:13"
}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X DELETE http://0.0.0.0:5000/api/v1/cities/b75ae104-a8a3-475e-bf74-ab0a066ca2af
{}
guillaume@ubuntu:~/AirBnB_v3$
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/cities/b75ae104-a8a3-475e-bf74-ab0a066ca2af
{
  "error": "Not found"
}
guillaume@ubuntu:~/AirBnB_v3$
```


- Repo:
- GitHub repository: AirBnB\_clone\_v3
  - File: api/v1/views/cities.py, api/v1/views/\_\_init\_\_.py

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

8. Amenity

mandatory

Score: 65.0% (Checks completed: 100.0%)

Create a new view for `Amenity` objects that handles all default RESTful API actions:

- In the file `api/v1/views/amenities.py`
- You must use `to_dict()` to serialize an object into valid JSON
- Update `api/v1/views/__init__.py` to import this new file

Retrieves the list of all `Amenity` objects: `GET /api/v1/amenities`

Retrieves a `Amenity` object: `GET /api/v1/amenities/<amenity_id>`

- If the `amenity_id` is not linked to any `Amenity` object, raise a `404` error

Deletes a `Amenity` object: `DELETE /api/v1/amenities/<amenity_id>`

- If the `amenity_id` is not linked to any `Amenity` object, raise a `404` error
- Returns an empty dictionary with the status code `200`

Creates a `Amenity` : `POST /api/v1/amenities`

- You must use `request.get_json` from Flask to transform the HTTP request to a dictionary
- If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
- If the dictionary doesn't contain the key `name`, raise a `400` error with the message `Missing name`
- Returns the new `Amenity` with the status code `201`

Updates a `Amenity` object: `PUT /api/v1/amenities/<amenity_id>`

- If the `amenity_id` is not linked to any `Amenity` object, raise a `404` error
- You must use `request.get_json` from Flask to transform the HTTP request to a dictionary
- If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
- Update the `Amenity` object with all key-value pairs of the dictionary
- Ignore keys: `id`, `created_at` and `updated_at`
- Returns the `Amenity` object with the status code `200`

- Repo:
- GitHub repository: AirBnB\_clone\_v3
  - File: api/v1/views/amenities.py, api/v1/views/\_\_init\_\_.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review



9. User

(/)

mandatory

Score: 65.0% (*Checks completed: 100.0%*)

Create a new view for `User` object that handles all default RESTful API actions:

- In the file `api/v1/views/users.py`
- You must use `to_dict()` to retrieve an object into a valid JSON
- Update `api/v1/views/__init__.py` to import this new file

Retrieves the list of all `User` objects: `GET /api/v1/users`

Retrieves a `User` object: `GET /api/v1/users/<user_id>`

- If the `user_id` is not linked to any `User` object, raise a `404` error

Deletes a `User` object: `DELETE /api/v1/users/<user_id>`

- If the `user_id` is not linked to any `User` object, raise a `404` error
- Returns an empty dictionary with the status code `200`

Creates a `User` : `POST /api/v1/users`

- You must use `request.get_json` from Flask to transform the HTTP body request to a dictionary
- If the HTTP body request is not valid JSON, raise a `400` error with the message `Not a JSON`
- If the dictionary doesn't contain the key `email`, raise a `400` error with the message `Missing email`
- If the dictionary doesn't contain the key `password`, raise a `400` error with the message `Missing password`
- Returns the new `User` with the status code `201`

Updates a `User` object: `PUT /api/v1/users/<user_id>`

- If the `user_id` is not linked to any `User` object, raise a `404` error
- You must use `request.get_json` from Flask to transform the HTTP body request to a dictionary
- If the HTTP body request is not valid JSON, raise a `400` error with the message `Not a JSON`
- Update the `User` object with all key-value pairs of the dictionary
- Ignore keys: `id`, `email`, `created_at` and `updated_at`
- Returns the `User` object with the status code `200`

Repo:

- GitHub repository: `AirBnB_clone_v3`
- File: `api/v1/views/users.py`, `api/v1/views/__init__.py`

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

10. Place

mandatory

Score: 4.48% (*Checks completed: 6.9%*)

Create a new view for `Place` objects that handles all default RESTful API actions:

- In the file `api/v1/views/places.py`
- You must use `to_dict()` to retrieve an object into a valid JSON
- Update `api/v1/views/__init__.py` to import this new file

Retrieves the list of all `Place` objects of a `City` : `GET /api/v1/cities/<city_id>/places`

- If the `city_id` is not linked to any `City` object, raise a `404` error

Retrieves a `Place` object.: `GET /api/v1/places/<place_id>`

- If the `place_id` is not linked to any `Place` object, raise a `404` error

Deletes a `Place` object: `DELETE /api/v1/places/<place_id>`

- If the `place_id` is not linked to any `Place` object, raise a `404` error
- Returns an empty dictionary with the status code `200`

Creates a `Place` : `POST /api/v1/cities/<city_id>/places`

- You must use `request.get_json` from Flask to transform the HTTP request to a dictionary
- If the `city_id` is not linked to any `City` object, raise a `404` error
- If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
- If the dictionary doesn't contain the key `user_id`, raise a `400` error with the message `Missing user_id`
- If the `user_id` is not linked to any `User` object, raise a `404` error
- If the dictionary doesn't contain the key `name`, raise a `400` error with the message `Missing name`
- Returns the new `Place` with the status code `201`

Updates a `Place` object: `PUT /api/v1/places/<place_id>`

- If the `place_id` is not linked to any `Place` object, raise a `404` error



- You must use `request.get_json` from Flask to transform the HTTP request to a dictionary
  - (4) If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
  - Update the `Place` object with all key-value pairs of the dictionary
- Ignore keys: `id`, `user_id`, `city_id`, `created_at` and `updated_at`
  - Returns the `Place` object with the status code `200`

Repo:


- GitHub repository: `AirBnB_clone_v3`
- File: `api/v1/views/places.py`, `api/v1/views/__init__.py`

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

11. Reviews

mandatory

Score: 0.0% (Checks completed: 0.0%)

Create a new view for `Review` object that handles all default RESTful API actions:

- In the file `api/v1/views/places_reviews.py`
- You must use `to_dict()` to retrieve an object into valid JSON
- Update `api/v1/views/__init__.py` to import this new file

Retrieves the list of all `Review` objects of a `Place` : `GET /api/v1/places/<place_id>/reviews`

- If the `place_id` is not linked to any `Place` object, raise a `404` error

Retrieves a `Review` object.: `GET /api/v1/reviews/<review_id>`

- If the `review_id` is not linked to any `Review` object, raise a `404` error

Deletes a `Review` object: `DELETE /api/v1/reviews/<review_id>`

- If the `review_id` is not linked to any `Review` object, raise a `404` error
- Returns an empty dictionary with the status code `200`

Creates a `Review` : `POST /api/v1/places/<place_id>/reviews`

- You must use `request.get_json` from Flask to transform the HTTP request to a dictionary
- If the `place_id` is not linked to any `Place` object, raise a `404` error
- If the HTTP body request is not valid JSON, raise a `400` error with the message `Not a JSON`
- If the dictionary doesn't contain the key `user_id`, raise a `400` error with the message `Missing user_id`
- If the `user_id` is not linked to any `User` object, raise a `404` error
- If the dictionary doesn't contain the key `text`, raise a `400` error with the message `Missing text`
- Returns the new `Review` with the status code `201`

Updates a `Review` object: `PUT /api/v1/reviews/<review_id>`

- If the `review_id` is not linked to any `Review` object, raise a `404` error
- You must use `request.get_json` from Flask to transform the HTTP request to a dictionary
- If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
- Update the `Review` object with all key-value pairs of the dictionary
- Ignore keys: `id`, `user_id`, `place_id`, `created_at` and `updated_at`
- Returns the `Review` object with the status code `200`

Repo:


- GitHub repository: `AirBnB_clone_v3`
- File: `api/v1/views/places_reviews.py`, `api/v1/views/__init__.py`

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

12. HTTP access control (CORS)

mandatory

Score: 65.0% (Checks completed: 100.0%)

A resource makes a cross-origin HTTP request when it requests a resource from a different domain, or port, than the one the first resource itself serves.

Read the full definition [here \(/rltoken/D55lFF8lgZDLPyIX6b6C5A\)](#)

Why do we need this?

Because you will soon start allowing a web client to make requests your API. If your API doesn't have a correct CORS setup, your web client won't be able to access your data.

With Flask, it's really easy, you will use the class `CORS` of the module `flask_cors`.



How to install it: `$ pip3 install flask_cors`

Update `api/v1/app.py` to create a `CORS` instance allowing: `/*` for `0.0.0.0`

You will update it later when you will deploy your API to production.

Now you can see this HTTP Response Header: `< Access-Control-Allow-Origin: 0.0.0.0`

```
guillaume@ubuntu:~/AirBnB_v3$ curl -X GET http://0.0.0.0:5000/api/v1/cities/1da255c0-f023-4779-8134-2b1b40f87683 -vvv
*   Trying 0.0.0.0...
* TCP_NODELAY set
* Connected to 0.0.0.0 (127.0.0.1) port 5000 (#0)
> GET /api/v1/states/2b9a4627-8a9e-4f32-a752-9a84fa7f4efd/cities/1da255c0-f023-4779-8134-2b1b40f87683 HTTP/1.1
> Host: 0.0.0.0:5000
> User-Agent: curl/7.51.0
> Accept: */*
>
* HTTP 1.0, assume close after body
< HTTP/1.0 200 OK
< Content-Type: application/json
< Access-Control-Allow-Origin: 0.0.0.0
< Content-Length: 236
< Server: Werkzeug/0.12.1 Python/3.4.3
< Date: Sun, 16 Apr 2017 04:20:13 GMT
<
{
  "__class__": "City",
  "created_at": "2017-03-25T02:17:06",
  "id": "1da255c0-f023-4779-8134-2b1b40f87683",
  "name": "New Orleans",
  "state_id": "2b9a4627-8a9e-4f32-a752-9a84fa7f4efd",
  "updated_at": "2017-03-25T02:17:06"
}
* Curl_http_done: called premature == 0
* Closing connection 0
guillaume@ubuntu:~/AirBnB_v3$
```

- Repo:
- GitHub repository: `AirBnB_clone_v3`
  - File: `api/v1/app.py`

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

13. Place - Amenity

#advanced

Score: 0.0% *(Checks completed: 0.0%)*

Create a new view for the link between `Place` objects and `Amenity` objects that handles all default RESTful API actions:

- In the file `api/v1/views/places_amenities.py`
- You must use `to_dict()` to retrieve an object into a valid JSON
- Update `api/v1/views/__init__.py` to import this new file
- Depending of the storage:
  - `DBStorage` : list, create and delete `Amenity` objects from `amenities` relationship
  - `FileStorage` : list, add and remove `Amenity` ID in the list `amenity_ids` of a `Place` object

Retrieves the list of all `Amenity` objects of a `Place` : `GET /api/v1/places/<place_id>/amenities`

- If the `place_id` is not linked to any `Place` object, raise a `404` error

Deletes a `Amenity` object to a `Place` : `DELETE /api/v1/places/<place_id>/amenities/<amenity_id>`

- If the `place_id` is not linked to any `Place` object, raise a `404` error
- If the `amenity_id` is not linked to any `Amenity` object, raise a `404` error
- If the `Amenity` is not linked to the `Place` before the request, raise a `404` error
- Returns an empty dictionary with the status code `200`

Link a `Amenity` object to a `Place` : `POST /api/v1/places/<place_id>/amenities/<amenity_id>`

- No HTTP body needed
- If the `place_id` is not linked to any `Place` object, raise a `404` error
- If the `amenity_id` is not linked to any `Amenity` object, raise a `404` error
- If the `Amenity` is already linked to the `Place`, return the `Amenity` with the status code `200`
- Returns the `Amenity` with the status code `201`

- Repo:
- GitHub repository: `AirBnB_clone_v3`




- File: `api/v1/views/places_amenities.py`, `api/v1/views/__init__.py` (*/*)

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

14. Security improvements!

#advanced

Score: 11.11% (*Checks completed: 11.11%*)

Currently, the `User` object is designed to store the user password in cleartext.

It's super bad!

To avoid that, improve the `User` object:

- Update the method `to_dict()` of `BaseModel` to remove the `password` key **except when it's used by `FileStorage` to save data to disk**. Tips: default parameters
- Each time a new `User` object is created or password updated, the password is hashed to a MD5 (`/rltoken/OsGdHSsrf84F1ddiMgG5OQ`) value
- In the database for `DBStorage`, the password stored is now hashed to a MD5 value
- In the file for `FileStorage`, the password stored is now hashed to a MD5 value

Repo:


- GitHub repository: `AirBnB_clone_v3`
- File: `models/base_model.py`, `models/user.py`

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

15. Search

#advanced

Score: 14.13% (*Checks completed: 21.74%*)

For the moment, the only way to list `Place` objects is via `GET /api/v1/cities/<city_id>/places`.

Good, but not enough...

Update `api/v1/views/places.py` to add a new endpoint: `POST /api/v1/places_search` that retrieves all `Place` objects depending of the JSON in the body of the request.

The JSON can contain 3 optional keys:

- `states`: list of `State` ids
- `cities`: list of `City` ids
- `amenities`: list of `Amenity` ids

Search rules:

- If the HTTP request body is not valid JSON, raise a `400` error with the message `Not a JSON`
- If the JSON body is empty or each list of all keys are empty: retrieve all `Place` objects
- If `states` list is not empty, results should include all `Place` objects for each `State` id listed
- If `cities` list is not empty, results should include all `Place` objects for each `City` id listed
- Keys `states` and `cities` are inclusive. Search results should include all `Place` objects in storage related to each `City` in every `State` listed in `states`, plus every `City` listed individually in `cities`, *unless* that `City` was already included by `states`.
  - Context:
    - State A has 2 cities A1 and A2
    - State B has 3 cities B1, B2 and B3
    - A1 has 1 place
    - A2 has 2 places
    - B1 has 3 places
    - B2 has 4 places
    - B3 has 5 places
  - Search: `states = State A` and `cities = B2`
  - Result: all 4 places from the city B2 and the place from the city A1 and the 2 places of the city A2 (because they are part of State A) => 7 places returned
- If `amenities` list is not empty, limit search results to only `Place` objects having all `Amenity` ids listed
- The key `amenities` is exclusive, acting as a filter on the results generated by `states` and `cities`, or on all `Place` if `states` and `cities` are both empty or missing.
- Results will only include `Place` objects having all listed `amenities`. If a `Place` doesn't have even one of these `amenities`, it won't be retrieved.





```
guillaume@ubuntu:~/AirBnB_v3$ curl -X POST http://0.0.0.0:5000/api/v1/places_search -H "Content-Type: application/json" -d '{"states": ["2b9a4627-8a9e-4f32-a752-9a84fa7f4efd", "459e021a-e794-447d-9dd2-e03b7963f7d2"], "cities": ["5976f0e7-5c5f-4949-aae0-90d68fd239c0"]}'
```

```
[
  {
    "__class__": "Place",
    "created_at": "2017-03-25T02:17:06",
    "id": "dacec983-cec4-4f68-bd7f-af9068a305f5",
    "name": "The Lynn House",
    "city_id": "5976f0e7-5c5f-4949-aae0-90d68fd239c0",
    "user_id": "3ea61b06-e22a-459b-bb96-d900fb8f843a",
    "description": "Our place is 2 blocks from Vista Park (Farmer's Market), Historic Warren Ballpark, and about 2 miles from Old Bisbee where there is shopping, dining, and site seeing. We offer continental breakfast. You get the quiet life with great mountain and garden views. This is a 100+ year old cozy home which has been on both the Garden and Home tours. You have access to whole house, except for 1 restricted area (She-Shack). Hosts are on site in a casita in the back from 8pm until 7am when we are in town.<BR /><BR />Our home has two bedrooms, one king and one queen. There are 2 bathrooms, 1 1950's soak tub with shower and 1 with shower only. Guests have access to the living/dining room area, and the kitchen (except for use of stove/oven). Each morning, coffee/tea, and muffins are ready for guests. A small frig is available in the dining room with water/juice and an area for guest items. 1 parking space is directly across the street.",
    "number_rooms": 2,
    "number_bathrooms": 2,
    "max_guest": 4,
    "price_by_night": 82,
    "latitude": 31.4141,
    "longitude": -109.879,
    "updated_at": "2017-03-25T02:17:06"
  },
  {
    "__class__": "Place",
    "created_at": "2017-03-25T12:17:06",
    "id": "85f979ad-a345-4190-9d1b-719bb3c642ba",
    "name": "Little blue House in New Orleans",
    "city_id": "1da255c0-f023-4779-8134-2b1b40f87683",
    "user_id": "44b3ab44-4798-4a3a-9f72-ee1eeace4b33",
    "description": "Nice place closed to Bourbon street.",
    "number_rooms": 1,
    "number_bathrooms": 1,
    "max_guest": 3,
    "price_by_night": 42,
    "latitude": 29.951065,
    "longitude": -90.071533,
    "updated_at": "2017-03-25T02:17:06"
  },
  ...
]
guillaume@ubuntu:~/AirBnB_v3$
```


- Repo:
- GitHub repository: AirBnB\_clone\_v3
  - File: api/v1/views/places.py

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

