(/)

Curriculum

SE Foundations Average: 108.76%



Python

Front-end

JavaScript

- By: Guillaume, CTO at Holberton School
- Weight: 2
- Project to be done in teams of 2 people (your team: Baraka Ngaira, Trevor Jey)
- **⇒** Project over took place from Oct 5, 2023 6:00 AM to Oct 9, 2023 6:00 AM
- ☑ Manual QA review was done by Onyejekwe philip on Oct 9, 2023 3:05 AM
- An auto review will be launched at the deadline

In a nutshell...

- Manual QA review: 116.3/117 mandatory & 63.0/63 optional
- Auto QA review: 6.0/6 mandatory
- Altogether: 198.86%
 - Mandatory: 99.43%
 - o Optional: 100.0%
 - o Calculation: 99.43% + (99.43% * 100.0%) == **198.86%**

Overall comment:

Good job

Concepts

For this project, we expect you to look at this concept:

• AirBnB clone (/concepts/74)





Resources

Read or watch:

- Selector (/rltoken/Bl2mJVVG07XCP6E8qtsQMg)
- Get and set content (/rltoken/oM3b0a0FGTy6AQ_UJ201Yw)
- Manipulate CSS classes (/rltoken/LL2uScQvjWnj2ZEx2CzxXw)
- Manipulate DOM elements (/rltoken/6JtTz9SaNX3AyVXht4tMYA)
- Document ready (/rltoken/1AbzN1nEfBKoSjB-9kjmrA)
- Introduction (/rltoken/OGDolOd0cdmwDJFJy4aw5w)
- GET & POST request (/rltoken/kmBzs QPD72Oz--Yk80JHw)
- HTTP access control (CORS) (/rltoken/tzqJx5SS5cF1BW_IAnXqqg)

Learning Objectives

At the end of this project, you are expected to be able to explain to anyone (/rltoken/_ii906pZ1sg8gkAF1dvsNQ), without the help of Google:

General

- How cool it is to request your own API
- How to modify an HTML element style
- How to get and update an HTML element content
- How to modify the DOM
- How to make a GET request with JQuery Ajax
- How to make a POST request with JQuery Ajax
- How to listen/bind to DOM events
- · How to listen/bind to user events

Copyright - Plagiarism

- You are tasked to come up with solutions for the tasks below yourself to meet with the above learning objectives.
- You will not be able to meet the objectives of this or any following project by copying and pasting someone else's work.
- You are not allowed to publish any content of this project.
- Any form of plagiarism is strictly forbidden and will result in removal from the program.

Requirements

General

- Allowed editors: vi, vim, emacs
- All your files will be interpreted on Chrome (version 57.0)
- · All your files should end with a new line
- A README.md file, at the root of the folder of the project, is mandatory
- Your code should be semistandard compliant with the flag --global \$: semistandard *.js --global \$

- All your JavaScript must be in the folder scripts
- (/). You must use JQuery version 3.x
 - You are not allowed to use var
 - HTML should not reload for each action: DOM manipulation, update values, fetch data...

GitHub

There should be one project repository per group. If you clone/fork/whatever a project repository with the same name before the second deadline, you risk a 0% score.

More Info

Import JQuery

```
<head>
     <script src="https://code.jquery.com/jquery-3.2.1.min.js"></script>
</head>
```

Before starting the project...

You will work on a codebase using Flasgger (/rltoken/VmGDpw_DCN16OJt_UoqsDQ), you will need to install it locally first before starting the RestAPI:

```
$ sudo apt-get install -y python3-lxml
$ sudo pip3 install flask_cors # if it was not installed yet
$ sudo pip3 install flasgger
```

If the RestAPI is not starting, please read the error message. Based on the(ses) error message(s), you will have to troubleshoot potential dependencies issues.

Here some solutions:

jsonschema **exception**

```
$ sudo pip3 uninstall -y jsonschema
$ sudo pip3 install jsonschema==3.0.1
```

No module named 'pathlib2'

```
$ sudo pip3 install pathlib2
```


Expose ports from your Vagrant

In your Vagrantfile, add this line for each port forwarded

```
# I expose the port 5001 of my vm to the port 5001 on my computer
config.vm.network :forwarded_port, guest: 5001, host: 5001
```

if you need to expose other ports, same line but you will need to replace the "guest port" (inside your vagrant) and your "host port" (outside your vagrant, used from your browser for example)

It's important in your project, to use the AirBnB API with the port 5001



Manual QA Review

It is your responsibility to request a review for this project from a peer before the project's deadline. If no peers have been reviewed, you should request a review from a TA or staff member.

Tasks

0. Last clone!

mandatory

Score: 100.0% (Checks completed: 100.0%)

A new codebase again? Yes!

For this project you will fork this codebase (/rltoken/18CpThAKqBP5uviO1DSSGw):

- Update the repository name to AirBnB_clone_v4
- Update the README.md:
 - Add yourself as an author of the project
 - Add new information about your new contribution
 - Make it better!

- If you're the owner of this codebase, create a new repository called AirBnB_clone_v4 and copy (/) over all files from AirBnB_clone_v3
 - If you didn't install Flasgger from the previous project, it's time! sudo pip3 install flasgger

GitHub repository: AirBnB_clone_v4

1. Cash only

mandatory

Score: 93.0% (Checks completed: 100.0%)

Write a script that starts a Flask web application:

- Based on web_flask,copy: web_flask/static, web_flask/templates/100-hbnb.html, web_flask/__init__.py and web_flask/100-hbnb.py into the web_dynamic folder
- Rename 100-hbnb.py to 0-hbnb.py
- Rename 100-hbnb.html to 0-hbnb.html
- Update 0-hbnb.py to replace the existing route to /0-hbnb/

If 100-hbnb.html is not present, use 8-hbnb.html instead

guillaume@ubuntu:~/AirBnB_v4\$ HBNB_MYSQL_USER=hbnb_dev HBNB_MYSQL_PWD=hbnb_dev_pwd HBNB_MYSQL_HOST=localhost HBNB_MYSQL_DB=hbnb_dev_db HBNB_TYPE_STORAGE=db python3 -m web_dynamic.0-hbnb

* Running on http://0.0.0.0:5000/ (Press CTRL+C to quit)

One problem now is the asset caching done by Flask.

To avoid that, you will add a guery string to each asset:

In 0-hbnb.py, add a variable cache_id to the render_template. The value of this variable must be an UUID(uuid.uuid4())

In 0-hbnb.html, add this variable cache_id as query string to each <link> tag URL

```
pwillaume@ubuntu:~/AirBnB_v4$ curl -s -XGET http://0.0.0.0:5000/0-hbnb/ | head -6

⟨!DOCTYPE HTML>

<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <link rel="stylesheet" type="text/css" href="../static/styles/4-common.css?e211c</pre>
9eb-7d17-4f12-85eb-4d50fa50cb1d" />
    <link rel="stylesheet" type="text/css" href="../static/styles/3-header.css?e211c</pre>
9eb-7d17-4f12-85eb-4d50fa50cb1d" />
guillaume@ubuntu:~/AirBnB_v4$ curl -s -XGET http://0.0.0.0:5000/0-hbnb/ | head -6
<!DOCTYPE HTML>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <link rel="stylesheet" type="text/css" href="../static/styles/4-common.css?f8344</pre>
13e-0aa9-4767-b64a-c92db9cb1f82" />
    <link rel="stylesheet" type="text/css" href="../static/styles/3-header.css?f8344</pre>
13e-0aa9-4767-b64a-c92db9cb1f82" />
guillaume@ubuntu:~/AirBnB_v4$
```

- GitHub repository: AirBnB_clone_v4
- Directory: web_dynamic
- File: 0-hbnb.py, templates/0-hbnb.html

☑ Done! Help >_ Get a sandbox QA Review

2. Select some Amenities to be comfortable!

mandatory

Score: 100.0% (Checks completed: 100.0%)

For the moment the filters section is static, let's make it dynamic!

Replace the route 0-hbnb with 1-hbnb in the file 1-hbnb.py (based on 0-hbnb.py)

Create a new template 1-hbnb.html (based on 0-hbnb.html) and update it:


- Import JQuery in the <head> tag
- Import the JavaScript static/scripts/1-hbnb.js in the <head> tag
 - In 1-hbnb.html and the following HTML files, add this variable cache_id as query string to the above <script> tag
- Add a <input type="checkbox"> tag to the li tag of each amenity
- The new checkbox must be at 10px on the left of the Amenity name
- Add to the input tags of each amenity (tag) the attribute data-id=":amenity_id" => this will allow us to retrieve the Amenity ID from the DOM


Add to the input tags of each amenity (tag) the attribute data-name=":amenity_name" =>
 this will allow us to retrieve the Amenity name from the DOM


Write a JavaScript script (static/scripts/1-hbnb.js):

- Your script must be executed only when DOM is loaded
- You must use JQuery
- Listen for changes on each input checkbox tag:
 - o if the checkbox is checked, you must store the Amenity ID in a variable (dictionary or list)
 - if the checkbox is unchecked, you must remove the Amenity ID from the variable
 - o update the h4 tag inside the div Amenities with the list of Amenities checked

As example:







- GitHub repository: AirBnB_clone_v4
- Directory: web_dynamic
- File: 1-hbnb.py, templates/1-hbnb.html, static/scripts/1-hbnb.js

☑ Done! Help >_ Get a sandbox QA Review

3. API status mandatory

Score: 100.0% (Checks completed: 100.0%)

Before requesting the HBNB API, it's better to know the status of this one.

Update the API entry point (api/v1/app.py) by replacing the current CORS cors(app, origins="0.0.0.0") by CORS(app, resources= $\{r''/api/v1/*'': \{"origins": "*"\}\}$).

Change the route 1-hbnb to 2-hbnb in the file 2-hbnb.py (based on 1-hbnb.py)

Create a new template 2-hbnb.html (based on 1-hbnb.html) and update it:

• Import the JavaScript static/scripts/2-hbnb.js in the <head> tag (instead of 1-hbnb.js)

- Add a new div element in the header tag:
 - Attribute ID should be api_status
 - Align to the right
 - Circle of 40px diameter



- (/)
- Center vertically
- At 30px of the right border
- Background color #cccccc
- Also add a class available for this new element in web_dynamic/static/styles/3-header.css:
 - Background color #ff545f


Write a JavaScript script (static/scripts/2-hbnb.js):


- Based on 1-hbnb.js
- Request http://0.0.0.0:5001/api/v1/status/:
 - If in the status is "OK", add the class available to the div#api_status
 - Otherwise, remove the class available to the div#api_status

To start the API in the port 5001:

guillaume@ubuntu:~/AirBnB_v4\$ HBNB_MYSQL_USER=hbnb_dev HBNB_MYSQL_PWD=hbnb_dev_pwd H
BNB_MYSQL_HOST=localhost HBNB_MYSQL_DB=hbnb_dev_db HBNB_TYPE_STORAGE=db HBNB_API_POR
T=5001 python3 -m api.v1.app
...

For example:





• GitHub repository: AirBnB_clone_v4

• File: api/v1/app.py, web_dynamic/2-hbnb.py, web_dynamic/templates/2-hbnb.html, web_dynamic/static/styles/3-header.css, web_dynamic/static/scripts/2-hbnb.js

☑ Done! Help >_ Get a sandbox QA Review

4. Fetch places

mandatory

Score: 100.0% (*Checks completed: 100.0%*)

Replace the route 2-hbnb with 3-hbnb in the file 3-hbnb.py (based on 2-hbnb.py)

Create a new template 3-hbnb.html (based on 2-hbnb.html) and update it:

- Import the JavaScript static/scripts/3-hbnb.js in the <head> tag (instead of 2-hbnb.js)
- Remove the entire Jinja section of displaying all places (all article tags)

Write a JavaScript script (static/scripts/3-hbnb.js):

- Based on 2-hbnb.js
- Request http://0.0.0.0:5001/api/v1/places_search/:
 - Description of this endpoint here (/rltoken/EkC2rNKurYlznWBiJYPtgA). If this endpoint is not available, you will have to add it to the API (you can work all together for creating this endpoint)
 - Send a POST request with Content-Type: application/json and an empty dictionary in the body - cURL version: curl "http://0.0.0.0:5001/api/v1/places_search" -XPOST -H "Content-Type: application/json" -d '{}'
 - Loop into the result of the request and create an article tag representing a Place in the section.places. (you can remove the Owner tag in the place description)

The final result must be the same as previously, but now, places are loaded from the front-end, not from the back-end!

Repo:

- GitHub repository: AirBnB_clone_v4
- File: web_dynamic/3-hbnb.py, web_dynamic/templates/3-hbnb.html, web_dynamic/static/scripts/3-hbnb.js

Q

5. Filter places by Amenity

mandatory

Score: 100.0% (Checks completed: 100.0%)

Replace the route 3-hbnb with 4-hbnb in the file 4-hbnb.py (based on 3-hbnb.py)
(/)

Create a new template 4-hbnb.html (based on 3-hbnb.html) and update it:

• Import the JavaScript static/scripts/4-hbnb.js in the <head> tag (instead of 3-hbnb.js)

Write a JavaScript script (static/scripts/4-hbnb.js):

- Based on 3-hbnb.js
- When the button tag is clicked, a new POST request to places_search should be made with the list of Amenities checked

Now you have the first filter implemented, enjoy!

Repo:

- GitHub repository: AirBnB_clone_v4
- File: web_dynamic/4-hbnb.py, web_dynamic/templates/4-hbnb.html, web_dynamic/static/scripts/4-hbnb.js

☑ Done! Help S— Get a sandbox QA Review

6. States and Cities

#advanced

Score: 100.0% (Checks completed: 100.0%)

Now, reproduce the same steps with the State and City filter:

Replace the route 4-hbnb to 100-hbnb in the file 100-hbnb.py (based on 4-hbnb.py)

Create a new template 100-hbnb.html (based on 4-hbnb.html) and update it:

- Import the JavaScript static/scripts/100-hbnb.js in the <head> tag (instead of 4-hbnb.js)
- Add to all li tags of each state a new tag: <input type="checkbox">
- Add to all li tags of each cities a new tag: <input type="checkbox">
- The new checkbox must be at 10px on the left of the State or City name
- Add to all input tags of each states (tag) the attribute data-id=":state_id"
- Add to all input tags of each states (tag) the attribute data-name=":state_name"
- Add to all input tags of each cities (tag) the attribute data-id=":city_id"
- Add to all input tags of each cities (tag) the attribute data-name=":city_name"

Write a JavaScript script (static/scripts/100-hbnb.js):

- Based on 4-hbnb.js
- Listen to changes on each input checkbox tag:
 - o if the checkbox is checked, you must store the State or City ID in a variable (dictionary or list)
 - if the checkbox is unchecked, you must remove the State or City ID from the variable
 - o update the h4 tag inside the div Locations with the list of States or Cities checked

• When the button tag is clicked, a new POST request to places_search should be made with the list of Amenities. Cities and States checked

Repo:

- GitHub repository: AirBnB_clone_v4
- File: web_dynamic/100-hbnb.py, web_dynamic/templates/100-hbnb.html, web_dynamic/static/scripts/100-hbnb.js

□ Done? Help	>_ Get a sandbox	QA Review
--------------	------------------	-----------

7. Reviews

#advanced

Score: 100.0% (Checks completed: 100.0%)

Let's add a new feature: show and hide reviews!

Replace the route 100-hbnb to 101-hbnb in the file 101-hbnb.py (based on 100-hbnb.py)

Create a new template 101-hbnb.html (based on 100-hbnb.html) and update it:

- Import the JavaScript static/scripts/101-hbnb.js in the <head> tag (instead of 101-hbnb.js)
- Design the list of reviews from this task (/rltoken/6QUObzD76iV79Sc0rFcAQQ)
- Add a span element at the right of the H2 "Reviews" with value "show" (add all necessary attributes to do this feature)

Write a JavaScript script (static/scripts/101-hbnb.js):

- Based on 100-hbnb.js
- When the span next to the Reviews h2 is clicked by the user:
 - Fetch, parse, display reviews and change the text to "hide"
 - o If the text is "hide": remove all Review elements from the DOM
 - This button should work like a toggle to fetch/display and hide reviews

Repo:

- GitHub repository: AirBnB_clone_v4
- File: web_dynamic/101-hbnb.py, web_dynamic/templates/101-hbnb.html, web_dynamic/static/scripts/101-hbnb.js

☐ Done?	Help	>_ Get a sandbox	QA Review
---------	------	------------------	-----------

Q

Ready for a new manual review

(/)

Copyright © 2024 ALX, All rights reserved.