

(/)



Curriculum

SE Foundations ^

Average: 108.76% v

0x0F. Python - Object-relational mapping

Python

OOP

SQL

MySQL

ORM

SQLAlchemy

By: Guillaume

Weight: 1

 Project over - took place from Aug 17, 2023 6:00 AM to Aug 21, 2023 6:00 AM☒ An auto review will be launched at the deadline

In a nutshell...

- **Auto QA review:** 98.0/165 mandatory & 0.0/32 optional
- **Altogether: 59.39%**
 - Mandatory: 59.39%
 - Optional: 0.0%
 - Calculation: $59.39\% + (59.39\% * 0.0\%) == 59.39\%$

Before you start...

Please make sure your MySQL server is in 8.0 -> How to install MySQL 8.0 in Ubuntu 20.04
(/rltoken/paGukker_0KoG3D9FqymNQ)

Background Context

In this project, you will link two amazing worlds: Databases and Python!

In the first part, you will use the module `MySQLdb` to connect to a MySQL database and execute your SQL queries.

In the second part, you will use the module `SQLAlchemy` (don't ask me how to pronounce it...) an Object Relational Mapper (ORM).



Help

The biggest difference is: no more SQL queries! Indeed, the purpose of an ORM is to abstract the storage to the usage. With an ORM, your biggest concern will be "What can I do with my objects" and not "How this object is stored? where? when?". You won't write any SQL queries only Python code. Last thing, your code won't be "storage type" dependent. You will be able to change your storage easily without re-writing your entire project.

Without ORM:

```
conn = MySQLdb.connect(host="localhost", port=3306, user="root", passwd="root", db="my_db", charset="utf8")
cur = conn.cursor()
cur.execute("SELECT * FROM states ORDER BY id ASC") # HERE I have to know SQL to grab all states in my database
query_rows = cur.fetchall()
for row in query_rows:
    print(row)
cur.close()
conn.close()
```

With an ORM:

```
engine = create_engine('mysql+mysqldb://{user}:{password}@localhost/{db}'.format("root", "root", "my_db"), pool_pre_ping=True)
Base.metadata.create_all(engine)

session = Session(engine)
for state in session.query(State).order_by(State.id).all(): # HERE: no SQL query, only objects!
    print("{}: {}".format(state.id, state.name))
session.close()
```

Do you see the difference? Cool, right?

The biggest difficulty with ORM is: The syntax!

Indeed, all of them have the same type of syntax, but not always. Please read tutorials and don't read the entire documentation before starting, just jump on it if you don't get something.

Resources

Read or watch:

- Object-relational mappers (/rltoken/a8DUOWhXpNX3TEwgyT-U8A)
- mysqlclient/MySQLdb documentation (/rltoken/JtFaKjnqxudr6Hi05Us1Lw) (*please don't pay attention to `_mysql`*)
- MySQLdb tutorial (/rltoken/TdUSYFNGbXJG1WjCEoq5FA)
- SQLAlchemy tutorial (/rltoken/YyL5hsscviNH04XGW-XpfA)
- SQLAlchemy (/rltoken/j9azWF2Db_2rNoITxOF3SA)
- mysqlclient/MySQLdb (/rltoken/0zLhY9KqKjn-zmdb7X598Q)
- Introduction to SQLAlchemy (/rltoken/pw50Bl1Bj84wksxm018dwA)
- Flask SQLAlchemy (/rltoken/B-xldMtGvpus8vHxAIRrPg)
- 10 common stumbling blocks for SQLAlchemy newbies (/rltoken/delzPMrfK8lxqm-AboFHWg)



- Python SQLAlchemy Cheatsheet (/rltoken/dZfUNK3IJicGMK5PU0bE7Q)
- (/). SQLAlchemy ORM Tutorial for Python Developers (/rltoken/hNxBKC8IHge5XjsRO8ksHQ) (**Warning:** *This tutorial is with PostgreSQL, but the concept of SQLAlchemy is the same with MySQL*)
- SQLAlchemy Tutorial (/rltoken/5G_R2NmQRFqiZb84qxYERQ)
- Python Virtual Environments: A primer (/rltoken/OXle6kXpmD88D0WbgbTWqg)

Learning Objectives

At the end of this project, you are expected to be able to explain to anyone (/rltoken/vPPdh3HKg3t23YFxUqHpFg), **without the help of Google:**

General

- Why Python programming is awesome
- How to connect to a MySQL database from a Python script
- How to `SELECT` rows in a MySQL table from a Python script
- How to `INSERT` rows in a MySQL table from a Python script
- What ORM means
- How to map a Python Class to a MySQL table
- How to create a Python Virtual Environment

Copyright - Plagiarism

- You are tasked to come up with solutions for the tasks below yourself to meet with the above learning objectives.
- You will not be able to meet the objectives of this or any following project by copying and pasting someone else's work.
- You are not allowed to publish any content of this project.
- Any form of plagiarism is strictly forbidden and will result in removal from the program.

Requirements

General

- Allowed editors: `vi`, `vim`, `emacs`
- All your files will be interpreted/compiled on Ubuntu 20.04 LTS using `python3` (version 3.8.5)
- Your files will be executed with `MySQLdb` version `2.0.x`
- Your files will be executed with `SQLAlchemy` version `1.4.x`
- All your files should end with a new line
- The first line of all your files should be exactly `#!/usr/bin/python3`
- A `README.md` file, at the root of the folder of the project, is mandatory
- Your code should use the `pycodestyle` (version `2.8.*`)
- All your files must be executable
- The length of your files will be tested using `wc`
- All your modules should have a documentation (`python3 -c 'print(__import__("my_module").__doc__)'`)



- All your classes should have a documentation (`python3 -c '(/)' print(__import__("my_module").MyClass.__doc__)'`)
- All your functions (inside and outside a class) should have a documentation (`python3 -c 'print(__import__("my_module").my_function.__doc__)'` and `python3 -c 'print(__import__("my_module").MyClass.my_function.__doc__)'`)
- A documentation is not a simple word, it's a real sentence explaining what's the purpose of the module, class or method (the length of it will be verified)
- You are not allowed to use `execute` with sqlalchemy

More Info

Install and activate venv

To create a Python Virtual Environment, allowing you to install specific dependencies for this python project, we will install venv:

```
$ sudo apt-get install python3.8-venv
$ python3 -m venv venv
$ source venv/bin/activate
```

Install MySQLdb module version 2.0.x

For installing MySQLdb , you need to have MySQL installed: [How to install MySQL 8.0 in Ubuntu 20.04 \(/rltoken/paGukker_0KoG3D9FqymNQ\)](#)

```
$ sudo apt-get install python3-dev
$ sudo apt-get install libmysqlclient-dev
$ sudo apt-get install zlib1g-dev
$ sudo pip3 install mysqlclient
...
$ python3
>>> import MySQLdb
>>> MySQLdb.version_info
(2, 0, 3, 'final', 0)
```

Install SQLAlchemy module version 1.4.x

```
$ sudo pip3 install SQLAlchemy
...
$ python3
>>> import sqlalchemy
>>> sqlalchemy.__version__
'1.4.22'
```



Also, you can have this warning message:

```
/usr/local/lib/python3.4/dist-packages/sqlalchemy/engine/default.py:552: Warning: (1681, "'@@SESSION.GTID_EXECUTED' is deprecated and will be removed in a future release.")
  cursor.execute(statement, parameters)
```

You can ignore it.

Tasks

0. Get all states

mandatory

Score: 100.0% (Checks completed: 100.0%)

Write a script that lists all states from the database `hbtn_0e_0_usa` :

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name` (no argument validation needed)
- You must use the module `MySQLdb` (`import MySQLdb`)
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Results must be sorted in ascending order by `states.id`
- Results must be displayed as they are in the example below
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql
-- Create states table in hbtn_0e_0_usa with some data
CREATE DATABASE IF NOT EXISTS hbtn_0e_0_usa;
USE hbtn_0e_0_usa;
CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");
```

```
guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./0-select_states.py root root hbtn_0e_0_usa
(1, 'California')
(2, 'Arizona')
(3, 'Texas')
(4, 'New York')
(5, 'Nevada')
guillaume@ubuntu:~/0x0F$
```



No test cases needed

(/)


Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 0-select_states.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

1. Filter states**mandatory**

Score: 100.0% (Checks completed: 100.0%)

Write a script that lists all states with a name starting with N (upper N) from the database

hbtn_0e_0_usa :

- Your script should take 3 arguments: mysql username , mysql password and database name (no argument validation needed)
- You must use the module MySQLdb (import MySQLdb)
- Your script should connect to a MySQL server running on localhost at port 3306
- Results must be sorted in ascending order by states.id
- Results must be displayed as they are in the example below
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql
-- Create states table in hbtn_0e_0_usa with some data
CREATE DATABASE IF NOT EXISTS hbtn_0e_0_usa;
USE hbtn_0e_0_usa;
CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./1-filter_states.py root root hbtn_0e_0_usa
(4, 'New York')
(5, 'Nevada')
guillaume@ubuntu:~/0x0F$
```

**No test cases needed**

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 1-filter_states.py

☒ Done!

Help

Check your code

> Get a sandbox

QA Review

2. Filter states by user input

mandatory

Score: 100.0% (Checks completed: 100.0%)

Write a script that takes in an argument and displays all values in the `states` table of `hbtn_0e_0_usa` where `name` matches the argument.

- Your script should take 4 arguments: `mysql username`, `mysql password`, `database name` and `state name searched` (no argument validation needed)
- You must use the module `MySQLdb` (`import MySQLdb`)
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- You must use `format` to create the SQL query with the user input
- Results must be sorted in ascending order by `states.id`
- Results must be displayed as they are in the example below
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql
-- Create states table in hbtn_0e_0_usa with some data
CREATE DATABASE IF NOT EXISTS hbtn_0e_0_usa;
USE hbtn_0e_0_usa;
CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./2-my_filter_states.py root root hbtn_0e_0_usa 'Arizona'
(2, 'Arizona')
```

No test cases needed**Repo:**


- GitHub repository: alx-higher_level_programming

- Directory: 0x0F-python-object_relational_mapping
- (/). File: 2-my_filter_states.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

3. SQL Injection...

mandatory

Score: 100.0% (Checks completed: 100.0%)

Wait, do you remember the previous task? Did you test "Arizona"; TRUNCATE TABLE states ; SELECT * FROM states WHERE name = '' as an input?

```
guillaume@ubuntu:~/0x0F$ ./2-my_filter_states.py root root hbtn_0e_0_usa "Arizona";
TRUNCATE TABLE states ; SELECT * FROM states WHERE name = ''
(2, 'Arizona')
guillaume@ubuntu:~/0x0F$ ./0-select_states.py root root hbtn_0e_0_usa
guillaume@ubuntu:~/0x0F$
```

What? Empty?

Yes, it's an SQL injection (/rltoken/qzLjdkHPTue2U1isMj5fJA) to delete all records of a table...

Once again, write a script that takes in arguments and displays all values in the states table of hbtn_0e_0_usa where name matches the argument. But this time, write one that is safe from MySQL injections!

- Your script should take 4 arguments: mysql username , mysql password , database name and state name searched (safe from MySQL injection)
- You must use the module MySQLdb (import MySQLdb)
- Your script should connect to a MySQL server running on localhost at port 3306
- Results must be sorted in ascending order by states.id
- Results must be displayed as they are in the example below
- Your code should not be executed when imported




```
guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql
-- Create states table in hbtn_0e_0_usa with some data

CREATE DATABASE IF NOT EXISTS hbtn_0e_0_usa;
USE hbtn_0e_0_usa;
CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

guillaume@ubuntu:~/0x0F$ cat 0-select_states.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./3-my_safe_filter_states.py root root hbtn_0e_0_usa 'Arizona'
(2, 'Arizona')
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 3-my_safe_filter_states.py

☒ Done![Help](#)[Check your code](#)[Get a sandbox](#)[QA Review](#)

4. Cities by states

mandatory

Score: 100.0% (Checks completed: 100.0%)

Write a script that lists all cities from the database hbtn_0e_4_usa

- Your script should take 3 arguments: mysql username, mysql password and database name
- You must use the module MySQLdb (import MySQLdb)
- Your script should connect to a MySQL server running on localhost at port 3306
- Results must be sorted in ascending order by cities.id
- You can use only execute() once
- Results must be displayed as they are in the example below
- Your code should not be executed when imported



```
guillaume@ubuntu:~/0x0F$ cat 4-cities_by_state.sql
-- Create states table in hbtn_0e_4_usa with some data
CREATE DATABASE IF NOT EXISTS hbtn_0e_4_usa;
USE hbtn_0e_4_usa;
CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

CREATE TABLE IF NOT EXISTS cities (
    id INT NOT NULL AUTO_INCREMENT,
    state_id INT NOT NULL,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id),
    FOREIGN KEY(state_id) REFERENCES states(id)
);
INSERT INTO cities (state_id, name) VALUES (1, "San Francisco"), (1, "San Jose"), (1, "Los Angeles"), (1, "Fremont"), (1, "Livermore");
INSERT INTO cities (state_id, name) VALUES (2, "Page"), (2, "Phoenix");
INSERT INTO cities (state_id, name) VALUES (3, "Dallas"), (3, "Houston"), (3, "Austin");
INSERT INTO cities (state_id, name) VALUES (4, "New York");
INSERT INTO cities (state_id, name) VALUES (5, "Las Vegas"), (5, "Reno"), (5, "Henderson"), (5, "Carson City");

guillaume@ubuntu:~/0x0F$ cat 4-cities_by_state.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./4-cities_by_state.py root root hbtn_0e_4_usa
(1, 'San Francisco', 'California')
(2, 'San Jose', 'California')
(3, 'Los Angeles', 'California')
(4, 'Fremont', 'California')
(5, 'Livermore', 'California')
(6, 'Page', 'Arizona')
(7, 'Phoenix', 'Arizona')
(8, 'Dallas', 'Texas')
(9, 'Houston', 'Texas')
(10, 'Austin', 'Texas')
(11, 'New York', 'New York')
(12, 'Las Vegas', 'Nevada')
(13, 'Reno', 'Nevada')
(14, 'Henderson', 'Nevada')
(15, 'Carson City', 'Nevada')
guillaume@ubuntu:~/0x0F$
```



No test cases needed


Repo:

- GitHub repository: alx-higher_level_programming
- (/). Directory: 0x0F-python-object_relational_mapping
- File: 4-cities_by_state.py

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

5. All cities by state

mandatory

Score: 100.0% (Checks completed: 100.0%)

Write a script that takes in the name of a state as an argument and lists all `cities` of that state, using the database `hbtn_0e_4_usa`

- Your script should take 4 arguments: `mysql username`, `mysql password`, `database name` and `state name` (SQL injection free!)
- You must use the module `MySQLdb` (`import MySQLdb`)
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Results must be sorted in ascending order by `cities.id`
- You can use only `execute()` once
- The results must be displayed as they are in the example below
- Your code should not be executed when imported



```
guillaume@ubuntu:~/0x0F$ cat 4-cities_by_state.sql
-- Create states table in hbtn_0e_4_usa with some data
CREATE DATABASE IF NOT EXISTS hbtn_0e_4_usa;
USE hbtn_0e_4_usa;
CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

CREATE TABLE IF NOT EXISTS cities (
    id INT NOT NULL AUTO_INCREMENT,
    state_id INT NOT NULL,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id),
    FOREIGN KEY(state_id) REFERENCES states(id)
);
INSERT INTO cities (state_id, name) VALUES (1, "San Francisco"), (1, "San Jose"), (1, "Los Angeles"), (1, "Fremont"), (1, "Livermore");
INSERT INTO cities (state_id, name) VALUES (2, "Page"), (2, "Phoenix");
INSERT INTO cities (state_id, name) VALUES (3, "Dallas"), (3, "Houston"), (3, "Austin");
INSERT INTO cities (state_id, name) VALUES (4, "New York");
INSERT INTO cities (state_id, name) VALUES (5, "Las Vegas"), (5, "Reno"), (5, "Henderson"), (5, "Carson City");

guillaume@ubuntu:~/0x0F$ ./5-filter_cities.py root root hbtn_0e_4_usa Texas

guillaume@ubuntu:~/0x0F$ cat 4-cities_by_state.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./5-filter_cities.py root root hbtn_0e_4_usa Texas
Dallas, Houston, Austin
guillaume@ubuntu:~/0x0F$ ./5-filter_cities.py root root hbtn_0e_4_usa Hawaii

guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 5-filter_cities.py

☒ Done![Help](#)[Check your code](#)[Get a sandbox](#)[QA Review](#)

6 First state model

mandatory

Score: 100.0% (Checks completed: 100.0%)



Write a python file that contains the class definition of a `State` and an instance `Base = declarative_base()`:

- `State` class:
 - inherits from `Base` Tips (/rltoken/SFKlwNZ3IG6_4TL6dEsluA)
 - links to the MySQL table `states`
 - class attribute `id` that represents a column of an auto-generated, unique integer, can't be null and is a primary key
 - class attribute `name` that represents a column of a string with maximum 128 characters and can't be null
- You must use the module `SQLAlchemy`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- **WARNING:** all classes who inherit from `Base` **must** be imported before calling `Base.metadata.create_all(engine)`



```
guillaume@ubuntu:~/0x0F$ cat 6-model_state.sql
-- Create database hbtn_0e_6_usa
CREATE DATABASE IF NOT EXISTS hbtn_0e_6_usa;
USE hbtn_0e_6_usa;
SHOW CREATE TABLE states;

guillaume@ubuntu:~/0x0F$ cat 6-model_state.sql | mysql -uroot -p
Enter password:
ERROR 1146 (42S02) at line 4: Table 'hbtn_0e_6_usa.states' doesn't exist
guillaume@ubuntu:~/0x0F$ cat 6-model_state.py
#!/usr/bin/python3
"""Start link class to table in database
"""
import sys
from model_state import Base, State

from sqlalchemy import (create_engine)

if __name__ == "__main__":
    engine = create_engine('mysql+mysqldb://{user}:{password}@localhost/{db}'.format(sys.argv[1],
sys.argv[2], sys.argv[3]), pool_pre_ping=True)
    Base.metadata.create_all(engine)

guillaume@ubuntu:~/0x0F$ ./6-model_state.py root root hbtn_0e_6_usa
guillaume@ubuntu:~/0x0F$ cat 6-model_state.sql | mysql -uroot -p
Enter password:
Table    Create Table
states  CREATE TABLE `states` (\n  `id` int(11) NOT NULL AUTO_INCREMENT,\n  `name` v
archar(128) NOT NULL,\n  PRIMARY KEY (`id`)\n) ENGINE=InnoDB DEFAULT CHARSET=latin1
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: model_state.py

☒ Done![Help](#)[Check your code](#)[Get a sandbox](#)[QA Review](#)

7. All states via SQLAlchemy

mandatory

Score: 100.0% (Checks completed: 100.0%)



Write a script that lists all `State` objects from the database `hbtn_0e_6_usa`

- Your script should take 3 arguments: `mysql` username, `mysql` password and database name

- You must use the module `SQLAlchemy`
- (/). You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Results must be sorted in ascending order by `states.id`
- The results must be displayed as they are in the example below
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ cat 7-model_state_fetch_all.sql
-- Insert states
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

guillaume@ubuntu:~/0x0F$ cat 7-model_state_fetch_all.sql | mysql -uroot -p hbtn_0e_6_usa
Enter password:
guillaume@ubuntu:~/0x0F$ ./7-model_state_fetch_all.py root root hbtn_0e_6_usa
1: California
2: Arizona
3: Texas
4: New York
5: Nevada
guillaume@ubuntu:~/0x0F$
```

No test cases needed


Repo:

- GitHub repository: `alx-higher_level_programming`
- Directory: `0x0F-python-object_relational_mapping`
- File: `7-model_state_fetch_all.py`

☒ Done!

Help

Check your code

 Get a sandbox

QA Review

8. First state

mandatory

Score: 100.0% (Checks completed: 100.0%)

Write a script that prints the first `State` object from the database `hbtn_0e_6_usa`

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name`
- You must use the module `SQLAlchemy`
- You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- The state you display must be the first in `states.id`
- You are not allowed to fetch all states from the database before displaying the result
- The results must be displayed as they are in the example below
- If the table `states` is empty, print `Nothing` followed by a new line



- Your code should not be executed when imported

(/)

```
guillaume@ubuntu:~/0x0F$ ./8-model_state_fetch_first.py root root hbtn_0e_6_usa
1: California
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 8-model_state_fetch_first.py

☒ Done!

Help

Check your code

> Get a sandbox

QA Review

9. Contains `a`

mandatory

Score: 0.0% (Checks completed: 0.0%)

Write a script that lists all `State` objects that contain the letter `a` from the database `hbtn_0e_6_usa`

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name`
- You must use the module `SQLAlchemy`
- You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Results must be sorted in ascending order by `states.id`
- The results must be displayed as they are in the example below
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ ./9-model_state_filter_a.py root root hbtn_0e_6_usa
1: California
2: Arizona
3: Texas
5: Nevada
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 9-model_state_filter_a.py




☒ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

10. Get a state

mandatory

Score: 0.0% (Checks completed: 0.0%)

Write a script that prints the `State` object with the `name` passed as argument from the database `hbtn_0e_6_usa`

- Your script should take 4 arguments: `mysql username`, `mysql password`, `database name` and `state name` to search (SQL injection free)
- You must use the module `SQLAlchemy`
- You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- You can assume you have one record with the state name to search
- Results must display the `states.id`
- If no state has the name you searched for, display `Not found`
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ ./10-model_state_my_get.py root root hbtn_0e_6_usa Texas
3
guillaume@ubuntu:~/0x0F$ ./10-model_state_my_get.py root root hbtn_0e_6_usa Illinois
Not found
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:


- GitHub repository: `alx-higher_level_programming`
- Directory: `0x0F-python-object_relational_mapping`
- File: `10-model_state_my_get.py`

☐ Done?

Help

Check your code

Ask for a new correction

 Get a sandbox

QA Review

11. Add a new state

mandatory

Score: 0.0% (Checks completed: 0.0%)



Write a script that adds the `State` object "Louisiana" to the database `hbtn_0e_6_usa`

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name`

- You must use the module `SQLAlchemy`
- (/). You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Print the new `states.id` after creation
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ ./11-model_state_insert.py root root hbtn_0e_6_usa
6
guillaume@ubuntu:~/0x0F$ ./7-model_state_fetch_all.py root root hbtn_0e_6_usa
1: California
2: Arizona
3: Texas
4: New York
5: Nevada
6: Louisiana
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: `alx-higher_level_programming`
- Directory: `0x0F-python-object_relational_mapping`
- File: `11-model_state_insert.py`

☐ Done?[Help](#)[Check your code](#)[Ask for a new correction](#)[Get a sandbox](#)[QA Review](#)

12. Update a state

mandatory

Score: 0.0% (Checks completed: 0.0%)

Write a script that changes the name of a `State` object from the database `hbtn_0e_6_usa`

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name`
- You must use the module `SQLAlchemy`
- You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Change the name of the `State` where `id = 2` to `New Mexico`
- Your code should not be executed when imported



```
guillaume@ubuntu:~/0x0F$ ./12-model_state_update_id_2.py root root hbtn_0e_6_usa
guillaume@ubuntu:~/0x0F$ ./7-model_state_fetch_all.py root root hbtn_0e_6_usa
1: California
2: New Mexico
3: Texas
4: New York
5: Nevada
6: Louisiana
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: 12-model_state_update_id_2.py

☐ Done?[Help](#)[Check your code](#)[Ask for a new correction](#)[Get a sandbox](#)[QA Review](#)

13. Delete states

mandatory

Score: 0.0% (Checks completed: 0.0%)

Write a script that deletes all `State` objects with a name containing the letter `a` from the database `hbtn_0e_6_usa`

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name`
- You must use the module `SQLAlchemy`
- You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Your code should not be executed when imported

```
guillaume@ubuntu:~/0x0F$ ./13-model_state_delete_a.py root root hbtn_0e_6_usa
guillaume@ubuntu:~/0x0F$ ./7-model_state_fetch_all.py root root hbtn_0e_6_usa
2: New Mexico
4: New York
guillaume@ubuntu:~/0x0F$
```

No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping



- File: 13-model_state_delete_a.py (/)

☐ Done?

Help

Check your code

Ask for a new correction

>_ Get a sandbox

QA Review

14. Cities in state

mandatory

Score: 0.0% (Checks completed: 0.0%)

Write a Python file similar to `model_state.py` named `model_city.py` that contains the class definition of a `City`.

- `City` class:
 - inherits from `Base` (imported from `model_state`)
 - links to the MySQL table `cities`
 - class attribute `id` that represents a column of an auto-generated, unique integer, can't be null and is a primary key
 - class attribute `name` that represents a column of a string of 128 characters and can't be null
 - class attribute `state_id` that represents a column of an integer, can't be null and is a foreign key to `states.id`
- You must use the module `SQLAlchemy`

Next, write a script `14-model_city_fetch_by_state.py` that prints all `City` objects from the database `hbtn_0e_14_usa`:

- Your script should take 3 arguments: `mysql username`, `mysql password` and `database name`
- You must use the module `SQLAlchemy`
- You must import `State` and `Base` from `model_state` - `from model_state import Base, State`
- Your script should connect to a MySQL server running on `localhost` at port `3306`
- Results must be sorted in ascending order by `cities.id`
- Results must be display as they are in the example below (`<state name>: (<city id>) <city name>`)
- Your code should not be executed when imported



```
guillaume@ubuntu:~/0x0F$ cat 14-model_city_fetch_by_state.sql
-- Create database hbtn_0e_14_usa, tables states and cities + some data
CREATE DATABASE IF NOT EXISTS hbtn_0e_14_usa;
USE hbtn_0e_14_usa;

CREATE TABLE IF NOT EXISTS states (
    id INT NOT NULL AUTO_INCREMENT,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id)
);
INSERT INTO states (name) VALUES ("California"), ("Arizona"), ("Texas"), ("New York"), ("Nevada");

CREATE TABLE IF NOT EXISTS cities (
    id INT NOT NULL AUTO_INCREMENT,
    state_id INT NOT NULL,
    name VARCHAR(256) NOT NULL,
    PRIMARY KEY (id),
    FOREIGN KEY(state_id) REFERENCES states(id)
);
INSERT INTO cities (state_id, name) VALUES (1, "San Francisco"), (1, "San Jose"), (1, "Los Angeles"), (1, "Fremont"), (1, "Livermore");
INSERT INTO cities (state_id, name) VALUES (2, "Page"), (2, "Phoenix");
INSERT INTO cities (state_id, name) VALUES (3, "Dallas"), (3, "Houston"), (3, "Austin");
INSERT INTO cities (state_id, name) VALUES (4, "New York");
INSERT INTO cities (state_id, name) VALUES (5, "Las Vegas"), (5, "Reno"), (5, "Henderson"), (5, "Carson City");

guillaume@ubuntu:~/0x0F$ cat 14-model_city_fetch_by_state.sql | mysql -uroot -p
Enter password:
guillaume@ubuntu:~/0x0F$ ./14-model_city_fetch_by_state.py root root hbtn_0e_14_usa
California: (1) San Francisco
California: (2) San Jose
California: (3) Los Angeles
California: (4) Fremont
California: (5) Livermore
Arizona: (6) Page
Arizona: (7) Phoenix
Texas: (8) Dallas
Texas: (9) Houston
Texas: (10) Austin
New York: (11) New York
Nevada: (12) Las Vegas
Nevada: (13) Reno
Nevada: (14) Henderson
Nevada: (15) Carson City
guillaume@ubuntu:~/0x0F$
```



No test cases needed

Repo:

- GitHub repository: alx-higher_level_programming
- Directory: 0x0F-python-object_relational_mapping
- File: model_city.py, 14-model_city_fetch_by_state.py

☐ Done?

Help

Check your code

Ask for a new correction

>_ Get a sandbox

QA Review

Done with the mandatory tasks? Unlock 3 advanced tasks now!

Copyright © 2024 ALX, All rights reserved.

