Robust autonomous landing of fixed-wing UAVs in wind

Tobias Fridén

Half time report

14/11 - 2019

Problem description

Research questions:

1. How can sampling-based motion planning techniques be used to generate landing sequences for fixed-wing UAVs?
2. How can safe landings be guaranteed when taking wind effects into account?

Scope



Figure 1: Components of a general autonomous system

Kinematic model

$$\dot{x}_N = \cos\psi + \cos \tag{1}$$

$$\dot{y}_E = \sin\psi + \sin \tag{2}$$

$$\dot{\psi} = \frac{g}{}\tan\phi \tag{3}$$

$$\dot{\phi} = f_\phi(\phi - \phi^c) \tag{4}$$

Straight path following in wind



Figure 2: Coordinate frame for straight path following

Straight path following in wind (contd)

$$\dot{d} \equiv \dot{p}_{E,s} = \sin(\psi - \psi_s) + \sin(-\psi_s) \tag{5}$$

$$\dot{\psi} = \frac{g}{} \tan\phi \tag{6}$$

$d \approx 0$, $\dot{d} \approx 0$ means that $\sin(\psi - \psi_s) + \sin(-\psi_s) = 0$ so

$$\equiv -\arcsin\left(\sin(-\psi_s)\right) + \psi_s \tag{7}$$

Trajectory following controller



Figure 3: L_1 controller logic

Trajectory following controller (contd)

$$= \begin{bmatrix} \cos\psi \\ \sin\psi \end{bmatrix} + \begin{bmatrix} \cos \\ \sin \end{bmatrix} \tag{8}$$

$$a^c = 2\frac{V^2}{L_1}\sin\eta, \quad V = \|\| \tag{9}$$

$$\phi^c = \tan^{-1}(a^c/g) \tag{10}$$

State and action set definitions

$$x = (x_N, y_E, \psi) \tag{11}$$

$$u = (p_{N,g}, p_{E,g}) \tag{12}$$

Closed loop system

(**??**) + (**??**) $\Rightarrow$

$$\dot{\psi} = \frac{a^c(x,u)}{} \tag{13}$$

Physical constraint: $\dot{\psi} \leq \dot{\psi}_{\mathsf{max}} \Rightarrow$

$$\underline{\dot{\psi}}(x,u) = \begin{cases} a^c(x,u)/ & |a^c(x,u)/| \leq \dot{\psi}_{\mathsf{max}} \\ \mathrm{sgn}(a^c(x,u)/)\dot{\psi}_{\mathsf{max}} & \text{otherwise} \end{cases} \tag{14}$$

Closed loop system (contd)

$$\dot{x} = f(x, u) = \begin{bmatrix} \cos\psi + \cos \\ \sin\psi + \sin \\ \underline{\dot{\psi}}(x, u) \end{bmatrix} \tag{15}$$

Motion primitives

- Different motion primitives for different wind direction
- Different motion primitives for different wind speeds

Motion primitives (contd)

Constraints on final course instead of heading where course is defined as

$$\psi_c(x) = \tan^{-1}\left(\frac{\sin\psi + \sin}{\cos\psi + \cos}\right) \tag{16}$$

Optimal control problem

$$
\begin{aligned}
\min_{x(t),u,T} \quad & J = |d(x(T),u)|^2 + |\psi_c(x(T)) - \psi_d|^2 + \int_0^T dt && \text{(17a)} \\
\text{subject to} \quad & \psi(0) = && \text{(17b)} \\
& \psi_c(x(0)) = 0, \quad |\psi_c(x(T)) - \psi_d| \leq \Delta\psi_{\min} && \text{(17c)} \\
& \dot{x} = f(x(t), u) && \text{(17d)} \\
& x(t) \in && \text{(17e)} \\
& u \in && \text{(17f)}
\end{aligned}
$$

Optimal control problem (contd)



Figure 4: J for $= 14$ m/s, $= 5$ m/s, $= 0°$, $\psi_d = 90°$

Optimal control problem (contd)

Derivative free optimization methods

$$\min_{x \in \mathbb{R}^n} \quad f : x \to \mathbb{R} \tag{18a}$$

$$\text{subject to} \quad x \in_{feasible} \tag{18b}$$

$$\tag{18c}$$

Mesh-Adaptive Direct Search (MADS)

Resulting primitives



(a) $= 0^\circ$ (b) $= 80^\circ$

Figure 5: Motion primitives for different wind directions, $= 5$ m/s

Heuristic function

- States defined in inertial frame
- Cost is distance travelled by UAV in air-relative frame
- Not equal to inertial frame distance if $\neq 0$

Cost for straight line paths

Assuming that $\psi_i = \psi_f =:$

$$V_{\|} = \cos\psi_s(\cos + \cos) + \sin\psi_s(\sin + \sin) \tag{19}$$

$$s_A = \frac{}{V_{\|}} \|\boldsymbol{p}_{i+1} - \boldsymbol{p}_i\| \tag{20}$$

Cost for arbitrary initial and final heading

- Dubin's path if $= 0$
- No analytical solution if $\neq 0$
- Numerical solutions exist but computationally expensive

Heuristic Look-Up Table

- Entries for different values of ψ_i from 0° to 180°
- Different require new HLUT
- Generated with Dijkstra's Algorithm using motion primitives

Heuristic Look-Up Table (contd)



Figure 6: Projection of queries on HLUT

Heuristic Look-Up Table (contd)



Figure 7: HLUT for $\psi_f = 0^\circ$

Landing sequences



Figure 8: Landing sequence definition

Landing sequences (contd)

- Approach: Descend at rate $\dot{h}$ given by $\boldsymbol{p}_A$ and $\boldsymbol{p}_L$
- Flare: When below altitude , begin descending at fixed rate
- Has to enter landing area above altitude h_A

Optimal landing sequence

Objectives:

1. Land as closely to the center of as possible
2. Land against the wind if possible

Optimal landing sequence (contd)



Figure 9: Variables to determine optimal landing sequence

Optimal landing sequence (contd)

Divided into two steps:

1. Determine ψ_L
2. Determine $R_a = \|\boldsymbol{p}_A - \boldsymbol{p}_2\|$ and $R_l = \|\boldsymbol{p}_L - \boldsymbol{p}_2\|$

Determining approach direction

$$V_L(\psi) = \cos\psi(\cos + \cos) + \sin\psi(\sin + \sin) \tag{21}$$

$$R_{\min}(\psi) = V_L(\psi)\frac{h_A -}{\dot{h}_{\max}} \tag{22}$$

$$R_{flare}(\psi) = V_L(\psi) \tag{23}$$

Determining approach direction (contd)

$L(\psi)$: Line from $\boldsymbol{p}_1$ in direction $\psi + 180^\circ$ with length K for some $K \geq 0$

$$\{\psi_L\}_{feas} = \{\psi : (R(\psi) \geq R_{\min}(\psi) + R_{flare}(\psi)) \cap (L(\psi) \notin)\} \quad (24)$$

$$\psi_{L,opt} = \underset{\psi \in \{\psi_L\}_{feas}}{\arg\min} \; R(\psi) \quad (25)$$

Determining approach parameters

$$\dot{h} = f(R_a, R_l) \tag{26}$$

$$h(R) = h_0 - R\frac{\dot{h}}{V_L} \tag{27}$$

$$R_c = \|\boldsymbol{p_1} - \boldsymbol{p}_2\| \tag{28}$$

Determining approach parameters (contd)

Constraints:

$$h(R_a - 2R_c) \geq h_A \tag{29}$$

$$h(R_a - R_{flare} - R_l) = \tag{30}$$

Determining approach parameters (contd)

$$
\begin{aligned}
\min_{R_a, R_l} \quad & J = R_a^2 + \lambda |R_c - R_l|^2 && (31a)\\
\text{subject to} \quad & R_a, R_l \geq 0 && (31b)\\
& \dot{h}(R_a, R_l) \leq \dot{h}_{\max} && (31c)\\
& (\mathbf{??}) \\
& (\mathbf{??})
\end{aligned}
$$

System overview



Figure 10: System overview

Results



(a) $= 0^\circ$



(b) $= 90^\circ$

Figure 11: Resulting landing procedures for different wind directions, $= 5$ m/s

Results (contd)



(a) $= 0^\circ$



(b) $= 90^\circ$

Figure 12: Resulting landing procedures for different wind directions, $= 5$ m/s

Possible improvements

- Extend formulation to handle varying winds with the same motion primitive set/HLUT
- Investigate admissibility of heuristic (especially projection)
- Handle wind variations in landing sequence generation
- Estimate wind mean and variance online from measurements