

■ Graphics

`Graphics[primitives, options]` represents a two-dimensional graphical image.

`Graphics` is displayed using `Show`. ■ The following primitives can be used:

<code>Point[{x, y}]</code>	point
<code>Line[{x₁, y₁}, ...]</code>	line
<code>Rectangle[{xmin, ymin}, {xmax, ymax}]</code>	filled rectangle
<code>Polygon[{x₁, y₁}, ...]</code>	filled polygon
<code>CellArray[array]</code>	array of gray levels
<code>Text[expr, {x, y}]</code>	text
<code>GrayLevel[i]</code>	intensity specification
<code>RGBColor[r, g, b]</code>	color specification
<code>PointSize[s]</code>	point size specification
<code>Thickness[t]</code>	line thickness specification
<code>Dashing[{d₁, ...}]</code>	line dashing specification

■ The following options can be given:

<code>AspectRatio</code>	<code>1/GoldenRatio</code>	ratio of height to width
<code>Axes</code>	<code>None</code>	whether to include axes
<code>AxesLabel</code>	<code>None</code>	axes labels
<code>DisplayFunction</code>	<code>\$DisplayFunction</code>	function for generating output
<code>Framed</code>	<code>False</code>	whether to draw a frame
<code>PlotColor</code>	<code>True</code>	whether to plot in color
<code>PlotLabel</code>	<code>None</code>	a label for the plot
<code>PlotRange</code>	<code>Automatic</code>	range of z values to include
<code>Ticks</code>	<code>Automatic</code>	tick marks

■ Nested lists of graphics primitives can be given. The scope of specifications such as `GrayLevel` is the list that contains them. ■ The standard print form for `Graphics[...]` is `-Graphics-`. `InputForm` prints the explicit list of primitives. ■ See page 140. ■ See also: `Plot`.