

■ OpenAppend

`OpenAppend["file"]` opens a file to append output to it.

The following options can be given:

<code>FormatType</code>	<code>InputForm</code>	default format for printing expressions
<code>GraphicsFont</code>	<code>"DefaultFont"</code>	default font for text in graphics output
<code>PageHeight</code>	<code>22</code>	number of lines per page
<code>PageWidth</code>	<code>78</code>	number of character widths per line
<code>TextRendering</code>	<code>Plain</code>	type of text output
<code>TotalHeight</code>	<code>Infinity</code>	maximum number of lines for a single expression
<code>TotalWidth</code>	<code>Infinity</code>	maximum number of character widths for a single expression

■ Files are specified by their names. Only one file with a particular name can be open at once. ■ On computer systems that support pipes, `OpenAppend["!command"]` runs the external program specified by *command*, and opens a pipe to send input to it. ■ If `OpenAppend` succeeds in opening a particular file or pipe, it returns the name of the file or pipe. Otherwise, it generates a message, and returns `Null`. ■ `OpenAppend` resolves file names according to the procedure described in Section ??.

■ The list `$$Media` gives names of all the files and pipes active at a particular time. ■ `ResetMedium` can be used to change the properties of a file or pipe, after it is already open. ■ Functions like `Put` and `Write` automatically open the files or pipes they need, if they are not already open. ■ See page 292. ■ See also: `Close`, `Put`.