

■ B.6 *Mathematica* Sessions

■ B.6.1 Global Variables

<code>In[n]</code>	the n^{th} input line
<code>Environment["var"]</code>	the value of an operating system environment variable, or Failed if the variable is not found
<code>Out[n]</code> or <code>%n</code>	the n^{th} output line
<code>\$CommandLine</code>	a list of the elements of the original operating system command line with which <i>Mathematica</i> was called
<code>\$Context</code>	the current context
<code>\$ContextPath</code>	the current context path
<code>\$Epilog</code>	an expression to be executed when you exit <i>Mathematica</i>
<code>\$IgnoreEOF</code>	whether to exit an interactive <i>Mathematica</i> session when an end-of-file character is received
<code>\$Line</code>	the current line number
<code>\$Path</code>	the current path to search for files
<code>\$Pre</code>	a function applied to each input expression before evaluation
<code>\$Post</code>	a function applied after evaluation
<code>\$PrePrint</code>	a function applied after <code>Out[n]</code> is assigned, but before the result is printed
<code>\$RecursionLimit</code>	the current recursion limit for evaluation
<code>\$System</code>	the type of computer system on which <i>Mathematica</i> is running
<code>\$Version</code>	the version of <i>Mathematica</i> being used

General global variables.

Input and output media can be either files or pipes.

<code>\$Display</code>	list of default media to use for graphics output
<code>\$DisplayFunction</code>	default function to use for graphics output
<code>\$Echo</code>	media to echo each line of input to
<code>\$Messages</code>	media to send messages to
<code>\$Output</code>	media to send standard output to
<code>\$Urgent</code>	media to send urgent messages to
<code>\$\$Media</code>	list of all active output media

Global variables for output.