

■ ListPlot

`ListPlot[{y1, y2, ...}]` plots a list of values. The x coordinates for each point are taken to be 1, 2,

`ListPlot[{x1, y1}, {x2, y2}, ...]` plots a list of values with specified x and y coordinates.

`ListPlot` returns a `Graphics` object. ■ Setting `PlotJoined -> True` gives a line joining the points. ■ The following options can be given:

<code>AspectRatio</code>	<code>1/GoldenRatio</code>	ratio of height to width
<code>Axes</code>	<code>Automatic</code>	whether to include axes
<code>AxesLabel</code>	<code>None</code>	axes labels
<code>DisplayFunction</code>	<code>\$DisplayFunction</code>	function for generating output
<code>Framed</code>	<code>False</code>	whether to draw a frame
<code>PlotColor</code>	<code>True</code>	whether to plot in color
<code>PlotJoined</code>	<code>False</code>	whether to join the points
<code>PlotLabel</code>	<code>None</code>	a label for the plot
<code>PlotRange</code>	<code>Automatic</code>	range of z values to include
<code>PlotStyle</code>	<code>Automatic</code>	graphics primitives to specify the style for points or lines
<code>Ticks</code>	<code>Automatic</code>	tick marks

■ You can specify properties of points or lines in the plot by setting the option `PlotStyle` to lists of such graphics primitives as `PointSize`, `Thickness`, `GrayLevel` and `RGBColor`. ■ See page 137. ■ See also: `Plot`.