

Creating an Emacs Diary Parser with Haskell and Parsec

Toby Tripp

March 2018

Contents

1	“Don’t Fear the Monad”	2
1.1	Outline (7:50)	2
1.2	Notation (8:25)	2
1.2.1	Composition	3
1.3	Monoids (20:40)	3
1.4	Monads (30:39)	3
2	The Maybe Monad	5
2.1	As Described by Computerphile	5
3	Other Monads	6
3.1	The Identity Monad	6
3.2	Definition of Maybe	6
3.3	The List <i>Monad</i>	6
4	Using Parsec	8
4.1	Parsing CSV	8
4.2	sepBy and endBy Combinators	9
5	Using HUnit to test the Parser	11
5.1	Helper Functions	11
5.1.1	Date Helpers	11
5.1.2	Parser Testing Helpers	11
5.1.3	Writing the Tests	12
5.1.4	The Preamble	12
5.2	Testing the Parser	13
6	The Emacs Diary Parser	17
6.1	Parsing Dates and Times	17
6.1.1	Date	18
6.1.2	Time	19
6.1.3	Interval	19
6.2	Testing the Parser	19

Chapter 1

“Don’t Fear the Monad”

Dr. Beckman, astrophysicist and senior software engineer, begins with a basic introduction to functional programming as a concept [1]. Most notably, he focuses on the concept of functions as being **replaceable** by table-lookups.

1.1 Outline (7:50)

1. Functions
2. Monoids
3. Functions
4. Monads

1.2 Notation (8:25)

FROM “IMPERATIVE” TO FUNCTIONAL NOTATION :

- $int\ x = x \in int$
- `x :: int`
- $int\ f(int\ x)$
- `f :: int → int`

GIVEN TYPE VARIABLE $a : \forall a$

- `A x`
- `x :: a`
- `static A f<A>(A x)`
- `f :: a → a`

1.2.1 Composition

Given:

```
x :: a
f :: a → a
g :: a → a
```

in imperative style function composition might appear as: `f(g(a))` or in reverse: `g(f(a))`.

In functional style, function application appears as: `g a` and composition can be shown as: `f(g a)`. Parenthesis are necessary due to partial application being left associative. For example, `f h g` is applied as though `(f h) g`.

It is also possible to use a composition operator, `o`, to imply composition: `(f o g) a`. So, given the above 1.2.1, we can deduce:

```
h = (f o g) a = f o g
h :: a → a
```

This does confuse the concepts of `a` as argument and `a` as type, but the point remains clear, I think.

1.3 Monoids (20:40)

In abstract algebra, a branch of mathematics, a monoid is an algebraic structure with a single associative binary operation and an identity element.

Monoids are studied in semigroup theory, because they are semigroups with identity.
^a:

^aWikipedia

A *Monoid* is a *Set* with:

1. an associative binary operator (generally composition)
2. an identity value

The operator need not be commutative.

In a programming context, a *Monoid* guarantees type-consistency over function composition.

1.4 Monads (30:39)

Given:

```
x :: a
f :: a → M a
g :: a → M a
g :: a → M a
```

`M` is described as a “Type Constructor.”

Again, Dr. Beckman is using `a` to represent both a value of type `a` as well as the type itself `a`. Here he introduced the *Monad* “bind” operator: `>>=`, which he likes to call “shove”:

```
f :: a → M a
g :: a → M a
-- the right hand side is g, but written with
-- a lambda to preserve symmetry
λa → (f a) >>= λa → (g a)
```

The reason to preserve symmetry in the above expression is that the desired expression is “bracketed” as: $\lambda a \rightarrow [(fa) >>= \lambda a \rightarrow (ga)]$ because the bind operator has type:

```
 $\langle >>= \rangle :: \text{Monad } m \Rightarrow m\ a \rightarrow (a \rightarrow m\ b) \rightarrow m\ b$ 
```

That is, $>>=$ accepts a *Monad* ($M\ a$) and returns a function from $a \rightarrow M\ a$.

The functions f , and g live in a *Monoid*. $M\ a$ (the *data*) lives in a *Monad*.

$\langle >>= \rangle$ is the analog of function composition and, therefore, obeys the rules of a *Monoid*. Including associativity and identity.

In a *Monad*, identity is—in Haskell—written as:

```
 $\text{return} :: \text{Monad } m \Rightarrow a \rightarrow m\ a$ 
```

Extended to non-uniform types:

```
 $g :: a \rightarrow Mb$   
 $f :: b \rightarrow Mc$   
 $\lambda a \rightarrow (g\ a) >>= \lambda b \rightarrow (f\ b) :: a \rightarrow Mc$   
 $g >>= \lambda b \rightarrow (f\ b)$ 
```

Chapter 2

The Maybe Monad

2.1 As Described by Computerphile

[3]

```
-- Type and 2 type constructors: Val and Div
data Expr = Val Int | Div Expr Expr

-- Val 1
-- Div (Val 6) (Val 2)

unsafe_eval :: Expr → Int
unsafe_eval (Val n) = n
unsafe_eval (Div x y) = div (eval x) (eval y)

-- eval (Div (Val 6) (Val 2))
```

What if `Div` is passed zero? The program will crash. So, error-checking is necessary.

```
safediv :: Int → Int → Maybe Int
safediv n m = if m == 0 then Nothing else Just (div n m)

eval :: Expr → Maybe Int
eval (Val n) = Just n
eval (Div x y) = case eval' x of
    Nothing → Nothing
    Just n → case eval' y of
        Nothing → Nothing
        Just m → safediv n m
```

Abstracting the pattern of `case` checking `Maybe` values can be represented as:

Without 'do' notation	With 'do' notation
<pre>eval' :: Expr → Maybe Int eval' (Val n) = return n eval' (Div x y) = eval' x >>= (λn → eval' y >>= (λm → safediv n m))</pre>	<pre>eval'' :: Expr → Maybe Int eval'' (Val n) = return n eval'' (Div x y) = do n ← eval'' x m ← eval'' y safediv n m</pre>

Chapter 3

Other Monads

The *Monad* type[4, p. 402]:

```
class Monad m where
  (>>=) :: m a → (a → m b) → m b
  return :: a → m a
  (>>)  :: m a → m b → m b
  fail  :: String → m a
```

Monad comes with some default definitions:

```
m >> k = m >>= λ_ → k
fail s = error s
```

From this definition it can be seen that `>>` acts like `>>=`, except that the value returned by the first argument is discarded rather than being passed to the second argument. [4, p. 403]

3.1 The Identity Monad

The identity monad [4, p. 404] takes a type to itself with definitions:

```
m >>= f = f m
return = id
```

3.2 Definition of Maybe

```
instance Monad Maybe where
  (Just x) >>= k = k x
  Nothing >>= k = Nothing
  return      = Just
  fail s      = Nothing
```

3.3 The List *Monad*

```
instance Monad [] where
  xs >>= f = concat (map f xs)
  return x = [x]
  fail s = []
```

Lists are, in fact, themselves instances of *Monad*.

```
fmap :: Functor f => (a -> b) -> f a -> f b
(>>=) :: Monad m => m a -> (a -> m b) -> m b
map   :: (a -> b) -> [a] -> [b]
```


Chapter 4

Using Parsec

4.1 Parsing CSV

```
import Text.ParserCombinators.Parsec
```

[2, Ch. 16]

Input type is a sequence of characters, i.e., a Haskell *String*. *String* is the same as *[Char]*. The return value is *[[String]]*; a list of a list of Strings. We'll ignore *st* for now.

The *do* block implies a *Monad*. *GenParser* is a parsing monad.

many is a higher-order function that passes input repeatedly to the function passed as its argument. It collects the return values and returns them in a list.

```
csvFile :: GenParser Char st [[String]]
csvFile =
  do result <- many line
  eof
  return result
```

A *line* is a list of *cells* followed by *eol*.

```
line :: GenParser Char st [String]
line =
  do result <- cells
  eol
  return result
```

```
cells :: GenParser Char st [String]
cells =
  do first <- cellContent
  next <- remainingCells
  return (first : next)
```

The choice operator, (*<|>*), tries the parser on the left and tries The parser on the right if the left consumes no input.

```
remainingCells :: GenParser Char st [String]
remainingCells =
  (char ',' >> cells) <|> (return [])
```

```
cellContent :: GenParser Char st String
cellContent =
  many (noneOf ",\n")
```

```
eol :: GenParser Char st Char
eol = char '\n'
```

```
parseCSV :: String → Either ParseError [[String]]
parseCSV input = parse csvFile "(unknown)" input
```

4.2 sepBy and endBy Combinators

```
import Text.ParserCombinators.Parsec
```

```
csvFile = endBy line eol
line    = sepBy cell (char ',')
cell    = quotedCell <|> many (noneOf ",\n\r")
```

A CSV cell may be either a bare cell or a quoted cell. Since a quoted cell may, itself, contain quotes (doubled for escape) a `quotedCell` is `many quotedChar`.

```
quotedCell =
  do char '"'
  \content ← many quotedChar
  \char ← "<?> \"quote_at_end_of_cell\" -- see eol below
  return content
```

The function `quotedChar` begins by consuming any character that is *not* itself a quote. If it is a quoted character, the stream must be checked for a second consecutive quote. If so, a single quote mark is returned to the result string.

Notice that `try` in `quotedChar` on the right side of `<|>`. Recall that I said that `try` only has an effect if it is on the left side of `<|>`. This `try` does occur on the left side of a `<|>`, but on the left of one that must be within the implementation of `many`.

This `try` is important. Let's say we are parsing a quoted cell, and are getting towards the end of it. There will be another cell following. So we will expect to see a quote to end the current cell, followed by a comma. When we hit `quotedChar`, we will fail the `noneOf` test and proceed to the test that looks for two quotes in a row. We'll also fail that one because we'll have a quote, then a comma. If we hadn't used `try`, we'd crash with an error at this point, saying that it was expecting the second quote, because the first quote was already consumed. Since we use `try`, this is properly recognized as not a character that's part of the cell, so it terminates the `many quotedChar` expression as expected. Lookahead has once again proven very useful, and the fact that it is so easy to add makes it a remarkable tool in `Parsec`.

```
quotedChar =
  noneOf "\""
  \<|> try (string "\n\r") >> return ''
```

`Parsec` also includes combinators for error handling and reporting. A first attempt at an `eol` implementation that handles multiple line-ending styles might appear as:

```
eol' = try (string "\n\r")
      <|> try (string "\r\n")
      <|> string "\n"
      <|> string "\r"
```

```
> parseCSV "line1"
Left "(unknown)" (line 1, column 6):
unexpected end of input
expecting ",", "\n\r", "\r\n", "\n" or "\r"
```

The failure above is unclear and requires knowledge of the parser implementation to debug fully. The monad `fail` function can be used to add messaging:

```
eol' = try (string "\n\r")
      <|> try (string "\r\n")
      <|> string "\n"
      <|> string "\r"
      <|> fail "Couldn't find EOL"
```

This adds messaging to the result, but is still noisy and unclear:

```
> parseCSV "line1"
Left "(unknown)" (line 1, column 6):
unexpected end of input
expecting ",", "\n\r", "\r\n", "\n" or "\r"
Couldn't find EOL
```

The Parsec `<?>` operator is designed to help here.

It is similar to `<|>` in that it first tries the parser on its left. Instead of trying another parser in the event of a failure, it presents an error message. Here's how we'd use it:

```
eol = try (string "\n\r")
      <|> try (string "\r\n")
      <|> string "\n"
      <|> string "\r"
      <?> "end of line"
```

This has a more pleasing result:

```
> parseCSV "line1"
Left "(unknown)" (line 1, column 6):
unexpected end of input
expecting "," or end of line
```

The general rule of thumb is that you put a human description of what you're looking for to the right of `<?>`.

```
parseCSV :: String → Either ParseError [[String]]
parseCSV input = parse csvFile "(unknown)" input
```

Chapter 5

Using HUnit to test the Parser

5.1 Helper Functions

```
module SpecHelpers where
import Test.HUnit

import Text.Printf

import Data.Time.Clock
import Data.Time.Calendar
import Data.Time.Format
import Data.Time.LocalTime

import Text.Parsec
import Text.Parsec.String
import Data.Time.LocalTime (utc)

import qualified EmacsDiary.Interval as Interval
```

5.1.1 Date Helpers

TimeZones

```
cdt = hoursToTimeZone (-5)
```

5.1.2 Parser Testing Helpers

```
assertParsesTo :: (Eq expected, Show expected)
  => Parsec SourceName () expected -- ^ Parser under test
  -> String                        -- ^ input
  -> expected                      -- ^ expected parser output
  -> IO ()

assertParsesTo p input expected =
  case runParser p nullState input input of
    (Left e) -> assertFailure $ show e
    (Right actual) -> assertEquals "" expected actual
  where
    nullState = ()
```

5.1.3 Writing the Tests

Table 5.1: Test Types

<code>tests :: Test</code>	Provides a way to convert data into a <code>Test</code> or set of <code>Test</code> .
<code>test :: Testable t => t -> Test</code>	Creates a test from the specified <code>Testable</code> , with the specified label attached to it.
<code>(~:) :: Testable t => String -> t -> Test</code>	Since <code>Test</code> is <code>Testable</code> , this can be used as a shorthand way of attaching a <code>STestLabel</code> to one or more tests.
<code>assertEqual :: (Show a, Eq a) => String -> a -> a -> Assertion</code>	
<code>(@=?) :: (Show a, Eq a) => a -> a -> Assertion</code>	Asserts that the specified actual value is equal to the expected value (with the actual value on the left-hand side).

5.1.4 The Preamble

Declare the test module and export its tests.

```
module EmacsDiary.RecordSpec (tests) where

import Test.HUnit
import SpecHelpers

import Data.Time.Calendar
import Data.Time.LocalTime

import EmacsDiary.Record
import qualified EmacsDiary.Interval as I
import qualified EmacsDiary.Ics as ICS
```

```
tstamp = ZonedTime local cdt
  where
    local = LocalTime d t
    d = fromGregorian 2008 07 07
    t = TimeOfDay 12 00 00
```

```
tests = test [
  "emit_a_diary_record_as_ics" ~: do
    let expected = unlines [
      "BEGIN:VCALENDAR"
      , "VERSION:2.0"
      , "BEGIN:VEVENT"
      , "UID:ED20080707170000"
      , "CREATED:20080707T170000Z"
      , "DTSTART:20080707T170000Z"
      , "DTEND:20080707T170000Z"
      , "SUMMARY:Happy Birthday, Son!"
      , "END:VEVENT"
      , ""
      , "BEGIN:VEVENT"
      , "UID:ED20080707180000"
      , "CREATED:20080707T170000Z"
      , "DTSTART:20080707T180000Z"
      , "DTEND:20080707T190000Z"
```

```

    , "SUMMARY: Eat_Cake."
    , "END:VEVENT"
    , ""
    , ""
    , "END:VCALENDAR"
  ]
let d = I.utcDate tstamp (I.gregorian 2008 7 7)
let e1 = Entry (I.instant d 12 00) [Description "Happy_Birthday,_Son!"]
let e2 = Entry (I.interval (I.makeTime d 13 00)
                    (Just (I.makeTime d 14 00)))
                    [Description "Eat_Cake."]
let input = Diary [
  push e1 $ push e2 (empty d)
]

assertEqual "" expected (ICS.toIcs input)
,

```

```

"repeating_events_as_ICS" ~: do
  let expected = unlines [
    "BEGIN:VCALENDAR"
    , "VERSION:2.0"
    , "BEGIN:VEVENT"
    , "UID:ED20080709193000"
    , "CREATED:20080707T170000Z"
    , "DTSTART:20080709T193000Z"
    , "DTEND:20080709T193000Z"
    , "RRULE:WEEKLY"
    , "SUMMARY:Coffee"
    , "END:VEVENT"
    , ""
    , ""
    , "END:VCALENDAR"
  ]
  let d = I.DayOfWeek I.Wednesday tstamp
  let e = Entry (I.instant d 14 30) [Description "Coffee"]
  let input = Diary [push e (empty d)]
  assertEqual "" expected (ICS.toIcs input)
]

```

5.2 Testing the Parser

```

module EmacsDiary.ParserSpec (tests) where

import Test.HUnit
import SpecHelpers

import Text.Parsec (runParser, many)
import Text.Printf (printf)
import Data.Time.LocalTime (hoursToTimeZone)

import qualified EmacsDiary.Record as R
import qualified EmacsDiary.Interval as I
import EmacsDiary.Parser (diary, record, entry)

```

Create a parsed-at time-stamp value for use in testing parsers.

```
import Data.Time.Calendar
import Data.Time.LocalTime

tstamp = ZonedTime local cdt
  where
    local = LocalTime d t
    d = fromGregorian 2008 07 07
    t = TimeOfDay 12 0 0
```

A sample *Record*

```
epochRecord = makeRecord (I.gregorian 1970 1 1)
makeRecord = R.empty ∘ (I.utcDate tstamp)
```

Parsers to test:

```
diaryParser = diary tstamp
recordParser = record tstamp
entryParser = entry epochRecord
```

```
tests = test [
  "parse_solitary_entry" ~: do
    let input = "\u0014:30\u00entry\u00a"
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["entry"])
  ,
```

```
  "parse_multi-element_entry" ~: do
    let input = unlines [
      "\u0014:30\u00field1",
      "\u00\u00field2",
      "\u00\u00field3"
    ]
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["field1", "field2", "field3"])
  ,
```

```
  "requires_leading_whitespace_for_entry" ~: do
    let input = unlines [
      "\u0014:30\u00field1;\u00field2",
      "Other\u00Text"
    ]
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["field1", "field2"])
  ,
```

```
  "entry_with_combinator" ~: do
    let input = unlines [
      "\u0014:30\u00field1",
      "\u0015:30\u00field2"
    ]
    assertParsesTo (many entryParser) input
      [(R.entry (I.instant I.epoch 19 30) ["field1"]),
       (R.entry (I.instant I.epoch 20 30) ["field2"])]
  ,
```

```
"parse_semicolon_separator" ~: do
  let input = unlines [
    "  14:30_field1;_field2",
    "    _field3"
  ]
  assertParsesTo entryParser input
  (R.entry (I.instant I.epoch 19 30) ["field1", "field2", "field3"])
,
```

```
"parse_date_and_time_with_empty_description_produces_error" ~: do
  let input = "7_July_2008_14:30\n"
  case runParser diaryParser () input input of
    (Left e) → assert True
    (Right r) → assertFailure
      (printf "parsing_should_have_failed,_but_got_%s" (show r))
,
```

```
"record_parsing_returns_a_Record" ~: do
  let input = "7_July_2008\n"
  assertParsesTo diaryParser input (R.Diary [makeRecord (I.gregorian 2008 7 7)])
,
```

```
"record_parser" ~: do
  let input = unlines ["7_July_2008_14:30_Work_on_parsers"]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  assertParsesTo recordParser input
  (R.push (R.entry (I.instant d 14 30) ["Work_on_parsers"])
   (R.empty d))
,
```

```
"parse_date_and_time_with_description" ~: do
  let input = unlines ["7_July_2008_14:30_Work_on_parsers"]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let e = R.entry (I.instant d 14 30) ["Work_on_parsers"]
  assertParsesTo diaryParser input (R.Diary [R.push e (R.empty d)])
,
```

```
"parse_multi-line_entry" ~: do
  let input = unlines [
    "7_July_2008_14:30_Work_on_parsers",
    "    _With_gusto!",
    ""
  ]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let e = R.entry (I.instant d 14 30) ["Work_on_parsers", "With_gusto!"]
  case runParser diaryParser () input input of
    (Left e) → assertFailure $ show e
    (Right actual) → assertEqual "Multi-line_entry"
      (R.Diary [R.push e $ makeRecord (I.gregorian 2008 7 7)])
      actual
,
```

In the Emacs Diary, weekly repeating events can be specified by using a week-day name instead of a specific date.

```
"weekday_entries" ~: do
```



```

let input = "Wednesday_08:00_Wake_up"
let e = R.entry (I.instant (I.utcDate tstamp (I.gregorian 2008 07 09)) 8 0) ["Wake_up"]
assertParsesTo diaryParser input (R.Diary [
  R.push e (R.Record (I.DayOfWeek I.Wednesday tstamp) [])])
,

```

```

"parse_entry_with_time-interval" ~: do
  let input = unlines [
    "7_July_2008_13:00-16:00_Gorge_on_Cake"
  ]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let t1 = I.makeTime d 13 0
  let t2 = I.makeTime d 16 0
  let e1 = R.entry (I.interval t1 (Just t2)) ["Gorge_on_Cake"]
  assertParsesTo diaryParser input
    (R.Diary [R.push e1 (makeRecord (I.gregorian 2008 7 7))])
,

```

```

"parse_multiple_records" ~: do
  let input = unlines [
    "7_July_2008_14:30_Work_on_parsers",
    "7_July_2008_15:15_Celebrate"
  ]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let e1 = R.entry (I.instant d 14 30) ["Work_on_parsers"]
  let e2 = R.entry (I.instant d 15 15) ["Celebrate"]
  case runParser diaryParser () input input of
    (Left e)      → assertFailure $ show e
    (Right actual) → assertEqual "Multiple_records"
      (R.Diary [(R.push e1 $ makeRecord (I.gregorian 2008 7 7)),
        (R.push e2 $ makeRecord (I.gregorian 2008 7 7))])
      actual
]

```

Chapter 6

The Emacs Diary Parser

6.1 Parsing Dates and Times

```
{-|
Description: Parsers for calendar time-intervals.
-}

module EmacsDiary.Parser.Interval (
  interval,
  date,
  time
)where

import qualified EmacsDiary.Parser.Tokens as T
import EmacsDiary.Interval (
  Date(..),
  WeekDay(..),
  Time,
  Interval(..),

  utcDate,
  makeTime,
  gregorian
)

import Text.Parsec (
  (<|>),           -- ^ 'choice' operator
  (<?>),           -- ^ 'unexpected' operator

  choice,
  option,
  string,
  try,
  unexpected
)

import Text.Parsec.String (Parser)
import Data.Time.Calendar (fromGregorian)
import Data.Time.LocalTime (
  ZonedTime,
  zonedTimeZone
)
```

```

date      :: ZonedTime          -- ^ current local time
           → Parser Date
time      :: Date → Parser Time
interval  :: Date → Parser Interval

```

6.1.1 Date

```

date localtime = day localtime <|> weekday localtime

day localt = do
  d ← dayP
  m ← monthP
  y ← yearP <?> "date"
  return $ utcDate localt (gregorian y m d)
weekday localt = T.lexeme $ choice $
  map kvp weekdays
  where
    kvp :: (String, WeekDay) → Parser Date
    kvp (wstring, wd) = try (string wstring) >> return (DayOfWeek wd localt)
    weekdays = [
      ("Sunday",    Sunday)
    , ("Monday",   Monday)
    , ("Tuesday",  Tuesday)
    , ("Wednesday", Wednesday)
    , ("Thursday", Thursday)
    , ("Friday",   Friday)
    , ("Saturday", Saturday)
    ]

dayP :: Parser Int
dayP = fromIntegral <$> T.numeric

yearP :: Parser Integer
yearP = T.numeric

monthP :: Parser Int
monthP = T.lexeme $ choice $
  map kvp months
  where
    kvp :: (String, Int) → Parser Int
    kvp (mn,n) = try (string mn) >> return n

months = [
  ("January", 1), ("Jan", 1),
  ("February", 2), ("Feb", 2),
  ("March", 3), ("Mar", 3),
  ("April", 4), ("Apr", 4),
  ("May", 5),
  ("June", 6), ("Jun", 6),
  ("July", 7), ("Jul", 7),
  ("August", 8), ("Aug", 8),
  ("September", 9), ("Sep", 9),
  ("October", 10), ("Oct", 10),
  ("November", 11), ("Nov", 11),
  ("December", 12), ("Dec", 12)
]

```

6.1.2 Time

```
time d = do
  h ← T.whitespace *> try (T.numeric <* T.symbol ":") <|> unexpected "time"
  m ← T.numeric <|> unexpected "time"
  return $ makeTime d (fromInteger h) (fromInteger m)
```

6.1.3 Interval

An `Interval` is a range of times on a specified `Date`. The Emacs Diary, so far as I know, does not support events spanning more than one day.

```
interval d = do
  t1 ← try (time d) <|> unexpected "start_time"
  t2 ← option t1 (T.symbol "-" *> (time d))
  return $ Interval t1 t2
```

6.2 Testing the Parser

```
module EmacsDiary.ParserSpec (tests) where

import Test.HUnit
import SpecHelpers

import Text.Parsec (runParser, many)
import Text.Printf (printf)
import Data.Time.LocalTime (hoursToTimeZone)

import qualified EmacsDiary.Record as R
import qualified EmacsDiary.Interval as I
import EmacsDiary.Parser (diary, record, entry)
```

Create a parsed-at time-stamp value for use in testing parsers.

```
import Data.Time.Calendar
import Data.Time.LocalTime

tstamp = ZonedTime local cdt
  where
    local = LocalTime d t
    d = fromGregorian 2008 07 07
    t = TimeOfDay 12 0 0
```

A sample `Record`

```
epochRecord = makeRecord (I.gregorian 1970 1 1)
makeRecord = R.empty ∘ (I.utcDate tstamp)
```

Parsers to test:

```
diaryParser = diary tstamp
recordParser = record tstamp
entryParser = entry epochRecord
```

```
tests = test [
  "parse_a_solitary_entry" ~: do
    let input = "\14:30\entry\n"
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["entry"])
  ,
```

```
  "parse_multi-element_entry" ~: do
    let input = unlines [
      "\14:30\field1",
      "\\field2",
      "\\field3"
    ]
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["field1", "field2", "field3"])
  ,
```

```
  "requires_leading_whitespace_for_entry" ~: do
    let input = unlines [
      "\14:30\field1;\field2",
      "Other\Text"
    ]
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["field1", "field2"])
  ,
```

```
  "entry_with_combinator" ~: do
    let input = unlines [
      "\14:30\field1",
      "\15:30\field2"
    ]
    assertParsesTo (many entryParser) input
      [(R.entry (I.instant I.epoch 19 30) ["field1"]),
       (R.entry (I.instant I.epoch 20 30) ["field2"])]
  ,
```

```
  "parse_semicolon_separator" ~: do
    let input = unlines [
      "\14:30\field1;\field2",
      "\\field3"
    ]
    assertParsesTo entryParser input
      (R.entry (I.instant I.epoch 19 30) ["field1", "field2", "field3"])
  ,
```

```
  "parse_date_and_time_with_empty_description_produces_error" ~: do
    let input = "7\July\2008\14:30\n"
    case runParser diaryParser () input input of
      (Left e) → assert True
      (Right r) → assertFailure
        (printf "parsing_should_have_failed,_but_got_\'%s\'" (show r))
  ,
```

```
  "record_parsing_returns_a_Record" ~: do
    let input = "7\July\2008\n"
```

```

    assertParsesTo diaryParser input (R.Diary [makeRecord (I.gregorian 2008 7 7)])
  ,

```

```

"record_parser" ~: do
  let input = unlines ["7_July_2008_14:30_Work_on_parsers"]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  assertParsesTo recordParser input
    (R.push (R.entry (I.instant d 14 30) ["Work_on_parsers"])
     (R.empty d))
  ,

```

```

"parse_date_and_time_with_description" ~: do
  let input = unlines ["7_July_2008_14:30_Work_on_parsers"]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let e = R.entry (I.instant d 14 30) ["Work_on_parsers"]
  assertParsesTo diaryParser input (R.Diary [R.push e (R.empty d)])
  ,

```

```

"parse_multi-line_entry" ~: do
  let input = unlines [
    "7_July_2008_14:30_Work_on_parsers",
    "    With_gusto!",
    ""
  ]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let e = R.entry (I.instant d 14 30) ["Work_on_parsers", "With_gusto!"]
  case runParser diaryParser () input of
    (Left e)      → assertFailure $ show e
    (Right actual) → assertEquals "Multi-line_entry"
      (R.Diary [R.push e $ makeRecord (I.gregorian 2008 7 7)])
      actual
  ,

```

In the Emacs Diary, weekly repeating events can be specified by using a week-day name instead of a specific date.

```

"weekday_entries" ~: do
  let input = "Wednesday_08:00_Wake_up"
  let e = R.entry (I.instant (I.utcDate tstamp (I.gregorian 2008 07 09)) 8 0) ["Wake_up"]
  assertParsesTo diaryParser input (R.Diary [
    R.push e (R.Record (I.DayOfWeek I.Wednesday tstamp) [])])
  ,

```

```

"parse_entry_with_time-interval" ~: do
  let input = unlines [
    "7_July_2008_13:00-16:00_Gorge_on_Cake"
  ]
  let d = I.utcDate tstamp (I.gregorian 2008 7 7)
  let t1 = I.makeTime d 13 0
  let t2 = I.makeTime d 16 0
  let e1 = R.entry (I.interval t1 (Just t2)) ["Gorge_on_Cake"]
  assertParsesTo diaryParser input
    (R.Diary [R.push e1 (makeRecord (I.gregorian 2008 7 7))])
  ,

```

```

"parse_multiple_records" ~: do
  let input = unlines [

```

```

        "7_July_2008_14:30_Work_on_parsers",
        "7_July_2008_15:15_Celebrate"]
let d = I.utcDate tstamp (I.gregorian 2008 7 7)
let e1 = R.entry (I.instant d 14 30) ["Work_on_parsers"]
let e2 = R.entry (I.instant d 15 15) ["Celebrate"]
case runParser diaryParser () input input of
  (Left e)      → assertFailure $ show e
  (Right actual) → assertEquals "Multiple_records"
    (R.Diary [(R.push e1 $ makeRecord (I.gregorian 2008 7 7)),
              (R.push e2 $ makeRecord (I.gregorian 2008 7 7))])
    actual
]

```

Bibliography

- [1] Dr. Brian Beckman. *Don't Fear the Monad*. YouTube. Nov. 2012. URL: <https://youtu.be/ZhuHCtR3xq8> (visited on 04/2018).
- [2] Bryan O'Sullivan, Don Stewart, and John Goerzen. *Real World Haskell*. O'Reilly Media, 2008. URL: <http://book.realworldhaskell.org/read/using-parsec.html>.
- [3] Sean Riley and Professor Graham Hutton. *Computerphile: What is a Monad?* YouTube. Nov. 2017. URL: <https://youtu.be/t1e8gqXLbsU> (visited on 04/2018).
- [4] Simon Thompson. *The Craft of Functional Programming*. Second. International Computer Science Series. Edinburgh Gate, England: Pearson Education Limited, 1999.