PORTATE IN LITRI/SECONDO (L/S) IN FUNZIONE DEL BATTENTE D'ACQUA

Ø (mm)	D ₂ (mm)	1 H (cm)	2 H (cm)	3 H (cm)	4 H (cm)	5 H (cm)	6 H (cm)	7 H (cm)	8 H (cm)	9 H (cm)	10 H (cm)	11 H (cm)
40	27	0,20 l/s	0,29 l/s	0,35 l/s	0,41 l/s	0,45 l/s	0,50 l/s	0,54 l/s	0,57 l/s	0,61 l/s	0,64 l/s	0,67 l/s
60	48	0,64 l/s	0,91 l/s	1,11 l/s	1,28 l/s	1,43 l/s	1,57 l/s	1,69 l/s	1,81 l/s	1,92 l/s	2,03 l/s	2,12 l/s
75	65	1,17 l/s	1,66 l/s	2,03 l/s	2,35 l/s	2,63 l/s	2,88 l/s	3,11 l/s	3,32 l/s	3,52 l/s	3,71 l/s	3,90 l/s
80	69	1,32 l/s	1,87 l/s	2,29 l/s	2,65 l/s	2,96 l/s	3,24 l/s	3,50 l/s	3,74 l/s	3,97 l/s	4,19 l/s	4,39 l/s
90	77	1,65 l/s	2,33 l/s	2,86 l/s	3,30 l/s	3,69 l/s	4,04 l/s	4,36 l/s	4,66 l/s	4,95 l/s	5,21 l/s	5,47 l/s
100	85	2,01 l/s	2,84 l/s	3,48 l/s	4,02 l/s	4,49 l/s	4,92 l/s	5,31 l/s	5,68 l/s	6,03 l/s	6,35 l/s	6,66 l/s
110	95	2,51 l/s	3,55 l/s	4,35 l/s	5,02 l/s	5,61 l/s	6,15 l/s	6,64 l/s	7,10 l/s	7,53 l/s	7,93 l/s	8,32 l/s
125	111	3,43 l/s	4,84 l/s	5,93 l/s	6,85 l/s	7,66 l/s	8,39 l/s	9,06 l/s	9,69 l/s	10,28 l/s	10,83 l/s	11,36 l/s
140	127	4,48 l/s	6,34 l/s	7,77 l/s	8,97 l/s	10,03 l/s	10,98 l/s	11,86 l/s	12,68 l/s	13,45 l/s	14,18 l/s	14,87 l/s
150	136	5,14 l/s	7,27 l/s	8,91 l/s	10,28 l/s	11,50 l/s	12,60 l/s	13,61 l/s	14,54 l/s	15,43 l/s	16,26 l/s	17,06 l/s
160	146	5,39 l/s	8,38 l/s	10,26 l/s	11,85 l/s	13,25 l/s	14,52 l/s	15,68 l/s	16,76 l/s	17,78 l/s	18,74 l/s	19,66 l/s
200	185	9,52 l/s	13,46 l/s	16,48 l/s	19,03 l/s	21,28 l/s	23,31 l/s	25,18 l/s	26,91 l/s	28,55 l/s	30,09 l/s	31,56 l/s

Ø = diametro nominale (mm)

 D_2 = diametro di entrata (mm)

H = altezza del battente d'acqua (cm)