High Pressure Filters

15P/30P Series

REVISION LEVEL - 000 CHANGED BY - SE/72 CATALOG NUMBER - 15 M/199 (if not printed on the catalog page)

PART NUMBER

HOW TO ORDER:

Select the desired symbol (in the correct position) to construct a model code.

Example:

Parker ITEM No. 933/36Q

| BOX 1 | BOX 2 | BOX 3 | BOX 4 | BOX 5 | BOX 6 | BOX 7 | BOX 8 | BOX 9 |
|-------|-------|-------|-------|-------|-------|-------|-------|-------------------------|
| F3 | 30P | 1 | 10Q | M2 | 50 | NN | 19 | (Assigned By Parker) |

| BOX 1: Seals | |
|--------------|------------------|
| Symbol | Description |
| None | Buna N (nitrile) |
| F3 | Viton |
| E8 | EPR |

| BOX 2: Bas | ic Assembly | |
|---------------------|------------------|--|
| Symbol | Description | |
| 15 P | Pressure filter | |
| 30P Pressure filter | | |
| 30PD | Duplex style 30P | |

| BOX 3: Leng | gth |
|-------------|-------------|
| Symbol | Description |
| 1 | Single |
| 2 | Double |

| BOX 4: Element Media | | | | |
|----------------------|--|--|--|--|
| Symt | pol Description | | | |
| 20C | Cellulos e | | | |
| 10C | Cellulos e | | | |
| 03C | Cellulose | | | |
| 20Q | Microglass II | | | |
| 10Q | Microglass II | | | |
| 05Q | Microglass II | | | |
| 02Q | Microglass II | | | |
| Note | For high collapse rated (2000 psid) elements, add "H" behind Q. For 3000 psid collapse rated elements, add "X" behind Q. | | | |

| BOX 5: Indicator | | | | |
|------------------|---|--|--|--|
| Symbol | Description | | | |
| N | No indicator, no pressure port | | | |
| Р | Port plugged | | | |
| M2 | Visual auto reset | | | |
| Н | Electrical indicator, w/½"-14 NPT connection and 12" leads | | | |
| E2 | Electrical/visual (DIN 43650 Hirschman style connection) | | | |
| E3 | Electrical/visual (ANSI/ B93.55M 3-pin Brad Harrison style connection) | | | |
| | de mount indicators, place after indicator symbol. Not | | | |

| вох | BOX 6: Bypass Or Indicator Setting | | | | |
|---|------------------------------------|--|--|--|--|
| Symbol Pressure Setting | | | | | |
| 50 | 50 psid | | | | |
| Note: If "no bypass" option (-11) and an indicator is selected, "50" denotes indicator calibration. | | | | | |

available on 30PD model.

| BOX 7: Ports | | | | |
|--|--------|----------------------|--|--|
| Model | Symbol | Description | | |
| 15P | MM | SAE-12 | | |
| 15P | XX | 34"-manifold porting | | |
| 30P | NN | SAE-16 | | |
| 30P | XX | 1"-manifold porting | | |
| 30PD | NN | SAE-16 | | |
| Note: Customer supplies subplate adaptor, or purchases optional Parker subplate. | | | | |

| BOX 8: Opti | ons |
|-------------|--------------------------|
| Symbol | Description |
| 1 | None |
| 11 | No bypass |
| 19 | SAE-5 drain port on bowl |
| 21 | No bypass and drain port |

Applied to filter assembly by Parker Filter Division. Use the full filter model code, including the design number when ordering replacement parts, elements and cartridges.

REPLACEMENT ELEMENTS

| Filter Model (viton seals) | | | | | |
|----------------------------|---------|-----------------|-----------------|-----------------|--|
| Media | 15P-1 | 15P-2 | 30P/30PD-1 | 30P/30PD-2 | |
| 20C | 925576 | 925596 | 922625 | 925834 | |
| 10C | 925385 | 925394 | 922624 | 925835 | |
| 03C | 925578 | 925598 | 922923 | 925836 | |
| 20Q | 930369Q | 930370Q | 933135Q | 933136Q | |
| 10Q | 932612Q | 932618Q | 932624Q | 932630Q | |
| 05Q | 932611Q | 932617Q | 932623 Q | 932629 Q | |
| 02Q | 932610Q | 932616Q | 932622Q | 932628Q | |
| IOQH | 932615Q | 932621Q | 932627Q | 932633Q | |
| 05QH | 932614Q | 932620 Q | 932626Q | 932632 Q | |
| 02QH | 932613Q | 932619 Q | 932625Q | 932631Q | |
| IOQX | 933577Q | 933579Q | 933581Q | 933583Q | |
| 02QX | 933576Q | 933578Q | 933580Q | 933582Q | |

FILTER ELEMENT REPLACEMENT ONLY

