

# MapReduce for k-means

5 questions

---

1  
point

1.

Suppose we are operating on a 1D vector. Which of the following operation is **not** data parallel over the vector elements?

- ☐ Add a constant to every element.
  - ☐ Multiply the vector by a constant.
  - ☐ Increment the vector by another vector of the same dimension.
  - ☐ Compute the average of the elements.
  - ☐ Compute the sign of each element.
- 

1  
point

2.

(True/False) A single mapper call can emit multiple (key,value) pairs.

- ☐ True
  - ☐ False
- 

1  
point

3.

(True/False) More than one reducer can emit (key,value) pairs with the same key simultaneously.

☐ True

☐ False

---

1  
point

4.

(True/False) Suppose we are running k-means using MapReduce. Some mappers may be launched for a new k-means iteration even if some reducers from the previous iteration are still running.

☐ True

☐ False

---

1  
point

5.

Consider the following list of binary operations. Which can be used for the reduce step of MapReduce? Choose all that apply.

☐  $OP1(x1, x2) = \text{MAX}(x1, x2)$

☐  $OP2(x1, x2) = x1 + x2 - 2$

☐  $OP3(x1, x2) = 3 * x1 + 2 * x2$

☐  $OP4(x1, x2) = x1^2 + x2$

☐  $OP5(x1, x2) = (x1 + x2) / 2$

---

Submit Quiz

