Sorbotech® LG 85

Sorbotech® LG 85 is a granular carbon manufactured from selected, high quality grades of coal. It is specially designed for drinking water treatment, eliminating substances having an influence on its colour, taste and smell. Additionally, it is a perfect medium for wastewater and process water filtration, removing organic impurities to a trace level.



SPECIFICATION

Iodine number	min. 850 mg/g
Granulation*	8x30 mesh (0,6 – 2,36 mm)
Moisture content	max. 5 %
Bulk density	approx. 500 kg/m^3
Hardness	min. 95 %
Ash content	max. 15 %

*Other granulations on demand

STORAGE

Activated carbon should be stored in sealed, unopened packages in dry place with temperature 5 – 40° C, away from sources of ignition and solvent vapours. Exposure to direct sunlight and moisture should be limited.

SAFETY

Wet activated carbon adsorbs oxygen from the air, what causes danger while working inside containers with activated carbon in closed or poorly ventilated places.

Under certain conditions, during contact with oxidizing agents and some organic compounds such as ketones (e.g. acetone), acrylates, esters, volatile acids, amines etc. activated carbon may react exothermally. In case of rapid temperature increase cooling with water is recommended.

Typical applications

- Water purification
- Wastewater treatment
- Pool water filtration
- Production solutions filtration

Packaging

- 20 kg bags
- 500/550 kg big bags

NARODOWY INSTYTUT ZDROWIA PUBLICZNEGO · PIB · PRODUKT Z ATESTEM
Nr B.BK.60110.0014.2025
ważny do: 06.03.2028

ACTIVATED CARBON ACES ENVIRONMENTAL SOLUTIONS

REACH COMPLIANCE

ISO 2015:9001

ACES Sp. z o.o.
Ul. Legionów 69
81-413 Gdynia
tel. 58 622 63 50
aces@aces.pl

ACES Sp. z o.o. reserves the right to change specification without notice.
Update: 01/03/2025