Company	: Akro Romanya	**Date**	: 31.07.2026
Att.	: Alexandru Soare	**Ref. Code**	: MC_620_AKRO_310726
Location	: Romania	**Att.**	: Gökhan Özler
Project	:	**Phone**	: + 90 554 499 24 24
Capacity	: 25,8 m^3/h	**e-mail**	: gozler@aosmithtr.com

Dear Customer,

A.O. Smith Company founded in Milwaukee, USA, in 1874. Innovative approaches and self-developed technologies have been accepting in many industries all over the world.
As the World's first used by A.O.Smith, arc welding method lend impetus to metal industry. In addition, for the first heating devices developed and produced by A.O.Smith uses the glass coating technology is a revolution in the heating sector.

Our company aims to find the most effective solutions such as in Reverse Osmosis, ultrafiltration, water softening, deionization, post treatment systems. In sales and marketing, our goal is to advertise new technology and equipment practically. This provides us to develop the process to find the solutions to your requests and keep you updated about new technologies. We are able to serve the best quality of the wide range of our own brand products and imported goods.

As your request of the Water Treatment System, technical data and prices offered for your information. We appreciate your interest and trust to A.O.Smith Company.

Kindest Regards,

Maxim Cernev
Project Quotation Eng.

Yusuf Ilgenoglu
Project Chief

**It is not signed because it exist in electronic form.*

1. FULLY AUTOMATED ACTIVATED CARBON FILTRATION SYSTEM

Activated Carbon Filtration Systems are used for removal of taste, odor, color, chlorine and chlorine compounds, and all organic materials that can be present in the water. A.O. Smith's special activated carbon mineral is placed in the system.

This device is equipped with a fully automatic control systems, adhering to the program will be initially required for certain periods (backwash and regeneration processes) without human need, makes itself at any time.

Amount	3 unit
Model	ACT300-48E
Service Flow Rate (Filt. Speed: 15 m/h)	18 m3/hour
Service Flow Rate (Filt. Speed: 25 m/h)	29 m3/hour
Actuator Type	Electric Actuator Valve
Valve Body Material	Cast iron
Valve Amount	5 pieces Actuator
Automation	Logo
Inlet / Outlet line connection diameter	3"
Tank Dimensions	125 cm x 250 cm
Tank Cross Sectional Area	1.23 m^2
Tank Material	FRP
Distribution type of inside the tank	PVC Diffuser
Piping Material	PVC
Backwash Duration	15 - 25 min.
Backwash Period	Time controlled backwash system.
Backwash Material	With water
Tank operation pressure	4 - 6 bar
Pressure drop	0,5 – 1 bar
Power	230 V / 50 Hz
Operating Temp.	4–40 ° C

* Device dimensions may vary.

2. BUYER'S RESPONSIBILITIES (OUT OF SCOPE)

- Raw Water Tank & Treated Water Tanks
- Raw Water Feed & Treated Water Pumps
- Disposal of backwash/discharge water coming from the system.
- Drainage piping of the system.
- Electric lines to the main control panel that will provide electricity needed to operate system.
- Plant building and all construction and concrete works. (if any needed)
- Delivery cost of the system.
- Start-up chemicals, consumables and chemicals
- Crane or other vehicles needed for settling of the equipment
- Foundation and base needed for all of the water storage tanks (if necessary)
- Visa procedures and providing visa for A.O.Smith supervisor. (if requested additionally)
- All accommodation, travel and food expenses of A.O.Smith supervisor. (if requested additionally)
- Mounting equipment, manways, cable trays, electric lines and all installation jobs.
- Supervising jobs and start-up.

3. COMMERCIAL TERMS

EQUIPMENTS	MODEL	UNIT	Unit Price (USD)	Total Price (USD)
Fully Automated Activated Carbon Filtration System	ACT300-48E	3	4.042	12.126
Electric Actuated Valve	3"	2	340	680
			TOTAL PRICE (USD)	**12.806,00 EXW**

- Production time of the water treatment system is 4-6 weeks.
- Prices given as EXW, Izmir – Turkey.
- Given price will be valid for 15 days from the offer submission date.

4. PAYMENT TERMS

- 100%: Advanced payment with the purchase order.