# Sorbotech® GE 604

**Sorbotech® GE 604** is an extruded activated carbon manufactured from selected grades of coal. Its high developed surface area allows effective adsorption of a wide range of organic compounds present in gases or air streams. Its perfectly available pore distribution makes it an excellent medium for industrial applications and ventilation systems.



## SPECIFICATION

| | |
|---|---|
| **CTC** | min. 60 % |
| **Granulation** | 4 mm |
| **Moisture content** | max. 5 % |
| **Bulk denisty** | approx. 480 kg/m$^3$ |
| **Hardness** | min. 95 % |
| **Ash content** | max. 15 % |

## STORAGE

Activated carbon should be stored in sealed, unopened packages in dry place with temperature 5 – 40° C, away from sources of ignition and solvent vapours. Exposure to direct sunlight and moisture should be limited.

## SAFETY

Wet activated carbon adsorbs oxygen from the air, what causes danger while working inside containers with activated carbon in closed or poorly ventilated places.

Under certain conditions, during contact with oxidizing agents and some organic compounds such as ketones (e.g. acetone), acrylates, esters, volatile acids, amines etc. activated carbon may react exothermally. In case of rapid temperature increase cooling with water is recommended.

## Typical applications

- Volitale organic compounds removal
- Fume hood filters production
- Spray booth filters
- Asphalt, solvent and fuel fumes filtration
- Odor removal
- Siloxanes removal

## Packaging

- 20 kg bags
- 500/550 kg big bags

NARODOWY INSTYTUT ZDROWIA PUBLICZNEGO · PIB · PZH
PRODUKT Z ATESTEM
Nr B.BK.60110.0019.2025
ważny do: 06.03.2028

ACTIVATED CARBON ACES ENVIRONMENTAL SOLUTIONS

REACH COMPLIANCE

ISO 2015:9001

**ACES Sp. z o.o.**
Ul. Legionów 69
81-413 Gdynia
tel. 58 622 63 50
aces@aces.pl

ACES Sp. z o.o. reserves the right to change specification without notice.
Update: 01/03/2025