AKRO
GRIJA PENTRU APĂ

contact@akro.ro
0268-413180 / 0728-994472
www.akro.ro

Technical Data Sheet
Time controlled filters for iron and manganese removal with Pyrolox Advantage media

Part no.	Pyrolox A. liter	Control head / connection	Flow rate m^3/h	Surface M2	Backwash flow rate	Weight Kg	Size (mm) H x L x W
BlueSoft 1054PA/67	20.4 (1.5 zsák)	RX-67C-DTF 1"	0.5-1.0	0.05	1.75 m^3/h	88	1600 x 270 x 270
BlueSoft 1354PA/67	34 (2.5 zsák)	RX-67C-DTF 1"	0.8-1.6	0.08	2.8 m^3/h	140	1610 x 350 x 350
BlueSoft 1465PA/67	40.8 (3 zsák)	RX-67C-DTF 1"	1.0-2.0	0.1	3.5 m^3/h	170	1890 x 370 x 370
BlueSoft 1665PA/67	54.4 (4 zsák)	RX-67C-DTF 1"	1.3-2.6	0.13	4.55 m^3/h	210	1930 x 420 x 420
BlueSoft 1865PA/75	68 (5 zsák)	RX-75A-DTF 2"	1.8-3.6	0.18	6.3 m^3/h	280	1980 x 500 x 500
BlueSoft 2162PA/75	81.6 (6 zsák)	RX-75A-DTF 2"	2.2-4.4	0.22	7.7 m^3/h	380	2080 x 560 x 560
BlueSoft 2472PA/75	108.8 (8 zsák)	RX-75A-DTF 2"	2.8-5.6	0.28	9.8 m^3/h	500	2170 x 620 x 620
BlueSoft 3072PA/111	176.8 (13 zsák)	RX-111A-DTF 2"	4.4-8.8	0.44	15.4 m^3/h	820	2490 x 700 x 700
BlueSoft 3672PA/111	244.8 (18 zsák)	RX-111A-DTF 2"	6.4-12.8	0.64	22.4 m^3/h	1240	2500 x 940 x 940
BlueSoft 4272PA/112	353.6 (26 zsák)	RX-112SM-DTF 2.5"	8.8-17.6	0.88	30.8 m^3/h	1680	2530 x 1210 x 1070
BlueSoft 4872PA/112	435.2 (32 zsák)	RX-112SM-DTF 2.5"	11.2-22.4	1.12	39.2 m^3/h	2270	2530 x 1210 x 1070

Iron equivalent (mg/l) =1 x Fe index (mg/l)+ 2 x Mn index (mg/l)+ 5 x H2S (mg/l)

Determination of the filtration velocity according to iron equivalent:

Iron equivalent	Filtration velocity
<0.2 mg/l	18 m/h
0.5 mg/l	15 m/h
1.0 mg/l	13 m/h
1.5 mg/l	12 m/h
2.0 mg/l	10 m/h
3.0 mg/l	8 m/h

Required filtering surface (m^2) = Flow rate (m^3/h) / Filtration velocity (m/h)

Important working conditions of Pyrolox Advantage:

Backwash:	60-70m/h
Bed depth:	30-45cm
Water pH-range:	6,5 – 9,0
Free volume:	min. 40% of the bed depth
Resistant to chlorine	



PYROLOX ADVANTAGE

str. Zizinului nr. 110,
Brașov, 500407, România