G-P Series

Ozone Generator G-P20 / G-P30 / G-P40 / G-P50 / G-P60

Features:

- Ozone production rate up to 60 g/h
- Integral oxygen concentrator with inlet air dryer
- Adjustable ozone output and flow rate
- Comfortable PLC system with PID controller and remote control capability
- Air cooled
- Stainless steel cabinet
- Weight: 158 – 250 kg
- Dimensions:
  G-P20 – G-P40: 600 x 600 x 1200 mm
  G-P50, G-P60: 730 x 900 x 1150 mm
- Power consumption: 1000 – 2100 W
- Power supply: 220 – 240 V, 50/60 Hz
- CE and EMC certified

G-P series ozone generator includes oxygen generation and ozone generation in one single splash water protected stainless steel cabinet. Oxygen is been generated on board by the maintenance free Pressure Swing Adsorption principle.
The unit combines without asking for an external feed gas supply the convenience of ambient air as gas source with the efficiency of oxygen.

The ozone generator is air-cooled being independent from a cooling water supply.

G-P series is movable through wheels allowing handling of the unit under limited space conditions.

A large variety of easy to use control interfaces simplifies integration into complete systems and complex processes.

Applications:

- Drinking water disinfection
- Beverage industry
- Food processing
- Cosmetic-/Pharmaceutical industry
- Aquaculture
- Waste water oxidation

AirTree Europe GmbH – Stettiner Straße 25 – D-34225 Baunatal

Tel.: +49 (0) 5601 92 818-0 / Fax.: +49 (0) 5601 92 818-10
E-Mail.: office@airtree-europe.com / www.airtree-europe.com