Sorbotech® LPW 90

Sorbotech® LPW 90 is a powder activated carbon manufactured from selected, high quality grades of wood. Its macroporous structure makes it an excellent medium for drinking water treatment, wastewater and process water filtration eliminating substances having an influence on its colour, taste and smell. Its dosage can be done by continuous or periodic feed system.



SPECIFICATION

Iodine number	min. 900 mg/g
Granulation	325 mesh (45 µm)
	200 mesh (70 µm)
Moisture content*	max. 10 %
Bulk density	approx. 350 kg/m^3
Methylene blue number	min. 200 mg/g
Ash content	max. 10 %

*during packing

STORAGE

Activated carbon should be stored in sealed, unopened packages in dry place with temperature 5 – 40° C, away from sources of ignition and solvent vapours. Exposure to direct sunlight and moisture should be limited.

SAFETY

Wet activated carbon adsorbs oxygen from the air, what causes danger while working inside containers with activated carbon in closed or poorly ventilated places.

Under certain conditions, during contact with oxidizing agents and some organic compounds such as ketones (e.g. acetone), acrylates, esters, volatile acids, amines etc. activated carbon may react exothermally. In case of rapid temperature increase cooling with water is recommended.

Typical applications

- Water purification
- Wastewater treatment
- Production solutions filtration

Packaging

- 20/25 kg bags
- 500/550 kg big bags
- In bulk, in a tanker

NARODOWY INSTYTUT ZDROWIA PUBLICZNEGO · PIB ·
PRODUKT Z ATESTEM
Nr B.BK.60110.0015.2025
ważny do: 06.03.2028

ACTIVATED CARBON ACES ENVIRONMENTAL SOLUTIONS
REACH COMPLIANCE

ISO 2015:9001

ACES Sp. z o.o.
ul. Legionów 69
81-413 Gdynia
tel. 58 622 63 50
aces@aces.pl

ACES Sp. z o.o. reserves the right to change specification without notice.
Update: 09/04/2026