OPT52: Predisposizione per Acqua calda

I sistemi UV standard possono essere utilizzati fino ad una temperatura di 80 °C.
Tuttavia, tra 50 °C e 80 °C l'emissione UV-C delle lampade diminuisce, quindi la portata massima a catalogo non è più garantita.
Per queste situazioni è consigliato richiedere dimensionamento a tech@sitauv.com
Per temperature tra 80 °C e 100 °C, SITA ha sviluppato un bloccaguaina in acciaio inox 316L disponibile acquistando l'optional OPT52 (*)(**).

Temperatura di esercizio (°C)	Configurazione impianto UV
0 - 50	Standard
50 - 80	Standard + dimensionamento specifico
80 - 100	Standard + OPT 52 + dimensionamento specifico

(*) Non applicabile per Serie HDPE.

(**) I sistemi a media pressione e la serie 400 montano già bloccaguaina in acciaio inox 316L.

OPT52: Hot water predisposition

The UV systems, in their standard configuration, can be used up to a temperature of 80 °C.
However, starting from 50 °C up to 80 °C the UV-C emission of lamps decreases, so catalogue flow rate is no longer guaranteed.
For these situations it is recommended to request a specific design to tech@sitauv.com
For temperatures between 80 °C and 100 °C, SITA has developed a 316L stainless steel sleeve bolts available purchasing the OPT52 option (*).

Working Temperature Range (°C)	UV System Configuration
0 - 50	Standard
50 - 80	Standard + specific sizing
80 - 100	Standard + OPT 52 + specific sizing

(*) Not applicable for HDPE series.

(**) Medium pressure lamp units and 400W lamp units already have this SS 316L sleeve bolt.



12/2019

S.I.T.A. srl – Via Rivarolo 61 – 16161 Genova Italy
tel 0039-010-7406848 – e-mail info@sitauv.com **– www.sitauv.com**