DATASHEET

# Filter Anthracite

**Filter ANTHRACITE** is a filtration material used primarily in the treatment of water in multimedia beds technology as its top layer. It consists mainly of broken and sieved fragments of natural anthracite. It has a high ability to capture impurities, including small particles. In multi-layer filtration process extends the filter's working time while maintaining a constant purified quality water. The product is almost completely inert, no particles of material, which may exceed the limits of drinking water parameters, are released into the water. The product complies with the PN-EN 12909 standard "Products used for treatment of water intended for human consumption - Anthracite."



## SPECIFICATION

| | |
|---|---|
| **Fixed carbon content** | min. 90 % |
| **Ash content** | max. 3,0 % |
| **Volatiles content** | max . 6,0 % |
| **Bulk density** | approx. 720 kg/m$^3$ |
| **Moisture content (as packaged)** | approx. 1,0 % |
| **Granulation** (undersize and oversize – compliant with the standard) | 0,6-1,6 mm<br>1,4-2,5 mm<br>2,0-4,0 mm<br>4,0-8,0 mm |

## STORAGE

Anthracite should be stored in sealed, unopened packages in dry place with temperature 5 – 40° C, away from sources of ignition and solvent vapours. Exposure to direct sunlight and moisture should be limited.

## BACKWASH PARAMETERS

**FILTER ANTHRACITE 0.6 - 1.6 mm**

- Rinsing with water approx. 35 m / h for 3 - 5 minutes
- Lowering the water level and flushing with air approx. 60 m/h for 3-5 minutes
- Bed degassing for 2-5 min
- Clean rinsing with water approx. 35 m/h

**FILTER ANTHRACITE 1.4 - 2.5 mm**

- Rinsing with water approx. 55 m/h for 3-5 minutes
- Lowering the water level and flushing with air approx. 60 m/h for 3-5 minutes
- Bed degassing for 2 - 5 min
- Clean rinsing with water approx. 55 m / h

## Applications

- Drinking water purification
- Wastewater treatment
- Production solutions filtration
- Swimming pool's water treatment

## Packaging

- 50 L bags
- big bags 1m$^3$

NARODOWY INSTYTUT ZDROWIA PUBLICZNEGO · PIB · PZH
PRODUKT Z ATESTEM
Nr B.BK.60110.1128.2022
ważny do: 2025.03.02

ACTIVATED CARBON ACES ENVIRONMENTAL SOLUTIONS
REACH COMPLIANCE
ISO 2015:9001

**ACES Sp. z o. o.**
ul. Łużycka 10
81-537 Gdynia
tel. +48 58 622 63 50
aces@aces.pl

ACES Sp. z o. o. reserves the right to change specification without notice.
Update: 01/04/2022