Sorbotech® LGCO 85

Sorbotech® LGCO 85 is a granular carbon manufactured from selected, high quality grades of coconut shell charcoal. Its highly developed internal area, microporous structure and superior mechanical hardness makes it a perfect medium for drinking water filtration, eliminating undesirable substances having an influence on its colour, taste and smell. Additionally, it is a perfect medium for wastewater and process water filtration, removing organic impurities to a trace level.



SPECIFICATION

Iodine number	min. 900 mg/g
Granulation*	8x30 mesh (0,6 – 2,36 mm)
Moisture content	max. 5 %
Bulk density	approx. 530 kg/m^3
Hardness	min. 98 %
Ash content	max. 4 %

*Other granulations on demand

STORAGE

Activated carbon should be stored in sealed, unopened packages in dry place with temperature 5 – 40° C, away from sources of ignition and solvent vapours. Exposure to direct sunlight and moisture should be limited.

SAFETY

Wet activated carbon adsorbs oxygen from the air, what causes danger while working inside containers with activated carbon in closed or poorly ventilated places.

Under certain conditions, during contact with oxidizing agents and some organic compounds such as ketones (e.g. acetone), acrylates, esters, volatile acids, amines etc. activated carbon may react exothermally. In case of rapid temperature increase cooling with water is recommended.

Typical applications

- Water purification
- Wastewater treatment
- Pool water filtration
- Production media filtration

Packaging

- 20 kg bags
- 500 kg big bags

ACES Sp. z o.o. reserves the right to change specification without notice.

ACES Sp. z o.o.
ul. Łużycka 10
81-537 Gdynia
tel. +48 58 622 63 50
aces@aces.pl