Watched Tracker API

Hoppscotch test collection. 53 requests in 10 folders, each with an automated status check.

How to read this document

Every endpoint starts with the baseUrl variable (see the environment PDF), so /users/ means <<baseUrl>>/users/. Text in << >> is a variable that Hoppscotch fills in. The Auth column says which token is sent in the Authorization: Bearer header. The Saves column lists variables that the request's test script stores for later requests. Run the folders in order, because later requests use the ids saved earlier.

Folder	Requests	What it checks
1 - Auth	6	Registering, logging in, a wrong password, and refreshing a token.
2 - Users	4	Listing, reading and updating users, and the 401 without a token.
3 - Roles	4	Create, read and update roles.
4 - Movies	5	CRUD for movies and a 404 for a missing one.
5 - Anime	5	CRUD for anime, including season and episode.
6 - K-Drama	5	CRUD for K-dramas and a 404 for a missing one.
7 - TV Series	5	CRUD for TV series, including season and episode.
8 - Type	5	Linking one media item to a type, and a 400 when two are sent.
9 - Permissions (normal user)	6	A normal user can read but gets 403 on create, update, delete and roles.
10 - Delete (run last)	8	Deletes everything the run created, then confirms the 404.

Folder 1 - Auth

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	Register (normal user)	POST	`/users/`	None	`{"first_name":"Test","last_name":"Viewer","username":"<<userUsername>>","email":"viewer@example.com","gender":"Other","password":"<<userPassword>>"}`	201	`userId`
2	Register without password (expect 400)	POST	`/users/`	None	`{"username":"nopass","email":"x@example.com"}`	400	-
3	Login (admin)	POST	`/login/`	None	`{"username":"<<adminUsername>>","password":"<<adminPassword>>"}`	200	`accessToken, refreshToken`
4	Login (normal user)	POST	`/login/`	None	`{"username":"<<userUsername>>","password":"<<userPassword>>"}`	200	`userAccessToken`
5	Login with wrong password (expect 401)	POST	`/login/`	None	`{"username":"<<adminUsername>>","password":"definitely-wrong"}`	401	-
6	Refresh token	POST	`/token/refresh/`	None	`{"refresh":"<<refreshToken>>"}`	200	`accessToken`

Folder 2 - Users

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List users	GET	`/users/`	Admin token	-	200	-
2	Get user	GET	`/users/<<userId>>/`	Admin token	-	200	-
3	Update user (no password needed)	PUT	`/users/<<userId>>/`	Admin token	`{"first_name":"Test","last_name":"Viewer Updated","username":"<<userUsername>>","email":"viewer@example.com","gender":"Other"}`	200	-
4	List users without token (expect 401)	GET	`/users/`	None	-	401	-

Folder 3 - Roles

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List roles	GET	`/roles/`	Admin token	-	200	-
2	Create role	POST	`/roles/`	Admin token	`{"name":"Tester"}`	201	`roleId`
3	Get role	GET	`/roles/<<roleId>>/`	Admin token	-	200	-
4	Update role	PUT	`/roles/<<roleId>>/`	Admin token	`{"name":"Tester Updated"}`	200	-

Folder 4 - Movies

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List 4 - Movies	GET	`/movies/`	Admin token	-	200	-
2	Create 4 - Movies	POST	`/movies/`	Admin token	`{"movie_name":"Inception"}`	201	`movieId`
3	Get 4 - Movies	GET	`/movies/<<movieId>>/`	Admin token	-	200	-
4	Update 4 - Movies	PUT	`/movies/<<movieId>>/`	Admin token	`{"movie_name":"Inception (2010)"}`	200	-
5	Get missing 4 - Movies (expect 404)	GET	`/movies/999999/`	Admin token	-	404	-

Folder 5 - Anime

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List 5 - Anime	GET	`/anime/`	Admin token	-	200	-
2	Create 5 - Anime	POST	`/anime/`	Admin token	`{"anime_name":"Attack on Titan","season":1,"episode":5}`	201	`animeId`
3	Get 5 - Anime	GET	`/anime/<<animeId>>/`	Admin token	-	200	-
4	Update 5 - Anime	PUT	`/anime/<<animeId>>/`	Admin token	`{"anime_name":"Attack on Titan","season":2,"episode":10}`	200	-
5	Get missing 5 - Anime (expect 404)	GET	`/anime/999999/`	Admin token	-	404	-

Folder 6 - K-Drama

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List 6 - K-Drama	GET	`/kdrama/`	Admin token	-	200	-
2	Create 6 - K-Drama	POST	`/kdrama/`	Admin token	`{"kdrama_name":"Crash Landing on You"}`	201	`kdramaId`
3	Get 6 - K-Drama	GET	`/kdrama/<<kdramaId>>/`	Admin token	-	200	-
4	Update 6 - K-Drama	PUT	`/kdrama/<<kdramaId>>/`	Admin token	`{"kdrama_name":"Crash Landing on You (2019)"}`	200	-
5	Get missing 6 - K-Drama (expect 404)	GET	`/kdrama/999999/`	Admin token	-	404	-

Folder 7 - TV Series

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List 7 - TV Series	GET	`/tvseries/`	Admin token	-	200	-
2	Create 7 - TV Series	POST	`/tvseries/`	Admin token	`{"tv_series":"Breaking Bad","season":1,"episode":3}`	201	`tvId`
3	Get 7 - TV Series	GET	`/tvseries/<<tvId>>/`	Admin token	-	200	-
4	Update 7 - TV Series	PUT	`/tvseries/<<tvId>>/`	Admin token	`{"tv_series":"Breaking Bad","season":2,"episode":7}`	200	-
5	Get missing 7 - TV Series (expect 404)	GET	`/tvseries/999999/`	Admin token	-	404	-

Folder 8 - Type

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List types	GET	`/type/`	Admin token	-	200	-
2	Create type (movie)	POST	`/type/`	Admin token	`{"movie":<<movieId>>}`	201	`typeId`
3	Create type with two media (expect 400)	POST	`/type/`	Admin token	`{"movie":<<movieId>>,"anime":<<animeId>>}`	400	-
4	Get type	GET	`/type/<<typeId>>/`	Admin token	-	200	-
5	Update type (switch to anime)	PUT	`/type/<<typeId>>/`	Admin token	`{"movie":null,"anime":<<animeId>>,"kdrama":null,"tv_series":null}`	200	-

Folder 9 - Permissions (normal user)

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	List movies as normal user (allowed)	GET	`/movies/`	Normal user token	-	200	-
2	Create movie as normal user (expect 403)	POST	`/movies/`	Normal user token	`{"movie_name":"Not allowed"}`	403	-
3	Update movie as normal user (expect 403)	PUT	`/movies/<<movieId>>/`	Normal user token	`{"movie_name":"Not allowed"}`	403	-
4	Delete movie as normal user (expect 403)	DELETE	`/movies/<<movieId>>/`	Normal user token	-	403	-
5	Create role as normal user (expect 403)	POST	`/roles/`	Normal user token	`{"name":"Hacker"}`	403	-
6	List movies without token (expect 401)	GET	`/movies/`	None	-	401	-

Folder 10 - Delete (run last)

#	Request	Method	Endpoint	Auth	Request body	Expect	Saves
1	Delete type	DELETE	`/type/<<typeId>>/`	Admin token	-	204	-
2	Delete movie	DELETE	`/movies/<<movieId>>/`	Admin token	-	204	-
3	Delete anime	DELETE	`/anime/<<animeId>>/`	Admin token	-	204	-
4	Delete K-Drama	DELETE	`/kdrama/<<kdramaId>>/`	Admin token	-	204	-
5	Delete TV series	DELETE	`/tvseries/<<tvId>>/`	Admin token	-	204	-
6	Delete role	DELETE	`/roles/<<roleId>>/`	Admin token	-	204	-
7	Delete user	DELETE	`/users/<<userId>>/`	Admin token	-	204	-
8	Get deleted movie (expect 404)	GET	`/movies/<<movieId>>/`	Admin token	-	404	-