Watched Tracker (local)

Hoppscotch environment. 15 variables used by the collection.

What this is

An environment is a set of named values that Hoppscotch swaps into requests wherever you see <<name>>. This one points the collection at the local Django server and holds the test accounts. The empty variables are filled in automatically while the collection runs, so leave them blank.

Variable	Initial value	Set by	Purpose
`baseUrl`	`http://127.0.0.1:8000/api`	You	Address of the API. This points to the local Django server.
`adminUsername`	`admin`	You	Admin account used by the Login (admin) request.
`adminPassword`	`admin12345`	You	Password of that admin account.
`userUsername`	`viewer`	You	Username given to the normal test user.
`userPassword`	`viewer12345`	You	Password of the normal test user.
`accessToken`	`(empty)`	Test script	Admin access token. Filled in by Login (admin) and Refresh token.
`refreshToken`	`(empty)`	Test script	Admin refresh token. Filled in by Login (admin).
`userAccessToken`	`(empty)`	Test script	Normal user access token. Filled in by Login (normal user).
`userId`	`(empty)`	Test script	Id of the test user. Filled in by Register (normal user).
`roleId`	`(empty)`	Test script	Id of the test role. Filled in by Create role.
`movieId`	`(empty)`	Test script	Id of the test movie. Filled in by Create 4 - Movies.
`animeId`	`(empty)`	Test script	Id of the test anime. Filled in by Create 5 - Anime.
`kdramaId`	`(empty)`	Test script	Id of the test K-drama. Filled in by Create 6 - K-Drama.
`tvId`	`(empty)`	Test script	Id of the test TV series. Filled in by Create 7 - TV Series.
`typeId`	`(empty)`	Test script	Id of the test type. Filled in by Create type (movie).

Setting it up

1. Start the local server: python manage.py runserver (it listens on http://127.0.0.1:8000).
2. Create the admin account with the username and password above, and give it the Admin role.
3. In Hoppscotch, import the collection and this environment, then select the environment in the top-right menu.
4. Run the folders in order, from 1 - Auth to 10 - Delete. Folder 10 removes the test data, so run it last.

Notes

The passwords above are throwaway local test values. To test the live site, change baseUrl to the Render API address (ending in /api) and use a real admin account, and do not commit real passwords to GitHub.