



ACM-ICPC World Finals 2017

Team Reference Document

University of Illinois at Urbana-Champaign:
Time Limit Exceeded

Coach

Uttam Thakore

Contestants

Yewen Fan, Tong Li, Yuting Zhang

Contents

| | | | | |
|----------|--|-----------|----------|---|
| 1 | Data Structures | 2 | | |
| 1.1 | Bitmasks | 2 | 3.10 | Schröder-Hipparchus Number 17 |
| 1.2 | Union-Find Disjoint Sets | 2 | 3.11 | Catalan Numbers 17 |
| 1.3 | Segment Tree | 2 | 4 | Computational Geometry |
| 1.4 | Fenwick Tree | 3 | | |
| 1.5 | Treap | 3 | 5 | String Processing |
| 1.6 | Splay | 4 | | |
| 1.7 | Trie | 6 | 5.1 | KMP 22 |
| 1.8 | Kth Element | 6 | 5.2 | Suffix Array 23 |
| 2 | Graph Theory | 7 | 6 | Sundry |
| 2.1 | Articulation Points and Bridges | 7 | | |
| 2.2 | Tarjan's Algorithm | 8 | 6.1 | Day of some Date 25 |
| 2.3 | Bipartite Graph Check | 9 | 6.2 | Java 25 |
| 2.4 | Kruskal's Algorithm | 9 | | |
| 2.5 | Prim's Algorithm | 9 | | |
| 2.6 | Dijkstra's Algorithm | 10 | | |
| 2.7 | Bellman Ford's Algorithm | 10 | | |
| 2.8 | Floyd Warshall's Algorithm | 10 | | |
| 2.9 | Shortest Path Faster Algorithm | 10 | | |
| 2.10 | Network Flow | 11 | | |
| 2.11 | Euler Tour | 11 | | |
| 2.12 | Max Cardinality Bipartite Matching | 12 | | |
| 2.13 | Min-Cost Flow | 13 | | |
| 3 | Math | 14 | | |
| 3.1 | Sieve of Eratosthenes | 14 | | |
| 3.2 | Euler Phi function | 14 | | |
| 3.3 | GCD mod related (CRT) | 14 | | |
| 3.4 | Enumerate Combination | 14 | | |
| 3.5 | Gauss Elimination | 15 | | |
| 3.6 | FFT | 15 | | |
| 3.7 | Simplex | 16 | | |
| 3.8 | Pell Function | 17 | | |
| 3.9 | 二次剩余 | 17 | | |

1 Data Structures

1.1 Bitmasks

```
#define lowBit(S) (S & (-S))
#define setAll(S, n) (S = (1 << n) - 1)
#define modulo(S, N) ((S) & (N - 1)) // returns S % N, where N
    is a power of 2
#define isPowerOfTwo(S) (!(S & (S - 1)))
#define nearestPowerOfTwo(S) ((int)pow(2.0,
    (int)((log((double)S) / log(2.0)) + 0.5)))
#define turnOffLastBit(S) ((S) & (S - 1))
#define turnOnLastZero(S) ((S) | (S + 1))
#define turnOffLastConsecutiveBits(S) ((S) & (S + 1))
#define turnOnLastConsecutiveZeroes(S) ((S) | (S - 1))
```

1.2 Union-Find Disjoint Sets

```
struct DisjointSets{
    void addelements(int num){
        while (num-->0)
            s.push_back(-1);
    }
    int find(int elem) {
        return s[elem] < 0 ? elem : s[elem] = find(s[elem]);
    }
    void setunion(int a, int b) {
        int root1 = find(a), root2 = find(b);
        int newSize = s[root1] + s[root2];
        if (s[root1] <= s[root2]){
            s[root2] = root1;
            s[root1] = newSize;
        }
        else{
            s[root1] = root2;
            s[root2] = newSize;
        }
    }
    vector<int> s;
};
```

1.3 Segment Tree

```
// Segment tree for range sum queries.
struct segment_tree {
    vector<long long> st, lazy;
    const vector<long long> &A;
    size_t n;
    inline int left(int p) { return p << 1;}
    inline int right(int p) { return (p << 1) + 1; }
    void propagate(int p, int L, int R) {
        if (lazy[p] != 0) {
            if (L != R) {
                lazy[left(p)] += lazy[p];
                lazy[right(p)] += lazy[p];
            }
            st[p] += (R - L + 1) * lazy[p];
            lazy[p] = 0;
        }
    }
    void build(int p, int L, int R) {
        if (L == R)
            st[p] = A[L];
        else {
            build(left(p), L, (L + R) / 2);
            build(right(p), (L + R) / 2 + 1, R);
            st[p] = st[left(p)] + st[right(p)];
        }
    }
    long long update(int p, int L, int R, int i, int j, long
        long val) {
        propagate(p, L, R);
        if (L > j || R < i)
            return st[p];
        if (L >= i && R <= j) {
            lazy[p] = val;
            propagate(p, L, R);
            return st[p];
        }
        return st[p] = update(left(p), L, (L + R) / 2, i, j,
            val) +
            update(right(p), (L + R) / 2 + 1, R, i, j,
                val);
    }
};
```

```

}
long long query(int p, int L, int R, int i, int j) {
    if (L > j || R < i)
        return 0;
    propagate(p, L, R);
    if (L >= i && R <= j)
        return st[p];
    return query(left(p), L, (L + R) / 2, i, j) +
           query(right(p), (L + R) / 2 + 1, R, i, j);
}
segment_tree(const vector<long long> &A): A(_A) {
    n = A.size();
    st.assign(n * 4, 0);
    lazy.assign(n * 4, 0);
    build(1, 0, n - 1);
}
void update(int i, int j, long long val) {
    update(1, 0, n - 1, i, j, val);
}
long long query(int i, int j) {
    return query(1, 0, n - 1, i, j);
}
};

```

1.4 Fenwick Tree

```

#define LSOne(S) (S & (-S))
class FenwickTree {
private:
    vi ft;
public:
    FenwickTree() {}
    // initialization: n + 1 zeroes, ignore index 0
    FenwickTree(int n) { ft.assign(n + 1, 0); }
    int rsq(int b) { // returns
        RSQ(1, b)
        int sum = 0; for (; b; b -= LSOne(b)) sum += ft[b];
        return sum; }
    int rsq(int a, int b) { // returns
        RSQ(a, b)

```

```

        return rsq(b) - (a == 1 ? 0 : rsq(a - 1)); }
    // adjusts value of the k-th element by v (v can be +ve/inc
    // or -ve/dec)
    void adjust(int k, int v) { // note: n =
        ft.size() - 1
        for (; k < (int)ft.size(); k += LSOne(k)) ft[k] += v; }
};

```

1.5 Treap

```

template<typename T>
struct treap{
    treap(){
        srand(time(0));
        root = nullptr;
    }
    void insert(const T& elem){
        insert(root, elem);
    }
    void remove(const T& elem){
        remove(root, elem);
    }
    struct node_t{
        T elem;
        shared_ptr<node_t> left, right;
        int priority;
    };

    shared_ptr<node_t> root;
    shared_ptr<node_t> rotateLeft(shared_ptr<node_t> node){
        shared_ptr<node_t> right = node->right, rightLeft =
            right->left;
        right->left = node;
        node->right = rightLeft;
        return right;
    }

    shared_ptr<node_t> rotateRight(shared_ptr<node_t> node){
        shared_ptr<node_t> left = node->left, leftRight =

```

```

        left->right;
    left->right = node;
    node->left = leftRight;
    return left;
}
void insert(shared_ptr<node_t>& node, const T& elem){
    if (node == nullptr){
        node = make_shared<node_t>();
        node->elem = elem;
        node->left = node->right = nullptr;
        node->priority = rand();
        return;
    }
    // We do not allow multiple keys with the same value
    if (node->elem == elem)
        return;

    if (node->elem > elem){
        insert(node->left, elem);
        if (node->priority < node->left->priority)
            node = rotateRight(node);
    }else{
        insert(node->right, elem);
        if (node->priority < node->right->priority)
            node = rotateLeft(node);
    }
}
void remove(shared_ptr<node_t>& node, const T& elem){
    if (node == nullptr)
        return;
    if (node->elem == elem){
        if (!node->left && !node->right)
            node = nullptr;
        // Keep rotating until the node to be deleted becomes
        // a leaf node.
        else if (!node->left || (node->left && node->right &&
            node->left->priority < node->right->priority)){
            node = rotateLeft(node);
            remove(node->left, elem);
        }
        else{

```

```

            node = rotateRight(node);
            remove(node->right, elem);
        }
    }
    else if (node->elem > elem)
        remove(node->right, elem);
    else
        remove(node->left, elem);
}
};

```

1.6 Splay

```

const int maxNodeCnt = 111111;
int nodeCnt, root, type[maxNodeCnt], parent[maxNodeCnt],
    childs[maxNodeCnt][2],
    size[maxNodeCnt], stack[maxNodeCnt], reversed[maxNodeCnt];
// ...
void clear() {
    root = 0;
    size[0] = 0;
    nodeCnt = 1;
}
int malloc() {
    type[nodeCnt] = 2;
    childs[nodeCnt][0] = childs[nodeCnt][1] = 0;
    size[nodeCnt] = 1;
    reversed[nodeCnt] = 0;
    return nodeCnt++;
}
void update(int x) {
    size[x] = size[childs[x][0]] + 1 + size[childs[x][1]];
    // ...
}
void pass(int x) {
    // NOTICE: childs[x][i] == 0
    if (reversed[x]) {
        swap(childs[x][0], childs[x][1]);
        type[childs[x][0]] = 0;
        reversed[childs[x][0]] ^= 1;
    }
}

```

```

        type[childs[x][1]] = 1;
        107reversed[childs[x][1]] ^= 1;
        reversed[x] = 0;
    }
    // ...
}

void rotate(int x) {
    int t = type[x],
        y = parent[x],
        z = childs[x][1 - t];
    type[x] = type[y];
    parent[x] = parent[y];
    if (type[x] != 2) {
        childs[parent[x]][type[x]] = x;
    }
    type[y] = 1 - t;
    parent[y] = x;
    childs[x][1 - t] = y;
    if (z) {
        type[z] = t;
        parent[z] = y;
    }
    childs[y][t] = z;
    update(y);
}

void splay(int x) {
    int stackCnt = 0;
    stack[stackCnt++] = x;
    for (int i = x; type[i] != 2; i = parent[i]) {
        stack[stackCnt++] = parent[i];
    }
    for (int i = stackCnt - 1; i > -1; --i) {
        pass(stack[i]);
    }
    while (type[x] != 2) {
        int y = parent[x];
        if (type[x] == type[y]) {
            rotate(y);
        } else {
            rotate(x);
        }
    }
}

    }
    if (type[x] == 2) {
        break;
    }
    rotate(x);
}
update(x);
}

int find(int x, int rank) {
    while (true) {
        pass(x);
        if (size[childs[x][0]] + 1 == rank) {
            break;
        }
        if (rank <= size[childs[x][0]]) {
            x = childs[x][0];
        } else {
            rank -= size[childs[x][0]] + 1;
            x = childs[x][1];
        }
    }
    return x;
}

void split(int &x, int &y, int a) {
    // NOTICE: x, y != 0
    y = find(x, a + 1);
    splay(y);
    x = childs[y][0];
    type[x] = 2;
    childs[y][0] = 0;
    update(y);
}

void split3(int &x, int &y, int &z, int a, int b) {
    split(x, z, b);
    split(x, y, a - 1);
}

void join(int &x, int y) {
    // NOTICE x, y != 0
    x = find(x, size[x]);
    splay(x);
}

```

```

    childs[x][1] = y;
    type[y] = 1;
    parent[y] = x;
    109update(x);
}
void join3(int &x, int y, int z) {
    join(y, z);
    join(x, y);
}
int getRank(int x) {
    splay(x);
    root = x;
    return size[childs[x][0]];
}
void reverse(int a, int b) {
    int x, y;
    split3(root, x, y, a + 1, b + 1);
    reversed[x] ^= 1;
    join3(root, x, y);
}

```

1.7 Trie

```

const int maxnode = 4000 * 100 + 10;
const int sigma_size = 26;

// This template use unnecessary large memory.
// should replace ch[maxnode][sigma_size] by vector<node>.
struct Trie {
    int ch[maxnode][sigma_size];
    int val[maxnode];
    int sz; // the number of node
    void clear() { sz = 1; memset(ch[0], 0, sizeof(ch[0])); }
    int idx(char c) { return c - 'a'; }

    // insert string s, with additional information v
    // v has to be non-zero, zero means "this node is not word
    // node"
    void insert(const char *s, int v) {

```

```

        int u = 0, n = strlen(s);
        for(int i = 0; i < n; i++) {
            int c = idx(s[i]);
            if(!ch[u][c]) { // the node not exist
                memset(ch[sz], 0, sizeof(ch[sz]));
                val[sz] = 0;
                ch[u][c] = sz++;
            }
            u = ch[u][c]; // going down
        }
        val[u] = v;
    }
};

```

1.8 Kth Element

```

const int D = 18;
const int N = 100000;
int n, value[N], rank[N], order[D][N], pos[D][N];
long long sum[D][N];
pair<int, int> backup[N];
void build (int d, int l, int r) {
    if (r - l > 1) {
        int m = (l + r) >> 1,
            curLeft = l,
            curRight = m;
        for (int i = l; i < r; ++i) {
            if (rank[order[d][i]] < m) {
                order[d + 1][curLeft++] = order[d][i];
            } else {
                order[d + 1][curRight++] = order[d][i];
            }
            pos[d][i] = curLeft;
        }
        build(d + 1, l, m);
        build(d + 1, m, r);
    }
    sum[d][r - 1] = value[order[d][r - 1]];
    for (int i = r - 2; i >= l; --i) {
        sum[d][i] = value[order[d][i]] + sum[d][i + 1];
    }
}

```

```

    }
}
// [l, r) [a, b) k-th sum
long long query (int d, int l, int r, int a, int b, int k) {
    if (k) {
        if (r - l == 1) {
            return sum[d][a];
        }
        int m = (l + r) >> 1,
            posBegin = pos[d][a];
        if (rank[order[d][a]] < m) {
            posBegin -= 1;
        }
        int posEnd = pos[d][b - 1],
            posCnt = posEnd - posBegin;
        if (k < posCnt) {
            return query(d + 1, l, m, posBegin, pos[d][b - 1], k);
        }
#define RIGHT(i) m + i + 1 - pos[d][i]
        int rightBegin = RIGHT(a);
        if (rank[order[d][a]] >= m) {
            rightBegin -= 1;
        }
        long long result = (posBegin < m? sum[d + 1][posBegin]:
            0) - (posEnd <
                m? sum[d + 1][posEnd]: 0);
        result += query(d + 1, m, r, rightBegin, RIGHT(b - 1), k
            - posCnt);
#undef RIGHT
        return result;
    }
    return 0;
}

void clear () {
    for (int i = 0; i < n; ++ i) {
        order[0][i] = i;
    }
    build(0, 0, n);
}

int main(){

```

```

    std::ios::sync_with_stdio(false);
    int testCount;
    scanf("%d", &testCount);
    for(int t = 1; t <= testCount; ++ t){
        std::cout << "Case #" << t << ":\n";
        scanf("%d", &n);
        for(int i = 0; i < n; ++ i){
            scanf("%d", value + i);
            backup[i] = std::make_pair(value[i], i);
        }
        std::sort(backup, backup + n);
        for(int i = 0; i < n; ++ i){
            rank[backup[i].second] = i;
        }
        int m;
        scanf("%d", &m);
        while(m --){
            int a, b;
            scanf("%d%d", &a, &b);
            b ++;
            int length = b - a;
            long long result = sum[0][a] - (b < n? sum[0][b]: 0);
            result -= query(0, 0, n, a, b, (length + 1) >> 1);
            result -= query(0, 0, n, a, b, length >> 1);
            std::cout << result << "\n";
        }
        std::cout << "\n";
    }
    return 0;
}

```

2 Graph Theory

2.1 Articulation Points and Bridges

```

vi dfs_low; // additional information for articulation
              points/bridges/SCCs
vi articulation_vertex;
int dfsNumberCounter, dfsRoot, rootChildren;
int DFS_WHITE = -1; // unvisited

```



```

void articulationPointAndBridge(int u) {
    dfs_low[u] = dfs_num[u] = dfsNumberCounter++; // dfs_low[u]
    <= dfs_num[u]
    for (int j = 0; j < (int)AdjList[u].size(); j++) {
        ii v = AdjList[u][j];
        if (dfs_num[v.first] == DFS_WHITE) {                // a
            tree edge
            dfs_parent[v.first] = u;
            if (u == dfsRoot) rootChildren++; // special case, count
            children of root

            articulationPointAndBridge(v.first);

            if (dfs_low[v.first] >= dfs_num[u])                // for
                articulation point
                articulation_vertex[u] = true;                // store this
                information first
            if (dfs_low[v.first] > dfs_num[u])                // for
                bridge
                printf(" Edge (%d, %d) is a bridge\n", u, v.first);
                dfs_low[u] = min(dfs_low[u], dfs_low[v.first]); // update
                dfs_low[u]
        }
        else if (v.first != dfs_parent[u]) // a back edge and not
            direct cycle
            dfs_low[u] = min(dfs_low[u], dfs_num[v.first]); // update
            dfs_low[u]
    } }

//inside int main()
printThis("Articulation Points & Bridges (the input graph
    must be UNDIRECTED)");
dfsNumberCounter = 0; dfs_num.assign(V, DFS_WHITE);
dfs_low.assign(V, 0);
dfs_parent.assign(V, -1); articulation_vertex.assign(V, 0);
printf("Bridges:\n");
for (int i = 0; i < V; i++)
    if (dfs_num[i] == DFS_WHITE) {
        dfsRoot = i; rootChildren = 0;

```

```

        articulationPointAndBridge(i);
        articulation_vertex[dfsRoot] = (rootChildren > 1); } //
        special case
    printf("Articulation Points:\n");
    for (int i = 0; i < V; i++)
        if (articulation_vertex[i])
            printf(" Vertex %d\n", i);

```

2.2 Tarjan's Algorithm

```

vi S, visited; // additional global
variables
int numSCC;

void tarjanSCC(int u) {
    dfs_low[u] = dfs_num[u] = dfsNumberCounter++; // dfs_low[u]
    <= dfs_num[u]
    S.push_back(u); // stores u in a vector based on order
    of visitation
    visited[u] = 1;
    for (int j = 0; j < (int)AdjList[u].size(); j++) {
        ii v = AdjList[u][j];
        if (dfs_num[v.first] == DFS_WHITE)
            tarjanSCC(v.first);
        if (visited[v.first]) // condition
            for update
            dfs_low[u] = min(dfs_low[u], dfs_low[v.first]);
    }

    if (dfs_low[u] == dfs_num[u]) { // if this is a root
        (start) of an SCC
        printf("SCC %d:", ++numSCC); // this part is done
        after recursion
        while (1) {
            int v = S.back(); S.pop_back(); visited[v] = 0;
            printf(" %d", v);
            if (u == v) break;
        }
        printf("\n");
    }

```

```

} }

//inside int main()
printThis("Strongly Connected Components (the input graph
must be DIRECTED)");
dfs_num.assign(V, DFS_WHITE); dfs_low.assign(V, 0);
visited.assign(V, 0);
dfsNumberCounter = numSCC = 0;
for (int i = 0; i < V; i++)
    if (dfs_num[i] == DFS_WHITE)
        tarjanSCC(i);

```

2.3 Bipartite Graph Check

```

queue<int> q; q.push(s);
vi color(V, INF); color[s] = 0;
bool isBipartite = true;
while (!q.empty() & isBipartite){
    int u = q.front(); q.pop();
    for (int j = 0; j < (int)AdjList[u].size(); j++){
        ii v = AdjList[u][j];
        if (color[v.first] == INF){
            color[v.first] = 1 - color[u];
            q.push(v.first);
        }
        else if (color[v.first] == color[u]){
            isBipartite = false; break;
        }
    }
}

```

2.4 Kruskal's Algorithm

```

vector< pair<int, ii> > EdgeList; // (weight, two vertices
of the edge
for (int i = 0; i < E; i++) {
    scanf("%d %d %d", &u, &v, &w); // read the triple: (u,
v, w)
    EdgeList.push_back(make_pair(w, ii(u, v))); // (w, u,
v)
    AdjList[u].push_back(ii(v, w));
    AdjList[v].push_back(ii(u, w));
}

```

```

}
sort(EdgeList.begin(), EdgeList.end()); // sort by edge
weight O(E log E)
// note: pair object has built-in comparison
function
int mst_cost = 0;
UnionFind UF(V); // all V are disjoint sets
initially
for (int i = 0; i < E; i++) { // for each edge,
O(E)
    pair<int, ii> front = EdgeList[i];
    if (!UF.isSameSet(front.second.first, front.second.second))
        { // check
            mst_cost += front.first; // add the weight of e
to MST
            UF.unionSet(front.second.first, front.second.second); //
link them
        }
} // note: the runtime cost of UFDS is
very light

// note: the number of disjoint sets must eventually be 1 for
a valid MST
printf("MST cost = %d (Kruskal's)\n", mst_cost);

```

2.5 Prim's Algorithm

```

vi taken; // global boolean flag to
avoid cycle
priority_queue<ii> pq; // priority queue to help choose
shorter edges

void process(int vtx) { // so, we use -ve sign to reverse the
sort order
    taken[vtx] = 1;
    for (int j = 0; j < (int)AdjList[vtx].size(); j++) {
        ii v = AdjList[vtx][j];
        if (!taken[v.first]) pq.push(ii(-v.second, -v.first));
    } // sort by (inc) weight then by
(inc) id
}

```

```
// inside int main() --- assume the graph is stored in AdjList,
    pq is empty
    taken.assign(V, 0);           // no vertex is taken at the
        beginning
    process(0); // take vertex 0 and process all edges incident
        to vertex 0
    mst_cost = 0;
    while (!pq.empty()) { // repeat until V vertices (E=V-1
        edges) are taken
        ii front = pq.top(); pq.pop();
        u = -front.second, w = -front.first; // negate the id and
            weight again
        if (!taken[u])           // we have not connected this
            vertex yet
            mst_cost += w, process(u); // take u, process all edges
                incident to u
    }                             // each edge is in pq only
        once!
    printf("MST cost = %d (Prim's)\n", mst_cost);
```

2.6 Dijkstra's Algorithm

```
// Dijkstra routine
vi dist(V, INF); dist[s] = 0;           // INF = 1B to
    avoid overflow
priority_queue< ii, vector<ii>, greater<ii> > pq;
    pq.push(ii(0, s));
        // ^to sort the pairs by increasing
            distance from s
while (!pq.empty()) {                             //
    main loop
    ii front = pq.top(); pq.pop(); // greedy: pick shortest
        unvisited vertex
    int d = front.first, u = front.second;
    if (d > dist[u]) continue; // this check is important, see
        the explanation
    for (int j = 0; j < (int)AdjList[u].size(); j++) {
        ii v = AdjList[u][j];           // all outgoing
            edges from u
```

```
        if (dist[u] + v.second < dist[v.first]) {
            dist[v.first] = dist[u] + v.second;           // relax
                operation
            pq.push(ii(dist[v.first], v.first));
        } } // note: this variant can cause duplicate items in the
            priority queue
```

2.7 Bellman Ford's Algorithm

```
// Bellman Ford routine
vi dist(V, INF); dist[s] = 0;
for (int i = 0; i < V - 1; i++) // relax all E edges V-1
    times, overall O(VE)
    for (int u = 0; u < V; u++)           // these two
        loops = O(E)
        for (int j = 0; j < (int)AdjList[u].size(); j++) {
            ii v = AdjList[u][j]; // we can record SP spanning
                here if needed
            dist[v.first] = min(dist[v.first], dist[u] + v.second);
                // relax
        }
    }
```

2.8 Floyd Warshall's Algorithm

```
for (int k = 0; k < V; k++) // common error: remember that
    loop order is k->i->j
    for (int i = 0; i < V; i++)
        for (int j = 0; j < V; j++)
            AdjMatrix[i][j] = min(AdjMatrix[i][j], AdjMatrix[i][k] +
                AdjMatrix[k][j]);
```

2.9 Shortest Path Faster Algorithm

```
// SPFA from source S
// initially, only S has dist = 0 and in the queue
vi dist(n, INF); dist[S] = 0;
queue<int> q; q.push(S);
vi in_queue(n, 0); in_queue[S] = 1;
```

```

while (!q.empty()) {
    int u = q.front(); q.pop(); in_queue[u] = 0;
    for (j = 0; j < (int)AdjList[u].size(); j++) { // all
        outgoing edges from u
        int v = AdjList[u][j].first, weight_u_v =
            AdjList[u][j].second;
        if (dist[u] + weight_u_v < dist[v]) { // if can relax
            dist[v] = dist[u] + weight_u_v; // relax
            if (!in_queue[v]) { // add to the queue only if it's
                not in the queue
                q.push(v);
                in_queue[v] = 1;
            }}
    }}}

```

2.10 Network Flow

```

void augment(int v, int min_edge){
    if (v == s){
        flow = min_edge;
        return;
    }
    else if (parent[v] != -1){
        int u = parent[v];
        augment(u, min(min_edge, residue[u][v]));
        residue[u][v] -= flow;
        residue[v][u] += flow;
    }
}

void Dinic(){
    max_flow = 0;
    while (true){
        parent.assign(V, -1);
        vector<bool> visited(V, false);
        queue<int> q;
        q.push(s);
        visited[s] = true;
        while (!q.empty()){
            int u = q.front();
            q.pop();

```

```

        if (u == t)
            break;
        for (int v : adjList[u])
            if (!visited[v] && residue[u][v] > 0){
                parent[v] = u;
                visited[v] = true;
                q.push(v);
            }
        int new_flow = 0;
        for (int u : adjList[t]){
            if (residue[u][t] <= 0)
                continue;
            flow = 0;
            augment(u, residue[u][t]);
            residue[u][t] -= flow;
            residue[t][u] += flow;
            new_flow += flow;
        }
        if (new_flow == 0)
            break;
        max_flow += new_flow;
    }
}

```

2.11 Euler Tour

```

void Euler_tour(int u, list<int> &tour, list<int>::iterator it,
    vector<vector<pair<int, bool>>> &adj_list) {
    for (auto &edge : adj_list[u]) {
        if (edge.second) {
            int v = edge.first;
            edge.second = false;
            for (auto &bi_edge : adj_list[v])
                if (bi_edge.first == u && bi_edge.second) {
                    bi_edge.second = false;
                    break;
                }
            Euler_tour(v, tour, tour.insert(it, u), adj_list);
        }
    }
}

```

2.12 Max Cardinality Bipartite Matching

```

int N, M, P, limit;
#define MAXN 50500
#define MAXE 150500
int pair_left[MAXN], pair_right[MAXN], dist_left[MAXN],
    dist_right[MAXN];
bool visited[MAXN];
int adjlist[MAXN];
int node[MAXE];
int link[MAXE];
bool BFS() {
    queue<int> q;
    memset(dist_right, -1, sizeof dist_right);
    memset(dist_left, -1, sizeof dist_left);
    for (int i = 0; i < N; i++) {
        if (pair_left[i] == -1) {
            dist_left[i] = 0;
            q.push(i);
        }
    }
    limit = INT_MAX;
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        if (dist_left[u] > limit)
            break;
        for (int i = adjlist[u]; i != -1; i = link[i]) {
            int v = node[i];
            if (dist_right[v] == -1) {
                dist_right[v] = dist_left[u] + 1;
                if (pair_right[v] == -1)
                    limit = dist_right[v];
            }
            else {
                dist_left[pair_right[v]] = dist_right[v] + 1;
                q.push(pair_right[v]);
            }
        }
    }
    return limit != INT_MAX;
}

bool DFS(int u) {

```

```

    for (int i = adjlist[u]; i != -1; i = link[i]) {
        int v = node[i];
        if (!visited[v] && dist_right[v] == dist_left[u] + 1) {
            visited[v] = true;
            if (pair_right[v] != -1 && dist_right[v] == limit)
                continue;
            if (pair_right[v] == -1 || DFS(pair_right[v])) {
                pair_right[v] = u;
                pair_left[u] = v;
                return true;
            }
        }
    }
    return false;
}

int main() {
    scanf("%d %d %d", &N, &M, &P);

    memset(pair_left, -1, sizeof pair_left);
    memset(pair_right, -1, sizeof pair_right);
    memset(link, -1, sizeof link);
    memset(adjlist, -1, sizeof adjlist);

    for (int i = 0; i < P; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        node[i] = v - 1;
        link[i] = adjlist[u - 1];
        adjlist[u - 1] = i;
    }

    int matching = 0;
    while (BFS()) {
        memset(visited, 0, sizeof visited);
        for (int i = 0; i < N; i++)
            if (pair_left[i] == -1)
                if (DFS(i))
                    matching++;
    }
    printf("%d\n", matching);
    return 0;
}

```

2.13 Min-Cost Flow

```

const int inf = 1000000000;
int s, t, node, totalCost;
vector<int> head, dist, vtx, next, c, cost;
vector<bool> vis;
void resize(vector<T> &a, int size, T init) //设大小、初始值
void init(int source, int target, int nodeCount)
    //初始化, 记得清空
void add(int a, int b, int cc, int cst) //双向加边
void spfa() {
    resize(vis, node, false); resize(dist, node, -inf);
    queue<int> q; q.push(t); vis[t]=true; dist[t]=0;
    while (q.size()) {
        int u = q.front(); q.pop();
        vis[u] = false;
        for (int p = head[u]; p != -1; p = next[p]) {
            if (c[p ^ 1] && dist[u] + cost[p ^ 1] > dist[vtx[p]]) {
                dist[vtx[p]] = dist[u] + cost[p ^ 1];
                if (!vis[vtx[p]]) {
                    vis[vtx[p]] = true; q.push(vtx[p]);
                    if (dist[q.back()] < dist[q.front()]) {
                        swap(q.front(), q.back());
                    }
                }
            }
        }
    }
}
int dfs(int u, int limit) {
    if (u == t) {
        totalCost += limit * dist[s];
        return limit;
    }
    int current = 0;
    vis[u] = true;
    for (int p = head[u]; p != -1; p = next[p]) {
        if (c[p] && !vis[vtx[p]] && dist[vtx[p]] + cost[p] ==
            dist[u]) {
            int delta = dfs(vtx[p], min(limit - current, c[p]));
            c[p] -= delta; c[p ^ 1] += delta;
            current += delta;
        }
    }
}

```

```

        if (current == limit) {
            break;
        }
    }
}
return current;
}
inline bool adjust() {
    int maxi = -inf;
    for (int i = 0; i < node; ++ i) {
        if (vis[i]) {
            for (int p = head[i]; p != -1; p = next[p]) {
                if (c[p] && !vis[vtx[p]]) {
                    assert(dist[vtx[p]] + cost[p] != dist[i]);
                    maxi = max(maxi, dist[vtx[p]] + cost[p] - dist[i]);
                }
            }
        }
    }
    if (maxi == -inf) {
        return false;
    }
    for (int i = 0; i < node; ++ i) {
        if (vis[i]) {
            dist[i] += maxi;
        }
    }
    return true;
}
int maxCostFlow() {
    spfa();
    totalCost = 0;
    do{
        do{
            resize(vis, node, false);
        }while (dfs(s, inf));
    }while (adjust());
    return totalCost;
}

```

3 Math

3.1 Sieve of Eratosthenes

```
#define BOUND 1000000
bitset<BOUND> bs;
vector<long long> primes;
void sieve() {
    bs.set();
    bs[0] = bs[1] = 0;
    for (long long i = 2; i <= BOUND; i++) {
        if (bs[i]) {
            for (long long j=i*i; j<=BOUND; j+=i) bs[j] = 0;
            primes.push_back(i);
        }
    }
}
```

3.2 Euler Phi function

```
int euler_phi(int n){
    int m = (int)sqrt(n+0.5);
    int ans = n;
    for(int i=2;i<=m;i++){
        if(n%i==0){
            ans = ans/i*(i-1);
            while(n%i==0) n /= i;
        }
    }
    if(n>1) ans = ans/n*(n-1);
    return ans;}
void euler_phi_table(int n, int *phi){
    for(int i=2;i<=n;i++) phi[i] = 0;
    phi[1] = 1;
    for(int i=2;i<=n;i++){
        if(!phi[i])
            for(int j=i;j<=n;j+=i){
                if(!phi[j]) phi[j] = j;
                phi[j] = phi[j]/i*(i-1);
            }
    }
}
```

3.3 GCD mod related (CRT)

```
//ax+by=gcd(a,b), min abs(x)+abs(y) x,y may be negative
void gcd(LL a, LL b, LL & d, LL & x, LL & y) {
    if(!b) { d = a; x = 1; y = 0; }
    else { gcd(b,a%b,d,y,x); y-=x*(a/b);}
}
// calculate inv(a) mod n. If not exist, return -1
LL inv(LL a, LL n) {
    LL d, x, y; gcd(a, n, d, x, y);
    return d == 1 ? (x+n)%n : -1; }
// n functions: x=a[i] (mod m[i]) m[i] co-prime
LL CRT(int n, int * a, int * m) {
    LL M = 1, d, y, x = 0;
    for(int i=0;i<n;i++) M *= m[i];
    for(int i=0;i<n;i++) {
        LL w = M / m[i];
        gcd(m[i], w, d, d, y);
        x = (x + y*w*a[i]) % M;
    }
    return (x+M)%M;}
// solve a^x=b mod n. n prime. If no solution, return -1
int log_mod(int a, int b, int n) {
    int m, v, e = 1;
    m = (int)sqrt(n+0.5);
    v = inv(pow_mod(a, m, n), n);
    map<int, int> x; x[1] = 0;
    for(int i=1;i<m;i++) {
        e = mul_mod(e, a, n);
        if(!x.count(e)) x[e] = i;
    }
    for(int i=0;i<m;i++) {
        if(x.count(b)) return i*m + x[b];
        b = mul_mod(b, v, n);
    }
    return -1;}
}
```

3.4 Enumerate Combination

```
const int maxn = 1000;
int com[maxn];
```

```

bool next_Com(int num, int k){ //0,1...num-1 choose k
    if(k == 0) return false;
    if(com[k-1]!=num-1){ com[k-1]++; return true;}
    int i;
    for(i=k-1;i>=0;i--){
        if(com[i]!=num-k+i) break;
    }
    if(i==-1) return false;
    com[i]++;
    for(int j=i+1;j<k;j++){
        com[j] = com[i]+(j-i);
    }
    return true; }
void makeFirstCom(int k){
    for(int i=0;i<k;i++) com[i] = i;
}

```

3.5 Gauss Elimination

```

const int maxn = 110;
typedef double Matrix[maxn][maxn];
// require matrix A invertible
// A is augmented matrix, A[i][n] = bi
// After execution, A[i][n] is the value of i-th variable
void gauss_elimination(Matrix A, int n) {
    int i, j, k, r;
    for (i=0; i<n; i++) {
        r = i;
        for (j=i+1; j<n; j++) {
            if (fabs(A[j][i]) > fabs(A[r][i])) r = j;
        }
        if (r != i)
            for (j=0; j<=n; j++)
                swap(A[r][j], A[i][j]);
        for (j=n; j>=i; j--)
            for (k=i+1; k<n; ++k)
                A[k][j] -= A[k][i] / A[i][i] * A[i][j];
    }
    for (i=n-1; i>=0; i--) {
        for (j=i+1; j<n; j++)
            A[i][n] -= A[j][n] * A[i][j];
    }
}

```

```

    A[i][n] /= A[i][i];
}
}

```

3.6 FFT

```

const long double PI = acos(0.0) * 2.0;
typedef complex<double> CD;
inline void FFT(vector<CD> &a, bool inverse) {
    int n = a.size();
    for(int i = 0, j = 0; i < n; i++) {
        if(j > i) swap(a[i], a[j]);
        int k = n;
        while(j & (k >= 1)) j ^= ~k;
        j |= k;
    }
    double pi = inverse ? -PI : PI;
    for(int step = 1; step < n; step <= 1) {
        double alpha = pi / step;
        for(int k = 0; k < step; k++) {
            CD omegak = exp(CD(0, alpha*k));
            for(int Ek = k; Ek < n; Ek += step < 1) {
                int Ok = Ek + step;
                CD t = omegak * a[Ok];
                a[Ok] = a[Ek] - t;
                a[Ek] += t;
            }
        }
    }
    if(inverse)
        for(int i = 0; i < n; i++) a[i] /= n;
}
inline vector<double> operator * (const vector<double>& v1,
    const vector<double>& v2) {
    int s1 = v1.size(), s2 = v2.size(), S = 2;
    while(S < s1 + s2) S <= 1;
    vector<CD> a(S,0), b(S,0);
    for(int i = 0; i < s1; i++) a[i] = v1[i];
    FFT(a, false);
    for(int i = 0; i < s2; i++) b[i] = v2[i];
}

```

```

FFT(b, false);
for(int i = 0; i < S; i++) a[i] *= b[i];
FFT(a, true);
vector<double> res(s1 + s2 - 1);
for(int i = 0; i < s1 + s2 - 1; i++) res[i] = a[i].real();
return res;
} // 用FFT实现的快速多项式乘法

```

3.7 Simplex

```

//输入矩阵a描述线性规划的标准形式。a为m+1行n+1列，其中行0~m-1为不等式
//行m为目标函数（最大化），列0~n-1为变量0~n-1的系数，列n为常数项
//第i个约束为a[i][0]*x[0] + a[i][1]*x[1] + ... <= a[i][n]
//目标为max(a[m][0]*x[0] + a[m][1]*x[1] + ... +
    a[m][n-1]*x[n-1] - a[m][n])
//注意：变量均有非负约束x[i] >= 0
const int maxm = 500; // 约束数目上限
const int maxn = 500; // 变量数目上限
const double INF = 1e100;
const double eps = 1e-10;
struct Simplex {
    int n; // 变量个数
    int m; // 约束个数
    double a[maxm][maxn]; // 输入矩阵
    int B[maxm], N[maxn]; // 算法辅助变量
    void pivot(int r, int c) {
        swap(N[c], B[r]);
        a[r][c] = 1 / a[r][c];
        for(int j = 0; j <= n; j++) if(j != c) a[r][j] *= a[r][c];
        for(int i = 0; i <= m; i++) if(i != r) {
            for(int j = 0; j <= n; j++) if(j != c) a[i][j] -= a[i][c]
                * a[r][j];
            a[i][c] = -a[i][c] * a[r][c];
        }
    }
    bool feasible() {
        for(;;) {
            int r, c;
            double p = INF;

```

```

            for(int i = 0; i < m; i++) if(a[i][n] < p) p = a[r = i][n];
            if(p > -eps) return true;
            p = 0;
            for(int i = 0; i < n; i++) if(a[r][i] < p) p = a[r][c = i];
            if(p > -eps) return false;
            p = a[r][n] / a[r][c];
            for(int i = r+1; i < m; i++) if(a[i][c] > eps) {
                double v = a[i][n] / a[i][c];
                if(v < p) { r = i; p = v; }
            }
            pivot(r, c);
        }
    }
    //解有界返回1，无解返回0，无界返回-1。b[i]为x[i]的值，ret为目标函数的值
    int simplex(int n, int m, double x[maxn], double& ret) {
        this->n = n;
        this->m = m;
        for(int i = 0; i < n; i++) N[i] = i;
        for(int i = 0; i < m; i++) B[i] = n+i;
        if(!feasible()) return 0;
        for(;;) {
            int r, c;
            double p = 0;
            for(int i = 0; i < n; i++) if(a[m][i] > p) p = a[m][c = i];
            if(p < eps) {
                for(int i = 0; i < n; i++) if(N[i] < n) x[N[i]] = 0;
                for(int i = 0; i < m; i++) if(B[i] < n) x[B[i]] =
                    a[i][n];
                ret = -a[m][n];
                return 1;
            }
            p = INF;
            for(int i = 0; i < m; i++) if(a[i][c] > eps) {
                double v = a[i][n] / a[i][c];
                if(v < p) { r = i; p = v; }
            }
            if(p == INF) return -1;
            pivot(r, c);
        }
    }
};

```

3.8 Pell Function

```
//求x^2-ny^2=1的最小正整数根,n不是完全平方数
p[1]=1;p[0]=0; q[1]=0;q[0]=1; a[2]=(int)(floor(sqrt(n)+1e-7));
g[1]=0;h[1]=1;
for (int i=2;i;++i) {
    g[i]=-g[i-1]+a[i]*h[i-1]; h[i]=(n-sqr(g[i]))/h[i-1];
    a[i+1]=(g[i]+a[2])/h[i]; p[i]=a[i]*p[i-1]+p[i-2];
    q[i]=a[i]*q[i-1]+q[i-2]; 检查p[i],q[i]是否为解, 如果是, 则退出
}
```

3.9 二次剩余

```
/*a*x^2+b*x+c==0 (mod P) 求0..P-1的根 */
int pDiv2,P,a,b,c,Pb,d;
inline int calc(int x,int Time){
    if (!Time) return 1; int tmp=calc(x,Time/2);
    tmp=(long long)tmp*tmp%P;
    if (Time&1) tmp=(long long)tmp*x%P; return tmp;
}
inline int rev(int x){ if (!x) return 0; return calc(x,P-2);}
inline void Compute(){
    while (1) { b=rand()%(P-2)+2; if (calc(b,pDiv2)+1==P)
        return; }
}
int main(){
    srand(time(0)^312314); int T;
    for (scanf("%d",&T);T;--T) {
        scanf("%d%d%d%d",&a,&b,&c,&P);
        if (P==2) {
            int cnt=0; for (int i=0;i<2;++i) if
                ((a*i+i*b*i+c)%P==0) ++cnt;
            printf("%d",cnt);
            for (int i=0;i<2;++i) if ((a*i+i*b*i+c)%P==0)
                printf(" %d",i);
            puts("");
        }else {
```

```
int delta=(long long)b*rev(a)*rev(2)%P;
a=(long long)c*rev(a)%P-sqr( (long long)delta )%P;
a%=P;a+=P;a%=P; a=P-a;a%=P; pDiv2=P/2;
if (calc(a,pDiv2)+1==P) puts("0");
else {
    int t=0,h=pDiv2; while (!(h%2)) ++t,h/=2;
    int root=calc(a,h/2);
    if (t>0) { Compute(); Pb=calc(b,h); }
    for (int i=1;i<=t;++i) {
        d=(long long)root*root*a%P;
        for (int j=1;j<=t-i;++j) d=(long long)d*d%P;
        if (d+1==P) root=(long long)root*Pb%P;
        Pb=(long long)Pb*Pb%P;
    }
    root=(long long)a*root%P;
    int root1=P-root; root-=delta;
    root%=P; if (root<0) root+=P;
    root1=-delta; root1%=P; if (root1<0) root1+=P;
    if (root>root1) { t=root;root=root1;root1=t; }
    if (root==root1) printf("1 %d\n",root);
    else printf("2 %d %d\n",root,root1);
}}return 0; }
```

3.10 Schröder-Hipparchus Number

$$S(n) = \frac{1}{n}((6n-9)S(n-1) - (n-3)S(n-2))$$

3.11 Catalan Numbers

$$Cat(n) = \frac{2n!}{n! \times n! \times (n+1)}$$

$$Cat(n+1) = \frac{(2n+2) \times (2n+1)}{(n+2) \times (n+1)} \times Cat(n)$$

4 Computational Geometry

```
struct Point{
    double x, y;
    Point(double x=0, double y=0):x(x), y(y){}
};
typedef Point Vector;
// Vector + Vector = Vector / Point + Vector = Point
Vector operator + (Vector A, Vector B){
```

```

    return Vector(A.x + B.x, A.y + B.y);}
// Point - Point = Vector
Vector operator - (Point A, Point B){
    return Vector(A.x - B.x, A.y - B.y);}
Vector operator * (Vector A, double p){
    return Vector(A.x * p, A.y * p);}
Vector operator / (Vector A, double p){
    return Vector(A.x / p, A.y / p);}
const double eps = 1e-10;
int dcmp(double x){
    if(fabs(x) < eps) return 0;
    return x < 0 ? -1 : 1; }
bool operator < (const Point& a, const Point& b){
    return dcmp(a.x - b.x) < 0 || (dcmp(a.x-b.x)==0 && dcmp(a.y -
        b.y) < 0); }
bool operator == (const Point& a, const Point &b){
    return dcmp(a.x-b.x) == 0 && dcmp(a.y-b.y) == 0; }
double Dot(Vector A, Vector B){
    return A.x*B.x + A.y*B.y; }
double Length(Vector A){
    return sqrt(Dot(A,A)); }
// polar angle theta is the counterclockwise angle from the
// x-axis at which a point in the xy-plane lies
// (-pi, pi]
double angle(Vector v) {
    return atan2(v.y, v.x); }
// counterclockwise angle from A to B [0, pi]
double Angle(Vector A, Vector B){
    return acos(Dot(A,B)/Length(A)/Length(B)); }
double Cross(Vector A, Vector B){
    return A.x*B.y - A.y*B.x; }
// counterclockwisely rotate A for rad
Vector Rotate(Vector A, double rad){
    return Vector(A.x*cos(rad)-A.y*sin(rad),
        A.x*sin(rad)+A.y*cos(rad)); }
// unit normal vector for A (left rotate pi/2) A != 0
Vector Normal(Vector A){
    double L = Length(A);
    return Vector(-A.y/L, A.x/L);}
// P+tv,Q+tw should have only one intersection,iff Cross(v,w)!=0

```

```

Point GetLineIntersection(Point P, Vector v, Point Q, Vector w){
    Vector u = P-Q;
    double t = Cross(w,u)/Cross(v,w);
    return P+v*t;}
// distance from P to line AB
double DistanceToLine(Point P, Point A, Point B){
    Vector v1 = B-A, v2 = P-A;
    return fabs(Cross(v1,v2))/Length(v1);}
// distance from P to segment AB
double DistanceToSegment(Point P, Point A, Point B){
    if(A == B) return Length(P-A);
    Vector v1 = B-A, v2 = P-A, v3 = P-B;
    if(dcmp(Dot(v1,v2))<0) return Length(v2);
    if(dcmp(Dot(v1,v3))>0) return Length(v3);
    return fabs(Cross(v1,v2))/Length(v1);}
Point GetLineProjection(Point P, Point A, Point B){
    Vector v = B-A;
    return A+v*(Dot(v,P-A) / Dot(v,v)); }
// determine segment a1a2 and b1b2 normal intersection (only
// one intersection, not endpoint)
// if allowing intersecting on endpoints:
// 1) c1 = c2 = 0: on the same line, probably intersecting
// 2) otherwise, one endpoint on the other segment (Use
//    OnSegment() method)
bool segmentProperIntersection(Point a1, Point a2, Point b1,
    Point b2){
    double c1 = Cross(a2-a1,b1-a1);
    double c2 = Cross(a2-a1,b2-a1);
    double c3 = Cross(b2-b1,a1-b1);
    double c4 = Cross(b2-b1,a2-b1);
    return dcmp(c1)*dcmp(c2)<0 && dcmp(c3)*dcmp(c4)<0;}
// determine P on segment a1a2 (endpoint excluded)
bool OnSegment(Point p, Point a1, Point a2) {
    return dcmp(Cross(a1-p,a2-p))==0 && dcmp(Dot(a1-p,a2-p))<0;}
// calculate the direct area for polygon (not necessarily
// convex)
double PolygonArea(Point* p, int n) {
    double area = 0;
    for(int i=1;i<n-1;i++)
        area += Cross(p[i]-p[0],p[i+1]-p[0]);
}

```

```

    return area/2;}
// convex hull: n points in array p, ch array for output,
    return the number of points on hull
// no duplicate points in input; the order of input points is
    not preserved
// if want input points on edges of hull, change two <= to <
int ConvexHull(Point* p, int n, Point* ch) {
    sort(p,p+n); int m = 0;
    for(int i=0;i<n;i++){
        while(m>1 && dcmp(Cross(ch[m-1]-ch[m-2], p[i]-ch[m-2])) <= 0)
            m--;
        ch[m++] = p[i];}
    int k = m;
    for(int i=n-2;i>=0;i--){
        while(m>k && dcmp(Cross(ch[m-1]-ch[m-2], p[i]-ch[m-2])) <= 0)
            m--;
        ch[m++] = p[i];}
    if(n>1) m--;
    return m;}
// return the diameter of set of points (Rotating Calipers
    Algorithm)
// ch: already convex hull (no three points in a line) n: the
    number of points
double diameter(Point* ch, int n) {
    if(n == 1) return 0;
    if(n == 2) return Length(ch[0] - ch[1]);
    ch[n] = ch[0];
    double ans = 0;
    for(int u = 0, v = 1; u < n; u++) {
        for(;;) {
            double diff = Cross(ch[u+1]-ch[u], ch[v+1]-ch[v]);
            if(dcmp(diff) <= 0) {
                ans = max(ans, Length(ch[u]-ch[v]));
                if(dcmp(diff) == 0)
                    ans = max(ans, Length(ch[u]-ch[v+1]));
                break;
            } v = (v + 1) % n;
        }
    }
    return ans;}
// poly: polygon n: the number of points

```

```

// return value: (-2, vertex) (-1, edges) (0, outside) (1,
    inside)
// determine if point on the left side of all edges (vertex
    already counterclock ordered)
int isPointInPolygon(Point p, Point* poly, int n){
    int wn = 0;
    for(int i=0;i<n;i++){
        if(p == poly[i]) return -2;
        if(OnSegment(p, poly[i], poly[(i+1)%n])) return -1;
        int k = dcmp(Cross(poly[(i+1)%n]-poly[i], p-poly[i]));
        int d1 = dcmp(poly[i].y - p.y);
        int d2 = dcmp(poly[(i+1)%n].y - p.y);
        if(k>0 && d1<=0 && d2>0) wn++;
        if(k<0 && d2<=0 && d1>0) wn--;
    }
    if(wn != 0) return 1;
    return 0;
}
struct Line{
    Point p; Vector v;
    Line(Point p, Vector v):p(p),v(v){}
    Point point(double t) {return p + v*t;}
    Line move(double d) {return Line(p + Normal(v)*d, v);}
};
struct Circle{
    Point c;
    double r;
    Circle(Point c, double r):c(c),r(r){}
    Point point(double a){return Point(c.x + cos(a)*r, c.y +
        sin(a)*r);}
};
// return number of intersection, sol has all intersection
// intersection P = A + t(B-A), simplify to et^2+ft+g = 0
int getLineCircleIntersection(Line L, Circle C, double& t1,
    double& t2, vector<Point>& sol){
    double a = L.v.x, b = L.p.x - C.c.x, c = L.v.y, d = L.p.y -
        C.c.y;
    double e = a*a + c*c, f = 2*(a*b+c*d), g = b*b + d*d -
        C.r*C.r;
    double delta = f*f - 4*e*g;

```

```

    if(dcmp(delta) < 0) return 0;
    if(dcmp(delta) == 0){
        t1 = t2 = -f / (2*e);
        sol.push_back(L.point(t1));
        return 1; }
    t1 = (-f - sqrt(delta)) / (2*e);
    sol.push_back(L.point(t1));
    t2 = (-f + sqrt(delta)) / (2*e);
    sol.push_back(L.point(t2));
    return 2;}
// return the number of intersection
// if two circle identical, then return -1
int getCircleCircleIntersection(Circle C1, Circle C2,
    vector<Point>& sol){
    double d = Length(C1.c-C2.c);
    if(dcmp(d) == 0){
        if(dcmp(C1.r-C2.r) == 0) return -1;
        return 0;
    }
    if(dcmp(C1.r+C2.r-d) < 0) return 0;
    if(dcmp(fabs(C1.r-C2.r) - d) > 0) return 0;
    double a = angle(C2.c-C1.c);
    double da = acos((C1.r*C1.r + d*d - C2.r*C2.r) / (2*C1.r*d));
    // angle from C1C2 to C1P1
    Point p1 = C1.point(a-da), p2 = C1.point(a+da);
    sol.push_back(p1);
    if(p1 == p2) return 1;
    sol.push_back(p2);
    return 2;}
// tangent lines from P to C
// v[i]: i-th tangent lines, return the number of tangent lines
int getTangents(Point p, Circle C, Vector* v){
    Vector u = C.c - p;
    double dist = Length(u);
    if(dist < C.r) return 0;
    else if(dcmp(dist-C.r)==0){
        v[0] = Rotate(u,PI/2);
        return 1;
    } else {
        double ang = asin(C.r / dist);
        v[0] = Rotate(u, -ang); v[1] = Rotate(u, +ang);
        return 2;
    }
}
// return the number of tangents, -1 means inf
// a[i], b[i]: point of tangency with i-th tangent on A, B;
// same when internally or externally tangent
int getTangents(Circle A, Circle B, Point* a, Point* b) {
    int cnt = 0;
    if(A.r < B.r){ swap(A, B); swap(a, b); }
    double d2 = (A.c.x-B.c.x)*(A.c.x-B.c.x) +
        (A.c.y-B.c.y)*(A.c.y-B.c.y);
    double rdif = A.r - B.r;
    double rsum = A.r + B.r;
    if(dcmp(d2 - rdif*rdif) < 0) // containing
        return 0;
    double base = atan2(B.c.y-A.c.y, B.c.x-A.c.x);
    if(dcmp(d2)==0 && dcmp(A.r-B.r)==0) // infinite tangents
        return -1;
    if(dcmp(d2-rdif*rdif) == 0){ // inscribe, one tangent
        a[cnt] = A.point(base); b[cnt] = B.point(base);
        cnt++; return 1;
    }
    double ang = acos((A.r-B.r)/sqrt(d2)); // two external common
    // tangents
    a[cnt] = A.point(base + ang);
    b[cnt] = B.point(base + ang); cnt++;
    a[cnt] = A.point(base - ang);
    b[cnt] = B.point(base - ang); cnt++;
    if(dcmp(d2-rsum*rsum) == 0){
        a[cnt] = A.point(base);
        b[cnt] = B.point(PI + base); cnt++;
    }
    else if(dcmp(d2 - rsum*rsum) > 0){ // two internal common
    // tangents
        double ang = acos((A.r+B.r) / sqrt(d2));
        a[cnt] = A.point(base+ang);
        b[cnt] = B.point(PI+base+ang); cnt++;
        a[cnt] = A.point(base-ang);
        b[cnt] = B.point(PI+base-ang); cnt++;
    }
}

```

```

    return cnt;}

void CircleCenter(point p0 , point p1 , point p2 , point &cp ){
    double a1=p1.x-p0.x , b1=p1.y-p0.y , c1=(sqr(a1)+sqr(b1)) /
        2 ;
    double a2=p2.x-p0.x , b2=p2.y-p0.y , c2=(sqr(a2)+sqr(b2)) /
        2 ;
    double d = a1*b2 - a2*b1 ;
    cp.x = p0.x + ( c1*b2 - c2*b1 ) / d ;
    cp.y = p0.y + ( a1*c2 - a2*c1 ) / d ;}

double Incenter(point A, point B, point C, point &cp ){
    double s , p , r , a , b , c ;
    a = dis(B, C) , b = dis(C, A) , c = dis(A, B) ; p = (a +b +c)
        / 2 ;
    s = sqrt ( p * ( p-a ) * ( p-b ) * ( p-c ) ) ; r = s / p ;
    cp.x = ( a*A.x + b*B.x + c*C.x ) / ( a + b + c ) ;
    cp.y = ( a*A.y + b*B.y + c*C.y ) / ( a + b + c ) ;
    return r ;}

void Orthocenter(point A, point B, point C, point &cp ){
    CircleCenter(A, B, C, cp );
    cp.x = A.x + B.x + C.x - 2 * cp.x ;cp.y = A.y + B.y + C.y - 2
        * cp.y ;}

double twoCircleAreaUnion(point a, point b , double r1, double
    r2){
    if (r1+r2<=(a-b).dist()) return 0;
    if (r1+(a-b).dist()<=r2) return pi*r1*r1;
    if (r2+(a-b).dist()<=r1) return pi*r2*r2;
    double c1, c2, ans=0;
    c1=(r1*r1-r2*r2+(a-b).dis()/(a-b).dist()/r1/2.0;
    c2=(r2*r2-r1*r1+(a-b).dis()/(a-b).dist()/r2/2.0;
    double s1,s2; s1=acos(c1); s2=acos(c2);
    ans+=s1*r1*r1-r1*r1*sin(s1)*cos(s1);
    ans+=s2*r2*r2-r2*r2*sin(s2)*cos(s2);
    return ans;
}////==两园面积交 dist=是距离, dis是平方

double area2(point pa, point pb) {
    if (pa.len() < pb.len()) swap(pa, pb); if (pb.len() < eps)
        return 0;

```

```

    double a, b, c, B, C, sinB, cosB, sinC, cosC, S, h, theta;
    a = pb.len(); b = pa.len(); c = (pb-pa).len();
    cosB=dot(pb,pb-pa)/a/c; sinB=fabs(det(pb,pb-pa)/a/c);
    cosC=dot(pa, pb) / a / b; sinC=fabs(det(pa,pb)/a/b);
    B=atan2(sinB , cosB); C=atan2(sinC, cosC);
    if (a > r) { S = C/2*r*r; h = a*b*sinC/c;
        if (h < r && B < PI/2) S -= (acos(h/r)*r*r -
            h*sqrt(r*r-h*h));
    }
    else if (b > r) { theta = PI - B - asin(sinB/r*a);
        S = .5*a*r*sin(theta) + (C-theta)/2*r*r; }
    else S = .5*sinC*a*b; return S; }// a, b, c, r fixed

double area(const point &o) {
    double S = 0; point oa = a-o, ob = b-o, oc = c-o;
    S += area2(oa, ob) * sign(det(oa, ob));
    S += area2(ob, oc) * sign(det(ob, oc));
    S += area2(oc, oa) * sign(det(oc, oa)); return abs(S);
}

```

////====多边形和圆相交的面积用有向面积, 划分成一个三角形和圆的面积的交

```

随机增量最小覆盖圆
const double eps=1e-7;
const int maxn=100000;
class circle{
    point o;
    double r;
}
point a[maxn];
int n;
circle ans;
double area(point a, point b, point c){
    return ((b.x-a.x)*(c.y-a.y)-(b.y-a.y)*(c.x-a.x));
}
double dis(point a, point b){
    return (a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y);
}
void init(){
    int i,j,k;
    scanf("%d",&n);

```

```

    rep(i,n) scanf("%lf%lf",&a[i].x,&a[i].y);
}
bool check(const point &a){
    return sqr(a.x-ans.o.x) + sqr(a.y-ans.o.y) <= ans.r + zero;
}
void Mincircle(){
    int i,j,k;
    ans.r=0; ans.x=0; ans.y=0;
    rep(i,n) if (!check(a[i])) {
        ans.o=a[i]; ans.r=0;
        rep(j,i) if (!check(a[j])) {
            CircleCenter(a[i],a[j],ans.o);
            ans.r=dis(ans.o,a[j]);
            rep(k,j) if (!check(a[k])) {
                CircleCenter(a[i],a[j],a[k],ans.o);
                ans.r=dis(ans.o,a[k]);
            }
        }
    }
    printf("%.4lf\n",sqrt(ans.r));
}

```

半平面交 n^2

```

const int maxn=200;
const double eps=1e-8;
const int infinite=10000;
struct point{
    double x,y;
    void input(){
        scanf("%lf%lf",&x,&y);
    }
} sol[maxn],tmp[maxn];
struct Tline{
    point a,b;
} line[maxn];
int n,m;
void rebuild(point a, point b){
    int i,t;
    double k1,k2;

```

```

    sol[m]=sol[0]; t=0;
    foru(i,1,m){
        k1=area(a,b,sol[i]);
        k2=area(a,b,sol[i-1]);
        if (cmp(k1)*cmp(k2)<0){
            tmp[t].x=(sol[i].x*k2-sol[i-1].x*k1) / (k2-k1);
            tmp[t].y=(sol[i].y*k2-sol[i-1].y*k1) / (k2-k1);
            t++;
        }
        if (cmp(area(a,b,sol[i])) >=0){
            tmp[t]=sol[i];
            t++;
        }
    }
    m=t;
    rep(i,m) sol[i]=tmp[i];
}
void work(){
    int i,j,k;
    double ans;
    point o;
    sol[0].x = 0; sol[0].y = 0;
    sol[1].x = infinite; sol[1].y = 0;
    sol[2].x = infinite; sol[2].y = infinite;
    sol[3].x = 0; sol[3].y = infinite;
    m=4;
    rep(i,n) rebuild(line[i].a,line[i].b);
    // 保留直线line[i].a,line[i+1].b
    // 左边的点
    if (m>0) printf("1\n");
    else printf("0\n");
}

```

5 String Processing

5.1 KMP

```

#define MAX_N 100010

```

```

char T[MAX_N], P[MAX_N]; // T = text, P = pattern

```

```

int b[MAX_N], n, m; // b = back table, n = length of T, m =
    length of P

void kmpPreprocess() { // call this before calling kmpSearch()
    int i = 0, j = -1; b[0] = -1; // starting values
    while (i < m) { // pre-process the pattern string P
        while (j >= 0 && P[i] != P[j]) j = b[j]; // if different,
            reset j using b
        i++; j++; // if same, advance both pointers
        b[i] = j; // observe i = 8, 9, 10, 11, 12 with j = 0, 1, 2,
            3, 4
    } // in the example of P = "SEVENTY SEVEN" above

void kmpSearch() { // this is similar as kmpPreprocess(), but
    on string T
    int i = 0, j = 0; // starting values
    while (i < n) { // search through string T
        while (j >= 0 && T[i] != P[j]) j = b[j]; // if different,
            reset j using b
        i++; j++; // if same, advance both pointers
        if (j == m) { // a match found when j == m
            printf("P is found at index %d in T\n", i - j);
            j = b[j]; // prepare j for the next possible match
        } } }

```

5.2 Suffix Array

```

#define MAX_N 100010 // second approach: O(n log n)
char T[MAX_N]; // the input string, up to 100K characters
int n; // the length of input string
int RA[MAX_N], tempRA[MAX_N]; // rank array and temporary rank
    array
int SA[MAX_N], tempSA[MAX_N]; // suffix array and temporary
    suffix array
int c[MAX_N]; // for counting/radix sort

char P[MAX_N]; // the pattern string (for string matching)
int m; // the length of pattern string

```

```

int Phi[MAX_N]; // for computing longest common prefix
int PLCP[MAX_N];
int LCP[MAX_N]; // LCP[i] stores the LCP between previous
    suffix T+SA[i-1]
    // and current suffix
    T+SA[i]

bool cmp(int a, int b) { return strcmp(T + a, T + b) < 0; } //
    compare

void constructSA_slow() { // cannot go beyond 1000
    characters
    for (int i = 0; i < n; i++) SA[i] = i; // initial SA: {0, 1,
        2, ..., n-1}
    sort(SA, SA + n, cmp); // sort: O(n log n) * compare: O(n) =
        O(n^2 log n)
}

void countingSort(int k) { //
    O(n)
    int i, sum, maxi = max(300, n); // up to 255 ASCII chars or
        length of n
    memset(c, 0, sizeof c); // clear frequency
        table
    for (i = 0; i < n; i++) // count the frequency of each
        integer rank
        c[i + k < n ? RA[i + k] : 0]++;
    for (i = sum = 0; i < maxi; i++) {
        int t = c[i]; c[i] = sum; sum += t;
    }
    for (i = 0; i < n; i++) // shuffle the suffix array if
        necessary
        tempSA[c[SA[i]+k < n ? RA[SA[i]+k] : 0]++] = SA[i];
    for (i = 0; i < n; i++) // update the suffix
        array SA
        SA[i] = tempSA[i];
}

void constructSA() { // this version can go up to 100000
    characters

```



```

int i, k, r;
for (i = 0; i < n; i++) RA[i] = T[i];           // initial
rankings
for (i = 0; i < n; i++) SA[i] = i; // initial SA: {0, 1, 2,
..., n-1}
for (k = 1; k < n; k <= 1) { // repeat sorting process log n
times
    countingSort(k); // actually radix sort: sort based on the
second item
    countingSort(0); // then (stable) sort based on the
first item
    tempRA[SA[0]] = r = 0; // re-ranking; start from rank
r = 0
    for (i = 1; i < n; i++) // compare adjacent
suffixes
        tempRA[SA[i]] = // if same pair => same rank r; otherwise,
increase r
        (RA[SA[i]] == RA[SA[i-1]] && RA[SA[i]+k] == RA[SA[i-1]+k])
        ? r : ++r;
    for (i = 0; i < n; i++) // update the rank
array RA
        RA[i] = tempRA[i];
    if (RA[SA[n-1]] == n-1) break; // nice optimization
trick
} }

void computeLCP_slow() {
    LCP[0] = 0; // default value
    for (int i = 1; i < n; i++) { // compute LCP by definition
        int L = 0; // always reset L to 0
        while (T[SA[i] + L] == T[SA[i-1] + L]) L++; // same L-th
char, L++
        LCP[i] = L;
    } }

void computeLCP() {
    int i, L;
    Phi[SA[0]] = -1; // default value
    for (i = 1; i < n; i++) // compute Phi in O(n)
        Phi[SA[i]] = SA[i-1]; // remember which suffix is behind

```

```

        this suffix
    for (i = L = 0; i < n; i++) { // compute Permuted LCP in O(n)
        if (Phi[i] == -1) { PLCP[i] = 0; continue; } // special case
        while (T[i + L] == T[Phi[i] + L]) L++; // L increased max n
times
        PLCP[i] = L;
        L = max(L-1, 0); // L decreased max n times
    }
    for (i = 0; i < n; i++) // compute LCP in O(n)
        LCP[i] = PLCP[SA[i]]; // put the permuted LCP to the correct
position
}

ii stringMatching() { // string matching in O(m log n)
    int lo = 0, hi = n-1, mid = lo; // valid matching = [0..n-1]
    while (lo < hi) { // find lower bound
        mid = (lo + hi) / 2; // this is round down
        int res = strcmp(T + SA[mid], P, m); // try to find P in
suffix 'mid'
        if (res >= 0) hi = mid; // prune upper half (notice the
>= sign)
        else lo = mid + 1; // prune lower half including mid
    } // observe '=' in "res >= 0" above
    if (strcmp(T + SA[lo], P, m) != 0) return ii(-1, -1); // if
not found
    ii ans; ans.first = lo;
    lo = 0; hi = n - 1; mid = lo;
    while (lo < hi) { // if lower bound is found, find upper
bound
        mid = (lo + hi) / 2;
        int res = strcmp(T + SA[mid], P, m);
        if (res > 0) hi = mid; // prune upper half
        else lo = mid + 1; // prune lower half including
mid
    } // (notice the selected branch when res == 0)
    if (strcmp(T + SA[hi], P, m) != 0) hi--; // special case
    ans.second = hi;
    return ans;
} // return lower/upperbound as first/second item of the pair,
respectively

```

```

ii LRS() {    // returns a pair (the LRS length and its index)
    int i, idx = 0, maxLCP = -1;
    for (i = 1; i < n; i++) // O(n), start from i = 1
        if (LCP[i] > maxLCP)
            maxLCP = LCP[i], idx = i;
    return ii(maxLCP, idx);
}

int owner(int idx) { return (idx < n-m-1) ? 1 : 2; }

ii LCS() {    // returns a pair (the LCS length and its index)
    int i, idx = 0, maxLCP = -1;
    for (i = 1; i < n; i++) // O(n), start from i = 1
        if (owner(SA[i]) != owner(SA[i-1]) && LCP[i] > maxLCP)
            maxLCP = LCP[i], idx = i;
    return ii(maxLCP, idx);
}

```

6 Sundry

6.1 Day of some Date

```

int whatday(int d, int m, int y) { //day month year
    int ans;
    if (m == 1 || m == 2) { m += 12; y --; }
    if ((y < 1752) || (y == 1752 && m < 9) || (y == 1752 && m == 9
        && d < 3))
        ans = (d + 2*m + 3*(m+1)/5 + y + y/4 + 5) % 7;
    else
        ans = (d + 2*m + 3*(m+1)/5 + y + y/4 - y/100 + y/400)%7;
    return ans;
}

```

6.2 Java

```

import java.io.*;
import java.util.*;
import java.math.*;
import static java.lang.Math.*;

public class main{
    public static StringTokenizer st;
    public static DataInputStream in;
    public static PrintStream out;
    private static int nextInt() throws Exception{
        for (;st.countTokens()==0;) st=new
            StringTokenizer(in.readLine());
        return Integer.valueOf(st.nextToken());
    }

    public static BigInteger getsqrt(BigInteger n){
        if (n.compareTo(BigInteger.ZERO)<=0) return n;
        BigInteger x,xx,txx;
        xx=x=BigInteger.ZERO;
        for (int t=n.bitLength()/2;t>=0;t--){
            txx=xx.add(x.shiftLeft(t+1)).add(BigInteger.ONE.shiftLeft(t+t));
            if (txx.compareTo(n)<=0){
                x=x.add(BigInteger.ONE.shiftLeft(t));
                xx=txx;
            }
        }
        return x;
    }

    public static void main(String args[]) throws Exception{
        in=new DataInputStream(System.in);
        out=new PrintStream(new
            BufferedOutputStream(System.out));
        st=new StringTokenizer(in.readLine());
        out.close();
    }
}

```
