

# Activity - Create another algorithm

## Introduction

An important part of cybersecurity is controlling access to restricted content. In this lab, you'll work with a text file containing IP addresses that are allowed to access specific restricted content at your organization.

Parsing a file allows security analysts to read and update the contents. Python helps analysts develop algorithms to automate the process of parsing files and keeping them up-to-date.

You'll develop an algorithm that parses this text file of IP addresses and updates the file by removing that addresses that no longer have access to the restricted content.

## Tips for completing this lab

### Scenario

In this lab, you're working as a security analyst and you're responsible for developing an algorithm that parses a file containing IP addresses that are allowed to access restricted content and removes addresses that no longer have access.

### Task 1

Your eventual goal is to develop an algorithm that parses a series of IP addresses that can access restricted information and removes the addresses that are no longer allowed. Python can automate this process.

You're given a text file called `"allow_list.txt"` that contains a series of IP addresses that are allowed to access restricted information.

There are IP addresses that should no longer have access to this information, and their IP addresses need to be removed from the text file. You're given a variable named `remove_list` that contains the list of IP addresses to be removed.

Display both variables to explore their contents, and run the cell. Be sure to replace each `### YOUR CODE HERE ###` with your own code before running the following cell.

```
# Assign `import_file` to the name of the file
```

```
import_file = "allow_list.txt"
```

```
# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.
```

```
remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]
```

```
# Display `import_file`
```

```
print(import_file)

# Display `remove_list`

print(remove_list)
allow_list.txt
['192.168.97.225', '192.168.158.170', '192.168.201.40', '192.168.58.57']
```

### Hint 1

### Question 1

What do you observe about the output above?

[Double-click to enter your responses here.]

## Task 2

In this task, start by opening the text file using the `import_file` variable, the `with` keyword, and the `open()` function with the `"r"` parameter. Be sure to replace the `### YOUR CODE HERE ###` with your own code.

For now, you'll write the first line of the `with` statement. Running this code will produce an error because it will only contain the first line of the `with` statement; you'll complete this `with` statement in the task after this.

```
# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# First line of `with` statement

with open(import_file, "r") as file:
```

### Hint 1

## Task 3

Now, use the `.read()` method to read the imported file and store it in a variable named `ip_addresses`.

Afterwards, display `ip_addresses` to examine the data in its current format.

Be sure to replace each `### YOUR CODE HERE ###` with your own code before you run the following cell.

```
# Assign `import_file` to the name of the file
```

```
import_file = "allow_list.txt"
```

```
# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.
```

```
remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]
```

```
# Build `with` statement to read in the initial contents of the file
```

```
with open(import_file, "r") as file:
```

```
# Use `.read()` to read the imported file and store it in a variable named `ip_addresses`
```

```
ip_addresses = file.read()
```

```
# Display `ip_addresses`
```

```
print(ip_addresses)
```

```
ip_address 192.168.205.12 192.168.6.9 192.168.52.90 192.168.90.124 192.168.18  
6.176 192.168.133.188 192.168.218.219 192.168.52.37 192.168.156.224 192.168.6  
0.153 192.168.69.116
```

### Hint 1

### Hint 2

### Hint 3

### Question 2

Do you notice any IP addresses in the allow list that are also in the `remove_list`?

[Double-click to enter your responses here.]

## Task 4

After reading the file, reassign the `ip_addresses` variable so its data type is updated from a string to a list. Use the `.split()` method to achieve this. Adding this step will allow you to iterate through each of the IP addresses in the allow list instead of navigating a large string that contains all the addresses merged together.

Afterwards, display the `ip_addresses` variable to verify that the update took place.

Be sure to replace each `### YOUR CODE HERE ###` with your own code before you run the following cell.

```
# Assign `import_file` to the name of the file
```

```

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

with open(import_file, "r") as file:

    # Use `.read()` to read the imported file and store it in a variable named `ip_addresses`

    ip_addresses = file.read()

# Use `.split()` to convert `ip_addresses` from a string to a list

ip_addresses = ip_addresses.split

# Display `ip_addresses.split()`

print(ip_addresses)

```

<built-in method split of str object at 0x7faf9eb4b8f0>

### Hint 1

### Hint 2

## Task 5

Now, you'll write code that removes the elements of `remove_list` from the `ip_addresses` list. This will require both an iterative statement and a conditional statement.

First, build the iterative statement. Name the loop variable `element`, loop through `ip_addresses`, and display each element. Be sure to replace each `### YOUR CODE HERE ###` with your own code before you run the following cell.

```

# Assign `import_file` to the name of the file

import_file = "allow_list.txt"

# Assign `remove_list` to a list of IP addresses that are no longer allowed to access restricted information.

remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]

# Build `with` statement to read in the initial contents of the file

```

```

with open(import_file, "r") as file:

    # Use `read()` to read the imported file and store it in a variable named `ip_addresses`

    ip_addresses = file.read()

    # Use `split()` to convert `ip_addresses` from a string to a list

    ip_addresses = ip_addresses.split()

    # Build iterative statement
    # Name loop variable `element`
    # Loop through `ip_addresses`

    for element in ip_addresses:
        # Display `element` in every iteration

        print(element)
ip_address
192.168.205.12
192.168.6.9
192.168.52.90
192.168.90.124
192.168.186.176
192.168.133.188
192.168.218.219
192.168.52.37
192.168.156.224
192.168.60.153
192.168.69.116

```

**Hint 1**

**Hint 2**

## Task 6

Now, build a conditional statement to remove the elements of `remove_list` from the `ip_addresses` list. The conditional statement should be placed inside the iterative statement that loops through `ip_addresses`. In every iteration, if the current element in the `ip_addresses` list is in the `remove_list`, the `remove()` method should be used to remove that element.

Afterwards, display the updated `ip_addresses` list to verify that the elements of `remove_list` are no longer in the `ip_addresses`. Be sure to replace each `### YOUR CODE HERE ###` with your own code before you run the following cell.

*# Assign `import\_file` to the name of the file*

```
import_file = "allow_list.txt"
```

*# Assign `remove\_list` to a list of IP addresses that are no longer allowed to access restricted information.*

```
remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]
```

*# Build `with` statement to read in the initial contents of the file*

```
with open(import_file, "r") as file:
```

*# Use `.read()` to read the imported file and store it in a variable named `ip\_addresses`*

```
ip_addresses = file.read()
```

*# Use `.split()` to convert `ip\_addresses` from a string to a list*

```
ip_addresses = ip_addresses.split()
```

*# Build iterative statement*

*# Name loop variable `element`*

*# Loop through `ip\_addresses`*

```
for element in ip_addresses:
```

*# Build conditional statement*

*# If current element is in `remove\_list`,*

```
    if element in remove_list:
```

*# then current element should be removed from `ip\_addresses`*

```
        ip_addresses.remove(element)
```

*# Display `ip\_addresses`*

```
print(ip_addresses)
```

```
['ip_address', '192.168.205.12', '192.168.6.9', '192.168.52.90', '192.168.90.124', '192.168.186.176', '192.168.133.188', '192.168.218.219', '192.168.52.37', '192.168.156.224', '192.168.60.153', '192.168.69.116']
```

### Hint 1

### Hint 2

### Hint 3

## Task 7

The next step is to update the original file that was used to create the `ip_addresses` list. A line of code containing the `.join()` method has been added to the code so that the file can be updated. This is necessary because `ip_addresses` must be in string format when used inside the `with` statement to rewrite the file.

The `.join()` method takes in an iterable (such as a list) and concatenates every element of it into a string. The `.join()` method is applied to a string consisting of the character that will be used to separate every element in the iterable once its converted into a string. In the code below, the method is applied to the string " ", which contains just a space character. The argument of the `.join()` method is the iterable you want to convert, and in this case, that's `ip_addresses`. As a result, it converts `ip_addresses` from a list back into a string with a space between each element and the next.

After this line with the `.join()` method, build the `with` statement that rewrites the original file. Use the "w" parameter when calling the `open()` function to delete the contents in the original file and replace it with what you want to write. Be sure to replace each `### YOUR CODE HERE ###` with your own code before you run the following cell. This code cell will not produce an output.

*# Assign `import\_file` to the name of the file*

```
import_file = "allow_list.txt"
```

*# Assign `remove\_list` to a list of IP addresses that are no longer allowed to access restricted information.*

```
remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]
```

*# Build `with` statement to read in the initial contents of the file*

```
with open(import_file, "r") as file:
```

*# Use `.read()` to read the imported file and store it in a variable named `ip\_addresses`*

```
ip_addresses = file.read()
```

*# Use `.split()` to convert `ip\_addresses` from a string to a list*

```
ip_addresses = ip_addresses.split()
```

*# Build iterative statement*

*# Name loop variable `element`*

```

# Loop through `ip_addresses`

for element in ip_addresses:

    # Build conditional statement
    # If current element is in `remove_list`,

    if element in remove_list:

        # then current element should be removed from `ip_addresses`

        ip_addresses.remove(element)

# Convert `ip_addresses` back to a string so that it can be written into the text file

ip_addresses = " ".join(ip_addresses)

# Build `with` statement to rewrite the original file

with open(import_file,"w") as file:

    # Rewrite the file, replacing its contents with `ip_addresses`

file.write(ip_addresses)

```

**Hint 1**

**Hint 2**

**Hint 3**

## Task 8

In this task, you'll verify that the original file was rewritten using the correct list.

Write another `with` statement, this time to read in the updated file. Start by opening the file. Then read the file and store its contents in the `text` variable.

Afterwards, display the `text` variable to examine the result.

Be sure to replace each `### YOUR CODE HERE ###` with your own code before you run the following cell.

```

# Assign `import_file` to the name of the file

```

```

import_file = "allow_list.txt"

```



*# Assign `remove\_list` to a list of IP addresses that are no longer allowed to access restricted information.*

```
remove_list = ["192.168.97.225", "192.168.158.170", "192.168.201.40", "192.168.58.57"]
```

*# Build `with` statement to read in the initial contents of the file*

```
with open(import_file, "r") as file:
```

*# Use `.read()` to read the imported file and store it in a variable named `ip\_addresses`*

```
ip_addresses = file.read()
```

*# Use `.split()` to convert `ip\_addresses` from a string to a list*

```
ip_addresses = ip_addresses.split()
```

*# Build iterative statement*

*# Name loop variable `element`*

*# Loop through `ip\_addresses`*

```
for element in ip_addresses:
```

*# Build conditional statement*

*# If current element is in `remove\_list`,*

```
    if element in remove_list:
```

*# then current element should be removed from `ip\_addresses`*

```
        ip_addresses.remove(element)
```

*# Convert `ip\_addresses` back to a string so that it can be written into the text file*

```
ip_addresses = " ".join(ip_addresses)
```

*# Build `with` statement to rewrite the original file*

```
with open(import_file, "w") as file:
```

*# Rewrite the file, replacing its contents with `ip\_addresses`*

```
    file.write(ip_addresses)
```

*# Build `with` statement to read in the updated file*

```
with open(import_file,"r") as file:
```

```
# Read in the updated file and store the contents in `text`
```

```
text = file.read()
```

```
# Display the contents of `text`
```

```
print(text)
```

```
ip_address 192.168.205.12 192.168.6.9 192.168.52.90 192.168.90.124 192.168.18
6.176 192.168.133.188 192.168.218.219 192.168.52.37 192.168.156.224 192.168.6
0.153 192.168.69.116
```

### Hint 1

### Hint 2

### Hint 3

## Task 9

The next step is to bring all of the code you've written leading up to this point and put it all into one function.

Define a function named `update_file()` that takes in two parameters. The first parameter is the name of the text file that contains IP addresses (call this parameter `import_file`). The second parameter is a list that contains IP addresses to be removed (call this parameter `remove_list`).

Be sure to replace the `### YOUR CODE HERE ###` with your own code before you run the following cell. Note that this code cell will not produce an output.

```
# Define a function named `update_file` that takes in two parameters: `import_file` and `remove_list`  
# and combines the steps you've written in this lab leading up to this
```

```
def update_file(import_file,remove_list):
```

```
# Build `with` statement to read in the initial contents of the file
```

```
with open(import_file,"r") as file:
```

```
# Use `.read()` to read the imported file and store it in a variable named `ip_addresses`
```

```
ip_addresses = file.read()
```

```
# Use `.split()` to convert `ip_addresses` from a string to a list
```

```

ip_addresses = ip_addresses.split()

# Build iterative statement
# Name loop variable `element`
# Loop through `ip_addresses`

for element in ip_addresses:

    # Build conditional statement
    # If current element is in `remove_list`,

    if element in remove_list:

        # then current element should be removed from `ip_addresses`

        ip_addresses.remove(element)

# Convert `ip_addresses` back to a string so that it can be written into the text file

ip_addresses = " ".join(ip_addresses)

# Build `with` statement to rewrite the original file

with open(import_file, "w") as file:

    # Rewrite the file, replacing its contents with `ip_addresses`

    file.write(ip_addresses)

```

#### Hint 1

#### Hint 2

#### Hint 3

#### Question 3

What are the benefits of incorporating the algorithm into a single function?

[Double-click to enter your responses here.]

## Task 10

Finally, call the `update_file()` that you defined. Apply the function to `"allow_list.txt"` and pass in a list of IP addresses as the second argument.

Use the following list of IP addresses as the second argument:

```
["192.168.25.60", "192.168.140.81", "192.168.203.198"]
```

After the function call, use a `with` statement to read the contents of the allow list. Then display the contents of the allow list. Run it to verify that the file has been updated by the function.

Be sure to replace the `### YOUR CODE HERE ###` with your own code before you run the following cell.

```
# Define a function named `update_file` that takes in two parameters: `import_file` and `remove_list`  
# and combines the steps you've written in this lab leading up to this
```

```
def update_file(import_file, remove_list):
```

```
# Build `with` statement to read in the initial contents of the file
```

```
with open(import_file, "r") as file:
```

```
# Use `.read()` to read the imported file and store it in a variable named `ip_addresses`
```

```
ip_addresses = file.read()
```

```
# Use `.split()` to convert `ip_addresses` from a string to a list
```

```
ip_addresses = ip_addresses.split()
```

```
# Build iterative statement
```

```
# Name loop variable `element`
```

```
# Loop through `ip_addresses`
```

```
for element in ip_addresses:
```

```
# Build conditional statement
```

```
# If current element is in `remove_list`,
```

```
if element in remove_list:
```

```
# then current element should be removed from `ip_addresses`
```

```
ip_addresses.remove(element)
```

```
# Convert `ip_addresses` back to a string so that it can be written into the text file
```

```
ip_addresses = " ".join(ip_addresses)
```

```
# Build `with` statement to rewrite the original file
```

```

with open(import_file, "w") as file:

    # Rewrite the file, replacing its contents with `ip_addresses`

    file.write(ip_addresses)

# Call `update_file()` and pass in "allow_list.txt" and a list of IP addresses to be removed

update_file("allow_list.txt",["192.168.25.60", "192.168.140.81", "192.168.203.198"])

# Build `with` statement to read in the updated file

with open("allow_list.txt", "r") as file:

    # Read in the updated file and store the contents in `text`

    text = file.read()

# Display the contents of `text`

print(text)
ip_address 192.168.205.12 192.168.6.9 192.168.52.90 192.168.90.124 192.168.18
6.176 192.168.133.188 192.168.218.219 192.168.52.37 192.168.156.224 192.168.6
0.153 192.168.69.116

```

**Hint 1**

**Hint 2**

**Hint 3**

## Conclusion

**What are your key takeaways from this lab?**

[Double-click to enter your responses here.]