

Code segment for DF implementation in the webpage checkout:

Tag Placement

Place the basic `<script>` tag in the `<head>` tag for optimal performance for either method.

For the basic `<script>` tag with `<noscript>` tag method, place the `<noscript>` tag in the `<body>` tag, as in [Example 1](#). Do not place the `<noscript>` tag in the `<head>` tag because it contains an `<iframe>` tag. Placing iframes in the head tag violates W3C validation and might cause problems.

Basic `<script>` Tag with `<noscript>` Tag (Recommended)

The recommended deployment includes a basic `<script>` tag, which loads a Javascript resource: `tags.js`, as well as an additional `<noscript>` tag. The purpose of the `<noscript>` tag is to ensure that profiling occurs, even if JavaScript is disabled.

According to the following example:

```
<!-- HEAD -->
<head>
<script type="text/javascript" src="https://h.online-
metrix.net/fp/tags.js?org_id=1snn5n9w&session_id=merchantID123456789"></script>
</head>

<!-- BODY -->
<body>
<noscript>
<iframe style="width: 100px; height: 100px; border: 0; position:absolute; top: -5000px;"
src="https://h.online-metrix.net/fp/tags?org_id=1snn5n9w &session_id=
merchantID123456789"></iframe>
</noscript>
</body>
```

Where:

`1snn5n9w` is the `org_id`. This `org_id` is the test `org_id` and you can use it only with CyberSource test environment. For the production environment you need to use the live `Org_id` = `k8vif92e`.

<code>1snn5n9w</code>	Test Environment
<code>k8vif92e</code>	Production Environment

`merchantID123456789` is an example of the `session_id`. The `session_id` is the CyberSource Merchant ID (`merchantID`) + an unique identifier (`123456789`). This identifier could be anything you want to use (needs to be unique for 48 hours). Usually people use a purchase identifier or anything else.

The code segments must be loaded before the customer submits an order. The codes that you need to put in your webpage could be **http** or **https**. You can also use a redirect method for that instead of the direct (below). See the manual for more information.

Sending information of API field to CYBS: deviceFingerPrintId

After implementing the code segment in the page checkout, an API field information (deviceFingerPrintId) must be included in the Request to be sent to CYBS. The transaction needs to have this field and the value used when called the online-metrix.net (the unique identifier, **123456789** in this example)

deviceFingerprintID=**123456789**

Request Field Description Type & Max Length

deviceFingerprintID - Field that contains the unique identifier of the session ID for the fingerprint. The string can contain uppercase and lowercase letters, digits, and these special characters: hyphen (-) and underscore (_). However, do not use the same uppercase and lowercase letters to indicate different sessions IDs. The session ID must be unique for each merchant ID. You can use any string that you are already generating, such as an order number or Web session ID.

See that the deviceFingerprintID is part of the session_id. The session_id in this case is **merchantID123456789**, but you must send only the identifier which is **123456789**.