

Hotel Management System — System Design and Overall Architecture

Project: Hotel Management System (HMS) **Document type:** Requirement & Design Specification — System Design and Overall Architecture **Method:** COMET (Collaborative Object Modeling and Architectural Design Method) **Date:** 22/09/2026

Table of Contents

- 1. Introduction
- 2. Actors
- 3. Use Case Model — Complete Inventory
- 4. Detailed Use Case Specifications
- 5. Analysis Modeling — Static Modeling (Ch. 7)
- 6. Analysis Modeling — Object and Class Structuring (Ch. 8)
- 7. Overall Software Architecture
- 8. Software Quality Attributes (Ch. 20)
- 9. Traceability Matrix

1. Introduction

1.1 Purpose

This document specifies the requirements model and the overall software architecture for the Hotel Management System (HMS). It follows the COMET method: use case modeling (Ch. 5–6) produces the functional requirements, static modeling (Ch. 7) produces the entity class model, object and class structuring (Ch. 8) allocates software objects into boundary / entity / control / application-logic categories, and the quality attributes (Ch. 20) drive the architectural decisions.

1.2 Scope

HMS covers the complete hotel operation lifecycle:

Domain	Coverage
Sales channel	Public room search, online booking, payment, voucher, confirmation
Front office	Walk-in booking, check-in / check-out, room assignment, invoicing, refunds
Customer self-service	Profile, booking history, invoices, reviews, loyalty points
Human resources	Attendance, shift scheduling, leave, payroll, task assignment
Management	Salary structure, approvals, room inventory, pricing, promotions, reporting
Administration	Accounts, roles & permissions, system configuration, audit, backup

1.3 Technology Stack

Layer	Technology
Client	React 18 + TypeScript + Vite, React Router, TanStack Query, Axios
Server	Node.js + Express + TypeScript
Data	MongoDB + Mongoose ODM
Auth	JWT access + refresh token, bcrypt password hashing, RBAC middleware
Integration	Payment gateway payOS (VietQR / bank transfer), Email/SMS provider

1.4 Definitions and Acronyms


Term	Meaning
HMS	Hotel Management System
UC	Use Case
RBAC	Role-Based Access Control
OTP	One-Time Password
ADR	Average Daily Rate
RevPAR	Revenue Per Available Room
COMET	Collaborative Object Modeling and Architectural Design Method

2. Actors

Per Ch. 6, an actor is an external entity that interacts with the system. HMS defines six actors with two generalization hierarchies.

Actor	Type	Description
Guest	Primary, human	An unregistered visitor. Can browse rooms, services, policies, reviews, promotions; can book a room and pay without an account; can register or log in.
Customer	Primary, human	A registered guest. Generalizes Guest — inherits every Guest capability and adds profile, booking history, invoices, reviews and loyalty features.
Employee	Primary, human	Any hotel staff member with an account. Base actor for all internal self-service: attendance, schedule, leave, payslip, tasks.
Receptionist	Primary, human	Front-desk staff. Generalizes Employee . Handles walk-in bookings, check-in/out, room status, payments.
Manager	Primary, human	Department/hotel manager. Generalizes Employee . Approves HR requests, manages inventory & pricing, views reports.
Admin	Primary, human	System administrator. Generalizes Employee . Manages accounts, roles, system configuration, audit and backup.
Payment Gateway	Secondary, external system	Authorizes and captures card payments, processes refunds.
Email / SMS Service	Secondary, external system	Delivers confirmations, OTPs and notifications.

2.1 Actor Generalization Hierarchy




An actor that generalizes another inherits all of its use cases. **Receptionist** therefore participates in **Login**, **View Personal Profile**, **Submit Leave Request** and every other **Employee** use case in addition to the front-desk ones.

3. Use Case Model — Complete Inventory


All 120 use cases from the six use case diagrams. Column **Rel.** gives the relationship to the base use case: **base** = directly associated with the actor, **«include»** = always executed as part of the base, **«extend»** = conditionally extends the base.

3.1 Guest (UC-G)




ID	Use Case	Rel.	Summary	Priority
UC-G01	Search Available Rooms	base	Search rooms by date range, occupancy, room type and price.	High
UC-G02	View Room / Room Type Details	«extend»	View photos, amenities, capacity and rate of a room type.	High
UC-G03	View Hotel Services	«extend»	Browse spa, restaurant, shuttle and other add-on services.	Medium
UC-G04	View Hotel Policies	base	Read check-in/out times, cancellation, pet and smoking policies.	Medium
UC-G05	View Customer Reviews	«extend»	Read published reviews and aggregate rating.	Medium
UC-G06	View Promotions / Offers	«extend»	Browse active promotional campaigns and seasonal offers.	Medium
UC-G07	Book Room	base	Create a reservation for selected room type and dates.	High
UC-G08	Enter Contact Information	«include»	Supply guest name, email, phone and special requests.	High
UC-G09	Select Add-on Services	«extend»	Add breakfast, airport pickup, spa to the booking.	Medium
UC-G10	Pay for Booking	«include»	Pay deposit or full amount via the payment gateway.	High
UC-G11	Apply Discount Code / Voucher	«extend»	Apply a voucher code to reduce the payable amount.	Medium
UC-G12	Receive Email / SMS Confirmation	«include»	Receive booking confirmation with reference code.	High
UC-G13	Check Booking Status	base	Look up a reservation by code and email.	High
UC-G14	Cancel Booking	«extend»	Cancel a reservation subject to the cancellation policy.	High
UC-G15	Modify Booking Details	«extend»	Change dates, occupancy or room type of a reservation.	Medium
UC-G16	Register Account	base	Create a customer account, becoming a Customer.	High
UC-G17	Login	base	Authenticate with username and password.	High
UC-G18	Submit Support Request / Contact Us	base	Send an inquiry or complaint to the hotel.	Low
UC-G19	Subscribe to Newsletter / Promotions	base	Opt in to marketing email/SMS.	Low

3.2 Customer (UC-C)




ID	Use Case	Rel.	Summary	Priority
UC-C01	Login	base	Authenticate and open a session.	High
UC-C02	Authenticate Session	«include»	Validate credentials and issue access/refresh tokens.	High
UC-C03	Reset Forgotten Password	«extend»	Request an OTP by email/SMS and set a new password.	High
UC-C04	Logout	base	Terminate the session and revoke the refresh token.	Medium
UC-C05	Change Password	«extend»	Replace the current password with a new one.	Medium
UC-C06	View Personal Profile	base	Display stored personal information.	Medium
UC-C07	Update Personal Profile	«extend»	Edit name, phone, address, date of birth.	Medium
UC-C08	Upload Avatar	«extend»	Upload a profile picture.	Low
UC-C09	Manage Saved Payment Methods	«extend»	Add or remove tokenized cards.	Medium
UC-C10	Manage Notification Preferences	«extend»	Choose which notifications to receive and by which channel.	Low
UC-C11	View Booking History	base	List all past and upcoming reservations.	High
UC-C12	View Booking Details	«include»	Show full detail of one reservation.	High
UC-C13	Rebook Previous Stay	«extend»	Create a new booking pre-filled from a past stay.	Low
UC-C14	View Payment History	base	List all payment transactions.	Medium
UC-C15	View Invoice / Receipt	«include»	Display the invoice for a stay.	Medium
UC-C16	Download Invoice	«extend»	Export the invoice as PDF.	Medium
UC-C17	Request Refund	«extend»	Submit a refund request for a cancelled or disputed charge.	High
UC-C18	Write Review	base	Publish a rating and comment for a completed stay.	Medium
UC-C19	Edit / Delete Own Review	«extend»	Modify or remove a previously published review.	Low
UC-C20	View Loyalty Points / Membership	base	Show point balance and membership tier.	Medium
UC-C21	Redeem Loyalty Points	«extend»	Convert points into a discount voucher.	Medium

3.3 Employee (UC-E)




ID	Use Case	Rel.	Summary	Priority
UC-E01	Login	base	Staff authentication into the internal portal.	High
UC-E02	Authenticate Session	«include»	Validate staff credentials, issue tokens with role claims.	High
UC-E03	Reset Forgotten Password	«extend»	OTP-based staff password reset.	Medium
UC-E04	Logout	base	End the staff session.	Medium
UC-E05	Change Password	«extend»	Staff-initiated password change.	Medium
UC-E06	View Personal Profile	base	View own employee record.	Low
UC-E07	Update Personal Profile	«extend»	Edit own contact details.	Low
UC-E08	Upload Avatar / Documents	«extend»	Upload photo, ID scan, certificates.	Low
UC-E09	Check In / Check Out Attendance	base	Record shift start and end times.	High
UC-E10	View Attendance History	«include»	List attendance records for a period.	Medium
UC-E11	Submit Attendance Correction Request	«extend»	Request correction of a wrong attendance record.	Medium
UC-E12	View Work Schedule / Shift	base	View the assigned shift roster.	High
UC-E13	Register Shift Preference	«include»	Declare preferred shifts for the next period.	Medium
UC-E14	Request Shift Swap	«extend»	Ask a colleague to exchange shifts.	Medium
UC-E15	Submit Leave Request	base	Apply for annual, sick or unpaid leave.	High
UC-E16	Cancel Leave Request	«extend»	Withdraw a pending leave request.	Medium
UC-E17	View Leave Balance	«extend»	Show remaining leave days by type.	Medium
UC-E18	View Salary / Payslip	base	View monthly payslip breakdown.	High
UC-E19	Download Payslip	«include»	Export the payslip as PDF.	Medium
UC-E20	Submit Payroll Inquiry	«extend»	Raise a question about a payslip item.	Low
UC-E21	View Assigned Tasks	base	List housekeeping/maintenance tasks assigned.	High
UC-E22	Update Task Status	«include»	Mark a task in-progress, done or blocked.	High
UC-E23	View Internal Announcements	«extend»	Read hotel-wide announcements.	Low
UC-E24	Receive Notifications	base	Receive push/email alerts for assignments and approvals.	Medium

3.4 Receptionist (UC-R)




ID	Use Case	Rel.	Summary	Priority
UC-R01	Search / Look Up Booking	base	Find a booking by code, guest name, phone or date.	High
UC-R02	View Booking Details	«include»	Show full reservation, guest and charge detail.	High
UC-R03	Create Walk-in Booking	«extend»	Create a reservation for a guest at the desk.	High
UC-R04	Modify Booking	«extend»	Change dates, room type or occupancy at the desk.	High
UC-R05	Cancel Booking	«extend»	Cancel a reservation and compute the penalty.	High
UC-R06	Check In Guest	base	Admit an arriving guest and activate the stay.	High
UC-R07	Verify Guest Identity	«include»	Validate passport/ID against the reservation.	High
UC-R08	Assign Room	«include»	Allocate a specific vacant-clean room.	High
UC-R09	Check Out Guest	base	Settle the folio and release the room.	High
UC-R10	Generate Final Invoice	«include»	Produce the final folio with all charges and taxes.	High
UC-R11	Extend Stay / Late Checkout	«extend»	Prolong the stay or grant late checkout with surcharge.	Medium
UC-R12	View Room Availability	base	Show the room rack by status and date.	High
UC-R13	Update Room Status	«include»	Set room to clean, dirty, inspected or out-of-order.	High
UC-R14	Change / Transfer Room	«extend»	Move an in-house guest to another room.	Medium
UC-R15	Process Payment	base	Take cash or card payment against a folio.	High
UC-R16	Issue Receipt / Invoice	«include»	Print or email the payment receipt.	High
UC-R17	Process Refund	«extend»	Return money for a cancellation or overcharge.	High
UC-R18	Apply Deposit / Surcharge	«extend»	Charge a security deposit or an incidental surcharge.	Medium
UC-R19	Register Add-on Service for Guest	base	Post a spa/restaurant/laundry charge to the folio.	Medium

3.5 Manager (UC-M)



ID	Use Case	Rel.	Summary	Priority
UC-M01	Manage Salary Structure	base	Define pay grades, base salary bands and allowance rules.	High
UC-M02	Adjust Employee Salary	«include»	Change an individual employee's salary with effective date.	High
UC-M03	Manage Bonus / Allowance	«extend»	Grant performance bonus or position allowance.	Medium
UC-M04	View Employee Performance	«extend»	Review KPI, attendance rate and task completion.	Medium
UC-M05	Manage Work Schedule	base	Build and publish the shift roster for a period.	High
UC-M06	Approve / Reject Leave Request	«include»	Decide on pending leave applications.	High
UC-M07	Approve Shift Swap Request	«extend»	Authorize a shift exchange between two employees.	Medium
UC-M08	Approve Attendance Correction	«extend»	Accept or reject an attendance correction request.	Medium
UC-M08b	Approve Payroll	«extend»	Lock and approve the monthly payroll run.	High
UC-M09	Manage Room Inventory	base	Add, retire and configure physical rooms.	High
UC-M10	Manage Room Type / Pricing	«include»	Define room types, base rates and seasonal pricing.	High
UC-M11	Manage Promotion / Voucher	«extend»	Create discount campaigns and voucher codes.	Medium
UC-M12	Manage Hotel Services	«extend»	Configure add-on services and their prices.	Medium
UC-M13	Approve Booking Cancellation	base	Authorize cancellations that exceed policy limits.	High
UC-M14	Approve Refund Request	«include»	Approve or reject a customer refund request.	High
UC-M15	Moderate Customer Review	«extend»	Publish, hide or reply to a customer review.	Medium
UC-M16	View Revenue Report	base	Revenue by period, channel, room type; ADR and RevPAR.	High
UC-M17	View Occupancy Report	base	Occupancy rate, arrivals, departures, forecast.	High
UC-M18	Export Report	«include»	Export a report to Excel or PDF.	Medium

3.6 Admin (UC-A)



ID	Use Case	Rel.	Summary	Priority
UC-A01	Manage User Accounts	base	Central account administration entry point.	High
UC-A02	Create Employee Account	«include»	Provision a new staff account with initial role.	High
UC-A03	Update Account Information	«extend»	Modify account attributes and department.	Medium
UC-A04	Deactivate / Lock Account	«extend»	Disable an account on termination or security event.	High
UC-A04b	Reset User Password	«extend»	Force-reset a user password administratively.	Medium
UC-A05	Manage Roles	base	Define the role catalogue.	High
UC-A06	Assign Role to Account	«include»	Grant a role to a user account.	High
UC-A07	Configure Role Permissions	«extend»	Edit the permission set of a role.	High
UC-A08	Revoke Role from Account	«extend»	Remove a role from an account.	High
UC-A09	Configure System Settings	base	Global system configuration entry point.	Medium
UC-A10	Manage Hotel Information	«include»	Maintain hotel name, address, contact, branding.	Medium
UC-A11	Manage Hotel Policies	«extend»	Edit check-in/out, cancellation and deposit policies.	Medium
UC-A12	Configure Payment Gateway	«extend»	Set gateway credentials, currency and modes.	High
UC-A13	View System Audit Log	base	Inspect the immutable audit trail.	Medium
UC-A14	View Login History	«include»	Review authentication attempts per account.	Medium
UC-A15	Export Audit Log	«extend»	Export audit entries for compliance.	Low
UC-A16	Backup Database	base	Trigger or schedule a database backup.	High
UC-A17	Restore Database	«extend»	Restore the database from a backup set.	High
UC-A18	Monitor System Health	base	View uptime, error rate, queue depth, resource usage.	Medium

3.7 Use Case Count Summary

Actor	Base	«include»	«extend»	Total
Guest	8	4	7	19
Customer	7	4	10	21
Employee	9	5	10	24
Receptionist	6	7	6	19
Manager	6	5	7	18
Admin	6	4	9	19
Total	42	29	49	120

4. Detailed Use Case Specifications

The twelve highest-priority use cases below are specified in full. They were selected because they carry the core business value (booking → payment → check-in → check-out → invoice), the critical control flows (authentication, approval workflows) and the highest architectural risk (concurrency on room allocation, external gateway integration).

#	ID	Use Case	Primary Actor	Why detailed
1	UC-G17	Login	Guest / Customer / Employee	Gateway to every authenticated use case
2	UC-G16	Register Account	Guest	Creates the Customer actor
3	UC-G01	Search Available Rooms	Guest	Highest-traffic read path
4	UC-G07	Book Room	Guest	Core revenue transaction
5	UC-G10	Pay for Booking	Guest	External gateway, money-critical
6	UC-G14	Cancel Booking	Guest / Customer	Policy + refund chain
7	UC-R06	Check In Guest	Receptionist	Concurrency on room allocation
8	UC-R09	Check Out Guest	Receptionist	Folio settlement
9	UC-R15	Process Payment	Receptionist	Front-desk money handling
10	UC-C17	Request Refund	Customer	Multi-step approval workflow
11	UC-M06	Approve / Reject Leave Request	Manager	Representative HR workflow
12	UC-A06	Assign Role to Account	Admin	Security-critical RBAC

UC-G17 — Login

Field	Value
ID and Name	UC-G17 — Login
Created By	System Design Team
Date Created	22/09/2026
Primary Actor	Guest (becoming Customer), Employee
Secondary Actors	Email / SMS Service
Trigger	The user clicks the Login button and submits credentials.

Description Allows a registered user (Customer or Employee) to authenticate with the HMS using a valid username/email and password, receiving a session token whose role claims determine the functions available to them.

Preconditions

- PRE-1: The user has a registered account in the system.
- PRE-2: The account status is **ACTIVE** (not locked or deactivated).

Postconditions

- POST-1: The user is authenticated; an access token and refresh token are issued.
- POST-2: The user is redirected to the landing page matching their role.
- POST-3: A login record is written to the audit log.

Normal Flow — 1.0: Login with username and password

1. The user opens the login page.
2. The system displays the login form (username/email, password).
3. The user enters valid credentials.
4. The user clicks **Login**.
5. The system validates that both fields are non-empty.
6. The system looks up the account and verifies the password hash. («include» UC-C02 Authenticate Session)
7. The system checks that the account is active and not locked.
8. The system issues an access token (15 min) and a refresh token (7 days).
9. The system resets the failed-attempt counter and records the login in the audit log.
10. The system redirects the user to the role-appropriate dashboard.

Alternative Flows

- **1.1: Login with Google (OAuth)**
 1. The user clicks **Login with Google**.
 2. The system redirects to the Google consent screen.
 3. The user authorizes the application.
 4. The system receives the profile; if no local account exists it creates one and links it.
 5. Continue from step 8 of the Normal Flow.
- **1.2: Forgotten password** — («extend» UC-C03 Reset Forgotten Password)
 1. The user clicks **Forgot password**.
 2. The system sends an OTP via the Email/SMS Service.
 3. The user submits the OTP and a new password.
 4. The system updates the password hash and returns to step 2 of the Normal Flow.

Exceptions

- **1.0.E1 — Empty field:** "Username and password must not be empty." Return to step 3.
- **1.0.E2 — Account not found:** "Invalid username or password." Return to step 3. *(The message is deliberately generic to prevent account enumeration.)*
- **1.0.E3 — Wrong password:** Increment the failed counter, show "Invalid username or password." Return to step 3.
- **1.0.E4 — Account locked after 5 failures:** Set status **LOCKED**, notify the user by email, show "Account locked. Contact the administrator." Terminate.
- **1.0.E5 — Account deactivated:** "This account has been deactivated." Terminate.
- **1.0.E6 — Email not verified:** the credentials are correct but the account is still **PENDING_VERIFICATION** (PRE-2). "Please verify your email address before signing in." Offer to resend the link. *(Checked only after the password is proven, so the status is never revealed to someone without the credentials.)*

Field	Value
Priority	High
Frequency of Use	Every session; several hundred per day.
Business Rules	BR-01 Password ≥ 8 chars with upper, lower, digit. BR-02 Lock after 5 consecutive failures. BR-03 Access token 15 min, refresh token 7 days.
Non-functional	Response ≤ 1 s at 200 concurrent logins; passwords hashed with bcrypt cost ≥ 10; TLS mandatory.
Assumptions	The user has network access; the email/SMS provider is available for OTP.

UC-G16 — Register Account

Field	Value
ID and Name	UC-G16 — Register Account
Primary Actor	Guest
Secondary Actors	Email / SMS Service
Trigger	The Guest clicks Sign up and submits the registration form.

Description Allows an unregistered Guest to create a Customer account, after which they gain access to profile, booking history, invoice, review and loyalty features.

Preconditions

- PRE-1: The email address is not already registered.

Postconditions

- POST-1: A new account is created with status **PENDING_VERIFICATION** and role **CUSTOMER**.
- POST-2: A verification email is sent.
- POST-3: After verification the status becomes **ACTIVE** and a loyalty account is opened with 0 points.

Normal Flow — 1.0: Self-registration

1. The Guest opens the registration page.
2. The system displays the form: full name, email, phone, password, confirm password.
3. The Guest fills the form and accepts the terms of service.
4. The Guest clicks **Register**.
5. The system validates format, password strength and password match.
6. The system checks that the email and phone are not already in use.
7. The system hashes the password and creates the account with status **PENDING_VERIFICATION**.
8. The system creates a linked loyalty account with a zero balance.
9. The system sends a verification link valid for 24 hours.
10. The system shows "Please check your email to verify your account."
11. The Guest clicks the link; the system sets the status to **ACTIVE** and redirects to login.

Alternative Flows

- **1.1: Registration during checkout** — the Guest ticks "Create an account" on the booking form; the system reuses the contact data already entered and continues from step 5.
- **1.2: Social sign-up** — the Guest registers via Google; the email is treated as verified and the status is set directly to **ACTIVE**.

Exceptions

- **1.0.E1 — Email already registered:** "This email is already in use. Log in instead?" Return to step 3.
- **1.0.E2 — Weak password:** Show the strength rule that failed. Return to step 3.
- **1.0.E3 — Passwords do not match:** "Passwords do not match." Return to step 3.
- **1.0.E4 — Verification link expired:** Offer to resend; a new link is generated.

Field	Value
Priority	High
Frequency of Use	Tens per day.
Business Rules	BR-04 One account per email. BR-05 Verification link valid 24 h. BR-06 Terms must be accepted.
Non-functional	Verification email delivered within 60 s.

UC-G01 — Search Available Rooms

Field	Value
ID and Name	UC-G01 — Search Available Rooms
Primary Actor	Guest
Secondary Actors	—
Trigger	The Guest submits the search form with dates and occupancy.

Description Lets a Guest find room types that are available for a given date range and occupancy, with live prices reflecting the applicable seasonal rate and active promotions.

Preconditions

- PRE-1: Room types and rate plans are configured (UC-M10).

Postconditions

- POST-1: A list of available room types with prices is displayed.
- POST-2: No system state is changed (read-only use case).

Normal Flow — 1.0: Search by date and occupancy

1. The Guest opens the home or search page.
2. The system displays the search form: check-in date, check-out date, adults, children, room count.
3. The Guest enters the criteria and clicks **Search**.

- The system validates that check-in $\geq$ today and check-out $>$ check-in.
- The system computes, for each room type, `availableCount = totalRooms - confirmedOverlappingBookings - blockedRooms`.
- The system filters out room types whose `availableCount` is 0 or whose capacity is below the requested occupancy.
- The system computes the price per room type for the stay, applying the seasonal rate for each night.
- The system applies any automatically-eligible promotion. (*«extend» UC-G06*)
- The system displays the result list sorted by price, with photos, capacity, amenities and total price.

Alternative Flows

- 1.1: Refine with filters** — the Guest applies price range, bed type, view or amenity filters; the system re-filters the current result set without another availability computation.
- 1.2: View details** — (*«extend» UC-G02*) the Guest clicks a room type and the system shows the full gallery, amenity list, policy and review summary.
- 1.3: Flexible dates** — the Guest selects " $\pm$ 3 days"; the system returns an availability calendar for the surrounding window.

Exceptions

- 1.0.E1 — Check-in in the past:** "Check-in date cannot be in the past." Return to step 3.
- 1.0.E2 — Check-out not after check-in:** "Check-out must be after check-in." Return to step 3.
- 1.0.E3 — Stay exceeds 30 nights:** "For stays longer than 30 nights please contact us." Return to step 3.
- 1.0.E4 — No availability:** "No rooms available for these dates." The system suggests the nearest available dates.

Field	Value
Priority	High
Frequency of Use	Highest-volume use case; thousands per day.
Business Rules	BR-07 Max 30 nights per booking. BR-08 Max 5 rooms per search. BR-09 Price = Σ nightly seasonal rate – promotion.
Non-functional	Response $\leq$ 2 s for a 30-day window; availability results cached 60 s; must handle 500 concurrent searches.

UC-G07 — Book Room

Field	Value
ID and Name	UC-G07 — Book Room
Primary Actor	Guest (or Customer)
Secondary Actors	Payment Gateway, Email / SMS Service
Trigger	The Guest clicks Book now on a selected room type.

Description Creates a reservation for a selected room type and date range, collects the guest contact details and optional add-on services, takes payment and issues a confirmation. This is the central revenue-producing use case of the system.

Preconditions

- PRE-1: The selected room type has availability for the requested dates (UC-G01).
- PRE-2: The Guest has completed a search and selected a room type.

Postconditions

- POST-1: A `Booking` exists with status `CONFIRMED` and a unique booking code.
- POST-2: Room inventory for those dates is decremented.
- POST-3: A `Payment` record exists with status `PAID` (or `PENDING` for pay-at-hotel).
- POST-4: A confirmation email/SMS has been sent.
- POST-5: If the actor is a Customer, the booking is linked to their account; loyalty points are credited later, on check-out (BR-29).

Normal Flow — 1.0: Online booking with immediate payment

- The Guest selects a room type and clicks **Book now**.
- The system re-verifies availability for the dates and holds the inventory for 15 minutes.
- The system displays the contact form. (*«include» UC-G08 Enter Contact Information*)

- 4. The Guest enters full name, email, phone and any special request.
- 5. The system optionally offers add-on services. («extend» UC-G09 Select Add-on Services)
- 6. The Guest may select add-ons; the system recalculates the total.
- 7. The system displays the booking summary: room type, dates, nights, guests, add-ons, taxes, total.
- 8. The Guest may enter a voucher code. («extend» UC-G11 Apply Discount Code / Voucher)
- 9. The Guest confirms. The system records the booking with status `PENDING` and a booking code, then proceeds to payment. («include» UC-G10 Pay for Booking) — the booking is recorded first so that every payment references a booking it can be reconciled against.
- 10. On successful payment the system confirms the booking (`PENDING` → `CONFIRMED` , \$6.4).
- 11. The system commits the inventory decrement and releases the hold.
- 12. The system sends the confirmation. («include» UC-G12 Receive Email / SMS Confirmation)
- 13. The system displays the confirmation page with the booking code.

Alternative Flows

- **1.1: Pay at hotel** — at step 9 the Guest chooses "Pay at hotel"; the system creates the booking with `paymentStatus = PENDING` , requires a credit-card guarantee, and continues from step 11.
- **1.2: Booking as a logged-in Customer** — the contact form at step 3 is pre-filled from the profile, and the booking is linked to the Customer's account. Loyalty points (1 % of room revenue, BR-12) are credited only when the stay completes (BR-29) — crediting at booking time would let a guest book, collect points and cancel.
- **1.3: Multi-room booking** — the Guest books several rooms of the same type; steps 2–11 are performed per room within a single transaction and a single booking code.

Exceptions

- **1.0.E1 — Availability lost during the flow:** another booking consumed the last room. "This room is no longer available." Return the Guest to UC-G01 with the criteria preserved.
- **1.0.E2 — Hold expired (15 min):** "Your session expired. Please search again." Release the hold and return to UC-G01.
- **1.0.E3 — Payment declined:** (see UC-G10) the booking moves `PENDING` → `CANCELLED` ; the hold is released; the Guest may retry. If the gateway times out instead, the booking stays `PENDING` with its hold until the gateway webhook confirms or fails it.
- **1.0.E4 — Invalid contact data:** the system highlights the offending field and returns to step 4.
- **1.0.E5 — Confirmation delivery failure:** the booking remains valid; the system queues a retry and displays the booking code on screen.

Field	Value
Priority	High
Frequency of Use	The primary revenue transaction; dozens to hundreds per day.
Business Rules	BR-10 Inventory hold expires after 15 min. BR-11 Booking code format <code>HMS-YYYYMMDD-XXXXX</code> . BR-12 Loyalty accrual 1 % of room revenue for Customers, credited on check-out (BR-29). BR-13 A booking must not exceed the room-type capacity.
Non-functional	The availability check and decrement must be atomic under concurrency (optimistic locking on the inventory document). End-to-end ≤ 5 s excluding gateway latency.
Assumptions	The payment gateway is reachable; rates and taxes are configured.

UC-G10 — Pay for Booking

Field	Value
ID and Name	UC-G10 — Pay for Booking
Primary Actor	Guest (or Customer)
Secondary Actors	Payment Gateway — <code>payOS</code> (VietQR / bank transfer, https://payos.vn)
Trigger	Included from UC-G07 step 9.

Description Collects payment for a booking through `payOS` and records the resulting transaction, guaranteeing that the booking is only confirmed when the money has actually arrived. `payOS` is **asynchronous**: the guest pays from their own banking app by scanning a VietQR, and `payOS` reports the result afterwards. A payment is therefore never approved in the same request that creates it.

Preconditions

- PRE-1: A **PENDING** booking exists with a computed payable amount > 0 (UC-G07 step 9).
- PRE-2: payOS credentials are configured and the webhook URL is registered (UC-A12).

Postconditions

- POST-1: A **Payment** record exists with status **PAID**, **FAILED** or **PENDING**, carrying a unique integer payOS **orderCode**.
- POST-2: On success the bank transfer reference is stored and the booking moves **PENDING → CONFIRMED**.
- POST-3: On failure, cancellation or expiry the booking moves **PENDING → CANCELLED** and the inventory hold is released.

Normal Flow — 1.0: VietQR payment via payOS

1. The system displays the amount due.
2. The Guest may apply a voucher. («extend» UC-G11) The system revalidates the code and recomputes the amount.
3. The system creates a **Payment** record with status **PENDING**, an idempotency key and a new payOS **orderCode** — **before** calling payOS, so a timeout still leaves a record to reconcile against.
4. The system creates a payOS payment link signed with HMAC-SHA256, with a bank memo of at most 9 characters and an expiry one minute before the 15-minute inventory hold.
5. The system redirects the Guest to the payOS checkout page.
6. The Guest scans the VietQR with a banking app and transfers the money.
7. payOS sends a signed webhook to the system.
8. The system verifies the webhook signature and checks that the amount received equals the amount due.
9. The system atomically sets the **Payment** to **PAID** (exactly once), stores the bank reference, and confirms the booking.
10. payOS redirects the Guest to the result page, which shows the confirmation.

Alternative Flows

- **1.1: Webhook not received** (e.g. a development machine that payOS cannot reach, or a lost delivery) — when the Guest reaches the result page, the system asks payOS server-to-server for the link status and applies it (steps 8–9). The status in the return URL's query string is **never trusted**, because anyone can type it.
- **1.2: Webhook and returning Guest arrive together** — both paths converge on one conditional atomic update; only one applies, so the money is booked once. (*Verified by test: without the guard, ten concurrent confirmations booked the payment ten times.*)
- **1.3: Guest cancels on the payOS page** — the Guest is sent to the cancel URL; the system reads the link status **CANCELLED** and moves the booking to **CANCELLED**, releasing the room.
- **1.4: Front-desk payment (UC-R15)** — the same link is created at the desk; the Receptionist shows its VietQR; the folio balance falls when the webhook arrives.

Exceptions

- **1.0.E1 — payOS refuses to create the link:** the **Payment** becomes **FAILED**, the booking **CANCELLED**, the hold is released; "Payment could not be started." The Guest may retry.
- **1.0.E2 — Transfer of the wrong amount (UNDERPAID):** the payment is **not** confirmed automatically; it stays **PENDING** and an audit entry **PAYMENT_AMOUNT_MISMATCH** is raised for staff to resolve.
- **1.0.E3 — payOS timeout while creating the link:** the **Payment** stays **PENDING** with its **orderCode**; the webhook or the reconciler settles it. No second link can be created for the same payment, because payOS rejects a reused **orderCode**.
- **1.0.E4 — Invalid webhook signature:** the request is rejected with 400, nothing changes, and the attempt is logged. The webhook endpoint is public, so the signature is its only authentication.
- **1.0.E5 — Voucher no longer valid:** "This voucher has expired or reached its usage limit." Recompute without it and return to step 2.
- **1.0.E6 — Guest abandons the payOS page:** the link expires before the inventory hold and the room returns to inventory when the hold lapses. The **PENDING** payment is marked **FAILED** the next time it is reconciled. (*A periodic sweeper for never-reconciled links is future work.*)

Field	Value
Priority	High
Frequency of Use	Once per booking.
Business Rules	BR-14 A booking is confirmed only after PAID . BR-15 Every payment carries an idempotency key and a payOS orderCode unique for all time. BR-16 Bank data never touches HMS servers — payOS hosts the checkout. BR-50 payOS has no refund API : refunds are made by manual bank transfer (UC-G14, UC-C17).
Non-functional	payOS calls time out at 30 s; signatures use HMAC-SHA256 with the checksum key and are checked byte-for-byte against the official @payos/node SDK; webhook signatures are compared in constant time; amounts are integer VND.

UC-G14 — Cancel Booking

Field	Value
ID and Name	UC-G14 — Cancel Booking
Primary Actor	Guest / Customer
Secondary Actors	Manager (for out-of-policy cases), Payment Gateway, Email Service
Trigger	The user opens a booking and clicks Cancel booking .

Description Cancels an existing reservation, computes the cancellation penalty from the hotel policy, releases the inventory and initiates any refund due.

Preconditions

- PRE-1: The booking exists with status **CONFIRMED**.
- PRE-2: The booking has not yet been checked in.

Postconditions

- POST-1: The booking status becomes **CANCELLED** (or **PENDING_APPROVAL** when out of policy).
- POST-2: The room inventory for those dates is released.
- POST-3: A refund is initiated for the refundable portion, if any.
- POST-4: A cancellation notice is emailed to the guest.

Normal Flow — 1.0: Cancel within the free-cancellation window

1. The user opens the booking (UC-G13 / UC-C12) and clicks **Cancel booking**.
2. The system verifies that the booking is **CONFIRMED** and not yet checked in.
3. The system evaluates the cancellation policy against the current time and the check-in date.
4. The system computes the penalty and the refundable amount and displays them for confirmation.
5. The user confirms the cancellation and optionally selects a reason.
6. The system sets the booking status to **CANCELLED** and records the reason and timestamp.
7. The system releases the inventory for the affected dates.
8. The system initiates the refund through the gateway for the refundable amount.
9. The system sends the cancellation confirmation email.
10. The system displays the cancellation summary.

Alternative Flows

- **1.1: Cancellation outside the policy window** — when the penalty is 100 % or the check-in is within 24 h, the system creates a **RefundRequest** with status **PENDING** and routes it to the Manager. (→ *UC-M14 Approve Refund Request*) The booking is cancelled immediately but the refund waits for approval.
- **1.2: Non-refundable rate** — the system shows "This rate is non-refundable. No refund will be issued." and proceeds without a refund.
- **1.3: Cancellation by the Receptionist** — (*UC-R05*) the Receptionist cancels at the desk on the guest's behalf, with an override privilege to waive the penalty subject to Manager approval.

Exceptions

- **1.0.E1 — Booking already checked in:** "A booking that has been checked in cannot be cancelled. Please contact the front desk." Terminate.
- **1.0.E2 — Booking already cancelled:** "This booking has already been cancelled." Terminate.
- **1.0.E3 — Refund failure at the gateway:** the cancellation stands; the refund is queued for retry and the Admin is alerted.
- **1.0.E4 — Stay already in progress:** redirect to the early-departure procedure at the front desk.

Field	Value
Priority	High
Frequency of Use	Roughly 10–15 % of bookings.
Business Rules	BR-17 Free cancellation ≥ 48 h before check-in. BR-18 50 % penalty between 48 h and 24 h. BR-19 100 % penalty inside 24 h. BR-20 Non-refundable rates are never auto-refunded.
Non-functional	The inventory release must be transactional with the status change; refunds initiated within 24 h and settled within 7 working days.

UC-R06 — Check In Guest

Field	Value
ID and Name	UC-R06 — Check In Guest
Primary Actor	Receptionist
Secondary Actors	—
Trigger	A guest arrives at the front desk and presents a booking code or identity document.

Description Admits an arriving guest: verifies identity against the reservation, allocates a specific vacant-clean room, collects any outstanding balance or deposit, and activates the stay so the folio can receive charges.

Preconditions

- PRE-1: A booking exists with status **CONFIRMED** for today.
- PRE-2: The Receptionist is authenticated with the **CHECK_IN** permission.
- PRE-3: At least one room of the booked type is in status **VACANT_CLEAN**.

Postconditions

- POST-1: The booking status becomes **CHECKED_IN** with the actual arrival time recorded.
- POST-2: A specific room is allocated and its status becomes **OCCUPIED**.
- POST-3: An open folio exists for the stay.
- POST-4: Guest identity details are recorded for legal registration.

Normal Flow — 1.0: Standard check-in of a confirmed booking

1. The Receptionist searches for the booking. («include» UC-R01 / UC-R02)
2. The system displays the reservation: guest, room type, dates, occupancy, balance.
3. The Receptionist requests the guest's identity document.
4. The Receptionist records the document type, number and expiry, and matches the name against the reservation. («include» UC-R07 Verify Guest Identity)
5. The system validates that the document is not expired and that the guest is of legal age.
6. The system lists the rooms of the booked type in status **VACANT_CLEAN**. («include» UC-R08 Assign Room)
7. The Receptionist selects a room, honouring any preference (floor, view, quiet).
8. The system locks the selected room to prevent double allocation.
9. The system shows any outstanding balance and required deposit.
10. The Receptionist collects the balance and/or deposit. («include» UC-R15 Process Payment, «extend» UC-R18 Apply Deposit)
11. The Receptionist confirms the check-in.
12. The system sets the booking to **CHECKED_IN**, sets the room to **OCCUPIED**, records the arrival timestamp, and opens the folio.
13. The system issues the key card and prints the registration card for signature.

Alternative Flows

- **1.1: Walk-in check-in** — no prior reservation. The Receptionist first creates one («extend» UC-R03 Create Walk-in Booking) and then continues from step 3.
- **1.2: Early check-in** — the guest arrives before the standard time. The system applies the early-check-in surcharge if a room is ready, or places the guest on a waiting list.
- **1.3: Room upgrade** — no room of the booked type is ready but a higher type is. The Receptionist assigns the upgrade, complimentary or charged, and the system records the reason.
- **1.4: Group check-in** — several bookings under one group code are processed together; the system assigns rooms in bulk and opens one master folio with individual sub-folios.

Exceptions

- **1.0.E1 — Booking not found:** offer to search by name/phone or to create a walk-in booking.
- **1.0.E2 — Identity mismatch:** "The document does not match the reservation holder." Require the reservation holder or authorization; do not proceed.
- **1.0.E3 — Expired identity document:** "The identity document has expired." Escalate to the Manager.
- **1.0.E4 — No vacant-clean room of the booked type:** the system offers an upgrade (1.3), or flags housekeeping to prioritize a dirty room, or places the guest on a waiting list.
- **1.0.E5 — Outstanding balance unpaid:** the check-in cannot be completed until the balance is settled or the Manager authorizes an exception.
- **1.0.E6 — Room allocated concurrently by another Receptionist:** the optimistic lock at step 8 fails. "This room has just been taken." Return to step 6 with a refreshed list.
- **1.0.E7 — Guest under the legal age without a guardian:** refuse the check-in per BR-24.

Field	Value
Priority	High
Frequency of Use	Once per stay; peaks around the standard 14:00 check-in time.
Business Rules	BR-21 Standard check-in from 14:00. BR-22 Identity registration is legally mandatory for all adult occupants. BR-23 A deposit is required for incidentals. BR-24 Minimum age 18 unless accompanied by a guardian. BR-25 A room may be allocated to exactly one active stay.
Non-functional	Check-in completed in ≤ 3 minutes of desk time; room allocation must be race-free under concurrent Receptionists; must remain operable in a degraded offline mode with later reconciliation.

UC-R09 — Check Out Guest

Field	Value
ID and Name	UC-R09 — Check Out Guest
Primary Actor	Receptionist
Secondary Actors	Payment Gateway, Email Service
Trigger	The guest presents at the desk to depart, or the departure is processed at the end of the stay.

Description Closes an in-house stay: consolidates all folio charges, produces the final invoice, settles the balance, returns the deposit and releases the room to housekeeping.

Preconditions

- PRE-1: The booking status is `CHECKED_IN`.
- PRE-2: The Receptionist is authenticated with the `CHECK_OUT` permission.

Postconditions

- POST-1: The booking status becomes `CHECKED_OUT` with the actual departure time recorded.
- POST-2: The folio is closed with a zero balance.
- POST-3: A final invoice is generated and issued.
- POST-4: The room status becomes `VACANT_DIRTY` and a housekeeping task is created.
- POST-5: Loyalty points are credited for a Customer.

Normal Flow — 1.0: Standard check-out

1. The Receptionist opens the in-house stay by room number or guest name.
2. The system displays the folio: room charges per night, add-on services, taxes, payments already made, balance.
3. The Receptionist reviews the outstanding charges with the guest and posts any final items (minibar, late charges). («extend» UC-R19)
4. The system recalculates the total and the taxes.
5. The system generates the final invoice. («include» UC-R10 Generate Final Invoice)
6. The Receptionist collects the outstanding balance. («include» UC-R15 Process Payment)
7. The system releases or applies the security deposit.
8. The system issues the invoice/receipt to the guest by print and email. («include» UC-R16)
9. The Receptionist collects the key card and confirms the check-out.
10. The system sets the booking to **CHECKED_OUT**, closes the folio and records the departure time.
11. The system sets the room to **VACANT_DIRTY** and raises a housekeeping task. («include» UC-R13 Update Room Status)
12. The system credits loyalty points if the guest is a registered Customer.
13. The system schedules the post-stay review invitation. (→ UC-C18)

Alternative Flows

- **1.1: Late check-out** — («extend» UC-R11) the guest departs after the standard time; the system applies the late-checkout surcharge or waives it per the Manager's authorization.
- **1.2: Early departure** — the guest leaves before the booked departure date; the system recomputes the charges and applies any early-departure penalty.
- **1.3: Express check-out** — the guest authorized the card on file; the system settles automatically, emails the invoice and performs steps 10–12 without the guest at the desk.
- **1.4: Company/corporate billing** — the balance is transferred to the corporate account ledger instead of being collected; the invoice is issued to the company.

Exceptions

- **1.0.E1 — Payment declined at settlement:** the check-out is blocked; the guest must supply another method; the Manager may authorize a debtor entry.
- **1.0.E2 — Disputed charge:** the item is flagged **DISPUTED**, escalated to the Manager, and the check-out proceeds on the undisputed balance.
- **1.0.E3 — Room damage found:** the Receptionist posts a damage charge against the deposit; if the damage exceeds the deposit a supplementary charge is raised.
- **1.0.E4 — Deposit refund fails at the gateway:** the check-out completes; the refund is queued for retry and the guest is informed of the timeline.
- **1.0.E5 — Missing key card:** a replacement fee is posted before completion.

Field	Value
Priority	High
Frequency of Use	Once per stay; peaks around the standard 12:00 check-out time.
Business Rules	BR-26 Standard check-out by 12:00. BR-27 Late check-out to 18:00 is charged at 50 % of the nightly rate. BR-28 The folio must reach zero before the stay closes. BR-29 Loyalty points are credited only on completed stays. BR-30 Invoices are immutable once issued; corrections require a credit note.
Non-functional	Invoice generated in ≤ 3 s; invoice numbering strictly sequential and gapless for tax compliance; folio totals computed in integer minor units.

UC-R15 — Process Payment

Field	Value
ID and Name	UC-R15 — Process Payment
Primary Actor	Receptionist
Secondary Actors	Payment Gateway
Trigger	A balance is due at check-in, at check-out, or when a guest settles a charge at the desk.

Description Records a payment taken at the front desk against a booking folio, by cash, card, bank transfer or voucher, and issues the corresponding receipt.

Preconditions

- PRE-1: A folio exists with a positive balance.
- PRE-2: The Receptionist has the `PROCESS_PAYMENT` permission.

Postconditions

- POST-1: A `Payment` record exists with status `PAID`.
- POST-2: The folio balance is reduced by the amount paid.
- POST-3: A receipt is issued.
- POST-4: The cash-drawer session total is updated for a cash payment.

Normal Flow — 1.0: Card payment at the desk

1. The Receptionist opens the folio and selects **Take payment**.
2. The system displays the outstanding balance.
3. The Receptionist enters the amount and selects the method **Card**.
4. The system creates a `Payment` with status `PENDING` and an idempotency key.
5. The system sends the amount to the card terminal / gateway.
6. The guest authorizes on the terminal.
7. The gateway returns an approval with a transaction reference.
8. The system sets the `Payment` to `PAID` and stores the reference.
9. The system reduces the folio balance and issues the receipt. («include» UC-R16)

Alternative Flows

- **1.1: Cash payment** — the Receptionist selects **Cash**, enters the tendered amount; the system computes the change, records the payment and updates the cash-drawer session.
- **1.2: Split payment** — the balance is settled across several methods; steps 3–8 repeat until the balance reaches zero.
- **1.3: Voucher / loyalty redemption** — a voucher or redeemed points cover part of the balance; the system validates the instrument and records a non-cash settlement.
- **1.4: Partial payment** — the guest pays less than the balance; the folio keeps the remainder open.

Exceptions

- **1.0.E1 — Card declined:** set `Payment` to `FAILED`, inform the guest, return to step 3 for another method.
- **1.0.E2 — Terminal offline:** fall back to manual card entry or cash; the Receptionist records the method used.
- **1.0.E3 — Amount exceeds the balance:** "The amount exceeds the outstanding balance." Offer to record the excess as a deposit or reduce the amount.
- **1.0.E4 — Gateway timeout:** the payment stays `PENDING`; the Receptionist must not retry blindly — the idempotency key prevents a double charge; the transaction is reconciled from the terminal batch.
- **1.0.E5 — Cash drawer not opened for the shift:** require the Receptionist to open a drawer session first.

Field	Value
Priority	High
Frequency of Use	Several times per stay.
Business Rules	BR-31 Every payment must be attributed to a folio and a cashier. BR-32 Cash payments must belong to an open drawer session. BR-33 Payments are immutable — corrections are made by a reversal entry. BR-34 A receipt is mandatory for every payment.
Non-functional	Payment recorded in ≤ 2 s excluding terminal time; full audit of cashier, terminal, timestamp and amount; amounts in integer minor units.

UC-C17 — Request Refund

Field	Value
ID and Name	UC-C17 — Request Refund
Primary Actor	Customer
Secondary Actors	Manager (approver), Payment Gateway, Email Service
Trigger	The Customer opens an invoice and clicks Request refund .

Description Lets a Customer ask for money back on a cancelled, overcharged or disputed booking. The request enters an approval workflow; on approval the money is returned through the original payment channel.

Preconditions

- PRE-1: A **Payment** with status **PAID** exists for the booking.
- PRE-2: The Customer is authenticated and owns the booking.
- PRE-3: No refund request is already pending for the same payment.

Postconditions

- POST-1: A **RefundRequest** exists with status **PENDING**.
- POST-2: The Manager is notified for approval.
- POST-3: On approval a refund transaction is issued to the original method and the request becomes **COMPLETED**.

Normal Flow — 1.0: Refund request and approval

1. The Customer opens the booking or invoice. («include» UC-C15)
2. The Customer clicks **Request refund**.
3. The system checks eligibility: the payment is **PAID**, within the 90-day refund window, and has no pending request.
4. The system displays the refund form: refundable amount, reason category, description, attachments.
5. The Customer selects a reason and submits the request.
6. The system creates a **RefundRequest** with status **PENDING** and a reference number.
7. The system notifies the Manager and emails the Customer an acknowledgement with the reference.
8. The Manager reviews the request. (→ UC-M14 Approve Refund Request)
9. The Manager approves the full or a partial amount with a note.
10. The system sets the request to **APPROVED** and issues the refund to the original payment method through the gateway.
11. The gateway confirms; the system sets the request to **COMPLETED** and records the refund transaction.
12. The system emails the Customer the outcome and the expected settlement date.

Alternative Flows

- **1.1: Automatic refund within policy** — where the cancellation falls in the free window (UC-G14), the system approves automatically at step 8 without Manager involvement.
- **1.2: Partial approval** — the Manager approves less than requested with a justification; the Customer is informed of the amount and the reason.
- **1.3: Refund to an alternative method** — the original card has expired; after identity verification the Manager authorizes a bank transfer to the Customer's account.

- **1.4: Rejection** — the Manager rejects with a reason; the request becomes **REJECTED** and the Customer is notified with the appeal channel.

Exceptions

- **1.0.E1 — Payment not refundable (non-refundable rate):** "This booking was made under a non-refundable rate." Offer the support channel.
- **1.0.E2 — Refund window expired:** "Refund requests must be made within 90 days of payment." Terminate.
- **1.0.E3 — A request already exists:** show the existing request and its status instead of creating a duplicate.
- **1.0.E4 — Gateway cannot refund:** the request stays **APPROVED** with a **REFUND_FAILED** flag; the Admin is alerted and a manual transfer is arranged. *With payOS this is the normal path, not an exception: payOS has no refund API (BR-50).*
- **1.0.E5 — Refund exceeds the amount paid:** the system caps the refundable amount at the sum actually captured.

Field	Value
Priority	High
Frequency of Use	A few per week.
Business Rules	BR-35 Refunds go to the original payment method by default. BR-36 The refund window is 90 days from payment. BR-37 A refund may never exceed the captured amount. BR-38 Refunds above a threshold require Manager approval. BR-39 Every refund decision is audit-logged with the approver.
Non-functional	Manager decision within 3 working days; settlement within 7–14 working days depending on the issuer; the whole chain is traceable from request to gateway reference.

UC-M06 — Approve / Reject Leave Request

Field	Value
ID and Name	UC-M06 — Approve / Reject Leave Request
Primary Actor	Manager
Secondary Actors	Employee (requester), Notification Service
Trigger	The Manager opens the pending-approvals queue, or is notified of a new leave request.

Description Lets a Manager decide on leave applications submitted by employees, checking the leave balance, the staffing impact on the roster, and the overlap with other approved leave.

Preconditions

- PRE-1: At least one **LeaveRequest** has status **PENDING**.
- PRE-2: The Manager has the **APPROVE_LEAVE** permission for the requester's department.

Postconditions

- POST-1: The request status becomes **APPROVED** or **REJECTED**, with the decision maker and timestamp.
- POST-2: On approval the employee's leave balance is decremented and the roster is marked.
- POST-3: The employee is notified of the outcome.

Normal Flow — 1.0: Approve a leave request

1. The Manager opens the pending-approvals list.
2. The system displays the pending requests with employee, leave type, dates, days, reason and submission time.
3. The Manager selects a request.
4. The system displays the detail together with the employee's remaining balance, the shifts affected, and other approved leave overlapping those dates.
5. The system flags any staffing risk, for example when coverage would fall below the departmental minimum.
6. The Manager approves with an optional note.
7. The system sets the request to **APPROVED**, records the approver and the timestamp.
8. The system decrements the employee's leave balance by the number of days.
9. The system marks the affected shifts as on-leave and flags the roster gaps for reassignment.

10. The system notifies the employee and updates the department leave calendar.

Alternative Flows

- **1.1: Reject the request** — the Manager rejects with a mandatory reason; the status becomes **REJECTED**; the balance is untouched; the employee is notified with the reason.
- **1.2: Partial approval** — the Manager approves a shorter period than requested; the system splits the request, approves the granted days and rejects the rest with a note.
- **1.3: Bulk approval** — the Manager selects several low-risk requests and approves them in one action; the system applies steps 7–10 to each.
- **1.4: Escalation** — leave longer than 10 consecutive days is escalated to a higher authority; the status becomes **ESCALATED**.

Exceptions

- **1.0.E1 — Insufficient leave balance:** "The employee has only N days remaining." The Manager may reject, approve partially, or approve as unpaid leave.
- **1.0.E2 — Staffing below the minimum:** the system warns and requires an explicit override justification, which is audit-logged.
- **1.0.E3 — The request was cancelled by the employee meanwhile:** (UC-E16) "This request has been withdrawn." Refresh the queue.
- **1.0.E4 — Blackout period:** the dates fall in a declared peak-season blackout; approval requires a higher-level override.
- **1.0.E5 — Concurrent decision by another Manager:** the optimistic lock fails; show the decision already recorded and refresh.

Field	Value
Priority	High
Frequency of Use	Several per week per department.
Business Rules	BR-40 Leave may not exceed the accrued balance unless approved as unpaid. BR-41 Departmental coverage must not fall below the minimum without an override. BR-42 A rejection requires a reason. BR-43 Requests must be decided within 5 working days. BR-44 A Manager may not approve their own leave.
Non-functional	The employee is notified within 1 minute of the decision; every decision is immutably audit-logged with the approver identity.

UC-A06 — Assign Role to Account

Field	Value
ID and Name	UC-A06 — Assign Role to Account
Primary Actor	Admin
Secondary Actors	Notification Service
Trigger	The Admin opens an account and selects Assign role , typically on hire, promotion or transfer.

Description Grants a role — and with it a permission set — to a user account, determining which use cases that user may perform. This is the security-critical heart of the RBAC model.

Preconditions

- PRE-1: The target account exists.
- PRE-2: The role exists in the role catalogue (UC-A05).
- PRE-3: The Admin has the **MANAGE_ROLES** permission.

Postconditions

- POST-1: The role is attached to the account with an effective date.
- POST-2: The user's effective permission set is recalculated.
- POST-3: Existing sessions of that user are invalidated so the new claims take effect.
- POST-4: The assignment is written to the audit log.

Normal Flow — 1.0: Assign a role

1. The Admin searches for and opens the account. («include» UC-A01)
2. The system displays the account with its current roles and effective permissions.

3. The Admin clicks **Assign role**.
4. The system lists the assignable roles, excluding those already held.
5. The Admin selects a role and optionally an effective date and expiry.
6. The system validates the assignment against the segregation-of-duties rules.
7. The system shows the resulting permission set for confirmation, highlighting newly granted permissions.
8. The Admin confirms.
9. The system attaches the role, recalculates the effective permissions and invalidates the user's active sessions.
10. The system writes an audit entry with the actor, target, role, timestamp and reason.
11. The system notifies the affected user of their new access.

Alternative Flows

- **1.1: Assign at account creation** — the role is chosen as part of UC-A02; steps 4–9 are executed inline as part of provisioning.
- **1.2: Temporary role** — the Admin sets an expiry date; a scheduled job revokes the role automatically when it lapses.
- **1.3: Revoke a role** — («extend» UC-A08) the Admin removes a role; the permissions are recalculated and the sessions invalidated in the same way.
- **1.4: Replace a role** — a promotion revokes the old role and assigns the new one in a single atomic operation.

Exceptions

- **1.0.E1 — Role already assigned:** "This account already holds that role." Terminate.
- **1.0.E2 — Segregation-of-duties conflict:** for example **Auditor** together with **Payroll Approver**. The system blocks the assignment and names the conflicting rule.
- **1.0.E3 — Account is locked or deactivated:** "Roles cannot be assigned to an inactive account." Require reactivation first.
- **1.0.E4 — Privilege escalation attempt:** an Admin tries to grant a role above their own authority; the system blocks it and raises a security alert.
- **1.0.E5 — Last Super Admin:** revoking the final Super Admin role is refused to prevent lockout.


Field	Value
Priority	High
Frequency of Use	On hire, promotion, transfer and termination.
Business Rules	BR-45 Permissions are granted through roles only, never directly to accounts. BR-46 An account may hold several roles; the effective set is their union. BR-47 Segregation-of-duties rules are enforced at assignment time. BR-48 At least one Super Admin must always exist. BR-49 Every role change is audit-logged and irreversible in the log.
Non-functional	Permission recalculation ≤ 1 s; new permissions effective on the next login; audit entries retained ≥ 5 years.

5. Analysis Modeling — Static Modeling (Ch. 7)


Static modeling defines the classes of the problem domain, their attributes and their relationships, independently of behaviour.

5.1 System Context Class Diagram

The context diagram shows the system as a single aggregate class surrounded by the external classes it communicates with.



5.2 Entity Class Model — Conceptual Static Model




5.3 Key Entity Attributes and Invariants

Entity	Key invariants
Booking	<code>checkOutDate > checkInDate</code> ; <code>nights ≤ 30</code> ; <code>adults + children ≤ roomType.capacity</code> ; status transitions only along <code>PENDING → CONFIRMED → CHECKED_IN → CHECKED_OUT</code> , with <code>CANCELLED</code> reachable only before <code>CHECKED_IN</code> .
Room	A room has at most one active stay at a time (BR-25); status ∈ { <code>VACANT_CLEAN</code> , <code>VACANT_DIRTY</code> , <code>OCCUPIED</code> , <code>OUT_OF_ORDER</code> , <code>INSPECTED</code> }.
Payment	<code>amount > 0</code> ; immutable once <code>PAID</code> ; <code>idempotencyKey</code> unique; corrections only by reversal (BR-33).
Invoice	<code>invoiceNumber</code> strictly sequential and gapless; immutable once issued (BR-30).
RefundRequest	<code>approvedAmount ≤ requestedAmount ≤ sum(payments.amount)</code> (BR-37).
LeaveRequest	<code>days ≤ leaveBalance</code> unless explicitly unpaid (BR-40); <code>approverId ≠ employeeId</code> (BR-44).
LoyaltyAccount	<code>pointBalance ≥ 0</code> ; accrual only on <code>CHECKED_OUT</code> stays (BR-29).
AuditLog	Append-only; never updated or deleted (BR-49).

6. Analysis Modeling — Object and Class Structuring (Ch. 8)

Per Ch. 8, each software object is categorized so that objects with similar characteristics are grouped, giving a design in which responsibilities are clearly separated.

6.1 Object Structuring Categories



6.2 Object Allocation by Category

«boundary» — User interaction objects (React)

Object	Responsibility	Realizes
LoginPage	Collect credentials, display errors	UC-G17
RegisterPage	Collect registration data	UC-G16
RoomSearchPage	Search criteria and result list	UC-G01
BookingWizardPage	Multi-step booking flow	UC-G07
PaymentPage	Method selection, gateway redirect	UC-G10
BookingDetailPage	Detail, cancel, modify	UC-G13/14/15
FrontDeskPage	Check-in / check-out console	UC-R06, UC-R09
RoomRackPage	Room availability and status board	UC-R12, UC-R13
ApprovalQueuePage	Manager pending approvals	UC-M06, UC-M14
AccountAdminPage	Accounts and role assignment	UC-A01, UC-A06

«boundary» — I/O and proxy objects (Express)

Object	Responsibility
AuthController	HTTP boundary for authentication
BookingController	HTTP boundary for booking operations
CheckInController	HTTP boundary for front-desk operations
PaymentGatewayProxy	Encapsulates the external payment gateway protocol
NotificationProxy	Encapsulates the email/SMS provider protocol

«entity» — Entity objects (Mongoose models)

User, Role, Customer, Employee, RoomType, Room, Booking, Folio, Charge, Payment, Invoice, RefundRequest, Service, Promotion, Review, LoyaltyAccount, Shift, Attendance, LeaveRequest, Payslip, AuditLog.


«control» — Control objects

Object	Kind	Coordinates
BookingCoordinator	coordinator	UC-G07: availability → contact → add-ons → payment → confirm
CheckInCoordinator	coordinator	UC-R06: verify → allocate → collect → activate
CheckOutCoordinator	coordinator	UC-R09: consolidate → invoice → settle → release
RefundCoordinator	coordinator	UC-C17 + UC-M14 approval chain
BookingStateMachine	state dependent	Booking lifecycle transitions
RoomStateMachine	state dependent	Room status transitions
HoldExpiryTimer	timer	Releases inventory holds after 15 min (BR-10)
PayrollRunTimer	timer	Triggers the monthly payroll run


«application logic» — Business logic and algorithm objects

Object	Kind	Encapsulated rule
PricingRule	business logic	Nightly seasonal rate, taxes, totals (BR-09)
CancellationPolicyRule	business logic	Penalty tiers (BR-17...BR-19)
LoyaltyRule	business logic	Accrual and redemption (BR-12, BR-29)
PromotionRule	business logic	Voucher validity and discount computation
LeavePolicyRule	business logic	Balance, coverage, blackout (BR-40...BR-44)
AvailabilityCalculator	algorithm	Availability over a date range
RoomAllocator	algorithm	Race-free selection of a vacant-clean room (BR-25)
InvoiceNumberGenerator	algorithm	Gapless sequential numbering (BR-30)
ReportingService	service	Revenue, occupancy, ADR, RevPAR
AuditService	service	Append-only audit trail (BR-49)


6.3 Object Interaction — UC-G07 Book Room



6.4 State-Dependent Control — Booking Lifecycle



6.5 State-Dependent Control — Room Lifecycle




7. Overall Software Architecture

7.1 Architectural Style


HMS uses a **layered client-server architecture** with a React single-page client and an Express REST service. The server is internally organized into four layers that map directly onto the Ch. 8 object categories.

Layer	Ch. 8 category	Contents
Presentation	«boundary» user interaction	React pages, components, hooks
API / Boundary	«boundary» I/O, «proxy»	Express routes, controllers, external proxies
Business	«control», «application logic»	Coordinators, state machines, rules, algorithms
Data	«entity»	Mongoose models and repositories

7.2 Layered Architecture Diagram



7.3 Subsystem Decomposition




Subsystem	Responsibility	Principal use cases
Auth & Identity	Authentication, session, RBAC enforcement	UC-G16, UC-G17, UC-C01...C05, UC-A06
Booking & Reservation	Search, book, modify, cancel	UC-G01, UC-G07, UC-G13...G15, UC-R03...R05
Front Desk Operations	Check-in/out, room status, folio	UC-R06...R14, UC-R19
Billing & Payment	Payments, invoices, refunds	UC-G10, UC-R15...R18, UC-C17, UC-M14
Inventory & Pricing	Rooms, room types, rates, promotions	UC-M09...M12
HR & Payroll	Attendance, shifts, leave, payroll	UC-E09...E24, UC-M01...M08b
Customer & Loyalty	Profile, reviews, points	UC-C06...C21, UC-M15
Reporting & Analytics	Revenue, occupancy, exports	UC-M16...M18
Administration & Audit	Accounts, roles, settings, audit, backup	UC-A01...A18

7.4 Package Diagram


The package diagram shows how the source code is physically organized and, more importantly, the permitted dependency directions between packages. Every dependency points **downward**: a package may only depend on packages in the layers below it. This acyclic, one-directional structure is what makes the system modifiable and testable (§8.1) — a change in a lower layer never forces a change in a higher one, and a lower layer can be unit-tested without the layers above it.

7.4.1 Top-Level Package Structure




7.4.2 Layered Package Dependencies

Collapsing the packages onto the four architectural layers makes the dependency rule explicit. Note that **rules** and **models** never depend on anything above them — this is why the «application logic» objects are pure and directly unit-testable.



7.4.3 Business Subsystem Packages

Within the business layer, the services are grouped by the subsystems of §7.3. Subsystem packages depend on shared rule packages but never on each other's internals — they collaborate only through the coordinators.




7.4.4 Package Responsibilities and Dependency Rules

Package	Ch. 8 category	May depend on	Must NOT depend on
client/pages	«boundary» user interaction	components , hooks , types	server internals
client/hooks	—	api , types	pages
client/api	«boundary» I/O	types	pages , hooks
server/routes	—	controllers , middleware	services , models
server/middleware	«boundary»	utils , models (auth only)	controllers , services
server/controllers	«boundary» I/O	services , dto , utils	models , repositories
server/services	«control»	rules , repositories , proxies , dto , utils	controllers , routes
server/rules	«application logic»	models , utils	services , repositories , proxies
server/repositories	—	models	services , controllers
server/models	«entity»	utils	everything above
server/proxies	«boundary» external	utils , dto	services , models
server/utils , dto	cross-cutting	—	everything

Why controllers must not reach models directly. If a controller queried a Mongoose model itself, business logic would leak into the HTTP boundary and the same rule would end up duplicated in every endpoint that needed it. Routing all data access through `services` keeps each business rule in exactly one place — this is the Ch. 20 Modifiability argument, and it is what makes the traceability matrix in §9 possible.

Why rules must not depend on repositories. The «application logic» objects are pure functions of their inputs. `PricingRule.calculate()` receives a room type and returns a breakdown; it never loads anything. That is what allows them to be unit-tested with plain object literals and no database, satisfying §8.1 Testability.

7.5 Deployment Architecture



7.6 API Surface (representative)

Method	Endpoint	Use case	Roles
POST	/api/auth/register	UC-G16	public
POST	/api/auth/login	UC-G17	public
POST	/api/auth/refresh	UC-C02	authenticated
POST	/api/auth/forgot-password	UC-C03	public
GET	/api/rooms/search	UC-G01	public
GET	/api/room-types/:id	UC-G02	public
POST	/api/bookings	UC-G07	public / customer
POST	/api/payments/payos/webhook	UC-G10 step 7–9	payOS (HMAC-signed, no JWT)
GET	/api/payments/payos/:orderCode/reconcile	UC-G10 alt. 1.1	public (returns statuses only)
POST	/api/payments/payos/confirm-webhook	UC-A12	admin (<code>MANAGE_SETTINGS</code>)
GET	/api/bookings/lookup	UC-G13	public
POST	/api/bookings/:id/cancel	UC-G14	customer / receptionist
GET	/api/me/bookings	UC-C11	customer
POST	/api/refund-requests	UC-C17	customer
POST	/api/front-desk/check-in	UC-R06	receptionist
POST	/api/front-desk/check-out	UC-R09	receptionist
POST	/api/folios/:id/payments	UC-R15	receptionist
GET	/api/rooms/availability	UC-R12	receptionist
PATCH	/api/rooms/:id/status	UC-R13	receptionist
PATCH	/api/leave-requests/:id/decision	UC-M06	manager
PATCH	/api/refund-requests/:id/decision	UC-M14	manager
GET	/api/reports/revenue	UC-M16	manager
POST	/api/accounts/:id/roles	UC-A06	admin
GET	/api/audit-logs	UC-A13	admin

8. Software Quality Attributes (Ch. 20)

8.1 Attributes and How They Are Achieved

Attribute	Design decision in HMS
Maintainability	Four-layer separation; each Ch. 8 object category lives in its own directory; business rules isolated from entity data so a policy change touches one rule object.
Modifiability	Each external interface is encapsulated in its own proxy (<code>PaymentGatewayProxy</code> , <code>NotificationProxy</code>), so swapping the gateway changes one class. Each finite state machine (<code>BookingStateMachine</code> , <code>RoomStateMachine</code>) is a separate class. Each data structure sits behind a repository.
Testability	Controllers hold no logic; coordinators depend on injected repositories and rules, so they are unit-testable without a database. Rule objects are pure functions of their inputs.
Traceability	Every use case ID (UC-xxx) appears in the header comment of the realizing controller, service and route, and in the traceability matrix in §9. Every business rule (BR-xx) is named in the rule object that enforces it.
Scalability	Stateless API instances behind a load balancer; sessions in Redis rather than in process memory; read-heavy availability queries cached; MongoDB replica set for read scaling.
Performance	Search ≤ 2 s with a 60 s availability cache; indexes on <code>booking.checkInDate</code> , <code>booking.bookingCode</code> , <code>room.status</code> ; integer minor units avoid floating-point cost and error.
Availability	Replica set with automatic failover; degraded offline mode for front-desk check-in with later reconciliation; retry queues for notification and refund failures.
Security	bcrypt password hashing; short-lived JWT with refresh rotation; RBAC middleware on every protected route; account logout after 5 failures; card data never stored (gateway holds PCI scope); append-only audit log; segregation-of-duties checks on role assignment.
Reusability	Rule and algorithm objects (<code>PricingRule</code> , <code>AvailabilityCalculator</code>) are free of HTTP and database concerns and are reused by the public booking flow and the front-desk flow alike.

8.2 Quality Attribute Scenarios

#	Attribute	Stimulus	Response measure
QA-1	Performance	500 concurrent room searches	95th percentile ≤ 2 s
QA-2	Scalability	Traffic doubles in peak season	Add API instances; no code change
QA-3	Availability	Primary database node fails	Failover ≤ 30 s; no committed booking lost
QA-4	Security	5 consecutive failed logins	Account locked, owner notified, event audited
QA-5	Modifiability	Payment gateway is replaced	The wire protocol changes only <code>PaymentGatewayProxy</code> . <i>Measured when replacing the generic gateway with payOS</i> : endpoints, headers, both signature algorithms and status codes stayed inside the proxy. But payOS is asynchronous (redirect + webhook) where the original design assumed a synchronous charge, and that change of interaction style also touched <code>PaymentService</code> (orderCode, reconcile), one new controller/route, two <code>Payment</code> fields and a client result page. Lesson: a proxy isolates a <i>protocol</i> , not an <i>interaction model</i> — the sync-vs-async decision belongs in the architecture, not the adapter.
QA-6	Reliability	Gateway times out mid-payment, or its webhook and the returning guest confirm the same payment concurrently	Payment is booked exactly once: the payOS <code>orderCode</code> prevents a second link, and the PENDING → PAID change is a conditional atomic update (10 concurrent confirmations → 1 capture; without the guard → 10)
QA-7	Integrity	Two receptionists allocate the same room	Optimistic lock rejects the second; BR-25 holds
QA-8	Traceability	Auditor asks who granted a role	Audit log returns actor, target, role, timestamp

9. Traceability Matrix

Requirements traceability per Ch. 20: every detailed use case traces forward to the classes that realize it and to the code artifacts that implement it.

Use Case	«boundary»	«control»	«application logic»	«entity»	Code artifact
UC-G17 Login	LoginPage , AuthController	AuthService	—	User , Role , AuditLog	LoginPage.tsx , auth.controller.ts , auth.service.ts
UC-G16 Register	RegisterPage †, AuthController	AuthService	—	User , Customer , LoyaltyAccount	auth.controller.ts , auth.service.ts
UC-G01 Search Rooms	RoomSearchPage , RoomController	— (read-only, see note 1)	AvailabilityCalculator , PricingRule	RoomType , Room , Booking	RoomSearchPage.tsx , booking.controller.ts , availability.calculator.ts , pricing.rule.ts
UC-G07 Book Room	BookingWizardPage , BookingController	BookingCoordinator , BookingStateMachine	PricingRule , AvailabilityCalculator	Booking , InventoryHold , Promotion , Payment	BookingWizardPage.tsx , booking.service.ts , booking-state-machine.ts
UC-G10 Pay Booking	BookingWizardPage (step 3), PaymentResultPage , PaymentController , PaymentGatewayProxy (payOS)	PaymentService	—	Payment , Booking , InventoryHold	payment.controller.ts , payment.service.ts , payment-gateway.proxy.ts , PaymentResultPage.tsx
UC-G14 Cancel Booking	MyBookingsPage , BookingController	BookingCoordinator , BookingStateMachine	CancellationPolicyRule	Booking , RefundRequest , Payment	MyBookingsPage.tsx , booking.service.ts , cancellation- policy.rule.ts
UC-R06 Check In	FrontDeskPage , FrontDeskController	CheckInCoordinator	RoomAllocator , FolioLedger	Booking , Room , Folio , Charge	FrontDeskPage.tsx , frontdesk.controller.ts , check-in.service.ts , room- allocator.ts
UC-R09 Check Out	FrontDeskPage , FrontDeskController	CheckOutCoordinator	InvoiceNumberGenerator , FolioLedger	Folio , Invoice , Room , LoyaltyAccount	check-in.service.ts , invoice- number.generator.ts
UC-R15 Process Payment	FrontDeskPage , FrontDeskController	PaymentService	—	Payment , Folio , DrawerSession	frontdesk.controller.ts , payment.service.ts
UC-C17 Request Refund	MyBookingsPage , RefundController	RefundCoordinator	—	RefundRequest , Payment	workflow.controller.ts , refund.service.ts
UC-M06 Approve Leave	ApprovalQueuePage , LeaveController	LeaveApprovalService	LeavePolicyRule	LeaveRequest , Employee , Shift	ApprovalQueuePage.tsx , leave.service.ts , leave- policy.rule.ts
UC-A06 Assign Role	AccountAdminPage †, AccountController	RoleAssignmentService	AuditService	User , Role , AuditLog	workflow.controller.ts , role.service.ts

† Designed in §6.2 but not yet implemented in the client boilerplate; the server endpoint exists and is exercised by the API.

Analysis → implementation notes. Ch. 8 lets analysis objects be merged or refined during design; where that happened, the table above shows the implemented name.

- 1. **UC-G01 has no control object.** It is read-only, and Ch. 8 notes that simple use cases do not need one; `RoomController` calls the two rule objects directly.
- 2. `CheckInController` / `CheckOutController` / `PaymentController` were merged into one `FrontDeskController`, since all three serve the same desk screen.
- 3. `HoldExpiryTimer` is realized as a MongoDB TTL index on `InventoryHold` (`expires: 0` on `expiresAt`) — the database is the timer.
- 4. `PromotionRule` is split between `Promotion.isValidOn()` (validity) and `PricingRule.discountFor()` (amount). `LoyaltyRule` is inline in `CheckOutCoordinator` (1 % of room revenue, BR-12/BR-29).
- 5. `FolioLedger` was added during implementation: the single entry point for posting a charge, which writes the VAT line with it so the folio balance is always tax-inclusive (see UC-R09, BR-28).

Appendix A — Source Artifacts

Artifact	Location
Use case diagrams	<code>uc_diagram/{Guest, Customer, Employee, Receptionist, Manager, Admin}.drawio</code>
Boilerplate code	<code>System Design and Overall Architecture/src/</code>
Course material	<code>material/Ch05-Ch08</code> , <code>material/Ch20</code>