

# A 128-BIT SYMMETRIC BLOCK CIPHER INTEGRATING 4D HYPERCUBE PERMUTATIONS AND ARX DIFFUSION FOR HIGH-THROUGHPUT ENVIRONMENTS

HAO GIA NGUYEN<sup>a</sup>, THE TRONG QUAN<sup>a</sup>

<sup>a</sup> Posts and Telecommunications Institute of Technology, Hanoi, Vietnam  
e-mail: theqt@stu.ptit.edu.vn

**Abstract** Resource-constrained embedded platforms require symmetric block ciphers that balance strict security margins with low-latency execution. Standard ciphers like AES-128 offer strong security, but their `MixColumns` diffusion depends on finite-field matrix operations over  $\text{GF}(2^8)$ , creating computational bottlenecks on processors without dedicated hardware acceleration. Conversely, lightweight Addition-Rotation-XOR (ARX) ciphers avoid S-boxes but require dozens of rounds to achieve full diffusion. To solve this trade-off, we propose Rubik-4D, an 8-round 128-bit block cipher designed over a four-dimensional hypercube state ( $SO(4)$  Lie group). We place the 16 state bytes on the vertices of a 4D tesseract ( $2 \times 2 \times 2 \times 2$ ) and interleave three transformations: non-linear S-box substitution, orthogonal  $SO(4)$  double rotations via 192-byte precomputed tables, and a 32-bit ARX ripple-carry layer. Automated MILP searches verify that Rubik-4D activates at least 22 S-boxes against differential attacks ( $P_{\text{diff}} \leq 2^{-132} < 2^{-128}$ ) and 108 S-boxes against linear cryptanalysis ( $N_D \approx 2^{434} \gg 2^{128}$ ), ruling out statistical shortcuts. The cipher inherently blocks slide attacks and passes both the NIST SP 800-22 and GM/T 0005-2021 randomness test batteries. On standard  $512 \times 512$  benchmark images (Lena and Baboon in CBC mode), Rubik-4D yields Shannon entropy above 7.999, adjacent-pixel correlation  $|r| \leq 0.026$ , and differential metrics matching theoretical ideals (NPCR  $\approx 99.61\%$ , UACI  $\approx 33.46\%$ ). On standard x86-64 hardware, the cipher sustains an average throughput of 151.65 MB/s across payloads up to 20 MB, outperforming software AES-128.

**Keywords:** symmetric block cipher, Rubik-4D, four-dimensional hypercube,  $SO(4)$  rotation, ARX diffusion, MILP cryptanalysis, image cryptanalysis, NIST SP 800-22, GM/T 0005-2021.

## 1. Introduction

Sensory devices and edge cameras produce vast volumes of multimedia telemetry. Protecting these data streams requires symmetric ciphers that are both mathematically sound and fast on embedded microprocessors [11, 17].

Standard block ciphers such as DES and AES [14, 15] were built for structured records. When applied to visual data on constrained microcontrollers, they face practical drawbacks:

1. Costly finite-field operations in SPNs: AES-128 offers robust algebraic security. However, its `MixColumns` stage relies on matrix multiplication over  $\text{GF}(2^8)$  [14]. Without specialized CPU instructions (like Intel AES-NI or ARM Crypto), microcontrollers must use large lookup tables or slow field arithmetic. This lowers speed and raises side-channel leakage risks [12, 13].
2. Slow carry spread in pure ARX: Lightweight ciphers such as Simon and Speck [17] avoid S-boxes to save silicon. Yet modular addition only moves carries one bit to the left per operation. Because carry bits spread gradually, these ciphers need dozens of rounds (32 in Speck-128, 68 in Simon-128) to achieve adequate diffusion [11].

To avoid field multiplication while breaking image pixel correlations, researchers explored puzzle-based encryption, especially 3D Rubik's cube scramblers with chaotic maps [1, 7, 8]. Physical cube twists mix coordinates across or-

thogonal faces efficiently [8]. Still, existing Rubik-based schemes are heuristic scramblers rather than formal block ciphers. They omit non-linear S-boxes, lack provable bounds on active elements, and remain vulnerable to differential cryptanalysis and chosen-plaintext attacks (CPA).

To bridge this gap, we present Rubik-4D, a 128-bit symmetric block cipher. We project the 16 state bytes onto the 16 vertices of a 4D hypercube ( $2 \times 2 \times 2 \times 2$ ). The cipher applies orthogonal double rotations from the Lie group  $SO(4)$ , mixing all four dimensions simultaneously. A 32-bit ARX layer then diffuses carries across words. Together, these steps produce complete avalanche in 8 rounds while exceeding 151 MB/s throughput in pure software.

We summarize our contributions below:

- We design Rubik-4D, an 8-round block cipher blending discrete  $SO(4)$  hypercube rotations, key-dependent table lookups, and 32-bit ARX diffusion.
- We formulate MILP models to prove exact security bounds: at least 22 active S-boxes under differential cryptanalysis ( $P_{\text{diff}} \leq 2^{-132}$ ) and 108 under linear cryptanalysis ( $N_D \approx 2^{434}$ ). We also show structural resistance to slide attacks.
- We establish formal algorithmic descriptions and verify exact bijectivity for forward and inverse operations.
- We test the generated keystream using both NIST SP 800-22 (187/188 pass rate) and GM/T 0005-2021 (17/18 pass rate) statistical suites.

- We analyze image security on standard test images, reporting near-ideal entropy, low adjacent correlation, and compliant NPCR and UACI metrics.
- We benchmark software speed against AES-128 [15], Speck-128 [17], Simon-128 [17], and ChaCha20 [18], demonstrating competitive throughput on general-purpose CPUs.

## 2. Related Work and Novelty Comparison

Rubik-inspired cryptography evolved through three distinct waves:

1. First wave (2011–2014) — Coordinate shifts and XOR chains: Loukhaoukha et al. [1] started this thread. They folded an  $M \times N$  picture into an  $M \times N \times 3$  cube, rolled rows and columns with keystream vectors, and chained cumulative XOR additions:  $I'(i, j) = I(i, j) \oplus K_R(i) \oplus K_C(j) \oplus I'(i-1, j)$ . But every step collapses into linear operations over  $\mathbb{F}_2$ . A chosen-plaintext attacker easily unpacks the scrambling vectors. Per-pixel manipulation also crawls (0.82 s per image, roughly 0.31 MB/s). Follow-up schemes by Zhang et al. [2] and Feng et al. [3] glued 1D Logistic maps or Fourier steps onto the cube, yet dynamical degradation plagued their trajectories. Diaconu and Loukhaoukha [10] enlarged the key room with digital chaos, leaving the linear core untouched.
2. Second wave (2021–2022) — Bit-level grids and arithmetic rules: Shuffling whole bytes leaves inner bit patterns intact. Zhu et al. [4] countered this with 3D-BERC. They sliced pixels into 8 bit planes, stacked them into a binary cube, and spun 2D slices. Vidhya and Brindha [5] tapped large prime factorization (CIERPF) to pick rotation angles. Even so, scattering individual bits across RAM thrashes CPU caches. Throughput stalls under 0.7 MB/s.
3. Third wave (2022–2024) — Quantum walks, hyperchaos, and frame twists: Zhao et al. [6] linked 2D quantum walks with Rubik permutations in *Scientific Reports*. Qiu et al. [8] turned to 4D hyperchaotic loops. Nair et al. [7] blended cube scrambling with bitmap frames and fixed rotations ( $90^\circ, 180^\circ$ ). These tricks disrupt picture pixels. But they still crawl (0.22–0.88 MB/s), drift between x86 and ARM floating-point units, and lack proven attack bounds.

Mainstream block ciphers took an entirely different route: lightweight ARX and MILP solvers. At CRYPTO 2020, Beierle et al. [11] built Alzette, demonstrating rapid diffusion via modular carries. At EUROCRYPT 2023, Hadipour et al. [12] automated impossible-differential proofs through MILP. Xiang et al. [13] pioneered similar optimization for division property attacks at ASIACRYPT 2016.

Looking closely at earlier Rubik-inspired proposals reveals three recurring pitfalls (Fig. 1(a)). First, these algorithms merely reorder pixel coordinates rather than evaluating genuine iterative block rounds. Without nonlinear

S-boxes over Galois fields, the entire transformation remains affine over  $\mathbb{F}_2$ , leaving the cipher fragile against differential pairs and plaintext recovery. Second, authors routinely judge security through ad-hoc visual metrics—such as NPCR, UACI, and Shannon entropy on arbitrary images—without establishing mathematical lower bounds on active components against differential [19] or linear attacks [22]. Third, heavy reliance on chaotic maps or quantum walks causes severe computational bottlenecks ( $< 1$  MB/s) and produces rounding discrepancies when compiled across distinct processor architectures.

To overcome these problems, Rubik-4D takes a fundamentally different path (Fig. 1(b)). We design a 128-bit block cipher that blends 4D hypercube permutations with a 32-bit ARX network. Rather than rotating faces in 3D, our cipher arranges the 16 state bytes across the vertices of a 4D tesseract. Using precomputed lookup tables, the diffusion layer evaluates  $SO(4)$  double rotations, mixing all four spatial dimensions simultaneously without invariant axes. Nonlinearity comes from AES S-boxes over  $\text{GF}(2^8)$  ( $\delta = 4$ , degree  $d = 7$ ), while a word-level modular carry ripple guarantees rapid diffusion across words. This combination produces full avalanche in just 8 rounds (compared to 32 in Speck and 68 in Simon). Furthermore, by framing the cipher’s differential propagation as an integer program, our MILP solver mathematically proves that 8 rounds activate at least 22 S-boxes, yielding a differential bound of  $P_{\text{diff}} \leq 2^{-132}$  and linear bound of  $N_D \approx 2^{434}$ . Finally, because all operations execute through 32-bit integer arithmetic and cache-resident tables, the software runs at 151 MB/s without floating-point inaccuracies.

Table 1 summarizes a qualitative and structural comparison between conventional Rubik-based cryptographic designs and the proposed Rubik-4D cipher.

Table 2 provides a step-by-step algorithmic pipeline comparison between representative Rubik cryptographic schemes across each developmental era and the proposed Rubik-4D cipher.

## 3. The Proposed Rubik-4D Cipher Scheme

Rubik-4D processes 128-bit plaintext blocks under a 128-bit secret key over  $R = 8$  identical iterative rounds. Table 3 summarizes the primary notational conventions used throughout this paper.

### 3.1. State representation and 4D tesseract geometry

The 128-bit internal cipher state is represented as an array of 16 bytes:

$$S = [b_0, b_1, b_2, \dots, b_{15}]^\top, \quad b_i \in \{0, 1\}^8 \quad (1)$$

Each byte index  $i \in \{0, \dots, 15\}$  is mapped to a unique vertex coordinate  $(x, y, z, w) \in \{0, 1\}^4$  of a four-dimensional binary hypercube via the canonical bit-decomposition:

$$i = (x \ll 3) \mid (y \ll 2) \mid (z \ll 1) \mid w \quad (2)$$

Table 1: Qualitative and structural comparison between conventional Rubik-inspired ciphers and Rubik-4D

| Architectural metric           | Loukhaoukha (2012) [1]               | Zhu et al. (2021) [4]                  | Nair et al. (2024) [7]               | Rubik-4D (Proposed)                                                |
|--------------------------------|--------------------------------------|----------------------------------------|--------------------------------------|--------------------------------------------------------------------|
| Geometric dimensionality       | 3D spatial ( $M \times N \times 3$ ) | 3D Bit-Level ( $M \times N \times 8$ ) | 3D Spatial ( $M \times N \times 3$ ) | 4D hypercube tesseract ( $2 \times 2 \times 2 \times 2$ )          |
| Mathematical lie group         | Discrete face cycles                 | Discrete bit rotations                 | Face shift + shuffling               | Special orthogonal group $SO(4)$                                   |
| Non-linear substitution layer  | None (XOR only)                      | None (Bit permutation)                 | Dynamic chaos logistic               | AES S-Box                                                          |
| Inter-word diffusion layer     | Heuristic bit-shuffling              | XOR-sum ripple                         | Frame/cyclic shift                   | 32-bit ARX Modular                                                 |
| Automated MILP security bounds | None                                 | None                                   | None                                 | Proven ( $P_{\text{diff}} \leq 2^{-132}$ , $N_D \approx 2^{434}$ ) |
| Hardware precision dependency  | floating-Point                       | floating-Point                         | floating-Point                       | Integer only                                                       |
| Formal cipher standard         | Image scrambler only                 | Image scrambler only                   | Image scrambler only                 | Block Cipher                                                       |
| Standard randomness validation | Empirical visual Only                | NIST SP 800-22 (Subset)                | Visual + entropy                     | NIST SP 800-22 (187/188) + GM/T 0005 (17/18 <sup>†</sup> )         |

<sup>†</sup>DFT test pass rate 98.87% exceeds threshold; distribution  $P$ -value anomaly is a documented test statistic bias [27].

Table 2: Step-by-step algorithmic execution comparison between representative Rubik schemes across generations and Rubik-4D

| Generation & scheme                            | Step 1: Init & partition                                                                                       | Step 2: Spatial permutation                                                                      | Step 3: Non-linear substitution                                                         | Step 4: Inter-word diffusion                                                                                                | Complexity & security                                                                                                 |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>First gen (2012)</b> Loukhaoukha et al. [1] | Format $M \times N$ image as 3D cube $M \times N \times 3$ ; generate key vectors $K_R, K_C$ .                 | Circularly roll rows left/right by $K_R$ ; circularly shift columns up/down by $K_C$ .           | <b>None</b> (Strictly linear arithmetic over $\mathbb{F}_2$ ).                          | Cumulative XOR diffusion across adjacent rows/columns: $I'(i, j) = I(i, j) \oplus K_R(i) \oplus K_C(j) \oplus I'(i-1, j)$ . | $O(M \times N)$ , 0.820 s/image; No formal bounds (vulnerable to CPA).                                                |
| <b>Second gen (2021)</b> Zhu et al. [4]        | Decompose bytes into 8 bit-planes; assemble 3D binary cube $L \times L \times L$ .                             | Rotate bit slices on $XY, YZ, ZX$ coordinate planes via chaotic indices.                         | Contraction mapping and bit-position shuffling (lacks Galois S-box).                    | Inter-plane bit scrambling combined with cumulative XOR sum across bit slices.                                              | $O(L^3)$ bit-level, 0.380 s/image; Empirical testing only.                                                            |
| <b>Third gen (2024)</b> Nair et al. [7]        | Partition color channels into $8 \times 8$ bitmap submatrices.                                                 | 3D Rubik scrambling across color channels + frame rotation ( $90^\circ, 180^\circ, 270^\circ$ ). | Dynamic chaotic Logistic mapping for pixel-level value permutation.                     | Adjacent bitmap block interleaved blending driven by chaotic map.                                                           | $O(M \times N)$ , 0.290 s/image; No mathematical provable bounds.                                                     |
| <b>Proposed (2026)</b> <b>Rubik-4D</b>         | Map 16 bytes to 16 vertices of 4D Tesseract $\{0, 1\}^4$ ; initial key whitening $S \leftarrow P \oplus K_0$ . | Double orthogonal rotation in Lie group $SO(4)$ without invariant axes ( $O(1)$ LUT).            | AES S-Box over $\text{GF}(2^8)$ ( $\delta = 4, d = 7$ ) eliminates algebraic linearity. | 32-bit ARX carry-ripple diffusion ( $\boxplus \rightarrow \ll n \rightarrow \oplus$ ) + round subkey addition $K_r$ .       | $O(1)$ per block, 1.73 ms/image (148.23 MB/s); MILP bounds: $P_{\text{diff}} \leq 2^{-132}$ , $N_D \approx 2^{434}$ . |

Table 3: Notational conventions.

| Symbol         | Definition                                                      |
|----------------|-----------------------------------------------------------------|
| $S$            | 128-bit internal cipher state (16 bytes)                        |
| $S^{(0)}$      | Initial state after key whitening                               |
| $S^{(r)}$      | Intermediate cipher state after round $r$                       |
| $W$            | State represented as four 32-bit words $[W_0, W_1, W_2, W_3]^T$ |
| $K_0$          | 128-bit master secret key                                       |
| $K_r$          | 128-bit derived subkey for round $r$                            |
| $C$            | 32-bit constant (0x5A5A5A5A)                                    |
| $x \boxplus y$ | Addition modulo $2^{32}$                                        |
| $x \oplus y$   | Bitwise exclusive-OR (XOR)                                      |
| $x \lll n$     | Circular left shift of $x$ by $n$ bit positions                 |
| $\pi_k$        | $k$ -th $SO(4)$ hypercube permutation table                     |
| $\Delta x$     | Differential XOR difference                                     |

### 3.2. Round function execution pipeline

Before round iterations, the state undergoes initial key whitening:

$$S^{(0)} \leftarrow \text{Plaintext} \oplus K_0 \quad (3)$$

For rounds  $r = 1, 2, \dots, 8$ , the intermediate state is updated through four deterministic stages, as formalized in Algorithm 1 and illustrated in Fig. 1(a):

#### 3.2.1. Non-linear substitution (SubBytes)

Each state byte is processed through the standard AES S-box over  $\text{GF}(2^8)$ :

$$b_i \leftarrow \text{S-Box}[b_i], \quad \forall i \in \{0, \dots, 15\} \quad (4)$$

#### Algorithm 1 Rubik-4D encryption pipeline.

**Input:** Plaintext block  $P$  (128-bit), Round count  $R = 8$ , Master key  $K_0$ , Subkeys  $\{K_1, \dots, K_R\}$ , Constant  $C = 0x5A5A5A5A$

**Output:** Ciphertext block  $C_{\text{out}}$  (128-bit)

```

1:  $S \leftarrow P \oplus K_0$  {Initial key whitening}
2: for  $r = 1$  to  $R$  do
3:   {Step 1: Non-linear substitution (SubBytes)}
4:   for  $i = 0$  to 15 do
5:      $S[i] \leftarrow \text{S-Box}[S[i]]$ 
6:   end for
7:   {Step 2:  $SO(4)$  hypercube spatial permutation}
8:    $\text{tbl}_{\text{idx}} \leftarrow ((r + (k_{\text{fold}} \& 7)) \bmod 6) \times 2 + ((k_{\text{fold}} \gg 3) \& 1)$ 
9:   for  $i = 0$  to 15 do
10:     $S_{\text{rot}}[i] \leftarrow S[\pi_{\text{tbl}_{\text{idx}}}[i]]$ 
11:  end for
12:  {Step 3: 32-bit ARX ripple-carry diffusion}
13:  Pack  $S_{\text{rot}}$  into 4 words:  $[W_0, W_1, W_2, W_3]^T$ 
14:   $W_1 \leftarrow W_1 \oplus \text{ROTL}_{32}(W_0 \boxplus C, 7)$ 
15:   $W_2 \leftarrow W_2 \oplus \text{ROTL}_{32}(W_1 \boxplus C, 11)$ 
16:   $W_3 \leftarrow W_3 \oplus \text{ROTL}_{32}(W_2 \boxplus C, 13)$ 
17:   $W_0 \leftarrow W_0 \oplus \text{ROTL}_{32}(W_3 \boxplus C, 17)$ 
18:  {Step 4: Subkey addition}
19:   $S \leftarrow [W_0, W_1, W_2, W_3]^T \oplus K_r$ 
20: end for
21: return  $C_{\text{out}} = S$ 

```




Figure 1: Operational pipeline of Rubik-4D: (a) Encryption transformation consisting of SubBytes,  $SO(4)$  hypercube spatial permutation, 32-bit ARX ripple diffusion, and AddRoundKey; (b) Bijective inverse decryption transformation.

### 3.2.2. $SO(4)$ tesseract permutation

Spatial mixing is executed along the 6 canonical orthogonal coordinate planes:  $XY, XZ, XW, YZ, YW$ , and  $ZW$ . Planar rotation by  $\theta = \pi/2$  on an orthogonal plane (e.g.,  $XY$ ) in four-dimensional Euclidean space is formalized by the transformation matrix:

$$R_{XY} \left( \frac{\pi}{2} \right) = \begin{bmatrix} 0 & -1 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \in SO(4) \quad (5)$$

Projected onto discrete vertex coordinates  $(u, v) \in \{0, 1\}^2$ , clockwise ( $\rho_{cw}$ ) and counter-clockwise ( $\rho_{ccw}$ ) cyclic actions are defined as:

$$\rho_{cw} : (0, 0) \mapsto (0, 1) \mapsto (1, 1) \mapsto (1, 0) \mapsto (0, 0) \quad (6)$$

These transformations produce 12 static permutation tables  $\pi_k$  ( $k \in \{0, \dots, 11\}$ ). Round  $r$  references index  $\text{tbl}_{idx}$ :

$$S_{\text{rot}}[i] \leftarrow S[\pi_{\text{tbl}_{idx}}[i]], \quad \forall i \in \{0, \dots, 15\} \quad (7)$$

which executes in  $O(1)$  complexity without conditional branching.

Why use  $SO(4)$  rotations instead of standard 2D array shifts? In  $\mathbb{R}^3$ , every rotation fixes a line (an invariant axis). In contrast,  $SO(4)$  supports double rotations: the state rotates along two mutually orthogonal planes simultaneously, leaving no stationary axis. When mapping the 16 state bytes onto hypercube vertices, one  $SO(4)$  step mixes coordinates across all four spatial dimensions at once.

Storage costs remain minimal. Twelve lookup tables of 16 bytes each total only 192 bytes. This small footprint resides entirely in L1 data cache, avoiding memory spills and guaranteeing constant-time, branchless execution.

### 3.2.3. 32-bit ARX ripple-carry diffusion

The 16 rotated bytes are packed into four 32-bit unsigned words  $W = [W_0, W_1, W_2, W_3]^T$ . Using the round constant  $C = 0x5A5A5A5A$ , the sequential ripple diffusion is evaluated:

$$\begin{cases} W_1 \leftarrow W_1 \oplus \text{ROTL}_{32}(W_0 \boxplus C, 7) \\ W_2 \leftarrow W_2 \oplus \text{ROTL}_{32}(W_1 \boxplus C, 11) \\ W_3 \leftarrow W_3 \oplus \text{ROTL}_{32}(W_2 \boxplus C, 13) \\ W_0 \leftarrow W_0 \oplus \text{ROTL}_{32}(W_3 \boxplus C, 17) \end{cases} \quad (8)$$

where  $\boxplus$  denotes modular addition modulo  $2^{32}$ , and  $\text{ROTL}_{32}(x, n)$  denotes a left circular bit shift by  $n$  bit positions.

### 3.2.4. Subkey addition (AddRoundKey)

The state resulting from the ARX layer is XORed with the derived round subkey  $K_r$ :

$$S^{(r)} \leftarrow W \oplus K_r \quad (9)$$

The final ciphertext block corresponds to  $C = S^{(8)}$ .

## 3.3. Decryption process

Decryption evaluates the inverse transformations from round  $r = 8$  down to  $r = 1$ , as formalized in Algorithm 2 and shown in Fig. 1(b):

$$S \leftarrow S \oplus K_r \quad (10)$$

The ARX operations are inverted by reversing the word order:

$$\begin{cases} W_0 \leftarrow W_0 \oplus \text{ROTL}_{32}(W_3 \boxplus C, 17) \\ W_3 \leftarrow W_3 \oplus \text{ROTL}_{32}(W_2 \boxplus C, 13) \\ W_2 \leftarrow W_2 \oplus \text{ROTL}_{32}(W_1 \boxplus C, 11) \\ W_1 \leftarrow W_1 \oplus \text{ROTL}_{32}(W_0 \boxplus C, 7) \end{cases} \quad (11)$$

Following ARX inversion, the inverse permutation  $\pi_{\text{tbl\_idx}}^{-1}$  and InvS-Box transformations are applied. Finally, key addition  $S \leftarrow S \oplus K_0$  recovers the original plaintext.

---

**Algorithm 2** Rubik-4D decryption pipeline.

---

**Input:** Ciphertext block  $C_{\text{out}}$  (128-bit), Round count  $R = 8$ , Master key  $K_0$ , Subkeys  $\{K_1, \dots, K_R\}$ , Constant  $C = 0x5A5A5A5A$

**Output:** Restored Plaintext block  $P$  (128-bit)

---

```

1:  $S \leftarrow C_{\text{out}}$ 
2: for  $r = R, \dots, 1$  do
3:   {Step 1: Inverse subkey addition}
4:    $[W_0, W_1, W_2, W_3]^\top \leftarrow S \oplus K_r$ 
5:   {Step 2: Inverse ARX ripple-carry diffusion}
6:    $W_0 \leftarrow W_0 \oplus \text{ROTL}_{32}(W_3 \boxplus C, 17)$ 
7:    $W_3 \leftarrow W_3 \oplus \text{ROTL}_{32}(W_2 \boxplus C, 13)$ 
8:    $W_2 \leftarrow W_2 \oplus \text{ROTL}_{32}(W_1 \boxplus C, 11)$ 
9:    $W_1 \leftarrow W_1 \oplus \text{ROTL}_{32}(W_0 \boxplus C, 7)$ 
10:  Unpack  $[W_0, W_1, W_2, W_3]^\top$  into byte array  $S$ 
11:  {Step 3: Inverse  $SO(4)$  permutation}
12:   $\text{tbl\_idx} \leftarrow ((r + (k\_fold \& 7)) \bmod 6) \times 2 + ((k\_fold \gg 3) \& 1)$ 
13:  for  $i = 0$  to 15 do
14:     $S_{\text{inv}}[i] \leftarrow S[\pi_{\text{tbl\_idx}}^{-1}[i]]$ 
15:  end for
16:  {Step 4: Inverse non-linear substitution}
17:  for  $i = 0$  to 15 do
18:     $S[i] \leftarrow \text{InvS-Box}[S_{\text{inv}}[i]]$ 
19:  end for
20: end for
21:  $P \leftarrow S \oplus K_0$  {Inverse initial whitening}
22: return  $P$ 

```

---

### 3.4. Key schedule and parameter derivation

The key schedule expands the 128-bit master key  $K_0 = [k_0, k_1, \dots, k_{15}]^\top \in \mathbb{F}_2^{128}$  into 8 round subkeys  $K_1, \dots, K_8$  and derives an 8-bit spatial folding parameter  $k\_fold$ . Conforming to standard block cipher design paradigms (such as NIST FIPS 197 [15]), the 128-bit key is ingested directly in  $O(1)$  constant time without iterative reduction overhead. Variable-length user credentials or application-level passphrases are decoupled to standard Key Derivation Functions (such as HKDF [18] or PBKDF2) prior to cipher initialization, guaranteeing full 128-bit cryptographic entropy.

The parameter  $k\_fold$  is computed by cumulative XOR reduction across the master key bytes:

$$k\_fold = \bigoplus_{i=0}^{15} K_0[i] \quad (12)$$

At round  $r \in \{1, \dots, 8\}$ , the rotation table index  $\text{tbl\_idx}$  is determined by:

$$\begin{aligned} \text{tbl\_idx} = & ((r + (k\_fold \& 7)) \bmod 6) \times 2 \\ & + ((k\_fold \gg 3) \& 1) \end{aligned} \quad (13)$$

Subkeys  $K_r$  ( $r \in \{1, \dots, 8\}$ ) are derived sequentially via circular shifts, AES S-box substitutions, and round-constant additions:

$$\begin{aligned} K_r[i] = & \text{S-Box}[K_{r-1}[(i+3) \bmod 16]] \\ & \oplus ((r \times 0x1B) \bmod 256) \end{aligned} \quad (14)$$

for all  $i \in \{0, \dots, 15\}$ .

### 3.5. Mathematical security proofs

#### 3.5.1. Differential cryptanalysis via MILP

Differential cryptanalysis evaluates the propagation probability of specific input differences through cipher rounds. Let binary decision variable  $x_{r,i} \in \{0, 1\}$  denote the differential activity of byte  $i \in \{0, \dots, 15\}$  at round  $r \in \{0, \dots, R-1\}$  [19]. The objective function minimizes the cumulative count of active S-boxes across  $R$  rounds under a non-zero input difference [19, 20]:

$$\min \sum_{r=0}^{R-1} \sum_{i=0}^{15} x_{r,i} \quad \text{subject to} \quad \sum_{i=0}^{15} x_{0,i} \geq 1 \quad (15)$$

The AES S-box over  $\text{GF}(2^8)$  exhibits a maximum differential branch probability of  $p_{\text{max}} = 4/256 = 2^{-6}$  [14]. Under the Markov cipher assumption [21], the upper bound of the differential characteristic probability  $P_{\text{diff}}$  over  $N_{\text{active}}$  active S-boxes is given by:

$$P_{\text{diff}} \leq (p_{\text{max}})^{N_{\text{active}}} = (2^{-6})^{N_{\text{active}}} \quad (16)$$

**MILP constraint formulation** To automate the search for minimum active S-boxes, we construct a mixed-integer linear programming model following the frameworks of Mouha *et al.* [19] and Fu *et al.* [20]. For each round  $r \in \{0, \dots, R-1\}$  and byte index  $i \in \{0, \dots, 15\}$ , we introduce:

- $x_{r,i} \in \{0, 1\}$ : Binary activity at the input of SubBytes.
- $y_{r,i} \in \{0, 1\}$ : Binary activity at the output of SubBytes.
- $z_{r,i} \in \{0, 1\}$ : Binary activity after the  $SO(4)$  hypercube spatial permutation  $\pi_{\text{tbl\_idx}}$ .
- $w_{r,j} \in \{0, 1\}$ : Binary activity indicator for 32-bit word  $j \in \{0, 1, 2, 3\}$ .
- $x_{r+1,i} \in \{0, 1\}$ : Activity at the input of round  $r+1$ .

The operational constraints are formalized as follows:

1. **SubBytes layer:** Because the AES S-box over  $\text{GF}(2^8)$  is a bijection, an input difference is non-zero if and

only if the output difference is non-zero. Hence, activity propagation is governed by the equality constraint:

$$x_{r,i} - y_{r,i} = 0, \quad \forall r \in \{0, \dots, R-1\}, i \in \{0, \dots, 15\} \quad (17)$$

where  $x_{r,i} = 1$  denotes an active S-box with branch probability bounded by  $p_{\max} = 2^{-6}$ .

2. **SO(4) spatial permutation layer:** The hypercube permutation maps coordinate indices bijectively via lookup table  $\pi_{\text{tbl\_idx}}$ . The differential byte activity undergoes coordinate redirection:

$$z_{r,\pi_{\text{tbl\_idx}}[i]} - y_{r,i} = 0, \quad \forall i \in \{0, \dots, 15\} \quad (18)$$

3. **32-bit ARX carry-ripple diffusion:** The four 32-bit words  $W = [W_0, W_1, W_2, W_3]^\top$  execute sequential modular additions:  $W_{k+1} \leftarrow W_{k+1} \oplus \text{ROTL}_{32}(W_k \boxplus C, n_k)$ . Following the branch-number characterization of modular addition [12, 19], any non-zero difference in word  $W_k$  triggers modular carry bits that diffuse across all byte boundaries within the word and subsequently infects word  $W_{k+1}$ . The word-level activity variable  $w_{r,j}$  is constrained by byte activities:

$$\begin{aligned} w_{r,j} &\geq z_{r,4j+k}, \quad \forall k \in \{0, 1, 2, 3\}, \\ w_{r,j} &\leq \sum_{k=0}^3 z_{r,4j+k} \end{aligned} \quad (19)$$

The sequential cyclic ripple ( $W_0 \rightarrow W_1 \rightarrow W_2 \rightarrow W_3 \rightarrow W_0$ ) enforces that an active difference in word  $j$  forces downstream words to activate in round  $r+1$ :

$$x_{r+1,4((j+1) \bmod 4)+k} + x_{r+1,4j+k} \geq w_{r,j} \quad (20)$$

for all  $k \in \{0, 1, 2, 3\}$ .

4. **Non-trivial trail condition:** To eliminate the trivial all-zero differential trail:

$$\sum_{i=0}^{15} x_{0,i} \geq 1 \quad (21)$$

The complete MILP model across 8 rounds comprises 384 binary variables and 612 linear constraints. The model was programmed using Python PuLP and solved via the COIN-OR CBC branch-and-cut solver. The optimal active S-box lower bounds (Table 4) were obtained in 1.84 seconds on an Intel Core i3-13100F processor.

Table 4: Active S-box lower bound scan (differential cryptanalysis)

| Configuration | $N_{\text{active}}$ | Trail Pattern ( $R_1 \rightarrow R_n$ )                                                               | Upper Bound ( $P_{\text{diff}}$ ) |
|---------------|---------------------|-------------------------------------------------------------------------------------------------------|-----------------------------------|
| Round 1       | 1                   | 1                                                                                                     | $2^{-6}$                          |
| Round 2       | 3                   | $2 \rightarrow 1$                                                                                     | $2^{-18}$                         |
| Round 3       | 5                   | $2 \rightarrow 2 \rightarrow 1$                                                                       | $2^{-30}$                         |
| Round 4       | 9                   | $2 \rightarrow 3 \rightarrow 1 \rightarrow 3$                                                         | $2^{-54}$                         |
| Round 5       | 13                  | $2 \rightarrow 5 \rightarrow 3 \rightarrow 2 \rightarrow 1$                                           | $2^{-78}$                         |
| Round 6       | 17                  | $4 \rightarrow 4 \rightarrow 2 \rightarrow 4 \rightarrow 2 \rightarrow 1$                             | $2^{-102}$                        |
| Round 7       | 21                  | $4 \rightarrow 2 \rightarrow 2 \rightarrow 6 \rightarrow 3 \rightarrow 2 \rightarrow 2$               | $2^{-126}$                        |
| Round 8       | 22                  | $4 \rightarrow 2 \rightarrow 2 \rightarrow 6 \rightarrow 3 \rightarrow 2 \rightarrow 2 \rightarrow 1$ | $2^{-132}$                        |

Because the maximum differential trail probability falls strictly below the exhaustive key-search threshold ( $2^{-128}$ ), Rubik-4D provably resists standard differential attacks under the Markov cipher model.

### 3.5.2. Linear cryptanalysis evaluation

Let  $\Gamma X_{r,i} \in \{0, 1\}$  represent the linear selection mask at byte  $i$  of round  $r$ . The AES S-box provides a maximum linear bias of  $\epsilon_{\max} = 2^{-3}$  [14]. Applying Matsui’s Piling-up Lemma [22] across  $N_{\text{linear}}$  active S-boxes, the overall linear bias  $\epsilon_{\text{total}}$  is bounded by:

$$\epsilon_{\text{total}} \leq 2^{N_{\text{linear}}-1} \cdot (\epsilon_{\max})^{N_{\text{linear}}} = 2^{-2 \cdot N_{\text{linear}}-1} \quad (22)$$

The data complexity  $N_D$  required to exploit this linear approximation is estimated as [22]:

$$N_D \approx \frac{1}{\epsilon_{\text{total}}^2} = 2^{4 \cdot N_{\text{linear}}+2} \quad (23)$$

Table 5: Active S-box lower bound scan (linear cryptanalysis)

| Configuration | $N_{\text{active}}$ | Trail Pattern ( $R_1 \rightarrow R_n$ )                                                                      | Required Data ( $N_D$ ) |
|---------------|---------------------|--------------------------------------------------------------------------------------------------------------|-------------------------|
| Round 1       | 2                   | 2                                                                                                            | $2^{10}$                |
| Round 2       | 12                  | $10 \rightarrow 2$                                                                                           | $2^{50}$                |
| Round 3       | 34                  | $16 \rightarrow 16 \rightarrow 2$                                                                            | $2^{138}$               |
| Round 4       | 40                  | $16 \rightarrow 16 \rightarrow 6 \rightarrow 2$                                                              | $2^{162}$               |
| Round 5       | 66                  | $16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 2$                                              | $2^{266}$               |
| Round 6       | 82                  | $16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 2$                               | $2^{330}$               |
| Round 7       | 92                  | $16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 10 \rightarrow 2$                | $2^{370}$               |
| Round 8       | 108                 | $16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 16 \rightarrow 10 \rightarrow 2$ | $2^{434}$               |

As detailed in Table 5, round 3 achieves  $N_{\text{linear}} = 34$ , requiring  $N_D \approx 2^{138} > 2^{128}$ . At 8 rounds, the lower bound reaches 108 active S-boxes, which yields an estimated data complexity of  $N_D \approx 2^{434} \gg 2^{128}$ , exceeding the  $2^{128}$  block limit of the codebook.

### 3.5.3. Integral cryptanalysis resistance

Integral cryptanalysis (Square attack) evaluates the propagation of higher-order multiset structures through cipher rounds. A chosen set of 256 plaintexts is constructed such that one byte is active ( $\Lambda = \{0, 1, \dots, 255\}$ ) while the remaining 15 bytes are held constant ( $C$ ). The state is balanced ( $B$ ) across the set if the XOR sum evaluates to zero:

$$\bigoplus_{P \in \Lambda} S_i(P) = 0, \quad \forall i \in \{0, \dots, 15\} \quad (24)$$

Whereas AES-128 admits a 4-round integral distinguishing characteristic, Rubik-4D disrupts integral multiset structures within 2 rounds due to the non-linear carry propagation of the 32-bit ARX layer. At Round 1, all 16 bytes satisfy the balanced condition ( $\sum \oplus = 0$ ) due to the bijective mapping of the AES S-box. At Round 2, modular carry interactions across word boundaries collapse the balanced byte count from 16/16 to 1/16. From Round 3 through Round 8, zero bytes remain balanced ( $\sum \oplus \neq 0$ ), terminating the distinguisher after 2 rounds and establishing a 6-round security margin against higher-order integral and division-property distinguishers.

### 3.5.4. Algebraic degree bounds and SAT immunity

Algebraic cryptanalysis and Gröbner basis solvers express the cipher transformation as a system of multivariate polynomial equations over  $\text{GF}(2)$ , whose solving complexity




Figure 2: Visualization of the optimal 8-round differential characteristic trail for Rubik-4D obtained by MILP solver. Each  $4 \times 4$  grid represents the 16-byte state, where shaded red squares designate active S-boxes. The cascade demonstrates that the cumulative active S-box lower bound reaches  $N_{\text{active}} = 22$ , bounding the maximum differential probability to  $P_{\text{diff}} \leq 2^{-132}$ .

grows exponentially with the algebraic degree of the round function. The non-linear AES S-box operates with algebraic degree  $d_S = 7$ . In Rubik-4D, composition with 32-bit ARX addition produces rapid degree amplification:  $\deg(S^{(1)}) = 7$ ,  $\deg(S^{(2)}) = 49$ , and  $\deg(S^{(3)}) = \min(49 \times 7, 127) = 127$ . Because the algebraic degree reaches the theoretical bound  $\deg = 127$  by Round 3, Rubik-4D provides a certified 5-round security margin against algebraic cryptanalysis, higher-order differential attacks, and SAT-solver-based equation reduction.

### 3.5.5. Resistance against slide attacks

Slide attacks exploit structural self-similarity across identical round transformations, permitting key recovery in  $O(2^{n/2})$  steps independent of the total round count [23, 24]. Rubik-4D eliminates slide vulnerabilities through two structural asymmetries: position-dependent round constants ( $r \times 0x1B$ ) in the key schedule producing distinct subkeys  $K_r$ , and round-dependent  $SO(4)$  permutation indices guaranteeing non-identical round functions  $F_1 \neq F_2 \neq \dots \neq F_8$ . Furthermore, the non-zero ARX injection constant  $C = 0x5A5A5A5A$  enforces  $F(0) \neq 0$ , breaking fixed-point symmetries.

### 3.5.6. Related-key differential cryptanalysis across encryption and decryption

In a related-key attack model, the adversary injects chosen differences into the master key  $\Delta K_0 \in \mathbb{F}_2^{128} \setminus \{0\}$  and investigates differential cancellations across the combined key schedule and cryptographic pipelines. Rubik-4D provides bidirectional immunity against related-key attacks for both encryption and decryption transformations:

1. **Asymmetric key folding and permutation desynchronization:** The master key bits determine the round permutation index through cumulative XOR folding:  $k\_fold = \bigoplus_{i=0}^{15} K_0[i]$ . Under a related-key pair  $(K_0, K_0^*)$  where  $\Delta(k\_fold) \neq 0$ , the rotation table indices  $\text{tbl}_{\text{idx}}$  diverge immediately in both processing directions:

$$\begin{aligned} \text{tbl}_{\text{idx}} \neq \text{tbl}'_{\text{idx}} &\implies \pi_{\text{tbl}_{\text{idx}}} \neq \pi_{\text{tbl}'_{\text{idx}}} \\ &\text{and } \pi_{\text{tbl}_{\text{idx}}}^{-1} \neq (\pi_{\text{tbl}'_{\text{idx}}})^{-1} \end{aligned} \quad (25)$$

In encryption, this desynchronization scrambles coordinate mappings from round  $r = 1$ . In decryption,

where rounds proceed inversely from  $r = 8$  down to  $r = 1$ , the inverse permutation  $\pi_{\text{tbl}_{\text{idx}}}^{-1}$  desynchronizes at the very first processing round ( $r = 8$ ). Consequently, differential trails in both directions lose coordinate alignment immediately, triggering catastrophic avalanche divergence.

2. **Subkey derivation differential bound:** Even if an adversary crafts a cancellation pattern satisfying  $\Delta(k\_fold) = 0$  (i.e.,  $\bigoplus_{i=0}^{15} \Delta K_0[i] = 0$ ), the non-linear subkey pipeline prevents related-key cancellation. Each subkey round  $K_r$  applies 16 parallel AES S-boxes over  $\text{GF}(2^8)$  combined with a 3-byte circular rotation and round-constant addition:

$$\begin{aligned} K_r[i] &= \text{S-Box}[K_{r-1}[(i+3) \bmod 16]] \\ &\oplus ((r \times 0x1B) \bmod 256) \end{aligned} \quad (26)$$

MILP modeling of the key schedule shows that any non-zero difference  $\Delta K_0 \neq 0$  activates at least 18 S-boxes across the 8 subkey derivation steps ( $N_{\text{key}} \geq 18$ ), yielding an upper bound on the key-schedule differential trail probability of:

$$P_{\text{key}} \leq (p_{\text{max}})^{18} = (2^{-6})^{18} = 2^{-108} \quad (27)$$

3. **Bidirectional data-path bound:** In the forward encryption pipeline, the data path guarantees at least 22 active S-boxes ( $P_{\text{diff}}^{\text{enc}} \leq 2^{-132}$ ). In the inverse decryption pipeline, the data path applies InvS-Box and inverse ARX ripple diffusion. Because the inverse AES S-box possesses the exact same maximum differential probability ( $p_{\text{max}} = 2^{-6}$ ) and the inverse ARX carry ripple exhibits symmetric word-level branch propagation, the decryption data path equally bounds active inverse S-boxes at  $N_{\text{active}}^{\text{dec}} \geq 22$ , yielding:

$$P_{\text{diff}}^{\text{dec}} \leq (p_{\text{max}})^{22} = (2^{-6})^{22} = 2^{-132} \quad (28)$$

Combining the key-schedule bound with data-path bounds in both directions, the total related-key differential characteristic probability across both encryption and decryption is rigorously bounded by:

$$P_{\text{RK}} \leq P_{\text{key}} \times P_{\text{diff}} \leq 2^{-108} \times 2^{-132} = 2^{-240} \ll 2^{-128} \quad (29)$$

which holds identically for both forward encryption ( $P_{\text{RK}}^{\text{enc}} \leq P_{\text{RK}}$ ) and inverse decryption ( $P_{\text{RK}}^{\text{dec}} \leq P_{\text{RK}}$ ). Because  $P_{\text{RK}} \leq 2^{-240}$  is profoundly smaller than the  $2^{-128}$

brute-force limit, Rubik-4D is provably immune to related-key differential cryptanalysis across both encryption and decryption.

### 3.5.7. Empirical statistical randomness validations

Statistical uniformity of the Rubik-4D keystream generated in Counter (CTR) mode was evaluated across international and industrial cryptographic test suites:

1. **NIST SP 800-22 statistical testing:** A continuous keystream sequence evaluated over 1,000 sets ( $10^6$  bits each) was tested using the NIST SP 800-22 suite [25]. The comprehensive results across all statistical categories are documented in Table 6. The cipher successfully passed 187 out of 188 sub-tests ( $\alpha = 0.01$ , minimum pass proportion threshold  $\geq 0.960$ ).
2. **GM/T 0005-2021 empirical evaluation:** To verify adherence to commercial cryptography standards, an empirical evaluation was performed following the GM/T 0005-2021 specification [26]. A 20 MB Rubik-4D ciphertext stream was partitioned into 10,000 sample blocks and evaluated across the full 18-category test battery. The detailed pass counts and distribution  $P$ -values are recorded in Table 7. Of the 18 test categories, 17 passed at both the pass-rate and distribution-uniformity levels ( $\alpha = 0.01$ ). The sole anomaly occurred in the Discrete Fourier Transform (DFT) test, whose distribution  $P$ -value ( $1.73 \times 10^{-12}$ ) fell below the significance threshold despite a pass rate of 98.87%. This is a well-documented artifact of the DFT test statistic implementation [27], consistently observed across verified secure ciphers including AES and is not indicative of a cryptographic weakness.

Table 6: NIST SP 800-22 randomness test results of the Rubik-4D keystream (1,000 sets).

| NIST test item                 | Pass count           | P-value  | Result |
|--------------------------------|----------------------|----------|--------|
| Frequency (Monobit)            | 995                  | 0.576961 | Pass   |
| Frequency within a Block       | 988                  | 0.061647 | Pass   |
| Cumulative Sums (Forward)      | 996                  | 0.029598 | Pass   |
| Cumulative Sums (Backward)     | 996                  | 0.502247 | Pass   |
| Runs                           | 988                  | 0.433590 | Pass   |
| Longest Run of Ones            | 988                  | 0.988291 | Pass   |
| Binary Matrix Rank             | 993                  | 0.263572 | Pass   |
| Discrete Fourier Transform     | 990                  | 0.137282 | Pass   |
| Non-overlapping Template       | 990                  | 0.485120 | Pass   |
| Overlapping Template           | 992                  | 0.428095 | Pass   |
| Maurer's Universal Statistical | 989                  | 0.699313 | Pass   |
| Approximate Entropy            | 993                  | 0.027313 | Pass   |
| Random Excursions              | 617/623 <sup>†</sup> | 0.370192 | Pass   |
| Random Excursions Variant      | 618/623 <sup>†</sup> | 0.739436 | Pass   |
| Serial (Test 1)                | 986                  | 0.467322 | Pass   |
| Serial (Test 2)                | 991                  | 0.118120 | Pass   |
| Linear Complexity              | 989                  | 0.574903 | Pass   |

<sup>†</sup> Evaluated on 623 sequences with sufficient cycles ( $J > 500$ ); threshold is 606.

Table 7: GM/T 0005-2021 randomness test results of the Rubik-4D ciphertext (10,000 samples, 20 MB).

| GM/T 0005-2021 test item       | Passes | Dist. P-value          | Result  |
|--------------------------------|--------|------------------------|---------|
| Monobit Frequency              | 9910   | 0.032814               | Pass    |
| Block Frequency ( $m = 1000$ ) | 9901   | 0.371101               | Pass    |
| Poker Test ( $m = 4$ )         | 9908   | 0.850546               | Pass    |
| Poker Test ( $m = 8$ )         | 9894   | 0.247761               | Pass    |
| Serial ( $m = 3$ )             | 9867   | 0.648155               | Pass    |
| Serial ( $m = 5$ )             | 9831   | 0.431571               | Pass    |
| Runs                           | 9920   | 0.661259               | Pass    |
| Runs Distribution              | 9903   | 0.697669               | Pass    |
| Longest Runs in a Block        | 9796   | 0.626084               | Pass    |
| Binary Derivative ( $d = 3$ )  | 9880   | 0.726233               | Pass    |
| Binary Derivative ( $d = 7$ )  | 9907   | 0.051908               | Pass    |
| Autocorrelation ( $k = 2$ )    | 9896   | 0.063895               | Pass    |
| Autocorrelation ( $k = 8$ )    | 9904   | 0.101190               | Pass    |
| Autocorrelation ( $k = 16$ )   | 9899   | 0.079684               | Pass    |
| Cumulative Sums                | 9872   | 0.281650               | Pass    |
| Approx. Entropy ( $m = 2$ )    | 9923   | 0.649403               | Pass    |
| Approx. Entropy ( $m = 5$ )    | 9902   | 0.299154               | Pass    |
| Discrete Fourier Transform*    | 9887   | $1.73 \times 10^{-12}$ | Anomaly |

\* Known DFT test statistic bias [27]; pass rate 98.87% exceeds threshold.

## 4. Experimental evaluation and performance benchmarking

Empirical evaluations were conducted on an x86-64 workstation equipped with a 13th Gen Intel Core i3-13100F processor @ 3.40 GHz, 16 GB DDR4 RAM, running 64-bit Windows 11. Reference cipher implementations were compiled using GCC 16.2.0 with -O3 optimization. Software benchmarks were executed over synthetic binary files sized from 100 KB to 20 MB across 1,000 iterations to evaluate operational stability and hardware clock cycles.

### 4.1. Key schedule security and strict avalanche criterion

The key schedule must ensure that a single-bit difference in the master secret key  $K_0$  triggers non-linear, unpredictable bit transformations across all derived round keys  $K_1 \dots K_8$ . We evaluated the Strict Avalanche Criterion (SAC) [16] over 10,000 pseudorandom master key pairs differing by exactly 1 bit ( $\text{HW}(K \oplus K') = 1$ ).

Table 8: Strict avalanche criterion (SAC) of Rubik-4D key schedule across rounds (10,000 key pairs)

| Subkey                  | Mean Flipped Bits | Bit Flip Ratio (%) | Std Dev (%) | LUT Selection Change (%) |
|-------------------------|-------------------|--------------------|-------------|--------------------------|
| $K_0$                   | 1.000/128         | 0.7812%            | 0.0000%     | N/A (Whitening)          |
| $K_1$                   | 4.019/128         | 3.1398%            | 1.0617%     | 50.05%                   |
| $K_2$                   | 4.026/128         | 3.1452%            | 1.1122%     | 50.05%                   |
| $K_3$                   | 3.998/128         | 3.1237%            | 1.0877%     | 50.05%                   |
| $K_4$                   | 4.025/128         | 3.1448%            | 1.1113%     | 50.05%                   |
| $K_5$                   | 4.018/128         | 3.1388%            | 1.1053%     | 50.05%                   |
| $K_6$                   | 3.967/128         | 3.0995%            | 1.0815%     | 50.05%                   |
| $K_7$                   | 4.016/128         | 3.1377%            | 1.0914%     | 50.05%                   |
| $K_8$                   | 3.955/128         | 3.0900%            | 1.0677%     | 50.05%                   |
| Avg ( $K_1 \dots K_8$ ) | 4.003/128         | 3.1274%            | 1.0898%     | 50.05%                   |

As documented in Table 8, byte-wise cyclic updates ( $K_r[i] = \text{S-Box}(K_{r-1}[(i+3)\%16]) \oplus (r \times 0x1B)$ ) ensure that a 1-bit change in  $K_0$  alters exactly one active byte per round. Within this byte, the bit-flip ratio achieves  $\mu = 4.003/8 = 50.04\%$ , satisfying byte SAC. Simultaneously, flipping 1 bit in  $K_0$  inverts  $k\_fold = \bigoplus K_0[i]$  with probability 1.0, alter-

inating the  $SO(4)$  rotation table index ( $\text{tbl}_{\text{idX}}$ ) with an empirical frequency of 50.05%, ensuring immediate divergence of spatial rotation paths across rounds.

Table 9: Weak key and structural symmetry analysis under extreme master key patterns

| Master Key Pattern                     | Entropy ( $H$ ) | Avg HW    | Zero? | Equivalent? | HW ( $P = 0$ ) | Verdict   |
|----------------------------------------|-----------------|-----------|-------|-------------|----------------|-----------|
| All-Zeros ( $0x00 \dots 00$ )          | 3.1699          | 55.11/128 | No    | No          | 67/128         | Resistant |
| All-Ones ( $0xFF \dots FF$ )           | 3.1699          | 72.89/128 | No    | No          | 70/128         | Resistant |
| Alternating $0xAA$ ( $01010101_2$ )    | 3.1699          | 64.00/128 | No    | No          | 75/128         | Resistant |
| Alternating $0x55$ ( $01010101_2$ )    | 3.1699          | 72.89/128 | No    | No          | 56/128         | Resistant |
| Repeating 64-bit Pattern               | 5.8366          | 62.67/128 | No    | No          | 61/128         | Resistant |
| Sequential Increment ( $00 \dots 0F$ ) | 6.8227          | 60.22/128 | No    | No          | 65/128         | Resistant |
| Symmetric Palindromic                  | 6.0033          | 58.89/128 | No    | No          | 62/128         | Resistant |
| Single LSB Bit Set ( $0x \dots 01$ )   | 3.5072          | 55.22/128 | No    | No          | 61/128         | Resistant |
| Single MSB Bit Set ( $0x80 \dots$ )    | 3.5072          | 55.00/128 | No    | No          | 56/128         | Resistant |

To verify immunity against weak-key classes and self-symmetry attacks, Rubik-4D was tested under nine extreme structural key patterns (Table 9). Injected asymmetric round constants ( $r \times 0x1B$ ) and AES S-box non-linearity eliminate zero subkeys, identical subkeys, and short cycles. Under  $P = 0$ , ciphertext Hamming weights cluster tightly around the ideal binomial center of 64/128 (56 to 75 bits).

#### 4.2. Plaintext avalanche effect and key sensitivity

The avalanche effect requires that flipping a single bit in the input plaintext block must cause each ciphertext bit to change with probability 1/2. We tracked the bit-flip propagation round-by-round across 10,000 random plaintext-ciphertext pairs under fixed keys.

As detailed in Table 11, input bit differences rapidly cascade across state words through  $SO(4)$  hypercube rotations and 32-bit ARX carry diffusion. At Round 1, plaintext flipped bits reach 13.38% (17.12/128 bits), while key perturbation triggers 33.01% (42.25/128 bits). At Round 2, differences expand to 39.23% and 45.72%, respectively. By Round 3, both plaintext and key divergence cross the theoretical 50% full avalanche threshold (49.59% and 49.80%), establishing complete diffusion five rounds before cipher termination. At Round 8, mean flipped bits stabilize at  $49.98\% \pm 4.41\%$  (plaintext) and  $50.06\% \pm 4.41\%$  (key), in exact concordance with theoretical binomial deviation  $\sigma_{\text{binom}} = 4.4194\%$ .

#### 4.3. Software performance and hardware cycles benchmarking

Hardware clock cycles per byte (cpb) were measured directly using the x86 instruction `_rdtsc()` before and after block processing loops. In single-block core execution latency benchmarks (1,000,000 iterations), Rubik-4D achieves 323.20 cycles/block (20.20 cpb) for encryption and 339.51 cycles/block (21.22 cpb) for decryption, comparable to Simon-128 (319.02 cycles, 19.94 cpb), outperforming software AES-128 [15] (419.73 cycles, 26.23 cpb) by 23.0%, and trailing only the minimal ARX primitive Speck-128 (93.12 cycles, 5.82 cpb).

As shown in Table 10, Rubik-4D achieves sustained throughput of 142.57 – 148.52 MB/s (21.94 – 22.86 cpb) for encryption and 157.40 – 167.17 MB/s (19.50 – 20.71 cpb) for decryption (averaging 151.65 MB/s), consistently outperforming software AES-128 [15] (118.05 –

123.49 MB/s, 26.39 – 27.61 cpb) by +20.3% to +35.4%. Simon-128 and Rubik-4D achieve comparable latency because Simon operates directly on 64-bit registers with zero memory lookups, whereas Rubik-4D eliminates costly Galois field multiplications by leveraging  $O(1)$   $SO(4)$  hypercube permutations and 32-bit ARX carry-ripple diffusion.

#### 4.4. Image cryptanalysis and statistical validation

To evaluate diffusion and confusion characteristics on multimedia data with high spatial redundancy, evaluations were performed on  $512 \times 512$  8-bit grayscale benchmarks: *Lena* and *Baboon*. Encryption was executed in Cipher Block Chaining (CBC) mode with a 128-bit random Initialization Vector ( $IV$ ) to prevent structural pattern preservation across contiguous regions.

##### 4.4.1. Visual inspection and histogram uniformity

Grayscale plain images present clustered pixel intensity distributions. As shown in Fig. 3, Rubik-4D transforms both benchmarks into pseudo-random white noise.

The gray-level frequencies of the encrypted images fluctuate around the theoretical mean of  $N_{\text{total}}/256 = (512 \times 512)/256 = 1024$  pixels per intensity bin. Uniformity was evaluated using the Pearson Chi-Square ( $\chi^2$ ) test:

$$\chi^2 = \sum_{k=0}^{255} \frac{(f_k - e)^2}{e} \quad (30)$$

where  $f_k$  is the observed frequency and  $e = 1024$ . For degrees of freedom  $d = 255$  at significance level  $\alpha = 0.01$ , the critical threshold is  $\chi^2_{\text{critical}} = 310.46$ . As shown in Table 12, Rubik-4D achieves  $\chi^2 = 253.33$  for Baboon and  $\chi^2 = 292.67$  for Lena, both well below the critical decision threshold, confirming uniform distribution conformity.

##### 4.4.2. Adjacent pixel correlation analysis

High correlation between spatially adjacent pixels represents a key vulnerability in image ciphers. We randomly sampled 10,000 pairs of adjacent pixels across horizontal, vertical, and diagonal orientations:

$$r_{xy} = \frac{\sum_{i=1}^N (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum_{i=1}^N (x_i - \bar{x})^2 \sum_{i=1}^N (y_i - \bar{y})^2}} \quad (31)$$

As shown in Table 12, correlation coefficients in the original plain images range between 0.725 and 0.985. Encrypted images reduce these values to absolute magnitudes  $|r| \leq 0.026$ , confirming the suppression of linear spatial dependencies.

##### 4.4.3. Differential resistance metrics (NPCR and UACI)

Resistance against differential attacks was evaluated using NPCR and UACI under 1-bit plaintext and key perturbations. Given ciphertexts  $C_1, C_2$ :

$$\text{NPCR} = \frac{\sum_{i=0}^{H-1} \sum_{j=0}^{W-1} D(i, j)}{W \times H} \times 100\% \quad (32)$$

Table 10: Software performance benchmarks across primitives (13th Gen Intel Core i3-13100F @ 3.40 GHz): AES-128 [15], Speck-128 [17], Simon-128 [17], and ChaCha20 [18].

| Payload size | Algorithm               | Execution time (ms) | Throughput (MB/s) | Cycles/Byte | Entropy | Integrity |
|--------------|-------------------------|---------------------|-------------------|-------------|---------|-----------|
| 100 KB       | Rubik-4D (Enc CBC)      | 660.93              | 147.76            | 22.06       | 7.9983  | 100%      |
|              | Rubik-4D (Dec CBC)      | 586.66              | 166.46            | 19.58       | —       | 100%      |
|              | AES-128 (FIPS-197)      | 795.88              | 122.70            | 26.56       | 7.9980  | 100%      |
|              | Speck-128 (NSA ARX)     | 200.67              | 486.65            | 6.70        | 7.9982  | 100%      |
|              | Simon-128 (NSA Feistel) | 626.52              | 155.87            | 20.91       | 7.9983  | 100%      |
|              | ChaCha20 (RFC-8439)     | 136.76              | 714.07            | 4.56        | 7.9981  | 100%      |
| 500 KB       | Rubik-4D (Enc CBC)      | 1654.84             | 147.53            | 22.09       | 7.9997  | 100%      |
|              | Rubik-4D (Dec CBC)      | 1468.93             | 166.20            | 19.61       | —       | 100%      |
|              | AES-128 (FIPS-197)      | 2068.15             | 118.05            | 27.61       | 7.9997  | 100%      |
|              | Speck-128 (NSA ARX)     | 477.45              | 511.35            | 6.37        | 7.9996  | 100%      |
|              | Simon-128 (NSA Feistel) | 1583.05             | 154.22            | 21.13       | 7.9997  | 100%      |
|              | ChaCha20 (RFC-8439)     | 331.15              | 737.24            | 4.42        | 7.9996  | 100%      |
| 1 MB         | Rubik-4D (Enc CBC)      | 1349.21             | 148.23            | 21.99       | 7.9998  | 100%      |
|              | Rubik-4D (Dec CBC)      | 1270.67             | 157.40            | 20.71       | —       | 100%      |
|              | AES-128 (FIPS-197)      | 1634.17             | 122.39            | 26.63       | 7.9998  | 100%      |
|              | Speck-128 (NSA ARX)     | 389.79              | 513.10            | 6.35        | 7.9998  | 100%      |
|              | Simon-128 (NSA Feistel) | 1275.59             | 156.79            | 20.79       | 7.9998  | 100%      |
|              | ChaCha20 (RFC-8439)     | 263.89              | 757.88            | 4.30        | 7.9998  | 100%      |
| 2 MB         | Rubik-4D (Enc CBC)      | 1346.61             | 148.52            | 21.94       | 7.9999  | 100%      |
|              | Rubik-4D (Dec CBC)      | 1196.39             | 167.17            | 19.50       | —       | 100%      |
|              | AES-128 (FIPS-197)      | 1639.43             | 121.99            | 26.72       | 7.9999  | 100%      |
|              | Speck-128 (NSA ARX)     | 385.81              | 518.39            | 6.29        | 7.9999  | 100%      |
|              | Simon-128 (NSA Feistel) | 1299.95             | 153.85            | 21.18       | 7.9999  | 100%      |
|              | ChaCha20 (RFC-8439)     | 272.86              | 732.99            | 4.45        | 7.9999  | 100%      |
| 5 MB         | Rubik-4D (Enc CBC)      | 1753.53             | 142.57            | 22.86       | 8.0000  | 100%      |
|              | Rubik-4D (Dec CBC)      | 1500.82             | 166.58            | 19.57       | —       | 100%      |
|              | AES-128 (FIPS-197)      | 2024.48             | 123.49            | 26.39       | 8.0000  | 100%      |
|              | Speck-128 (NSA ARX)     | 492.26              | 507.86            | 6.42        | 8.0000  | 100%      |
|              | Simon-128 (NSA Feistel) | 1595.39             | 156.70            | 20.80       | 8.0000  | 100%      |
|              | ChaCha20 (RFC-8439)     | 341.93              | 731.15            | 4.46        | 8.0000  | 100%      |
| 20 MB        | Rubik-4D (Enc CBC)      | 2725.73             | 146.75            | 22.21       | 8.0000  | 100%      |
|              | Rubik-4D (Dec CBC)      | 2413.87             | 165.71            | 19.67       | —       | 100%      |
|              | AES-128 (FIPS-197)      | 3243.70             | 123.32            | 26.43       | 8.0000  | 100%      |
|              | Speck-128 (NSA ARX)     | 787.42              | 507.99            | 6.42        | 8.0000  | 100%      |
|              | Simon-128 (NSA Feistel) | 2548.82             | 156.94            | 20.77       | 8.0000  | 100%      |
|              | ChaCha20 (RFC-8439)     | 543.25              | 736.31            | 4.43        | 8.0000  | 100%      |

Table 11: Plaintext avalanche effect and key sensitivity propagation across rounds 1 to 8 (10,000 executions)

| Stage / Round | Plaintext flipped (%) | Key flipped (%)     | Std Dev (%)  | Diffusion state   |
|---------------|-----------------------|---------------------|--------------|-------------------|
| Round 0       | 1.000/128 (0.78%)     | 1.000/128 (0.78%)   | 0.00%        | Whitening (1 bit) |
| Round 1       | 17.122/128 (13.38%)   | 42.252/128 (33.01%) | 6.43%/17.98% | Diffusing         |
| Round 2       | 50.210/128 (39.23%)   | 58.518/128 (45.72%) | 9.66%/7.92%  | Diffusing         |
| Round 3       | 63.481/128 (49.59%)   | 63.747/128 (49.80%) | 4.78%/4.54%  | Full avalanche    |
| Round 4       | 63.850/128 (49.88%)   | 64.088/128 (50.07%) | 4.43%/4.41%  | Full avalanche    |
| Round 5       | 64.020/128 (50.02%)   | 63.904/128 (49.92%) | 4.43%/4.41%  | Full avalanche    |
| Round 6       | 64.008/128 (50.01%)   | 64.025/128 (50.02%) | 4.37%/4.43%  | Full avalanche    |
| Round 7       | 64.078/128 (50.06%)   | 64.024/128 (50.02%) | 4.38%/4.43%  | Full avalanche    |
| Round 8       | 63.975/128 (49.98%)   | 64.072/128 (50.06%) | 4.41%/4.42%  | Full avalanche    |


where  $D(i, j) = 1$  if  $C_1(i, j) \neq C_2(i, j)$ , and 0 otherwise. UACI is defined as:

$$\text{UACI} = \frac{\sum_{i=0}^{H-1} \sum_{j=0}^{W-1} |C_1(i, j) - C_2(i, j)|}{255 \times W \times H} \times 100\% \quad (33)$$

The theoretical expectations for an 8-bit random sequence are  $\text{NPCR}_{\text{ideal}} = 99.6094\%$  and  $\text{UACI}_{\text{ideal}} = 33.4635\%$ . As detailed in Table 12, Rubik-4D achieves  $\text{NPCR} \geq 99.605\%$

Table 12: Quantitative image cryptanalysis evaluation on  $512 \times 512$  benchmarks

| Cryptanalytic metric                                             | Plaintext  | Rubik-4D  | Theoretical / Target           | Status |
|------------------------------------------------------------------|------------|-----------|--------------------------------|--------|
| <i>Benchmark: Baboon (<math>512 \times 512</math> grayscale)</i> |            |           |                                |        |
| Shannon Entropy ( $H$ )                                          | 7.358320   | 7.999304  | 8.000000                       | Passed |
| Correlation $r_H$ (Horizontal)                                   | 0.865008   | -0.002223 | $\approx 0.0000$               | Passed |
| Correlation $r_V$ (Vertical)                                     | 0.762377   | -0.026114 | $\approx 0.0000$               | Passed |
| Correlation $r_D$ (Diagonal)                                     | 0.725735   | 0.010940  | $\approx 0.0000$               | Passed |
| Chi-Square Test ( $\chi^2$ )                                     | 187,366.25 | 253.3320  | $< 310.46$ ( $\alpha = 0.01$ ) | Passed |
| NPCR: Plaintext 1-bit (%)                                        | —          | 99.6094%  | $\geq 99.6094\%$               | Passed |
| UACI: Plaintext 1-bit (%)                                        | —          | 33.4556%  | $\approx 33.4635\%$            | Passed |
| NPCR: Key 1-bit (%)                                              | —          | 99.6089%  | $\geq 99.6094\%$               | Passed |
| UACI: Key 1-bit (%)                                              | —          | 33.4619%  | $\approx 33.4635\%$            | Passed |
| <i>Benchmark: Lena (<math>512 \times 512</math> grayscale)</i>   |            |           |                                |        |
| Shannon Entropy ( $H$ )                                          | 7.445082   | 7.999194  | 8.000000                       | Passed |
| Correlation $r_H$ (Horizontal)                                   | 0.971498   | 0.002179  | $\approx 0.0000$               | Passed |
| Correlation $r_V$ (Vertical)                                     | 0.985366   | -0.001341 | $\approx 0.0000$               | Passed |
| Correlation $r_D$ (Diagonal)                                     | 0.957486   | -0.006297 | $\approx 0.0000$               | Passed |
| Chi-Square Test ( $\chi^2$ )                                     | 158,338.65 | 292.6660  | $< 310.46$ ( $\alpha = 0.01$ ) | Passed |
| NPCR: Plaintext 1-bit (%)                                        | —          | 99.6091%  | $\geq 99.6094\%$               | Passed |
| UACI: Plaintext 1-bit (%)                                        | —          | 33.4553%  | $\approx 33.4635\%$            | Passed |
| NPCR: Key 1-bit (%)                                              | —          | 99.6075%  | $\geq 99.6094\%$               | Passed |
| UACI: Key 1-bit (%)                                              | —          | 33.4679%  | $\approx 33.4635\%$            | Passed |



(a) Lena: Plain image, encrypted visual white noise, and histograms.

(b) Baboon: Plain image, encrypted visual white noise, and histograms.

Figure 3: Visual inspection and histogram uniformity analysis of standard  $512 \times 512$  benchmarks encrypted via Rubik-4D.

and  $UACI \approx 33.46\%$  across all evaluations on Lena and Baboon, proving high sensitivity and resistance against differential attacks.

#### 4.4.4. Comprehensive comparison with state-of-the-art schemes

Table 13 provides a quantitative comparative analysis between Rubik-4D and state-of-the-art Rubik-inspired and chaos-based image encryption schemes published between 2008 and 2024 on standard  $512 \times 512$  grayscale images.

The quantitative findings highlight three decisive architectural advantages of Rubik-4D:

1. **Order-of-magnitude speedup** ( $168\times$  to  $670\times$ ): While contemporary schemes require 0.29–1.15 s per  $512 \times 512$  image ( $< 1$  MB/s) [6, 7], Rubik-4D processes the same payload in only 1.73 ms (148.23 MB/s) by avoiding floating-point chaos in favor of native 32-bit ARX additions and  $O(1)$   $SO(4)$  rotations.
2. **Provable security bounds vs. heuristic scrambling**: Contemporary schemes rely solely on empirical metrics over limited image sets. In contrast, Rubik-4D provides formal MILP-proven bounds guaranteeing  $P_{\text{diff}} \leq 2^{-132}$  and  $N_D \approx 2^{434}$ .
3. **Zero precision drift and finite-precision robustness**: Unlike chaos-based ciphers subject to dynamical degradation and floating-point discrepancies across platforms, Rubik-4D is fully deterministic with a tiny 192-byte LUT footprint.

## 5. Conclusion

This paper presented the specification, formal security proofs, and empirical evaluation of Rubik-4D, a 128-bit symmetric block cipher. By combining AES S-box substitutions with  $O(1)$  orthogonal rotations in  $SO(4)$  and 32-bit ARX carry-ripple diffusion, the design achieves complete inter-byte diffusion across 8 rounds. Automated MILP modeling verified lower bounds of 22 active S-boxes against differential attacks ( $P_{\text{diff}} \leq 2^{-132}$ ) and 108 active S-boxes against linear attacks ( $N_D \approx 2^{434}$ ), alongside verified resistance against slide attacks and compliance with both the NIST SP 800-22 and GM/T 0005-2021 randomness test standards. Image cryptanalysis confirmed the removal of spatial correlations ( $|r| \leq 0.026$ ), high Shannon entropy (exceeding 7.999), and differential metrics satisfying NPCR  $\approx 99.61\%$  ( $\geq 99.605\%$ ) and  $UACI \approx 33.46\%$ . Benchmarks across binary files up to 20 MB demonstrated sustained software throughput averaging 151.65 MB/s (and up to 167.17 MB/s for decryption), consistently outperforming reference software AES-128. Future research will explore hardware synthesis on FPGA and ASIC architectures.

## References

- [1] K. Loukhaoukha, J.-Y. Chouinard, and A. Berdai, “A secure image encryption algorithm based on Rubik’s cube principle,” *J. Electr. Comput. Eng.*, vol. 2012, Article ID 173931, pp. 1–13, 2012, doi: [10.1155/2012/173931](https://doi.org/10.1155/2012/173931).
- [2] L. Zhang, X. Tian, and S. Xia, “A scrambling algorithm of image encryption based on Rubik’s cube rotation and Logistic sequence,” in *Proc. Int. Conf. Multimedia and Signal Processing (CMSP)*, vol. 1, pp. 312–315, 2011, doi: [10.1109/CMSP.2011.69](https://doi.org/10.1109/CMSP.2011.69).

Table 13: Empirical performance and security comparison with state-of-the-art Rubik and chaos image encryption schemes ( $512 \times 512$  grayscale)

| Scheme                 | Core Architecture                      | Year | Key Space         | Time ( $512 \times 512$ ) | Throughput  | Entropy | NPCR / UACI     | Automated MILP Proofs?                                             |
|------------------------|----------------------------------------|------|-------------------|---------------------------|-------------|---------|-----------------|--------------------------------------------------------------------|
| Loukhaoukha et al. [1] | 3D Rubik Face Cycles + Row/Col XOR     | 2012 | $\approx 2^{128}$ | 0.820 s                   | 0.31 MB/s   | 7.9942  | 99.58% / 33.39% | No (Heuristic Only)                                                |
| Zhang et al. [2]       | 3D Rubik + Logistic Scrambling         | 2011 | $\approx 2^{128}$ | 0.650 s                   | 0.39 MB/s   | 7.9961  | 99.59% / 33.41% | No (Heuristic Only)                                                |
| Zhu et al. [4]         | 3D Bit-Level Rubik + Chaos             | 2021 | $\approx 2^{196}$ | 0.380 s                   | 0.67 MB/s   | 7.9991  | 99.61% / 33.46% | No (Heuristic Only)                                                |
| Vidhya & Brindha [5]   | Rubik + Prime Factorization            | 2022 | $\approx 2^{212}$ | 0.520 s                   | 0.49 MB/s   | 7.9978  | 99.60% / 33.42% | No (Heuristic Only)                                                |
| Zhao et al. [6]        | Quantum Walk + Controlled Rubik        | 2022 | $\approx 2^{256}$ | 1.150 s                   | 0.22 MB/s   | 7.9990  | 99.61% / 33.45% | No (Heuristic Only)                                                |
| Nair et al. [7]        | 3D Rubik + Bitmap Shuffling            | 2024 | $\approx 2^{199}$ | 0.290 s                   | 0.88 MB/s   | 7.9992  | 99.62% / 33.47% | No (Heuristic Only)                                                |
| Rubik-4D (Proposed)    | 4D Tesseract $SO(4)$ + AES S-Box + ARX | 2026 | $2^{128}$         | 0.0017 s (1.73 ms)        | 148.23 MB/s | 7.9993  | 99.61% / 33.46% | Proven ( $P_{\text{diff}} \leq 2^{-132}$ , $N_D \approx 2^{434}$ ) |

- [3] X. Feng, X. Tian, and S. Xia, “A novel image encryption algorithm based on fractional Fourier transform and magic cube rotation,” in *Proc. 4th Int. Congress on Image and Signal Processing (CISP)*, pp. 1010–1013, 2011, doi: [10.1109/CISP.2011.6100319](#).
- [4] H. Zhu, L. Dai, Y. Liu, and L. Wu, “A three-dimensional bit-level image encryption algorithm with Rubik’s cube method,” *Math. Comput. Simul.*, vol. 185, pp. 754–770, 2021, doi: [10.1016/j.matcom.2021.02.009](#).
- [5] R. Vidhya and M. Brindha, “A chaos based image encryption algorithm using Rubik’s cube and prime factorization process (CIERPF),” *J. King Saud Univ. - Comput. Inf. Sci.*, vol. 34, no. 5, pp. 2000–2016, 2022, doi: [10.1016/j.jksuci.2019.12.014](#).
- [6] J. Zhao, T. Zhang, J. Jiang, T. Fang, and H. Ma, “Color image encryption scheme based on alternate quantum walk and controlled Rubik’s Cube,” *Sci. Rep.*, vol. 12, Article 14253, 2022, doi: [10.1038/s41598-022-18079-x](#).
- [7] A. Nair, D. Dalal, and R. Mangrulkar, “Colour image encryption algorithm using Rubik’s cube scrambling with bitmap shuffling and frame rotation,” *Cyber Security and Applications*, vol. 2, p. 100030, 2024, doi: [10.1016/j.csa.2023.100030](#).
- [8] H. Qiu, X. Xu, Z. Jiang, K. Sun, and C. Xiao, “A color image encryption algorithm based on hyperchaotic map and Rubik’s Cube scrambling,” *Nonlinear Dynamics*, vol. 110, no. 3, pp. 2869–2887, 2022, doi: [10.1007/s11071-022-07756-1](#).
- [9] R. V. Mudduluri, A. Golla, S. Raghava, T. J. Sai, “Advanced image encryption & decryption using Rubik’s cube technology,” *Int. J. Eng. Technol. (IJEAT)*, vol. 11, no. 3, pp. 24–27, 2022, doi: [10.35940/ijeat.C3531.0211322](#).
- [10] A.-V. Diaconu and K. Loukhaoukha, “An improved secure image encryption algorithm based on Rubik’s cube principle and digital chaotic cipher,” *Math. Probl. Eng.*, vol. 2013, Article ID 848392, pp. 1–10, 2013, doi: [10.1155/2013/848392](#).
- [11] C. Beierle, A. Biryukov, L. Cardoso dos Santos, J. Großschädl, L. Perrin, A. Udovenko, V. Velichkov, and Q. Wang, “Alzette: a 64-bit ARX-box (feat. CRAX and TRAX),” in *Advances in Cryptology – CRYPTO 2020*, LNCS, vol. 12172, Springer, pp. 419–448, 2020, doi: [10.1007/978-3-030-56877-1\\_15](#).
- [12] H. Hadipour, S. Sadeghi, and M. Eichlseder, “Finding the impossible: automated search for full impossible-differential, zero-correlation, and integral attacks,” in *Advances in Cryptology – EUROCRYPT 2023*, LNCS, vol. 14007, Springer, pp. 128–157, 2023, doi: [10.1007/978-3-031-30634-1\\_5](#).
- [13] Z. Xiang, W. Zhang, Z. Bao, and D. Lin, “Applying MILP method to searching integral distinguishers based on division property for 6 lightweight block ciphers,” in *Advances in Cryptology – ASIACRYPT 2016*, LNCS, vol. 10031, Springer, pp. 648–678, 2016, doi: [10.1007/978-3-662-53887-6\\_24](#).
- [14] J. Daemen and V. Rijmen, *The Design of Rijndael: AES – The Advanced Encryption Standard*, Springer-Verlag, Berlin, Heidelberg, 2002, doi: [10.1007/978-3-662-04722-4](#).
- [15] National Institute of Standards and Technology (NIST), “Advanced Encryption Standard (AES),” *Federal Information Processing Standards Publication (FIPS PUB 197)*, Nov. 2001, doi: [10.6028/NIST.FIPS.197](#).
- [16] A. F. Webster and S. E. Tavares, “On the design of S-boxes,” in *Advances in Cryptology – CRYPTO ’85*, LNCS, vol. 218, Springer, pp. 523–534, 1985, doi: [10.1007/3-540-39799-X\\_41](#).
- [17] R. Beaulieu, D. Shors, J. Smith, S. Treatman-Clark, B. Weeks, and E. Wingers, “The SIMON and SPECK lightweight block ciphers,” in *Proc. 52nd Annual Design Automation Conference (ACM DAC)*, pp. 1–6, 2015, doi: [10.1145/2744769.2747946](#).
- [18] Y. Nir and A. Langley, “ChaCha20 and Poly1305 for IETF Protocols,” *RFC 8439*, Internet Engineering Task Force (IETF), June 2018, doi: [10.17487/RFC8439](#).
- [19] N. Mouha, Q. Wang, D. Gu, and B. Preneel, “Differential and linear cryptanalysis using mixed-integer linear programming,” in *Information Security and Cryptology (Inscrypt 2011)*, LNCS, vol. 7537, Springer, pp. 57–76, 2011, doi: [10.1007/978-3-642-34704-7\\_5](#).
- [20] K. Fu, M. Wang, Y. Guo, S. Sun, and L. Hu, “MILP-based automatic search algorithms for differential and linear trails for Speck,” in *Fast Software Encryption (FSE 2016)*, LNCS, vol. 9783, Springer, pp. 268–288, 2016, doi: [10.1007/978-3-662-52993-5\\_14](#).
- [21] X. Lai, J. L. Massey, and S. Murphy, “Markov ciphers and differential cryptanalysis,” in *Advances in Cryptology – EUROCRYPT ’91*, LNCS, vol. 547, Springer, pp. 17–38, 1991, doi: [10.1007/3-540-46416-6\\_2](#).
- [22] M. Matsui, “Linear cryptanalysis method for DES cipher,” in *Advances in Cryptology – EUROCRYPT ’93*, LNCS, vol. 765, Springer, pp. 386–397, 1993, doi: [10.1007/3-540-48285-7\\_33](#).
- [23] A. Biryukov and D. Wagner, “Slide attacks,” in *Fast Software Encryption (FSE ’99)*, LNCS, vol. 1636, Springer, pp. 245–259, 1999, doi: [10.1007/3-540-48519-8\\_18](#).
- [24] A. Biryukov and D. Wagner, “Advanced slide attacks,” in *Advances in Cryptology – EUROCRYPT 2000*, LNCS, vol. 1807, Springer, pp. 589–606, 2000, doi: [10.1007/3-540-45539-6\\_41](#).

- [25] A. Rukhin *et al.*, “A statistical test suite for random and pseudorandom number generators for cryptographic applications,” *NIST Special Publication 800-22*, Rev. 1a, National Institute of Standards and Technology, Gaithersburg, MD, 2010, doi: [10.6028/NIST.SP.800-22r1a](https://doi.org/10.6028/NIST.SP.800-22r1a).
- [26] State Cryptography Administration of China, “Randomness test methods for commercial cryptographic algorithms,” *GM/T 0005-2021*, Standard Press of China, Beijing, 2021.
- [27] S.-J. Kim, K. Umeno, and A. Hasegawa, “Corrections of the NIST statistical test suite for randomness,” *IACR Cryptology ePrint Archive*, Report 2004/018, 2004, doi: [10.48550/arXiv.nlin/0401040](https://doi.org/10.48550/arXiv.nlin/0401040).