



CleanOcean

Smart Contract Security Audit

Audit Report
May, 2021



Table of contents

| | |
|---------------------------------|----|
| Project Introduction | 2 |
| Auditing Methodologies applied: | 3 |
| Static Analysis | 4 |
| Auditing Tools | 4 |
| Tokenomics | 5 |
| Issues Checking | 6 |
| Severity Issue Categories | 8 |
| Issues Found | 9 |
| Automated Testing | 14 |
| Functional View | 18 |
| Inheritance Chart | 19 |
| Audit Findings Results | 20 |

Project Introduction

Clean Ocean is a frictionless decentralized yield-generation charity eco-token. The token operates on an automated liquidity-locking and self-staking direct distribution protocol, providing safe, secure and hassle-free transactions and yield-generation for all holders automatically.

| | |
|---------------------|---|
| Name | CLEANOCEAN |
| Total Supply | 1,000,000,000,000,000 |
| Type | BSC Token |
| Website | https://cleanocean.io/ |
| Platform | Binance Smart Chain |
| Pancake Swap Supply | 310,000,000,000,000 |
| Holders | 17,829 addresses |
| Deployed Contract | 0x579F11C75Eb4e47F5290122e87CA411644aDCD97 |

Token Audit Team performed a security audit for **Clean Ocean** smart contracts during the period of Sep 3, 2021 to Sep 4, 2021.

The code for the audit was taken from following the official link:

<https://github.com/eic0/CleanOcean/blob/main/CleanOcean.sol>

Auditing Methodologies applied:

- In this audit, we can review the code listed below.
- The overall quality of code.
- Whether the implementation of BEP 20 standards.
- Whether the code is secure.
- Gas Optimization
- Code is safe from reentrancy and other vulnerabilities

Manual Audit

- Manually analyzing the source code line-by-line in an attempt to identify security vulnerabilities.
- Gas Consumption and optimization
- Assessing the overall project structure, complexity & quality.
- Checking whether all the libraries used in the code of the latest version.

Automated Audit

- Projects can be Automated using these tools with Slither, Manticore, Sol Graph others.
 - Performing Unit testing.
 - Symbolic execution, which is analyzing a program to determine what inputs cause each part of a program to execute.
- Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.

Static Analysis

Static Analysis of Smart Contracts was done to identify contract vulnerabilities. In this step a series of automated tools are used to test security of smart contracts.

Auditing Tools

Language: Solidity

Platform and tools: Slither, Manti-Core, VScode, Solhint, Solc-select, Solidity-coverage

Audit Aim: The focus of the audit was to verify whether the smart contract is secure, resilient, and working according to the standard specs. The audit activity can be categorized into three types

- Security
- Sound Architecture
- Code Correctness and Quality

Tokenomics:

The Tokenomics were as follows (in number of tokens):

1,000,000,000,000,000 Total Supply

300,000,000,000,000 Initial Burn

300,000,000,000,000 DxSale Pre-Sale Supply

310,000,000,000,000 PancakeSwap Supply

90,000,000,000,000 Dev-Wallet

(Numbers might vary slightly) 1,000,000,000,000,000 Total Supply

The founders hold around 8.5% of the total supply in a locked wallet.

This wallet exists to ensure the ongoing of the project and consists of the following parts:

50% Charity funds

30% Marketing budget

10% Development budget

10% Reserve

Issues Checking

We have scanned this smart contract code for commonly known and more specific Vulnerabilities that are below listed:

| SN | Issue Description | Status |
|----|--|----------|
| 1 | Re-entrancy | Verified |
| 2 | Compiler errors | Verified |
| 3 | Timestamp Dependence | Verified |
| 4 | Unsafe external calls | Verified |
| 5 | Gas Limit and Loops | Verified |
| 6 | DoS with Block Gas Limit | Verified |
| 7 | Private user data leaks | Verified |
| 8 | Code clones, functionality duplication | Verified |
| 9 | Style guide violation | Verified |
| 10 | Costly Loop | Verified |
| 11 | Balance equality | Verified |
| 12 | Unchecked math | Verified |

| | | |
|----|---|----------|
| 13 | Integer overflow/underflow | Verified |
| 14 | Cross-function Race Condition | Verified |
| 15 | Fallback function security | Verified |
| 16 | Data Consistency | Verified |
| 17 | Balance equality | Verified |
| 18 | ERC20 API violation | Verified |
| 19 | Deployment Consistency | Verified |
| 20 | Arithmetic accuracy | Verified |
| 21 | Transaction-Ordering Dependence (TOD) / Front Running | Verified |
| 22 | Address hardcoded | Verified |
| 23 | Scoping and Declarations | Verified |
| 24 | Implicit visibility level | Verified |
| 25 | Call Depth Attack (deprecated) | Verified |

Severity Issue Categories

Every issue in this report was assigned a severity level from the following:

Critical

Critical vulnerabilities are usually straightforward to exploit and can lead to token loss etc.

High

The issue affects the ability of the contract to compile or operate in a significant way.

Medium

Issues on this level could potentially bring problems and should eventually be fixed.

Low

Low-level vulnerabilities are mostly related to outdated, unused, etc. code snippets that can't have a significant impact on execution.

Informational

The issue has no impact on the contract's ability to operate.

Issues Found

- **Critical severity issues** - No Critical severity issues found.
- **High severity issues** - No Critical severity issues found.
- **Medium severity issues** - 1 medium severity issues found.
- **Low severity issues** - 1 low severity issues were found.
- **Informational** - 5 Informational severity issues were found.

| High | Medium | Low | Informational |
|------|--------|-----|---------------|
| 0 | 1 | 1 | 5 |

Medium level severity issues

1. Unused-Return

Severity: Medium

Description

The return value of an external call is not stored in a local or state variable:

```
function addLiquidity(uint256 tokenAmount!, uint256 ethAmount!) private {  
    // approve token transfer to cover all possible scenarios  
    _approve(address(this), address(uniswapV2Router), tokenAmount!);  
  
    // add the liquidity  
    uniswapV2Router.addLiquidityETH{value: ethAmount!}(  
        address(this),  
        tokenAmount!,  
        0, // slippage is unavoidable  
        0, // slippage is unavoidable  
        owner(),  
        block.timestamp  
    );  
}
```

ignores return value

Suggestion:

Ensure that all the return values of the function calls are used.

Low level severity issues

1. block.timestamp

Severity: **Low**

Description

Uses timestamp for comparisons.

In the case of block.timestamp, developers often attempt to use it to trigger time-dependent events. As Ethereum is decentralized, nodes can synchronize time only to some degree. Moreover, malicious miners can alter the timestamp of their blocks, especially if they can gain advantages by doing so. However, miners can't set a timestamp smaller than the previous one (otherwise the block will be rejected), nor can they set the timestamp too far ahead in the future

```
function unlock() public virtual {  
    require(_previousOwner == msg.sender, "You don't have permission to unlock");  
    require(now > _lockTime, "Contract is locked until 7 days");  
    emit OwnershipTransferred(_owner, _previousOwner);  
    _owner = _previousOwner;  
}
```

Suggestion:

Developers should write smart contracts with the notion that block values are not precise, and the use of them can lead to unexpected effects

<https://consensys.github.io/smart-contract-best-practices/recommendations/#timestamp-dependence>

Informational level severity issues

1. DEAD-CODE

Severity: Informational

Description:

Functions that are not used. is not used in the contract, and make the code's review more difficult.

```
Address.functionCallWithValue(address,bytes,uint256,string) (CleanOcean.sol#363-384) is never used and should be removed
Address.functionCall(address,bytes) (CleanOcean.sol#323-325) is never used and should be removed
Address.functionCall(address,bytes,string) (CleanOcean.sol#333-335) is never used and should be removed
Address.functionCallWithValue(address,bytes,uint256) (CleanOcean.sol#348-350) is never used and should be removed
Address.functionCallWithValue(address,bytes,uint256,string) (CleanOcean.sol#358-361) is never used and should be removed
Address.isContract(address) (CleanOcean.sol#270-279) is never used and should be removed
Address.sendValue(address,uint256) (CleanOcean.sol#297-303) is never used and should be removed
Context.msgData() (CleanOcean.sol#242-245) is never used and should be removed
SafeMath.mod(uint256,uint256) (CleanOcean.sol#215-217) is never used and should be removed
```

Suggestion:

Remove unused functions.

2. Conformance-To-Solidity-Naming-Conventions

Severity: Informational

Description:

In the contract, many function names were found to be starting with capital letters. Functions other than constructors should use mixed Case

```
Function IUniswapV2Pair.DOMAIN_SEPARATOR() (CleanOcean.sol#509) is not in mixedCase
Function IUniswapV2Pair.PERMIT_TYPEHASH() (CleanOcean.sol#510) is not in mixedCase
Function IUniswapV2Pair.MINIMUM_LIQUIDITY() (CleanOcean.sol#527) is not in mixedCase
Function IUniswapV2Router01.WETH() (CleanOcean.sol#549) is not in mixedCase
Parameter CleanOcean.setSwapAndLiquifyEnabled(bool). enabled (CleanOcean.sol#896) is not in mixedCase
Parameter CleanOcean.calculateTaxFee(uint256). amount (CleanOcean.sol#955) is not in mixedCase
Parameter CleanOcean.calculateLiquidityFee(uint256). amount (CleanOcean.sol#961) is not in mixedCase
Variable CleanOcean.taxFee (CleanOcean.sol#709) is not in mixedCase
Variable CleanOcean._liquidityFee (CleanOcean.sol#712) is not in mixedCase
Variable CleanOcean._maxTxAmount (CleanOcean.sol#721) is not in mixedCase
```

Rule exceptions:

Allow constant variable name/symbol/decimals to be lowercase (ERC20).

Allow _ at the beginning of the mixed_case match for private variables and unused parameters.

Suggestion:

Follow the Solidity: <https://docs.soliditylang.org/en/v0.4.25/style-guide.html#naming-conventions>

3. State Variable Default Visibility

Severity: Informational

```
bool inSwapAndLiquify;
```

Description:

The Visibility of the inSwapAndLiquify variable is not defined. Labeling the visibility explicitly makes it easier to catch incorrect assumptions about who can access the variable.

The default is internal for state variables, but it should be made explicit.

Suggestion:

We recommend adding the visibility for the state variable of inSwapAndLiquify. Variables can be specified as being public, internal or private. Explicitly define visibility for all state variables.

4. Public function that could be declared external

Severity: Informational

Description:

The following public functions that are never called by the contract should be declared external to save gas

- ❖ includeInFee
- ❖ setLiquidityFeePercent
- ❖ setSwapAndLiquifyEnabled
- ❖ excludeFromFee
- ❖ _reflectFee

Suggestion:

Use the external attribute for functions never called from the contract.

5. State variables that could be declared constant

Severity: Informational

Description:

The above constant state variables should be declared constant to save gas.

_decimals

_name

_symbol

_tTotal

numTokensSellToAddToLiquidity

Suggestion:

Add the constant attributes to state variables that never change

Automated Testing

We have to use Automated testing Slither. It is an Automated Analysis Tool in Smart Contract.

```
INFO:Detectors:
Reentrancy in CleanOcean._transfer(address,address,uint256) (CleanOcean.sol#994-1038):
  External calls:
    - swapAndLiquify(contractTokenBalance) (CleanOcean.sol#1025)
      - uniswapV2Router.addLiquidityETH(value: ethAmount)(address(this),tokenAmount,0,0,owner(),block.timestamp) (CleanOcean.sol#1086-1093)
      - uniswapV2Router.swapExactTokensForETHSupportingFeeOnTransferTokens(tokenAmount,0,path,address(this),block.timestamp) (CleanOcean.sol#1072-1078)
    External calls sending eth:
      - swapAndLiquify(contractTokenBalance) (CleanOcean.sol#1025)
        - uniswapV2Router.addLiquidityETH(value: ethAmount)(address(this),tokenAmount,0,0,owner(),block.timestamp) (CleanOcean.sol#1086-1093)
  State variables written after the call(s):
    - _tokenTransfer(from,to,amount,takeFee) (CleanOcean.sol#1037)
      - rOwned[address(this)] = rOwned[address(this)].add(rLiquidity) (CleanOcean.sol#950)
      - rOwned[sender] = rOwned[sender].sub(rAmount) (CleanOcean.sol#1119)
      - rOwned[sender] = rOwned[sender].sub(rAmount) (CleanOcean.sol#1128)
      - rOwned[sender] = rOwned[sender].sub(rAmount) (CleanOcean.sol#1139)
      - rOwned[sender] = rOwned[sender].sub(rAmount) (CleanOcean.sol#866)
      - rOwned[recipient] = rOwned[recipient].add(rTransferAmount) (CleanOcean.sol#1120)
      - rOwned[recipient] = rOwned[recipient].add(rTransferAmount) (CleanOcean.sol#1130)
      - rOwned[recipient] = rOwned[recipient].add(rTransferAmount) (CleanOcean.sol#1140)
      - rOwned[recipient] = rOwned[recipient].add(rTransferAmount) (CleanOcean.sol#868)
    - _tokenTransfer(from,to,amount,takeFee) (CleanOcean.sol#1037)
      - rTotal = rTotal.sub(rFee) (CleanOcean.sol#905)
    - _tokenTransfer(from,to,amount,takeFee) (CleanOcean.sol#1037)
      - tOwned[address(this)] = tOwned[address(this)].add(tLiquidity) (CleanOcean.sol#952)
      - tOwned[sender] = tOwned[sender].sub(tAmount) (CleanOcean.sol#1138)
      - tOwned[sender] = tOwned[sender].sub(tAmount) (CleanOcean.sol#865)
      - tOwned[recipient] = tOwned[recipient].add(tTransferAmount) (CleanOcean.sol#1129)
      - tOwned[recipient] = tOwned[recipient].add(tTransferAmount) (CleanOcean.sol#867)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#reentrancy-vulnerabilities
```

```
INFO:Detectors:
CleanOcean.addLiquidity(uint256,uint256) (CleanOcean.sol#1081-1094) ignores return value by uniswapV2Router.addLiquidityETH(value: ethAmount)(address(this),tokenAmount,0,0,owner(),block.timestamp) (CleanOcean.sol#1086-1093)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#unused-return
INFO:Detectors:
CleanOcean.allowance(address,address).owner (CleanOcean.sol#782) shadows:
  - Ownable.owner() (CleanOcean.sol#418-420) (function)
CleanOcean._approve(address,address,uint256).owner (CleanOcean.sol#986) shadows:
  - Ownable.owner() (CleanOcean.sol#418-420) (function)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#local-variable-shadowing
INFO:Detectors:
Reentrancy in CleanOcean._transfer(address,address,uint256) (CleanOcean.sol#994-1038):
  External calls:
    - swapAndLiquify(contractTokenBalance) (CleanOcean.sol#1025)
      - uniswapV2Router.addLiquidityETH(value: ethAmount)(address(this),tokenAmount,0,0,owner(),block.timestamp) (CleanOcean.sol#1086-1093)
      - uniswapV2Router.swapExactTokensForETHSupportingFeeOnTransferTokens(tokenAmount,0,path,address(this),block.timestamp) (CleanOcean.sol#1072-1078)
```

```
State variables written after the call(s):
  - _approve(sender,msgSender(),allowances[sender][msgSender()].sub(amount,ERC20: transfer amount exceeds allowance)) (CleanOcean.sol#793)
  - allowances[owner][spender] = amount (CleanOcean.sol#990)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#reentrancy-vulnerabilities-2
INFO:Detectors:
Reentrancy in CleanOcean._transfer(address,address,uint256) (CleanOcean.sol#994-1038):
  External calls:
    - swapAndLiquify(contractTokenBalance) (CleanOcean.sol#1025)
      - uniswapV2Router.addLiquidityETH(value: ethAmount)(address(this),tokenAmount,0,0,owner(),block.timestamp) (CleanOcean.sol#1086-1093)
      - uniswapV2Router.swapExactTokensForETHSupportingFeeOnTransferTokens(tokenAmount,0,path,address(this),block.timestamp) (CleanOcean.sol#1072-1078)
    External calls sending eth:
      - swapAndLiquify(contractTokenBalance) (CleanOcean.sol#1025)
        - uniswapV2Router.addLiquidityETH(value: ethAmount)(address(this),tokenAmount,0,0,owner(),block.timestamp) (CleanOcean.sol#1086-1093)
  Event emitted after the call(s):
    - Transfer(sender,recipient,tTransferAmount) (CleanOcean.sol#1123)
      - tokenTransfer(from,to,amount,takeFee) (CleanOcean.sol#1037)
    - Transfer(sender,recipient,tTransferAmount) (CleanOcean.sol#1143)
      - tokenTransfer(from,to,amount,takeFee) (CleanOcean.sol#1037)
    - Transfer(sender,recipient,tTransferAmount) (CleanOcean.sol#1133)
      - tokenTransfer(from,to,amount,takeFee) (CleanOcean.sol#1037)
    - Transfer(sender,recipient,tTransferAmount) (CleanOcean.sol#871)
```

```

    Event emitted after the call(s):
    - Approval(owner,spender,amount) (CleanOcean.sol#991)
    - approve(sender, msgSender(), allowances[sender][ msgSender()].sub(amount,ERC20: transfer amount exceeds allowance)) (CleanOcean.sol#793)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#reentrancy-vulnerabilities-3
INFO:Detectors:
Ownable.unlock() (CleanOcean.sol#465-470) uses timestamp for comparisons
    Dangerous comparisons:
    - require(bool,string)(now > lockTime,Contract is locked until 7 days) (CleanOcean.sol#467)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#block-timestamp
INFO:Detectors:
Address.isContract(address) (CleanOcean.sol#270-279) uses assembly
    - INLINE ASM (CleanOcean.sol#277)
Address.functionCallWithValue(address,bytes,uint256,string) (CleanOcean.sol#363-384) uses assembly
    - INLINE ASM (CleanOcean.sol#376-379)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#assembly-usage
INFO:Detectors:
Address.functionCallWithValue(address,bytes,uint256,string) (CleanOcean.sol#363-384) is never used and should be removed
Address.functionCall(address,bytes) (CleanOcean.sol#323-325) is never used and should be removed
Address.functionCall(address,bytes,string) (CleanOcean.sol#333-335) is never used and should be removed
Address.functionCallWithValue(address,bytes,uint256) (CleanOcean.sol#348-350) is never used and should be removed
Address.functionCallWithValue(address,bytes,uint256,string) (CleanOcean.sol#358-361) is never used and should be removed
Address.isContract(address) (CleanOcean.sol#270-279) is never used and should be removed
Address.sendValue(address,uint256) (CleanOcean.sol#297-303) is never used and should be removed
Context.msgData() (CleanOcean.sol#242-245) is never used and should be removed
SafeMath.mod(uint256,uint256) (CleanOcean.sol#215-217) is never used and should be removed
SafeMath.mod(uint256,uint256,string) (CleanOcean.sol#231-234) is never used and should be removed
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#dead-code
INFO:Detectors:
CleanOcean._rTotal (CleanOcean.sol#702) is set pre-construction with a non-constant function or state variable:
    - (MAX - (MAX % tTotal))
CleanOcean._previousTaxFee (CleanOcean.sol#710) is set pre-construction with a non-constant function or state variable:
    - _taxFee
CleanOcean._previousLiquidityFee (CleanOcean.sol#713) is set pre-construction with a non-constant function or state variable:
    - _liquidityFee
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#function-initializing-state-variables
INFO:Detectors:
Low level call in Address.sendValue(address,uint256) (CleanOcean.sol#297-303):
    - (success) = recipient.call(value: amount)() (CleanOcean.sol#301)
Low level call in Address.functionCallWithValue(address,bytes,uint256,string) (CleanOcean.sol#363-384):
    - (success,returnData) = target.call(value: weiValue)(data) (CleanOcean.sol#367)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#low-level-calls

```

```

INFO:Detectors:
Function IUniswapV2Pair.DOMAIN_SEPARATOR() (CleanOcean.sol#509) is not in mixedCase
Function IUniswapV2Pair.PERMIT_TYPEHASH() (CleanOcean.sol#510) is not in mixedCase
Function IUniswapV2Pair.MINIMUM_LIQUIDITY() (CleanOcean.sol#527) is not in mixedCase
Function IUniswapV2Router01.WETH() (CleanOcean.sol#549) is not in mixedCase
Parameter CleanOcean.setSwapAndLiquifyEnabled(bool), enabled (CleanOcean.sol#896) is not in mixedCase
Parameter CleanOcean.calculateTaxFee(uint256), amount (CleanOcean.sol#955) is not in mixedCase
Parameter CleanOcean.calculateLiquidityFee(uint256), amount (CleanOcean.sol#961) is not in mixedCase
Variable CleanOcean._taxFee (CleanOcean.sol#709) is not in mixedCase
Variable CleanOcean._liquidityFee (CleanOcean.sol#712) is not in mixedCase
Variable CleanOcean._maxTxAmount (CleanOcean.sol#721) is not in mixedCase
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#conformance-to-solidity-naming-conventions
INFO:Detectors:
Redundant expression "this (CleanOcean.sol#243)" inContext (CleanOcean.sol#237-246)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#redundant-statements
INFO:Detectors:
Variable IUniswapV2Router01.addLiquidity(address,address,uint256,uint256,uint256,uint256,address,uint256).amountADesired (CleanOcean.sol#554) is too similar to IUniswapV2Router01.addLiquidity(address,address,uint256,uint256,uint256,uint256,address,uint256).amountBDesired (CleanOcean.sol#555)
Variable CleanOcean._getRValues(uint256,uint256,uint256,uint256).rTransferAmount (CleanOcean.sol#926) is too similar to CleanOcean._transferBothExcluded(address,address,uint256).tTransferAmount (CleanOcean.sol#864)
Variable CleanOcean._getRValues(uint256,uint256,uint256,uint256).rTransferAmount (CleanOcean.sol#926) is too similar to CleanOcean._transferToExcluded(address,address,uint256).tTransferAmount (CleanOcean.sol#864)

```

```

Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#variable-names-are-too-similar
INFO:Detectors:
CleanOcean.slitherConstructorVariables() (CleanOcean.sol#687-1150) uses literals with too many digits:
    - tTotal = 1000000000 * 10 ** 6 * 10 ** 9 (CleanOcean.sol#701)
CleanOcean.slitherConstructorVariables() (CleanOcean.sol#687-1150) uses literals with too many digits:
    - _maxTxAmount = 5000000 * 10 ** 6 * 10 ** 9 (CleanOcean.sol#721)
CleanOcean.slitherConstructorVariables() (CleanOcean.sol#687-1150) uses literals with too many digits:
    - numTokensSellToAddToLiquidity = 500000 * 10 ** 6 * 10 ** 9 (CleanOcean.sol#722)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#too-many-digits
INFO:Detectors:
CleanOcean._decimals (CleanOcean.sol#707) should be constant
CleanOcean._name (CleanOcean.sol#705) should be constant
CleanOcean._symbol (CleanOcean.sol#706) should be constant
CleanOcean._tTotal (CleanOcean.sol#701) should be constant
CleanOcean._numTokensSellToAddToLiquidity (CleanOcean.sol#722) should be constant
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#state-variables-that-could-be-declared-constant
INFO:Detectors:
renounceOwnership() should be declared external:
    - Ownable.renounceOwnership() (CleanOcean.sol#437-440)

```



```

Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#variable-names-are-too-similar
INFO:Detectors:
CleanOcean.slitherConstructorVariables() (CleanOcean.sol#687-1150) uses literals with too many digits:
  - _tTotal = 1000000000 * 10 ** 6 * 10 ** 9 (CleanOcean.sol#701)
CleanOcean.slitherConstructorVariables() (CleanOcean.sol#687-1150) uses literals with too many digits:
  - maxTxAmount = 5000000 * 10 ** 6 * 10 ** 9 (CleanOcean.sol#721)
CleanOcean.slitherConstructorVariables() (CleanOcean.sol#687-1150) uses literals with too many digits:
  - numTokensSellToAddToLiquidity = 500000 * 10 ** 6 * 10 ** 9 (CleanOcean.sol#722)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#too-many-digits
INFO:Detectors:
CleanOcean.decimals (CleanOcean.sol#707) should be constant
CleanOcean.name (CleanOcean.sol#705) should be constant
CleanOcean.symbol (CleanOcean.sol#706) should be constant
CleanOcean._tTotal (CleanOcean.sol#701) should be constant
CleanOcean.numTokensSellToAddToLiquidity (CleanOcean.sol#722) should be constant
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#state-variables-that-could-be-declared-constant
INFO:Detectors:
renounceOwnership() should be declared external:
  - Ownable.renounceOwnership() (CleanOcean.sol#437-440)

```

```

includeInFee(address) should be declared external:
  - CleanOcean.includeInFee(address) (CleanOcean.sol#878-880)
setSwapAndLiquifyEnabled(bool) should be declared external:
  - CleanOcean.setSwapAndLiquifyEnabled(bool) (CleanOcean.sol#896-899)
isExcludedFromFee(address) should be declared external:
  - CleanOcean.isExcludedFromFee(address) (CleanOcean.sol#982-984)
Reference: https://github.com/crytic/slither/wiki/Detector-Documentation#public-function-that-could-be-declared-external
INFO:Slither:./CleanOcean.sol analyzed (10 contracts with 75 detectors), 116 result(s) found

```

Sol-hint Tool:

A linter for Solidity that provides both Security and Style Guide validations.

Coding style issues influence code readability and, in some cases, may lead to bugs in future. Smart Contracts have a naming convention, indentation and code layout issues. It's recommended to use Solidity Style Guide to fix all the issues. Consider following the Solidity guidelines on formatting the code and commenting for all the files. It can improve the overall code quality and readability

```
contracts/CleanOcean.sol
243:2 error Line length must be no more than 120 but current length is 132 max-line-length
295:2 error Line length must be no more than 120 but current length is 160 max-line-length
314:2 error Line length must be no more than 120 but current length is 156 max-line-length
333:2 error Line length must be no more than 120 but current length is 122 max-line-length
358:2 error Line length must be no more than 120 but current length is 146 max-line-length
363:2 error Line length must be no more than 120 but current length is 149 max-line-length
741:2 error Line length must be no more than 120 but current length is 134 max-line-length
793:2 error Line length must be no more than 120 but current length is 130 max-line-length
803:2 error Line length must be no more than 120 but current length is 138 max-line-length
864:2 error Line length must be no more than 120 but current length is 146 max-line-length
922:2 error Line length must be no more than 120 but current length is 147 max-line-length
1118:2 error Line length must be no more than 120 but current length is 146 max-line-length
1127:2 error Line length must be no more than 120 but current length is 146 max-line-length
1137:2 error Line length must be no more than 120 but current length is 146 max-line-length

X14 problems (14 errors, 0 warnings)
```

Functional View

| Function | Return Type | Test Result |
|----------------------|-------------|-------------|
| name | Public | Verified |
| symbol | Public | Verified |
| decimals | Public | Verified |
| totalSupply | Public | Verified |
| balanceOf | Public | Verified |
| transfer | Public | Verified |
| allowance | Public | Verified |
| approve | Public | Verified |
| TransferFrom | Public | Verified |
| increaseAllowance | Public | Verified |
| decreaseAllowance | Public | Verified |
| isExcludedFromReward | Public | Verified |
| totalFees | Public | Verified |
| deliver | Public | Verified |
| reflectionFromToken | Public | Verified |

| | | |
|----------------------|--------|----------|
| tokenFromReflection | Public | Verified |
| excludeFromReward | Public | Verified |
| includeInReward | Public | Verified |
| transferBothExcluded | Public | Verified |

Inheritance Chart



Audit Findings Results

There were **1 Medium** and **1 Low issue** and **5 Informational** found during the audit. All the mentioned findings may have an effect only in case of specific conditions performed by the contract owner. None of the critical issues were resolved.

Generally, the contracts are well written and structured. The findings during the audit have some impact on contract performance or security

Disclaimer

This audit does not provide a security or correctness guarantee of audited smart contracts. You agree that your access and/or use, including but not limited to any services, products, platforms, content, will be at your Own risk. Smart contract remains under development and is subject to unknown risks and flaws. The review does not extend to the compiler layer, or any other areas beyond the programming language aspects that could present security risks. A report does not indicate the endorsement of any particular project or team, nor guarantee its security.



<http://tokenaudit.net/>



<https://t.me/TokenAudit>



<https://twitter.com/AuditToken>