

100plus API 5.0

一、Introduction of API concatenation

1. Let players access WEB to play games.

Launch game(POST):

{100plus url}/launchGame

Parameter	Description
100plus url	API Link (Please ask customer service for API Link)

Request Body:

Field	Type	JSON Description
account	string	Player ID
password	string	Player Password (MD5)
lang	string	zh-CN、en、th Simplified Chinese、English、Thai

Success Response:

Field	Inheritance	Type	JSON Description
status	Root	string	"success": true success Other messages: fail
clientUrl	Root	string	Lobby address https://xxxx

```
{  
  "status": "success",  
  "clientUrl": "https://xxxx"  
}
```

Error Response:

Field	Inheritance	Type	JSON Description
status	Root	string	"success": true success Other messages: fail
code	Root	string	error code
message	Root	string	error message

```
{  
  "status": "error",
```

```

"code": "lob_001",
"message": "Incorrect account or password."
}

```

2. Offering api call with IP addresses

Only allow appointed IP addresses to use Api.

Please offer every IP address that you would like set to us.

二、Request format

The combination of API Link

{100plus url}/b/{API Method}?hash={hash}&from={from}&secret={secret}

Parameter	Description
100plus url	API Link (Please ask customer service for API Link)
API Method	each API method, please refer to 三、API methods
hash	Encoding response's JSON body into HMAC SHA256 Please notice that when you use php to convert JSON into JSON String, remember to come with <code>JSON_UNESCAPED_UNICODE + JSON_UNESCAPED_SLASHES</code> 例如 <pre>\$message = json_encode(\$param, JSON_UNESCAPED_UNICODE + JSON_UNESCAPED_SLASHES);</pre> PHP example: <pre>function getHash(\$param, \$APIAuthorizationCode, \$secretkey) { \$key = \$APIAuthorizationCode . \$secretkey; \$message = json_encode(\$param, JSON_UNESCAPED_UNICODE + JSON_UNESCAPED_SLASHES); \$hash = hash_hmac('SHA256', \$message, \$key); echo (\$hash); }</pre> \$message: Request Body 的 JSON string \$key: API Authorization Code+ SecretKey (Please ask customer service for Secret key) NodeJS example:

	<pre>const crypto = require('crypto'); function getHash (body, APIAuthorizationCode, secretkey) { const message = (typeof body === 'string') ? body : JSON.stringify(body); const key = APIAuthorizationCode + secretkey; const hmac = crypto.createHmac('SHA256', key); hmac.update(message); return hmac.digest('hex'); }</pre> hash test: https://test99.100plus.me/testHash/index.html
from	Agent ID
secret	API Authorization code , please get code from the company.

hash concatenation verified :

ex. Authorization code: very, SecretKey: SecretKey

\$key: verySecretKey

\$message: {"message":"Hello World!"}

from HMAC SHA256, should get code as the following:

```
514acab8e3ff3f6b7562e8b6ef44141d21e90d7aa19002a38314ecc9fbce2553
```

API address example:

API address <http://testapi.xxx.com>

API Method [addAccount](#)

Agent account [MYBtest01](#)

Authorization code [very](#)

```
http://testapi.xxx.com/b/addAccount?hash=514acab8e3ff3f6b7562e8b6ef44141d21e90d7aa19002a38314ecc9fbce2553&from=MYBtest01&secret=very
```

Request Header:

```
Content-Type: application/json; charset=utf-8
```

Request Method: POST

Request Body: refer to API methods, JSON String

Response:

If success, callback function:

Refer to API methods, JSON String

EX:

```
{
  "status": "true"
}
```

```
}
```

If error, callback function with the following form :

Item	Field	Inheritance	Type
1	status	Root	"error":
2	code	Root	error code
3	message	Root	error message
4	action	Root	Definition of client's action : "continue": when an error message happens, no action. Continue the next round immediately. "closeWindow": when an error message happens, close the window. "retry": when an error message happens, need to retry sending Network signal again.

Ex:

```
{  
  "status": "error",  
  "code": "req_005",  
  "message": "Invalid token",  
  "action": "closeWindow",  
}
```

三、API methods

Method 1: addAccount

API Method	addAccount
API URL	{100plus url}/b/addAccount?hash={hash}&from={from}&secret={secret}
Description	addAccount
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	type	string	agent player
2	account	string	Account Agent account must be filled up. Account cannot be less than 7 digits, length <= 16 and must be a combination of numbers and letters.
3	password	string	Password Password cannot be less than 6 digits, length <= 20 and must be a combination of numbers and letters which have at least one capital letter and one lowercase letter.
4	name	string	Name
5	tel	string	Contact phone number
6	desc	string	Remark
7	setScore	string	Set score is available while add account

```
{
  "type": "agent",
  "account": "test001",
  "password": "Test!001",
  "name": "agent_001",
  "tel": "0800123123",
  "desc": "agent 001"
```

```
}
```

```
{
  "type": "player",
  "password": "Test!001",
  "name": "player_001",
  "tel": "0800123123",
  "desc": "player 001"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	account	Root	string	Player account (Total 11 numbers) Agent account (9-18 digits)

```
{
  "status": "success",
  "account": "MYtest001"
}
```

```
{
  "status": "success",
  "account": "01123123123"
}
```

Method 2: editAccount (including password)

API Method	editAccount
API URL	{100plus url}/b/editAccount?hash={hash}&from={from}&secret={secret}
Description	edit Account (including password)
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Account

2	password	string	New password, only fill up when the password needs to be changed. Password cannot be less than 6 digits, length <= 20 and must be a combination of numbers and letters which have at least one capital letter and one lowercase letter.
3	name	string	Name
4	tel	string	Contact phone number
5	desc	string	Remark

```
{
  "account": "MYtest001",
  "password": "Test!001new",
  "name": "MYtest",
  "tel": "0800123123",
  "desc": "test distributor"
}
```

```
{
  "account": "01123123123",
  "name": "01123123123",
  "tel": "0800123123",
  "desc": "player 001"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail

```
{
  "status": "success"
}
```

Method 3: setScore Topup and Withdraw

API Method	setScore
API URL	{100plus url}/b/setScore?hash={hash}&from={from}&secret={secret}
Description	Topup and Withdraw

Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Typr	JSON Description
1	account	string	Account
2	setScore	string	set score The maximum top up depends on how many scores in agent's account. The maximum withdraw depends on how many scores in player's account.

```
{
  "account": "MYtest001",
  "setScore": "20.00"
}
```

```
{
  "account": "01123123123",
  "setScore": "-20.00"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail

```
{
  "status": "success"
}
```

Method 4: getSearchAccountList

API Method	getSearchAccountList
API URL	{100plus url}/b/getSearchAccountList?hash={hash}&from={from}&secret={secret}
Description	Check user details (by level)

Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Account

```
{
  "account": "MYtest001"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	accountList	Root	json	Account list
3	Account role Type	accountList	array	agent player
4	account	Account role	string	Account
5	parentAccount	Account role	string	Parent account (upper level)
6	score	Account role	string	Score
7	entries	Account role	string	entries amount (reserve)
8	winning	Account role	string	winning amount (reserve)
9	revert	Account role	string	revert amount (reserve)
10	revertComp	Account role	string	revertComp amount (reserve)
11	name	Account role	string	Name
12	tel	Account role	string	Contact number
13	desc	Account role	string	Remark

```
{
  "status": "success",
```

```

"accountList":{
  "agent": [{
    "account": "MYtest001",
    "parentAccount": "MYBtest001",
    "score": "100.00",
    "entries": "0.00",
    "winning": "0.00",
    "revert": "0.00",
    "revertComp": "0.00",
    "name": "agent_001",
    "tel": "0800123123",
    "desc": "agent 001"
  }],
  "player": [{
    "account": "01123123123",
    "parentAccount": "MYtest001",
    "score": "20.00",
    "entries": "0.00",
    "winning": "0.00",
    "revert": "0.00",
    "revertComp": "0.00",
    "name": "player_001",
    "tel": "0800123123",
    "desc": "player 001"
  }]
}
}

```

Method 5: getAccount

API Method	getAccount
API URL	{100plus url}/b/getAccount?hash={hash}&from={from}&secret={secret}
Description	Check user's general details
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Account

```
{
  "account": "MYtest001"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	account	Root	string	Account
3	parentAccount	Root	string	parent account (upper level)
4	score	Root	string	Score
5	entries	Root	string	entries amount (reserve)
6	winning	Root	string	winning amount (reserve)
7	revert	Root	string	revert amount (reserve)
8	revertComp	Root	string	revertComp amount (reserve)
9	name	Root	string	Name
10	tel	Root	string	Contact phone number
11	desc	Root	string	Remark

```
{
  "status": "success",
  "account": "01123123123",
  "parentAccount": "MYtest001",
  "score": "20.00",
  "entries": "0.00",
  "winning": "0.00",
  "revert": "0.00",
  "revertComp": "0.00",
  "name": "player_001",
  "tel": "0800123123",
  "desc": "player 001"
}
```

Method 6: getAccountList

API Method	getAccountList
API URL	{100plus url}/b/getAccountList?hash={hash}&from={from}&secret={secret}

Description	Get agent or player listing
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	page	string	Page
2	countPerPage	string	20 records per page
3	type	string	agent player

```
{
  "page": "1",
  "countPerPage": "20",
  "type": "agent"
}
```

```
{
  "page": "1",
  "countPerPage": "20",
  "type": "player"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	type	Root	string	agent player
3	totalCount	Root	string	Total count
4	accountList	Root	json	Account List
5	account	accountList	string	User's account
6	score	accountList	string	score
7	entries	accountList	string	entries amount (reserve)
8	winning	accountList	string	winning amount (reserve)

9	revert	accountList	string	revert amount (reserve)
10	revertComp	accountList	string	revertComp amount (reserve)
11	name	accountList	string	Name
12	tel	accountList	string	Contact number
13	desc	accountList	string	Remark

```
{
  "status": "success",
  "type": "agent",
  "totalCount": "1",
  "accountList": [{
    "account": "01123123123",
    "score": "100000.00",
    "entries": "0.00",
    "winning": "0.00",
    "revert": "0.00",
    "revertComp": "0.00",
    "name": "agent_001",
    "tel": "0800123123",
    "desc": "agent1"
  }]
}
```

```
{
  "status": "success",
  "type": "player",
  "totalCount": "2",
  "accountList": [{
    "account": "01123123123",
    "score": "20.00",
    "entries": "0.00",
    "winning": "0.00",
    "revert": "0.00",
    "revertComp": "0.00",
    "name": "player_001",
    "tel": "0800123123",
    "desc": "player1"
  }, {
    "account": "01123123126",
    "score": "0.00",
    "entries": "0.00",
    "winning": "0.00",
    "revert": "0.00",
    "revertComp": "0.00",
    "name": "player_001",
  }
}
```

```

        "tel": "01123123126",
        "desc": "player2"
    }
}

```

Method 7: Check Player daily win/loss account

API Method	getWinList
API URL	{100plus url}/b/getWinList?hash={hash}&from={from}&secret={secret}
Description	Check player daily win/loss account
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Account
2	startDate	string	Start date, UTC+8, ex: 2019-11-21
3	endDate	string	End date, UTC+8, ex: 2019-11-25

```

{
    "account": "01123123123",
    "startDate": "2020-07-20",
    "endDate": "2020-07-20"
}

```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	timezone	Root	number	Timezone
3	totalWin	Root	string	Total win
4	winList	Root	string	Results
5	date	winList	string	Date
6	win	winList	string	Win results

7	win1	winList	string	win1 (reserve)
8	win2	winList	string	win2 (reserve)
9	win3	winList	string	win3 (reserve)
10	win4	winList	string	win4 (reserve)

```
{
  "status": "success",
  "timezone": 8,
  "totalWin": "-53.8",
  "winList": [
    {
      "date": "2021-12-20",
      "win": "-53.8",
      "win1": "-53.8",
      "win2": "0",
      "win3": "0",
      "win4": "0"
    }
  ]
}
```

Method 8: getWinList Agent win/loss report

API Method	getWinList
API URL	{100plus url}/b/getWinList?hash={hash}&from={from}&secret={secret}
Description	Agent win/loss report
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
------	-------	------	------------------

1	account	string	Account
2	startDate	string	Start date, UTC+8, ex: 2019-11-21
3	endDate	string	End date, UTC+8, ex: 2019-11-25

```
{
  "account": "MYtest001",
  "startDate": "2020-07-20",
  "endDate": "2020-07-21"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	timezone	Root	number	Timezone
3	totalWin	Root	string	Total win
4	winList	Root	string	Check Results
5	date	winList	string	Date
6	win	winList	string	Win results
7	win1	winList	string	Win1 (Reserve)
8	win2	winList	string	Win2 (Reserve)
9	win3	winList	string	Win3 (Reserve)
10	win4	winList	string	Win4 (Reserve)

```
{
  "status": "success",
  "timezone": 8,
  "totalWin": "-53.8",
  "winList": [
    {
      "date": "2021-12-20",
      "win": "-53.8",
    }
  ]
}
```



```

        "win1": "-53.8",
        "win2": "0",
        "win3": "0",
        "win4": "0"
    }
]
}

```

Method 9: getTotalReport

API Method	getTotalReport
API URL	{100plus url}/b/getTotalReport?hash={hash}&from={from}&secret={secret}
Description	Check player or agent general report
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Account
2	type	string	'0':Player total report '1':Agent total report
3	startDate	string	Start date, UTC+8, ex: 2019-11-21
4	endDate	string	End date, UTC+8, ex: 2019-11-25
5	page	number	page
6	countPerPage	number	countPerPage

```

{
    "account": "MYtest001",
    "type": "0",
    "startDate": "2019-11-01",
    "endDate": "2019-11-02"
    "page": 1,
    "countPerPage": 20
}

```

```
}
```

```
{  
  "account": "MYtest001",  
  "type": "1",  
  "startDate": "2019-11-01",  
  "endDate": "2019-11-02"  
  "page": 1,  
  "countPerPage": 20  
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	timezone	Root	number	Time zone
3	totalCount	Root	number	Total count
4	totalWin	Root	string	Total win
5	winList	Root	string	Check results [{},{},{}]
6	account	winList	string	Account
7	win	winList	string	Win
8	win1	winList	string	Win1 (Reserve)
9	win2	winList	string	Win2 (Reserve)
10	win3	winList	string	Win3 (Reserve)
11	win4	winList	string	Win4 (Reserve)
12	name	winList	string	Name
13	tel	winList	string	Contact phone number
14	desc	winList	string	Remark

```
{  
  "status": "success",  
  "timezone": 8,  
  "totalCount": 1,
```

```

    "totalWin": "2.8",
    "winList": [
      {
        "account": "01805187667",
        "win": "2.8",
        "win1": "2.8",
        "win2": "0",
        "win3": "0",
        "win4": "0",
        "name": "1",
        "tel": "",
        "desc": ""
      }
    ]
  }
}

```

Method 10: getScoreList

API Method	getScoreList
API URL	{100plus url}/b/getScoreList?hash={hash}&from={from}&secret={secret}
Description	Check player's score history details
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Account
2	startDate	string	Start date, UTC+0, ex: 2019-11-21
3	startTime	string	Start time, UTC+0, ex: 00:00:00
4	endDate	string	End date, UTC+0, ex: 2019-11-25

5	endTime	string	End time, UTC+0, ex: 23:59:59
6	page	string	Default page 1
7	countPerPage	string	20 records per page

```
{
  "account": "01123123123",
  "startDate": "2020-05-20",
  "startTime": "00:00:00",
  "endDate": "2020-05-20",
  "endTime": "23:59:59",
  "page": "1",
  "countPerPage": "20"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	page	Root	string	Default page 1
3	timezone	Root	number	Time zone
4	totalCount	Root	string	Total count
5	totalScore	Root	string	Total set score
6	totalComps	Root	string	Total comps (Reserve)
7	scoreList	Root	array	Topup and withdraw list
8	id	scoreList	string	Transaction ID
9	account	scoreList	string	User's account
10	assignAccount	scoreList	string	Assigned account
11	setScore	scoreList	string	Set score
12	setComps	scoreList	string	Set comps (Reserve)
13	beforeScore	scoreList	string	Before score
14	afterScore	scoreList	string	After score
15	beforeEntries	scoreList	string	Before Entries (Reserve)
16	afterEntries	scoreList	string	After Entries (Reserve)

17	beforeWinning	scoreList	string	Before Winning (Reserve)
18	afterWinning	scoreList	string	Ahter Winning (Reserve)
19	ip	scoreList	string	User's IP
20	type	scoreList	number	0: purchase 1: redeem 2: revert
21	time	scoreList	string	Time
22	amount	scoreList	number	Set positive value for amount
23	amountComps	scoreList	number	Set positive value for comps

```
{
  "status": "success",
  "page": "1",
  "timezone": 8,
  "totalCount": 2,
  "totalComps": "0.00",
  "totalScore": "4,001.00",
  "scoreList": [
    {
      "id": "71befef5",
      "account": "MYdev45670301",
      "assignAccount": "01826577674",
      "setScore": "21",
      "setComps": "0",
      "beforeScore": "4033.8",
      "afterScore": "4054.8",
      "beforeEntries": "0",
      "afterEntries": "0",
      "beforeWinning": "0",
      "afterWinning": "0",
      "ip": "192.0.0.1",
```

```

        "type": 0,
        "time": "2021-12-20 13:17:28",
        "amount": 21,
        "amountComps": 0
    },
    {
        "id": "75ee22f2",
        "account": "MYdev45670301",
        "assignAccount": "01826577674",
        "setScore": "3980",
        "setComps": "0",
        "beforeScore": "0",
        "afterScore": "3980",
        "beforeEntries": "0",
        "afterEntries": "0",
        "beforeWinning": "0",
        "afterWinning": "0",
        "ip": "192.0.0.1",
        "type": 0,
        "time": "2021-12-20 11:32:45",
        "amount": 3980,
        "amountComps": 0
    }
]
}

```

Method 11: getPlayerGameLog

API Method	getPlayerGameLog
API URL	{100plus url}/b/getPlayerGameLog?hash={hash}&from={from}&secret={secret}
説明	Check player game log, only record one week.

Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	Player account
2	page	string	Default page 1
3	countPerPage	string	20 records per page
4	startDate	string	Start date, UTC+0, ex: 2019-11-21
5	startTime	string	Start time, UTC+0, ex: 00:00:00
6	endTime	string	End time, UTC+0, ex: 23:59:59

```
{
  "account": "01123123123",
  "page": "1",
  "countPerPage": "20",
  "startDate": "2020-05-20",
  "startTime": "00:00:00",
  "endTime": "23:59:59"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail
2	balance	Root	string	Balance. Two decimal places
3	entries	Root	string	entries (reserve)
4	entriesDollar	Root	string	entries (reserve)
5	winning	Root	string	winning (reserve)
6	winningDollar	Root	string	winning (reserve)
7	revert	Root	string	revert (reserve)
8	revertComp	Root	string	revertComp (reserve)
9	page	Root	string	Default page 1

10	totalCount	Root	string	Total count
11	playerPlayLog	Root	array	game log
12	roundId	playerGameLog	string	Round ID
13	gpId	playerGameLog	string	遊戲供應商
14	game	playerGameLog	string	game name/ activity code/ blank
15	gameId	playerGameLog	string	Game ID
16	tableId	playerGameLog	string objec	Table ID
17	bet	playerGameLog	string	Bet
18	win	playerGameLog	string	Win
19	netWin	playerGameLog	string	Total Win
20	beginMoney	playerGameLog	string	Begin money
21	endMoney	playerGameLog	string	End money
22	beginEntries	playerGameLog	string	begin entries (reserve)
23	endEntries	playerGameLog	string	end entries (reserve)
24	beginWinning	playerGameLog	string	begin winning (reserve)
25	endWinning	playerGameLog	string	end winning (reserve)
26	time	playerGameLog	string	Time
27	wpTime	playerGameLog	string	Trans day, UTC+8 EX: 2020-03-09 19:15:51
28	jpWin	playerGameLog	string	jp win
29	jpClass	playerGameLog	string	win jp type 0: loss 1: jp in game 2: group jp in lobby 3: Plus jp
30	jpType	playerGameLog	string	win jp type (0-N) 0: loss 1: JP1 2: JP2 3: JP3 4: JP4 5: JP5

				 N: JPN
31	freeGame	playerGameLog	string	free game total round
32	luckyDraw	playerGameLog	string	lucky draw total count
33	bonusGame	playerGameLog	string	bonus game total round
34	event	playerGameLog	string	0: game record 1: Top up 2: Withdraw 3: Activity

```
{
  "status": "success",
  "balance": "4054.8",
  "entries": "0",
  "entriesDollar": "0",
  "winning": "0",
  "winningDollar": "0",
  "revert": "0",
  "revertComp": "0",
  "page": "1",
  "totalCount": "6",
  "playerGameLog": [
    {
      "event": "0",
      "roundId": "09a1280bc7ec4c34b7867a5948b79883",
      "gpId": "BD",
      "gameId": "1003",
      "tableId": {
        "tableId": "0"
      },
      "bet": "1.80",
      "win": "0.00",

```

```

        "netWin": "-1.80",
        "beginMoney": "4035.60",
        "endMoney": "4033.80",
        "beginWinning": "0",
        "endWinning": "0",
        "time": "2021-12-20 11:36:00",
        "wpTime": "2021-12-20 11:36:00",
        "jpWin": "0",
        "jpClass": "0",
        "jpType": "0",
        "freeGame": "0",
        "luckyDraw": "0",
        "bonusGame": "0",
        "game": "Jin Lian Pan",
        "beginEntries": "0",
        "endEntries": "0"
    }
}
]
}

```

Method 12: disable/enable Account

API Method	disableAccount
API URL	{100plus url}/b/disableAccount?hash={hash}&from={from}&secret={secret}
Description	Disable/enable account
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	account	string	account

2	disable	string	0:disable, disable appointed account with it's agents and players 1:enable, only enable appointed account
---	---------	--------	--

```
{
  "account": "MYtest001",
  "disable": "0"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
1	status	Root	string	"success": true success Other messages: fail

```
{
  "status": "success"
}
```

Method 13: getOrder

API Method	getOrder
API URL	{100plus url}/b/getOrder?hash={hash}&from={from}&secret={secret}
Description	check order, check details for topup and withdraw
Request Header	Content-Type: application/json; charset=utf-8
Request Method	POST

Request:

Item	Field	Type	JSON Description
1	id	string	Transcation ID

```
{
  "id": "abcdefgh"
}
```

Response:

Item	Field	Inheritance area	Type	JSON Description
------	-------	------------------	------	------------------

1	status	Root	string	"success": true success Other messages: fail
2	id	Root	string	Transcation ID
3	account	Root	string	Account
4	assignAccount	Root	string	assigned account
5	setScore	Root	string	set score
6	setComps	Root	string	set comps
7	beforeScore	Root	string	Before score
8	afterScore	Root	string	After score
9	beforeEntries	Root	string	before entries (reserve)
10	afterEntries	Root	string	after entries (reserve)
11	beforeWinning	Root	string	before winning (reserve)
12	afterWinning	Root	string	after winning (reserve)
13	ip	Root	string	User's IP
14	time	Root	string	Time

```
{
  "status": "success",
  "id": "8d35ea4b",
  "account": "MYag11111",
  "assignAccount": "01971335461",
  "setScore": "-2.00",
  "setComps": "0.00",
  "beforeScore": "5.00",
  "afterScore": "3.00",
  "beforeEntries": "0.00",
  "afterEntries": "0.00",
  "beforeWinning": "0.00",
  "afterWinning": "0.00",
  "ip": "192.0.0.1",
```

```
"time": "2021-12-20 10:23:15"
}
```

四、error message list

code	message
req_007	UNDER MAINTENANCE
req_015	Please contact your agent
req_026	Invalid request
manage_127	Please input type
manage_128	Please input score
manage_129	Incorrect score format
manage_101	Please input account
manage_112	Please input name
manage_113	Please input tel
manage_114	Please input desc
manage_115	Invalid password format
manage_005	Data/Account not exist
manage_003	Authority denied
manage_175	Invalid type
manage_103	Please enter start time
manage_104	Please enter start time
manage_105	Please enter end time
manage_106	Please enter end time
manage_107	startDate&startTime format wrong
manage_108	endDate&endTime format wrong
manage_109	Please input page
manage_110	Please input countPerPage

manage_141	Please input id
wp_001	redis error、db error...
wp_002	input parameter error
wp_003	insufficient amount
wp_004	invalid token
wp_005	invalid sessionId
wp_006	roundId is exist
wp_007	invalid roundId
wp_008	round is closed
wp_009	invalid transacationId
wp_010	round is not closed
wp_011	access denied