

SCI-AST v0.1

Engineering conformance view

Stage B targeted implementation-blind scientific author draft
Scientific owner: Grant Wilson

Revision r0.2 draft, 2026-08-22

Use of this view. This is the requirements-oriented view containing all six canonical formal modules. The separate scientist-facing rationale is a concise narrative. This specification defines prospective conformance obligations and falsifiers; it does not report that any implementation, schema, product, test, or observation conforms or has been validated, frozen, or made ready.

Conformance reading guide

A future conformance review should trace every **SCI-AST-REQ-NNN** to an explicit representation, application point, failure path, persisted identity, and one or more independent falsification fixtures. It must evaluate the ordered composition as a whole, not merely compare output shape. It must also show that unavailable authority remains unavailable, that no stale or default value enters a required result, and that AST does not absorb ALIGN, RTC, MAP, geometry-producer, target-selection, or downstream-use ownership.

The exact imported compatibility anchor is **SCI-ALIGN_TO_SCI-ASTv0.1/r0.1**. The stable ALIGN slot is s with identity (o, s) ; j is local storage row only; n is stable RTC output sample identity; and x/r remain exclusively the paired KID readout coordinates.

Review object	Minimum prospective evidence
Identity and parentage	Exact observation, occurrence, grid/slot, geometry, frame, center/WCS, plan/version, and lifecycle binding.
Numerical relation	Unit/topology checks, independent oracle, limiting cases, directional signs, domain and non-finite behavior.
Failure behavior	Typed unavailability, no substitute/default/stale state, and required-output propagation.
Ownership	No reconstruction or policy selection beyond AST's bounded TAN/WCS coordinate authority.
Parity	Deterministic sequential/parallel and supported real/simulation scientific identity.

Contents

1	Notation and typed identities	3
1.1	Indices and scientific objects	3
1.2	Units, topology, and indexing	4
1.3	Exact parent identities	4
1.4	Availability and cause types	4
2	Normative scientific requirements	5
2.1	Identity, input admission, and cause separation	5
2.2	Pointing support and correction	5
2.3	Detector geometry, field rotation, and composition	6

2.4	Direction, frame, topology, and projection	7
2.5	Physical center, WCS, and pixel facts	7
2.6	Validity, atomic output, products, and lifecycle	8
2.7	Map-center Jacobian and uncertainty	9
2.8	ALIGN-grid, RTC-grid, and MAP handoff	9
2.9	Provenance, availability, and verification obligations	10
3	Scientific definitions and ownership boundary	10
3.1	Bounded scientific object	10
3.2	Exact ALIGN import	11
3.3	Pointing-support modes	11
3.4	Detector geometry and field rotation	11
3.5	Ordered, noncommuting AST composition	12
3.6	Frame and product-family identities	12
3.7	Center, WCS, pixels, and request state	12
3.8	AST projection versus MAP deposition	13
3.9	ALIGN-grid and RTC-output-grid coordinates	13
3.10	Map-center Jacobian and uncertainty	13
3.11	Lifecycle, products, and claim separation	13
4	Canonical equations and typed operators	14
4.1	Directions, tangent basis, and circular topology	14
4.2	Exact displacement oracle and input normalization	14
4.3	Pointing-support realization	15
4.4	Ordered detector-direction composition	15
4.5	Gnomonic projection	15
4.6	Continuous WCS and nominal discrete pixel	16
4.7	Typed map-center Jacobian and covariance	16
4.8	Grid roles, RTC response, and delegated MAP operator	17
5	Declared assumptions and conditional adequacy	17
6	Edge cases and falsifiable predictions	18
6.1	Correction, signal independence, and causes	18
6.2	Geometry, composition, topology, and frames	19
6.3	TAN, WCS, pixels, and product availability	19
6.4	Jacobian, uncertainty, RTC, and MAP	20
6.5	Lifecycle, parity, failure, and empirical gates	21

1 Notation and typed identities

This module fixes the symbols used by both views of the SCI-AST v0.1 authority. A symbol is meaningful only together with its declared identity, unit, frame, topology, support, parent, validity, and availability. Array position or a similar name is never an identity.

1.1 Indices and scientific objects

Symbol	Meaning
o	Immutable observation identity.
d	Admitted detector/acquisition occurrence, including its observation binding; it is not merely an array row or an optional design identity.
s	Stable detector-reference slot identity on the exact admitted SCI-ALIGN grid. Its stable identity is (o, s) ; it is independent of any local storage row or numerical array position.
j	Local storage row only. It is never an external identity, an ALIGN slot, an occurrence identity, or a scientific parent.
n	Stable output-sample identity on an exact resolved SCI-RTC output grid.
$k \in \{0, 1\}$	Producer-selected pointing-support record identity.
p	Pixel identity used by a MAP-owned deposition/gridding operator.
F	Declared output frame. H denotes the declared native horizon frame; J denotes the explicitly identified equatorial J2000 frame used by Science. The letters do not supply missing frame semantics.
$\hat{\mathbf{u}}_{\text{sky}}$	Unit sky direction in a declared spherical frame. Symbols x and r are reserved exclusively for the paired KID readout coordinates.
$\mathbf{e}_\ell, \mathbf{e}_b$	Local orthonormal tangent basis toward increasing longitude at fixed latitude and increasing latitude.
$\mathbf{c}_k, \mathbf{c}_s$	Pointing-support correction and its realization at stable ALIGN slot s , expressed as declared tangent components in radians.
$\mathbf{g}_d$	Selected detector-geometry datum, including its immutable APT realization and occurrence binding.
$\mathcal{G}_\gamma$	Selected, versioned geometry and field-rotation relation with lineage γ ; it includes the declared gauge, basis, handedness, pivot state, affine limitations, time/elevation support, and uncertainty availability.
ξ_{ds}	Realized detector tangent displacement supplied by $\mathcal{G}_\gamma$ at the current aligned sample time and elevation.
$R_{F \leftarrow H, s}$	Named frame operator from the declared native horizon frame to F at stable slot s , including required time, site, epoch/equinox, EOP/refraction policy, version, and validity.
$\mathbf{w}$	Continuous tangent-plane coordinate, in arcseconds for Point/OOF/Beammap and degrees for Science.
$\mathbf{q} = (q_1, q_2)^T$	Continuous one-based FITS pixel coordinate.
(j, h)	Zero-based local storage row and column. Neither is an external identity; j is reserved for local storage row only.
$\mathcal{W}_o$	Immutable realized WCS identity for the declared observation/product plan.
θ_{ds}^A	AST coordinate on the exact ALIGN-grid parent.
θ_{dn}^{RTC}	Separately parented AST coordinate on the exact resolved RTC output grid.
G_{pi}	Estimator-specific sample-to-pixel deposition/gridding operator owned by SCI-MAP, even when materialized by AST as a delegated service.
I_{pi}^{geom}	Optional geometry-only candidate incidence, neighbor stencil, or pixel-support relation. It is not an estimator and has no numerical-contribution, normalization, conservation, MAP-support, validity, response, or covariance meaning.
$J_{\text{AST}, 0}^{(\text{out} \leftarrow \text{in})}$	Typed <code>astrometric_map_center_jacobian</code> , evaluated at the declared physical center.

1.2 Units, topology, and indexing

Angles used by the spherical equations are radians unless an equation states otherwise. Define

$$\kappa \equiv \frac{\pi}{180\,3600} \quad \text{radian per arcsecond.} \quad (1)$$

FITS/WCS pixel coordinates are one-based. In-memory rows and columns are zero-based. Internal windows and supports are half-open and retain stable identities. A longitude component must declare whether it is a coordinate increment or an on-sky tangent component.

For a period P , *shortest signed difference* means a deterministic member of $[-P/2, P/2)$, while persisted normalized longitude is a member of $[0, P)$. Exactly antipodal interpolation is unavailable unless an explicit unwrap authority selects the path and parents that selection. At a coordinate pole, the unit vector rather than longitude is the direction identity.

1.3 Exact parent identities

The parent of an ALIGN-grid detector sky direction is

$$\begin{aligned} \Pi_{ds}^{A,\text{direction}} = (&o, d, s, \text{SCI-ALIGN_TO_SCI-AST v0.1/r0.1,} \\ &\text{ALIGN plan/grid/source relation, observing state,} \\ &\text{pointing correction, } \gamma, F). \end{aligned} \quad (2)$$

It binds the stable slot (o, s) and never a local row j . The exact ALIGN profile is compatible only when its profile identity and declared version/revision preserve every required identity, semantic state, ownership boundary, and typed-availability rule. A successor must name the revision it supersedes and map every changed, removed, or newly required item explicitly; similar shape or field names do not establish compatibility.

The successive tangent, continuous-pixel, and nominal-pixel roles add only their scientific dependencies:

$$\Pi_{ds}^{A,\text{tangent}} = (\Pi_{ds}^{A,\text{direction}}, \text{selected physical center, tangent projection identity}), \quad (3)$$

$$\Pi_{ds}^{A,\text{pixel}} = (\Pi_{ds}^{A,\text{tangent}}, \mathcal{W}_o), \quad (4)$$

$$\Pi_{ds}^{A,\text{nominal pixel}} = (\Pi_{ds}^{A,\text{pixel}}, \text{rounding rule, dimensions, bounds convention}). \quad (5)$$

Consequently a WCS failure cannot erase a valid direction or tangent fact, and a nominal-pixel failure cannot erase a valid continuous pixel. A requested product family may still require atomic completion and fail that product while preserving the individual facts and exact causes.

The parent of θ_{dn}^{RTC} extends the appropriate available direction, tangent, or pixel role rather than relabeling it:

$$\begin{aligned} \Pi_{dn}^{\text{RTC}} = (&o, d, n, \Pi_{dM_n}^{A,\text{role}}, \text{RTC product/plan/grid, } M_n, t_n, \\ &\text{phase/delay, segment, decimation,} \\ &\text{support/response/correction state}). \end{aligned} \quad (6)$$

Here M_n denotes the exact RTC-selected representative stable ALIGN slot when applicable; it is never selected by AST. The selected role and every response/correction fact are part of the identity.

1.4 Availability and cause types

Every optional or unresolved quantity carries a typed state and exact reason. The vocabulary used here is:

- `available` and `available_conditional`;
- `unavailable_input`, `unavailable_authority`, and `unavailable_unsupported`; and
- `not_applicable` and `not_persisted_standard`.

A producer may refine these states, but must not collapse unavailable into numeric zero or an empty unlabeled field.

Five cause types are distinct throughout:

1. detector-occurrence identity;

2. detector signal-coordinate validity and numerical payload availability for x and r ;
3. SCI-ALIGN mapping validity;
4. SCI-AST coordinate validity; and
5. downstream use-specific eligibility under a named owner's policy.

No cause is an alias, precedence rule, or rescue rule for another.

2 Normative scientific requirements

The key word “shall” marks a falsifiable v0.1 obligation. The identifiers are stable and sequential; a successor may append requirements but shall not renumber these identities.

2.1 Identity, input admission, and cause separation

SCI-AST-REQ-001 — One-way lifecycle. Requested, effective, observation-resolved, and realized AST states shall be distinct one-way objects; a later state shall not rewrite the accepted request.

SCI-AST-REQ-002 — Observation identity. Every realized AST bundle shall bind one exact immutable observation identity and product-plan identity.

SCI-AST-REQ-003 — Detector occurrence. Every detector coordinate shall bind an exact detector/acquisition occurrence and its observation, not merely an array position or optional design identity.

SCI-AST-REQ-004 — Admitted detector binding. A detector-to-geometry binding shall be either a proven observation-local row relation or an explicit keyed relation; bare row coincidence shall be rejected.

SCI-AST-REQ-005 — Distinct detector identities. Acquisition identity, selected measured-geometry identity, and optional design identity shall remain separate and shall not be substituted for one another.

SCI-AST-REQ-006 — Immutable ALIGN transfer. AST shall consume the exact SCI-ALIGN_TO_SCI-ASTv0.1/r0.1 transfer bundle without reconstructing, reinterpreting, or independently finalizing any transferred fact. Compatibility shall preserve every required identity, semantic state, ownership boundary, and typed-availability rule; a successor shall name the revision it supersedes and map every semantic change explicitly.

SCI-AST-REQ-007 — No shaped substitute. A missing required ALIGN payload, field, record, plan, version, source relation, or parent shall not be replaced by a similarly shaped or similarly named object.

SCI-AST-REQ-008 — No clock or mapping reconstruction. AST shall not reconstruct clocks, offsets, assignment, interpolation, gap/guard, continuity synthesis, epoch, topology, or source mapping from transferred values or array shape.

SCI-AST-REQ-009 — Aligned-field typing. Every consumed boresight or current observing-state field shall declare identity, registry version, unit, unchanged producer frame, topology, operator, exact source mapping/support, origin, validity, and uncertainty availability.

SCI-AST-REQ-010 — Signal-independent coordinate availability. A finite or requested x^A or r^A numerical detector-signal payload shall not be a prerequisite for an otherwise fully defined AST coordinate.

SCI-AST-REQ-011 — Paired signal provenance. Transferred x^A/r^A producer facts shall retain their common source relation and origin/synthesis state and their coordinate-specific numerical-validity and payload states without mixing or cross-filling.

SCI-AST-REQ-012 — Five typed causes. Detector-occurrence identity, signal-coordinate validity and payload availability, ALIGN mapping validity, AST coordinate validity, and downstream use-specific eligibility shall be represented as five distinct causes with no implicit precedence, alias, or rescue rule.

2.2 Pointing support and correction

SCI-AST-REQ-013 — Producer selection. A named pointing-support producer shall select the exact correction record identities and native support; AST shall not select a calibrator, replacement, or stale record.

SCI-AST-REQ-014 — Correction semantics. Each correction shall declare vector meaning, sign, ordered basis, coordinate-increment versus tangent meaning, arcsecond unit, parent, support mode/times, covariance availability, and application count before admission.

SCI-AST-REQ-015 — Explicit sign adapter. A producer residual with the opposite action shall be converted only by one explicit, versioned adapter whose direction and single application are recorded; an ambiguous sign shall fail before state replacement.

SCI-AST-REQ-016 — Constant support. One finite correction pair shall realize the **constant** mode of Equation 16 over its declared admitted observation support.

SCI-AST-REQ-017 — Bracketed-MJD support. Two finite correction pairs with finite, strictly increasing MJD supports shall realize Equation 17 only for occurrences satisfying $0 \leq \lambda_s \leq 1$.

SCI-AST-REQ-018 — No extrapolation. AST shall neither clamp, extrapolate, choose the nearest endpoint, nor reuse another observation for an occurrence outside producer-selected correction support.

SCI-AST-REQ-019 — Legacy-span admission. Two deliberately absent support times may select only the explicit `legacy_observation_span` mode, using the exact first and last admitted aligned sample identities/times in Equation 18.

SCI-AST-REQ-020 — Ambiguous support failure. Mixed absent/present, reversed, equal, non-finite, or otherwise ambiguous two-support encodings shall fail; a one-sample span is admissible only when both endpoint corrections are exactly equal and reduce to constant mode.

SCI-AST-REQ-021 — Current-state separation. Pointing interpolation shall use the exact ALIGN-admitted time relation, while field rotation shall use the aligned current science-sample time/elevation; the latter shall not be inferred from a pointing-support record.

SCI-AST-REQ-022 — Support covariance. When support covariance is reported, AST shall apply Equation 19, retain supplied cross-covariance, and keep model, selection, calibrator, and systematic terms separate; unavailable terms shall not become zero.

2.3 Detector geometry, field rotation, and composition

SCI-AST-REQ-023 — Geometry authorities. Every selected geometry shall bind SCI-BEAM's measured relative-geometry authority and limitations plus an exact named observation-specific association or transformation authority and instance, or shall be typed unavailable.

SCI-AST-REQ-024 — Complete geometry artifact. The selected artifact shall declare raw observation-local coordinates and, where applicable, horizon-fixed/derotated coordinates; ordered basis/handedness; units; gauge; angle support; versioned rotation law; pivot state; covariance; unresolved affine modes; exact APT realization; occurrence binding; and complete lineage.

SCI-AST-REQ-025 — No inferred origin or detector. AST shall not infer APT origin equals telescope boresight, nominate a reference detector, or infer a geometry relation from design identity or row order.

SCI-AST-REQ-026 — Gauge preservation. Every geometry realization shall preserve the declared origin/recentering translation, basis, handedness, tangent versus coordinate-increment meaning, and conventional pivot parent.

SCI-AST-REQ-027 — Current field rotation. AST shall evaluate the selected versioned field-rotation relation at the current aligned occurrence time/elevation and other declared current state, within its exact support.

SCI-AST-REQ-028 — Rotation support. A geometry or rotation value outside its declared time, elevation, or domain support shall be unavailable; AST shall not clamp, extrapolate, or replace it with an unversioned field-rotation relation.

SCI-AST-REQ-029 — Affine and pivot availability. Unknown pivot covariance or unresolved translation, scale, skew, shear, or other affine terms shall retain typed unavailability/bounds and shall not be set silently to zero or identity.

SCI-AST-REQ-030 — Same-realization key. Every pointing-support observation and the science observation receiving its correction shall have identical K_γ from Equation 9, unless Requirement 031 is satisfied.

SCI-AST-REQ-031 — Authorized equivalence transform. A cross-realization transform shall name both immutable parents, prove equivalence over a declared detector/ time/elevation domain, act in the correct direction and units,

propagate covariance, cross-covariance and transform uncertainty, and record authority, version, validity, and failure behavior.

SCI-AST-REQ-032 — Incompatible transfer failure. Absent the complete transform in Requirement 031, any mismatch in K_γ shall make the dependent correction/coordinate unavailable without rewriting unrelated ALIGN or signal facts.

SCI-AST-REQ-033 — Noncommuting order. AST shall apply the eight operations in Section 3.5 in their stated order and retain each stage’s exact parents.

SCI-AST-REQ-034 — No duplicate operation. Composition history and application counts shall prevent any pointing, geometry, rotation, frame, RTC, or upstream coordinate correction from being applied twice.

SCI-AST-REQ-035 — Bounded small-angle operator. Production use of Equation 24 shall require a preregistered field/elevation/ time domain, detector population, coordinate and pixel metric, named use, tolerance owner/value, spherical oracle/version, and fail-closed behavior; AST shall invent neither a universal threshold nor an automatic fallback.

2.4 Direction, frame, topology, and projection

SCI-AST-REQ-036 — Vector direction identity. A sky direction shall be represented by a finite normalizable unit vector in one declared frame; longitude alone shall not establish direction at a pole.

SCI-AST-REQ-037 — Longitude-component type. Every longitude-like correction or offset shall declare coordinate-increment or on-sky tangent meaning and shall be normalized according to Equation 14.

SCI-AST-REQ-038 — Circular topology. Longitude differences shall use the exact $[-P/2, P/2)$ convention in Equation 11; persisted longitude shall use Equation 12 in its declared unit interval. Exactly antipodal interpolation shall be unavailable without an explicit unwrap authority.

SCI-AST-REQ-039 — Product-family frame split. Point, OOF, and Beammap shall use native AltAz tangent azimuth/elevation coordinates in arcseconds; Science shall use explicitly identified equatorial J2000 TAN coordinates in degrees.

SCI-AST-REQ-040 — Named frame transform. Every non-identity frame operation shall name source/target frames, epoch/equinox, time scale, site, model/version, EOP/refraction applicability, required inputs, validity, and uncertainty availability.

SCI-AST-REQ-041 — No frame relabeling. Missing or incompatible frame authority shall make the dependent coordinate unavailable; AST shall not equate J2000, FK5, ICRS, apparent, observed, or unrefracted frames by name or default.

SCI-AST-REQ-042 — Exact TAN domain. The forward TAN mathematical domain shall be finite $D > 0$ as in Equation 25; v0.1 shall impose no universal positive $D_{\min}$.

SCI-AST-REQ-043 — TAN invalidity. A non-finite direction, D , tangent output, or $D \leq 0$ shall produce explicit AST coordinate invalidity and no stale, center, clamped, or edge-pixel substitute.

SCI-AST-REQ-044 — Projection units and axes. Tangent outputs shall preserve the exact frame, ordered axes, topology, and units in Equations 28 and 29.

2.5 Physical center, WCS, and pixel facts

SCI-AST-REQ-045 — Center selection authority. Every WCS shall bind the exact physical center and selection/product-plan identity supplied by a named upstream target/product authority.

SCI-AST-REQ-046 — No center inference. AST automatic WCS shall never search, fit, recenter, derive a center from map bounds, or default a missing/ambiguous center; the affected WCS shall be unavailable.

SCI-AST-REQ-047 — Legacy all-zero adapter. Only the exact all-zero pattern across all six named legacy CRPIX/CRVAL/TAN controls shall adapt to internal **automatic**; the adapter and original request shall be recorded.

SCI-AST-REQ-048 — Unsupported explicit WCS. A nonzero or non-finite legacy explicit WCS control request shall fail at v0.1 admission as unsupported; numeric zero outside the exact six-field adapter shall remain an ordinary value.

SCI-AST-REQ-049 — Immutable WCS identity. The realized WCS shall bind projection, center authority, CRVAL, one-based CRPIX, CD or equivalent PC+CDELTA, axis order/sign/rotation/handedness, dimensions/bounds, units, frame/epoch, precision, product plan, and version.

SCI-AST-REQ-050 — Nonsingular continuous WCS. The CD-equivalent matrix shall be finite and nonsingular, and continuous FITS coordinates shall satisfy Equation 30; hidden transpose, flip, or axis exchange shall fail directional checks.

SCI-AST-REQ-051 — Reference-pixel policy. When the center policy is geometric array center, CRPIX shall satisfy Equation 31; any other declared policy shall still place CRVAL exactly at its one-based CRPIX and shall be recorded.

SCI-AST-REQ-052 — Index bases. FITS pixel centers and zero-based local storage indices shall obey Equation 32; local row j shall never be used as the stable ALIGN slot s or another external identity, and a consumer shall not infer one convention from the other.

SCI-AST-REQ-053 — Nominal pixel rule. When requested, the v0.1 nominal containing pixel shall obey the half-open nearest-center rule in Equation 33, or shall name a separately versioned rule with equivalent boundary tests.

SCI-AST-REQ-054 — Bounds separation. Continuous coordinate validity, nominal discrete pixel identity, in-bounds/out-of-bounds state, MAP support/coverage, and coordinate precision shall remain distinct facts.

SCI-AST-REQ-055 — Non-finite pixel behavior. A non-finite continuous coordinate or pixel shall be invalid and shall never be cast to an integer, mapped to an edge, or retained from a prior occurrence.

2.6 Validity, atomic output, products, and lifecycle

SCI-AST-REQ-056 — Dedicated AST validity. Direction, tangent, continuous-pixel, nominal-pixel, and RTC coordinate roles shall each publish a dedicated AST coordinate-validity cause and exact reason, distinct from ALIGN and downstream states.

SCI-AST-REQ-057 — Dependency-limited failure. A missing or invalid required input shall make only its dependent coordinate/product/claim unavailable unless the required product contract demands whole-product failure; WCS failure shall not erase a valid direction or tangent fact, pixel failure shall not erase a valid tangent fact, and no failure shall rewrite unrelated exact relations.

SCI-AST-REQ-058 — Role-factored atomic records. Each direction, tangent, continuous-pixel, nominal-pixel, or RTC role shall publish its value, exact layered parent, validity, uncertainty/Jacobian availability, and provenance atomically. A family contract may additionally require an atomic complete product without collapsing the individual scientific facts or causes.

SCI-AST-REQ-059 — Required-output failure. Failure to construct or write a required coordinate role, WCS, provenance, or product shall fail the required product and reduction; partial or mislabeled product output shall not be success, but valid upstream role facts and their exact causes shall remain reportable.

SCI-AST-REQ-060 — Typed optional absence. An optional, unsupported, or unavailable coordinate role, Jacobian, I_{pi}^{geom} , or G_{pi} product shall carry its exact typed state and reason and shall not masquerade as a complete role record or family product.

SCI-AST-REQ-061 — Full and mini TOD truth. Full TOD may retain coordinate arrays with compact interpretation/validity state; mini TOD shall declare coordinate arrays unavailable rather than silently omit their meaning.

SCI-AST-REQ-062 — Complete replacement. Observation resolution shall build a complete immutable candidate before atomic replacement; failure shall leave no partial or prior AST state usable by the next observation.

SCI-AST-REQ-063 — Sequential/parallel equivalence. Under the declared numerical policy, sequential and parallel schedules shall produce identical per-parent coordinates, nominal pixels, validity, counts, WCS identity, and deterministic provenance order.

SCI-AST-REQ-064 — Real/simulation parity. Supported real and simulation paths shall use the same equations, support, wrap, index, validity, and output-failure rules; simulation shall differ only through explicit origin/generator provenance.

2.7 Map-center Jacobian and uncertainty

SCI-AST-REQ-065 — Typed Jacobian schema. Every available `astrometric_map_center_jacobian` shall bind exact input domain, output codomain, direction, axis order, units, center/WCS/product parents, family, approximation domain, method/version, and included/unavailable terms.

SCI-AST-REQ-066 — Family request gate. The map-center Jacobian shall be typed unavailable until a named product family requests its exact domain, codomain, axis order, units, and direction.

SCI-AST-REQ-067 — Center-only scope. V0.1 shall evaluate the Jacobian only at the declared map center and shall not create per-sample, per-detector, per-pixel, response-grid, dense, or broadly composed astrometric response/covariance.

SCI-AST-REQ-068 — Response exclusions. The AST Jacobian shall not be labeled or used as a source-amplitude, beam, RTC temporal, MAP transfer, or point-source response.

SCI-AST-REQ-069 — Available covariance only. AST shall transform only declared available map-center covariance and cross-covariance terms using the typed realized derivative; unavailable terms shall remain unavailable.

SCI-AST-REQ-070 — No unjustified total. A total map-center covariance shall be formed only when all claimed components, cross-covariances, conditioning, and combination assumptions are declared.

SCI-AST-REQ-071 — Native tangent uncertainty. When native tangent uncertainty is the product quantity, AST shall preserve it with its frame, basis, units, parent, conditioning, and availability rather than relabel it as another domain.

SCI-AST-REQ-072 — Selection uncertainty. Discrete selection/availability uncertainty shall not be converted to Gaussian covariance without a separately approved model and parent.

2.8 ALIGN-grid, RTC-grid, and MAP handoff

SCI-AST-REQ-073 — ALIGN-grid coordinate parents. θ_{ds}^A shall bind stable slot (o, s) , never local row j . Its direction parent shall bind the exact ALIGN profile/plan/grid/source relation, detector occurrence, observing state, correction, geometry/rotation realization, and frame. Tangent, pixel, and nominal-pixel roles shall extend that identity only as specified by Equations 3–5.

SCI-AST-REQ-074 — RTC-grid coordinate parent. θ_{dn}^{RTC} shall extend the appropriate exact ALIGN-grid direction, tangent, or pixel role and bind the exact RTC product/plan/grid and all facts in Equation 6, even when it numerically equals a phase-zero representative stable ALIGN slot.

SCI-AST-REQ-075 — RTC fact completeness. The RTC parent shall include selected direction/tangent/pixel role; owner, product, plan, version, detector and stable output sample; representative stable ALIGN slot; selected output time, scale, support, uncertainty, phase/delay sign, unit, value and count; segment, decimation factor, phase and support; correction state, temporal response, and status/reasons.

SCI-AST-REQ-076 — No RTC reconstruction. AST shall not infer or reconstruct RTC plan, grid, cadence, phase, delay, time shift, representative stable ALIGN slot, selected coordinate role, segment, decimation support, response, or correction state from shape or numerical coincidence.

SCI-AST-REQ-077 — No repeated upstream operation. Constructing θ_{dn}^{RTC} shall not repeat ALIGN, reapply an RTC/upstream coordinate correction, silently reuse pre-RTC time, or promote an unavailable upstream role by borrowing a downstream WCS or pixel fact.

SCI-AST-REQ-078 — Full RTC sky-response support. A response-aware consumer shall retain the RTC temporal operator and the full contributing set of ALIGN-grid coordinates; it shall not replace them by one nominal output coordinate.

SCI-AST-REQ-079 — No angular signal filtering. AST shall not apply RTC signal coefficients directly to angular coordinates as a representation of filtered sky response, consistent with Equation 40.

SCI-AST-REQ-080 — Projection ownership. AST shall own TAN/WCS astrometric projection and continuous coordinate facts; MAP shall own sample-to-pixel deposition/ gridding selection, numerical operator, support, normalization, boundaries, conservation, response, covariance, accumulation, cropping, and reprojection.

SCI-AST-REQ-081 — Candidate versus deposition gate. AST may publish separately named I_{pi}^{geom} as geometry-only incidence, neighbor stencil, or candidate pixel support, but it shall carry no numerical-contribution meaning, normalization or conservation claim, MAP-support or validity meaning, response, or covariance authority. AST may materialize G_{pi} only for a complete exact MAP-owned request naming kernel family, parameters, support, normalization, edge/boundary behavior, conservation claim, requested artifact form, response/covariance role, plan identity, and version.

SCI-AST-REQ-082 — Delegated parentage. Every exact materialized G_{pi} shall bind the exact AST coordinate parent, WCS/pixel geometry, exact RTC output-grid parent when applicable, and exact MAP projection-plan parent as in Equation 42.

SCI-AST-REQ-083 — No ownership transfer. AST materialization shall neither select nor authorize estimator-specific G_{pi} and shall not transfer MAP scientific ownership to AST.

2.9 Provenance, availability, and verification obligations

SCI-AST-REQ-084 — Requested provenance. Requested provenance shall retain exact accepted values and source identities, pointing pairs/support, center, projection, scale, orientation, dimensions, products, and inactive expert values.

SCI-AST-REQ-085 — Effective provenance. Effective provenance shall retain activation, normalized units/topology, sign adapter, support policy, WCS request state, projection family, compatibility decisions, and their versions.

SCI-AST-REQ-086 — Observation-resolved provenance. Observation-resolved provenance shall retain observation/detector/geometry/ALIGN/RTC identities as applicable, support bracket, frame operator, field origins/validity, center authority, exact WCS/bounds, approximation record, and uncertainty availability.

SCI-AST-REQ-087 — Realized provenance. Realized provenance shall retain applied support and endpoint identities, occurrence and product counts, exclusions and reasons, coordinate extrema/wrap events, exact serialized WCS, algorithm and contract versions, unavailable terms, required-output outcomes, product links, and artifact digests.

SCI-AST-REQ-088 — Reconstructible compactness. Compact provenance may reuse stable ALIGN-grid and detector bindings, but shall reconstruct every policy decision and bind each persisted coordinate/product to its exact parents and versions.

SCI-AST-REQ-089 — Empirical gates. Small-angle, time-representation, and large-array precision adequacy shall be tested against preregistered domains, metrics, tolerances, owners, oracles, and failure rules; a required-data skip shall not be counted as a pass.

SCI-AST-REQ-090 — Claim separation. Scientific-contract authorship, implementation conformity, representation fidelity, empirical validation, observational performance, freeze, and production readiness shall remain separate claims; this Stage B draft shall assert none of the latter claims.

3 Scientific definitions and ownership boundary

3.1 Bounded scientific object

For an admitted observation, detector occurrence, and explicitly parented sample, SCI-AST realizes role-factored coordinate records

$$\begin{aligned}\mathcal{A}_{\text{direction}} &= \{\hat{\mathbf{u}}_{\text{sky}}^F, \nu_{\text{AST}}^{\text{direction}}, \mathcal{U}_{\text{direction}}, \Pi_{\text{direction}}, \mathcal{P}\}, \\ \mathcal{A}_{\text{tangent}} &= \{\mathbf{w}, \nu_{\text{AST}}^{\text{tangent}}, \mathcal{U}_{\text{tangent}}, \Pi_{\text{tangent}}, \mathcal{P}\}, \\ \mathcal{A}_{\text{pixel}} &= \{\mathbf{q}, \mathcal{W}_o, \nu_{\text{AST}}^{\text{pixel}}, \mathcal{U}_{\text{pixel}}, \Pi_{\text{pixel}}, \mathcal{P}\}.\end{aligned}\tag{7}$$

Each available role is atomic within its own dependency layer: its scientific value, dedicated validity cause, bounded uncertainty/Jacobian availability, complete parentage, and four-stage provenance are mutually consistent. Optional nominal containing-pixel and zero-based local-index facts form a further atom under an exact rounding and bounds convention. A requested product family may require an atomic complete set of roles and fail that product if one is unavailable, but a WCS or pixel failure does not erase an otherwise valid direction or tangent fact. A finite number without its role identity is not an AST coordinate.

The v0.1 estimator begins with the exact immutable SCI-ALIGN transfer bundle, producer-selected pointing support, selected observation-specific detector geometry, declared frame plan, and upstream-selected physical center/product plan. It ends with the coordinate/WCS bundle. It does not select a calibrator or center, create detector geometry, reconstruct ALIGN or RTC, filter detector signals, accumulate a map, fit a source, infer a beam or pointing solution, calibrate signal, or decide a universal use policy.

3.2 Exact ALIGN import

Here *detector-reference* means the selected detector-stream reference interface, its clock relation, and its assigned grid. It never means a reference detector. A nominal slot or nominal time alone is not proof of a physical event, physical integration, or acquired exposure.

The SCI-ALIGN input is the exact profile `SCI-ALIGN_TO_SCI-ASTv0.1/r0.1`, one immutable transfer rather than a menu. Compatibility requires this exact profile identity plus a declared compatible version/revision and preservation of every required identity, semantic state, ownership boundary, and typed-availability rule. Similar shape or field names do not establish compatibility. A successor must name the profile revision it supersedes and provide an explicit semantic mapping for every changed, removed, or newly required item. The transfer binds the detector-reference interface, grid and slot identities; native, corrected and assigned times; native source occurrences and temporal weights; residuals; field identity, units, unchanged producer frame, topology and operator; origin/synthesis/unavailability and acquired-exposure facts; interval and support identities; validity; response and uncertainty availability; and the requested, effective, observation-resolved, and realized ALIGN plan and provenance. Expanded source detail may be replaced only by an exactly reconstructible generative record supplied by ALIGN.

The paired detector-signal source relation is

$$x^A = A_{\text{ALIGN}}x^{\text{acq}}, \quad r^A = A_{\text{ALIGN}}r^{\text{acq}}, \quad (8)$$

with identical native occurrences, weights, residuals, slots, common source relation, and origin/synthesis state. Numerical validity and payload availability remain coordinate-specific. AST needs the occurrence/time/ mapping and observing-state relation, not a finite or requested x^A or r^A value. No relation crosses a Tune/readout mapping-revision boundary without a separately named authority, response, and uncertainty.

Aligned boresight, current science-sample time, current elevation, current azimuth when required, and all other declared occurrence-local observing-state fields are separate from pointing-correction records. Field rotation consumes the current aligned observing state and never infers current elevation from a bracketing correction record.

3.3 Pointing-support modes

A named producer selects the exact correction records and their native support. ALIGN supplies their admitted relation to detector-reference time. AST admits exactly one of three modes:

constant

one finite correction pair over the declared observation support;

bracketed_mjd

two finite correction pairs with finite, strictly increasing MJD support that brackets every dependent occurrence;

legacy_observation_span

two correction pairs whose two support times are both deliberately absent at the documented legacy boundary, interpolated only over the exact first and last admitted aligned sample identities/times.

Mixed, ambiguous, equal, reversed, non-finite, or unsupported time encodings do not choose a mode. AST interpolates within the selected mode and never extrapolates, clamps, chooses a nearest record, or reuses a stale observation.

3.4 Detector geometry and field rotation

SCI-BEAM owns measured relative detector geometry and its measurement limitations. An exact named Tol-Prop/TolAPT or other approved authority owns the observation-specific association/transformation and immutable APT realization. AST consumes and composes the selected artifact; it neither creates focal-plane truth nor assigns generic geometry-origin authority to SCI-CAL.

The selected artifact declares, as applicable, raw observation-local and horizon-fixed/derotated coordinates; ordered basis and handedness; tangent or coordinate-increment meaning; angular units; origin/recentering gauge; effective angle and time/elevation support; versioned field-rotation law; conventional pivot with covariance or typed unavailability; geometry covariance and cross terms; unresolved translation, scale, skew, shear, or other affine modes; exact APT content identity; occurrence binding; and full association/transformation lineage. AST does not infer that APT origin is telescope boresight, nominate a reference detector, identify rows by bare coincidence, or reduce the physical relation to a pure rotation about a known pivot.

Pointing-support observations and the science observation receiving their correction have the identical compatibility key

$$K_\gamma = (\text{APT realization, coordinate realization/gauge, geometry version, rotation law/version, pivot definition, AST composition convention}). \quad (9)$$

A mismatch is incompatible unless a separately authorized exact transform names both immutable parents, proves equivalence over a declared domain, acts in the correct direction and units, propagates covariance, cross-covariance and transform uncertainty, and records authority, version, validity, and failure behavior.

3.5 Ordered, noncommuting AST composition

The canonical order is:

1. admit the exact aligned boresight and current observing state;
2. interpret and apply the producer-selected pointing correction inside its selected native support;
3. realize the selected detector geometry and field rotation at the current aligned sample time and elevation;
4. compose the detector direction under the declared sign, basis, handedness, origin, gauge, and pivot conventions;
5. apply the declared native or named frame transform;
6. apply circular topology and the tangent-plane projection;
7. realize the exact WCS from the upstream-selected center/product plan;
8. publish continuous FITS pixels and any explicitly requested nominal discrete pixel facts with their bounds state.

These operations are generally noncommuting. They are not reordered because a zero or infinitesimal special case appears to commute. Composition history prevents any already-applied operation from being applied twice. Delegated G_{pi} materialization and any geometry-only candidate incidence are downstream of this order and are not a ninth AST composition stage.

3.6 Frame and product-family identities

Point, OOF, and Beammap use native AltAz tangent-plane azimuth/elevation coordinates in arcseconds. Science uses explicitly identified equatorial J2000 TAN coordinates in degrees. J2000, FK5, ICRS, apparent place, observed AltAz, and unrefracted AltAz are not synonyms. A transform declares source and target frames, epoch/equinox, time scale, site, version, required EOP or refraction inputs and their applicability. A missing transform is not repaired by relabeling or by inventing a default epoch.

Only the ordinary nonpolarimetric coordinate path is in scope. AST v0.1 does not interpret polarization. Optional HWPR timing may remain only as an ALIGN-parent fact; no demodulation, polarization calibration or response, or Stokes reconstruction is authorized. Raw KID readout x is not identified as Stokes I. Supported AltAz and RA/Dec simulations use the same applicable contract as real data; Galactic or other unsupported frame requests fail at admission.

3.7 Center, WCS, pixels, and request state

The physical center is selected by a named upstream target/product authority. AST realizes and encodes that exact selection. It never searches, fits, silently recenters, derives a center from bounds, or supplies a default.

The scientific WCS request states are `automatic`, `explicit`, `unsupported`, and `unavailable`. The exact all-zero pattern across the six legacy controls `crpix1`, `crpix2`, `crval1_J2000`, `crval2_J2000`, `tan_ra`, and `tan_dec` adapts only at the legacy boundary to `automatic`. Nonzero or non-finite legacy explicit requests are unsupported in v0.1 and fail at admission. Numeric zero everywhere else is an ordinary value.

An immutable WCS binds projection, physical-center authority, CRVAL, one-based CRPIX, CD or an exactly equivalent PC+CDELTA representation, axis order/sign/rotation/handedness, dimensions, bounds, output units, frame/epoch, precision, product plan, and realization version. Continuous WCS coordinate, nominal containing pixel, zero-based memory index, in-bounds state, map coverage, and coordinate precision are distinct facts.

3.8 AST projection versus MAP deposition

SCI-AST owns the TAN/WCS astrometric projection: the exact geometric relation from an admitted detector-time occurrence to detector sky direction, tangent-plane coordinate, continuous FITS pixel coordinate, WCS identity, coordinate validity and bounded astrometric uncertainty, plus an optional nominal containing pixel under a declared rule.

SCI-MAP owns the estimator-specific sample-to-pixel deposition/gridding projection and realized G_{pi} : kernel family and parameters, support, one-hot or fractional behavior, normalization, edge/boundary treatment, conservation claim, numerical contribution, and response/covariance consequences. MAP also owns accumulation, support, weighting, coaddition, cropping, reprojection, and estimator/final-map validity.

AST may publish an optional geometry-only candidate relation I_{pi}^{geom} before a complete MAP estimator request. That separately named artifact can describe incidence, a neighbor stencil, or candidate pixel support, but it has no numerical-contribution meaning, no normalization or conservation claim, no MAP support or validity meaning, and no response or covariance authority. It is never G_{pi} .

AST may materialize the exact G_{pi} only for the complete exact MAP-owned request already required by this contract. The artifact binds its AST coordinate and WCS parent, its exact RTC output-grid parent when applicable, and its MAP deposition-plan identity. Delegated materialization transfers neither policy nor scientific ownership to AST: AST determines exactly where the occurrence is; MAP determines exactly how it contributes to pixels.

3.9 ALIGN-grid and RTC-output-grid coordinates

θ_{ds}^A and θ_{dn}^{RTC} are different scientific roles. The first is parented to the exact ALIGN grid and occurrence. The second is parented additionally to the exact RTC product, resolved plan, output grid, representative occurrence, selected output time, phase/delay convention, segment, decimation factor and phase, support, conditional response, and coordinate-correction state. Even a phase-zero RTC case that numerically selects one aligned occurrence retains the RTC parent and is not relabeled.

For an RTC signal operator, the full sky-response support jointly retains the temporal operator and all contributing θ_{ds}^A . Applying temporal signal coefficients directly to circular or nonlinear angular coordinates is not the filtered sky response, and one nominal output coordinate does not replace that support.

3.10 Map-center Jacobian and uncertainty

The only v0.1 astrometric response product is the typed `astrometric_map_center_jacobian` at the declared center. An available instance binds exact domain, codomain, direction, axis order, units, center/WCS/product parents, applicable family, approximation domain, method and version, and every included or unavailable uncertainty term. It is unavailable until a product family requests the exact domain and codomain.

The object is an astrometric coordinate derivative, not source-amplitude, beam, RTC temporal, MAP transfer, or point-source response. V0.1 does not publish per-sample, per-detector, per-pixel, response-grid, dense, or broadly composed covariance. Missing inputs and cross terms remain unavailable; a total is formed only under complete declared components and combination assumptions.

3.11 Lifecycle, products, and claim separation

Requested, effective, observation-resolved, and realized state are distinct one-way objects. Observation resolution constructs a complete immutable candidate before atomic replacement of prior state. Failure or absence resets dependent optional state and leaves no stale candidate usable by another observation. Sequential and parallel scheduling, and supported real and simulation paths, preserve the same coordinate meaning and deterministic identity.

Full TOD may retain coordinate arrays with compact interpretation and validity state. Mini TOD declares coordinate arrays unavailable. A required coordinate, WCS, provenance, or output failure fails the required product and reduction;

partial or mislabeled output is not success.

This document defines a scientific contract and falsifiable predictions. It does not itself establish implementation conformity, representation fidelity, empirical adequacy, observational performance, validation, freeze, production readiness, or scientific approval of this Stage B draft.

4 Canonical equations and typed operators

The exact spherical equations in this section are mathematical identities and the independent offline oracle. The v0.1 production geometry may retain the established small-angle operator only inside the preregistered adequacy domain defined in Section 5; no automatic spherical fallback or universal numerical threshold is implied.

4.1 Directions, tangent basis, and circular topology

For longitude ℓ and latitude b in a declared frame,

$$\hat{\mathbf{u}}_{\text{sky}}(\ell, b) = \begin{bmatrix} \cos b \cos \ell \\ \cos b \sin \ell \\ \sin b \end{bmatrix}, \quad \mathbf{e}_\ell = \begin{bmatrix} -\sin \ell \\ \cos \ell \\ 0 \end{bmatrix}, \quad \mathbf{e}_b = \begin{bmatrix} -\sin b \cos \ell \\ -\sin b \sin \ell \\ \cos b \end{bmatrix}. \quad (10)$$

Away from a coordinate pole, $\mathbf{e}_\ell$ and $\mathbf{e}_b$ are unit tangent vectors toward increasing longitude at fixed latitude and increasing latitude. The direction remains $\hat{\mathbf{u}}_{\text{sky}}$ at a pole. The symbols x and r are reserved for paired KID readout coordinates and never denote sky vectors or TAN axes.

For period P ,

$$\text{wrap}_P(\theta) = \theta - P \left\lfloor \frac{\theta + P/2}{P} \right\rfloor \in [-P/2, P/2), \quad (11)$$

$$\text{norm}_P(\theta) = \theta - P \left\lfloor \frac{\theta}{P} \right\rfloor \in [0, P). \quad (12)$$

Longitude and azimuth use $P = 2\pi$. The half-open endpoint convention is deterministic. Exactly antipodal samples have no unique shortest interpolation path; interpolation is unavailable unless an explicit unwrap authority names and parents the selected path.

4.2 Exact displacement oracle and input normalization

For tangent components $\boldsymbol{\eta} = (\eta_\ell, \eta_b)^\text{T}$, let $\rho = \|\boldsymbol{\eta}\|$ and, for $\rho > 0$, $\hat{\mathbf{v}} = (\eta_\ell \mathbf{e}_\ell + \eta_b \mathbf{e}_b)/\rho$. The exact spherical displacement oracle is

$$\text{Exp}_{\hat{\mathbf{u}}_{\text{sky}}}(\boldsymbol{\eta}) = \begin{cases} \cos \rho \hat{\mathbf{u}}_{\text{sky}} + \sin \rho \hat{\mathbf{v}}, & \rho > 0, \\ \hat{\mathbf{u}}_{\text{sky}}, & \rho = 0. \end{cases} \quad (13)$$

Renormalization may remove roundoff only; it may not hide invalid input.

An input longitude-like component is normalized at the boundary as

$$\eta_\ell = \begin{cases} \cos b \Delta\ell, & \text{declared coordinate increment,} \\ \Delta\ell_{\text{tangent}}, & \text{declared on-sky tangent component.} \end{cases} \quad (14)$$

The declared correction pair $\mathbf{a}_k$ in arcseconds becomes

$$\mathbf{c}_k = \kappa \mathbf{a}_k. \quad (15)$$

Positive components move toward the increasing declared tangent-basis axes. An upstream residual requiring the opposite action needs one explicit, parented sign adapter and an application count of one.

4.3 Pointing-support realization

One finite pair is constant:

$$\mathbf{c}_s = \mathbf{c}_0. \quad (16)$$

For two finite, strictly increasing MJD supports $m_0 < m_1$ and aligned stable-slot occurrence time m_s ,

$$\lambda_s = \frac{m_s - m_0}{m_1 - m_0}, \quad \mathbf{c}_s = (1 - \lambda_s)\mathbf{c}_0 + \lambda_s\mathbf{c}_1, \quad 0 \leq \lambda_s \leq 1. \quad (17)$$

For explicit legacy observation-span mode, where t_- and t_+ are the times of the exact first and last admitted aligned sample identities,

$$\lambda_s^{\text{span}} = \frac{t_s - t_-}{t_+ - t_-}, \quad \mathbf{c}_s = (1 - \lambda_s^{\text{span}})\mathbf{c}_0 + \lambda_s^{\text{span}}\mathbf{c}_1, \quad t_- \leq t_s \leq t_+. \quad (18)$$

A one-sample span is defined only when the endpoint corrections are exactly equal, in which case Equation 16 applies. When the two-support covariance is available, stack $\mathbf{c}_* = (\mathbf{c}_0^T, \mathbf{c}_1^T)^T$ and define

$$\mathbf{H}_s = \begin{bmatrix} (1 - \lambda_s)\mathbf{I}_2 & \lambda_s\mathbf{I}_2 \end{bmatrix}, \quad \mathbf{C}_{c,s}^{\text{formal}} = \mathbf{H}_s \mathbf{C}_{c,*} \mathbf{H}_s^T. \quad (19)$$

Cross-covariance is retained when supplied. Model, selection, and systematic terms remain separately labeled.

4.4 Ordered detector-direction composition

Let $\hat{\mathbf{u}}_{\text{sky},s}^B$ be the exact aligned boresight in the declared native horizon frame. The spherical oracle for the first two geometric stages is

$$\hat{\mathbf{u}}_{\text{sky},s}^{H,c} = \text{Exp}_{\hat{\mathbf{u}}_{\text{sky},s}}^{\wedge_B}(\mathbf{c}_s), \quad (20)$$

$$\boldsymbol{\xi}_{ds} = \mathcal{G}_\gamma(\mathbf{g}_d; t_s, E_s, \text{declared occurrence-local state}), \quad (21)$$

$$\hat{\mathbf{u}}_{\text{sky},ds}^H = \mathcal{C}_\gamma(\hat{\mathbf{u}}_{\text{sky},s}^{H,c}, \boldsymbol{\xi}_{ds}), \quad (22)$$

$$\hat{\mathbf{u}}_{\text{sky},ds}^F = \mathbf{R}_{F \leftarrow H,s}(\hat{\mathbf{u}}_{\text{sky},ds}^H). \quad (23)$$

$\mathcal{C}_\gamma$ is the selected composition relation and carries the same gauge, pivot, basis, handedness, affine limitations, and lineage as $\mathcal{G}_\gamma$. In the admitted pure tangent-displacement limiting case, $\mathcal{C}_\gamma(\hat{\mathbf{u}}_{\text{sky}}, \boldsymbol{\xi}) = \text{Exp}_{\hat{\mathbf{u}}_{\text{sky}}}^{\wedge}(\boldsymbol{\xi})$; the contract does not presume that this limiting case describes every selected artifact.

The established production small-angle relation may be written

$$\boldsymbol{\eta}_{ds}^{\text{prod}} \simeq \mathbf{c}_s + \mathbf{B}_{ds} \mathbf{f}_d, \quad (24)$$

only when $\mathbf{B}_{ds}$ is the declared selected geometry/rotation mapping and the preregistered adequacy record admits the exact occurrence, detector, product use, and error metric. Equation 13 and the full selected geometry relation are the offline oracle for that record.

4.5 Gnomonic projection

For output direction $\hat{\mathbf{u}}_{\text{sky}}$, center $\hat{\mathbf{u}}_{\text{sky},0}$, and center basis $(\mathbf{e}_1, \mathbf{e}_2)$,

$$D = \hat{\mathbf{u}}_{\text{sky}} \cdot \hat{\mathbf{u}}_{\text{sky},0}, \quad \zeta_1 = \frac{\hat{\mathbf{u}}_{\text{sky}} \cdot \mathbf{e}_1}{D}, \quad \zeta_2 = \frac{\hat{\mathbf{u}}_{\text{sky}} \cdot \mathbf{e}_2}{D}, \quad D > 0. \quad (25)$$

The inverse is

$$\hat{\mathbf{u}}_{\text{sky}} = \frac{\hat{\mathbf{u}}_{\text{sky},0} + \zeta_1 \mathbf{e}_1 + \zeta_2 \mathbf{e}_2}{\sqrt{1 + \zeta_1^2 + \zeta_2^2}}. \quad (26)$$

In longitude and latitude, with $\Delta\ell = \text{wrap}_{2\pi}(\ell - \ell_0)$,

$$\begin{aligned} D &= \sin b_0 \sin b + \cos b_0 \cos b \cos \Delta\ell, \\ \zeta_1 &= \frac{\cos b \sin \Delta\ell}{D}, \quad \zeta_2 = \frac{\cos b_0 \sin b - \sin b_0 \cos b \cos \Delta\ell}{D}. \end{aligned} \quad (27)$$

The mathematical domain is finite $D > 0$. There is no universal positive $D_{\min}$. A separately preregistered footprint bound may be tighter, but does not alter the mathematical domain. Non-finite input or output and $D \leq 0$ are coordinate invalidity, never a center or edge pixel.

For Point/OOF/Beammap,

$$\mathbf{w} = 206264.806247 (\zeta_1, \zeta_2)^T \text{ arcsec}, \quad (28)$$

with ordered AZOFFSET/ELOFFSET identity. For Science,

$$\mathbf{w} = \frac{180}{\pi} (\zeta_1, \zeta_2)^T \text{ degree}, \quad (29)$$

with explicitly identified RA—TAN/DEC—TAN axes in the declared equatorial J2000 frame.

4.6 Continuous WCS and nominal discrete pixel

Let $\mathbf{q}_0 = \text{CRPIX}$ be one-based and let $\mathbf{M}$ be the declared nonsingular CD matrix in plane-units per pixel:

$$\mathbf{w} = \mathbf{M}(\mathbf{q} - \mathbf{q}_0), \quad \mathbf{q} = \mathbf{q}_0 + \mathbf{M}^{-1}\mathbf{w}. \quad (30)$$

When the product plan places the projection center at the geometric array center for N_1 columns and N_2 rows,

$$\text{CRPIX}_1 = \frac{N_1 + 1}{2}, \quad \text{CRPIX}_2 = \frac{N_2 + 1}{2}. \quad (31)$$

Even dimensions therefore have half-integer reference pixels. A different declared reference-pixel policy remains valid only when Equation 30 places CRVAL there exactly and provenance records that policy.

At pixel centers,

$$q_1 = h + 1, \quad q_2 = j + 1. \quad (32)$$

The v0.1 half-open nearest-center assignment is

$$h = \lfloor q_1 - \tfrac{1}{2} \rfloor, \quad j = \lfloor q_2 - \tfrac{1}{2} \rfloor, \quad 0 \leq h < N_1, \quad 0 \leq j < N_2. \quad (33)$$

Another rule is a separately identified operator with equivalent boundary tests; it is never inferred from integer casting.

4.7 Typed map-center Jacobian and covariance

For Equation 25, let $a = \hat{\mathbf{u}}_{\text{sky}} \cdot \mathbf{e}_1$ and $b = \hat{\mathbf{u}}_{\text{sky}} \cdot \mathbf{e}_2$. The direction-to-plane derivative is

$$\mathbf{J}_{w \leftarrow u_{\text{sky}}} = \begin{bmatrix} (D\mathbf{e}_1^T - a\hat{\mathbf{u}}_{\text{sky},0}^T)/D^2 \\ (D\mathbf{e}_2^T - b\hat{\mathbf{u}}_{\text{sky},0}^T)/D^2 \end{bmatrix}, \quad (34)$$

followed by the declared unit conversion. For a family-requested typed input $\mathbf{c}_{\text{in}}$ and output $\mathbf{c}_{\text{out}}$,

$$\mathbf{J}_{\text{AST},0}^{(\text{out} \leftarrow \text{in})} = \left. \frac{\partial \mathbf{c}_{\text{out}}}{\partial \mathbf{c}_{\text{in}}} \right|_{\hat{\mathbf{u}}_{\text{sky},0}, \mathcal{W}_o}. \quad (35)$$

Its direction, axes, units, family, center/WCS parent, approximation domain, method, and included or unavailable terms are part of the type. For an available map-center covariance term k ,

$$\mathbf{C}_{\text{out}}^{(k)} = \mathbf{J}_{\text{out} \leftarrow k} \mathbf{C}_k \mathbf{J}_{\text{out} \leftarrow k}^T. \quad (36)$$

Supplied cross terms are propagated. No total is reported unless all claimed components, cross-covariances, and combination assumptions are declared.

4.8 Grid roles, RTC response, and delegated MAP operator

On the ALIGN grid and the RTC output grid, respectively,

$$\theta_{ds}^A = \mathcal{A}_{\text{AST}}(d, s; \Pi_{ds}^{A, \text{role}}), \quad (37)$$

$$\theta_{dn}^{\text{RTC}} = \mathcal{A}_{\text{AST}}(d, n; \Pi_{dn}^{\text{RTC}}). \quad (38)$$

For an RTC signal relation

$$y_{dn} = \sum_s L_{ns} x_{ds}, \quad (39)$$

the sky response retains L_{ns} and the full set $\{\theta_{ds}^A\}$ jointly. In general,

$$\text{sky-response}(L_{ns}, \{\theta_{ds}^A\}) \neq \sum_s L_{ns} \theta_{ds}^A. \quad (40)$$

Before a complete MAP estimator request, AST may publish only the separately named geometry candidate

$$I_{pi}^{\text{geom}} = \mathcal{I}_{\text{AST}}(\Pi_i^{A, \text{pixel}}, \mathcal{W}_o, [\Pi_i^{\text{RTC}}]_{\text{if applicable}}), \quad (41)$$

which denotes incidence, a neighbor stencil, or candidate pixel support only. It has no numerical-contribution meaning, normalization or conservation claim, MAP-support or validity meaning, response, or covariance authority.

When and only when a complete exact MAP plan Π^{MAP} requests it, a delegated G_{pi} materialization has the typed parent relation

$$G_{pi}^{\text{materialized}} = \mathcal{M}_{\text{AST}}\left(\Pi_i^{\text{AST}}, \mathcal{W}_o, [\Pi_i^{\text{RTC}}]_{\text{if applicable}}, \Pi_{\text{kernel/support/boundary/normalization}}^{\text{MAP}}\right). \quad (42)$$

$\mathcal{M}_{\text{AST}}$ denotes a materialization service, not scientific selection or ownership of G_{pi} . Thus AST determines exactly where the occurrence is, while MAP determines exactly how it contributes to pixels.

5 Declared assumptions and conditional adequacy

These are bounded assumptions of the v0.1 scientific object, not achieved claims. If a required assumption is false, unsupported, or unavailable, the dependent output is unavailable or fails closed as stated by the requirements.

SCI-AST-ASM-001 — Authoritative upstream selection. The exact SCI-ALIGN_TO_SCI-ASTv0.1/r0.1 bundle, pointing-support record selection, physical-center selection, frame plan, RTC plan when used, and MAP projection plan when used are supplied by their named authorities. AST validates and consumes these selections but does not create them. The exact per-family center owner remains open under AST-OWNER-Q002.

SCI-AST-ASM-002 — Exact aligned field registry. Every required boresight and current observing-state field arrives with stable identity, registry version, unit, unchanged producer frame, topology, operator, source relation, support, origin, validity, and uncertainty availability. The exact registry and composition-history semantics remain open under AST-OWNER-Q001; outputs needing an unresolved field are unavailable rather than inferred.

SCI-AST-ASM-003 — Immutable selected geometry. A selected geometry instance is bound to one immutable APT realization and complete approved lineage. The exact producer, association authority/schema, and cross-realization transform remain open under AST-OWNER-Q006; an unresolved instance cannot be used unconditionally.

SCI-AST-ASM-004 — No hidden commutation. The ordered composition in Section 3.5 is physical authority. Zero-offset or infinitesimal cases are limiting cases only and do not authorize reordering, double application, or removal of lineage.

SCI-AST-ASM-005 — Bounded small-angle production. The established small-angle production relation is admissible only under a preregistered record naming the field/elevation/time domain, detector population, coordinate and pixel error metrics, required product use, tolerance owner and value, and fail-closed behavior. Exact spherical composition is the independent offline oracle. The owner and quantitative record remain open under AST-OWNER-Q004; no universal threshold or automatic fallback is created here.

SCI-AST-ASM-006 — Time adequacy. A time representation is adequate only when a preregistered angular-error analysis bounds the induced astrometric error for the named use. Unused digits and an arbitrary microsecond target are not authority. The quantitative time bound remains unavailable under AST-OWNER-Q004.

SCI-AST-ASM-007 — Large-array precision adequacy. Compact WCS authorities and fitted/catalog coordinates use adequate high precision. A representation for large coordinate arrays is admitted only after a preregistered empirical coordinate/pixel adequacy bound for the required product use. The bound remains unavailable under AST-OWNER-Q004.

SCI-AST-ASM-008 — Named frame semantics. A requested frame transform is available only with declared source/target identities, epoch/equinox, time scale, site, model/version, input availability, and EOP/refraction applicability. Ordinary native AltAz paths do not acquire unnecessary EOP/refraction requirements, and missing equatorial authority is not repaired by relabeling.

SCI-AST-ASM-009 — TAN operating support. The mathematical forward TAN domain is finite $D > 0$. A product may impose a tighter footprint-derived operating support only through a separately preregistered authority, metric, and failure rule. This package invents no positive universal $D_{\min}$.

SCI-AST-ASM-010 — Conditional uncertainty. Only explicitly available map-center input covariance and cross-covariance terms are propagated. The producer, conditioning, and per-family availability of those terms remain open under AST-OWNER-Q003. Unavailable is not zero.

SCI-AST-ASM-011 — Typed Jacobian request. A map-center Jacobian exists as an available product only after a named family requests exact input/output domains, axis order, units, and direction. Those family-specific requests remain open under AST-OWNER-Q007.

SCI-AST-ASM-012 — RTC role is explicit. RTC-grid coordinates or response-aware use exist only for named families with an exact RTC profile instance. The requesting families and profile owner remain open under AST-OWNER-Q008. Missing RTC parent facts do not alter unrelated ALIGN-grid coordinate availability.

SCI-AST-ASM-013 — MAP-specific retained-grid policy is external. The deferred MAP-003 retained-WCS/crop/dual-axis disposition under AST-OWNER-Q005 is not supplied by this v0.1 authority. Any later requirement that changes AST admission or parentage requires a named amendment; until then, MAP cropping and retained-grid policy remain MAP-owned.

SCI-AST-ASM-014 — Ordinary nonpolarimetric coordinate scope. Only the ordinary nonpolarimetric coordinate path is admitted. AST does not interpret polarization. Optional HWPR timing may remain only as an ALIGN-parent fact; no demodulation, polarization calibration or response, or Stokes reconstruction is authorized. In particular, raw KID readout x is not identified as Stokes I. Galactic simulation, general reprojection, source fitting, calibration, photometry, beam inference, and map accumulation are outside this authority.

SCI-AST-ASM-015 — No achieved-status inference. Compilation, document verification, a plausible image, a downstream fit, or existing operational use cannot establish scientific approval, implementation conformity, observational performance, validation, freeze, or production readiness.

6 Edge cases and falsifiable predictions

Each prediction states a future truth condition for an implementation or representation claiming this contract. No prediction is reported as tested or satisfied here. Required-data absence is not a pass. A successor may append identifiers but shall not renumber these.

6.1 Correction, signal independence, and causes

SCI-AST-PRED-001. Zero correction and zero admitted detector displacement return the declared boresight to numerical roundoff; if that boresight is the selected TAN center, the continuous tangent coordinate is zero and the FITS coordinate is CRPIX.

SCI-AST-PRED-002. Injecting +1 arcsecond separately in each declared tangent correction component produces positive displacement along the matching basis axis with magnitude κ in the small-offset oracle.

SCI-AST-PRED-003. A declared longitude coordinate increment and an equal-valued on-sky tangent component differ by the $\cos b$ factor in Equation 14; conflating them produces a latitude/elevation-dependent error.

SCI-AST-PRED-004. For bracketed MJD support, the two endpoints and midpoint reproduce c_0 , $(c_0 + c_1)/2$, and c_1 , and any affine correction ramp is reproduced.

SCI-AST-PRED-005. Occurrences immediately outside either MJD endpoint, or fixtures with equal, reversed, mixed, or non-finite support, produce no clamped, nearest, extrapolated, or stale correction output.

SCI-AST-PRED-006. Explicit legacy observation-span mode reproduces its exact first and last admitted occurrence corrections and affine midpoint, records both endpoint identities, and never identifies itself as bracketed MJD.

SCI-AST-PRED-007. A one-sample legacy span is admitted only when both endpoint corrections are exactly equal; unequal endpoints make the dependent output unavailable.

SCI-AST-PRED-008. A correlated two-support covariance fixture reproduces Equation 19; a fully shared systematic does not artificially shrink at the midpoint.

SCI-AST-PRED-009. With exact occurrence/time/mapping, geometry, observing state, correction, frame, and product inputs, toggling a numerical x or r payload between finite, invalid, non-finite, unavailable, and not requested does not by itself change the AST coordinate.

SCI-AST-PRED-010. Fixtures varying each of the five cause types independently retain five independently reportable states: no signal or AST state rescues an invalid ALIGN mapping, and no coordinate fact alone authorizes downstream eligibility.

6.2 Geometry, composition, topology, and frames

SCI-AST-PRED-011. A finite non-collinear pointing correction and detector displacement match the declared ordered composition and differ from reversed composition by the expected nonzero higher-order term.

SCI-AST-PRED-012. Permuting geometry rows leaves every detector coordinate unchanged when an admitted keyed binding is used; a proven observation-local row mode is stable only inside its declared binding, while bare coincidence, duplicate keys, or missing keys fail.

SCI-AST-PRED-013. Changing any component of K_γ between pointing support and science observation makes the dependent correction/coordinate unavailable when no authorized equivalence transform is supplied.

SCI-AST-PRED-014. A supplied cross-realization transform is accepted only when both immutable parents, direction/units, domain, covariance/cross-covariance, transform uncertainty, authority, version, and failure behavior are complete; removing any required item makes the dependent transfer unavailable.

SCI-AST-PRED-015. Field rotation responds to the current aligned science-occurrence time/elevation fixture and is invariant to an unrelated elevation stored on a bracketing pointing record.

SCI-AST-PRED-016. A geometry angle or rotation-law query just outside its declared time/elevation support is unavailable and is neither clamped nor replaced by an unversioned parallactic-angle calculation.

SCI-AST-PRED-017. Fixtures with unavailable pivot covariance or unresolved affine translation, scale, skew, or shear retain those typed limitations; their outputs do not equal a silently zeroed or identity-modeled uncertainty claim.

SCI-AST-PRED-018. Directions and centers straddling $0/2\pi$ use the short signed separation, yield a continuous tangent projection, and persist normalized longitude under the exact $[-P/2, P/2)$ convention. An exactly antipodal interpolation fixture is unavailable unless an explicit unwrap authority is supplied.

SCI-AST-PRED-019. Near either coordinate pole, vector direction and in-domain round-trip remain finite, while an ambiguous longitude-only input does not establish a coordinate.

SCI-AST-PRED-020. Identical physical directions requested under Point/OOF/Beammap and Science roles produce their declared AltAz-arcsecond and equatorial-J2000- degree identities; relabeling one as the other without a named transform fails.

6.3 TAN, WCS, pixels, and product availability

SCI-AST-PRED-021. The selected TAN center maps exactly to $(0, 0)$; finite $D > 0$ is in the mathematical domain, while $D \leq 0$ or non-finite D /output is invalid. No fixture is rejected solely by an invented universal positive $D_{\min}$.

SCI-AST-PRED-022. Random preregistered in-domain unit directions in both admitted frame families satisfy inverse-TAN(forward-TAN($\hat{\mathbf{u}}_{\text{sky}}$)) = $\hat{\mathbf{u}}_{\text{sky}}$ to the preregistered angular tolerance.

SCI-AST-PRED-023. The exact upstream-selected physical center, and no center inferred from bounds, source fit, coverage, or array contents, maps to tangent zero and the realized CRPIX.

SCI-AST-PRED-024. Only the exact six-field legacy all-zero pattern enters `automatic`; changing one field to a nonzero or non-finite value fails as unsupported explicit control, while numeric zero in unrelated data remains numeric.

SCI-AST-PRED-025. Removing or making ambiguous the selected center makes the affected automatic WCS unavailable without searching, fitting, recentering, or reusing a prior center; an otherwise valid detector sky direction remains available.

SCI-AST-PRED-026. Positive tangent-axis perturbations move continuous pixels in the directions predicted by the realized CD-equivalent matrix; transpose, hidden flip, and swapped-axis fixtures fail.

SCI-AST-PRED-027. Odd and even geometric-center policies satisfy Equation 31, including half-integer CRPIX for even dimensions; every different declared policy still maps CRVAL exactly to its CRPIX.

SCI-AST-PRED-028. Pixel centers satisfy Equation 32; the half-open nearest-center rule includes its lower edge, excludes its upper edge, and does not depend on language-specific integer casting.

SCI-AST-PRED-029. Subpixel dithers move the continuous WCS coordinate continuously and change the nominal discrete pixel only at the declared boundary; neither event changes MAP coverage or claims coordinate precision.

SCI-AST-PRED-030. Missing, NaN, or infinite required direction, tangent, WCS, or continuous-pixel inputs produce explicit invalidity/unavailability and never a cast integer, edge pixel, center, or stale coordinate. Failure at a downstream role leaves valid upstream direction or tangent facts and their causes intact.

SCI-AST-PRED-031. A full-TOD request may retain coordinate arrays with compact interpretation state, whereas an otherwise equivalent mini-TOD request reports those arrays unavailable rather than silently omitting their identity.

6.4 Jacobian, uncertainty, RTC, and MAP

SCI-AST-PRED-032. For every claimed available family/domain pair, the typed map-center Jacobian agrees with a preregistered symmetric finite-difference or validated automatic/analytic derivative oracle, including unit, axis-sign, center, pixel, and near-wrap fixtures.

SCI-AST-PRED-033. Small correlated map-center input draws reproduce Equation 36 in the declared linear domain, including the supplied cross term; removing a term changes its state to unavailable rather than numeric zero.

SCI-AST-PRED-034. Without a named family and exact input/output domains, the `astrometric_map_center_jacobian` is unavailable and is not inferred from shape, WCS, or consumer name.

SCI-AST-PRED-035. An ordinary phase-zero RTC fixture may make θ_{dn}^{RTC} numerically equal to one θ_{ds}^A , but the two outputs retain different exact parent identities and roles. Permuting local storage rows j does not change the stable (o, s) identity.

SCI-AST-PRED-036. Removing any required RTC plan, grid, occurrence, time, phase/delay, segment, decimation, support, response, or correction fact makes only the dependent RTC-grid coordinate, response composition, or delegated G_{pi} unavailable; unrelated ALIGN-grid direction, tangent, and available pixel roles remain unchanged.

SCI-AST-PRED-037. For a temporal operator with negative coefficients or coordinates crossing circular topology, direct $\sum_s L_{ns} \theta_{ds}^A$ differs from the sky response obtained by retaining the operator and its full coordinate support, falsifying angular signal filtering.

SCI-AST-PRED-038. Changing the RTC output-grid parent or MAP deposition-plan parent while holding numerical coordinates and array shape fixed changes the identity of every exact delegated G_{pi} artifact; a separately named I_{pi}^{geom} remains a non-estimator candidate and similar shape is not compatibility.

SCI-AST-PRED-039. AST refuses exact delegated G_{pi} materialization when the MAP kernel, support, normalization, boundary, conservation, artifact form, plan/version, or response/covariance role is missing or ambiguous. Any geometry-only output then remains labeled I_{pi}^{geom} and makes none of those MAP claims.

SCI-AST-PRED-040. Two MAP-owned deposition plans using the same AST continuous coordinates may realize different valid G_{pi} operators without changing the underlying AST coordinate/WCS identity, demonstrating the ownership boundary.

6.5 Lifecycle, parity, failure, and empirical gates

SCI-AST-PRED-041. A valid–missing–valid observation sequence with different correction, geometry, center, WCS, and RTC modes shows no inherited prior state; recovery after failure constructs a clean candidate.

SCI-AST-PRED-042. Permuted scheduling and thread counts preserve per-parent coordinates, pixels, validity, counts, serialized WCS, and deterministic provenance order under the declared numerical policy.

SCI-AST-PRED-043. Identical supported abstract inputs through real and simulation paths produce the same scientific coordinate and validity; only declared origin/generator/version/seed provenance differs.

SCI-AST-PRED-044. Injected required coordinate, WCS, provenance, and product-write failures each produce unsuccessful required-product/reduction state and no apparently complete mislabeled artifact.

SCI-AST-PRED-045. Within a preregistered small-angle domain, the production operator’s coordinate and pixel errors relative to the exact spherical oracle satisfy the named tolerance; outside the domain or without the record, the dependent adequacy claim/output fails closed rather than switching algorithms silently.

SCI-AST-PRED-046. Preregistered time-quantization and large-array representation perturbations satisfy their named angular/pixel error bounds for the required use; a missing owner, metric, domain, tolerance, or failure rule cannot yield an achieved-adequacy claim.

SCI-AST-PRED-047. Unsupported Galactic/other-frame simulation or polarization-science requests fail at admission and do not emerge as relabeled supported coordinates. An optional HWPR timing parent authorizes no AST demodulation, polarization calibration/response, or Stokes reconstruction, and raw KID readout x is never relabeled Stokes I.

SCI-AST-PRED-048. A downstream source, pointing, OOF, or Beammap fit may succeed or fail without changing the already realized AST coordinate identity or retroactively establishing AST validity.

SCI-AST-PRED-049. For every persisted coordinate, compact provenance reconstructs the requested, effective, observation-resolved, and realized policy; changing any parent or version changes the reconstructed identity rather than silently aliasing it.

SCI-AST-PRED-050. A compilation, clean render, or plausible coordinate image alone does not change the explicit states of scientific approval, implementation conformity, empirical validation, freeze, or production readiness.

Conformance disposition

Every requirement remains prospective until separately authorized evidence binds it to an exact implementation and representation. Open owner questions are not implementation choices: they keep only their dependent outputs or quantitative claims unavailable. Passing a subset of predictions cannot establish scientific approval, overall conformity, validation, freeze, or production readiness.