
SCI-POINT

Scientific Rationale and Contract

Scientific contract v0.1 Document revision r0.1

Conditional generic Stage B contract

Authority status. This document establishes a conditional scientific meaning for known-source per-array Pointing fits. The numerical compatibility method, formal-error method, full-map-RMS method, exact numerical parent-route instances, registered named-use profiles, fixed/full procedure response, and observational bias/accuracy remain unavailable where stated. Implementation conformity has not been assessed under this contract.

Scientific owner	Grant Wilson
Source authority	Exact owner-approved SCI-POINT Stage A r0.3 author packet
Base operator	POINT-FIT/ELLIPTICAL-GAUSSIAN-COMPATIBILITY@1
Primary result	Per-array AltAz tangent-plane source displacement
Contract date	2026-09-02

Reader's summary

Input: one exact observation-local per-array MAP, JINC, FLT-FIXED, or FLT-MATCHED signal product; exact parent state and optional terminal FRUIT ancestry; a valid expected source position; an exact AltAz tangent boundary; and requested method/use state.

Output when dependencies are available: a six-role zero-background elliptical-Gaussian fit and the measured displacement $\Delta_{\text{POINT}} = \hat{\mu} - \mu_{\text{expected}}$ in arcseconds, with identities, states, support, uncertainty availability, diagnostics, and named-use facts.

Current numerical status: unavailable. The contract does not invent the missing numerical methods.

The science is deliberately narrow. A known, isolated, bright Pointing source is fitted on one specified array map. The useful measurement is where the processed source appears relative to an authoritative expected position in a declared physical tangent basis. Search centers and peaks help an algorithm find a candidate; they do not define the astrometric zero point or establish that the fitted feature is the intended source.

The same fit also supplies amplitude and effective-shape diagnostics. Their meaning remains that of the exact processed parent map. Amplitude is not automatically universal flux. Width and orientation are not automatically an intrinsic beam. Any use for a pointing correction, photometric transfer, or telescope/observing QC has a separate policy owner and evaluation.

Contents

Reader's summary	1
1 Why a conditional contract is scientifically useful	3
2 Physical interpretation in one sentence	3
3 Normative notation and state axes	3
3.1 Three independent state systems	3
4 Scientific operation and ownership	4
4.1 Producer-transformer-consumer boundary	4
4.2 Eligible parent families are not equivalent	4
4.3 Product roles and claim ceilings	5
4.4 Applicability facts	5
4.5 Draft named-use profile identities	5
5 Model, measurement, and conditional estimators	6
5.1 Invariant zero-background source model	6
5.2 Coordinate transform and signed displacement	6
5.3 Conditional numerical fit	6
5.4 Association is not optimization	7
5.5 Residual and deterministic mismatch	7
5.6 Conditional diagnostic identities	7
6 Inputs, assumptions, and dependency gates	7
6.1 Exact input record	7
6.2 Method authorities and present availability	8
6.3 Product and claim dependency matrix	8
6.4 Uncertainty budget	9
6.5 Response and bias separation	9
6.6 Named-use ownership	9
6.7 Claim classes and evidence ceiling	9
7 Validity, unavailable states, and edge cases	9
7.1 Typed unavailable-state register	9
7.2 Edge-case rules	10

8	Scientific-owner decisions represented	11
9	What later validation would and would not establish	11
A	Normative conformance requirements	11
B	Falsifiable predictions and traceability	13
C	Document status and nonclaims	14

1 Why a conditional contract is scientifically useful

A mature operation can have a stable scientific purpose while still lacking a content-bound description of its numerical procedure. In that situation, inventing a familiar least-squares fit or conventional Gaussian width would silently replace the operation. SCI-POINT therefore freezes what is known: the targeted source class, six scientific parameter roles, zero-background model family, coordinate measurement, parent routes, ownership boundaries, state semantics, and falsifiable consequences. It leaves the unavailable objective, weighting, width convention, search details, solver rule, formal errors, and full-map RMS unavailable.

This separation permits later recovery of three exact methods without changing the package’s primary estimand. It also prevents one missing diagnostic from erasing a future authorized fit. The compatibility method controls the fit. The formal-error method controls marginal formal errors and dependent uses. The full-map-RMS method controls only a descriptive amplitude/RMS ratio.

2 Physical interpretation in one sentence

For one identified source and one exact processed map, fit the approved elliptical-Gaussian family in the map’s physical AltAz tangent metric, establish that the fitted feature is the source, and report its centroid minus the authoritative expected position while preserving every parent, method, response, uncertainty, and use limitation.

3 Normative notation and state axes

The words **shall**, **shall not**, **required**, and **prohibited** are normative. “Available” means that every dependency for the stated quantity is bound and valid. “Unavailable” means that the quantity or claim has not been established; it never means numerical zero. “Failed” means that an authorized computation was attempted but did not return a conforming result.

Symbol or term	Meaning
m_q	Exact parent signal at admitted row or pixel q .
u_q	Physical coordinate supplied by the exact AltAz tangent-boundary transform for parent coordinate p_q .
A	Fitted amplitude in the exact parent product’s unit, calibration, and response.
μ	Continuous fitted centroid in the declared ordered AltAz tangent basis.
Σ_g	Symmetric positive-definite invariant Gaussian shape matrix.
θ	The six scientific roles: amplitude, two centroid components, two principal-width roles, and orientation.
W_{fit}	Exact fit-weight role, distinct from parent covariance, inverse covariance, reliability weight, and uncertainty products.
Δ_{POINT}	Measured source displacement, fitted centroid minus authoritative expected source position, in arcseconds in the declared basis.
parent	One exact observation-local, per-array MAP, JINC, FLT-FIXED, or FLT-MATCHED signal product.
terminal FRUIT ancestry	Lineage attached to one of the four parent families; it is not a fifth parent family.
named use	One owner-defined consumer purpose evaluated without changing the immutable POINT result.

3.1 Three independent state systems

Producer lifecycle, component identifiability, and named-use evaluation shall remain independent.

Producer lifecycle	not_requested, requested, effective, unavailable, resolved, fit_attempted, fit_realized, complete_publication_candidate, publication_decided, published, failed, not_produced, or superseded.
Component identifiability	Exactly one of available_identifiable, available_bound_censored, weakly_identified, undefined_by_model_symmetry, unavailable, or failed for every required parameter role.

Named-use evaluation Four fields, kept separate:
 request: `requested` or `not_requested`;
 applicability: `applicable`, `inapplicable`, or `decision_unavailable`;
 eligibility: `eligible`, `ineligible`, or `decision_unavailable`;
 realization: `realized`, `not_realized`, `unavailable`, or `failed`.

After the four named-use fields are evaluated, the owning consumer may prescribe an action such as `diagnostic_display_only`. That token is an action, not an eligibility value, producer state, or universal quality flag. The token `diagnostic_only` is not a producer state or SCI-VAL eligibility value.

4 Scientific operation and ownership

SCI-POINT fits one known, isolated, bright Pointing source on one exact observation-local per-array map product. Each requested observation-array-parent-method fit is scientifically atomic. The primary scientific result, when all dependencies are available, is a two-component source displacement in a declared AltAz tangent basis. The complete fit also has amplitude, centroid, two width roles, orientation, support, constraints, method identity, parent identity, uncertainty state, association state, and use-specific evaluation facts.

SCI-POINT is a producer of per-array measurements. It does not detect blind sources, deblend, catalog, make or filter maps, run FRUIT recurrence, calibrate, infer per-detector beams, perform OOF inference, aggregate arrays, form a telescope correction, select a correction, or apply one.

4.1 Producer-transformer-consumer boundary

The exact parent producer owns its estimand, signal unit, calibration, normalization, WCS, grid, frame, tangent relation, support, validity, missing/non-finite policy, response, covariance or uncertainty state, null-space, lifecycle, and provenance. POINT binds and consumes those facts without redefining them.

The source-reference producer owns the expected source position and its identity, convention, time or epoch, frame, atmospheric and aberration treatment, morphology or reference origin, uncertainty, validity, lifecycle, and provenance. AST owns the exact AltAz tangent-basis realization. A named pointing-support producer owns cross-array membership, aggregation, weights, dependence, partial-set policy, measurement-to-correction sign, telescope user/paddle-offset composition, selection, native support, and correction record publication. AST owns conforming application.

SCI-BEAM owns per-detector Beammap fits, detector PSF, sensitivity, APT, and beam authority. CAL or TolProj owns photometric-transfer admission and reference-flux authority. A named telescope/observing-condition QC process owns its reference populations, thresholds, comparisons, aggregation, trend analysis, actions, and causal interpretation. NOI owns separately authorized empirical uncertainty. SCI-VAL registers and evaluates exact profiles but authors none of their scientific policies.

4.2 Eligible parent families are not equivalent

Family	Exact POINT signal role	Required route distinction
MAP	MAP-SIGNAL/ OBSERVATION-LEVEL-NORMALIZED@1	Exact observation-level normalized signal; never a coadd.
JINC	JINC-SIGNAL/NORMALIZED-JINC-MAP@1	Exact signed and normalized signal; N , C , Q , coefficient-squared accounting, response, covariance, and state records are companions, not alternate signal parents.
FLT-FIXED	FLT-FIXED-SIGNAL/ TRANSFORMED-MAP@1	Exact transformed signal with its MAP/JINC parent, filter operator, normalization, response, edge/support, and covariance state.
FLT-MATCHED	FLT-MATCHED-SIGNAL/ MATCHED-TEMPLATE-AMPLITUDE-FIELD@1	Exact matched-template amplitude field with template, noise/covariance selector, normalization, phase/origin, response, and complete support.

POINT shall not choose, substitute, equate, or fall back among routes. The route-specific chain from source morphology through parent response to the expected processed-map profile and Gaussian compatibility shall be bound for each instance. Every numerical route currently has state `unavailable_pending_method_and_route_binding`. Eligibility of a family does not establish an exact numerical parent, Gaussian adequacy, response fidelity, zero centroid bias, or numerical availability.

A terminal FRUIT product retains its exact MAP, JINC, FLT-FIXED, or FLT-MATCHED identity and adds the complete method, terminal iteration, generation, recurrence, restart, response, support, covariance, calibration, null/additive-reference, lifecycle, and provenance ancestry. The record shall assert that the product is terminal. Intermediate iterations and coadds are outside base v0.1.

4.3 Product roles and claim ceilings

Role	Meaning and ceiling
POINT-FIT-RESULT	Conditional numerical six-role fit with lifecycle, component states, support, method, and parent; not association, a catalog, an intrinsic beam, or a correction.
POINT-DISPLACEMENT-MEASUREMENT	Source-associated fitted centroid minus expected position in the exact AltAz basis; not an absolute spherical position or correction vector.
POINT-AMPLITUDE-DIAGNOSTIC	Required amplitude in the exact parent unit/calibration/response and a candidate input to CAL/TolProj admission; not universal flux or pre-established photometric eligibility.
POINT-EFFECTIVE-SHAPE-DIAGNOSTIC	Required width roles and angle under the processed-map response; not an intrinsic telescope beam, detector PSF, SCI-BEAM product, or unique cause.
POINT-FIT-QUALITY-CONTROL-METRICS	Centroid, amplitude, shape, support, constraints, uncertainty, residual/response state, and fit state for an owner-governed QC use; not an automatic threshold or action.
POINT-SOURCE-ASSOCIATION-STATE	established , unavailable , or failed , with method, domain, cause, lifecycle, and provenance; never implied by a peak or finite fit.
POINT-FIXED-BRANCH-RESPONSE-STATE	Response conditional on one exact branch, support, weight state, and active constraints; not full-procedure response.
POINT-FULL-PROCEDURE-RESPONSE-STATE	Response obtained by rerunning every data-dependent branch under perturbation; not observational accuracy.
POINT-OBSERVATIONAL-BIAS-ACCURACY-STATE	Separate empirical authority; unavailable bias is not zero bias.
POINT-UNCERTAINTY-STATE	Separately typed formal, coordinate, reference, response, empirical, NOI, calibration, dependence, and correction uncertainty; not an implied total.

4.4 Applicability facts

The four facts **known**, **isolated**, **bright**, and **approximately_centered** each carry value/state, exact authority or method, domain, cause, validity, lifecycle, and provenance. **known** requires a valid source identity and expected-position record. **isolated** requires authority over confusing sources or structure in the search and fit domains. **bright** is a compatibility-method class, not significance or either diagnostic ratio. **approximately_centered** is an exact relation among expected position, search domain, fit domain, parent support, and map boundary. Tests for the latter three remain unavailable pending method authority. Labels, filenames, defaults, map finiteness, fitted amplitude, or ratios shall not instantiate them.

4.5 Draft named-use profile identities

The following collision-free mechanics are drafts for final owner review, not registered profiles:

- VAL-PROFILE/SCI-POINT/FIT-COMPLETENESS/PER-ARRAY@draft-r0.3, owned by POINT;
- VAL-PROFILE/POINTING-SUPPORT/POINT-DISPLACEMENT-ADMISSION@draft-r0.3, owned by the pointing-support producer;
- VAL-PROFILE/TELESCOPE-QC/POINT-PARAMETER-ADMISSION@draft-r0.3, owned by the named QC process; and

- VAL-PROFILE/CAL-TOLPROJ/POINT-AMPLITUDE-TRANSFER@draft-r0.3, owned by CAL/TolProj.

Each record shall bind profile version/digest, owner, use, source facts and bindings, the four named-use fields, unavailable-state behavior, reasons, prescribed consumer action, evaluation identity, and provenance. No aggregate or universal profile enters base v0.1.

5 Model, measurement, and conditional estimators

5.1 Invariant zero-background source model

For physical tangent coordinate $\mathbf{u}_q$, the only base model family is

$$g_q(A, \boldsymbol{\mu}, \boldsymbol{\Sigma}_g) = A \exp\left[-\frac{1}{2}(\mathbf{u}_q - \boldsymbol{\mu})^\top \boldsymbol{\Sigma}_g^{-1}(\mathbf{u}_q - \boldsymbol{\mu})\right], \quad (1)$$

where $\boldsymbol{\Sigma}_g$ is symmetric positive definite. The invariant principal extents are strictly positive and ordered major not less than minor. The source model has no constant, gradient, local baseline, or other nuisance term. Its six roles are amplitude, two centroid coordinates, two principal-width roles, and orientation.

The exact numerical parameter ordering, published width convention, angle origin, positive direction, gauge/period canonicalization, amplitude domain, parameter bounds, active-bound interpretation, and source-profile convention remain unavailable until POINT-COMPATIBILITY-METHOD v0.1 is owner-approved. At exact circularity, orientation is `undefined_by_model_symmetry`; a finite placeholder is not a measurement. Exchanging principal axes with the corresponding angle transformation leaves Equation 1 invariant.

5.2 Coordinate transform and signed displacement

For parent coordinate p_q , the exact AST boundary supplies

$$\mathbf{u}_q = T(p_q; \text{coordinate state}). \quad (2)$$

The model shall use the physical tangent metric, not storage-pixel distance, unless the boundary proves their equivalence over admitted support. The ordered basis vectors, handedness, positive directions, angular unit, time and state, Jacobian where relevant, support, uncertainty, lifecycle, provenance, and failure behavior are all bound facts. Axis labels, memory order, display orientation, and FITS array order are not sign authority.

The measurement is

$$\Delta_{\text{POINT}} = \hat{\boldsymbol{\mu}} - \boldsymbol{\mu}_{\text{expected}}, \quad [\Delta_{\text{POINT}}] = \text{arcsec}, \quad (3)$$

in that exact basis. If the tangent-coordinate origin equals the expected position, $\boldsymbol{\mu}_{\text{expected}} = (0, 0)$ and $\Delta_{\text{POINT}} = \hat{\boldsymbol{\mu}}$. The search center affects search and initialization only and never defines the zero point. POINT owns the sign in Equation 3; correction sign and composition are downstream.

5.3 Conditional numerical fit

The most that can be stated before method recovery is

$$\hat{\boldsymbol{\theta}} = \text{Resolve}_{\boldsymbol{\theta} \in \Theta_{\text{effective}}} D(m, g_{\boldsymbol{\theta}}; W_{\text{fit}}). \quad (4)$$

The admitted rows, scalar objective or likelihood D , weight meaning and normalization, constraints, comparison of multiple solutions, convergence, retry, and solution rule are not supplied. Equation 4 shall not be instantiated by guessing least squares, inverse variance, reliability weighting, or covariance weighting. Fit weights, parent stochastic covariance, inverse covariance, the formal-error model, and parent uncertainty are distinct roles.

The preserved mature procedure has configurable expected-center/central search, weighted-peak initialization, global fallback, bounded fit domain, and amplitude/width/angle constraints. Requested, effective, resolved, applied, and realized states remain distinct. A sentinel shall resolve to a named effective state, and every fallback, restart, retry, branch, bound, and termination shall be reported. Exact rules belong to POINT-COMPATIBILITY-METHOD v0.1.

5.4 Association is not optimization

Expected position, requested search center, effective search center, selected seed, fitted centroid, and source association are distinct. Every central, global-fallback, restart, retry, or other authorized branch yields a candidate seed, never source identity. Source-attributed displacement and amplitude require `POINT-SOURCE-ASSOCIATION-STATE=established` under one branch-independent method and declared association domain. A central or global peak, finite fit, small displacement, large amplitude, dynamic range, or formal standardization cannot establish association.

5.5 Residual and deterministic mismatch

The scientific decomposition is

$$m = g(\theta_{\text{true}}) + b + n, \quad (5)$$

where b is any deterministic parent component not represented by the zero-background model and n is stochastic variation. POINT neither fits nor silently removes b . It can bias every fit role; a finite fit does not turn it into noise. Once fitting is authorized, the fitted model and residual shall be published or reconstructible with objective, support, row count, rank, convergence, active constraints, branch state, residual diagnostics, and parent additive-reference/null state.

5.6 Conditional diagnostic identities

Only the following names are admitted:

$$\text{fitted_amplitude_over_full_map_rms} = \hat{A}/\text{RMS}_{\text{full}}, \quad (6)$$

$$\text{fitted_amplitude_over_formal_amplitude_error} = \hat{A}/\sigma_A. \quad (7)$$

Equation 6 is descriptive dynamic range only and is unavailable until `POINT-FULL-MAP-RMS-METHOD v0.1` binds the parent/generation, population, centering, weighting, source-region treatment, support/edge, non-finite and zero-denominator rules, units, lifecycle, provenance, and parent relation. `sig2noise` may be an exact legacy alias only after that approval. `peak_over_full_map_rms` is not an admitted alias.

Equation 7 is formal standardization only and is unavailable until `POINT-FORMAL-ERROR-METHOD v0.1` and its signed-versus-absolute convention are approved and σ_A is positive and finite. `fit_sig2noise` is its exact legacy alias when available. Neither ratio is statistical significance, detection probability, false-alarm statistic, completeness, or purity. A zero or non-finite denominator produces the future method's typed unavailable or failed state, never an infinite claim.

6 Inputs, assumptions, and dependency gates

6.1 Exact input record

Every requested fit shall bind all of the following without filename or directory inference:

1. observation, array, exact parent family, immutable product, method, version, generation, and complete terminal FRUIT ancestry when applicable;
2. parent estimand, signal role, unit, calibration, normalization, WCS, grid, frame, exact AltAz tangent basis, pixel metric, orientation, handedness, support, validity, missing/non-finite policy, response, covariance/uncertainty, null/additive-reference, phase/origin where applicable, lifecycle, and provenance;
3. authoritative expected source position and its full source, target, catalog or ephemeris authority, convention, time/epoch, frame, atmospheric and aberration treatment, morphology/reference origin, uncertainty, validity, lifecycle, and provenance;
4. parent-map WCS/reference origin, requested and effective search center, selected seed, fitted centroid, and association state as distinct objects;
5. requested fit method and every requested, effective, resolved, applied, and realized search, support, weight, constraint, fallback, retry, and termination state; and
6. each typed applicability fact and each requested named-use evaluation.

Every route boundary instance shall additionally bind its exact predecessor package/version/source digest, signal role, owner approval, compatibility/supersession status, source morphology, response chain, processed-map profile, Gaussian compatibility, response-center relation, model-mismatch state, expected centroid bias or typed unavailability, fit-domain relation, and displacement-claim status.

6.2 Method authorities and present availability

The base operator identity is POINT-FIT/ELLIPTICAL-GAUSSIAN-COMPATIBILITY@1. Its numerical realization is gated by three scientifically and lifecycle-distinct records:

Authority	Current state	Consequence
POINT-COMPATIBILITY-METHOD v0.1	pending separate owner approval	No numerical fit or fit-derived product. The future record must bind model parameterization, rows, objective, weights, support, search, initialization, association, fallback, constraints, solver-independent resolution, termination, rank, identifiability, sentinel, failure, identity, and compatibility status.
POINT-FORMAL-ERROR-METHOD v0.1	pending separate owner approval	Marginal formal errors, formal standardization, and formal-uncertainty-dependent uses are unavailable. An otherwise authorized fit is not erased. Joint covariance remains unavailable unless separately authorized.
POINT-FULL-MAP-RMS-METHOD v0.1	pending separate owner approval	Only <code>fitted_amplitude_over_full_map_rms</code> and exact legacy alias <code>sig2noise</code> are blocked. An otherwise authorized fit, displacement, effective shape, or formal error is not erased.

The exact numerical parent-route instances, registered named-use profiles, fixed-branch response, full-procedure response, and observational bias/accuracy are also unavailable. No familiar practice, optimizer output, method name, finite value, or adjacent-package analogy may fill any gap.

6.3 Product and claim dependency matrix

Product or claim	Required available facts	Blocking result
Fit result	Exact numerical parent and tangent metric; approved compatibility method; admitted support; objective/weight state; successful realization; component states	No numerical fit or fit-derived product.
Fit components	Conforming fit and exact component-identifiability state	Only the affected component is unavailable or failed; conforming siblings remain.
Source association	Exact source-reference authority and branch-independent method/domain	Source attribution is unavailable or failed.
Processed-map displacement	Fitted centroid; expected position; identical tangent chart/basis; established association	No source-attributed displacement. Response and centroid bias may be typed unavailable but remain visible.
Unbiased pointing or correction-use claim	Displacement plus every named-use-required response center, centroid bias, uncertainty, and pointing-support policy	Named use is ineligible or decision-unavailable; missing bias is not zero.
Formal errors	Conforming fit and approved formal-error method	Formal errors unavailable; fitted values may remain.
Formal standardization	Fitted amplitude and positive finite approved formal amplitude error	Diagnostic unavailable.
Dynamic-range diagnostic	Fitted amplitude and approved full-map-RMS method on exact related parent	Only that diagnostic is unavailable.
Photometric transfer	Associated amplitude plus CAL/TolProj profile and source/reference authority	Photometric eligibility is ineligible or decision-unavailable.
Telescope-QC display	Required fit facts plus QC-owner applicability, eligibility, and action	Display not realized; it cannot rescue another use.

Response and covariance availability are evaluated by the applicable row and named-use policy. Missing response or

covariance neither universally erases all processed-map results nor authorizes response, bias, uncertainty, correction, calibration, or photometric claims.

6.4 Uncertainty budget

Conditional formal fit error, joint parameter covariance, source-reference or ephemeris uncertainty, WCS/tangent-coordinate uncertainty, parent response/model-mismatch uncertainty, calibration uncertainty, empirical pointing repeatability, NOI uncertainty, cross-array dependence, and pointing-correction uncertainty are separate components with separate owners. They may be combined only when every variance and cross-covariance needed for the declared operation is available. Missing covariance is not zero, diagonal covariance, or independence.

If fit and published tangent bases differ, exact transformation generally requires joint centroid covariance. Transforming marginal errors alone through a non-axis-aligned Jacobian does not produce exact AltAz marginal errors. A later joint-covariance, astrometric, empirical-repeatability, or NOI companion is separately versioned and does not rewrite the immutable POINT fit claim.

6.5 Response and bias separation

POINT can be nonlinear because search, fallback, support, or active constraints can depend on the data. A fixed-branch response is conditional on one exact seed/fallback branch, fit support, weight state, and active-constraint set. A full-procedure response reruns every data-dependent search, fallback, support, constraint, and optimization choice under perturbation. Observational centroid bias and pointing accuracy require a separate empirical authority. Source association is separate from all three. Parent response is input state, not automatically fitter response; a local Jacobian is not full-procedure response. All three POINT response/bias roles are presently unavailable, and their absence does not imply zero response error or zero centroid bias.

6.6 Named-use ownership

POINT owns only the per-array fit-completeness policy. The pointing-support producer owns displacement admission. The named telescope/observing QC process owns parameter admission and actions. CAL/TolProj owns amplitude admission for photometric transfer. The same immutable result may pass one use, fail another, and be shown diagnostically for a third. No state or action propagates across uses. Failure of one array does not erase siblings; POINT imputes no array and publishes no observation-wide success. A downstream partial-set aggregate must record its exact policy and membership.

6.7 Claim classes and evidence ceiling

This contract establishes scientific meaning and conditional engineering conformance requirements. It does not establish representation fidelity, implementation conformity, numerical production, response or covariance fidelity, uncertainty coverage, observational validation, pointing accuracy, performance, readiness, production suitability, production authorization, or Unity activity.

7 Validity, unavailable states, and edge cases

7.1 Typed unavailable-state register

ID	Unavailable quantity or claim	Release condition or disposition
SCI-POINT-UNAV-001	POINT-owned cross-array aggregate	Outside base v0.1; successor decision required.
SCI-POINT-UNAV-002	POINT correction candidate or applied correction	Outside scope; pointing-support producer and AST retain ownership.
SCI-POINT-UNAV-003	Numerical MAP/JINC/FLT route	Exact predecessor authority, product, state, and compatibility binding.
SCI-POINT-UNAV-004	Numerical compatibility fit and every fit-derived product	Approved compatibility method, exact numerical parent, and route binding.
SCI-POINT-UNAV-005	POINT whole-observation success from partial arrays	Outside scope; downstream owns partial-set admission.

ID	Unavailable quantity or claim	Release condition or disposition
SCI-POINT-UNAV-006	Full joint covariance or uncertainty coverage	Separately authorized representation and evidence.
SCI-POINT-UNAV-007	Absolute flux or calibration accuracy	CAL/TolProj authority and evidence; never POINT alone.
SCI-POINT-UNAV-008	Intrinsic beam inferred from Pointing width	Separate authorized method; SCI-BEAM boundary.
SCI-POINT-UNAV-009	Statistical significance or detection probability	Complete probabilistic method and validation.
SCI-POINT-UNAV-010	Applied correction for another observation	Producer selection and AST application authority.
SCI-POINT-UNAV-011	OOF or blank-field source result	Separate package authority.
SCI-POINT-UNAV-012	Coadd or intermediate-FRUIT parent	Outside base v0.1.
SCI-POINT-UNAV-013	Universal cross-use eligibility or aggregate profile	Prohibited; policies remain use-specific.
SCI-POINT-UNAV-014	Source-attributed displacement or amplitude	Valid source reference and established association.
SCI-POINT-UNAV-015	Published AltAz displacement	Exact AST/source-to-POINT basis boundary and valid transform.
SCI-POINT-UNAV-016	Marginal formal errors and dependent uses	Approved formal-error method; fit values may remain.
SCI-POINT-UNAV-017	Fitted-amplitude/full-map-RMS diagnostic	Exact RMS population, centering, weighting, support, finite, and denominator rules.
SCI-POINT-UNAV-018	Full-procedure response or observational bias/accuracy	Separate response or empirical authority.
SCI-POINT-UNAV-019	Full-map RMS and canonical ratio/ sig2noise	Approved full-map-RMS method; only this diagnostic is blocked.
SCI-POINT-UNAV-020	Known/isolated/bright/approximately-centered fact	Exact fact authority or test and cause.
SCI-POINT-UNAV-021	Exact numerical parent boundary instance	Exact package/version/source digest, role, owner approval, compatibility, and boundary state.

7.2 Edge-case rules

Condition	Required behavior
Missing method, boundary, input, or applicability authority	The dependent quantity is unavailable with identity and cause; no default is inferred.
Attempted computation cannot conform	Report failed ; do not relabel it scientifically unavailable.
Missing or non-finite admitted support	Apply the future compatibility method's exact failure/unavailability rule; never silently delete rows.
Active parameter bound	Report the constraint and available_bound_censored where applicable.
Weak curvature or near degeneracy	Report weakly_identified ; formal error may be unavailable independently of the fitted value.
Exact circularity	Orientation is undefined_by_model_symmetry .
Major/minor exchange	Enforce canonical ordering and transform orientation consistently without changing the invariant model.
Centroid on a search or fit boundary	Report boundary/constraint state; named-use eligibility is evaluated separately.
Rank-deficient or non-positive curvature	Formal error is unavailable unless the future exact method defines another conforming result; fit-component state is assessed separately.

Condition	Required behavior
Unmodeled constant, gradient, or structure	Preserve residual and parent additive-reference state; do not fit or silently subtract it.
Association unavailable or failed	A numerical fit may remain a diagnostic, but source-attributed amplitude and displacement are unavailable.
Zero or non-finite diagnostic denominator	Ratio is unavailable or failed under its future exact method, never infinite.
Unavailable response or covariance	Follow the dependency matrix; do not universally erase or authorize claims.
One array unavailable or failed	Preserve sibling atomic products; publish no POINT observation-wide success.
Terminal-FRUIT assertion absent, or intermediate iteration	Reject the parent for base v0.1.
Requested route unavailable	Do not choose, substitute, or fall back to another parent route.
Diagnostic-display action present	Preserve the four named-use fields; the action cannot rescue any other exclusion.

8 Scientific-owner decisions represented

This contract implements the closed ODQ-001 through ODQ-009 decisions, including the ODQ-003A terminal-FRUIT and ODQ-003B coadd distinctions. It preserves per-array outputs, downstream correction ownership, four explicit routes without substitution, the six-role zero-background compatibility family, explicit search/fallback state, independent lifecycle/identifiability/ named-use axes, conditional marginal formal errors, bounded amplitude/shape claims, and separate policy owners.

No scientific decision remains open inside the generic conditional boundary. The remaining owner actions are content approvals, not invitations to infer missing science: approve exact compatibility, formal-error, and full-map-RMS method records; approve exact numerical route boundary instances; review the four draft named-use profile identities/mechanics; and separately authorize fixed/full procedure response or observational bias/accuracy if desired.

9 What later validation would and would not establish

Contract conformance would show that identities, records, states, equations, dependencies, and failure behavior match this authority. Representation tests would show that stored and transformed values preserve those meanings. Numerical tests could evaluate the predictions only after the relevant method and route are approved. Observational validation could separately measure bias, repeatability, coverage, or pointing performance. Production readiness would additionally require operational, performance, and deployment evidence. Passing one layer does not establish the next.

A Normative conformance requirements

An implementation conforms to one requirement only when the exact records and states named by that requirement are present and valid. A finite numerical value does not substitute for a missing identity, authority, or state.

Requirement	Normative statement	Scientific source
SCI-POINT-REQ-001	Treat every requested observation-array-parent-method fit as an independent scientific atom with its own lifecycle.	Secs. 4, 6.6
SCI-POINT-REQ-002	Bind every exact input-record field in Section 6.1; do not infer identity from filenames, labels, or location.	Sec. 6.1
SCI-POINT-REQ-003	Admit only exact MAP, JINC, FLT-FIXED, or FLT-MATCHED signal roles and preserve their distinct meanings and companions.	Sec. 4.2
SCI-POINT-REQ-004	Never automatically select, substitute, equate, or fall back among parent routes.	Sec. 4.2

Requirement	Normative statement	Scientific source
SCI-POINT-REQ-005	Treat FRUIT only as complete terminal ancestry on one admitted route; reject intermediate iterations and coadds.	Sec. 4.2
SCI-POINT-REQ-006	Bind the exact route response chain, processed profile, Gaussian compatibility, response center, model mismatch, centroid-bias state, and claim status before numerical use.	Secs. 6.1, 4.2
SCI-POINT-REQ-007	Bind expected source position, parent WCS origin, search center, and fitted centroid as four distinct objects.	Secs. 6.1, 5.2
SCI-POINT-REQ-008	Use the exact ordered AltAz tangent basis, physical metric, transform, handedness, positive directions, state, support, uncertainty, and provenance.	Eqs. 2–3
SCI-POINT-REQ-009	Publish displacement only as fitted centroid minus expected position in arcseconds; do not encode correction sign.	Eq. 3
SCI-POINT-REQ-010	Use only the zero-background six-role elliptical-Gaussian family in Equation 1; add no background or second model family.	Sec. 5.1
SCI-POINT-REQ-011	Preserve the invariant positive-definite shape, canonical principal ordering, and symmetry-defined orientation state without inventing numerical width or angle conventions.	Sec. 5.1
SCI-POINT-REQ-012	Produce no numerical fit or fit-derived product until the approved compatibility method, exact parent, and route binding are available.	Sec. 6.2
SCI-POINT-REQ-013	Keep objective, weights, stochastic covariance, inverse covariance, formal-error model, and parent uncertainty distinct; never guess Equation 4.	Sec. 5.3
SCI-POINT-REQ-014	Preserve requested, effective, resolved, applied, and realized search, support, fallback, retry, constraint, sentinel, and termination states.	Sec. 5.3
SCI-POINT-REQ-015	Establish source association independently for every authorized search, fallback, restart, and retry branch before source attribution.	Sec. 5.4
SCI-POINT-REQ-016	Carry known, isolated, bright, and approximately-centered applicability as typed facts with authority, domain, cause, validity, life-cycle, and provenance.	Sec. 4.4
SCI-POINT-REQ-017	When fitting is authorized, publish or make reconstructible the model, residual, objective, support, row count, rank, convergence, constraints, branch state, residual diagnostics, and additive-reference/null state.	Sec. 5.5
SCI-POINT-REQ-018	Give every required fit component exactly one component-identifiability state and preserve available sibling components when another is unavailable or failed.	Secs. 3.1, 6.3
SCI-POINT-REQ-019	Publish amplitude only in the exact parent unit, calibration, response, constraint, support, association, and uncertainty context; do not call it universal flux.	Secs. 4.3, 4.1
SCI-POINT-REQ-020	Publish widths and angle only as processed-map effective-shape and QC roles; do not claim intrinsic beam or unique cause.	Secs. 4.3, 5.1
SCI-POINT-REQ-021	Publish marginal formal errors only under the separately approved formal-error method with assumptions, conditioning, domain, units, and limitations.	Secs. 6.2, 6.4
SCI-POINT-REQ-022	Represent absent joint covariance as unavailable, not zero, diagonal, or independence, and preserve later uncertainty companions as separate versions.	Sec. 6.4
SCI-POINT-REQ-023	Use only the conditional diagnostic names and formulas in Equations 6–7; label their claim ceilings truthfully.	Sec. 5.6
SCI-POINT-REQ-024	Do not admit <code>peak_over_full_map_rms</code> as an alias unless a future compatibility-method finding separately authorizes it.	Sec. 5.6
SCI-POINT-REQ-025	Keep fixed-branch response, full-procedure response, observational bias/accuracy, source association, and parent response distinct.	Sec. 6.5

Requirement	Normative statement	Scientific source
SCI-POINT-REQ-026	Apply the product-and-claim dependency matrix row by row; missing response or covariance shall neither erase nor authorize unrelated claims.	Sec. 6.3
SCI-POINT-REQ-027	Keep producer lifecycle, component identifiability, and the four named-use fields independent and lossless.	Sec. 3.1
SCI-POINT-REQ-028	Use <code>diagnostic_display_only</code> only as a post-evaluation consumer action; never use <code>diagnostic_only</code> as producer state or eligibility.	Sec. 3.1
SCI-POINT-REQ-029	Preserve separate policy ownership for fit completeness, displacement admission, telescope-QC admission, and photometric-transfer admission; VAL only registers/evaluates.	Secs. 4.1, 4.5
SCI-POINT-REQ-030	Treat all four named-use profile identities as unapproved drafts pending final owner review and never construct an aggregate/universal profile.	Sec. 4.5
SCI-POINT-REQ-031	Publish no POINT cross-array aggregate, correction, correction selection, correction application, or whole-observation success.	Secs. 4, 6.6
SCI-POINT-REQ-032	Do not impute a missing array or erase conforming siblings after one array's failure.	Secs. 4, 6.6
SCI-POINT-REQ-033	Keep deterministic unmodeled background/structure visible as residual and parent state; do not fit or silently subtract it.	Eq. 5
SCI-POINT-REQ-034	Apply every typed unavailable state and edge rule in Section 7, including exact cause and release condition.	Sec. 7
SCI-POINT-REQ-035	Keep all uncertainty-budget components separate and combine none without every required variance and cross-covariance.	Sec. 6.4
SCI-POINT-REQ-036	Publish a full-procedure response only when every data-dependent branch is rerun under perturbation; do not infer empirical accuracy from either response role.	Sec. 6.5
SCI-POINT-REQ-037	Evaluate every named use using request, applicability, eligibility, and realization before any action, without cross-use rescue or propagation.	Secs. 3.1, 6.6
SCI-POINT-REQ-038	Respect the evidence ceiling: this contract alone authorizes no implementation, numerical, fidelity, validation, accuracy, performance, readiness, production, or Unity claim.	Sec. 6.7

B Falsifiable predictions and traceability

These predictions specify tests that a future implementation or representation can fail. They are not claims that such validation has occurred.

Prediction	Falsifiable consequence	Governing requirements
SCI-POINT-PRED-001	An exact noiseless matching Gaussian recovers the authorized parameters subject to the exact compatibility method.	REQ-010,012,013
SCI-POINT-PRED-002	Authorized scaling of the parent signal and compatible unit scales amplitude as the method declares without moving the source reference.	REQ-006,007,019
SCI-POINT-PRED-003	Positive displacement follows fitted centroid minus expected position; correction sign remains downstream.	REQ-008,009,031
SCI-POINT-PRED-004	Changing only the search center may change branch or seed but never measurement zero.	REQ-007,009,014
SCI-POINT-PRED-005	WCS handedness or basis changes transform components through the exact boundary, independent of memory/display order.	REQ-008,009
SCI-POINT-PRED-006	Central-search and global-fallback branches remain distinguishable in realized state.	REQ-014
SCI-POINT-PRED-007	An exact score tie follows the future method's deterministic tie rule.	REQ-012,014
SCI-POINT-PRED-008	A wrong global peak cannot yield source-attributed displacement without established association.	REQ-015
SCI-POINT-PRED-009	Principal-axis exchange with corresponding angle transformation leaves the Gaussian invariant.	REQ-011
SCI-POINT-PRED-010	Exact circularity makes orientation undefined by model symmetry.	REQ-011,018
SCI-POINT-PRED-011	Active amplitude, width, or angle constraints are reported and affected components are bound-censored where applicable.	REQ-014,018

Prediction	Falsifiable consequence	Governing requirements
SCI-POINT-PRED-012	An unmodeled constant or gradient can bias fit roles and remains visible in residual/additive-reference state.	REQ-017,033
SCI-POINT-PRED-013	Missing or non-finite support follows the exact future method rule and is never silently deleted.	REQ-012,034
SCI-POINT-PRED-014	Reliability weights cannot be interpreted as inverse covariance without explicit authority.	REQ-013
SCI-POINT-PRED-015	Rank deficiency, active bounds, non-positive curvature, or angle degeneracy can preserve fitted values while formal errors remain unavailable.	REQ-018,021,034
SCI-POINT-PRED-016	MAP/JINC/FLT response mismatch changes compatibility or bias state and is not erased by common Gaussian naming.	REQ-003,006,025
SCI-POINT-PRED-017	Parent-response asymmetry may yield typed centroid-bias state rather than assumed zero bias.	REQ-006,025
SCI-POINT-PRED-018	A terminal FRUIT product retains its exact terminal route and ancestry; an intermediate iteration is rejected.	REQ-005
SCI-POINT-PRED-019	Failure of one array preserves conforming siblings and produces no POINT observation-wide success.	REQ-001,031,032
SCI-POINT-PRED-020	No input produces a POINT-owned cross-array aggregate or telescope correction.	REQ-031
SCI-POINT-PRED-021	Dynamic range follows the exact RMS authority and is unavailable for a zero or unavailable denominator.	REQ-023,034
SCI-POINT-PRED-022	Formal standardization is unavailable without the formal-error method and never becomes statistical significance by naming.	REQ-021,023
SCI-POINT-PRED-023	One fit may have different four-axis values across uses; diagnostic display changes neither lifecycle nor eligibility.	REQ-027,028,037
SCI-POINT-PRED-024	Missing profile, source authority, coordinate boundary, or association yields the corresponding typed unavailable decision.	REQ-007,008,015,030,034
SCI-POINT-PRED-025	Fixed-branch response cannot be reported as full-procedure response, and neither establishes empirical accuracy.	REQ-025,036
SCI-POINT-PRED-026	Missing compatibility method yields no numerical fit or fit-derived product.	REQ-012
SCI-POINT-PRED-027	With compatibility fitting available but formal-error authority missing, fitted values may exist while formal errors, unsupported joint covariance, and formal standardization remain unavailable.	REQ-021,022,026
SCI-POINT-PRED-028	Missing full-map-RMS authority blocks only the canonical dynamic-range ratio and alias, not an otherwise authorized fit or formal error.	REQ-023,026
SCI-POINT-PRED-029	Every search, fallback, restart, and retry branch requires exact association before source-attributed amplitude or displacement.	REQ-015
SCI-POINT-PRED-030	Response or covariance unavailability follows the dependency matrix and neither universally erases nor authorizes products and claims.	REQ-025,026
SCI-POINT-PRED-031	A diagnostic-display action cannot rescue correction, photometric, fit-completeness, or another named-use exclusion.	REQ-028,037

C Document status and nonclaims

This is the initial Stage B representation of scientific contract v0.1, document revision r0.1. It was authored from the exclusive Stage A r0.3 author packet. It claims no implementation inspection, conformity, numerical production, response/covariance fidelity, uncertainty coverage, observational validation, pointing accuracy, performance, readiness, production authorization, or Unity activity.